

TEST REPORT

BNetzA-CAB-02/21-102

Test report no.: 1-0079/20-03-02-A

Testing laboratory

CTC advanced GmbH

Untertuerkheimer Strasse 6 – 10
66117 Saarbruecken / Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

Internet: <https://www.ctcadvanced.com>

e-mail: mail@ctcadvanced.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkkS)

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate starting with the registration number: D-PL-12076-01.

Applicant

Hans Turck GmbH & Co. KG

Witzlebenstr. 7

45472 Mülheim an der Ruhr / GERMANY

Phone:

Contact: Matthias Linde

e-mail: matthias.linde@turck.com

Phone: +49 2353 709-6198

Manufacturer

Hans Turck GmbH & Co. KG

Witzlebenstr. 7

45472 Mülheim an der Ruhr / GERMANY

Test standard/s

FCC - Title 47 CFR
Part 15

FCC - Title 47 of the Code of Federal Regulations; Chapter I;
Part 15 - Radio frequency devices

For further applied test standards please refer to section 3 of this test report.

Test Item

Kind of test item: 122-123 GHz FMCW Radar

Model name:

EUT 1: G1 (1 inch thread): LRS510-10-69-LI2UPN8-H1141

EUT 2: G3/4 (3/4 inch thread): LRS510-10-51-LI2UPN8-H1141

FCC-ID

YQ7-LRS-510-10

Frequency:

122 GHz – 123 GHz

Technology tested:

FMCW Radar

Antenna:

Integrated antenna

Power supply:

24 V DC

Temperature range:

-20°C to +55°C



This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report authorized:



cn=Sebastian Janoschka, o=CTC advanced GmbH, ou=JKA-190527,
email=sebastian.janoschka@ctcadvanced.com, c=DE
2021.05.18 13:38:09 +02'00'

Sebastian Janoschka
Lab Manager
Radio Communications & EMC

Test performed:



cn=Thomas Vogler, o=CTC advanced GmbH, ou=VOG-161125,
email=thomas.vogler@ctcadvanced.com, c=DE
2021.05.18 12:18:51 +02'00'

Thomas Vogler
Lab Manager
Radio Communications & EMC

1 Table of contents

1	Table of contents	2
2	General information	3
2.1	Notes and disclaimer.....	3
2.2	Application details.....	3
2.3	Test laboratories sub-contracted.....	3
3	Test standard/s, references and accreditations	4
4	Test environment.....	4
5	Reporting statements of conformity – decision rule.....	5
6	Test item.....	6
6.1	General description	6
6.2	Additional information.....	6
7	Sequence of testing	7
7.1	Sequence of testing radiated spurious 9 kHz to 30 MHz	7
7.2	Sequence of testing radiated spurious 30 MHz to 1 GHz.....	8
7.3	Sequence of testing radiated spurious 1 GHz to 18 GHz.....	9
7.4	Sequence of testing radiated spurious above 18 GHz.....	10
7.5	Sequence of testing radiated spurious above 50 GHz with external mixers	11
8	Description of the test setup	12
8.1	Shielded semi anechoic chamber.....	13
8.2	Radiated measurements fully anechoic chamber.....	14
8.3	Radiated measurements 18 GHz to 50 GHz in test lab.....	15
8.4	Radiated measurements > 50 GHz in test lab.....	15
8.5	Radiated power measurements using RF detector according to ANSI C63.10-2013.....	16
8.6	AC power-line conducted emissions.....	18
9	Measurement uncertainty	19
10	Far field consideration for measurements above 18 GHz	20
11	Measurement results.....	21
11.1	Summary	21
12	Measurement results.....	22
12.1	Occupied bandwidth (20 dB Bandwidth)	22
12.2	Maximum E.I.R.P.	25
12.3	Spurious emissions radiated.....	28
12.3.1	Spurious emissions radiated (1" version).....	30
12.3.2	Spurious emissions radiated (3/4" version).....	47
12.4	Frequency Stability	64
13	Conducted spurious emissions < 30 MHz.....	70
14	Glossary.....	75
15	Document history	76
16	Accreditation Certificate – D-PL-12076-01-05.....	76

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CTC advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTC advanced GmbH.

The testing service provided by CTC advanced GmbH has been rendered under the current "General Terms and Conditions for CTC advanced GmbH".

CTC advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CTC advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CTC advanced GmbH test report include or imply any product or service warranties from CTC advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CTC advanced GmbH.

All rights and remedies regarding vendor's products and services for which CTC advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by CTC advanced GmbH. In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

This test report replaces the test report with the number 1-0079/20-03-02 and dated 2021-04-22.

2.2 Application details

Date of receipt of order:	2020-10-09
Date of receipt of test item:	2020-10-29
Start of test:	2020-11-02
End of test:	2021-04-19
Person(s) present during the test:	--

*Date of each measurement, if not shown in the plot, can be requested. Dates are stored in the measurement software.

2.3 Test laboratories sub-contracted

None

3 Test standard/s, references and accreditations

Test standard	Date	Description
FCC - Title 47 CFR Part 15		FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices

Guidance	Version	Description
ANSI C63.4-2017	-/-	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.10-2013	-/-	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
ANSI C63.26-2015	-/-	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services

Accreditation	Description	
D-PL-12076-01-05	Telecommunication FCC requirements https://www.dakks.de/as/ast/d/D-PL-12076-01-05.pdf	 

4 Test environment


Temperature	:	T_{nom} T_{max} T_{min}	+22 °C during room temperature tests +55 °C during high temperature tests -20 °C during low temperature tests
Relative humidity content	:		49 %
Barometric pressure	:		1008 hpa
Power supply	:	V_{nom}	24 V DC

5 Reporting statements of conformity – decision rule

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed in chapter 3.

The measurement uncertainty is mentioned in this test report, see chapter 9, but is not taken into account - neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong.

measured value, measurement uncertainty, verdict



6 Test item

6.1 General description

Kind of test item	:	122-123 GHz FMCW Radar
Model name:	:	EUT 1: G1 (1 inch thread): LRS510-10-69-LI2UPN8-H1141 EUT 2: G3/4 (3/4 inch thread): LRS510-10-51-LI2UPN8-H1141
S/N serial number	:	n.a.
Hardware status	:	1
Software status	:	1
Firmware status	:	n.a.
Frequency band	:	122 GHz – 123 GHz
Type of modulation	:	FMCW
Number of channels	:	1
Antenna	:	Integrated antenna
Power supply	:	24 V DC
Temperature range	:	-20°C to +55°C

6.2 Additional information

Test setup and EUT photos are included in test report:

1-0079/20-03-01_AnnexA

1-0079/20-03-01_AnnexB

1-0079/20-03-01_AnnexC

7 Sequence of testing

7.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, it is placed on a table with 0.8 m height.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement*

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all emissions.

Final measurement

- Identified emissions during the pre-measurement are maximized by the software by rotating the turntable from 0° to 360°.
- Loop antenna is rotated about its vertical axis for maximum response at each azimuth about the EUT. (For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT)
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.

^{*)}Note: The sequence will be repeated three times with different EUT orientations.

7.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$ and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

7.3 Sequence of testing radiated spurious 1 GHz to 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

7.4 Sequence of testing radiated spurious above 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet.
- The measurement distance is as appropriate (e.g. 0.5 m).
- The EUT is set into operation.

Premeasurement

- The test antenna is handheld and moved carefully over the EUT to cover the EUT's whole sphere and different polarizations of the antenna.

Final measurement

- The final measurement is performed at the position and antenna orientation causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement and the limit is stored.

7.5 Sequence of testing radiated spurious above 50 GHz with external mixers

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet.
- The measurement distance is as appropriate for far field (e.g. 0.25 m).
- The EUT is set into operation.

Premeasurement

- The test antenna with external mixer is handheld and moved carefully over the EUT to cover the EUT's whole sphere and different polarizations of the antenna.
- Caution is taken to reduce the possible overloading of the external mixer.

Final measurement

- The final measurement is performed at the position and antenna orientation causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- As external mixers may generate false images care is taken to ensure that any emission measured by the spectrum analyzer does indeed originate in the EUT. Signal identification feature of spectrum analyzer is used to eliminate false mixer images (i.e., it is not the fundamental emission or a harmonic falling precisely at the measured frequency).
- Final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement and the limit is stored.

8 Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).


In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).

Agenda: Kind of Calibration

k	calibration / calibrated	EK	limited calibration
ne	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vlk!	Attention: extended calibration interval		
NK!	Attention: not calibrated	*)	next calibration ordered / currently in progress

8.1 Shielded semi anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are confirmed with specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analyzers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.




Measurement distance: tri-log antenna 10 meter

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	n. a.	Switch-Unit	3488A	HP	2719A14505	300000368	ev	-/-	-/-
2	n. a.	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP	2920A04466	300000580	ne	-/-	-/-
3	n. a.	Meßkabine 1	HF-Absorberhalle	MWB AG 300023		300000551	ne	-/-	-/-
4	n. a.	EMI Test Receiver	ESCI 3	R&S	100083	300003312	k	09.12.2020	08.12.2021
5	n. a.	Antenna Tower	Model 2175	ETS-Lindgren	64762	300003745	izw	-/-	-/-
6	n. a.	Positioning Controller	Model 2090	ETS-Lindgren	64672	300003746	izw	-/-	-/-
7	n. a.	Turntable Interface-Box	Model 105637	ETS-Lindgren	44583	300003747	izw	-/-	-/-
8	n. a.	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck Mess - Elektronik	318	300003696	vKII	04.09.2019	03.09.2021
9	n. a.	Switch-Unit	3488A	HP	2719A14505	300000368	ev	-/-	-/-
10	n. a.	EMI Test Receiver	ESR3	Rohde & Schwarz	102587	300005771	k	10.12.2020	09.06.2022

8.2 Radiated measurements fully anechoic chamber




Equipment table (Chamber C):

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	n. a.	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP	2818A03450	300001040	vKI!	09.12.2020	08.12.2023
2	n. a.	Active Loop Antenna 9 kHz to 30 MHz	6502	EMCO	2210	300001015	vKI!	13.06.2019	12.06.2021
3	n. a.	Anechoic chamber	FAC 3/5m	MWB / TDK	87400/02	300000996	ev	-/-	-/-
4	n. a.	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck Mess - Elektronik	371	300003854	vKI!	14.01.2020	13.01.2022
5	n. a.	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	9709-5289	300000213	vKI!	14.07.2020	13.07.2022
6	n. a.	Switch / Control Unit	3488A	HP	*	300000199	ne	-/-	-/-
7	n. a.	Variable isolating transformer	MPL IEC625 Bus Variable isolating transformer	Erfi	91350	300001155	ne	-/-	-/-
8	n. a.	EMI Test Receiver 20Hz- 26,5GHz	ESU26	R&S	100037	300003555	k	11.12.2020	10.12.2021
9	n. a.	Highpass Filter	WHKX7.0/18G-8SS	Wainwright	19	300003790	ne	-/-	-/-
10	n. a.	Broadband Amplifier 0.5-18 GHz	CBLU5184540	CERNEX	22049	300004481	ev	-/-	-/-
11	n. a.	Broadband Amplifier 5-13 GHz	CBLU5135235	CERNEX	22010	300004491	ev	-/-	-/-
12	n. a.	4U RF Switch Platform	L4491A	Agilent Technologies	MY50000037	300004509	ne	-/-	-/-
13	n. a.	NEXIO EMV-Software	BAT EMC V3.16.0.49	EMCO		300004682	ne	-/-	-/-
14	n. a.	PC	ExOne	F+W		300004703	ne	-/-	-/-
15	n. a.	RF-Amplifier	AMF-6F06001800-30-10P-R	NARDA-MITEQ Inc	2011572	300005241	ev	-/-	-/-


8.3 Radiated measurements 18 GHz to 50 GHz in test lab

Radiated measurements > 12.75 GHz




8.4 Radiated measurements > 50 GHz in test lab

Radiated measurements RF laboratory



Note: conversion loss of mixer is already included in analyzer value.

8.5 Radiated power measurements using RF detector according to ANSI C63.10-2013




Note: EUT is replaced by reference source for substitution measurement

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	n.a.	Horn Antenna 18,0-40,0 GHz	LHAF180	Microw.Devel	39180-103-021	300001747	✓KII	18.02.2019	17.02.2022
2	n. a.	Std. Gain Horn Antenna 18,0-26,5 GHz	638	Narda		300000486	✓KII	21.01.2020	20.01.2022
3	n. a.	Std. Gain Horn Antenna 26,5-40,0 GHz	V637	Narda	82-16	300000510	✓KII	23.01.2020	22.01.2022
4	n.a.	Std. Gain Horn Antenna 33,0-50,1 GHz	2324-20	Flann	57	400000683	ne	-/-	-/-
5	n. a.	Std. Gain Horn Antenna 49,9-75,8 GHz	2524-20	Flann	*	300001983	ne	-/-	-/-
6	n. a.	Std. Gain Horn Antenna 60-90 GHz	COR 60_90	Thomson CSF		300000814	ne	-/-	-/-
7	n. a.	Std. Gain Horn Antenna 73,8-112 GHz	2724-20	Flann	*	300001988	ne	-/-	-/-
8	n.a.	Std. Gain Horn Antenna 92,3-140 GHz	2824-20	Flann		300001993	ne	-/-	-/-
9	n. a.	Std. Gain Horn Antenna 114-173 GHz	2924-20	Flann	*	300001999	ne	-/-	-/-
10	n. a.	Std. Gain Horn Antenna 145-220 GHz	3024-20	Flann	*	300002000	ne	-/-	-/-
11	n. a.	Std. Gain Horn Antenna 217-330 GHz	32240-20	Flann	233278	300004960	ne	-/-	-/-
12	n. a.	Standard Gain Horn 325-500 GHz	570240-20	Flann	273569	300006097	ne	-/-	-/-
14	n. a.	Harmonic Mixer 3-Port, 50-75 GHz	FS-Z75	Rohde & Schwarz	101578	300005788	k	17.06.2020	16.06.2021
15	n. a.	Harmonic Mixer 3-Port, 60-90 GHz	FS-Z90	R&S	101555	300004691	k	08.07.2020	07.07.2021
16	n. a.	Harmonic Mixer 3-Port, 75-110 GHz	FS-Z110	R&S	101411	300004959	k	19.06.2020	18.06.2021
17	n.a.	Harmonic Mixer 3-port, 90-140 GHz	FS-Z140	Rohde & Schwarz	101119	300005581	k	09.07.2020	08.07.2021
18	n. a.	Harmonic Mixer 3-Port, 110-170 GHz	FS-Z170	Radiometer Physics GmbH	100014	300004156	k	28.05.2020	27.05.2021
19	n. a.	Harmonic Mixer 3-Port, 140-220 GHz	SAM-220	Radiometer Physics GmbH	200001	300004157	k	14.07.2020	13.07.2021
20	n. a.	Harmonic Mixer 3-Port, 220-325 GHz	SAM-325	Radiometer Physics GmbH	100002	300004158	k	23.07.2020	22.07.2021
21	n.a.	Harmonic Mixer 325-500GHz	FS-Z500	Radiometer Physics GmbH	101016	300006096	k	25.05.2020	24.05.2021
22	n. a.	Spectrum Analyzer 2 Hz - 85 GHz	FSW85	R&S	101333	300005568	k	17.06.2020	16.06.2021
23	n. a.	Spectrum Analyzer	FSW50	Rohde & Schwarz	101332	300005935	k	26.02.2020	25.02.2021
24	n.a.	Std. Gain Horn Antenna 90-140 GHz	COR 90_140	Thomson CSF		300000799	ev	-/-	-/-
25	n.a.	F-Band Positive Amplitude Detector	SFD-903144-08SF-P1	Sage Millimeter Inc.	07354-1	300006119	ev	-/-	-/-
26	n.a.	SG Extension Module 110 - 170 GHz	E8257DV06	VDI	US53250018	300005540	ev	-/-	-/-
27	n.a.	Std. Gain Horn Antenna 114-173 GHz	2924-20	Flann	*	300001999	ne	-/-	-/-
28	n.a.	Synthesized Sweeper 10 MHz - 40 GHz	83640A	HP	3119A00458	300002266	✓KII	13.12.2019	12.12.2021
29	n.a.	2.5 GHz Digital Phosphor Oscilloscope	DPO7254	Tektronix	B022702	300003573	✓KII	07.12.2020	06.12.2022

8.6 AC power-line conducted emissions



$$FS = UR + CF + VC$$

(FS-field strength; UR-voltage at the receiver; CR-loss of the cable and filter; VC-correction factor of the ISN)

Example calculation:

$$FS [dB\mu V/m] = 37.62 [dB\mu V/m] + 9.90 [dB] + 0.23 [dB] = 47.75 [dB\mu V/m] \quad (244.06 \mu V/m)$$

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	-/-	Two-line V-Network (LISN) 9 kHz to 30 MHz	ESH3-Z5	R&S	892475/017	300002209	vKI!	11.12.2019	10.12.2021
2	-/-	RF-Filter-section	85420E	HP	3427A00162	300002214	NK!	-/-	-/-
3	-/-	EMI Test Receiver	ESCI 3	R&S	100083	300003312	k	09.12.2020	08.12.2021
4	-/-	Hochpass 150 kHz	EZ-25	R&S	100010	300003798	ev	-/-	-/-

9 Measurement uncertainty

Measurement uncertainty	
Test case	Uncertainty
Spectrum bandwidth	span/1000
Output power	± 3 dB
Spurious emissions radiated below 30 MHz	± 3 dB
Spurious emissions radiated 30 MHz to 1 GHz	± 3 dB
Spurious emissions radiated 1 GHz to 12.75 GHz	± 3.7 dB
Spurious emissions radiated above 12.75 GHz	± 4.5 dB
DC and low frequency voltages	± 3 %
Temperature	± 1 °C
Humidity	± 3 %

10 Far field consideration for measurements above 18 GHz

Far field distance calculation:

$$D_{ff} = 2 \times D^2 / \lambda$$

with

D_{ff} Far field distance
 D Antenna dimension
 λ wavelength

Spurious emission measurements:

Antenna frequency range in GHz	Highest measured frequency in GHz	D in cm	λ in cm	D_{ff} in cm
18-26	26	3.4	1.15	20.04
26-40	40	2.2	0.75	12.91
40-50	50	2.77	0.60	25.58
50-75	75	1.85	0.40	17.11
75-110	110	1.24	0.27	11.28
90 - 140	140	1.02	0.22	9.46
110-170	170	0.85	0.18	8.19
140-220	220	0.68	0.14	6.78
220-325	325	0.43	0.09	4.11
325-500	500	0.26	0.06	2.29

In band measurement (EIRP, OBW):

Antenna frequency range in GHz	Highest measured frequency in GHz	Antenna dimension in cm	Wavelength in cm	far field distance in cm
110 - 170	123	1	0.24	8.33

11 Measurement results

11.1 Summary

☒	No deviations from the technical specifications were ascertained
☐	There were deviations from the technical specifications ascertained
☐	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC 47 CFR Part 15 / IC RSS-210	see below	2021-05-18	-/-

Test specification clause	Test case	Temperature conditions	Power supply	Pass	Fail	NA	NP	Results (max.)
§15.215	Occupied bandwidth	Nominal	Nominal	☒	☐	☐	☐	complies
§15.258(b) (1) / (3)	Maximum E.I.R.P.	Nominal	Nominal	☒	☐	☐	☐	complies
§15.258(c)	Spurious Emissions	Nominal	Nominal	☒	☐	☐	☐	complies
§15.255(d)	Frequency stability	Extreme Nominal	Extreme Nominal	☒	☐	☐	☐	complies

Note: C = Compliant; NC = Not compliant; NA = Not applicable; NP = Not performed

12 Measurement results

12.1 Occupied bandwidth (20 dB Bandwidth)

Description:

Measurement of the Bandwidth of the wanted signal.

Measurement:

Measurement parameter	
Detector:	Pos-Peak
Sweep time:	1 s
Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Span:	See plot
Trace-Mode:	Max Hold

Limits:


FCC
CFR Part 15.258
The occupied bandwidth from intentional radiators operated within the specified frequency band shall comply with the following:
Frequency range
116 GHz – 123 GHz

Measurement results:

Test condition $T_{\text{nom}} / V_{\text{nom}}$	F_L in GHz	F_H in GHz	Occupied bandwidth in MHz
20 dB OBW (1" version)	122.014 500	122.944 600	929.10
26 dB OBW (1" version)	122.009 500	122.952 500	943.10
20 dB OBW (3/4" version)	122.014 500	122.944 600	929.10
26 dB OBW (3/4" version)	122.009 500	122.952 500	943.10
Measurement uncertainty	$\pm \text{span}/1000$		


Result: The measurement is passed.

Plot 1: 20 dB OBW, 1 inch version, operating frequency band



11:13:19 02.11.2020

Plot 2: 26 dB OBW, 1 inch version, complete band




13:34:01 05.11.2020

Plot 3: 20 dB OBW, ¾ inch version, operating frequency band



14:23:02 05.11.2020

Plot 4: 26 dB OBW, ¾ inch version, complete band



15:28:18 05.11.2020

12.2 Maximum E.I.R.P.

Description:

Measurement of the maximum radiated e.i.r.p. of the wanted signal.

Measurement:

Measurement parameter	
Detector:	Pos-Peak (RF-Detector)
Video bandwidth:	10 MHz
Trace-Mode:	Max Hold

Limits:

FCC Part 15.258 (b)

Emission levels within the 116-123 GHz, 174.8-182 GHz, 185-190 GHz and 244-246 GHz bands shall not exceed the following equivalent isotropically radiated power (EIRP) limits as measured during the transmit interval:

The average power of any emission shall not exceed 40 dBm and the peak power of any emission shall not exceed 43 dBm.

The peak power shall be measured with a detection bandwidth that encompasses the entire occupied bandwidth within the intended band of operation, e.g., 116-123 GHz, 174.8-182 GHz, 185-190 GHz or 244-246 GHz. The average emission levels shall be measured over the actual time period during which transmission occurs.

Measurement results:


Test condition	Max E.I.R.P. 10 MHz VBW	Average E.I.R.P. 10 MHz VBW
$T_{\text{nom}} / V_{\text{nom}}$	7.7 dBm	7.6 dBm
Measurement uncertainty	± 3 dB	

Test condition	Duty cycle
$T_{\text{nom}} / V_{\text{nom}}$	0.98

Description of the E.I.R.P. measurement by substitution method:


- 1) EUT emission measured with RF-detector:
 - Measurement distance: $d = 0.26 \text{ m}$
 - Maximum readout value on oscilloscope: $V = 0.5 \text{ mV}$
- 2) Substitution of EUT by a CW reference source with a frequency of $f = 122 \text{ GHz}$ and a fixed output power of $P_{\text{ref}} = 28.4 \text{ dBm}$
 - Readout value on oscilloscope adjusted by far field attenuation, 0.5 mV found at 2.8 m distance
- 3) Calculation of the Max E.I.R.P. of the EUT:
 - Free space loss: $\text{FSL}(d) = 20 \times \log(4 \times \pi \times d \times f / c)$, c : speed of light
 - Max E.I.R.P. = $P_{\text{ref}} - \text{FSL}(2.8 \text{ m}) + \text{FSL}(0.26 \text{ m}) = 7.7 \text{ dBm}$
- 4) Calculation of the Average E.I.R.P. of the EUT:
 - Measured duty cycle of the EUT: 98%
 - Average E.I.R.P. = $\text{Max E.I.R.P.} + 10 \times \log(0.98) = 7.6 \text{ dBm}$

Setup of the substitution:



- 1) Synthesized Sweeper 10 MHz - 40 GHz
- 2) SG Extension Module 110 - 170 GHz & Std. Gain Horn Antenna 114-173 GHz
- 3) F-Band Positive Amplitude Detector & Std. Gain Horn Antenna 90-140 GHz

Oscilloscope measurement:



12.3 Spurious emissions radiated

Description:

Measurement of the radiated spurious emissions.

Measurement:

Measurement parameter	
Detector:	Quasi Peak / Pos-Peak / RMS
Sweep time:	Auto
Resolution bandwidth:	F < 1 GHz: 100 kHz F > 1 GHz: 1 MHz
Video bandwidth:	Auto
Frequency range:	30 MHz to 500 GHz
Trace-Mode:	Max Hold

Limits:

FCC Part 15.258 / RSS-210

(c) Spurious emissions shall be limited as follows:

- (1) The power density of any emissions outside the band of operation, e.g., 116-123 GHz, 174.8-182 GHz, 185-190 GHz or 244-246 GHz, shall consist solely of spurious emissions.
- (2) Radiated emissions below 40 GHz shall not exceed the general limits in §15.209.

FCC / IC		
CFR Part 15.209(a) / RSS-210 / RSS-Gen		
Radiated emission limits		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3

- (3) Between 40 GHz and the highest frequency specified in § 15.33, the level of these emissions shall not exceed 90 pW/cm² at a distance of 3 meters.
- (4) The levels of the spurious emissions shall not exceed the level of the fundamental emission.

Limit conversion:

ANSI C63.10-2013 9.6

Power density at the distance specified by the limit: PD [W/m²]

Equivalent isotropically radiated power: EIRP [dBm]

Distance at which the power density limit is specified: d [m]

$$\text{EIRP[dBm]} = 10 \times \log(4 \times \pi \times d^2 \times \text{PD[W/m}^2])$$

According to this formula, an emission limit of PD = 90 pW/cm² at a distance of 3 meters corresponds to EIRP = -10 dBm.

Measurement results:


Note:

Measurements were performed in normal operation mode (frequency sweep) and in stopped mode (frequency sweep stopped at three positions within the range of operation: near top, near middle, near bottom) in accordance with §15.31(c), (m).


If the results in the cases of the stopped frequency sweep are comparable, only the results with a stop in the middle of the operating frequency range are shown below.

12.3.1 Spurious emissions radiated (1'' version)


Plot 5: 9 kHz – 30 MHz, normal mode



Plot 6: 9 kHz – 30 MHz, stopped mode (sweep stopped in the middle of the range of operation)




Plot 7: 30 MHz – 1 GHz, normal mode



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
40.865	19.09	30.0	10.9	1000	120.0	118.0	V	112	14
200.006	24.74	33.5	8.8	1000	120.0	170.0	V	67	11
280.000	28.66	36.0	7.3	1000	120.0	109.0	V	-7	14
359.121	27.22	36.0	8.8	1000	120.0	98.0	V	164	16
440.006	30.92	36.0	5.1	1000	120.0	98.0	V	159	17
859.808	27.62	36.0	8.4	1000	120.0	132.0	V	247	23


Plot 8: 30 MHz – 1 GHz, stopped mode (sweep stopped in the middle of the range of operation)



Final Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
48.276	16.41	30.0	13.6	1000	120.0	102.0	V	16	14
160.130	19.93	33.5	13.6	1000	120.0	102.0	V	67	9
192.147	23.36	33.5	10.1	1000	120.0	170.0	V	95	11
224.193	26.54	36.0	9.5	1000	120.0	107.0	V	22	12
256.221	22.62	36.0	13.4	1000	120.0	101.0	V	157	13
879.275	28.04	36.0	8.0	1000	120.0	170.0	H	67	23

Plot 9: 1 GHz – 18 GHz, normal mode




Frequency (MHz)	Peak (dBμV/m)	Peak Limit (dBμV/m)	Margin (dB)	Average (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)
9604.800	54.82	74	19.18	50.56	54	3.44

Plot 10: 1 GHz – 18 GHz, stopped mode (sweep stopped near the bottom of the range of operation)




Frequency (MHz)	Peak (dBμV/m)	Peak Limit (dBμV/m)	Margin (dB)	Average (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)
9532.200	52.65	74	17.35	47.89	54	6.11

Plot 11: 1 GHz – 18 GHz, stopped mode (sweep stopped in the middle of the range of operation)




Frequency (MHz)	Peak (dBμV/m)	Peak Limit (dBμV/m)	Margin (dB)	Average (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)
9568.500	52.25	74	21.75	46.79	54	7.21

Plot 12: 1 GHz – 18 GHz, stopped mode (sweep stopped near the top of the range of operation)




Frequency (MHz)	Peak (dBμV/m)	Peak Limit (dBμV/m)	Margin (dB)	Average (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)
9603.7	50.05	74	23.95	41.59	54	12.41


Plot 13: 18 GHz – 40 GHz, normal mode




Plot 14: 18 GHz – 40 GHz, stopped mode (sweep stopped in the middle of the range of operation)




Plot 15: 40 GHz – 50 GHz, normal mode




Plot 16: 40 GHz – 50 GHz, stopped mode (sweep stopped in the middle of the range of operation)




Plot 17: 50 GHz – 75 GHz, normal mode




Plot 18: 50 GHz – 75 GHz, normal mode




Plot 19: 50 GHz – 75 GHz, stopped mode (sweep stopped near the bottom of the range of operation)



Plot 20: 50 GHz – 75 GHz, stopped mode (sweep stopped near the bottom of the range of operation)




Plot 21: 50 GHz – 75 GHz, stopped mode (sweep stopped in the middle of the range of operation)




10:34:33 15.01.2021

Plot 22: 50 GHz – 75 GHz, stopped mode (sweep stopped in the middle of the range of operation)




10:33:44 15.01.2021


Plot 23: 50 GHz – 75 GHz, stopped mode (sweep stopped near the top of the range of operation)



Plot 24: 50 GHz – 75 GHz, stopped mode (sweep stopped near the top of the range of operation)




Plot 25: 75 GHz – 90 GHz, normal mode




10:49:19 15.01.2021

Plot 26: 75 GHz – 90 GHz, stopped mode (sweep stopped in the middle of the range of operation)




10:45:21 15.01.2021

Plot 27: 90 GHz – 116 GHz, normal mode




14:40:02 14.01.2021

Plot 28: 90 GHz – 116 GHz, stopped mode (sweep stopped near the bottom of the range of operation)




14:43:48 14.01.2021


Plot 29: 123 GHz – 140 GHz, normal mode




Plot 30: 123 GHz – 140 GHz, stopped mode (sweep stopped near the top of the range of operation)




Plot 31: 140 GHz – 220 GHz, normal mode



Plot 32: 140 GHz – 220 GHz, stopped mode (sweep stopped in the middle of the range of operation)




Plot 33: 220 GHz – 325 GHz, normal mode




11:13:18 20.01.2021

Plot 34: 220 GHz – 325 GHz, stopped mode (sweep stopped in the middle of the range of operation)




11:09:44 20.01.2021

Plot 35: 325 GHz – 400 GHz, normal mode




Plot 36: 325 GHz – 400 GHz, stopped mode (sweep stopped in the middle of the range of operation)




12.3.2 Spurious emissions radiated (3/4" version)


Plot 37: 9 kHz – 30 MHz, normal mode



Plot 38: 9 kHz – 30 MHz, stopped mode (sweep stopped in the middle of the range of operation)




Plot 39: 30 MHz – 1 GHz, normal mode



Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
48.075	18.03	30.0	12.0	1000	120.0	114.0	V	80	14
200.012	22.82	33.5	10.7	1000	120.0	170.0	V	-18	11
280.001	27.11	36.0	8.9	1000	120.0	123.0	V	-22	14
359.154	27.07	36.0	8.9	1000	120.0	106.0	V	165	16
440.865	25.89	36.0	10.1	1000	120.0	98.0	V	247	17
879.067	27.99	36.0	8.0	1000	120.0	140.0	H	67	23


Plot 40: 30 MHz – 1 GHz, stopped mode (sweep stopped in the middle of the range of operation)



Final Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
55.958	17.04	30.0	13.0	1000	120.0	114.0	V	184	15
160.617	20.44	33.5	13.1	1000	120.0	98.0	V	180	9
224.885	20.84	36.0	15.2	1000	120.0	110.0	V	-22	12
289.112	18.71	36.0	17.3	1000	120.0	105.0	V	67	14
385.494	21.97	36.0	14.0	1000	120.0	101.0	V	157	16
944.694	28.39	36.0	7.6	1000	120.0	170.0	H	247	24

Plot 41: 1 GHz – 18 GHz, normal mode




Frequency (MHz)	Peak (dBμV/m)	Peak Limit (dBμV/m)	Margin (dB)	Average (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)
9604.800	54.12	74	19.88	49.44	54	4.56

Plot 42: 1 GHz – 18 GHz, stopped mode (sweep stopped near the bottom of the range of operation)




Frequency (MHz)	Peak (dBμV/m)	Peak Limit (dBμV/m)	Margin (dB)	Average (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)
9532.200	52.1	74	21.9	47.1	54	6.9

Plot 43: 1 GHz – 18 GHz, stopped mode (sweep stopped in the middle of the range of operation)




Frequency (MHz)	Peak (dBμV/m)	Peak Limit (dBμV/m)	Margin (dB)	Average (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)
9568.500	54.31	74	19.69	50.11	54	3.89

Plot 44: 1 GHz – 18 GHz, stopped mode (sweep stopped near the top of the range of operation)




Frequency (MHz)	Peak (dBμV/m)	Peak Limit (dBμV/m)	Margin (dB)	Average (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)
9603.7	51.14	74	22.86	44.67	54	9.33


Plot 45: 18 GHz – 40 GHz, normal mode




Plot 46: 18 GHz – 40 GHz, stopped mode (sweep stopped in the middle of the range of operation)




Plot 47: 40 GHz – 50 GHz, normal mode



Plot 48: 40 GHz – 50 GHz, stopped mode (sweep stopped in the middle of the range of operation)




Plot 49: 50 GHz – 75 GHz, normal mode




10:16:53 15.01.2021

Plot 50: 50 GHz – 75 GHz, normal mode




10:20:00 15.01.2021


Plot 51: 50 GHz – 75 GHz, stopped mode (sweep stopped near the bottom of the range of operation)




Plot 52: 50 GHz – 75 GHz, stopped mode (sweep stopped near the bottom of the range of operation)




Plot 53: 50 GHz – 75 GHz, stopped mode (sweep stopped in the middle of the range of operation)




Plot 54: 50 GHz – 75 GHz, stopped mode (sweep stopped in the middle of the range of operation)




Plot 55: 50 GHz – 75 GHz, stopped mode (sweep stopped near the top of the range of operation)




Plot 56: 50 GHz – 75 GHz, stopped mode (sweep stopped near the top of the range of operation)




Plot 57: 75 GHz – 90 GHz, normal mode



Plot 58: 75 GHz – 90 GHz, stopped mode (sweep stopped in the middle of the range of operation)




Plot 59: 90 GHz – 116 GHz, normal mode




14:52:16 14.01.2021

Plot 60: 90 GHz – 116 GHz, stopped mode (sweep stopped near the bottom of the range of operation)




15:01:02 14.01.2021

Plot 61: 123 GHz – 140 GHz, normal mode




15:28:18 14.01.2021

Plot 62: 123 GHz – 140 GHz, stopped mode (sweep stopped near the top of the range of operation)




15:10:01 14.01.2021


Plot 63: 140 GHz – 220 GHz, normal mode




Plot 64: 140 GHz – 220 GHz, stopped mode (sweep stopped in the middle of the range of operation)




Plot 65: 220 GHz – 325 GHz, normal mode




Plot 66: 220 GHz – 325 GHz, stopped mode (sweep stopped in the middle of the range of operation)



Plot 67: 325 GHz – 400 GHz, normal mode



Plot 68: 325 GHz – 400 GHz, stopped mode (sweep stopped in the middle of the range of operation)



12.4 Frequency Stability

Description:

§15.215(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. In the case of intentional radiators operating under the provisions of subpart E, the emission bandwidth may span across multiple contiguous frequency bands identified in that subpart. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Fundamental emissions must be contained within the frequency bands specified in this section during all conditions of operation. Equipment is presumed to operate over the temperature range -20 to $+50$ degrees Celsius with an input voltage variation of 85% to 115% of rated input voltage, unless justification is presented to demonstrate otherwise.

Measurement:

f_C is the point in the radiation where the power is at maximum. The frequency points where the power falls 10 dB below the f_C level and above f_C level are designated as f_L and f_H respectively.

The operating frequency range (i.e. the frequency band of operation) is defined as $f_H - f_L$.

Measurement parameter	
Detector:	Peak
Sweep time:	100 s
Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Span:	2 GHz
Trace-Mode:	Max Hold
Temperature:	$-20\text{ °C} / +50\text{ °C}$
Voltage:	20.4 V / 24 V / 27.6 V

Limits:

FCC
CFR Part 15.258 (d)
The occupied bandwidth from intentional radiators operated within the specified frequency band shall comply with the following:
Frequency range
116 GHz – 123 GHz (regulatory) 122 – 123 GHz (EUT)

Measurement Results:


a) 1" version

Test Conditions	Transmitter Frequency Range [GHz]		Occupied Bandwidth [MHz]
	f_L	f_H	
-20 °C / V_{nom}	122.014 500	122.9436	929.10
-10 °C / V_{nom}	122.014 500	122.9436	929.10
0 °C / V_{nom}	122.014 500	122.9436	929.10
10 °C / V_{nom}	122.014 500	122.9436	929.10
20 °C / V_{min}	122.014 500	122.9436	929.10
20 °C / V_{nom}	122.014 500	122.9436	929.10
20 °C / V_{max}	122.014 500	122.9436	929.10
30 °C / V_{nom}	122.014 500	122.9436	929.10
40 °C / V_{nom}	122.014 500	122.9436	929.10
50 °C / V_{nom}	122.014 500	122.9436	929.10
55 °C / V_{nom}	122.014 500	122.9436	929.10

b) 3/4" version

Test Conditions	Transmitter Frequency Range [GHz]		Occupied Bandwidth [MHz]
	f_L	f_H	
-20 °C / V_{nom}	122.014 500	122.9456	931.10
-10 °C / V_{nom}	122.014 500	122.9456	931.10
0 °C / V_{nom}	122.014 500	122.9436	929.10
10 °C / V_{nom}	122.014 500	122.9436	929.10
20 °C / V_{min}	122.014 500	122.9436	929.10
20 °C / V_{nom}	122.014 500	122.9436	929.10
20 °C / V_{max}	122.014 500	122.9436	929.10
30 °C / V_{nom}	122.014 500	122.9436	929.10
40 °C / V_{nom}	122.014 500	122.9436	929.10
50 °C / V_{nom}	122.014 500	122.9436	929.10
55 °C / V_{nom}	122.014 500	122.9436	929.10

Result: The measurement is passed.

Plot 69: Occupied Bandwidth of 1" version at -20 °C / V_{nom}

17:10:48 06.11.2020

Plot 70: Occupied Bandwidth of 1" version at +55 °C / V_{nom}

14:26:26 06.11.2020

Plot 71: Occupied Bandwidth of 1" version at 20 °C / V_{min}


14:00:30 06.11.2020

Plot 72: Occupied Bandwidth of 1" version at 20 °C / V_{max}


14:06:17 06.11.2020

Plot 73: Occupied Bandwidth of 3/4" version at -20 °C / V_{nom}

10:41:41 06.11.2020

Plot 74: Occupied Bandwidth of 3/4" version at +55 °C / V_{nom}

12:59:20 06.11.2020

Plot 75: Occupied Bandwidth of 3/4" version at 20 °C / V_{min}

11:55:01 06.11.2020

Plot 76: Occupied Bandwidth of 3/4" version at 20 °C / V_{max}

11:58:01 06.11.2020

13 Conducted spurious emissions < 30 MHz

Description:

Measurement of the conducted spurious emissions in transmit mode below 30 MHz. Both power lines, phase and neutral line, are measured. Found peaks are re-measured with average and quasi peak detection to show compliance to the limits.

Measurement:

Measurement parameter	
Detector:	Peak - Quasi Peak / Average
Sweep time:	Auto
Video bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Resolution bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace-Mode:	Max Hold

Limits:


FCC		IC
CFR Part 15.207(a)		RSS-Gen 8.8
Conducted Spurious Emissions < 30 MHz		
Frequency (MHz)	Quasi-Peak (dBμV/m)	Average (dBμV/m)
0.15 – 0.5	79 to 69* (Class A) 66 to 56* (Class B)	79 to 69* (Class A) 56 to 46* (Class B)
0.5 – 5	73 (Class A) 56 (Class B)	63 (Class A) 46 (Class B)
5 – 30.0	73 (Class A) 60 (Class B)	63 (Class A) 50 (Class B)

*Decreases with the logarithm of the frequency

Measurement results:

See plots below.


Plot 77: Phase line 1" version



Project ID: 1-0079/20-03-02

Frequency	Quasi peak level	Margin quasi peak	Limit QP	Average level	Margin average	Limit AV
MHz	dBµV	dB	dBµV	dBµV	dB	dBµV
0.317906	38.04	21.72	59.761	37.08	14.12	51.203
0.448500	34.13	22.77	56.903	32.23	15.24	47.471
0.832819	33.07	22.93	56.000	31.51	14.49	46.000
4.676006	36.07	19.93	56.000	32.71	13.29	46.000
4.870031	37.25	18.75	56.000	34.73	11.27	46.000
4.996894	34.40	21.60	56.000	31.25	14.75	46.000
26.787394	31.99	28.01	60.000	19.92	30.08	50.000
27.041119	27.28	32.72	60.000	16.09	33.91	50.000
27.876919	29.72	30.28	60.000	21.50	28.50	50.000


Plot 78: Neutral line 1'' version



Project ID: 1-0079/20-03-02

Frequency	Quasi peak level	Margin quasi peak	Limit QP	Average level	Margin Average	Limit AV
MHz	dBµV	dB	dBµV	dBµV	dB	dBµV
0.191044	42.31	21.68	63.991	38.87	15.95	54.827
0.317906	38.98	20.78	59.761	38.09	13.11	51.203
0.448500	34.96	21.94	56.903	33.35	14.12	47.471
4.735706	32.25	23.75	56.000	27.41	18.59	46.000
4.862569	28.82	27.18	56.000	24.05	21.95	46.000
4.993163	31.62	24.38	56.000	27.27	18.73	46.000
26.951569	29.96	30.04	60.000	18.91	31.09	50.000
27.653044	21.29	38.71	60.000	15.14	34.86	50.000
27.843338	29.42	30.58	60.000	22.97	27.03	50.000


Plot 79: Phase line ¾" version



Project ID: 1-0079/20-03-02

Frequency	Quasi peak level	Margin quasi peak	Limit QP	Average level	Margin average	Limit AV
MHz	dBµV	dB	dBµV	dBµV	dB	dBµV
0.317906	37.25	22.52	59.761	35.96	15.24	51.203
0.765656	30.28	25.72	56.000	28.61	17.39	46.000
0.892519	28.82	27.18	56.000	27.30	18.70	46.000
4.601381	34.59	21.41	56.000	31.31	14.69	46.000
4.731975	38.05	17.95	56.000	35.42	10.58	46.000
4.858837	35.94	20.06	56.000	33.43	12.57	46.000
29.029875	34.25	25.75	60.000	22.01	27.99	50.000
29.608219	35.69	24.31	60.000	21.34	28.66	50.000
29.988806	31.77	28.23	60.000	20.30	29.70	50.000

Plot 80: Neutral line ¾" version



Project ID: 1-0079/20-03-02

Frequency	Quasi peak level	Margin quasi peak	Limit QP	Average level	Margin Average	Limit AV
MHz	dBµV	dB	dBµV	dBµV	dB	dBµV
0.191044	42.84	21.15	63.991	38.52	16.31	54.827
0.317906	38.21	21.55	59.761	37.17	14.03	51.203
0.444769	31.45	25.52	56.972	29.65	17.93	47.578
4.537950	33.39	22.61	56.000	29.08	16.92	46.000
4.731975	34.77	21.23	56.000	31.10	14.90	46.000
4.858837	35.05	20.95	56.000	31.61	14.39	46.000
29.279869	41.61	18.39	60.000	36.14	13.86	50.000
29.406731	41.11	18.89	60.000	36.26	13.74	50.000
29.854481	40.41	19.59	60.000	34.51	15.49	50.000

14 Glossary

EUT	Equipment under test
DUT	Device under test
UUT	Unit under test
GUE	GNSS User Equipment
ETSI	European Telecommunications Standards Institute
EN	European Standard
FCC	Federal Communications Commission
FCC ID	Company Identifier at FCC
IC	Industry Canada
PMN	Product marketing name
HMN	Host marketing name
HVIN	Hardware version identification number
FVIN	Firmware version identification number
EMC	Electromagnetic Compatibility
HW	Hardware
SW	Software
Inv. No.	Inventory number
S/N or SN	Serial number
C	Compliant
NC	Not compliant
NA	Not applicable
NP	Not performed
PP	Positive peak
QP	Quasi peak
AVG	Average
OC	Operating channel
OCW	Operating channel bandwidth
OBW	Occupied bandwidth
OOB	Out of band
DFS	Dynamic frequency selection
CAC	Channel availability check
OP	Occupancy period
NOP	Non occupancy period
DC	Duty cycle
PER	Packet error rate
CW	Clean wave
MC	Modulated carrier
WLAN	Wireless local area network
RLAN	Radio local area network
DSSS	Dynamic sequence spread spectrum
OFDM	Orthogonal frequency division multiplexing
FHSS	Frequency hopping spread spectrum
GNSS	Global Navigation Satellite System
C/N₀	Carrier to noise-density ratio, expressed in dB-Hz

15 Document history

Version	Applied changes	Date of release
	Final version	2021-04-22
-A	FCC-ID corrected	2021-05-18

16 Accreditation Certificate – D-PL-12076-01-05

first page	last page
 Deutsche Akkreditierungsstelle GmbH Entrusted according to Section 8 subsection 1 AkkStelleG in connection with Section 1 subsection 1 AkkStelleGBV Signatory to the Multilateral Agreements of EA, ILAC and IAF for Mutual Recognition Accreditation  The Deutsche Akkreditierungsstelle GmbH attests that the testing laboratory CTC advanced GmbH Untertürkheimer Straße 6-10, 66117 Saarbrücken is competent under the terms of DIN EN ISO/IEC 17025:2018 to carry out tests in the following fields: Telecommunication (FCC Requirements) The accreditation certificate shall only apply in connection with the notice of accreditation of 09.06.2020 with the accreditation number D-PL-12076-01. It comprises the cover sheet, the reverse side of the cover sheet and the following annex with a total of 05 pages. Registration number of the certificate: D-PL-12076-01-05 Frankfurt am Main, 09.06.2020 by order: Dipl.-Ing. (FH) Ralf Egnier Head of Division The certificate together with its annex reflects the status at the time of the date of issue. The current status of the scope of accreditation can be found in the database of accredited bodies of Deutsche Akkreditierungsstelle GmbH. https://www.dakks.de/en/content/accredited-bodies-dakks (see notes attached)	Deutsche Akkreditierungsstelle GmbH Office Berlin Spittelmarkt 10 10117 Berlin Office Frankfurt am Main Europa-Allee 52 60527 Frankfurt am Main Office Braunschweig Bundesallee 100 38116 Braunschweig The publication of extracts of the accreditation certificate is subject to the prior written approval by Deutsche Akkreditierungsstelle GmbH (DAkKS). Exempted is the unchanged form of separate disseminations of the cover sheet by the conformity assessment body mentioned overleaf. No impression shall be made that the accreditation also extends to fields beyond the scope of accreditation attested by DAkKS. The accreditation was granted pursuant to the Act on the Accreditation Body (AkkStelleG) of 31 July 2009 (Federal Law Gazette I p. 2625) and the Regulation (EC) No 765/2008 of the European Parliament and of the Council of 9 July 2008 setting out the requirements for accreditation and market surveillance relating to the marketing of products (Official Journal of the European Union L 218 of 9 July 2008, p. 30). DAkKS is a signatory to the Multilateral Agreements for Mutual Recognition of the European co-operation for Accreditation (EA), International Accreditation Forum (IAF) and International Laboratory Accreditation Cooperation (ILAC). The signatories to these agreements recognise each other's accreditations. The up-to-date state of membership can be retrieved from the following websites: EA: www.european-accreditation.org ILAC: www.ilac.org IAF: www.iaf.nu

Note: The current certificate annex is published on the website (link see below) of the Accreditation Body DAkKS or may be received by CTC advanced GmbH on request

<https://www.dakks.de/as/ast/d/D-PL-12076-01-05e.pdf>

END OF TEST REPORT