

TEST REPORT

Applicant: Queclink Wireless Solutions Co., Ltd.
Address: No.30, Lane 500, Xinlong Road, Minhang District, Shanghai, 201101
Equipment Type: GPS Tracker
Model Name: GL330MG(refer to section 2.3)
Brand Name: Queclink
FCC ID: YQD-GL330MG
Test Standard: 47 CFR Part 2.1091-2023
KDB 447498 D04 v01
Sample Arrival Date N/A
Test Date: N/A
Date of Issue: May 18, 2026

ISSUED BY:

Shanghai Tejet Communications Technology Co., Ltd. Testing Center

**Prepared by:** Huang Xiaoqin**Reviewed by:** Cai Xueguo**Approved by:** Zhang Yanqing
(Laboratory Manager)*Huang Xiaoqin**Cai Xueguo**Zhang Yanqing*

Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>May 18, 2026</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	Test Laboratory	3
1.2	Test Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information.....	4
2.2	Manufacturer Information	4
2.3	General Description for Equipment under Test (EUT)	4
2.4	Technical Information	5
3	SUMMARY OF TEST RESULT	6
3.1	Test Standards.....	6
4	DEVICE CATEGORY AND LEVELS LIMITS	7
5	ASSESSMENT RESULT	9
5.1	Output Power	9
5.2	Tune-up power.....	10
5.3	RF Exposure Evaluation Result.....	11
5.4	Collocated Power Calculation.....	12
5.5	Conclusion	12

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Address	1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China

1.2 Test Location

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Location	1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1352. The laboratory is a testing organization accredited by ISED as a accredited testing laboratory. The company number is 29671 and CAB identifier number is CN0142.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Queclink Wireless Solutions Co., Ltd.
Address	No.30, Lane 500, Xinlong Road, Minhang District, Shanghai, 201101

2.2 Manufacturer Information

Manufacturer	Queclink Wireless Solutions Co., Ltd.
Address	No.30, Lane 500, Xinlong Road, Minhang District, Shanghai, 201101

2.3 General Description for Equipment under Test (EUT)

EUT Name	GPS Tracker
Model Name Under Test	GL330MG
Series Model Name	HPN-A00, GL330B
Description of Model name differentiation	GL330MG, HPN-A00 and GL330B share the same PCBA, the only difference is HPN-A00 using another type of casing design compare to GL330MG, GL330B was design with a bigger lithium battery compare to GL330MG. (this information provided by the applicant)
Hardware Version	V1.02
Software Version	R00A02V01
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	4G Network FDD Cat M1: B2/B4/B5/B12/B13/B25/B26/B66 NB: B2/B4/B5/B12/B13/B17/B25/B26/B66 BLE, 2.4G WIFI SCAN, GNSS
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	WWAN, Bluetooth		
Frequency Range	LTE Band2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	LTE Band4	TX: 1710 ~ 1755 MHz	RX: 2110 ~ 2155 MHz
	LTE Band5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE Band12	TX: 699 ~ 716 MHz	RX: 729 ~ 746 MHz
	LTE Band13	TX: 777 ~ 787 MHz	RX: 746 ~ 756 MHz
	LTE Band17	TX: 704 ~ 716 MHz	RX: 734 ~ 746 MHz
	LTE Band25	TX: 1850 ~ 1915 MHz	RX: 1930 ~ 1995 MHz
	LTE Band26	TX: 814 ~ 849 MHz	RX: 859 ~ 894 MHz
	LTE Band66	TX: 1710 ~ 1780MHz	RX: 2110 ~ 2180 MHz
	Bluetooth	2402 ~ 2480 MHz	
Antenna Type	WWAN	PIFA Antenna	
	Bluetooth	Chip Antenna	
Exposure Category	General Population/Uncontrolled Exposure		
Product Type	Mobile Device		

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1091-2023	Radiofrequency radiation exposure evaluation: mobile devices
2	KDB 447498 D04 v01	447498 D04 Interim General RF Exposure Guidance v01

4 DEVICE CATEGORY AND LEVELS LIMITS

Mobile Devices:

CFR Title 47 §2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

FCC KDB 447498 D04 General RF Exposure Guidance v01 Limit

Evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i. e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).
The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
300		39	65	88	110	129	148	166	184	201	217
450		22	44	67	89	112	135	158	180	203	226
835		9	25	44	66	90	116	145	175	207	240
1900		3	12	26	44	66	92	122	157	195	236
2450		3	10	22	38	59	83	111	143	179	219
3600		2	8	18	32	49	71	96	125	158	195
5800		1	6	14	25	40	58	80	106	136	169

5 ASSESSMENT RESULT

5.1 Output Power

LTE Cat-M1								
Mode	Band 2	Band 4	Band 5	Band 12	Band 13	Band 25	Band 26	Band 66
Maximum Tune-Up (dBm)	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00
Antenna Gain (dBi)	0.90	2.40	-4.13	-3.69	-2.80	0.90	-3.45	2.40
EIRP/ERP (dBm)	24.90	26.40	17.72	18.16	19.05	24.90	18.40	26.40
Note: This table listed the worst case conducted power value, please refer to RF test report No. NIE: 72148RAN.001A3 for more details.								

LTE NB-IoT									
Mode	Band 2	Band 4	Band 5	Band 12	Band 13	Band 17	Band 25	Band 26	Band 66
Maximum Tune-Up (dBm)	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00
Antenna Gain (dBi)	0.90	2.40	-4.13	-3.69	-2.80	-3.69	0.90	-3.45	2.40
EIRP/ERP (dBm)	24.90	26.40	17.72	18.16	19.05	18.16	24.90	18.40	26.40
Note: This table listed the worst case conducted power value, please refer to RF test report No. NIE: 72148RAN.001A3 for more details.									

Bluetooth	
Mode	BLE Max
Conducted Power (dBm)	6.31
Antenna Gain (dBi)	2.36
EIRP (dBm)	8.67
Note: This table listed the worst case conducted power value, please refer to RF test report No. Ti-EE26030059-601 for more details.	

5.2 Tune-up power

Mode	Conducted Power Range (dBm)		EIRP Range (dBm)		ERP Range (dBm)	
LTE Cat-M1 Band 2	22.00	24.00	22.90	24.90	20.75	22.75
LTE Cat-M1 Band 4	22.00	24.00	24.40	26.40	22.25	24.25
LTE Cat-M1 Band 5	22.00	24.00	/	/	15.72	17.72
LTE Cat-M1 Band 12	22.00	24.00	/	/	16.16	18.16
LTE Cat-M1 Band 13	22.00	24.00	/	/	17.05	19.05
LTE Cat-M1 Band 25	22.00	24.00	22.90	24.90	20.75	22.75
LTE Cat-M1 Band 26	22.00	24.00	/	/	16.40	18.40
LTE Cat-M1 Band 66	22.00	24.00	24.40	26.40	22.25	24.25
LTE NB-IoT Band 2	22.00	24.00	22.90	24.90	20.75	22.75
LTE NB-IoT Band 4	22.00	24.00	24.40	26.40	22.25	24.25
LTE NB-IoT Band 5	22.00	24.00	/	/	15.72	17.72
LTE NB-IoT Band 12	22.00	24.00	/	/	16.16	18.16
LTE NB-IoT Band 13	22.00	24.00	/	/	17.05	19.05
LTE NB-IoT Band 17	22.00	24.00	/	/	16.16	18.16
LTE NB-IoT Band 25	22.00	24.00	22.90	24.90	20.75	22.75
LTE NB-IoT Band 26	22.00	24.00	/	/	16.40	18.40
LTE NB-IoT Band 66	22.00	24.00	24.40	26.40	22.25	24.25
Bluetooth	5.00	7.00	7.36	9.36	5.21	7.21
Note1: ERP= EIRP -2.15dB.						
Note2: According KDB 447498 D04, used the greater of maximum conducted power and ERP to compare with the threshold value Pth.						

5.3 RF Exposure Evaluation Result

Evolution mode	f(MHz)	Distance (cm)	Maximum power (dBm)	Threshold Power (mW)	Plimit(mW)	P/Plimit	Verdict
LTE Cat-M1 Band 2	1850	20	24.00	251.19	3060.00	0.0821	Pass
LTE Cat-M1 Band 4	1710	20	24.25	266.07	3060.00	0.0870	Pass
LTE Cat-M1 Band 5	824	20	24.00	251.19	1680.96	0.1494	Pass
LTE Cat-M1 Band 12	699	20	24.00	251.19	1425.96	0.1762	Pass
LTE Cat-M1 Band 13	777	20	24.00	251.19	1585.08	0.1585	Pass
LTE Cat-M1 Band 25	1850	20	24.00	251.19	3060.00	0.0821	Pass
LTE Cat-M1 Band 26	814	20	24.00	251.19	1660.56	0.1513	Pass
LTE Cat-M1 Band 66	1710	20	24.25	266.07	3060.00	0.0870	Pass
LTE NB-IoT Band 2	1850	20	24.00	251.19	3060.00	0.0821	Pass
LTE NB-IoT Band 4	1710	20	24.25	266.07	3060.00	0.0870	Pass
LTE NB-IoT Band 5	824	20	24.00	251.19	1680.96	0.1494	Pass
LTE NB-IoT Band 12	699	20	24.00	251.19	1425.96	0.1762	Pass
LTE NB-IoT Band 13	777	20	24.00	251.19	1585.08	0.1585	Pass
LTE NB-IoT Band 17	704	20	24.00	251.19	1436.16	0.1749	Pass
LTE NB-IoT Band 25	1850	20	24.00	251.19	3060.00	0.0821	Pass
LTE NB-IoT Band 26	814	20	24.00	251.19	1660.56	0.1513	Pass
LTE NB-IoT Band 66	1710	20	24.25	266.07	3060.00	0.0870	Pass
Bluetooth	2402	20	-2.00	0.63	3060.00	0.0002	Pass

5.4 Collocated Power Calculation

Evolution mode	Frequency(MHz)	Power /Limit	$\Sigma(\text{Power}/\text{Limit})$	Verdict
LTE Band12	699MHz ~ 716MHz	0.1762	0.1764	Pass
Bluetooth	2402MHz-2480MHz	0.0002		

Note:

1. $\Sigma(\text{Power} / \text{Limit})$: This is a summation of [(power for each transmitter/ antenna included in the simultaneous transmission)/ (corresponding Power limit)], for WWAN+ Bluetooth.
2. Both of the WWAN+ Bluetooth can transmit simultaneously, the formula of calculated the Power is $CP1 / LP1 + CP2 / LP2 + \dots \text{etc.} < 1$
 CP = Calculation power
 LP = Limit of power
3. The worst-case situation is 0.1764, which is less than "1". This confirmed that the device comply with FCC KDB 447498 D04 Power limit.
4. More power list please refer to RF test report.

5.5 Conclusion

This EUT is deemed to comply with the reference level limits, therefore the basic restrictions are compliant with human exposure limits.

Statement

1. The Testing Center guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. For the report with Accreditation Symbol, the items marked with "☆" are not within the accredited scope.
3. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the test report stamp.
4. The test data and results are only valid for the tested samples provided by the customer.
5. This report shall not be partially reproduced without the written permission of the Testing Center.
6. Any objection shall be raised to the Testing Center within 30 days after receiving the report.

--END OF REPORT--