

TEST REPORT

Applicant: Queclink Wireless Solutions Co., Ltd.
Address: No.30, Lane 500, Xinlong Road, Minhang District,
Shanghai, 201101, China
Equipment Type: Industrial Router
Model Name: WR310FNA
Brand Name: Queclink
FCC ID: YQD-WR310FNA
Test Standard: 47 CFR Part 2.1091
KDB 447498 D04 v01
Sample Arrival Date: Jul. 27, 2026
Test Date: Aug. 24, 2026
Date of Issue: Sep. 01, 2026

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Xu Rui*Xu Rui***Checked by:** Zong Liyao*Zong Liyao***Approved by:** Liao Jianming

(Technical Director)

Liao Jianming

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Sep. 01, 2026</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	3
1.1	Test Laboratory	3
1.2	Test Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information	4
2.2	Manufacturer Information.....	4
2.3	General Description for Equipment under Test (EUT).....	4
2.4	Technical Information	5
3	SUMMARY OF TEST RESULT	7
3.1	Test Standards	7
3.2	Limit Standards.....	7
4	DEVICE CATEGORY AND LEVELS LIMITS	8
5	ASSESSMENT RESULT	10
5.1	Output Power	10
5.2	Tune-up power	12
5.3	RF Exposure Evaluation Result	14
5.4	Collocated Power Calculation	15
5.5	Conclusion.....	15

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	601, Building 2, Intelligent Connected Vehicle Industrial Park, No.55, Xiangshan Road, Luotian Community, Yanluo Sub-district, Bao'an District, Shenzhen
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☐ Building 2, Intelligent Connected Vehicle Industrial Park, No.55, Xiangshan Road, Luotian Community, Yanluo Sub-district, Bao'an District, Shenzhen, Guangdong
	☒ 1/F., Building B, Ganghongji High-Tech Intelligent Industrial Park, No.1008, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Queclink Wireless Solutions Co., Ltd.
Address	No.30, Lane 500, Xinlong Road, Minhang District, Shanghai, 201101, China

2.2 Manufacturer Information

Manufacturer	Queclink Wireless Solutions Co., Ltd.
Address	No.30, Lane 500, Xinlong Road, Minhang District, Shanghai, 201101, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	Industrial Router
Model Name Under Test	WR310FNA
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	4G Network LTE FDD Band 2/4/5/7/12/13/14/17/25/26/29/30/66/71
	LTE TDD Band 38/41/42/43/48
	5G Network
	NSA: NR n2/n5/n7/n12/n13/n14/n25/n26/n29/n30/n38/n41/n48/n66/n70/n71/n77/n78
	SA: NR n2/n5/n7/n12/n13/n14/n25/n26/n29/n30/n38/n41/n48/n66/n70/n71/n77/n78
	Bluetooth (BLE)
	WIFI 802.11a, 802.11b, 802.11g, 802.11n, 802.11ac and 802.11ax
	GPS, GLONASS, BDS, Galileo, QZSS

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	LTE, NR, WIFI, Bluetooth		
Frequency Range	LTE Band 2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	LTE Band 4	TX: 1710 ~ 1755 MHz	RX: 2110 ~ 2115 MHz
	LTE Band 5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE Band 7	TX: 2500 ~ 2570 MHz	RX: 2620 ~ 2690 MHz
	LTE Band 12	TX: 699 ~ 716 MHz	RX: 729 ~ 746 MHz
	LTE Band 13	TX: 777 ~ 787 MHz	RX: 746 ~ 756 MHz
	LTE Band 14	TX: 788 ~ 798 MHz	RX: 758 ~ 768 MHz
	LTE Band 17	TX: 704 ~ 716 MHz	RX: 734 ~ 746 MHz
	LTE Band 25	TX: 1850 ~ 1915 MHz	RX: 1930 ~ 1995 MHz
	LTE Band 26	TX: 814 ~ 849 MHz	RX: 859 ~ 894 MHz
	LTE Band 30	TX: 2305 ~ 2315 MHz	RX: 2350 ~ 2360 MHz
	LTE Band 38	TX: 2570 ~ 2620 MHz	RX: 2570 ~ 2620 MHz
	LTE Band 41	TX: 2496 ~ 2690 MHz	RX: 2496 ~ 2690 MHz
	LTE Band 42	TX: 3400 ~ 3600 MHz	RX: 3400 ~ 3600 MHz
	LTE Band 43	TX: 3600 ~ 3800 MHz	RX: 3600 ~ 3800 MHz
	LTE Band 48	TX: 3550 ~ 3700 MHz	RX: 3550 ~ 3700 MHz
	LTE Band 66	TX: 1710 ~ 1780 MHz	RX: 2110 ~ 2200 MHz
	LTE Band 71	TX: 663 ~ 698 MHz	RX: 617 ~ 652 MHz
	n2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	n5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	n7	TX: 2500 ~ 2570 MHz	RX: 2620 ~ 2690 MHz
	n12	TX: 699 ~ 716 MHz	RX: 729 ~ 746 MHz
	n13	TX: 777 ~ 787 MHz	RX: 746 ~ 756 MHz
	n14	TX: 788 ~ 798 MHz	RX: 758 ~ 768 MHz
	n25	TX: 1850 ~ 1915 MHz	RX: 1930 ~ 1995 MHz
	n26	TX: 814 ~ 849 MHz	RX: 859 ~ 894 MHz
	n30	TX: 2305 ~ 2315 MHz	RX: 2350 ~ 2360 MHz
	n38	TX: 2570 ~ 2620 MHz	RX: 2570 ~ 2620 MHz
	n41	TX: 2496 ~ 2690 MHz	RX: 2496 ~ 2690 MHz

	n48	TX: 3550 ~ 3700 MHz	RX: 3550 ~ 3700 MHz
	n66	TX: 1710 ~ 1780 MHz	RX: 2110 ~ 2200 MHz
	n70	TX: 1695 ~ 1710 MHz	RX: 1995 ~ 2020 MHz
	n71	TX: 663 ~ 698 MHz	RX: 617 ~ 652 MHz
	n77	TX: 3300 ~ 4200 MHz	RX: 3300 ~ 4200 MHz
	n78	TX: 3300 ~ 3800 MHz	RX: 3300 ~ 3800 MHz
	802.11b/g	2412 ~ 2462 MHz	
	802.11n(HT20/HT40)	2412 ~ 2462 MHz	
	802.11ax(HE20/HE40)	2412 ~ 2462 MHz	
	802.11a	5150 ~ 5250 MHz	
		5250 ~ 5350 MHz	
		5470 ~ 5725 MHz	
		5725 ~ 5850 MHz	
	802.11n(HT20/HT40)	5150 ~ 5250 MHz	
		5250 ~ 5350 MHz	
		5470 ~ 5725 MHz	
		5725 ~ 5850 MHz	
	802.11ac (VHT20/VHT40/VHT80)	5150 ~ 5250 MHz	
		5250 ~ 5350 MHz	
		5470 ~ 5725 MHz	
		5725 ~ 5850 MHz	
	802.11ax (HE20/HE40/HE80)	5150 ~ 5250 MHz	
		5250 ~ 5350 MHz	
		5470 ~ 5725 MHz	
		5725 ~ 5850 MHz	
	802.11ac(VHT160)/ 802.11ax(HE160)	5150 ~ 5250 MHz	
		5470 ~ 5725 MHz	
	Bluetooth	2402 ~ 2480 MHz	
Antenna Type	WWAN	Dipole Antenna	
	WIFI	Dipole Antenna	
	Bluetooth	Dipole Antenna	
Exposure Category	General Population/Uncontrolled Exposure		
Product Type	Mobile Device		

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	KDB 447498 D04 v01	447498 D04 Interim General RF Exposure Guidance v01

3.2 Limit Standards

No.	Identity	Document Title
1	47 CFR Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices

4 DEVICE CATEGORY AND LEVELS LIMITS

Mobile Devices:

CFR Title 47 §2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

FCC KDB 447498 D04 General RF Exposure Guidance v01 Limit

Evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i. e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).
The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
300		39	65	88	110	129	148	166	184	201	217
450		22	44	67	89	112	135	158	180	203	226
835		9	25	44	66	90	116	145	175	207	240
1900		3	12	26	44	66	92	122	157	195	236
2450		3	10	22	38	59	83	111	143	179	219
3600		2	8	18	32	49	71	96	125	158	195
5800		1	6	14	25	40	58	80	106	136	169

5 ASSESSMENT RESULT

5.1 Output Power

Mode	LTE Band 2	LTE Band 4	LTE Band 5	LTE Band 7	LTE Band 12	LTE Band 13
Conducted Power (dBm)	25.00	25.00	25.00	25.00	25.00	25.00
Antenna Gain (dBi)	1.37	1.37	1.18	2.07	1.18	1.18
ERP/EIRP (dBm)	26.37	26.37	24.03	27.07	24.03	24.03
Mode	LTE Band 14	LTE Band 17	LTE Band 25	LTE Band 26	LTE Band 30	LTE Band 38
Conducted Power (dBm)	25.00	25.00	25.00	25.00	25.00	28.00
Antenna Gain (dBi)	1.18	1.18	1.37	1.18	1.11	2.07
ERP/EIRP (dBm)	24.03	24.03	26.37	24.03	26.11	30.07
Mode	LTE Band 41	LTE Band 42	LTE Band 43	LTE Band 48	LTE Band 66	LTE Band 71
Conducted Power (dBm)	28.00	28.00	28.00	22.00	25.00	25.00
Antenna Gain (dBi)	2.07	0.58	0.58	0.58	1.37	1.18
ERP/EIRP (dBm)	30.07	28.58	28.58	22.58	26.37	24.03
Note: This report listed the worst case conducted power value, please refer to 2303RSU050-U12, 2401RSU047-U4 report for more details.						

Mode	n2	n5	n7	n12	n13	n14
Conducted Power (dBm)	25.00	25.00	25.00	25.00	25.00	25.00
Antenna Gain (dBi)	1.37	1.18	2.07	1.18	1.18	1.18
ERP/EIRP (dBm)	26.37	24.03	27.07	24.03	24.03	24.03
Mode	n25	n26	n30	n38	n41	n48
Conducted Power (dBm)	25.00	25.00	25.00	28.00	31.00	25.00
Antenna Gain (dBi)	1.37	1.18	1.11	2.07	2.07	0.58
ERP/EIRP (dBm)	26.37	24.03	26.11	30.07	33.07	25.58
Mode	n66	n70	n71	n77	n78	/
Conducted Power (dBm)	25.00	25.00	25.00	31.00	31.00	/
Antenna Gain (dBi)	1.37	1.37	1.18	0.58	0.58	/
ERP/EIRP (dBm)	26.37	26.37	24.03	31.58	31.58	/
Note: This report listed the worst case conducted power value, please refer to 2303RSU050-U12, 2401RSU047-U4 report for more details.						

Mode	Bluetooth	2.4G WIFI-ANT0	2.4G WIFI-ANT1	2.4G WIFI-MIMO
Conducted Power (dBm)	6.36	20.05	19.99	22.75
Antenna Gain (dBi)	1.88	1.88	1.88	4.89
EIRP (dBm)	8.24	21.93	21.87	27.64
Mode	5.2G WIFI	5.3G WIFI	5.6G WIFI	5.8G WIFI
Conducted Power (dBm)	22.76	23.00	23.15	22.93
Antenna Gain (dBi)	-0.23	-0.49	1.58	1.08
EIRP (dBm)	22.53	22.51	24.73	24.01
Note: This report listed the worst case conducted power value, please refer to Ti-EE26070991-601, Ti-EE26070991-602, Ti-EE26070991-603 report for more details.				

5.2 Tune-up power

Mode	Conducted Power Range (dBm)	EIRP Range (dBm)	ERP Range (dBm)
LTE Band 2	[23.00, 25.00]	[24.37, 26.37]	[22.22, 24.22]
LTE Band 4	[23.00, 25.00]	[24.37, 26.37]	[22.22, 24.22]
LTE Band 5	[23.00, 25.00]	/	[22.03, 24.03]
LTE Band 7	[23.00, 25.00]	[25.07, 27.07]	[22.92, 24.92]
LTE Band 12	[23.00, 25.00]	/	[22.03, 24.03]
LTE Band 13	[23.00, 25.00]	/	[22.03, 24.03]
LTE Band 14	[23.00, 25.00]	/	[22.03, 24.03]
LTE Band 17	[23.00, 25.00]	/	[22.03, 24.03]
LTE Band 25	[23.00, 25.00]	[24.37, 26.37]	[22.22, 24.22]
LTE Band 26	[23.00, 25.00]	/	[22.03, 24.03]
LTE Band 30	[23.00, 25.00]	[24.11, 26.11]	[21.96, 23.96]
LTE Band 38	[26.00, 28.00]	[28.07, 30.07]	[25.92, 27.92]
LTE Band 41	[26.00, 28.00]	[28.07, 30.07]	[25.92, 27.92]
LTE Band 42	[26.00, 28.00]	[26.58, 28.58]	[24.43, 26.43]
LTE Band 43	[26.00, 28.00]	[26.58, 28.58]	[24.43, 26.43]
LTE Band 48	[20.00, 22.00]	[20.58, 22.58]	[18.43, 20.43]
LTE Band 66	[23.00, 25.00]	[24.37, 26.37]	[22.22, 24.22]
LTE Band 71	[23.00, 25.00]	/	[22.03, 24.03]
n2	[23.00, 25.00]	[24.37, 26.37]	[22.22, 24.22]
n5	[23.00, 25.00]	/	[22.03, 24.03]
n7	[23.00, 25.00]	[25.07, 27.07]	[22.92, 24.92]
n12	[23.00, 25.00]	/	[22.03, 24.03]
n13	[23.00, 25.00]	/	[22.03, 24.03]
n14	[23.00, 25.00]	/	[22.03, 24.03]
n25	[23.00, 25.00]	[24.37, 26.37]	[22.22, 24.22]
n26	[23.00, 25.00]	/	[22.03, 24.03]
n30	[23.00, 25.00]	[24.11, 26.11]	[21.96, 23.96]
n38	[26.00, 28.00]	[28.07, 30.07]	[25.92, 27.92]
n41	[29.00, 31.00]	[31.07, 33.07]	[28.92, 30.92]
n48	[20.00, 22.00]	[20.58, 22.58]	[18.43, 20.43]
n66	[23.00, 25.00]	[24.37, 26.37]	[22.22, 24.22]
n70	[23.00, 25.00]	[24.37, 26.37]	[22.22, 24.22]
n71	[23.00, 25.00]	/	[22.03, 24.03]
n77	[29.00, 31.00]	[29.58, 31.58]	[27.43, 29.43]
n78	[29.00, 31.00]	[29.58, 31.58]	[27.43, 29.43]
Bluetooth	[4.50, 6.50]	[6.38, 8.38]	[4.23, 6.23]

2.4G WIFI-ANT0	[18.50, 20.50]	[20.38, 22.38]	[18.23, 20.23]
2.4G WIFI-ANT1	[18.00, 20.00]	[19.88, 21.88]	[17.73, 19.73]
2.4G WIFI-MIMO	[21.00, 23.00]	[25.89, 27.89]	[23.74, 25.74]
5.2G WIFI	[21.00, 23.00]	[20.77, 22.77]	[18.62, 20.62]
5.3G WIFI	[21.00, 23.00]	[20.51, 22.51]	[18.36, 20.36]
5.6G WIFI	[21.50, 23.50]	[23.08, 25.08]	[20.93, 22.93]
5.8G WIFI	[21.00, 23.00]	[22.08, 24.08]	[19.93, 21.93]
Note1: ERP= EIRP -2.15dB. Note2: According KDB 447498 D04, used the greater of maximum conducted power and ERP to compare with the threshold value Pth.			

5.3 RF Exposure Evaluation Result

Evolution Mode	Maximum Power (dBm)	Maximum Power (mw)	Distance (mm)	Threshold Power (mW)	Power / Limit	Verdict
LTE Band 2	25.00	316.23	200	3060.00	0.103	Pass
LTE Band 4	25.00	316.23	200	3060.00	0.103	Pass
LTE Band 5	25.00	316.23	200	1680.96	0.188	Pass
LTE Band 7	25.00	316.23	200	3060.00	0.103	Pass
LTE Band 12	25.00	316.23	200	1425.96	0.222	Pass
LTE Band 13	25.00	316.23	200	1585.08	0.200	Pass
LTE Band 14	25.00	316.23	200	1607.52	0.197	Pass
LTE Band 17	25.00	316.23	200	1436.16	0.220	Pass
LTE Band 25	25.00	316.23	200	3060.00	0.103	Pass
LTE Band 26	25.00	316.23	200	1660.56	0.190	Pass
LTE Band 30	25.00	316.23	200	3060.00	0.103	Pass
LTE Band 38	28.00	630.96	200	3060.00	0.206	Pass
LTE Band 41	28.00	630.96	200	3060.00	0.206	Pass
LTE Band 42	28.00	630.96	200	3060.00	0.206	Pass
LTE Band 43	28.00	630.96	200	3060.00	0.206	Pass
LTE Band 48	22.00	158.49	200	3060.00	0.052	Pass
LTE Band 66	25.00	316.23	200	3060.00	0.103	Pass
LTE Band 71	25.00	316.23	200	1352.52	0.234	Pass
n2	25.00	316.23	200	3060.00	0.103	Pass
n5	25.00	316.23	200	1680.96	0.188	Pass
n7	25.00	316.23	200	3060.00	0.103	Pass
n12	25.00	316.23	200	1425.96	0.222	Pass
n13	25.00	316.23	200	1585.08	0.200	Pass
n14	25.00	316.23	200	1607.52	0.197	Pass
n25	25.00	316.23	200	3060.00	0.103	Pass
n26	25.00	316.23	200	1660.56	0.190	Pass
n30	25.00	316.23	200	3060.00	0.103	Pass
n38	28.00	630.96	200	3060.00	0.206	Pass
n41	31.00	1258.93	200	3060.00	0.411	Pass
n48	22.00	158.49	200	3060.00	0.052	Pass
n66	25.00	316.23	200	3060.00	0.103	Pass
n70	25.00	316.23	200	3060.00	0.103	Pass
n71	25.00	316.23	200	1352.52	0.234	Pass
n77	31.00	1258.93	200	3060.00	0.411	Pass
n78	31.00	1258.93	200	3060.00	0.411	Pass
Bluetooth	6.50	4.47	200	3060.00	0.001	Pass

2.4G WIFI-ANT0	20.50	112.20	200	3060.00	0.037	Pass
2.4G WIFI-ANT1	20.00	100.00	200	3060.00	0.033	Pass
2.4G WIFI-MIMO	25.74	374.97	200	3060.00	0.123	Pass
5.2G WIFI	23.00	199.53	200	3060.00	0.065	Pass
5.3G WIFI	23.00	199.53	200	3060.00	0.065	Pass
5.6G WIFI	23.50	223.87	200	3060.00	0.073	Pass
5.8G WIFI	23.00	199.53	200	3060.00	0.065	Pass

5.4 Collocated Power Calculation

Evolution Mode	Power / Limit	$\Sigma(\text{Power} / \text{Limit})$ of WWAN + Bluetooth + 2.4G WIFI	Verdict
WWAN	0.411	0.535	Pass
Bluetooth	0.001		
2.4G WIFI	0.123		

Note:

- $\Sigma(\text{Power} / \text{Limit})$: This is a summation of [(power for each transmitter/ antenna included in the simultaneous transmission)/ (corresponding Power limit)], for WWAN + Bluetooth + 2.4G WIFI.
- Both of the WWAN/BT/WIFI can transmit simultaneously, the formula of calculated the Power is $CP1 / LP1 + CP2 / LP2 + \dots \text{etc.} < 1$
 CP = Calculation power
 LP = Limit of power
- The worst-case situation is 0.535, which is less than "1". This confirmed that the device comply with FCC KDB 447498 D04 Power limit.
- The DUT work frequency range used is 2496 MHz ~ 2690 MHz, 2412 MHz ~ 2462 MHz and 2402 MHz ~ 2480 MHz the result close to the limit by the above formula, so we select worst case power to calculate the exclusion power threshold.

5.5 Conclusion

This EUT is deemed to comply with the reference level limits, therefore the basic restrictions are compliant with human exposure limits.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--