

Appendix I- RF Exposure statement

Exposure Requirements – FCC KDB # 447498 D01

FCC KDB # 447498 D01 V06 – RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES, Appendix A shows that the SAR Test Exclusion Threshold for a device with a separation distance.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	mm
150	232	271	310	349	387	SAR Test Exclusion Threshold (mW)
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

MHz	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
100	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567	
150	387	397	407	417	427	437	447	457	467	477	487	497	507	517	527	
300	274	294	314	334	354	374	394	414	434	454	474	494	514	534	554	
450	224	254	284	314	344	374	404	434	464	494	524	554	584	614	644	
835	164	220	275	331	387	442	498	554	609	665	721	776	832	888	943	
900	158	218	278	338	398	458	518	578	638	698	758	818	878	938	998	
1500	122	222	322	422	522	622	722	822	922	1022	1122	1222	1322	1422	1522	mW
1900	109	209	309	409	509	609	709	809	909	1009	1109	1209	1309	1409	1509	
2450	96	196	296	396	496	596	696	796	896	996	1096	1196	1296	1396	1496	
3600	79	179	279	379	479	579	679	779	879	979	1079	1179	1279	1379	1479	
5200	66	166	266	366	466	566	666	766	866	966	1066	1166	1266	1366	1466	

Calculated EIRP

The maximum measured transmitter power is the following:

Frequency [GHz]	Conducted Output Power P_{out} [dBm]	Conducted Output Power P_{out} [mW]	Maximum Antenna Gain [dBi]	P_{out} EIRP [dBm]	P_{out} EIRP [mW]
2.402	-2.33	0.58479008	3.19	0.86	1.22

Note:

Per the equation in section 1.3.1 of FCC Document # 412172 D01 Determining ERP and EIRP v01;

$$EIRP = p_t \times g_t$$

where:

p_t = transmitter output power in watts

g_t = Numeric gain of transmitting antenna (unitless)

Evaluation for FCC

According to FCC KDB # 447498 D01 V06, Clause 4.3.1

- (a) For 100MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\frac{(\text{max. power of channel, including tune - up tolerance, mW})}{(\text{min. test separation distance, mm})} \times \sqrt{f(\text{GHz})}$$

≤ 3.0 , for 1-g SAR, and ≤ 7.5 , for 10-g extremity SAR

So, the max allowed power for 1-g SAR with distance 5mm is 9.68mW

And the max allowed power for 10-g extremity SAR with distance 5mm is 24.20mW

Conclusion

The max EIRP of the device is 1.22mW, which is totally lower than the 1-g and 10-g SAR test exclusion thresholds.
So, SAR data is not required for FCC.