



## RF Exposure Evaluation

For

Datecs Ltd.

EP-700

Test Model: EP-700

Additional Model No.: EP-700 MX

Prepared for : Datecs Ltd.  
Address : 115A Tzarigradsko Shosse, Fl.4 SOFIA 1784 Bulgaria

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,  
Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : April 27, 2025  
Number of tested samples : 2  
Sample No. : A250427137-1, A250427137-2  
Serial number : Prototype  
Date of Test : April 27, 2025 ~ May 14, 2025  
Date of Report : May 15, 2025



**RF Exposure Evaluation****Report Reference No. .... : LCSA04275083ED**

Date of Issue..... : May 15, 2025

**Testing Laboratory Name ..... : Shenzhen LCS Compliance Testing Laboratory Ltd.**Address..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,  
Shajing Street, Baoan District, Shenzhen, 518000, ChinaTesting Location/ Procedure..... : Full application of Harmonised standards ■  
Partial application of Harmonised standards □  
Other standard testing method □**Applicant's Name..... : Datecs Ltd.**

Address..... : 115A Tzarigradsko Shosse, Fl.4 SOFIA 1784 Bulgaria

**Test Specification**Standard ..... : FCC KDB publication 447498 D01 General RF Exposure Guidance  
v06  
FCC CFR 47 part1 1.1310  
FCC CFR 47 part2 2.1091**Test Report Form No..... : TRF-4-E-214 A/0**

TRF Originator ..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF ..... : Dated 2011-03

**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**EUT Description..... : EP-700**

Trade Mark..... : Datecs

Test Model ..... : EP-700

Ratings..... : Please Refer to Page 6

Result ..... : **PASS****Compiled by:**

Martin Lee/ Administrator

**Supervised by:**

Jack Liu/ Technique principal

**Approved by:**

Gavin Liang/ Manager





## RF Exposure Evaluation

|                          |                       |                                      |
|--------------------------|-----------------------|--------------------------------------|
| <b>Test Report No. :</b> | <b>LCSA04275083ED</b> | <u>May 15, 2025</u><br>Date of issue |
|--------------------------|-----------------------|--------------------------------------|

|                          |                                                      |
|--------------------------|------------------------------------------------------|
| EUT.....                 | : EP-700                                             |
| Test Model.....          | : EP-700                                             |
| <b>Applicant.....</b>    | <b>: Datecs Ltd.</b>                                 |
| Address.....             | : 115A Tzarigradsko Shosse, Fl.4 SOFIA 1784 Bulgaria |
| Telephone.....           | : /                                                  |
| Fax.....                 | : /                                                  |
| <b>Manufacturer.....</b> | <b>: Datecs Ltd.</b>                                 |
| Address.....             | : 115A Tzarigradsko Shosse, Fl.4 SOFIA 1784 Bulgaria |
| Telephone.....           | : /                                                  |
| Fax.....                 | : /                                                  |
| <b>Factory.....</b>      | <b>: Datecs Ltd.</b>                                 |
| Address.....             | : 115A Tzarigradsko Shosse, Fl.4 SOFIA 1784 Bulgaria |
| Telephone.....           | : /                                                  |
| Fax.....                 | : /                                                  |

|                     |             |
|---------------------|-------------|
| <b>Test Result:</b> | <b>PASS</b> |
|---------------------|-------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

| Report Version | Issue Date   | Revision Content | Revised By |
|----------------|--------------|------------------|------------|
| 000            | May 15, 2025 | Initial Issue    | ---        |
|                |              |                  |            |
|                |              |                  |            |





## TABLE OF CONTENTS

| Description                            | Page |
|----------------------------------------|------|
| 1. Product Information.....            | 6    |
| 2. Evaluation Method .....             | 6    |
| 3. Limit .....                         | 7    |
| 4. MPE Calculation Method .....        | 7    |
| 5. Antenna Information.....            | 7    |
| 6. Conducted Power.....                | 8    |
| 7. Manufacturing Tolerance .....       | 8    |
| 8. Measurement Results .....           | 9    |
| 9. Conclusion.....                     | 10   |
| 10. Description of Test Facility ..... | 10   |
| 11.Measurement Uncertainty.....        | 10   |





## 1. Product Information

|                      |                                                                                                                                                |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| EUT                  | : EP-700                                                                                                                                       |
| Test Model           | : EP-700                                                                                                                                       |
| Additional Model No. | : EP-700 MX                                                                                                                                    |
| Model Declaration    | : PCB board, structure and internal of these model(s) are the same, So no additional models were tested                                        |
| Ratings              | : Input:100-240V~,50/60Hz,1.5AMax<br>Output:5V---0.5A, 24V---1A<br>DC 3.7V by Rechargeable Li-ion Battery, 200mAh(for the RTC function of MCU) |
| Hardware Version     | : 1.xx                                                                                                                                         |
| Software Version     | : 5.xx                                                                                                                                         |
| Bluetooth:           |                                                                                                                                                |
| Frequency Range      | : 2402MHz~2480MHz                                                                                                                              |
| Channel Number       | : 79 channels for Bluetooth V4.2 (DSS)<br>40 channels for Bluetooth V4.2 (DTS)                                                                 |
| Channel Spacing      | : 1MHz for Bluetooth V4.2 (DSS)<br>2MHz for Bluetooth V4.2 (DTS)                                                                               |
| Modulation Type      | : GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V4.2 (DSS)<br>GFSK for Bluetooth V4.2 (DTS)                                                       |
| Bluetooth Version    | : V4.2                                                                                                                                         |
| Antenna Description  | : PCB Antenna, 3.4dBi(Max.)                                                                                                                    |
| WIFI (2.4G Band):    |                                                                                                                                                |
| Frequency Range      | : 2412MHz~2462MHz                                                                                                                              |
| Channel Spacing      | : 5MHz                                                                                                                                         |
| Channel Number       | : 11 Channels for 20MHz bandwidth (2412~2462MHz)<br>7 Channels for 40MHz bandwidth (2422~2452MHz)                                              |
| Modulation Type      | : IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK)<br>IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)     |
| Antenna Description  | : PCB Antenna, 3.4dBi(Max.)                                                                                                                    |
| Exposure category    | : General population/uncontrolled environment                                                                                                  |
| EUT Type             | : Production Unit                                                                                                                              |
| Device Type          | : Mobile Device                                                                                                                                |

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

## 2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.





### 3. Limit

#### 3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

#### 3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

| Frequency Range(MHz)                        | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minute) |
|---------------------------------------------|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for Occupational/Controlled Exposure |                              |                              |                                     |                         |
| 0.3 – 3.0                                   | 614                          | 1.63                         | (100) *                             | 6                       |
| 3.0 – 30                                    | 1842/f                       | 4.89/f                       | (900/f <sup>2</sup> )*              | 6                       |
| 30 – 300                                    | 61.4                         | 0.163                        | 1.0                                 | 6                       |
| 300 – 1500                                  | /                            | /                            | f/300                               | 6                       |
| 1500 – 100,000                              | /                            | /                            | 5                                   | 6                       |

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

| Frequency Range(MHz)                          | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minute) |
|-----------------------------------------------|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for Occupational/Uncontrolled Exposure |                              |                              |                                     |                         |
| 0.3 – 3.0                                     | 614                          | 1.63                         | (100) *                             | 30                      |
| 3.0 – 30                                      | 824/f                        | 2.19/f                       | (180/f <sup>2</sup> )*              | 30                      |
| 30 – 300                                      | 27.5                         | 0.073                        | 0.2                                 | 30                      |
| 300 – 1500                                    | /                            | /                            | f/1500                              | 30                      |
| 1500 – 100,000                                | /                            | /                            | 1.0                                 | 30                      |

F=frequency in MHz

\*=Plane-wave equivalent power density

#### 4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

#### 5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

| Internal/ External Identification | Antenna type and antenna number | Operate frequency band | Maximum antenna gain | Notes            |
|-----------------------------------|---------------------------------|------------------------|----------------------|------------------|
| Internal                          | PCB Antenna                     | 2400MHz ~ 2500MHz      | 3.4dBi               | BT/ WIFI Antenna |





## 6. Conducted Power

[BT]

| Mode          | Channel | Frequency (MHz) | Peak Conducted Output Power (dBm) |
|---------------|---------|-----------------|-----------------------------------|
| GFSK          | 0       | 2402            | 10.41                             |
|               | 39      | 2441            | 11.74                             |
|               | 78      | 2480            | 11.62                             |
| $\pi/4$ DQPSK | 0       | 2402            | 12.06                             |
|               | 39      | 2441            | 13.35                             |
|               | 78      | 2480            | 13.27                             |
| 8DPSK         | 0       | 2402            | 12.53                             |
|               | 39      | 2441            | 13.54                             |
|               | 78      | 2480            | 13.48                             |

[BLE 1M]

| Mode | Channel | Frequency (MHz) | Peak Conducted Output Power (dBm) |
|------|---------|-----------------|-----------------------------------|
| BLE  | 0       | 2402            | 10.24                             |
|      | 19      | 2440            | 11.76                             |
|      | 39      | 2480            | 11.45                             |

[2.4G WIFI]

| Mode       | Channel | Frequency (MHz) | Peak Conducted Output Power (dBm) |
|------------|---------|-----------------|-----------------------------------|
| 11B        | 1       | 2412            | 20.14                             |
|            | 6       | 2437            | 20.03                             |
|            | 11      | 2462            | 19.62                             |
| 11G        | 1       | 2412            | 20.6                              |
|            | 6       | 2437            | 20.72                             |
|            | 11      | 2462            | 20                                |
| 11N20 SISO | 1       | 2412            | 20.56                             |
|            | 6       | 2437            | 20.57                             |
|            | 11      | 2462            | 19.95                             |
| 11N40 SISO | 3       | 2412            | 20.27                             |
|            | 6       | 2437            | 20.42                             |
|            | 9       | 2462            | 19.95                             |

## 7. Manufacturing Tolerance

[BT]

| GFSK (Peak)           |           |            |            |
|-----------------------|-----------|------------|------------|
| Channel               | Channel 0 | Channel 39 | Channel 78 |
| Target (dBm)          | 10.0      | 11.0       | 11.0       |
| Tolerance $\pm$ (dB)  | 1.0       | 1.0        | 1.0        |
| $\pi/4$ -DQPSK (Peak) |           |            |            |
| Channel               | Channel 0 | Channel 39 | Channel 78 |
| Target (dBm)          | 12.0      | 13.0       | 13.0       |
| Tolerance $\pm$ (dB)  | 1.0       | 1.0        | 1.0        |
| 8DPSK (Peak)          |           |            |            |





| Channel              | Channel 0 | Channel 39 | Channel 78 |
|----------------------|-----------|------------|------------|
| Target (dBm)         | 12.0      | 13.0       | 13.0       |
| Tolerance $\pm$ (dB) | 1.0       | 1.0        | 1.0        |

## [BLE1M]

| BT LE (Peak)         |           |            |            |
|----------------------|-----------|------------|------------|
| Channel              | Channel 0 | Channel 19 | Channel 39 |
| Target (dBm)         | 10.0      | 11.0       | 11.0       |
| Tolerance $\pm$ (dB) | 1.0       | 1.0        | 1.0        |

## [2.4G WIFI]

| 11B (Peak)           |           |           |            |
|----------------------|-----------|-----------|------------|
| Channel              | Channel 1 | Channel 6 | Channel 11 |
| Target (dBm)         | 20.0      | 20.0      | 19.0       |
| Tolerance $\pm$ (dB) | 1.0       | 1.0       | 1.0        |
| 11G (Peak)           |           |           |            |
| Channel              | Channel 1 | Channel 6 | Channel 11 |
| Target (dBm)         | 20.0      | 20.0      | 20.0       |
| Tolerance $\pm$ (dB) | 1.0       | 1.0       | 1.0        |
| 11N20 (Peak)         |           |           |            |
| Channel              | Channel 1 | Channel 6 | Channel 11 |
| Target (dBm)         | 20.0      | 20.0      | 19.0       |
| Tolerance $\pm$ (dB) | 1.0       | 1.0       | 1.0        |
| 11N40 (Peak)         |           |           |            |
| Channel              | Channel 3 | Channel 6 | Channel 9  |
| Target (dBm)         | 20.0      | 20.0      | 19.0       |
| Tolerance $\pm$ (dB) | 1.0       | 1.0       | 1.0        |

## 8. Measurement Results

### 8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r=20\text{cm}$ , as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

## [BT]

| Modulation Type | Output power |         | Antenna Gain (dBi) | Antenna Gain (linear) | MPE (mW/cm <sup>2</sup> ) | MPE Limits (mW/cm <sup>2</sup> ) |
|-----------------|--------------|---------|--------------------|-----------------------|---------------------------|----------------------------------|
|                 | dBm          | mW      |                    |                       |                           |                                  |
| GFSK            | 12.0         | 15.8489 | 3.4                | 2.1878                | 0.0069                    | 1.0000                           |
| $\pi/4$ -DQPSK  | 14.0         | 25.1189 | 3.4                | 2.1878                | 0.0109                    | 1.0000                           |
| 8-DPSK          | 14.0         | 25.1189 | 3.4                | 2.1878                | 0.0109                    | 1.0000                           |





## [BLE1M]

| Modulation Type | Output power |         | Antenna Gain (dBi) | Antenna Gain (linear) | MPE (mW/cm <sup>2</sup> ) | MPE Limits (mW/cm <sup>2</sup> ) |
|-----------------|--------------|---------|--------------------|-----------------------|---------------------------|----------------------------------|
|                 | dBm          | mW      |                    |                       |                           |                                  |
| GFSK            | 12.0         | 15.8489 | 3.4                | 2.1878                | 0.0069                    | 1.0000                           |

## [2.4G WIFI]

| Modulation Type   | Output power |          | Antenna Gain (dBi) | Antenna Gain (linear) | MPE (mW/cm <sup>2</sup> ) | MPE Limits (mW/cm <sup>2</sup> ) |
|-------------------|--------------|----------|--------------------|-----------------------|---------------------------|----------------------------------|
|                   | dBm          | mW       |                    |                       |                           |                                  |
| IEEE 802.11b      | 21.0         | 125.8925 | 3.4                | 2.1878                | 0.0548                    | 1.0000                           |
| IEEE 802.11g      | 21.0         | 125.8925 | 3.4                | 2.1878                | 0.0548                    | 1.0000                           |
| IEEE 802.11n HT20 | 21.0         | 125.8925 | 3.4                | 2.1878                | 0.0548                    | 1.0000                           |
| IEEE 802.11n HT40 | 21.0         | 125.8925 | 3.4                | 2.1878                | 0.0548                    | 1.0000                           |

## Remark:

1. Output power including tune-up tolerance;
2. Output power was adjusted to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

## 8.2 Simultaneous Transmission MPE Evaluation

The EUT equipped with one WLAN/NBT (Model ESP32WROOM) and BT modular (Model: Datecs BT-402), two modulars share difference antenna. need consider simultaneous transmission for two modulars. BT modular (Model: Datecs BT-402, FCC ID: YRW-BT402) MPE values refer to Modular Test Report Number: LCSA08134191EA.

| Maximum MPE Ratio <sub>ESP32WROOM</sub> | Maximum MPE Ratio <sub>BT-402</sub> | Maximum MPE Ratio <sub>ESP32WROOM + Maximum MPE Ratio<sub>BT-402</sub></sub> | Limit | Results |
|-----------------------------------------|-------------------------------------|------------------------------------------------------------------------------|-------|---------|
| 0.0548                                  | 0.0013                              | 0.0561                                                                       | 1.00  | PASS    |

## 9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

## 10. Description of Test Facility

NVLAP Accreditation Code is 600167-0.  
FCC Designation Number is CN5024.  
CAB identifier is CN0071.  
CNAS Registration Number is L4595.  
Test Firm Registration Number: 254912.

## 11.Measurement Uncertainty

BT /BLE/2.4GWLAN:

| Test Item    | Frequency Range | Uncertainty | Note |
|--------------|-----------------|-------------|------|
| Output power | 1GHz-40GHz      | ±0.57dB     | (1)  |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

-----THE END OF REPORT-----

