

TEST REPORT



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2020-01677
Page (1) / (45) Pages

1. Client

- Name : TMT ENGINEERING Co., Ltd.
- Address : 701 Gangbuk Electronics Complex, Deongneung-ro 40gil 74, Gangbuk-gu, Seoul, KOREA 01138
- Date of Receipt : 2020-02-05

2. Manufacturer

- Name : TMT ENGINEERING Co., Ltd.
- Address : 701 Gangbuk Electronics Complex, Deongneung-ro 40gil 74, Gangbuk-gu, Seoul, KOREA 01138

3. Use of Report : For FCC Certification

4. Test Sample / Model: RF MODULE / TM8258, TM8258A, TM8258B

5. Date of Test : 2020-04-08 to 2020-04-13

6. Test Standard(method) used : FCC 47 CFR part 15 subpart C 15.247

7. Testing Environment: Temp.: (23 ± 1) °C, Humidity: (49 ± 3) % R.H.

8. Test Results : Compliance

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full.

Affirmation	Tested by	Technical Manager
	Ji-Hye Kim: (Signature)	Won-Jae, Hwang: (Signature)

2020-04-16

Republic of KOREA **CTK Co., Ltd.**



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2020-01677
Page (2) / (45) Pages

REPORT REVISION HISTORY

Date	Revision	Page No
2020-04-16	Issued (CTK-2020-01677)	all

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.

CONTENTS

1. General Product Description	4
1.1 Client Information	4
1.2 Product Information.....	4
1.3 Peripheral Devices	4
1.4 Model Differences.....	4
2. Facility and Accreditations.....	5
2.1 Test Facility	5
2.2 Laboratory Accreditations and Listings.....	5
2.3 Calibration Details of Equipment Used for Measurement.....	5
3. Test Specifications	6
3.1 Standards	6
3.2 Mode of operation during the test	7
3.3 Device Modifications	7
3.4 Maximum Measurement Uncertainty	7
3.5 Test Software	7
4. Technical Characteristic Test.....	8
4.1 6dB Bandwidth	8
4.2 Maximum peak Conducted Output Power	14
4.3 Transmitter Power Spectral Density.....	19
4.4 Conducted Spurious emission.....	24
4.5 Radiated Emission	27
4.6 AC Conducted Emissions	42
APPENDIX A – Test Equipment Used For Tests	45

1. General Product Description

1.1 Client Information

Company	TMT ENGINEERING Co., Ltd.
Contact Point	701 Gangbuk Electronics Complex, Deongneung-ro 40gil 74, Gangbuk-gu, Seoul, KOREA 01138
Contact Person	Name : Hoon Lee E-mail : axle@tmteng.com Tel : +82 070-4334-5694 Fax : -

1.2 Product Information

FCC ID	YTZ-TM8258
Product Description	RF MODULE
Model name	TM8258
Variant Model name	TM8258A, TM8258B
Operating Frequency	2 402 MHz - 2 480 MHz
RF Output Power	1 Mbps : 9.93 dBm (9.84 mW) 2 Mbps : 9.93 dBm (9.84 mW)
Antenna Specification	Antenna type : Dipole Antenna Peak Gain : 1 dBi
Number of channels	40
Channel Spacing	1 MHz
Type of Modulation	GFSK (Bluetooth 5.0 - LE)
Power Source	DC 5 V
Hardware Rev	1.00
Software Rev	1.00

1.3 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.
Note Computer	HP	15-bs563TU	CND7253QPR
AC/DC Adapter	HP	HSTNN-LA40	-

1.4 Model Differences

Model Name	Description
TM8258	Basic model name
TM8258A	Variant Model name, Changing the antenna mounting direction
TM8258B	Variant Model name, Changing the antenna mounting direction

2. Facility and Accreditations

2.1 Test Facility

The measurement facility is located at (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yong-in-si, Gyeonggi-do, Korea.

2.2 Laboratory Accreditations and Listings

Country	Agency	Registration Number
USA	FCC	805871
CANADA	ISED	8737A-2
KOREA	NRRA	KR0025

2.3 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

3. Test Specifications

3.1 Standards

FCC Part Section(s)	Requirement(s)	Status (Note 1)	Test Condition
15.247(a)	6 dB Bandwidth	C	Conducted
15.247(b)	Maximum Output Power	C	
15.247(d)	Conducted Spurious emission	C	
15.247(d)	Unwanted Emission(Conducted)	C	
15.247(e)	Transmitter Power Spectral Density	C	
15.209	Radiated Emissions	C	Radiated
15.207	AC Conducted Emissions	C	Line Conducted
<u>Note 1:</u> C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable			
<u>Note 2:</u> The data in this test report are traceable to the national or international standards.			
<u>Note 3:</u> The sample was tested according to the following specification: FCC Part 15.247			
<u>Note 4:</u> The tests were performed according to the method of measurements prescribed in KDB No.558074, ANSI C63.10-2013			

3.2 Mode of operation during the test

The EUT is operated in a manner representative of the typical of the equipments.
 During at testing, system components were manipulated within the confines of typical usage to maximize each emission. All modulation modes were tests.
 The results are only attached worst cases.

Test Frequency

Lowest channel	Middle channel	Highest channel
2 402 MHz	2 440 MHz	2 480 MHz

Test mode

Mode	Duty Cycle	Duty Cycle Factor
1 Mbps	100 %	0 dB
2 Mbps	100 %	0 dB

3.3 Device Modifications

The following modifications were necessary for compliance:

Not applicable

3.4 Maximum Measurement Uncertainty

The value of the measurement uncertainty for the measurement of each parameter.
 Coverage factor $k = 2$, Confidence levels of 95 %

Description	Uncertainty
Conducted RF Output Power	± 1.5 dB
Power Spectral Density	± 1.5 dB
Occupied Bandwidth	± 0.1 MHz
Unwanted Emission(conducted)	± 3.0 dB
Radiated Emissions ($f \leq 1$ GHz)	± 4.0 dB
Radiated Emissions ($f > 1$ GHz)	± 5.0 dB

3.5 Test Software

Conducted Test	Ics Pro Ver. 6.0.3
Radiated Test	TOYO EMI software EP5RE Ver. 6.0.1.0
Line Conducted Test	ESCI7, ESCI3 : EMC32 Ver. 8.50.0 ESR7 : EMC32 Ver. 8.53.0

4. Technical Characteristic Test

4.1 6dB Bandwidth

Test Procedures

KDB 558074 - Section 8.2
ANSI C63.10-2013 - Section 11.8.2

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Procedures

ANSI C63.10-2013 - Section 6.9

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.

Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

Test Settings :

Center frequency = the highest, middle and the lowest channels

- | | |
|--|----------------------------|
| a) RBW = 100 kHz | b) VBW $\geq 3 \times$ RBW |
| c) Detector = peak | d) Trace mode = Max hold |
| e) Sweep = auto couple | |
| f) Allow trace to fully stabilize | |
| g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. | |

Minimum Standard :

6 dB Bandwidth > 500kHz

Test Data :

Test mode : 1 Mbps

Frequency (MHz)	6dB Bandwidth (MHz)	99 % Bandwidth (MHz)	Result
2 402	0.672	1.05	Complies
2 440	0.696	1.04	Complies
2 480	0.680	1.04	Complies


Test mode : 2 Mbps

Frequency (MHz)	6dB Bandwidth (MHz)	99 % Bandwidth (MHz)	Result
2 402	1.40	2.05	Complies
2 440	1.33	2.04	Complies
2 480	1.35	2.05	Complies

See next pages for actual measured spectrum plots.


1 Mbps - Lowest Frequency (2 402 MHz)

[6 dB Bandwidth]



Date: 10.APR.2020 17:31:40


[99% Bandwidth]



Date: 10.APR.2020 17:31:53


1 Mbps - Middle Frequency (2 440 MHz)

[6 dB Bandwidth]



Date: 10.APR.2020 17:38:47


[99% Bandwidth]



Date: 10.APR.2020 17:39:00


1 Mbps - Highest Frequency (2 480 MHz)

[6 dB Bandwidth]



Date: 20.NOV.2019 22:44:16


[99% Bandwidth]



Date: 20.NOV.2019 22:44:29


2 Mbps - Highest Frequency (2 480 MHz)

[6 dB Bandwidth]



Date: 10.APR.2020 18:00:46

[99% Bandwidth]



Date: 10.APR.2020 18:00:59

4.2 Maximum peak Conducted Output Power

Test Procedures

KDB 558074 - Section 8.3.1.1
ANSI C63.10-2013 - Section 11.9.1.1

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Test Settings:

Center frequency = the highest, middle and the lowest channels

- a) RBW $\geq$ DTS bandwidth
- b) VBW $\geq 3 \times$ RBW
- c) span $\geq 3 \times$ RBW
- d) Sweep time = auto couple
- e) Detector = peak
- f) Trace mode = max hold
- g) Allow trace to fully stabilize
- h) Use peak marker function to determine the peak amplitude level.

Limit :

Maximum Output Power < 1 W (30 dBm)

Test Data :

Test mode : 1 Mbps


Frequency (MHz)	Maximum peak Conducted Output Power		
	Output power (dBm)	Output power (mW)	Result
2 402	9.35	8.61	Complies
2 440	9.93	9.84	Complies
2 480	9.26	8.43	Complies

Test mode : 2 Mbps

Frequency (MHz)	Maximum peak Conducted Output Power		
	Output power (dBm)	Output power (mW)	Result
2 402	9.26	8.43	Complies
2 440	9.93	9.84	Complies
2 480	9.13	8.18	Complies


See next pages for actual measured spectrum plots.

1 Mbps - Lowest Frequency (2 402 MHz)




Date: 10.APR.2020 17:32:09

1 Mbps - Middle Frequency (2 440 MHz)




Date: 10.APR.2020 17:39:16

1 Mbps - Highest Frequency (2 480 MHz)




Date: 10.APR.2020 17:41:56

2 Mbps - Lowest Frequency (2 402 MHz)




Date: 10.APR.2020 17:57:42

2 Mbps - Middle Frequency (2 440 MHz)



Date: 10.APR.2020 17:59:47

2 Mbps - Highest Frequency (2 480 MHz)



Date: 10.APR.2020 18:01:15

4.3 Transmitter Power Spectral Density

Test Procedures

KDB 558074 - Section 8.4

ANSI C63.10-2013 - Section 11.10.2

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance.

Test Settings:

Center frequency = the highest, middle and the lowest channels

- a) RBW : $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- b) VBW $\geq 3 \times \text{RBW}$
- c) span $\geq 1.5 \times \text{DTS bandwidth}$
- d) Sweep time = auto couple
- e) Detector = peak
- f) Trace mode = max hold
- g) Allow trace to fully stabilize
- h) Use the peak marker function to determine the maximum amplitude level within the RBW.

Limit :

Power Spectral Density < 8dBm @ 3 kHz BW

Test Data :

Test mode : 1 Mbps


Frequency (MHz)	Power Spectral Density	
	dBm	Result
2 402	-1.45	Complies
2 440	-0.89	Complies
2 480	-0.74	Complies

Test mode : 2 Mbps

Frequency (MHz)	Power Spectral Density	
	dBm	Result
2 402	-2.91	Complies
2 440	-2.77	Complies
2 480	-3.45	Complies


See next pages for actual measured spectrum plots.

1 Mbps - Lowest Frequency (2 402 MHz)




Date: 10.APR.2020 17:32:25

1 Mbps - Middle Frequency (2 440 MHz)




Date: 10.APR.2020 17:39:32

1 Mbps - Highest Frequency (2 480 MHz)




Date: 10.APR.2020 17:42:12

2 Mbps - Lowest Frequency (2 402 MHz)




Date: 10.APR.2020 17:57:58

2 Mbps - Middle Frequency (2 440 MHz)



Date: 10.APR.2020 18:00:03

2 Mbps - Highest Frequency (2 480 MHz)



Date: 10.APR.2020 18:01:31

4.4 Conducted Spurious emission

Test Procedures

KDB 558074 - Section 8.5

ANSI C63.10-2013 - Section 11.11.3

The Unwanted emission from the EUT were measured according to the dictates PKPSD measurement procedure in section 11.11 of ANSI C63.10-2013.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Settings:

Center frequency = the highest, middle and the lowest channels

- | | |
|---|-----------------------------|
| a) RBW = 100 kHz | b) VBW $\geq$ 3 x RBW |
| c) Detector = peak | d) Sweep time = auto couple |
| e) Trace mode= max hold | |
| f) Allow trace to fully stabilize | |
| g) Use the peak marker function to determine the maximum amplitude level. | |

Limit :

Emission level < 20 dBc



Test results: Complies

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest in-band spectral density. Therefore the applying equipment meets the requirement.

See next pages for actual measured spectrum plots.



Spurious Emission

Test Mode : 1 Mbps




Date: 10.APR.2020 17:32:57

Date: 10.APR.2020 17:42:44





Date: 10.APR.2020 17:32:41

Date: 10.APR.2020 17:39:47




Date: 10.APR.2020 17:42:28


Test Mode : 2 Mbps




Date: 10.APR.2020 17:58:30



Date: 10.APR.2020 18:02:03



Date: 10.APR.2020 17:58:14



Date: 10.APR.2020 18:00:18

Date: 10.APR.2020 18:01:46

4.5 Radiated Emission

Test Location

- ☒ 10 m SAC (test distance : ☐ 10 m, ☒ 3 m)
☒ 3 m SAC (test distance : 3 m)

Test Procedures

KDB 558074 - Section 8.5, 8.6
ANSI C63.10-2013 - Section 11.11, 11.12

- 1) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- 2) In the frequency range above 30 MHz, Bi-Log Test Antenna(30 MHz to 1 GHz) and Horn Test Antenna(above 1 GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is carried from 1m to 4m above the ground to determine the maximum value of the field strength. The emissions levels at both horizontal and vertical polarizations should be tested.

Test Settings:

Frequency Range = 9 kHz ~ 1 GHz

- a) RBW = 100 kHz for $f < 1$ GHz, 9 kHz for $f < 30$ MHz
b) VBW $\geq$ RBW
c) Detector = CISPR Quasi-peak
d) Sweep time = auto couple

- Peak

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10th harmonic)

- a) RBW = 1 MHz
b) VBW $\geq 3 \times$ RBW
c) Detector = Peak
d) Sweep time = auto
e) Trace mode = max hold

- Average (duty cycle $\geq 98\%$)

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10th harmonic)

- a) RBW = 1 MHz
b) VBW $\geq 3 \times$ RBW
c) Detector = RMS
d) Sweep time = auto
e) Averaging type = power (i.e., RMS)
f) Trace mode = average (at least 100 traces)

- Average (duty cycle < 98%, duty cycle variations are less than $\pm 2\%$)

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10th harmonic)

a) RBW = 1 MHz

b) VBW $\geq 3 \times$ RBW

c) Detector = RMS

d) Sweep time = auto

e) Averaging type = power (i.e., RMS)

f) Trace mode = average (at least 100 traces)

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 % duty cycle.

If power averaging (RMS) mode, then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.

Limit :

FCC Part 15 § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	MHz	MHz	GHz
0.09-0.11	8.37626-8.38675	73-74.6	399.9-410	2690-2900	10.6-12.7
¹ 0.495-0.505	8.41425-8.41475	74.8-75.2	608-614	3260-3267	13.25-13.4
2.1735-2.1905	12.29-12.293	108-121.94	960-1240	3332-3339	14.47-14.5
4.125-4.128	12.51975-12.52025	123-138	1300-1427	3345.8-3358	15.35-16.2
4.17725-4.17775	12.57675-12.57725	149.9-150.05	1435-1626.5	3600-4400	17.7-21.4
4.20725-4.20775	13.36-13.41	156.52475-156.52525	1645.5-1646.5	4500-5150	22.01-23.12
6.215-6.218	16.42-16.423	156.7-156.9	1660-1710	5350-5460	23.6-24
6.26775-6.26825	16.69475-16.69525	162.0125-167.17	1718.8-1722.2	7250-7750	31.2-31.8
6.31175-6.31225	16.80425-16.80475	167.72-173.2	2200-2300	8025-8500	36.43-36.5
8.291-8.294	25.5-25.67	240-285	2310-2390	9000-9200	² Above 38.6
8.362-8.366	37.5-38.25	322-335.4	2483.5-2500	9300-9500	

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

FCC Part 15 § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in Table 2. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

Table 2. General Field Strength Limits for Licence-Exempt Transmitters

Frequency(MHz)	Field Strength uV/m@3m	Field Strength dBuV/m@3m	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705-30	30	-	30
30-88	100**	40	3
88-216	150**	43.5	3
216-960	200**	46	3
Above 960	500	54	3


** Except as provided in 15.209(g).fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz, 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g.15.231 and 15.241.

Note :


- 1) For above 1 GHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
- 2) For above 1 GHz, limit field strength of harmonics : 54 dBuV/m@3m (AV) and 74 dBuV/m@3m (PK)

Test Setup:


- 1) For field strength of emissions from 9 kHz to 30 MHz



- 2) For field strength of emissions from 30 MHz to 1 GHz



3) For field strength of emissions above 1 GHz



We have done TM8258, TM8258A and TM8258B models test. Worst case is TM8258. So the worst data of TM8258 are shown.

Test results


1) 9 kHz to 30 MHz

Test mode : Transmitter (BLE_1 Mbps, Worst Case)

The requirements are:

☒ Complies

Test Data



Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
The emissions 9 kHz to 30 MHz were 20 dB lower than the limit.			

Remark :


1. The unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
2. Result = Reading + c.f(Correction factor)
3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator - Amp Gain
4. This data is the Peak(PK) value.

Test mode : Transmitter (BLE_2 Mbps, Worst Case)

The requirements are:

☒ Complies

Test Data



Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
The emissions 9 kHz to 30 MHz were 20 dB lower than the limit.			

Remark :

1. The unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
2. Result = Reading + c.f(Correction factor)
3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator - Amp Gain
4. This data is the Peak(PK) value.


2) 30 MHz to 1 GHz

Test mode : Transmitter (BLE_1 Mbps, Worst Case)

The requirements are:

☒ Complies

Test Data



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	47.460	V	35.9	-14.7	21.2	40.0	18.8	100.0	269.0
2	100.204	H	36.1	-13.8	22.3	43.5	21.2	399.0	349.0
3	100.325	V	40.2	-13.8	26.4	43.5	17.1	100.0	206.0
4	551.981	V	29.5	0.0	29.5	46.0	16.5	100.0	229.0
5	663.653	H	31.9	1.1	33.0	46.0	13.0	101.0	220.0
6	663.774	V	30.4	1.1	31.5	46.0	14.5	100.0	239.0

Remark :


1. The unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
2. Result = Reading + c.f(Correction factor)
3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator - Amp Gain

Test mode : Transmitter (BLE_2 Mbps, Worst Case)

The requirements are:

☒ Complies

Test Data



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	100.204	H	36.2	-13.8	22.4	43.5	21.1	309.0	211.0
2	100.325	V	38.4	-13.8	24.6	43.5	18.9	101.0	260.0
3	227.153	H	36.8	-12.4	24.4	46.0	21.6	209.0	63.0
4	248.371	H	35.1	-9.8	25.3	46.0	20.7	101.0	290.0
5	665.350	V	29.7	1.1	30.8	46.0	15.2	101.0	57.0
6	666.441	H	30.9	1.1	32.0	46.0	14.0	101.0	203.0

Remark :



1. The unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
2. Result = Reading + c.f(Correction factor)
3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator - Amp Gain


3) above 1 GHz

The requirements are:

☒ Complies

Test Data





Test mode : Transmitter (BLE_1 Mbps)

Low (2 402 MHz)

Frequency [MHz]	(P)	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]
4 803.34	H	48.9	-----	74.0	-----	25.1	-----
4 804.11	H	-----	36.8	-----	54.0	-----	17.2
4 804.63	V	50.5	-----	74.0	-----	23.5	-----
4 804.04	V	-----	42.7	-----	54.0	-----	11.3
7 205.33	H	57.6	-----	74.0	-----	16.4	-----
7 206.54	H	-----	48.6	-----	54.0	-----	5.4
7 206.76	V	59.9	-----	74.0	-----	14.1	-----
7 206.71	V	-----	51.3	-----	54.0	-----	2.7
9 609.02	H	61.7	-----	74.0	-----	12.3	-----
9 607.16	H	-----	52.6	-----	54.0	-----	1.4
9 609.20	V	61.6	-----	74.0	-----	12.4	-----
9 607.30	V	-----	46.2	-----	54.0	-----	7.8
12 008.78	H	63.3	-----	74.0	-----	10.7	-----
12 011.18	H	-----	51.6	-----	54.0	-----	2.4
12 011.38	V	61.4	-----	74.0	-----	12.6	-----
12 011.15	V	-----	49.0	-----	54.0	-----	5.0

Mid (2 440 MHz)

Frequency [MHz]	(P)	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]
4 879.52	H	47.8	-----	74.0	-----	26.2	-----
4 880.07	H	-----	36.6	-----	54.0	-----	17.4
4 879.45	V	51.1	-----	74.0	-----	22.9	-----
4 879.97	V	-----	42.5	-----	54.0	-----	11.5
7 319.28	H	57.1	-----	74.0	-----	16.9	-----
7 320.67	H	-----	48.3	-----	54.0	-----	5.7
7 319.23	V	58.9	-----	74.0	-----	15.1	-----
7 319.57	V	-----	50.3	-----	54.0	-----	3.7
9 759.04	H	60.0	-----	74.0	-----	14.0	-----
9 759.12	H	-----	50.4	-----	54.0	-----	3.6
9 761.06	V	59.8	-----	74.0	-----	14.2	-----
9 760.93	V	-----	48.2	-----	54.0	-----	5.8
12 201.17	H	61.3	-----	74.0	-----	12.7	-----
12 201.09	H	-----	49.4	-----	54.0	-----	4.6
12 201.18	V	60.9	-----	74.0	-----	13.1	-----
12 199.13	V	-----	46.7	-----	54.0	-----	7.3

High (2 480 MHz)

Frequency [MHz]	(P)	Level PK [dB(uV / m)]	Level AV [dB(uV / m)]	Limit PK [dB(uV / m)]	Limit AV [dB(uV / m)]	Margin PK [dB]	Margin AV [dB]
4 960.12	H	48.7	-----	74.0	-----	25.3	-----
4 959.89	H	-----	37.4	-----	54.0	-----	16.6
4 960.44	V	52.6	-----	74.0	-----	21.4	-----
4 960.08	V	-----	40.4	-----	54.0	-----	13.6
7 440.74	H	61.5	-----	74.0	-----	12.5	-----
7 440.48	H	-----	52.7	-----	54.0	-----	1.3
7 440.62	V	58.8	-----	74.0	-----	15.2	-----
7 439.51	V	-----	48.3	-----	54.0	-----	5.7
9 921.02	H	57.3	-----	74.0	-----	16.7	-----
9 920.82	H	-----	46.6	-----	54.0	-----	7.4
9 919.03	V	58.8	-----	74.0	-----	15.2	-----
9 920.79	V	-----	46.3	-----	54.0	-----	7.7
12 398.75	H	60.2	-----	74.0	-----	13.8	-----
12 401.25	H	-----	48.2	-----	54.0	-----	5.8
12 399.00	V	60.3	-----	74.0	-----	13.7	-----
12 398.87	V	-----	45.4	-----	54.0	-----	8.6

Remarks

1. The unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
2. Correction factor = Antenna factor + Cable loss - Amp Gain

Test mode : Transmitter (BLE_2 Mbps)

Low (2 402 MHz)

Frequency [MHz]	(P)	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]
4 802.97	H	47.3	-----	74.0	-----	26.7	-----
4 804.93	H	-----	34.7	-----	54.0	-----	19.3
4 803.09	V	49.9	-----	74.0	-----	24.1	-----
4 805.08	V	-----	40.4	-----	54.0	-----	13.6
7 207.62	H	56.1	-----	74.0	-----	17.9	-----
7 204.76	H	-----	46.2	-----	54.0	-----	7.8
7 204.62	V	58.8	-----	74.0	-----	15.2	-----
7 207.09	V	-----	49.7	-----	54.0	-----	4.3
9 610.08	H	60.2	-----	74.0	-----	13.8	-----
9 609.87	H	-----	49.8	-----	54.0	-----	4.2
9 609.88	V	60.1	-----	74.0	-----	13.9	-----
9 609.93	V	-----	44.5	-----	54.0	-----	9.5
12 012.47	H	62.7	-----	74.0	-----	11.3	-----
12 012.23	H	-----	50.3	-----	54.0	-----	3.7
12 007.50	V	60.8	-----	74.0	-----	13.2	-----
12 012.17	V	-----	47.9	-----	54.0	-----	6.1

Mid (2 440 MHz)

Frequency [MHz]	(P)	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]
4 880.75	H	47.2	-----	74.0	-----	26.8	-----
4 880.93	H	-----	35.7	-----	54.0	-----	18.3
4 880.98	V	50.8	-----	74.0	-----	23.2	-----
4 879.05	V	-----	40.8	-----	54.0	-----	13.2
7 321.50	H	57.2	-----	74.0	-----	16.8	-----
7 318.84	H	-----	47.9	-----	54.0	-----	6.1
7 321.44	V	58.8	-----	74.0	-----	15.2	-----
7 318.80	V	-----	49.5	-----	54.0	-----	4.5
9 761.94	H	60.1	-----	74.0	-----	13.9	-----
9 761.83	H	-----	49.2	-----	54.0	-----	4.8
9 761.92	V	59.5	-----	74.0	-----	14.5	-----
9 761.99	V	-----	47.4	-----	54.0	-----	6.6
12 202.43	H	61.9	-----	74.0	-----	12.1	-----
12 202.43	H	-----	48.5	-----	54.0	-----	5.5
12 202.58	V	61.1	-----	74.0	-----	12.9	-----
12 197.87	V	-----	45.8	-----	54.0	-----	8.2

High (2 480 MHz)

Frequency [MHz]	(P)	Level PK [dB(uV / m)]	Level AV [dB(uV / m)]	Limit PK [dB(uV / m)]	Limit AV [dB(uV / m)]	Margin PK [dB]	Margin AV [dB]
4 958.97	H	48.2	-----	74.0	-----	25.8	-----
4 960.97	H	-----	37.0	-----	54.0	-----	17.0
4 959.20	V	53.0	-----	74.0	-----	21.0	-----
4 959.15	V	-----	39.0	-----	54.0	-----	15.0
7 438.46	H	61.3	-----	74.0	-----	12.7	-----
7 441.31	H	-----	51.7	-----	54.0	-----	2.3
7 441.60	V	59.5	-----	74.0	-----	14.5	-----
7 441.28	V	-----	47.5	-----	54.0	-----	6.5
9 922.15	H	56.7	-----	74.0	-----	17.3	-----
9 918.21	H	-----	45.3	-----	54.0	-----	8.7
9 918.20	V	59.0	-----	74.0	-----	15.0	-----
9 921.88	V	-----	44.8	-----	54.0	-----	9.2
12 397.67	H	59.7	-----	74.0	-----	14.3	-----
12 402.36	H	-----	47.5	-----	54.0	-----	6.5
12 397.52	V	60.3	-----	74.0	-----	13.7	-----
12 402.38	V	-----	45.1	-----	54.0	-----	8.9

Remarks

1. The unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
2. Correction factor = Antenna factor + Cable loss - Amp Gain

4.6 AC Conducted Emissions

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Procedures

RSS-Gen - Section 8.8

Module has been tested by mounting the End product(Printer).

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.

Amplitude measurements were performed with a quasi-peak detector and an average detector.

Limit

- 15.207(a)

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average**
0.15 ~ 0.5	66 to 56*	56 to 46*
0.5 ~ 5	56	46
5 ~ 30	60	50

* The level decreases linearly with the logarithm of the frequency.

** A linear average detector is required.

Test Results


The requirements are:

☒ Complies

Test Data

[LINE]

3CE_Class B_L1



Final Result 1


Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.159000	50.5	1000.0	9.000	On	L1	9.8	15.0	65.5
0.186000	45.8	1000.0	9.000	On	L1	9.8	18.5	64.2
0.235500	40.3	1000.0	9.000	On	L1	9.8	21.9	62.3
0.370500	39.2	1000.0	9.000	On	L1	10.0	19.3	58.5
0.519000	45.2	1000.0	9.000	On	L1	10.0	10.8	56.0
0.537000	42.9	1000.0	9.000	On	L1	10.0	13.1	56.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.186000	31.2	1000.0	9.000	On	L1	9.8	23.0	54.2
0.348000	33.3	1000.0	9.000	On	L1	9.9	15.7	49.0
0.375000	32.3	1000.0	9.000	On	L1	10.0	16.1	48.4
0.519000	39.6	1000.0	9.000	On	L1	10.0	6.4	46.0
0.537000	37.2	1000.0	9.000	On	L1	10.0	8.8	46.0
0.766500	27.7	1000.0	9.000	On	L1	9.9	18.3	46.0

[NEUTRAL]

3CE_Class B_N



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	51.9	1000.0	9.000	On	N	9.8	14.1	66.0
0.186000	48.8	1000.0	9.000	On	N	9.8	15.4	64.2
0.330000	39.8	1000.0	9.000	On	N	9.9	19.7	59.5
0.352500	40.9	1000.0	9.000	On	N	9.9	18.0	58.9
0.510000	45.3	1000.0	9.000	On	N	10.0	10.7	56.0
0.564000	41.0	1000.0	9.000	On	N	10.0	15.0	56.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	36.1	1000.0	9.000	On	N	9.8	19.9	56.0
0.348000	33.6	1000.0	9.000	On	N	9.9	15.5	49.0
0.370500	34.0	1000.0	9.000	On	N	9.9	14.5	48.5
0.510000	39.4	1000.0	9.000	On	N	10.0	6.6	46.0
0.573000	34.8	1000.0	9.000	On	N	10.0	11.2	46.0
0.757500	29.4	1000.0	9.000	On	N	9.9	16.6	46.0

APPENDIX A – Test Equipment Used For Tests

	Name of Equipment	Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date
1	SPECTRUM ANALYZER	Rohde & Schwarz	FSP-30	100994	2019-10-16	2020-10-16
2	Signal Generator	Rohde & Schwarz	SMB100A	175528	2019-10-16	2020-10-16
3	EMI Test Receiver	Rohde & Schwarz	ESCI7	100814	2019-10-22	2020-10-22
4	Bilog Antenna	Schaffner	CBL6111C	2551	2018-05-10	2020-05-10
5	Active Loop Antenna	SCHWARZBECK	FMZB 1513	1513-126	2018-05-27	2020-05-27
6	6dB Attenuator	R&S	DNF	272.4110.50-2	2019-10-25	2020-10-25
7	AMPLIFIER	SONOMA	310	291721	2020-01-22	2021-01-22
8	EMI Test Receiver	Rohde & Schwarz	ESU40	100336	2020-01-17	2021-01-17
9	Preamplifier	Agilent	8449B	3008A02011	2019-11-25	2020-11-25
10	Horn Antenna	ETS-Lindgren	3117	00154525	2019-09-25	2020-09-25
11	Horn Antenna	ETS-Lindgren	3116	00062916	2019-04-22	2020-04-22
12	Band Reject Filter	Micro Tronics	BRM50702	G233	2020-01-21	2021-01-21
13	LISN	Rohde & Schwarz	ENV216	101235	2020-01-17	2021-01-17