



FCC RADIO TEST REPORT

FCC ID: YVV-AEEDW120001

Product : WIFI REPEATER

Trade Name : AEE

Model Name : DW12

Serial Model : DW12A,DW12B,DW13,DW13A,DW13B

Report No. : NTEK-2014NT0702043F

Prepared for

SHENZHEN AEE TECHNOLOGY CO., LTD.

AEE Hi-Tech Park, Xili, Nanshan Dist., Shenzhen, 518108 China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599

Website: www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name SHENZHEN AEE TECHNOLOGY CO., LTD.

Address AEE Hi-Tech Park, Xili, Nanshan Dist., Shenzhen, 518108 China

Manufacture's Name... SHENZHEN AEE TECHNOLOGY CO., LTD.

Address AEE Hi-Tech Park, Xili, Nanshan Dist., Shenzhen, 518108 China

Product description

Product name WIFI REPEATER

Model and/or type DW12
reference

Serial Model DW12A,DW12B,DW13,DW13A,DW13B

Standards FCC Part15.247: 01 Oct. 2013

Test procedure ANSI C63.4-2003 and 558074 D01 DTS Meas Guidance v03r02

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.


This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.


Date of Test

Date (s) of performance of tests 07 Jul. 2014 ~24 Jul. 2014

Date of Issue..... 24 Jul. 2014

Test Result..... **Pass**

Testing Engineer : 
Denny Huang

Technical Manager : 
(Brown Lu)

Authorized Signatory : 
(Bill Yao)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	12
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3 . EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
3.1.2 TEST PROCEDURE	15
3.1.3 DEVIATION FROM TEST STANDARD	15
3.1.4 TEST SETUP	15
3.1.5 EUT OPERATING CONDITIONS	15
3.1.6 TEST RESULTS	16
3.2 RADIATED EMISSION MEASUREMENT	18
3.2.1 RADIATED EMISSION LIMITS	18
3.2.2 TEST PROCEDURE	19
3.2.3 DEVIATION FROM TEST STANDARD	19
3.2.4 TEST SETUP	20
3.2.5 EUT OPERATING CONDITIONS	21
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	22
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	23
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	25
4 . POWER SPECTRAL DENSITY TEST	26
4.1 APPLIED PROCEDURES / LIMIT	26
4.1.1 TEST PROCEDURE	26
4.1.2 DEVIATION FROM STANDARD	26
4.1.3 TEST SETUP	26
4.1.4 EUT OPERATION CONDITIONS	26
4.1.5 TEST RESULTS	27
5 . BANDWIDTH TEST	35
5.1 APPLIED PROCEDURES / LIMIT	35
5.1.1 TEST PROCEDURE	35

Table of Contents

	Page
TEST SETUP	35
5.1.2 EUT OPERATION CONDITIONS	35
5.1.3 TEST RESULTS	36
6 . PEAK OUTPUT POWER TEST	44
6.1 APPLIED PROCEDURES / LIMIT	44
6.1.1 TEST PROCEDURE	44
6.1.2 DEVIATION FROM STANDARD	44
6.1.3 TEST SETUP	44
6.1.4 EUT OPERATION CONDITIONS	44
6.1.5 TEST RESULTS	45
7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	46
7.1 DEVIATION FROM STANDARD	46
7.2 TEST SETUP	46
7.3 EUT OPERATION CONDITIONS	46
7.4 TEST RESULTS	47
8 . ANTENNA REQUIREMENT	53
8.1 STANDARD REQUIREMENT	53
8.2 EUT ANTENNA	53
9 . EUT TEST PHOTO	54
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add.:1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	WIFI REPEATER	
Trade Name	AEE	
Model Name	DW12	
Serial Model	DW12A,DW12B,DW13,DW13A,DW13B	
Model Difference	All the model are the same circuit and RF module, except the model name and colour.	
Product Description	The EUT is a WIFI REPEATER	
	Operation Frequency:	802.11b/g/n(20MHz): 2412~2462MHz 802.11n(40MHz):2422~2452MHz
	Modulation Type:	CCK/OFDM/DBPSK/DAPSK
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n(20MHz/40MHz):150/144.44/130/117/115.56/104/86.67/78/52/6.5Mbps
	Number Of Channel	802.11b/g/n20MHz:11CH 802.11n40MHz:7CH
	Antenna Designation:	Please see Note 3.
	Output Power(Conducted):	802.11b: 14.51 dBm (Max.) 802.11g: 13.76 dBm (Max.) 802.11n(20M): 13.64dBm (Max.) 802.11n(40M): 11.45 dBm (Max.)
	Antenna Gain (dBi)	Antenna A: 5.0 dbi Antenna B: 5.0 dbi
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.	
Ratings	DC 3.7V	
Charging Voltage and Current	DC5V/1A	
Battery	DC 3.7V	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.


Channel List for 802.11b/g/n(20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	06	2437	09	2452		
04	2427	07	2442				
05	2432	08	2447				

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Gain (dBi)	NOTE
A	N/A	N/A	Ceramic antenna	5.0	Wifi Antenna
B	N/A	N/A	Ceramic antenna	5.0	Wifi Antenna



The Control software can control antenna A and B,

Two antennas simultaneously transmit.

For MIMO mode, Directional gain= $G_{ANT} + 10\log(N)$ dBi = 11.02dBi

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n/20MHz CH1/ CH6/ CH11
Mode 4	802.11n/40MHz CH3/ CH6/ CH9
Mode 5	Link Mode

For Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode


For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n/20MHz CH1/ CH6/ CH11
Mode 4	802.11n/40MHz CH3/ CH6/ CH9

Note:


- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test



Radiated Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	WIFI REPEATER	AEE	DW12	N/A	EUT
E-2	Notebook	DELL	PP10L	N/A	
E-3	Adapter	DELL	PA-10	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.2m	
C-2	NO	NO	0.8m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2014.07.06	2015.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2014.06.07	2015.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2014.07.06	2015.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2014.06.07	2015.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2014.06.07	2015.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2014.07.06	2015.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2013.12.22	2014.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2014.07.06	2015.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2014.07.06	2015.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2014.06.07	2015.06.06	1 year
2	LISN	R&S	ENV216	101313	2013.08.24	2014.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2013.08.24	2014.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2014.06.07	2015.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.06.07	2015.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2014.06.08	2015.06.07	1 year

1	Attenuation	MCE	24-10-34	BN9258	2014.06.08	2015.06.07	1 year
---	-------------	-----	----------	--------	------------	------------	--------

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.6 TEST RESULTS

EUT :	WIFI REPEATER	Model Name. :	DW12
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5.0V form PC AC 120V/60Hz	Test Mode :	Mode 5

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1940	26.83	9.51	36.34	63.86	-27.52	QP
0.1940	19.62	9.51	29.13	53.86	-24.73	AVG
0.4980	16.72	9.51	26.23	46.03	-19.80	AVG
0.4980	30.20	9.51	39.71	56.03	-16.32	QP
0.8660	25.91	9.53	35.44	56.00	-20.56	QP
0.8660	15.30	9.53	24.83	46.00	-21.17	AVG
1.5700	16.95	9.54	26.49	46.00	-19.51	AVG
1.5700	27.14	9.54	36.68	56.00	-19.32	QP
3.9740	29.27	9.59	38.86	56.00	-17.14	QP
3.9740	19.43	9.59	29.02	46.00	-16.98	AVG
6.6779	25.99	9.66	35.65	60.00	-24.35	QP
6.6779	16.35	9.66	26.01	50.00	-23.99	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	WIFI REPEATER	Model Name. :	DW12
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5.0V form PC AC 120V/60Hz	Test Mode :	Mode 5

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.2500	32.37	9.50	41.87	61.75	-19.88	QP
0.2500	19.21	9.50	28.71	51.75	-23.04	AVG
0.3820	29.88	9.52	39.40	58.23	-18.83	QP
0.3820	13.30	9.52	22.82	48.23	-25.41	AVG
0.5060	16.49	9.53	26.02	46.00	-19.98	AVG
0.5060	32.62	9.53	42.15	56.00	-13.85	QP
0.6460	30.83	9.53	40.36	56.00	-15.64	QP
0.6460	14.43	9.53	23.96	46.00	-22.04	AVG
3.8900	27.67	9.59	37.26	56.00	-18.74	QP
3.8900	16.94	9.59	26.53	46.00	-19.47	AVG
6.6700	23.90	9.66	33.56	60.00	-26.44	QP
6.6700	15.18	9.66	24.84	50.00	-25.16	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz

**3.2.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT:	WIFI REPEATER	Model Name. :	DW12
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.


3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT :	WIFI REPEATER	Model Name :	DW12
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Polarization :	Horizontal
Test Power :	DC 3.7V	Test Mode :	Mode 1

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
133.6187	18.52	11.71	30.23	43.50	-13.27	QP
239.9874	28.41	13.49	41.90	46.00	-4.10	QP
250.3011	28.51	13.59	42.10	46.00	-3.90	QP
303.5437	23.48	14.30	37.78	46.00	-8.22	QP
425.0280	15.93	18.81	34.74	46.00	-11.26	QP
845.0878	10.73	27.25	37.98	46.00	-8.02	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	WIFI REPEATER	Model Name :	DW12
Temperature :	24 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Polarization :	Vertical
Test Power :	DC 3.7V	Test Mode :	Mode 1

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
134.5592	13.25	11.67	24.92	43.50	-18.58	QP
234.1682	19.14	13.09	32.23	46.00	-13.77	QP
240.8302	19.05	13.49	32.54	46.00	-13.46	QP
425.0280	10.68	18.81	29.49	46.00	-16.51	QP
494.1983	11.87	20.17	32.04	46.00	-13.96	QP
665.8034	18.56	23.85	42.41	46.00	-3.59	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2412 MHz)-Above 1G							
4824.211	48.82	10.44	59.26	74.00	-14.74	Pk	Vertical
4824.211	30.14	10.44	40.58	54.00	-13.42	Av	Vertical
7236.134	42.11	12.39	54.50	74.00	-19.50	Pk	Vertical
7236.134	26.38	12.39	38.77	54.00	-15.23	Av	Vertical
4824.099	50.24	10.44	60.68	74.00	-13.32	Pk	Horizontal
4824.099	31.32	10.44	41.76	54.00	-12.24	Av	Horizontal
7236.282	42.78	12.39	55.17	74.00	-18.83	Pk	Horizontal
7236.282	27.95	12.39	40.34	54.00	-13.66	Av	Horizontal
Mid Channel (2437 MHz)-Above 1G							
4874.136	46.42	10.40	56.82	74.00	-17.18	Pk	Vertical
4874.136	27.31	10.40	37.71	54.00	-16.29	Av	Vertical
7311.264	40.03	12.75	52.78	74.00	-21.22	Pk	Vertical
7311.264	22.99	12.75	35.74	54.00	-18.26	Av	Vertical
4874.311	47.17	10.40	57.57	74.00	-16.43	Pk	Horizontal
4874.311	28.39	10.40	38.79	54.00	-15.21	Av	Horizontal
7311.025	39.28	12.75	52.03	74.00	-21.97	Pk	Horizontal
7311.025	23.97	12.75	36.72	54.00	-17.28	Av	Horizontal
High Channel (2462 MHz)- Above 1G							
4924.288	49.36	10.39	59.75	74.00	-14.25	Pk	Vertical
4924.288	30.63	10.39	41.02	54.00	-12.98	Av	Vertical
7386.144	42.47	12.68	55.15	74.00	-18.85	Pk	Vertical
7386.144	26.04	12.68	38.72	54.00	-15.28	Av	Vertical
4924.093	49.01	10.39	59.40	74.00	-14.60	Pk	Horizontal
4924.093	31.13	10.39	41.52	54.00	-12.48	Av	Horizontal
7386.179	41.41	12.68	54.09	74.00	-19.91	Pk	Horizontal
7386.179	26.65	12.68	39.33	54.00	-14.67	Av	Horizontal

Note:"802.11b" mode is the worst mode.

4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. 3 kHz ≤ Set the RBW ≤ 100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.


4.1.5 TEST RESULTS



EUT :	WIFI REPEATER	Model Name :	DW12
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX b Mode /CH01, CH06, CH11		

Frequency	Power Density A (dBm)	Power Density B (dBm)	Total Power density (dBm)	Limit (dBm)	Result
2412 MHz	-14.55	-14.72	-11.62	2.98	PASS
2437 MHz	-14.59	-14.69	-11.63	2.98	PASS
2462 MHz	-14.09	-14.23	-11.15	2.98	PASS

NOTE: A(B) Represent the value of antenna A and B,The worst data is A Antenna, only shown Antenna A Plot.

Limit = $-11.02+6=2.98$ dBm.








EUT :	WIFI REPEATER	Model Name :	DW12
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX g Mode /CH01, CH06, CH11		

Frequency	Power Density A (dBm)	Power Density B (dBm)	Total Power density (dBm)	Limit (dBm)	Result
2412 MHz	-13.76	-13.96	-11.01	2.98	PASS
2437 MHz	-13.15	-13.45	-11.05	2.98	PASS
2462 MHz	-13.07	-13.38	-10.78	2.98	PASS

NOTE: A(B) Represent the value of antenna A and B, The worst data is A Antenna, only shown Antenna A Plot.

Limit = $-11.02 + 6 = 2.98 \text{ dBm}$.






EUT :	WIFI REPEATER	Model Name :	DW12
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		


Frequency	Power Density A (dBm)	Power Density B (dBm)	Total Power density (dBm)	Limit (dBm)	Result
2412 MHz	-15.17	-15.41	-12.28	2.98	PASS
2437 MHz	-15.32	-15.69	-12.49	2.98	PASS
2462 MHz	-14.93	-15.11	-12.01	2.98	PASS

NOTE: A(B) Represent the value of antenna A and B, The worst data is A Antenna, only shown Antenna A Plot.


Limit = $-8-11.02+6=2.98\text{dBm}$.



TX CH06



TX CH11




EUT :	WIFI REPEATER	Model Name :	DW12
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09		


Frequency	Power Density A (dBm)	Power Density B (dBm)	Total Power density (dBm)	Limit (dBm)	Result
2422 MHz	-20.07	-20.14	-17.09	2.98	PASS
2437 MHz	-20.16	-20.31	-17.22	2.98	PASS
2452 MHz	-18.27	-18.45	-15.35	2.98	PASS

NOTE: A(B) Represent the value of antenna A and B, The worst data is A Antenna, only shown Antenna A Plot.


Limit = $-8 - 11.02 + 6 = 2.98 \text{ dBm}$.



TX CH06



TX CH09



5. BANDWIDTH TEST


5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



5.1.2 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.3 TEST RESULTS


EUT :	WIFI REPEATER	Model Name :	DW12
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX b Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)		Limit (kHz)	Result
		ANT A	ANT B		
Low	2412	10.152	10.067	500	Pass
Middle	2437	10.142	10.075	500	Pass
High	2462	10.136	10.046	500	Pass


NOTE: A(B) Represent the value of antenna A and B, The worst data is A Antenna, only shown Antenna A Plot.



TX CH 06




TX CH 11




EUT :	WIFI REPEATER	Model Name :	DW12
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX g Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)		Limit (kHz)	Result
		ANT A	ANT B		
Low	2412	16.523	16.363	500	Pass
Middle	2437	16.554	16.346	500	Pass
High	2462	16.538	16.473	500	Pass


NOTE: A(B) Represent the value of antenna A and B, The worst data is A Antenna, only shown Antenna A Plot.



TX CH 06




TX CH 11





EUT :	WIFI REPEATER	Model Name :	DW12
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)		Limit (kHz)	Result
		ANT A	ANT B		
Low	2412	17.720	17.573	500	Pass
Middle	2437	17.756	17.637	500	Pass
High	2462	17.771	17.474	500	Pass

NOTE: A(B) Represent the value of antenna A and B, The worst data is A Antenna, only shown Antenna A Plot.







EUT :	WIFI REPEATER	Model Name :	DW12
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09		

Channel	Frequency (MHz)	6dB bandwidth (MHz)		Limit (kHz)	Result
		ANT A	ANT B		
Low	2422	36.547	36.345	500	Pass
Middle	2437	36.531	36.472	500	Pass
High	2452	36.518	36.386	500	Pass


NOTE: A(B) Represent the value of antenna A and B, The worst data is A Antenna, only shown Antenna A Plot.



TX CH 06



TX CH 09



6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

EUT :	WIFI REPEATER	Model Name :	DW12
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX b/g/n20/n40 Mode		

Test Channel	Frequency	Maximum output power. Antenna port				Total Power		LIMIT
		(PK) (dBm)		(AV) (dBm)		(PK)	(AV)	
	(MHz)	ANT A	ANT B	ANT A	ANT B	dBm	dBm	dBm
TX 802.11b Mode								
CH01	2412	11.98	10.95	7.54	6.95	14.51	10.27	24.98
CH06	2437	11.92	10.94	7.34	6.96	14.47	10.16	24.98
CH11	2462	11.86	10.96	7.46	6.89	14.44	10.19	24.98
TX 802.11g Mode								
CH01	2412	10.87	10.34	6.85	6.34	13.62	9.61	24.98
CH06	2437	10.84	10.54	6.82	6.35	13.70	9.60	24.98
CH11	2462	10.93	10.57	6.97	6.49	13.76	9.75	24.98
TX 802.11n/20M Mode								
CH01	2412	10.58	10.45	6.51	6.45	13.53	9.49	24.98
CH06	2437	10.73	10.52	6.63	6.56	13.64	9.61	24.98
CH11	2462	10.56	10.36	6.68	6.36	13.47	9.53	24.98
TX 802.11n/40M Mode								
CH03	2422	8.52	8.13	6.64	6.26	11.34	9.46	24.98
CH06	2437	8.41	8.11	6.72	6.23	11.27	9.49	24.98
CH09	2452	8.59	8.29	6.79	6.25	11.45	9.54	24.98

Limit =30-11.02+6=24.98 dBm for output power

7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

7.1 DEVIATION FROM STANDARD

No deviation.

7.2 TEST SETUP



7.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.4 TEST RESULTS

EUT :	WIFI REPEATER	Model Name :	DW12
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V


Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
802.11b			
Left-band	39..73	20	Pass
Right-band	53.75	20	Pass
802.11g			
Left-band	23.95	20	Pass
Right-band	31.91	20	Pass
802.11n20			
Left-band	29.34	20	Pass
Right-band	28.98	20	Pass
802.11n40			
Left-band	24.78	20	Pass
Right-band	26.27	20	Pass

Radiated band edge:


Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
802.11b							
2390	56.85	-13.06	43.79	74	-30.21	peak	Vertical
2390	56.59	-13.06	43.53	74	-30.47	peak	Horizontal
2483.5	57.78	-12.78	45	74	-29.00	peak	Vertical
2483.5	57.83	-12.78	45.05	74	-28.95	peak	Horizontal
802.11g							
2390	56.75	-13.06	43.69	74	-30.31	peak	Vertical
2390	55.93	-13.06	42.87	74	-31.13	peak	Horizontal
2483.5	57.64	-12.78	44.86	74	-29.14	peak	Vertical
2483.5	57.86	-12.78	45.08	74	-28.92	peak	Horizontal
802.11n20							
2390	58.97	-13.06	45.91	74	-28.09	peak	Vertical
2390	58.75	-13.06	45.69	74	-28.31	peak	Horizontal
2483.5	58.89	-12.78	46.11	74	-27.89	peak	Vertical
2483.5	59.01	-12.78	46.23	74	-27.77	peak	Horizontal
802.11n40							
2390	59.76	-13.06	46.7	74	-27.30	peak	Vertical
2390	60.85	-13.06	47.79	74	-26.21	peak	Horizontal
2483.5	59.39	-12.78	46.61	74	-27.39	peak	Vertical
2483.5	59.24	-12.78	46.46	74	-27.54	peak	Horizontal

Note: Test method to see chapter 3.2 . When PK value is lower than the Average value limit,
average not record.


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side




802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side




802.11n-HT20: Band Edge, Left Side




802.11n-HT20: Band Edge, Right Side



802.11n-HT40: Band Edge, Left Side



802.11n-HT40: Band Edge, Right Side



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT


15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is external Antenna. It comply with the standard requirement.

9. EUT TEST PHOTO

Radiated Measurement Photos



Conducted Measurement Photos