

47 CFR PART 15 SUBPART C TEST REPORT

for

Wireless Trackball Mouse

Model No.: M-IT11MR

FCC ID: YWO-M-IT11MR

of

Applicant: ELECOM CO., LTD.

Address: Fushimimachi 4-1-1, Chuo-ku, Osaka City, Osaka Japan 541-8765

Tested and Prepared

By

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634



Report No.: W6M22509-24722-C-1

6F., No. 58, Ln. 188, Rueiguang Rd., Neihu Dist., Taipei City, Taiwan (R.O.C.)
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wtls@wtls-lab.com



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

TABLE OF CONTENTS

1	GENERAL INFORMATION	2
1.1	NOTES.....	2
1.2	TESTING LABORATORY	3
1.2.1	Location	3
1.2.2	Details of accreditation status	3
1.3	APPLICATION DETAILS	3
1.4	GENERAL INFORMATION OF TEST ITEM	4
1.5	DUTY CYCLE AND FACTOR	4
1.6	TEST STANDARDS.....	5
2	TEST CONFIGURATION	6
2.1	TEST ENVIRONMENT	6
2.2	MEASUREMENT UNCERTAINTY	6
2.3	TEST EQUIPMENT LIST	7
3	TEST RESULTS (ENCLOSURE)	8
3.1	PEAK OUTPUT POWER (TRANSMITTER)	9
3.2	SPURIOUS EMISSIONS RADIATED – TRANSMITTER OPERATING	14
3.3	EMISSIONS IN NONRESTRICTED FREQUENCY BANDS	16
3.4	MINIMUM 6 dB BANDWIDTH	19
3.5	PEAK POWER SPECTRAL DENSITY	23
3.6	POWER LINE CONDUCTED EMISSION	27

Appendix: Diagrams



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

Laboratory disclaimer-

1. The test results of this test report relate exclusively to the item tested as specified in 1.5.
2. The test report may only be reproduced or published in full.
3. Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.
4. Antenna gain is provided by applicant and laboratory issue relevant data and results.

Tester:

December 26, 2025

Kent Lin

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

December 26, 2025

Kevin Wang

Date

WTS

Name

Signature



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

1.2 Testing laboratory

1.2.1 Location

10m OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist.,
New Taipei City 207, Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No. 99, Sec. 1, Balian Rd., Xizhi Dist.,
New Taipei City 221032, Taiwan (R.O.C.)

Worldwide Testing Services (Taiwan) Co., Ltd.
6F., No. 58, Ln. 188, Ruiguang Rd., Neihu Dist.,
Taipei City 114, Taiwan (R.O.C.)
Tel: 886-2-6606-8877

1.2.2 Details of accreditation status

Accredited testing laboratory

FCC filed test laboratory Reg. No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.
Accredited no.: ./.
Street: ./.
Town: ./.
Country: ./.

1.3 Application details

Approval holder

Name: ELECOM CO., LTD.
Street: Fushimimachi 4-1-1, Chuo-ku,
Town: Osaka City, Osaka
Country: Japan 541-8765

Manufacturer: (if applicable)

1.

Name: ELECOM CO., LTD.
Street: Fushimimachi 4-1-1, Chuo-ku,
Town: Osaka City, Osaka
Country: Japan 541-8765

2.

Name: G.TECH TECHNOLOGY VIETNAM COMPANY LIMITED
Street: Factory No.1 and No.3 of Feng Xu Investment Vietnam Co.,Ltd,
Land lot L5.2, L5.3, L5.4, L5.5A Do Son Industrial Park Hai
Phong, Do Son Ward,



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

Town: Hai Phong City,
Country: Vietnam

Application details

Date of receipt of test item: November 20, 2025

Date of test: from November 21, 2025 to December 15, 2025

1.4 General information of Test item

Type of test item: Wireless Trackball Mouse

Model no.: M-IT11MR

Multi-listing model no.: M-IT10MR

Brand name: ELECOM

Power supply: Battery 1.5Vd.c. (AA x 1)

Technical data

Mode	Channel	Conducted Power (dBm)
BLE 1M	Ch00 : 2402 MHz	-0.56
	Ch19 : 2440 MHz	-0.71
	Ch39 : 2480 MHz	-0.84
2.4G	Ch00 : 2402 MHz	-0.44
	Ch19 : 2440 MHz	-0.41
	Ch39 : 2480 MHz	-0.76

Type of antenna: PCB antenna

Antenna gain: 5.2 dBi

Operation modes: Duplex

Modulation type: GFSK

Sample no.: #01


1.5 Duty cycle and factor

The duty factor is computed as $[10 \log (1 / D)]$, where D is the duty cycle.

Mode	T _{on} (ms)	T _{on} +T _{off} (ms)	Duty cycle (%)	1/T - VBW (kHz)
BLE 1M	100	100	100	0.01
2.4G	100	100	100	0.01




Registration number: W6M22509-24722-C-1
FCC ID: YWO-M-IT11MR
Duty cycle plot
BLE 1M



DUTY
Date: 26.NOV.2025 16:43:25

2.4G



DUTY
Date: 27.NOV.2025 14:11:59

1.6 Test standards

47 CFR PART 15 SUBPART C § 15.247 (2024-10)
ANSI C63.10-2020+ Cor.1-2023+C63.10a-2024



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

2 Test configuration

2.1 Test environment

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Extreme conditions parameters: ./.

2.2 Measurement uncertainty

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Emission (Power Line Conducted Emission)	Expanded Uncertainty : AMN : 0.94 dB Voltage probe : 1.21 dB Include Pulse Limiter : 1.5 dB
Estimation Result of Uncertainty of Radiated Emission (3M-966A) (Spurious Emissions radiated – Transmitter operating)	Expanded Uncertainty : 0.009-30 MHz : 1.85 dB 30-1000 MHz : 3.92 dB 1-18 GHz : 3.19 dB 18-40 GHz : 1.90 dB
Estimation Result of Uncertainty of Bandwidth Measurement (Minimum 6 dB Bandwidth)	Expanded Uncertainty : 0.37 kHz
Estimation Result of Uncertainty of Conducted Output Power Measurement (Peak Output Power (transmitter))	Expanded Uncertainty : 1.63 dB
Estimation Result of Uncertainty of Power Density Measurement (Peak Power Spectral Density)	Expanded Uncertainty : 1.63 dB
Estimation Result of Uncertainty of Band Edge Measurement (Emissions in nonrestricted frequency bands)	Expanded Uncertainty : 0.63dBc

The decision rule is: Measurement uncertainty is not included in the calculation of test results.



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

2.3 Test Equipment List

Max Output Power & 6dB Bandwidth & Bandedge & Power Density & Duty

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2025/2/14	2026/2/13
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2025/3/5	2026/3/4
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2025/2/14	2026/2/13
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2025/2/14	2026/2/13

Spurious Emission(966A)

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 153	Signal Analyzer	FSV40	101929	R&S	2025/9/10	2026/9/9
ETSTW-RE 154	EMI Test Receiver	ESR3	102829	R&S	2025/2/14	2026/4/8
ETSTW-RE 160	Amplifier Module	CHC 3	None	WTS	2025/7/11	2026/7/10
ETSTW-RE 177	TRILOG Broadband Antenna	VULB 9168&EMCI-N-6-06	01380&AT-06007	SCHWARZBECK&EMC	2025/3/10	2026/3/9
ETSTW-RE 178	Double Ridged Guide Horn Antenna	DRH18-E	210505A18ES	RFSPIN	2025/3/7	2026/3/6
ETSTW-Cable 077	SMA type cable (10m)	EMC104-SM-SM-10000	230511	EMCI	2025/7/11	2026/7/10
ETSTW-Cable 084	SMA type cable (1m)	SF104-11SMA-1000	816477/4	HONOVA	2025/7/11	2026/7/10
ETSTW-Cable 089	SMA type cable (2m)	SF104-11SMA-2000	SN 811889/4	HUBER+SUHNER	2025/7/11	2026/7/10
WTSTW-SW 002	EMI TEST SOFTWARE	EZ EMC	None	Farad	Version ETS-03A1 Version EMEC-3A1+	
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2025/7/31	2026/7/30
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2025/9/12	2026/9/11
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2025/9/12	2026/9/11
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2025/9/12	2026/9/11



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)(3)	☒	☒	☐
Spurious Emissions radiated – Transmitter operating	15.247(d), 15.205, 15.209	☒	☒	☐
Emissions in nonrestricted frequency bands	15.247(d)	☒	☒	☐
Minimum 6 dB Bandwidth	15.247(a)(2)	☒	☒	☐
Peak Power Spectral Density	15.247(e)	☒	☒	☐
Power Line Conducted Emission	15.207(a)	☐	☐	☐

The following is intentionally left blank.



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

3.1 Peak Output Power (transmitter)

3.1.1 Applicable Standard

FCC Rule: 15.247(b)(3)


For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.1.2 Test procedure

Following Subclause 11.9.1.1 of ANSI C63.10

1. Set the RBW $\geq$ DTS bandwidth , VBW $\geq$ $[3 \times \text{RBW}]$, span $\geq$ $[3 \times \text{RBW}]$.
2. Sweep time = auto couple , Detector = peak , Trace mode = max hold.
3. Allow trace to fully stabilize and determine the peak amplitude level.

3.1.3 Test Setup



3.1.4 Limits

Frequency (MHz)	Power (dBm)
902 - 928	30
2400 – 2483.5	30
5725 – 5850	30

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to point operation consider §15.247 (b)(4)



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR


3.1.5 Test Environmental Conditions

Test date: 2025/11/26-2025/11/27 Temperature: 23.3°C Humidity: 58.6% Tester: Paul

3.1.6 Test results

Band	Mode	Channel / Frequency	Power (dBm)	Limit (dBm)
2.4GHz	BLE 1M	Ch00 : 2402 MHz	-0.56	30
		Ch19 : 2440 MHz	-0.71	30
		Ch39 : 2480 MHz	-0.84	30
	2.4G	Ch00 : 2402 MHz	-0.44	30
		Ch19 : 2440 MHz	-0.41	30
		Ch39 : 2480 MHz	-0.76	30


BLE 1M




MAX OUTPUT POWER BLE 1M CH00
Date: 26.NOV.2025 16:55:10



Registration number: W6M22509-24722-C-1
FCC ID: YWO-M-IT11MR



MAX OUTPUT POWER BLE 1M CH19
Date: 26.NOV.2025 16:56:21




MAX OUTPUT POWER BLE 1M CH39
Date: 26.NOV.2025 16:57:14



Registration number: W6M22509-24722-C-1


FCC ID: YWO-M-IT11MR

2.4G



MAX OUTPUT POWER 2.4G 2402MHz

Date: 27.NOV.2025 14:17:00




MAX OUTPUT POWER 2.4G 2440MHz

Date: 27.NOV.2025 14:18:25



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR



MAX OUTPUT POWER 2.4G 2480MHz

Date: 27.NOV.2025 14:19:46



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

3.2 Spurious Emissions radiated – Transmitter operating

3.2.1 Applicable Standard

FCC Rules: 15.247 (d), 15.205, 15.209

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

3.2.2 Test procedure

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. Below 1GHz measurement the EUT is placed on turntable which is 0.8m above ground plane. And above 1GHz measurement EUT was placed on low permittivity and low tangent turn table which is 1.5m above ground plane.
2. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m height to find out the highest emissions.
3. Receiver or Spectrum analyzer configuration
 - (a)120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
 - (b)RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
 - (c)RBW=1MHz, VBW=10Hz(1/T) and Peak detector is for average measured value of radiated emission above 1GHz.


3.2.3 Limits

Frequency (MHz)	Field strength (uV/m)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

3.2.4 Test Setup



Below 1 GHz



Above 1 GHz

3.2.5 Test results (With Environmental Conditions)

Explanation: See attached diagrams in Appendix.



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

3.3 Emissions in nonrestricted frequency bands

3.3.1 Applicable Standard

FCC Rules: 15.247(d)


In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.

3.3.2 Test procedure

1. Set RBW = 100 kHz , VBW $\geq [3 \times \text{RBW}]$
2. Set Detector = peak , Sweep time = auto , Trace mode = max hold, and allow sweep to continue until the trace stabilizes
3. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

3.3.3 Test setup



3.3.4 Limits

See 3.3.1

3.3.5 Test Environmental Conditions

Test date: 2025/11/26-2025/12/12 Temperature: 22.8°C Humidity: 56.6% Tester: Paul




Registration number: W6M22509-24722-C-1


FCC ID: YWO-M-IT11MR

3.3.6 Test results

BLE 1M



BANDEDGE BLE 1M CH00
Date: 26.NOV.2025 16:37:36




BANDEDGE BLE 1M CH39
Date: 12.DEC.2025 09:16:20




Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

2.4G



BANDEDGE 2.4G 2402MHz
Date: 27.NOV.2025 14:05:49



BANDEDGE 2.4G 2480MHz
Date: 27.NOV.2025 14:07:43



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

3.4 Minimum 6 dB Bandwidth

3.4.1 Applicable Standard


FCC Rules: 15.247(a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.4.2 Test procedure

1. Set RBW = 100 kHz , Set the VBW $\geq [3 \times \text{RBW}]$.
2. Set Detector = peak , Trace mode = max hold , Sweep = auto couple and allow the trace to stabilize.
3. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.4.3 Test setup



3.4.4 Limits

Frequency Range (MHz)	Limits (kHz)
902-928	≥ 500
2400-2483.5	
5725-5850	

3.4.5 Test Environmental Conditions

Test date: 2025/11/26-2025/11/27 Temperature: 23.3°C Humidity: 58.6% Tester: Paul




Registration number: W6M22509-24722-C-1


FCC ID: YWO-M-IT11MR

3.4.6 Test results

BLE 1M



6DB BANDWIDTH BLE 1M CH00
Date: 26.NOV.2025 16:31:30




6DB BANDWIDTH BLE 1M CH10
Date: 26.NOV.2025 16:33:36




Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR



6DB BANDWIDTH BLE 1M CH39
Date: 26.NOV.2025 16:34:55



2.4G



6DB BANDWIDTH 2.4G 2402MHz
Date: 27.NOV.2025 13:57:13



Registration number: W6M22509-24722-C-1
FCC ID: YWO-M-IT11MR





Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

3.5 Peak Power Spectral Density

3.5.1 Applicable Standard


FCC Rules: 15.247(e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.5.2 Test procedure

1. Set the RBW to $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$, the VBW $\geq [3 \times \text{RBW}]$.
2. Set Detector = peak , Sweep time = auto couple , Trace mode = max hold and allow trace to fully stabilize
3. Use the peak marker function to determine the maximum amplitude level within the RBW.

3.5.3 Test setup



3.5.4 Limits

Frequency Range (MHz)	Limits (dBm/3KHz)
902-928	8
2400-2483.5	
5725-5850	

3.5.5 Test Environmental Conditions

Test date: 2025/11/26-2025/11/27 Temperature: 23.3°C Humidity: 58.6% Tester: Paul




Registration number: W6M22509-24722-C-1


FCC ID: YWO-M-IT11MR

3.5.6 Test results

BLE 1M




POWER DENSITY BLE 1M CH00
Date: 26.NOV.2025 17:02:45



POWER DENSITY BLE 1M CH19
Date: 26.NOV.2025 17:01:41




Registration number: W6M22509-24722-C-1
FCC ID: YWO-M-IT11MR



POWER DENSITY BLE 1M CH39
Date: 26.NOV.2025 17:04:27


2.4G




POWER DENSITY 2.4G 2402MHz
Date: 27.NOV.2025 14:30:21



Registration number: W6M22509-24722-C-1
FCC ID: YWO-M-IT11MR



POWER DENSITY 2.4G 2440MHz
Date: 27.NOV.2025 14:28:55



POWER DENSITY 2.4G 2480MHz
Date: 27.NOV.2025 14:32:19

Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

3.6 Power Line Conducted Emission

3.6.1 Applicable Standard


FCC Rules:15.207(a)

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

3.6.2 Test procedure

1. EUT is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. Connect EUT to a 50 μ H/50 ohms line impedance stabilization network (LISN). AC input is 120V/60Hz
3. This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

3.6.3 Test setup



3.6.4 Limits

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

3.6.5 Test results (With Environmental Conditins)

Explanation: This test is not required because the EUT is powered by battery.



Registration number: W6M22509-24722-C-1

FCC ID: YWO-M-IT11MR

Appendix

Measurement diagrams

Radiated Emission



Radiated Emission Measurement

Operator: Hung

File :[主測]1_BLE(1M)_TX


Data :#1

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 05:24:52

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Horizontal

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	55.2200	32.99	peak	-12.74	20.25	40.00	100	100	-19.75	
	149.3100	33.38	peak	-12.47	20.91	43.50	100	206	-22.59	
	280.2600	34.12	peak	-12.52	21.60	46.00	100	223	-24.40	
	384.0500	33.03	peak	-9.86	23.17	46.00	100	123	-22.83	
	458.7400	33.81	peak	-7.94	25.87	46.00	100	6	-20.13	
*	586.7800	33.72	peak	-5.31	28.41	46.00	100	251	-17.59	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File :[主測]1_BLE(1M)_TX

Data :#2


Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 05:25:37

Humidity:38.2 %

80.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	59.1000	33.51	peak	-12.76	20.75	40.00	100	293	-19.25	
	155.1300	33.12	peak	-12.24	20.88	43.50	100	8	-22.62	
	350.1000	33.56	peak	-10.98	22.58	46.00	100	353	-23.42	
	484.9300	33.97	peak	-7.70	26.27	46.00	100	97	-19.73	
	599.3900	33.37	peak	-5.00	28.37	46.00	100	321	-17.63	
*	712.8800	33.33	peak	-2.94	30.39	46.00	100	187	-15.61	



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3

Data :#1


Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:00:59

Humidity:38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3


Data :#6

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:03:41

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #2


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:01:41

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4804.000	48.44	peak	5.81	54.25	74.00	150	213	-19.75	
*	4804.000	40.16	AVG	5.81	45.97	54.00	150	213	-8.03	
	7206.000	34.04	peak	12.70	46.74	74.00	150	30	-27.26	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #7


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:04:24

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4804.000	43.34	peak	5.81	49.15	74.00	150	176	-24.85	
	7206.000	34.24	peak	12.70	46.94	74.00	150	1	-27.06	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #3


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:02:30

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9608.000	33.56	peak	14.40	47.96	74.00	150	282	-26.04	
*	12010.000	33.99	peak	17.79	51.78	74.00	150	177	-22.22	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #8


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:05:05

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9608.000	33.35	peak	14.40	47.75	74.00	150	4	-26.25	
*	12010.000	33.46	peak	17.79	51.25	74.00	150	257	-22.75	

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3

Data :#4


Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:02:46

Humidity:38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File :3


Data :#9

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:05:22

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



Radiated Emission Measurement

Operator: Hung

File :3


Data :#5

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:02:56

Humidity:38.2 %



Site : 966A Chamber
Condition : FCC_part 15 RE-Class C_Above 1GHz_PK
EUT : W6M22509-24722
M/N:
Test Mode : TX 2402MHz
Note :

Polarization: *Horizontal*
Power : 1.5 Vd.c.
Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3


Data :#10

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:05:32

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3


Data : #1

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:11:43

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3


Data :#6

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:14:26

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #2


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:12:26

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4880.000	44.13	peak	6.05	50.18	74.00	150	155	-23.82	
	7320.000	34.73	peak	13.38	48.11	74.00	150	291	-25.89	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #7


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:15:10

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4880.000	41.17	peak	6.05	47.22	74.00	150	173	-26.78	
	7320.000	33.32	peak	13.38	46.70	74.00	150	71	-27.30	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #3

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:13:14

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9760.000	32.42	peak	14.73	47.15	74.00	150	63	-26.85	
*	12200.000	33.02	peak	16.39	49.41	74.00	150	193	-24.59	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #8


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:15:51

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9760.000	32.59	peak	14.73	47.32	74.00	150	149	-26.68	
*	12200.000	33.15	peak	16.39	49.54	74.00	150	172	-24.46	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File :3


Data :#4

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:13:31

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: *Horizontal*

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #9


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:16:07

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3


Data :#5

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:13:41

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3

Data :#10


Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:16:17

Humidity:38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3


Data :#1

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:19:07

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: *Horizontal*

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3


Data : #6

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:21:49

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #2


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:19:49

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4960.000	44.14	peak	6.41	50.55	74.00	150	201	-23.45	
	7440.000	33.14	peak	13.18	46.32	74.00	150	268	-27.68	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #7


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:22:32

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4960.000	40.74	peak	6.41	47.15	74.00	150	105	-26.85	
	7440.000	33.31	peak	13.18	46.49	74.00	150	265	-27.51	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #3


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:20:38

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9920.000	32.53	peak	14.48	47.01	74.00	150	40	-26.99	
*	12400.000	33.40	peak	17.39	50.79	74.00	150	1	-23.21	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3


Data : #8

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:23:13

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9920.000	32.53	peak	14.48	47.01	74.00	150	143	-26.99	
*	12400.000	33.86	peak	17.39	51.25	74.00	150	126	-22.75	

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3


Data :#4

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:20:54

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: *Horizontal*

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3


Data :#9

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:23:30

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3


Data :#5

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:21:04

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: *Horizontal*

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3


Data :#10

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:23:40

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :


Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Horizontal

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	56.1900	33.07	peak	-12.74	20.33	40.00	100	0	-19.67	
	145.4300	33.13	peak	-12.63	20.50	43.50	100	128	-23.00	
	274.4400	33.31	peak	-12.81	20.50	46.00	100	28	-25.50	
	360.7700	32.81	peak	-10.74	22.07	46.00	100	339	-23.93	
	436.4300	33.15	peak	-8.41	24.74	46.00	100	339	-21.26	
*	534.4000	33.19	peak	-6.54	26.65	46.00	100	51	-19.35	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File :02


Data :#2

Date: 2025/11/28

Temperature: 24.8 °C

Time: 下午 03:24:48

Humidity: 43.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	49.4000	33.16	peak	-12.76	20.40	40.00	100	40	-19.60	
	153.1900	32.75	peak	-12.32	20.43	43.50	100	102	-23.07	
	321.9700	32.83	peak	-11.49	21.34	46.00	100	1	-24.66	
	440.3100	33.89	peak	-8.27	25.62	46.00	100	359	-20.38	
	537.3100	33.52	peak	-6.55	26.97	46.00	100	236	-19.03	
*	619.7600	33.28	peak	-4.48	28.80	46.00	100	191	-17.20	



Radiated Emission Measurement

Operator: Hung

File :2402 Bandedge


Data :#1

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:39:38

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: *Horizontal*

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2353.800	60.03	peak	-3.38	56.65	74.00	150	58	-17.35	
*	2353.800	50.88	AVG	-3.38	47.50	54.00	150	58	-6.50	
	2390.000	46.38	peak	-3.41	42.97	74.00	150	58	-31.03	
	2390.000	34.29	AVG	-3.41	30.88	54.00	150	58	-23.12	



Radiated Emission Measurement

Operator: Hung

File : 2402 Bandedge

Data : #2


Date: 2025/11/27

Temperature: 23.5 °C

120.0 dBuV/m

Time: 下午 02:41:41

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2390.000	45.69	peak	-3.41	42.28	74.00	150	355	-31.72	
*	2390.000	34.36	AVG	-3.41	30.95	54.00	150	355	-23.05	



Radiated Emission Measurement

Operator: Hung

File :2480 Bandedge


Data :#1

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:29:22

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2483.500	45.34	peak	-3.62	41.72	74.00	150	59	-32.28	
	2483.500	34.99	AVG	-3.62	31.37	54.00	150	59	-22.63	
	2528.400	58.42	peak	-3.52	54.90	74.00	150	59	-19.10	
*	2528.400	47.41	AVG	-3.52	43.89	54.00	150	59	-10.11	



Radiated Emission Measurement

Operator: Hung

File : 2480 Bandedge


Data : #2

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:35:08

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2483.500	44.60	peak	-3.62	40.98	74.00	150	355	-33.02	
*	2483.500	34.71	AVG	-3.62	31.09	54.00	150	355	-22.91	



Radiated Emission Measurement

Operator: Hung

File :[主測]1_2


Data :#1

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 05:22:29

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Horizontal

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	59.1000	32.63	peak	-12.76	19.87	40.00	100	152	-20.13	
	165.8000	33.42	peak	-12.58	20.84	43.50	100	358	-22.66	
	266.6800	33.55	peak	-13.20	20.35	46.00	100	169	-25.65	
	353.9800	33.62	peak	-10.90	22.72	46.00	100	331	-23.28	
	425.7600	33.79	peak	-8.80	24.99	46.00	100	124	-21.01	
*	502.3900	34.47	peak	-7.33	27.14	46.00	100	141	-18.86	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File :[主測]1_2

Data :#2


Date: 2025/11/27

Temperature:23.5 °C

80.0 dBuV/m

Time: 下午 05:23:14

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	44.5500	33.81	peak	-13.27	20.54	40.00	100	220	-19.46	
	156.1000	32.77	peak	-12.20	20.57	43.50	100	203	-22.93	
	349.1300	34.80	peak	-11.00	23.80	46.00	100	298	-22.20	
	452.9200	34.05	peak	-8.05	26.00	46.00	100	359	-20.00	
	492.6900	35.19	peak	-7.56	27.63	46.00	100	148	-18.37	
*	597.4500	33.93	peak	-5.04	28.89	46.00	100	1	-17.11	



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3


Data : #1

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:55:53

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File :3


Data :#6

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:58:35

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3


Data : #2

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:56:35

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4804.000	42.63	peak	5.81	48.44	74.00	150	217	-25.56	
	7206.000	34.13	peak	12.70	46.83	74.00	150	13	-27.17	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #7


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:59:19

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4800.000	42.84	peak	5.80	48.64	74.00	150	205	-25.36	
	7206.000	34.06	peak	12.70	46.76	74.00	150	131	-27.24	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #3

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:57:24

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9608.000	33.77	peak	14.40	48.17	74.00	150	80	-25.83	
*	12010.000	33.55	peak	17.79	51.34	74.00	150	341	-22.66	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #8

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:00:00

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9608.000	33.84	peak	14.40	48.24	74.00	150	189	-25.76	
*	12010.000	33.20	peak	17.79	50.99	74.00	150	359	-23.01	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File :3


Data :#4

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:57:41

Humidity:38.2 %



Site : 966A Chamber
Condition : FCC_part 15 RE-Class C_Above 1GHz_PK
EUT : W6M22509-24722
M/N:
Test Mode : TX 2402MHz
Note :

Polarization: **Horizontal**
Power : 1.5 Vd.c.
Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3

Data :#9


Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 03:00:16

Humidity:38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File :3


Data :#5

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 02:57:51

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



Radiated Emission Measurement

Operator: Hung

File :3


Data :#10

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 03:00:26

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3


Data : #1

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:03:37

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: *Horizontal*

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3


Data :#6

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 03:06:20

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #2


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:04:20

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4880.000	41.90	peak	6.05	47.95	74.00	150	217	-26.05	
	7320.000	33.60	peak	13.38	46.98	74.00	150	86	-27.02	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #7


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:07:03

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4880.000	42.24	peak	6.05	48.29	74.00	150	119	-25.71	
	7320.000	33.27	peak	13.38	46.65	74.00	150	261	-27.35	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #3

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:05:08

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9760.000	32.68	peak	14.73	47.41	74.00	150	12	-26.59	
*	12200.000	33.34	peak	16.39	49.73	74.00	150	281	-24.27	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #8


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:07:44

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9760.000	32.47	peak	14.73	47.20	74.00	150	7	-26.80	
*	12200.000	33.03	peak	16.39	49.42	74.00	150	330	-24.58	

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3

Data :#4


Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 03:05:25

Humidity:38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File :3


Data :#9

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 03:08:00

Humidity:38.2 %



Site : 966A Chamber
Condition : FCC_part 15 RE-Class C_Above 1GHz_PK
EUT : W6M22509-24722
M/N:
Test Mode : TX 2440MHz
Note :

Polarization: Vertical
Power : 1.5 Vd.c.
Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3


Data :#5

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 03:05:35

Humidity:38.2 %



Site : 966A Chamber
Condition : FCC_part 15 RE-Class C_Above 1GHz_PK
EUT : W6M22509-24722
M/N:
Test Mode : TX 2440MHz
Note :

Polarization: *Horizontal*
Power : 1.5 Vd.c.
Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File :3


Data :#10

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 03:08:10

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3

Data :#1


Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 03:10:59

Humidity:38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: *Horizontal*

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3


Data : #6

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:13:42

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #2


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:11:42

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4960.000	44.03	peak	6.41	50.44	74.00	150	206	-23.56	
	7440.000	32.43	peak	13.18	45.61	74.00	150	126	-28.39	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #7


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:14:25

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: Vertical

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4960.000	41.92	peak	6.41	48.33	74.00	150	148	-25.67	
	7440.000	32.76	peak	13.18	45.94	74.00	150	296	-28.06	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3

Data : #3


Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:12:31

Humidity: 38.2 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9920.000	32.81	peak	14.48	47.29	74.00	150	182	-26.71	
*	12400.000	34.30	peak	17.39	51.69	74.00	150	285	-22.31	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3


Data : #8

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:15:06

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9920.000	32.52	peak	14.48	47.00	74.00	150	176	-27.00	
*	12400.000	33.59	peak	17.39	50.98	74.00	150	49	-23.02	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File :3


Data :#4

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 03:12:47

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File :3


Data :#9

Date: 2025/11/27

Temperature:23.5 °C

Time: 下午 03:15:23

Humidity:38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3


Data : #5

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:12:57

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 3


Data : #10

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:15:33

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :


Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Horizontal

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	48.4300	32.82	peak	-12.86	19.96	40.00	100	28	-20.04	
	156.1000	32.45	peak	-12.20	20.25	43.50	100	150	-23.25	
	310.3300	33.41	peak	-11.70	21.71	46.00	100	359	-24.29	
	408.3000	33.38	peak	-9.39	23.99	46.00	100	195	-22.01	
	495.6000	33.62	peak	-7.51	26.11	46.00	100	162	-19.89	
*	586.7800	33.73	peak	-5.31	28.42	46.00	100	329	-17.58	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File :05[系列]1_2

Data :#2


Date: 2025/11/28

Temperature:24.8 °C

80.0 dBuV/m

Time: 下午 03:28:34

Humidity:43.2 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz


Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	56.1900	33.46	peak	-12.74	20.72	40.00	100	142	-19.28	
	170.6500	33.30	peak	-13.02	20.28	43.50	100	4	-23.22	
	313.2400	33.58	peak	-11.64	21.94	46.00	100	214	-24.06	
	409.2700	33.20	peak	-9.36	23.84	46.00	100	125	-22.16	
	520.8200	33.12	peak	-6.52	26.60	46.00	100	358	-19.40	
*	602.3000	33.57	peak	-4.92	28.65	46.00	100	8	-17.35	



Site : 966A Chamber
Condition : FCC 15.247 PK (Bandedge)
EUT : W6M22509-24722
M/N:
Test Mode : TX 2402MHz
Note :

Polarization: *Horizontal*
Power : 1.5 Vd.c.
Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2354.700	58.79	peak	-3.38	55.41	74.00	150	50	-18.59	
*	2354.700	46.76	AVG	-3.38	43.38	54.00	150	50	-10.62	
	2390.000	47.05	peak	-3.41	43.64	74.00	150	50	-30.36	
	2390.000	34.60	AVG	-3.41	31.19	54.00	150	50	-22.81	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File : 2402 Bandedge


Data : #2

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 02:52:03

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22509-24722

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2390.000	43.80	peak	-3.41	40.39	74.00	150	353	-33.61	
*	2390.000	34.23	AVG	-3.41	30.82	54.00	150	353	-23.18	



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Hung

File : 2480 Bandedge


Data : #1

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:21:14

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Horizontal**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2483.500	46.77	peak	-3.62	43.15	74.00	150	57	-30.85	
	2483.500	36.95	AVG	-3.62	33.33	54.00	150	57	-20.67	
	2528.400	57.84	peak	-3.52	54.32	74.00	150	57	-19.68	
*	2528.400	45.35	AVG	-3.52	41.83	54.00	150	57	-12.17	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Hung

File : 2480 Bandedge


Data : #2

Date: 2025/11/27

Temperature: 23.5 °C

Time: 下午 03:24:52

Humidity: 38.2 %



Site : 966A Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22509-24722

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Vertical**

Power : 1.5 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2483.500	46.78	peak	-3.62	43.16	74.00	150	359	-30.84	
*	2483.500	35.65	AVG	-3.62	32.03	54.00	150	359	-21.97	