

TEST REPORT

Product Name: Compact Hotel Phone
Trade Mark: GRANDSTREAM
Model No.: GHP611W
Add. Model No.: GHP610W
HVIN: GHP611WM1
Add. HVIN: GHP610WM1
Report Number: 24121715264RFC-2
Test Standards: FCC 47 CFR Part 15 Subpart E
RSS-247 Issue 3
RSS-Gen Issue 5
FCC ID: YZZGHP61XWM1
IC: 11964A-GHP61XWM1
Test Result: PASS
Date of Issue: March 19, 2025

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6th, Baoneng Science and Technology Park,
Longhua Street, Longhua District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:

David Chen

David Chen
Senior Project Engineer

Reviewed by:

Kevin Liang

Kevin Liang
Assistant Manager

Approved by:



Date:

March 19, 2025

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Version

Version No.	Date	Description
V1.0	March 19, 2025	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	5
1.4 OTHER INFORMATION	7
1.5 DESCRIPTION OF SUPPORT UNITS	7
1.6 TEST LOCATION	7
1.7 TEST FACILITY	7
1.8 DEVIATION FROM STANDARDS	8
1.9 ABNORMALITIES FROM STANDARD CONDITIONS	8
1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
1.11 MEASUREMENT UNCERTAINTY	8
2. TEST SUMMARY	9
3. EQUIPMENT LIST	10
4. TEST CONFIGURATION	11
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	11
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	11
4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE	11
4.2 TEST CHANNELS	12
4.3 EUT TEST STATUS	12
4.4 PRE-SCAN	13
4.5 TEST SETUP	14
4.5.1 FOR RADIATED EMISSIONS TEST SETUP	14
4.5.2 FOR CONDUCTED EMISSIONS TEST SETUP	15
4.5.3 FOR CONDUCTED RF TEST SETUP	16
4.6 SYSTEM TEST CONFIGURATION	17
4.7 DUTY CYCLE	18
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION	22
5.1 REFERENCE DOCUMENTS FOR TESTING	22
5.2 ANTENNA REQUIREMENT	22
5.3 26 dB BANDWIDTH & OCCUPIED BANDWIDTH	23
5.4 6 dB BANDWIDTH & OCCUPIED BANDWIDTH	24
5.5 MAXIMUM CONDUCTED OUTPUT POWER OR E.I.R.P	25
5.6 PEAK POWER SPECTRAL DENSITY	31
5.7 RADIATED EMISSIONS AND BAND EDGE MEASUREMENT	34
5.8 DYNAMIC FREQUENCY SELECTION	77
5.9 AC POWER LINE CONDUCTED EMISSION	81
APPENDIX A RF TEST DATA	84
A1. 99% BANDWIDTH	84
A2. 26dB BANDWIDTH	134
A3. PEAK POWER SPECTRAL DENSITY	172
A4. 6dB BANDWIDTH	225
A5. DYNAMIC FREQUENCY SELECTION	242
APPENDIX 1 PHOTOS OF TEST SETUP	249
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	249

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	Compact Hotel Phone		
Model No.:	GHP611W		
Add. Model No.:	GHP610W		
HVIN:	GHP611WM1		
Add. HVIN:	GHP610WM1		
Trade Mark:	GRANDSTREAM		
DUT Stage:	Identical Prototype		
EUT Supports Function: (Provided by the customer)	2.4 GHz ISM Band:	IEEE 802.11b/g/n/ax	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac/ax
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac/ax
		5 470 MHz to 5 730MHz	IEEE 802.11a/n/ac/ax
		5 730 MHz to 5 850 MHz	IEEE 802.11a/n/ac/ax
Sample Received Date:	December 17, 2024		
Sample Tested Date:	December 17, 2024 to March 7, 2025		
Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model GHP611W, but the circuit and the electronic construction do not change, declared by the manufacturer.			

Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

1.2.2 Description of Accessories

Adapter (1)	
Model No.:	DCT06W120050US-D0
Input:	100-240V~50/60Hz 200 mA
Output:	12.0V == 0.5A
DC Cable	1.8 Meter, Unshielded without ferrite

Adapter (2)	
Model No.:	DCT06W120050US-D1
Input:	100-240V~50/60Hz 200 mA
Output:	12.0V == 0.5A
DC Cable	1.8 Meter, Unshielded without ferrite

Adapter (3)	
Model No.:	GLH006G-1200050CU
Input:	100-240V~50/60Hz 0.3A

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Output:	12.0V == 0.5A 6.0W
DC Cable	1.8 Meter, Unshielded without ferrite

Adapter (4)	
Model No.:	TS-A006-120050AB
Input:	100-240V~50/60Hz 0.2A
Output:	12.0V == 0.5A 6.0W
DC Cable	1.8 Meter, Unshielded without ferrite

Cable	
Connector:	Phone Cord
Cable Type:	Unshielded without ferrite
Length:	2.5 Meter

Others	
Charging base	

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Bands:	5150 MHz to 5250 MHz (U-NII-1)
	5250 MHz to 5350 MHz (U-NII-2A)
	5470 MHz to 5730 MHz (U-NII-2C) ^{Note1}
	5730 MHz to 5850 MHz (U-NII-3)
Frequency Ranges:	5180 MHz to 5240 MHz
	5260 MHz to 5320 MHz
	5500 MHz to 5720 MHz
	5745 MHz to 5825 MHz
Support Standards:	IEEE 802.11a/n/ac/ax
TPC Function:	Not Support
DFS Operational mode:	Slave without radar Interference detection function
Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11ax: OFDM /OFDMA ^{Note2} (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20: 20 MHz
	IEEE 802.11n-HT40/ac-VHT40/ax-HE40: 40 MHz
Data Rate:	IEEE 802.11a: Up to 54 Mbps
	IEEE 802.11n-HT20: Up to MCS7
	IEEE 802.11n-HT40: Up to MCS7
	IEEE 802.11ac-VHT20: Up to MCS8
	IEEE 802.11ac-VHT40: Up to MCS9
	IEEE 802.11ax-HE20/HE40: Up to MCS11
Number of Channels:	5150 MHz to 5250 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40
	5250 MHz to 5350 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

	2 for IEEE 802.11n-HT40)/ac-VHT40/ax-HE40				
	5470 MHz to 5725 MHz: 12 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 6 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40				
	5725 MHz to 5850 MHz: 5 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40				
Antenna Type:	Dipole Antenna				
Antenna Gain: (Provided by the customer)	5150 MHz to 5250 MHz: 3.5 dBi				
	5250 MHz to 5350 MHz: 3.5 dBi				
	5470 MHz to 5725 MHz: 3.5 dBi				
	5725 MHz to 5850 MHz: 3.5 dBi				
Maximum conducted output power (dBm):		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11a:	16.88	17.50	16.97	15.94
	IEEE 802.11n-HT20:	16.38	17.25	16.77	15.53
	IEEE 802.11n-HT40:	16.58	17.08	17.20	15.49
	IEEE 802.11ac-VHT20	16.91	17.30	16.75	15.39
	IEEE 802.11ac-VHT40	16.41	17.08	17.20	15.54
	IEEE 802.11ax-HE20	16.57	17.40	16.90	15.87
	IEEE 802.11ax-HE40	16.50	17.37	17.20	15.36
Maximum EIRP (dBm):		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11a:	20.38	21.00	20.47	19.44
	IEEE 802.11n-HT20:	19.88	20.75	20.27	19.03
	IEEE 802.11n-HT40:	20.08	20.58	20.70	18.99
	IEEE 802.11ac-VHT20	20.41	20.80	20.25	18.89
	IEEE 802.11ac-VHT40	19.91	20.58	20.70	19.04
	IEEE 802.11ax-HE20	20.07	20.90	20.40	19.37
	IEEE 802.11ax-HE40	20.00	20.87	20.70	18.86
Normal Test Voltage:	12Vdc				
Note: 1. The device (subject to RSS-247) shall not be capable of transmitting within the band 5600-5650 MHz 2. For 802.11ax modes, the device not support partial RU mode					

1.4 OTHER INFORMATION

Operation Frequency Each of Channel				
	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
IEEE 802.11a, IEEE 802.11n-HT20, IEEE 802.11ac-VHT20 IEEE 802.11ax-HE20	$f = 5000 + 5k, k = 32 + 4n$			$f = 5000 + 5k,$ $k = 145 + 4n$
	$n = 1, \dots, 4$	$n = 5, \dots, 8$	$n = 17, \dots, 27$	$n = 1, \dots, 5$
IEEE 802.11n-HT40, IEEE 802.11ac-VHT40 IEEE 802.11ax-HE40	$f = 5000 + 5k, k = 30 + 8n$			$f = 5000 + 5k,$ $k = 143 + 8n$
	$n = 1, 2$	$n = 1, \dots, 5$	$n = 9, \dots, 13$	$n = 1, 2$
Note: f is the operating frequency (MHz); k is the operating channel.				

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	FCC ID	Supplied by
Notebook	DELL	Latitude 3400	16238087894	N/A	Notebook
Mouse	DELL	MS111	CN-011D3V-738	N/A	UnionTrust
Wireless Home Router	SAGEMCOM	FAST5280	253703944	VW3FAST5280	UnionTrust
Key-Press Attenuator	Huaxin	KT2.5-90/1S-2S	UTTL-EN023	N/A	UnionTrust
4 Way Divider	WOKEN	0120A040560002D	UTTL-EN028	N/A	UnionTrust

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.1Meter	UnionTrust

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.9 dB
5	Radiated emission 1GHz-18GHz	± 4.8 dB
6	Radiated emission 18GHz-26GHz	± 5.1 dB
7	Radiated emission 26GHz-40GHz	± 5.1 dB
8	Conducted spurious emissions	± 2.7 dB
9	RF Power, Conducted	± 0.68 dB
10	Occupied Bandwidth	± 1.86 %
11	Radio Frequency	5.6 GHz: ± 6.4 × 10 ⁻⁸
12	Transmission Time	± 0.19 %

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart E Test Cases			
Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203 FCC 47 CFR Part 15 Subpart E Section 15.407(a)(1) (2) RSS-Gen Issue 5, Section 6.8	N/A	PASS
26 dB emission bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(2)(5) RSS-247 Issue 3 Section 6.2.1.2	KDB 789033 D02 v02r01 Section C.1	PASS
6 dB bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (e) RSS-247 Issue 3 Section 6.2.4.1	KDB 789033 D02 v02r01 Section C.2	PASS
Occupied Bandwidth	RSS-Gen Issue 5, Section 6.7	RSS-Gen Issue 5, section 6.7	PASS
Maximum conducted output power	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3) RSS-247 Issue 3 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1	KDB 789033 D02 v02r01 Section E.3.a (Method PM)	PASS
Peak Power Spectral Density	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3) RSS-247 Issue 3 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1	KDB 789033 D02 v02r01 Section F	PASS
Radiated Emissions and Band Edge Measurement	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(1)(2)(3)(4)(6) FCC 47 CFR Part 15 Subpart C Section 15.209/205 RSS-247 Issue 3 Section 6.2.1.2/6.2.2.2/6.2.3.2/6.2.4.2	KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6	PASS
Dynamic Frequency Selection	FCC 47 CFR Part 15 Subpart E Section 15.407 (h) RSS-247 Issue 3 Section 6.3	KDB 905462 D03 Client Without DFS New Rules v01r02	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(6) FCC 47 CFR Part 15 Subpart C Section 15.207 RSS-Gen Issue 5, Section 8.8	ANSI C63.10-2013, Section 6.2.	PASS
Note: 1) N/A: In this whole report not applicable.			
Disclaimer and Explanations: The declared of product specification and data (e.g. antenna gain, RF specification, etc) for EUT presented in the report are provided by the customer, and the customer takes all the responsibilities for the accuracy of product specification.			

For Dynamic Frequency Selection

Test Case	Result
Channel Availability Check Time	N/A ¹
U-NII Detection Bandwidth	N/A ¹
Channel Closing Transmission Time	PASS
Channel Move Time	PASS
DFS Detection Threshold	N/A ¹
Non- Occupancy Period	N/A ¹
Note: 1) The EUT is slave, NA In this whole report not applicable.	

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	3m SAC	ETS-LINDGREN	3m	Euroshiedpn-CT001270-1317	11-Nov-2023	10-Nov-2026
☒	Receiver	R&S	ESIB26	100114	25-Oct-2024	24-Oct-2025
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	29-Oct-2024	28-Oct-2025
☒	Loop Antenna	ETS-LINDGREN	6502	00202525	28-Oct-2024	27-Oct-2025
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	29-Oct-2024	28-Oct-2025
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	29-Oct-2024	28-Oct-2025
☒	Preamplifier	HP	8447F	2805A02960	25-Oct-2024	24-Oct-2025
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201541	01-Apr-2024	31-Mar-2025
☒	Pre-amplifier	ETS-Lindgren	00118385	00201874	01-Apr-2024	31-Mar-2025
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	28-Oct-2024	27-Oct-2025
☒	Pre-amplifier	ETS-Lindgren	00118384	00202652	28-Oct-2024	27-Oct-2025
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Band Rejection Filter (5150MHz~5880MHz)	Micro-Tronics	BRM50716	G186	25-Oct-2024	24-Oct-2025
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	Receiver	R&S	ESCI3	1166.5950.03	25-Oct-2024	24-Oct-2025
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	25-Oct-2024	24-Oct-2025
☒	LISN	R&S	EVN216	3560.6550.12	26-Sep-2024	25-Sep-2025
☐	LISN	ETS-Lindgren	3816/2SH	00201088	25-Oct-2024	24-Oct-2025
☒	Test Software	EZ-EMC	EZ-CON	Software Version: EMC-CON 3A1.1		

Conducted RF test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	29-Mar-2024	28-Mar-2025
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	25-Oct-2024	24-Oct-2025
☒	MXG X-Series RF Vector Signal Generator	KEYSIGHT	N5182B	MY51350267	25-Oct-2024	24-Oct-2025

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NT/NV	+15 to +35	12	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test Sample

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
26 dB emission bandwidth	24.5	51.2	100.2	S202412174876-ZJA02/4	Allen Zhou
6 dB bandwidth					
Occupied Bandwidth					
Maximum conducted output power					
Peak Power Spectral Density					
Dynamic Frequency Selection	21.3	41.5	100.7	S202412174876-ZJA03/4	Jackson Wu
Radiated Emissions and Band Edge Measurement					
AC Power Line Conducted Emission	21.7	37.7	100.5	S202412174876-ZJA01/4	Linson Xie

4.2 TEST CHANNELS

Mode	Tx/Rx Frequency	Test RF Channel Lists			
		Lowest(L)	Middle(M)	Highest(H)	Straddle band
IEEE 802.11a IEEE 802.11n-HT20 IEEE 802.11ac-VHT20 IEEE 802.11ax-HE20	5150 MHz to 5250 MHz	Channel 36	Channel 44	Channel 48	--
		5180 MHz	5220 MHz	5240 MHz	--
	5250 MHz to 5350 MHz	Channel 52	Channel 60	Channel 64	--
		5260 MHz	5300 MHz	5320 MHz	--
	5470 MHz to 5725 MHz	Channel 100	Channel 116	Channel 140	Channel 144
		5500 MHz	5580 MHz	5700 MHz	5720 MHz
	5725 MHz to 5850 MHz	Channel 149	Channel 157	Channel 165	--
		5745 MHz	5785 MHz	5825 MHz	--
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40 IEEE 802.11ax-HE40	5150 MHz to 5250 MHz	Channel 38	--	Channel 46	--
		5190 MHz	--	5230 MHz	--
	5250 MHz to 5350 MHz	Channel 54	--	Channel 62	--
		5270 MHz	--	5310 MHz	--
	5470 MHz to 5725 MHz	Channel 102	Channel 110	Channel 134	Channel 142
		5510 MHz	5550 MHz	5670 MHz	5710 MHz
	5725 MHz to 5850 MHz	Channel 151	--	Channel 159	--
		5755 MHz	--	5795 MHz	--

4.3 EUT TEST STATUS

Mode	Tx/Rx Function	Description
IEEE 802.11a/n/ac/ax	1Tx/1Rx	1. Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

Power Setting				
	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
IEEE 802.11a	16	Default	Default	Default
IEEE 802.11n-HT20	16	Default	Default	Default
IEEE 802.11n-HT40	16	Default	Default	Default
IEEE 802.11ac-VHT20	16	Default	Default	Default
IEEE 802.11ac-VHT40	16	Default	Default	Default
IEEE 802.11ax-HE20	16	Default	Default	Default
IEEE 802.11ax-HE40	16	Default	Default	Default

Test Software
Test software name: Command



4.4 PRE-SCAN


Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate. Following data rate was (were) selected for the final test as listed below

Mode	Worst-case data rates
IEEE 802.11a	6 Mbps
IEEE 802.11n-HT20	MCS0
IEEE 802.11n-HT40	MCS0
IEEE 802.11ac-VHT20	MCS0
IEEE 802.11ac-VHT40	MCS0
IEEE 802.11ax-HE20	MCS0
IEEE 802.11ax-HE40	MCS0


4.5 TEST SETUP

4.5.1 For Radiated Emissions test setup






4.5.2 For Conducted Emissions test setup



4.5.3 For Conducted RF test setup



4.6 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in (see table below) orientation.

Frequency	Mode	Antenna Port	Worst-case axis positioning
Above 1GHz	1TX	Chain 0	Z axis

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.7 DUTY CYCLE

Test Procedure: ANSI C63.10-2013 Clause 12.2.


Test Results

Mode	Data Rates	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/T Minimum VBW (kHz)
IEEE 802.11a	6 Mbps	2.00	2.24	0.89	89.29	0.49	0.50
IEEE 802.11n-HT20	MCS 0	5.12	5.28	0.97	96.97	0.13	0.20
IEEE 802.11n-HT40	MCS 0	4.88	5.12	0.95	95.31	0.21	0.20
IEEE 802.11ac-VHT20	MCS 0	5.08	5.28	0.96	96.21	0.17	0.20
IEEE 802.11ac-VHT40	MCS 0	4.88	5.12	0.95	95.31	0.21	0.20
IEEE 802.11ax-HE20	MCS 0	3.88	4.12	0.94	94.17	0.26	0.26
IEEE 802.11ax-HE40	MCS 0	3.84	4.08	0.94	94.12	0.26	0.26

Remark:

- 1) Duty cycle= On Time/ Period;
- 2) Duty Cycle factor = $10 * \log(1/ \text{Duty cycle})$;
- 3) Average factor = $20 \log_{10} \text{Duty Cycle}$.

The test plots as follows



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888



Fax: +86-755-28230886



E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1







5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	RSS-247 Issue 3	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
4	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
5	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
6	KDB 789033 D02 General UNII Test Procedures New Rules v02r01	Guidelines for compliance testing of unlicensed national information infrastructure (U-NII) device part 15, subpart E
7	KDB 905462 D06 802.11 Channel Plans New Rules v02	Operation in U-NII bands -802.11 channel PLAN(\$15.407)
8	KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02	Compliance measurement procedures for Unlicensed –National Information Infrastructure devices operates in the frequency bands 5250 MHz to 5350 MHz and 5470 MHz to 5725 MHz bands incorporating dynamic frequency selection
9	KDB 905462 D03 Client Without DFS New Rules v01r02	U-NII client devices without radar detection capability

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.407(a)(1) (2) requirement: The conducted output power limit specified in paragraph (a) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (a) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power and the peak power spectral density shall be reduced by the by the amount in dB that the directional gain of the antenna exceeds 6 dBi. RSS-Gen Issue 5, Section 6.8 requirement: According to RSS-Gen Issue 5, Section 6.8, a transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns. EUT Antenna: Antenna in the interior of the equipment and no consideration of replacement. The gain of the antenna is 3.5 dBi.

5.326 DB BANDWIDTH & OCCUPIED BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(2)(5)
RSS-247 Issue 3 Section 6.2.1.2
Test Method: KDB 789033 D02 v02r01 Section C.1
Limit: None; for reporting purposes only.
Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum analyzer.

Spectrum analyzer according to the following Settings:

- a) Set RBW = approximately 1 % of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.
Instruments Used: Refer to section 3 for details
Test Mode: Link mode
Test Results: Please refer to Appendix A

5.46 DB BANDWIDTH & OCCUPIED BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (e)
RSS-247 Issue 3 Section 6.2.4.1

Test Method: KDB 789033 D02 v02r01 Section C.2

Limit: Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum Analyzer.

Spectrum analyzer according to the following Settings:

6dB Bandwidth

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 * \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

- a) Set RBW = 1% to 5% of the occupied bandwidth
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Please refer to Appendix A

5.5 MAXIMUM CONDUCTED OUTPUT POWER OR E.I.R.P

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3)
RSS-247 Issue 3 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1

Test Method: KDB 789033 D02 v02r01 Section E.3.a (Method PM)

Limits: FCC 47 CFR Part 15 Subpart E

1. For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3. For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Limits: RSS-247 Issue 3

1. Frequency band 5150-5250 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

2. Frequency band 5250-5350 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

- a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;
- b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

Additional requirements

In addition to the above requirements, devices shall comply with the following, where applicable:

- a) Outdoor fixed devices with a maximum e.i.r.p. greater than 200 mW shall comply with the following e.i.r.p. at different elevations, where θ is the angle above the local horizontal plane (of the Earth) as shown below:

i. -13 dBW/MHz	for $0^\circ \leq \theta < 8^\circ$
ii. $-13 - 0.716 (\theta - 8)$ dBW/MHz	for $8^\circ \leq \theta < 40^\circ$
iii. $-35.9 - 1.22 (\theta - 40)$ dBW/MHz	for $40^\circ \leq \theta \leq 45^\circ$
iv. -42 dBW/MHz	for $\theta > 45^\circ$

The measurement procedure defined in Annex A of this document shall be used to verify the compliance to the e.i.r.p. at different elevations.

- b) Devices, other than outdoor fixed devices, having an e.i.r.p. greater than 200 mW shall comply with either i. or ii. below:
 - i. devices shall comply with the e.i.r.p. elevation mask in 6.2.2.3(a); or
 - ii. devices shall implement a method to permanently reduce their e.i.r.p. via a firmware feature in the event that the Department requires it. The test report must demonstrate how the device's power table can be updated to meet this firmware requirement. The manufacturer shall provide this firmware to update all systems automatically in compliance with the directions received from the Department.

3. Frequency bands 5470-5600 MHz and 5650-5725 MHz

The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

4. Frequency band 5725-5850 MHz

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices

operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint³ systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

Test Procedure:

1. Connected the EUT's antenna port to measure device by 10dB attenuator.
2. Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of Tx on burst.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Gain and the maximum output power limit.
RSS-247 Issue 3

Frequency Band	Antenna Gain (dBi)	Power Limits (dBm)
U-NII-1	3.5	23.0
U-NII-2A	3.5	24.0
U-NII-2C	3.5	24.0
U-NII-3	3.5	30.0

FCC 47 CFR Part 15 Subpart E

Frequency Band	Antenna Gain (dBi)	Power Limits (dBm)
U-NII-1	3.5	24.0
U-NII-2A	3.5	24.0
U-NII-2C	3.5	24.0
U-NII-3	3.5	30.0

Frequency band 5150-5250 MHz

RSS-247 Issue 3:

For IEEE 802.11a, the minimum 99% emission bandwidth is 17.626MHz

$10 \text{ dBm} + 10\log_{10}(17.626) = 22.46 \text{ dBm} < 23 \text{ dBm}$

So the 22.46 dBm limit applicable

For IEEE 802.11n-HT20/ ac-VHT20/ax-HE20, the minimum 99% emission bandwidth is 18.732 MHz

$10 \text{ dBm} + 10\log_{10}(18.732) = 22.73 \text{ dBm} < 23 \text{ dBm}$

So the 22.73 dBm limit applicable

For IEEE 802.11n-HT40/ ac-VHT40/ax-HE40, the minimum 99% emission bandwidth is 37.166 MHz

$10 \text{ dBm} + 10\log_{10}(37.166) = 25.70 \text{ dBm} > 23 \text{ dBm}$

So the 23 dBm limit applicable

Frequency band 5250-5350 MHz

RSS-247 Issue 3:

For IEEE 802.11 a, the minimum 99% emission bandwidth is 17.669 MHz

$11 \text{ dBm} + 10\log_{10}(17.669) = 23.47 \text{ dBm} < 24 \text{ dBm}$

So the 23.47 dBm limit applicable

For IEEE 802.11n-HT20/ ac-VHT20/ax-HE20, the minimum 99% emission bandwidth is 18.746 MHz

$11 \text{ dBm} + 10\log_{10}(18.746) = 23.73 \text{ dBm} < 24 \text{ dBm}$

So the 23.58 dBm limit applicable

For IEEE 802.11 n-HT40/ac-VHT40/ax-HE40, the minimum 99% emission bandwidth is 37.244 MHz

$11 \text{ dBm} + 10\log_{10}(37.244) = 26.71 \text{ dBm} > 24 \text{ dBm}$

So the 24 dBm limit applicable

EIRP:

For IEEE 802.11 a/n-HT20/ac-VHT20/ax-HE20, the minimum 99% emission bandwidth is 18.746MHz

$17 \text{ dBm} + 10\log_{10}(18.746) = 29.73 \text{ dBm}$

$29.73 \text{ dBm} > 27 \text{ dBm}$

So the 27 dBm limit applicable

For IEEE 802.11 n-HT40/ac-VHT40/ax-HE40, the minimum 99% emission bandwidth is 37.244 MHz

$17 \text{ dBm} + 10\log_{10}(37.244) = 32.71 \text{ dBm} > 27 \text{ dBm}$

So the 27 dBm limit applicable

FCC 47 CFR Part 15 Subpart E:

For IEEE 802.11 a/n/ac/ax, the minimum 26 dB emission bandwidth is 23.23 MHz

$11 \text{ dBm} + 10\log_{10}(23.23) = 24.66 \text{ dBm} > 24 \text{ dBm}$

So the 24 dBm limit applicable

Frequency bands 5470-5725 MHz (RSS-247 Issue 3 Not including 5600-5650 MHz)

RSS-247 Issue 3:

For IEEE 802.11 a, the minimum 99% emission bandwidth is 17.870 MHz

$11 \text{ dBm} + 10\log_{10}(17.870) = 23.52 \text{ dBm} < 24 \text{ dBm}$

So the 23.52 dBm limit applicable

For IEEE 802.11n-HT20/ac-VHT20/ax-HE20, the minimum 99% emission bandwidth is 18.949 MHz

$11 \text{ dBm} + 10\log_{10}(18.949) = 23.78 \text{ dBm} < 24 \text{ dBm}$

So the 23.78 dBm limit applicable

For IEEE 802.11 n-HT40/ac-VHT40/ax-HE40, the minimum 99% emission bandwidth is 37.595 MHz

$11 \text{ dBm} + 10\log_{10}(37.595) = 26.75 \text{ dBm} > 24 \text{ dBm}$

So the 24 dBm limit applicable

EIRP:

For IEEE 802.11 a/n-HT20/ac-VHT20/ax-HE20, the minimum 99% emission bandwidth is 17.870 MHz
 $17 \text{ dBm} + 10\log_{10}(17.870) = 29.52 \text{ dBm}$
 $29.52 \text{ dBm} > 27 \text{ dBm}$
 So the 27 dBm limit applicable

For IEEE 802.11 n-HT40/ac-VHT40/ax-HE40, the minimum 99% emission bandwidth is 37.595 MHz
 $17 \text{ dBm} + 10\log_{10}(37.595) = 32.75 \text{ dBm} > 27 \text{ dBm}$
 So the 27 dBm limit applicable

FCC 47 CFR Part 15 Subpart E:

For IEEE 802.11 a/n/ac/ax, the minimum 26 dB emission bandwidth is 23.23 MHz
 $11 \text{ dBm} + 10\log_{10}(23.23) = 24.66 \text{ dBm} > 24 \text{ dBm}$
 So the 24 dBm limit applicable

Test Mode	Antenna	Freq(MHz)	Result [dBm]	FCC Limit [dBm]	ISED Limit [dBm]	Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
11A	Ant1	5180	16.43	24	--	3.5	19.93	22.46	PASS
11A	Ant1	5220	16.52	24	--	3.5	20.02	22.46	PASS
11A	Ant1	5240	16.88	24	--	3.5	20.38	22.46	PASS
11A	Ant1	5260	17.33	24	23.47	3.5	20.83	27	PASS
11A	Ant1	5300	16.85	24	23.47	3.5	20.35	27	PASS
11A	Ant1	5320	17.50	24	23.47	3.5	21.00	27	PASS
11A	Ant1	5500	16.97	24	23.52	3.5	20.47	27	PASS
11A	Ant1	5580	16.83	24	23.52	3.5	20.33	27	PASS
11A	Ant1	5700	15.80	24	23.52	3.5	19.30	27	PASS
11A	Ant1	5720	16.20	24	23.52	3.5	19.70	27	PASS
11A	Ant1	5745	15.43	30	30	3.5	18.93	---	PASS
11A	Ant1	5785	15.94	30	30	3.5	19.44	---	PASS
11A	Ant1	5825	15.86	30	30	3.5	19.36	---	PASS
11N20SISO	Ant1	5180	16.38	24	--	3.5	19.88	22.73	PASS
11N20SISO	Ant1	5220	16.27	24	--	3.5	19.77	22.73	PASS
11N20SISO	Ant1	5240	16.33	24	--	3.5	19.83	22.73	PASS
11N20SISO	Ant1	5260	17.18	24	23.73	3.5	20.68	27	PASS
11N20SISO	Ant1	5300	17.25	24	23.73	3.5	20.75	27	PASS
11N20SISO	Ant1	5320	16.89	24	23.73	3.5	20.39	27	PASS
11N20SISO	Ant1	5500	16.77	24	23.78	3.5	20.27	27	PASS
11N20SISO	Ant1	5580	16.59	24	23.78	3.5	20.09	27	PASS
11N20SISO	Ant1	5700	16.55	24	23.78	3.5	20.05	27	PASS
11N20SISO	Ant1	5720	15.42	24	23.78	3.5	18.92	27	PASS
11N20SISO	Ant1	5745	14.87	30	30	3.5	18.37	---	PASS
11N20SISO	Ant1	5785	15.53	30	30	3.5	19.03	---	PASS
11N20SISO	Ant1	5825	15.19	30	30	3.5	18.69	---	PASS
11N40SISO	Ant1	5190	15.80	24	--	3.5	19.30	23	PASS
11N40SISO	Ant1	5230	16.58	24	--	3.5	20.08	23	PASS
11N40SISO	Ant1	5270	17.02	24	24	3.5	20.52	27	PASS
11N40SISO	Ant1	5310	17.08	24	24	3.5	20.58	27	PASS
11N40SISO	Ant1	5510	17.01	24	24	3.5	20.51	27	PASS
11N40SISO	Ant1	5550	17.20	24	24	3.5	20.70	27	PASS
11N40SISO	Ant1	5670	15.68	24	24	3.5	19.18	27	PASS
11N40SISO	Ant1	5710	15.28	24	24	3.5	18.78	27	PASS
11N40SISO	Ant1	5755	15.49	30	30	3.5	18.99	---	PASS
11N40SISO	Ant1	5795	13.95	30	30	3.5	17.45	---	PASS
11AC20SISO	Ant1	5180	16.06	24	--	3.5	19.56	22.73	PASS
11AC20SISO	Ant1	5220	16.86	24	--	3.5	20.36	22.73	PASS
11AC20SISO	Ant1	5240	16.91	24	--	3.5	20.41	22.73	PASS
11AC20SISO	Ant1	5260	16.79	24	23.73	3.5	20.29	27	PASS
11AC20SISO	Ant1	5300	17.30	24	23.73	3.5	20.80	27	PASS
11AC20SISO	Ant1	5320	16.67	24	23.73	3.5	20.17	27	PASS
11AC20SISO	Ant1	5500	16.75	24	23.78	3.5	20.25	27	PASS

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

11AC20SISO	Ant1	5580	15.66	24	23.78	3.5	19.16	27	PASS
11AC20SISO	Ant1	5700	16.47	24	23.78	3.5	19.97	27	PASS
11AC20SISO	Ant1	5720	15.52	24	23.78	3.5	19.02	27	PASS
11AC20SISO	Ant1	5745	15.39	30	30	3.5	18.89	---	PASS
11AC20SISO	Ant1	5785	15.18	30	30	3.5	18.68	---	PASS
11AC20SISO	Ant1	5825	15.22	30	30	3.5	18.72	---	PASS
11AC40SISO	Ant1	5190	16.41	24	--	3.5	19.91	23	PASS
11AC40SISO	Ant1	5230	16.12	24	--	3.5	19.62	23	PASS
11AC40SISO	Ant1	5270	16.59	24	24	3.5	20.09	27	PASS
11AC40SISO	Ant1	5310	17.08	24	24	3.5	20.58	27	PASS
11AC40SISO	Ant1	5510	17.02	24	24	3.5	20.52	27	PASS
11AC40SISO	Ant1	5550	17.20	24	24	3.5	20.70	27	PASS
11AC40SISO	Ant1	5670	15.83	24	24	3.5	19.33	27	PASS
11AC40SISO	Ant1	5710	15.79	24	24	3.5	19.29	27	PASS
11AC40SISO	Ant1	5755	14.78	30	30	3.5	18.28	---	PASS
11AC40SISO	Ant1	5795	15.54	30	30	3.5	19.04	---	PASS
11AX20SISO	Ant1	5180	16.18	24	--	3.5	19.68	22.73	PASS
11AX20SISO	Ant1	5220	16.47	24	--	3.5	19.97	22.73	PASS
11AX20SISO	Ant1	5240	16.57	24	--	3.5	20.07	22.73	PASS
11AX20SISO	Ant1	5260	17.40	24	23.73	3.5	20.90	27	PASS
11AX20SISO	Ant1	5300	17.01	24	23.73	3.5	20.51	27	PASS
11AX20SISO	Ant1	5320	17.30	24	23.73	3.5	20.80	27	PASS
11AX20SISO	Ant1	5500	16.90	24	23.78	3.5	20.40	27	PASS
11AX20SISO	Ant1	5580	15.69	24	23.78	3.5	19.19	27	PASS
11AX20SISO	Ant1	5700	15.79	24	23.78	3.5	19.29	27	PASS
11AX20SISO	Ant1	5720	15.78	24	23.78	3.5	19.28	27	PASS
11AX20SISO	Ant1	5745	15.10	30	30	3.5	18.60	---	PASS
11AX20SISO	Ant1	5785	15.35	30	30	3.5	18.85	---	PASS
11AX20SISO	Ant1	5825	15.87	30	30	3.5	19.37	---	PASS
11AX40SISO	Ant1	5190	16.23	24	--	3.5	19.73	23	PASS
11AX40SISO	Ant1	5230	16.50	24	--	3.5	20.00	23	PASS
11AX40SISO	Ant1	5270	17.37	24	24	3.5	20.87	27	PASS
11AX40SISO	Ant1	5310	16.56	24	24	3.5	20.06	27	PASS
11AX40SISO	Ant1	5510	16.86	24	24	3.5	20.36	27	PASS
11AX40SISO	Ant1	5550	17.20	24	24	3.5	20.70	27	PASS
11AX40SISO	Ant1	5670	15.85	24	24	3.5	19.35	27	PASS
11AX40SISO	Ant1	5710	15.31	24	24	3.5	18.81	27	PASS
11AX40SISO	Ant1	5755	15.07	30	30	3.5	18.57	---	PASS
11AX40SISO	Ant1	5795	15.36	30	30	3.5	18.86	---	PASS

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

5.6 PEAK POWER SPECTRAL DENSITY

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3)
RSS-247 Issue 3 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1

Test Method: KDB 789033 D02 v02r01 Section F

Limits: FCC 47 CFR Part 15 Subpart E

1. For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3. For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Limits: RSS-247 Issue 3

1. Frequency band 5150-5250 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

2. Frequency band 5250-5350 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

- a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;
- b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

Unwanted emission limits

Devices shall comply with the following:

- a) All emissions outside the band 5250-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p.; or
- b) All emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. and its power shall comply with the spectral power density for operation within the band 5150-5250 MHz. The device, except devices installed in vehicles, shall be labelled or include in the user manual the following text "for indoor use only."

Additional requirements

In addition to the above requirements, devices shall comply with the following, where applicable:

- a) Outdoor fixed devices with a maximum e.i.r.p. greater than 200 mW shall comply with the following e.i.r.p. at different elevations, where θ is the angle above the local horizontal plane (of the Earth) as shown below:

i. -13 dBW/MHz	for $0^\circ \leq \theta < 8^\circ$
ii. $-13 - 0.716 (\theta - 8)$ dBW/MHz	for $8^\circ \leq \theta < 40^\circ$
iii. $-35.9 - 1.22 (\theta - 40)$ dBW/MHz	for $40^\circ \leq \theta \leq 45^\circ$
iv. -42 dBW/MHz	for $\theta > 45^\circ$

The measurement procedure defined in Annex A of this document shall be used to verify the compliance to the e.i.r.p. at different elevations.

- b) Devices, other than outdoor fixed devices, having an e.i.r.p. greater than 200 mW shall comply with either i. or ii. below:
 - iii. devices shall comply with the e.i.r.p. elevation mask in 6.2.2.3(a); or
 - iv. devices shall implement a method to permanently reduce their e.i.r.p. via a firmware feature in the event that the Department requires it. The test report must demonstrate how the device's power table can be updated to meet this firmware requirement. The manufacturer shall provide this firmware to update all systems automatically in compliance with the directions received from the Department.

3. Frequency bands 5470-5600 MHz and 5650-5725 MHz

The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall

implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

4. Frequency band 5725-5850 MHz

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint³ systems, omnidirectional applications and multiple colocated transmitters transmitting the same information.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum Analyzer.

Spectrum analyzer according to the following Settings:

1. For U-NII-1, U-NII-2A, U-NII-2C band:

Using method SA-2

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz, Set VBW $\geq$ 3 RBW, Detector = RMS
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value and add 10 log (1/duty cycle)

2. For U-NII-3 band:

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 500 kHz, Set VBW $\geq$ 3 RBW, Detector = RMS
- Use the peak marker function to determine the maximum power level in any 500 kHz band segment within the fundamental EBW.
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value and add 10 log (1/duty cycle)

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Please refer to Appendix A

Test Data:

Gain and the maximum output power limit.

RSS-247 Issue 3:

Frequency Band	Antenna Gain (dBi)	PSD Limits (dBm/MHz or dBm/500kHz)
U-NII-1	3.5	10.0
U-NII-2A	3.5	10.0
U-NII-2C	3.5	11.0
U-NII-3	3.5	30.0

FCC 47 CFR Part 15 Subpart E:

Frequency Band	Antenna Gain (dBi)	PSD Limits (dBm/MHz or dBm/500kHz)
U-NII-1	3.5	11.0
U-NII-2A	3.5	11.0
U-NII-2C	3.5	11.0
U-NII-3	3.5	30.0

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

5.7 RADIATED EMISSIONS AND BAND EDGE MEASUREMENT

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(1)(2)(3)(4)(6)
FCC 47 CFR Part 15 Subpart C Section 15.209/205
RSS-247 Issue 3 Section 6.2.1.2/6.2.2.2/6.2.3.2/6.2.4.2

Test Method: KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

1. Limits of Radiated Emission and Band edge Measurement

Radiated emissions that fall in the restricted bands must comply with the general emissions limits in 15.209(a) as below table. Other emissions shall be at least 20 dB below the highest level of the desired power.

Frequency	Field strength (microvolt/meter)	Limit (dB μ V/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

- The lower limit shall apply at the transition frequencies.
- Emission level (dB μ V/m) = 20 log Emission level (uV/m).
- For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

2. Limits of Unwanted Emission Out of the Restricted Bands

Applicable To	Limit	
789033 D02 General U-NII Test Procedures New Rules v01r04	Field Strength at 3 m	
	PK: 74 (dBμV/m)	AV: 54 (dBμV/m)
Applicable To	EIRP Limit	Equivalent Field Strength at 3 m
FCC Part 15.407 (b)(1) RSS-247 Issue 3 Section 6.2.1.2	PK: -27 (dBm/MHz)	PK: 74 (dBμV/m)
FCC Part 15.407 (b)(2) RSS-247 Issue 3 Section 6.2.2.2	PK: -27 (dBm/MHz)	PK: 74 (dBμV/m)
FCC Part 15.407 (b)(3) RSS-247 Issue 3 Section 6.2.3.2	PK: -27 (dBm/MHz)	PK: 68.2 (dBμV/m)
FCC Part 15.407 (b)(4) RSS-247 Issue 3 Section 6.2.4.2	27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;	PK: 68.2 (dBμV/m)
	15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;	
	10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges;	
	-27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.	

Test Setup: Refer to section 4.5.1 for details.

Test Procedures:

- The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Remark:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for RMS Average (Duty cycle < 98 %) for Average detection (AV) at frequency above 1 GHz, then the measurement results was added to a correction factor (10 log(1/duty cycle)).
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz (Duty cycle ≥ 98 %) or ≥ 1/T(duty cycle is < 98%) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>


UTTR-RF-RSS247-V1.1

Radiated Emission Test Data (9 KHz ~ 30 MHz):

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Radiated Emission Test Data (30 MHz ~ 1 GHz):
Worst-Case Configuration(IEEE 802.11a Channel 64)
Horizontal


No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	34.045	29.41	-7.01	22.40	40.00	-17.60	QP
2	50.461	37.05	-14.19	22.86	40.00	-17.14	QP
3	216.120	33.56	-10.98	22.58	46.00	-23.42	QP
4	336.482	34.18	-7.22	26.96	46.00	-19.04	QP
5	433.340	31.76	-3.35	28.41	46.00	-17.59	QP
6	912.695	26.88	4.51	31.39	46.00	-14.61	QP



Radiated Emission Test Data (Above 1GHz):								
No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11a_Channel 36								
1	10360.000	39.58	3.38	42.96	--	--	Average	Horizontal
2	10360.000	57.18	3.38	60.56	68.20	-7.64	Peak	Horizontal
3	15483.440	34.90	7.62	42.52	54.00	-11.48	Average	Horizontal
4	15483.440	53.89	7.62	61.51	74.00	-12.49	Peak	Horizontal
5	10360.000	42.39	3.38	45.77	--	--	Average	Vertical
6	10360.000	61.05	3.38	64.43	68.20	-3.77	Peak	Vertical
7	15483.440	36.89	7.62	44.51	54.00	-9.49	Average	Vertical
8	15483.440	58.40	7.62	66.02	74.00	-7.98	Peak	Vertical
IEEE 802.11a_Channel 44								
1	10440.000	42.68	3.38	46.06	--	--	Average	Horizontal
2	10440.000	62.26	3.38	65.64	68.20	-2.56	Peak	Horizontal
3	15573.390	53.81	7.53	61.34	74.00	-12.66	Average	Horizontal
4	15573.390	35.52	7.53	43.05	54.00	-10.95	Peak	Horizontal
5	10440.000	43.59	3.38	46.97	--	--	Average	Vertical
6	10440.000	63.61	3.38	66.99	68.20	-1.21	Peak	Vertical
7	15573.390	58.21	7.53	65.74	74.00	-8.26	Average	Vertical
8	15573.390	38.49	7.53	46.02	54.00	-7.98	Peak	Vertical
IEEE 802.11a_Channel 48								
1	10480.000	41.64	3.39	45.03	--	--	Average	Horizontal
2	10480.000	61.09	3.39	64.48	68.20	-3.72	Peak	Horizontal
3	15663.860	51.16	7.44	58.60	74.00	-15.40	Average	Horizontal
4	15663.860	34.76	7.44	42.20	54.00	-11.80	Peak	Horizontal
5	10480.000	43.30	3.39	46.69	--	--	Average	Vertical
6	10480.000	62.76	3.39	66.15	68.20	-2.05	Peak	Vertical
7	15663.860	56.62	7.44	64.06	74.00	-9.94	Average	Vertical
8	15663.860	37.08	7.44	44.52	54.00	-9.48	Peak	Vertical
IEEE 802.11a_Channel 52								
1	10520.000	40.31	3.35	43.66	--	--	Average	Horizontal
2	10520.000	60.12	3.35	63.47	68.20	-4.73	Peak	Horizontal
3	15780.000	32.99	7.35	40.34	54.00	-13.66	Average	Horizontal
4	15780.000	49.80	7.35	57.15	74.00	-16.85	Peak	Horizontal
5	10480.000	43.30	3.39	46.69	--	--	Average	Vertical
6	10520.000	63.72	3.35	67.07	68.20	-1.13	Peak	Vertical
7	15663.860	37.08	7.44	44.52	54.00	-9.48	Average	Vertical
8	15780.000	57.22	7.35	64.57	74.00	-9.43	Peak	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11a_Channel 60								
1	10600.000	40.69	3.19	43.88	--	--	Average	Horizontal
2	10600.000	60.03	3.19	63.22	68.20	-4.98	Peak	Horizontal
3	15846.370	49.29	7.28	56.57	74.00	-17.43	Average	Horizontal
4	15900.000	30.46	7.24	37.70	54.00	-16.30	Peak	Horizontal
5	10600.000	43.65	3.19	46.84	--	--	Average	Vertical
6	10625.640	66.74	3.13	69.87	74.00	-4.13	Peak	Vertical
7	15846.370	36.20	7.28	43.48	54.00	-10.52	Average	Vertical
8	15846.370	55.58	7.28	62.86	74.00	-11.14	Peak	Vertical
IEEE 802.11a_Channel 64								
1	10640.000	39.93	3.10	43.03	54.00	-10.97	Average	Horizontal
2	10640.000	58.66	3.10	61.76	74.00	-12.24	Peak	Horizontal
3	15846.370	49.25	7.28	56.53	74.00	-17.47	Average	Horizontal
4	15960.000	31.10	7.19	38.29	54.00	-15.71	Peak	Horizontal
5	10640.000	43.34	3.10	46.44	54.00	-7.56	Average	Vertical
6	10640.000	64.23	3.10	67.33	74.00	-6.67	Peak	Vertical
7	15846.370	56.08	7.28	63.36	74.00	-10.64	Average	Vertical
8	15960.000	32.09	7.19	39.28	54.00	-14.72	Peak	Vertical
IEEE 802.11a_Channel 100								
1	11000.000	43.99	2.36	46.35	54.00	-7.65	Average	Horizontal
2	11000.000	62.68	2.36	65.04	74.00	-8.96	Peak	Horizontal
3	16500.000	31.56	8.00	39.56	--	--	Average	Horizontal
4	16500.000	44.97	8.00	52.97	68.20	-15.23	Peak	Horizontal
5	11000.000	45.36	2.36	47.72	54.00	-6.28	Average	Vertical
6	11000.000	64.50	2.36	66.86	74.00	-7.14	Peak	Vertical
7	16406.780	48.23	7.84	56.07	68.20	-12.13	Average	Vertical
8	16500.000	31.44	8.00	39.44	--	--	Peak	Vertical
IEEE 802.11a_Channel 116								
1	11160.000	39.19	2.25	41.44	54.00	-12.56	Average	Horizontal
2	11160.000	60.24	2.25	62.49	74.00	-11.51	Peak	Horizontal
3	16740.000	30.48	8.31	38.79	--	--	Average	Horizontal
4	16740.000	44.33	8.31	52.64	68.20	-15.56	Peak	Horizontal
5	11160.000	39.19	2.25	41.44	54.00	-12.56	Average	Vertical
6	11160.000	60.14	2.25	62.39	74.00	-11.61	Peak	Vertical
7	16740.000	30.48	8.31	38.79	--	--	Average	Vertical
8	16740.000	43.34	8.31	51.65	68.20	-16.55	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11a_Channel 140								
1	11400.000	38.37	2.11	40.48	54.00	-13.52	Average	Horizontal
2	11400.000	55.03	2.11	57.14	74.00	-16.86	Peak	Horizontal
3	17100.000	31.46	8.79	40.25	--	--	Average	Horizontal
4	17100.000	44.79	8.79	53.58	68.20	-14.62	Peak	Horizontal
5	11390.480	56.72	2.12	58.84	74.00	-15.16	Average	Vertical
6	11400.000	40.47	2.11	42.58	54.00	-11.42	Peak	Vertical
7	16987.000	48.44	8.63	57.07	68.20	-11.13	Average	Vertical
8	17100.000	31.50	8.79	40.29	--	--	Peak	Vertical
IEEE 802.11a_Channel 144								
1	11440.000	36.59	2.09	38.68	54.00	-15.32	Average	Horizontal
2	11440.000	53.75	2.09	55.84	74.00	-18.16	Peak	Horizontal
3	17160.000	31.44	8.88	40.32	--	--	Average	Horizontal
4	17160.000	43.82	8.88	52.70	68.20	-15.50	Peak	Horizontal
5	11440.000	38.21	2.09	40.30	54.00	-13.70	Average	Vertical
6	11440.000	57.82	2.09	59.91	74.00	-14.09	Peak	Vertical
7	17085.680	47.38	8.78	56.16	68.20	-12.04	Average	Vertical
8	17160.000	31.28	8.88	40.16	--	--	Peak	Vertical
IEEE 802.11a_Channel 149								
1	11490.000	34.88	2.06	36.94	54.00	-17.06	Average	Horizontal
2	11490.000	57.10	2.06	59.16	74.00	-14.84	Peak	Horizontal
3	17235.000	31.07	8.99	40.06	--	--	Average	Horizontal
4	17235.000	43.62	8.99	52.61	68.20	-15.59	Peak	Horizontal
5	11490.000	36.14	2.06	38.20	54.00	-15.80	Average	Vertical
6	11490.000	58.43	2.06	60.49	74.00	-13.51	Peak	Vertical
7	17235.000	30.91	8.99	39.90	--	--	Average	Vertical
8	17235.000	43.34	8.99	52.33	68.20	-15.87	Peak	Vertical
IEEE 802.11a_Channel 157								
1	11570.000	36.90	2.05	38.95	54.00	-15.05	Average	Horizontal
2	11570.000	53.25	2.05	55.30	74.00	-18.70	Peak	Horizontal
3	17355.000	30.71	9.16	39.87	--	--	Average	Horizontal
4	17355.000	43.41	9.16	52.57	68.20	-15.63	Peak	Horizontal
5	11570.000	39.10	2.05	41.15	54.00	-12.85	Average	Vertical
6	11570.000	57.72	2.05	59.77	74.00	-14.23	Peak	Vertical
7	17355.000	30.71	9.16	39.87	--	--	Average	Vertical
8	17355.000	42.92	9.16	52.08	68.20	-16.12	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11a_Channel 165								
1	11650.000	35.87	2.08	37.95	54.00	-16.05	Average	Horizontal
2	11650.000	51.52	2.08	53.60	74.00	-20.40	Peak	Horizontal
3	17475.000	29.94	9.33	39.27	--	--	Average	Horizontal
4	17475.000	42.88	9.33	52.21	68.20	-15.99	Peak	Horizontal
5	11650.000	37.57	2.08	39.65	54.00	-14.35	Average	Vertical
6	11650.000	54.08	2.08	56.16	74.00	-17.84	Peak	Vertical
7	17475.000	29.94	9.33	39.27	--	--	Average	Vertical
8	17475.000	42.88	9.33	52.21	68.20	-15.99	Peak	Vertical
IEEE 802.11n-HT20_Channel 36								
1	10360.000	41.41	3.38	44.79	--	--	Average	Horizontal
2	10360.000	61.49	3.38	64.87	68.20	-3.33	Peak	Horizontal
3	15483.440	36.62	7.62	44.24	54.00	-9.76	Average	Horizontal
4	15483.440	56.96	7.62	64.58	74.00	-9.42	Peak	Horizontal
5	10360.000	42.05	3.38	45.43	68.20	-22.77	Peak	Vertical
6	10360.000	59.96	3.38	63.34	68.20	-4.86	Average	Vertical
7	15483.440	36.70	7.62	44.32	54.00	-9.68	Peak	Vertical
8	15483.440	57.15	7.62	64.77	74.00	-9.23	Average	Vertical
IEEE 802.11n-HT20_Channel 44								
1	10440.000	42.70	3.38	46.08	--	--	Average	Horizontal
2	10440.000	59.61	3.38	62.99	68.20	-5.21	Peak	Horizontal
3	15573.390	35.12	7.53	42.65	54.00	-11.35	Average	Horizontal
4	15573.390	51.15	7.53	58.68	74.00	-15.32	Peak	Horizontal
5	10440.000	43.30	3.38	46.68	--	--	Average	Vertical
6	10440.000	62.88	3.38	66.26	68.20	-1.94	Peak	Vertical
7	15573.390	38.19	7.53	45.72	54.00	-8.28	Average	Vertical
8	15573.390	58.14	7.53	65.67	74.00	-8.33	Peak	Vertical
IEEE 802.11n-HT20_Channel 48								
1	10480.000	41.37	3.39	44.76	--	--	Average	Horizontal
2	10480.000	60.43	3.39	63.82	68.20	-4.38	Peak	Horizontal
3	15663.860	34.71	7.44	42.15	54.00	-11.85	Average	Horizontal
4	15663.860	50.74	7.44	58.18	74.00	-15.82	Peak	Horizontal
5	10480.000	43.18	3.39	46.57	--	--	Average	Vertical
6	10480.000	63.29	3.39	66.68	68.20	-1.52	Peak	Vertical
7	15663.860	36.99	7.44	44.43	54.00	-9.57	Average	Vertical
8	15663.860	57.13	7.44	64.57	74.00	-9.43	Peak	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT20_Channel 52								
1	10520.000	40.42	3.35	43.77	--	--	Average	Horizontal
2	10520.000	58.87	3.35	62.22	68.20	-5.98	Peak	Horizontal
3	15663.860	52.23	7.44	59.67	74.00	-14.33	Average	Horizontal
4	15780.000	32.92	7.35	40.27	54.00	-13.73	Peak	Horizontal
5	10520.000	43.61	3.35	46.96	--	--	Average	Vertical
6	10520.000	63.27	3.35	66.62	68.20	-1.58	Peak	Vertical
7	15663.860	35.38	7.44	42.82	54.00	-11.18	Average	Vertical
8	15780.000	56.00	7.35	63.35	74.00	-10.65	Peak	Vertical
IEEE 802.11n-HT20_Channel 60								
1	10600.000	40.57	3.19	43.76	--	--	Average	Horizontal
2	10600.000	59.57	3.19	62.76	68.20	-5.44	Peak	Horizontal
3	15846.370	49.92	7.28	57.20	74.00	-16.80	Average	Horizontal
4	15900.000	30.38	7.24	37.62	54.00	-16.38	Peak	Horizontal
5	10600.000	43.53	3.19	46.72	--	--	Average	Vertical
6	10600.000	63.50	3.19	66.69	68.20	-1.51	Peak	Vertical
7	15846.370	35.64	7.28	42.92	54.00	-11.08	Average	Vertical
8	15846.370	54.42	7.28	61.70	74.00	-12.30	Peak	Vertical
IEEE 802.11n-HT20_Channel 64								
1	10640.000	39.18	3.10	42.28	54.00	-11.72	Average	Horizontal
2	10640.000	58.25	3.10	61.35	74.00	-12.65	Peak	Horizontal
3	15960.000	30.98	7.19	38.17	54.00	-15.83	Average	Horizontal
4	15960.000	45.98	7.19	53.17	74.00	-20.83	Peak	Horizontal
5	10640.000	45.12	3.10	48.22	54.00	-5.78	Average	Vertical
6	10640.000	64.80	3.10	67.90	74.00	-6.10	Peak	Vertical
7	15846.370	53.32	7.28	60.60	74.00	-13.40	Average	Vertical
8	15960.000	31.95	7.19	39.14	54.00	-14.86	Peak	Vertical
IEEE 802.11n-HT20_Channel 100								
1	11000.000	44.16	2.36	46.52	54.00	-7.48	Average	Horizontal
2	11000.000	59.77	2.36	62.13	74.00	-11.87	Peak	Horizontal
3	16500.000	31.40	8.00	39.40	--	--	Average	Horizontal
4	16500.000	44.07	8.00	52.07	68.20	-16.13	Peak	Horizontal
5	11000.000	45.47	2.36	47.83	54.00	-6.17	Average	Vertical
6	11000.000	64.97	2.36	67.33	74.00	-6.67	Peak	Vertical
7	16406.780	47.73	7.84	55.57	68.20	-12.63	Average	Vertical
8	16500.000	31.40	8.00	39.40	--	--	Peak	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT20_Channel 116								
1	11160.000	38.16	2.25	40.41	54.00	-13.59	Average	Horizontal
2	11160.000	58.87	2.25	61.12	74.00	-12.88	Peak	Horizontal
3	16740.000	30.35	8.31	38.66	--	--	Average	Horizontal
4	16740.000	43.02	8.31	51.33	68.20	-16.87	Peak	Horizontal
5	11160.000	38.80	2.25	41.05	54.00	-12.95	Average	Vertical
6	11160.000	60.26	2.25	62.51	74.00	-11.49	Peak	Vertical
7	16740.000	30.35	8.31	38.66	--	--	Average	Vertical
8	16740.000	43.12	8.31	51.43	68.20	-16.77	Peak	Vertical
IEEE 802.11n-HT20_Channel 140								
1	11400.000	38.26	2.11	40.37	54.00	-13.63	Average	Horizontal
2	11400.000	54.46	2.11	56.57	74.00	-17.43	Peak	Horizontal
3	17100.000	31.54	8.79	40.33	--	--	Average	Horizontal
4	17100.000	44.27	8.79	53.06	68.20	-15.14	Peak	Horizontal
5	11400.000	40.08	2.11	42.19	54.00	-11.81	Average	Vertical
6	11400.000	57.73	2.11	59.84	74.00	-14.16	Peak	Vertical
7	17100.000	31.46	8.79	40.25	--	--	Average	Vertical
8	17100.000	44.33	8.79	53.12	68.20	-15.08	Peak	Vertical
IEEE 802.11n-HT20_Channel 144								
1	11440.000	36.63	2.09	38.72	54.00	-15.28	Average	Horizontal
2	11440.000	53.33	2.09	55.42	74.00	-18.58	Peak	Horizontal
3	17160.000	31.32	8.88	40.20	--	--	Average	Horizontal
4	17160.000	44.51	8.88	53.39	68.20	-14.81	Peak	Horizontal
5	11440.000	38.17	2.09	40.26	54.00	-13.74	Average	Vertical
6	11440.000	54.59	2.09	56.68	74.00	-17.32	Peak	Vertical
7	17085.680	48.22	8.78	57.00	68.20	-11.20	Average	Vertical
8	17160.000	31.24	8.88	40.12	--	--	Peak	Vertical
IEEE 802.11n-HT20_Channel 149								
1	11490.000	34.93	2.06	36.99	54.00	-17.01	Average	Horizontal
2	11490.000	54.13	2.06	56.19	74.00	-17.81	Peak	Horizontal
3	17235.000	31.07	8.99	40.06	--	--	Average	Horizontal
4	17235.000	43.79	8.99	52.78	68.20	-15.42	Peak	Horizontal
5	11490.000	35.86	2.06	37.92	54.00	-16.08	Average	Vertical
6	11490.000	57.32	2.06	59.38	74.00	-14.62	Peak	Vertical
7	17235.000	30.99	8.99	39.98	--	--	Average	Vertical
8	17235.000	43.93	8.99	52.92	68.20	-15.28	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT20_Channel 157								
1	11570.000	36.94	2.05	38.99	54.00	-15.01	Average	Horizontal
2	11570.000	52.09	2.05	54.14	74.00	-19.86	Peak	Horizontal
3	17355.000	30.80	9.16	39.96	--	--	Average	Horizontal
4	17355.000	43.42	9.16	52.58	68.20	-15.62	Peak	Horizontal
5	11570.000	38.94	2.05	40.99	54.00	-13.01	Average	Vertical
6	11570.000	55.00	2.05	57.05	74.00	-16.95	Peak	Vertical
7	17355.000	30.67	9.16	39.83	--	--	Average	Vertical
8	17355.000	43.13	9.16	52.29	68.20	-15.91	Peak	Vertical
IEEE 802.11n-HT20_Channel 165								
1	11650.000	35.61	2.08	37.69	54.00	-16.31	Average	Horizontal
2	11650.000	51.42	2.08	53.50	74.00	-20.50	Peak	Horizontal
3	17475.000	29.94	9.33	39.27	--	--	Average	Horizontal
4	17475.000	43.07	9.33	52.40	68.20	-15.80	Peak	Horizontal
5	11650.000	37.38	2.08	39.46	54.00	-14.54	Average	Vertical
6	11650.000	54.41	2.08	56.49	74.00	-17.51	Peak	Vertical
7	17475.000	29.89	9.33	39.22	--	--	Average	Vertical
8	17475.000	43.51	9.33	52.84	68.20	-15.36	Peak	Vertical
IEEE 802.11n-HT40_Channel 38								
1	10380.000	42.38	3.38	45.76	--	--	Average	Horizontal
2	10380.000	55.96	3.38	59.34	68.20	-8.86	Peak	Horizontal
3	15483.440	36.27	7.62	43.89	54.00	-10.11	Average	Horizontal
4	15483.440	51.62	7.62	59.24	74.00	-14.76	Peak	Horizontal
5	10380.000	43.38	3.38	46.76	--	--	Average	Vertical
6	10380.000	57.14	3.38	60.52	68.20	-7.68	Peak	Vertical
7	15483.440	39.24	7.62	46.86	54.00	-7.14	Average	Vertical
8	15483.440	55.44	7.62	63.06	74.00	-10.94	Peak	Vertical
IEEE 802.11n-HT40_Channel 46								
1	10460.000	41.13	3.40	44.53	--	--	Average	Horizontal
2	10460.000	56.89	3.40	60.29	68.20	-7.91	Peak	Horizontal
3	15690.000	33.63	7.42	41.05	54.00	-12.95	Average	Horizontal
4	15690.000	50.43	7.42	57.85	74.00	-16.15	Peak	Horizontal
5	10460.000	43.79	3.40	47.19	--	--	Average	Vertical
6	10460.000	58.76	3.40	62.16	68.20	-6.04	Peak	Vertical
7	15690.000	37.70	7.42	45.12	54.00	-8.88	Average	Vertical
8	15690.000	55.57	7.42	62.99	74.00	-11.01	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT40_Channel 54								
1	10540.000	41.41	3.30	44.71	--	--	Average	Horizontal
2	10540.000	57.29	3.30	60.59	68.20	-7.61	Peak	Horizontal
3	15754.850	34.70	7.37	42.07	54.00	-11.93	Average	Horizontal
4	15754.850	47.55	7.37	54.92	74.00	-19.08	Peak	Horizontal
5	10540.000	61.87	3.30	65.17	68.20	-3.03	Average	Vertical
6	10564.270	43.38	3.26	46.64	--	--	Peak	Vertical
7	15754.850	38.46	7.37	45.83	54.00	-8.17	Average	Vertical
8	15754.850	55.88	7.37	63.25	74.00	-10.75	Peak	Vertical
IEEE 802.11n-HT40_Channel 62								
1	10620.000	56.12	3.14	59.26	74.00	-14.74	Average	Horizontal
2	10625.640	42.50	3.13	45.63	54.00	-8.37	Peak	Horizontal
3	15846.370	33.99	7.28	41.27	54.00	-12.73	Average	Horizontal
4	15846.370	51.31	7.28	58.59	74.00	-15.41	Peak	Horizontal
5	10620.000	48.01	3.14	51.15	54.00	-2.85	Average	Vertical
6	10620.000	60.10	3.14	63.24	74.00	-10.76	Peak	Vertical
7	15846.370	37.35	7.28	44.63	54.00	-9.37	Average	Vertical
8	15846.370	51.54	7.28	58.82	74.00	-15.18	Peak	Vertical
IEEE 802.11n-HT40_Channel 102								
1	11020.000	41.58	2.35	43.93	54.00	-10.07	Average	Horizontal
2	11020.000	58.72	2.35	61.07	74.00	-12.93	Peak	Horizontal
3	16530.000	30.78	8.04	38.82	--	--	Average	Horizontal
4	16530.000	43.68	8.04	51.72	68.20	-16.48	Peak	Horizontal
5	11020.000	42.48	2.35	44.83	54.00	-9.17	Average	Vertical
6	11020.000	60.90	2.35	63.25	74.00	-10.75	Peak	Vertical
7	16530.000	32.44	8.04	40.48	--	--	Average	Vertical
8	16530.000	48.48	8.04	56.52	68.20	-11.68	Peak	Vertical
IEEE 802.11n-HT40_Channel 110								
1	11100.000	41.33	2.30	43.63	54.00	-10.37	Average	Horizontal
2	11100.000	57.35	2.30	59.65	74.00	-14.35	Peak	Horizontal
3	16650.000	29.89	8.20	38.09	--	--	Average	Horizontal
4	16650.000	43.48	8.20	51.68	68.20	-16.52	Peak	Horizontal
5	11100.000	43.26	2.30	45.56	54.00	-8.44	Average	Vertical
6	11100.000	59.68	2.30	61.98	74.00	-12.02	Peak	Vertical
7	16597.950	47.99	8.13	56.12	68.20	-12.08	Average	Vertical
8	16650.000	29.89	8.20	38.09	--	--	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT40_Channel 134								
1	11340.000	38.93	2.16	41.09	54.00	-12.91	Average	Horizontal
2	11340.000	51.69	2.16	53.85	74.00	-20.15	Peak	Horizontal
3	17010.000	30.57	8.67	39.24	--	--	Average	Horizontal
4	17010.000	42.73	8.67	51.40	68.20	-16.80	Peak	Horizontal
5	11340.000	40.48	2.16	42.64	54.00	-11.36	Average	Vertical
6	11340.000	52.72	2.16	54.88	74.00	-19.12	Peak	Vertical
7	16888.890	46.26	8.50	54.76	68.20	-13.44	Average	Vertical
8	17010.000	30.73	8.67	39.40	--	--	Peak	Vertical
IEEE 802.11n-HT40_Channel 142								
1	11420.000	35.37	2.10	37.47	54.00	-16.53	Average	Horizontal
2	11420.000	50.05	2.10	52.15	74.00	-21.85	Peak	Horizontal
3	17130.000	30.24	8.84	39.08	--	--	Average	Horizontal
4	17130.000	42.75	8.84	51.59	68.20	-16.61	Peak	Horizontal
5	11420.000	37.37	2.10	39.47	54.00	-14.53	Average	Vertical
6	11420.000	54.39	2.10	56.49	74.00	-17.51	Peak	Vertical
7	17130.000	30.79	8.84	39.63	--	--	Average	Vertical
8	17130.000	43.24	8.84	52.08	68.20	-16.12	Peak	Vertical
IEEE 802.11n-HT40_Channel 151								
1	11510.000	38.00	2.05	40.05	54.00	-13.95	Average	Horizontal
2	11510.000	51.33	2.05	53.38	74.00	-20.62	Peak	Horizontal
3	17265.000	29.93	9.03	38.96	--	--	Average	Horizontal
4	17265.000	43.12	9.03	52.15	68.20	-16.05	Peak	Horizontal
5	11510.000	40.28	2.05	42.33	54.00	-11.67	Average	Vertical
6	11510.000	52.84	2.05	54.89	74.00	-19.11	Peak	Vertical
7	17184.940	46.18	8.92	55.10	68.20	-13.10	Average	Vertical
8	17265.000	29.89	9.03	38.92	--	--	Peak	Vertical
IEEE 802.11n-HT40_Channel 159								
1	11590.000	36.67	2.07	38.74	54.00	-15.26	Average	Horizontal
2	11590.000	50.33	2.07	52.40	74.00	-21.60	Peak	Horizontal
3	17385.000	29.63	9.21	38.84	--	--	Average	Horizontal
4	17385.000	41.82	9.21	51.03	68.20	-17.17	Peak	Horizontal
5	11590.000	39.54	2.07	41.61	54.00	-12.39	Average	Vertical
6	11590.000	51.97	2.07	54.04	74.00	-19.96	Peak	Vertical
7	17385.000	29.68	9.21	38.89	--	--	Average	Vertical
8	17385.000	41.98	9.21	51.19	68.20	-17.01	Peak	Vertical

Radiated Emission Test Data (Above 1GHz): Worst-Case Configuration								
No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ax-HE20_Channel 36								
1	10360.000	41.41	3.38	44.79	--	--	Average	Horizontal
2	10360.000	61.49	3.38	64.87	68.20	-3.33	Peak	Horizontal
3	15483.440	36.62	7.62	44.24	54.00	-9.76	Average	Horizontal
4	15483.440	56.96	7.62	64.58	74.00	-9.42	Peak	Horizontal
5	10360.000	42.05	3.38	45.43	--	--	Average	Vertical
6	10360.000	59.96	3.38	63.34	68.20	-4.86	Peak	Vertical
7	15483.440	36.70	7.62	44.32	54.00	-9.68	Average	Vertical
8	15483.440	57.15	7.62	64.77	74.00	-9.23	Peak	Vertical
IEEE 802.11ax-HE20_Channel 44								
1	10440.000	42.70	3.38	46.08	--	--	Average	Horizontal
2	10440.000	59.61	3.38	62.99	68.20	-5.21	Peak	Horizontal
3	15573.390	35.12	7.53	42.65	54.00	-11.35	Average	Horizontal
4	15573.390	51.15	7.53	58.68	74.00	-15.32	Peak	Horizontal
5	10440.000	43.30	3.38	46.68	--	--	Average	Vertical
6	10440.000	62.88	3.38	66.26	68.20	-1.94	Peak	Vertical
7	15573.390	38.19	7.53	45.72	54.00	-8.28	Average	Vertical
8	15573.390	58.14	7.53	65.67	74.00	-8.33	Peak	Vertical
IEEE 802.11ax-HE20_Channel 48								
1	10480.000	41.37	3.39	44.76	--	--	Average	Horizontal
2	10480.000	60.43	3.39	63.82	68.20	-4.38	Peak	Horizontal
3	15663.860	34.71	7.44	42.15	54.00	-11.85	Average	Horizontal
4	15663.860	50.74	7.44	58.18	74.00	-15.82	Peak	Horizontal
5	10480.000	43.18	3.39	46.57	--	--	Average	Vertical
6	10480.000	63.29	3.39	66.68	68.20	-1.52	Peak	Vertical
7	15663.860	36.99	7.44	44.43	54.00	-9.57	Average	Vertical
8	15663.860	57.13	7.44	64.57	74.00	-9.43	Peak	Vertical
IEEE 802.11ax-HE20_Channel 52								
1	10520.000	40.42	3.35	43.77	--	--	Average	Horizontal
2	10520.000	58.87	3.35	62.22	68.20	-5.98	Peak	Horizontal
3	15663.860	52.23	7.44	59.67	74.00	-14.33	Average	Horizontal
4	15780.000	32.92	7.35	40.27	54.00	-13.73	Peak	Horizontal
5	10520.000	43.61	3.35	46.96	--	--	Average	Vertical
6	10520.000	63.27	3.35	66.62	68.20	-1.58	Peak	Vertical
7	15663.860	35.38	7.44	42.82	54.00	-11.18	Average	Vertical
8	15780.000	56.00	7.35	63.35	74.00	-10.65	Peak	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ax-HE20_Channel 60								
1	10600.000	40.57	3.19	43.76	--	--	Average	Horizontal
2	10600.000	59.57	3.19	62.76	68.20	-5.44	Peak	Horizontal
3	15846.370	49.92	7.28	57.20	74.00	-16.80	Average	Horizontal
4	15900.000	30.38	7.24	37.62	54.00	-16.38	Peak	Horizontal
5	10600.000	43.53	3.19	46.72	--	--	Average	Vertical
6	10600.000	63.50	3.19	66.69	68.20	-1.51	Peak	Vertical
7	15846.370	35.64	7.28	42.92	54.00	-11.08	Average	Vertical
8	15846.370	54.42	7.28	61.70	74.00	-12.30	Peak	Vertical
IEEE 802.11ax-HE20_Channel 64								
1	10640.000	39.18	3.10	42.28	54.00	-11.72	Average	Horizontal
2	10640.000	58.25	3.10	61.35	74.00	-12.65	Peak	Horizontal
3	15960.000	30.98	7.19	38.17	54.00	-15.83	Average	Horizontal
4	15960.000	45.98	7.19	53.17	74.00	-20.83	Peak	Horizontal
5	10640.000	45.12	3.10	48.22	54.00	-5.78	Average	Vertical
6	10640.000	64.80	3.10	67.90	74.00	-6.10	Peak	Vertical
7	15846.370	53.32	7.28	60.60	74.00	-13.40	Average	Vertical
8	15960.000	31.95	7.19	39.14	54.00	-14.86	Peak	Vertical
IEEE 802.11ax-HE20_Channel 100								
1	11000.000	44.16	2.36	46.52	54.00	-7.48	Average	Horizontal
2	11000.000	59.77	2.36	62.13	74.00	-11.87	Peak	Horizontal
3	16500.000	31.40	8.00	39.40	--	--	Average	Horizontal
4	16500.000	44.07	8.00	52.07	68.20	-16.13	Peak	Horizontal
5	11000.000	45.47	2.36	47.83	54.00	-6.17	Average	Vertical
6	11000.000	64.97	2.36	67.33	74.00	-6.67	Peak	Vertical
7	16406.780	47.73	7.84	55.57	68.20	-12.63	Average	Vertical
8	16500.000	31.40	8.00	39.40	--	--	Peak	Vertical
IEEE 802.11ax-HE20_Channel 116								
1	11160.000	38.16	2.25	40.41	54.00	-13.59	Average	Horizontal
2	11160.000	58.87	2.25	61.12	74.00	-12.88	Peak	Horizontal
3	16740.000	30.35	8.31	38.66	--	--	Average	Horizontal
4	16740.000	43.02	8.31	51.33	68.20	-16.87	Peak	Horizontal
5	11160.000	38.80	2.25	41.05	54.00	-12.95	Average	Vertical
6	11160.000	60.26	2.25	62.51	74.00	-11.49	Peak	Vertical
7	16740.000	30.35	8.31	38.66	--	--	Average	Vertical
8	16740.000	43.12	8.31	51.43	68.20	-16.77	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ax-HE20_Channel 140								
1	11400.000	38.26	2.11	40.37	54.00	-13.63	Average	Horizontal
2	11400.000	54.46	2.11	56.57	74.00	-17.43	Peak	Horizontal
3	17100.000	31.54	8.79	40.33	--	--	Average	Horizontal
4	17100.000	44.27	8.79	53.06	68.20	-15.14	Peak	Horizontal
5	11400.000	40.08	2.11	42.19	54.00	-11.81	Average	Vertical
6	11400.000	57.73	2.11	59.84	74.00	-14.16	Peak	Vertical
7	17100.000	31.46	8.79	40.25	--	--	Average	Vertical
8	17100.000	44.33	8.79	53.12	68.20	-15.08	Peak	Vertical
IEEE 802.11ax-HE20_Channel 144								
1	11440.000	36.63	2.09	38.72	54.00	-15.28	Average	Horizontal
2	11440.000	53.33	2.09	55.42	74.00	-18.58	Peak	Horizontal
3	17160.000	31.32	8.88	40.20	--	--	Average	Horizontal
4	17160.000	44.51	8.88	53.39	68.20	-14.81	Peak	Horizontal
5	11440.000	38.17	2.09	40.26	54.00	-13.74	Average	Vertical
6	11440.000	54.59	2.09	56.68	74.00	-17.32	Peak	Vertical
7	17085.680	48.22	8.78	57.00	68.20	-11.20	Average	Vertical
8	17160.000	31.24	8.88	40.12	--	--	Peak	Vertical
IEEE 802.11ax-HE20_Channel 149								
1	11490.000	34.93	2.06	36.99	54.00	-17.01	Average	Horizontal
2	11490.000	54.13	2.06	56.19	74.00	-17.81	Peak	Horizontal
3	17235.000	31.07	8.99	40.06	--	--	Average	Horizontal
4	17235.000	43.79	8.99	52.78	68.20	-15.42	Peak	Horizontal
5	11490.000	35.86	2.06	37.92	54.00	-16.08	Average	Vertical
6	11490.000	57.32	2.06	59.38	74.00	-14.62	Peak	Vertical
7	17235.000	30.99	8.99	39.98	--	--	Average	Vertical
8	17235.000	43.93	8.99	52.92	68.20	-15.28	Peak	Vertical
IEEE 802.11ax-HE20_Channel 157								
1	11570.000	36.94	2.05	38.99	54.00	-15.01	Average	Horizontal
2	11570.000	52.09	2.05	54.14	74.00	-19.86	Peak	Horizontal
3	17355.000	30.80	9.16	39.96	--	--	Average	Horizontal
4	17355.000	43.42	9.16	52.58	68.20	-15.62	Peak	Horizontal
5	11570.000	38.94	2.05	40.99	54.00	-13.01	Average	Vertical
6	11570.000	55.00	2.05	57.05	74.00	-16.95	Peak	Vertical
7	17355.000	30.67	9.16	39.83	--	--	Average	Vertical
8	17355.000	43.13	9.16	52.29	68.20	-15.91	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ax-HE20_Channel 165								
1	11650.000	35.61	2.08	37.69	54.00	-16.31	Average	Horizontal
2	11650.000	51.42	2.08	53.50	74.00	-20.50	Peak	Horizontal
3	17475.000	29.94	9.33	39.27	--	--	Average	Horizontal
4	17475.000	43.07	9.33	52.40	68.20	-15.80	Peak	Horizontal
5	11650.000	37.38	2.08	39.46	54.00	-14.54	Average	Vertical
6	11650.000	54.41	2.08	56.49	74.00	-17.51	Average	Vertical
7	17475.000	29.89	9.33	39.22	--	--	Peak	Vertical
8	17475.000	43.51	9.33	52.84	68.20	-15.36	Average	Vertical
IEEE 802.11ax-HE40_Channel 38								
1	10380.000	41.61	3.38	44.99	--	--	Average	Horizontal
2	10380.000	54.70	3.38	58.08	68.20	-10.12	Peak	Horizontal
3	15483.440	35.15	7.62	42.77	54.00	-11.23	Average	Horizontal
4	15483.440	50.19	7.62	57.81	74.00	-16.19	Peak	Horizontal
5	10380.000	43.53	3.38	46.91	--	--	Average	Vertical
6	10380.000	57.97	3.38	61.35	68.20	-6.85	Peak	Vertical
7	15483.440	38.46	7.62	46.08	54.00	-7.92	Average	Vertical
8	15483.440	54.80	7.62	62.42	74.00	-11.58	Peak	Vertical
IEEE 802.11ax-HE40_Channel 46								
1	10460.000	40.45	3.40	43.85	--	--	Average	Horizontal
2	10460.000	57.10	3.40	60.50	68.20	-7.70	Peak	Horizontal
3	15690.000	33.23	7.42	40.65	54.00	-13.35	Average	Horizontal
4	15690.000	48.46	7.42	55.88	74.00	-18.12	Peak	Horizontal
5	10460.000	43.00	3.40	46.40	--	--	Average	Vertical
6	10460.000	59.99	3.40	63.39	68.20	-4.81	Peak	Vertical
7	15573.390	59.27	7.53	66.80	74.00	-7.20	Average	Vertical
8	15690.000	36.76	7.42	44.18	54.00	-9.82	Peak	Vertical
IEEE 802.11ax-HE40_Channel 54								
1	10540.000	41.06	3.30	44.36	--	--	Average	Horizontal
2	10540.000	56.56	3.30	59.86	68.20	-8.34	Peak	Horizontal
3	15754.850	34.39	7.37	41.76	54.00	-12.24	Average	Horizontal
4	15754.850	47.52	7.37	54.89	74.00	-19.11	Peak	Horizontal
5	10540.000	43.48	3.30	46.78	--	--	Average	Vertical
6	10540.000	59.46	3.30	62.76	68.20	-5.44	Peak	Vertical
7	15754.850	37.62	7.37	44.99	54.00	-9.01	Average	Vertical
8	15754.850	54.06	7.37	61.43	74.00	-12.57	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ax-HE40_Channel 62								
1	10620.000	41.48	3.14	44.62	54.00	-9.38	Average	Horizontal
2	10620.000	55.29	3.14	58.43	74.00	-15.57	Peak	Horizontal
3	15930.000	29.78	7.21	36.99	54.00	-17.01	Average	Horizontal
4	15930.000	43.73	7.21	50.94	74.00	-23.06	Peak	Horizontal
5	10620.000	47.53	3.14	50.67	54.00	-3.33	Average	Vertical
6	10620.000	61.13	3.14	64.27	74.00	-9.73	Peak	Vertical
7	15846.370	37.21	7.28	44.49	54.00	-9.51	Average	Vertical
8	15846.370	52.27	7.28	59.55	74.00	-14.45	Peak	Vertical
IEEE 802.11ax-HE40_Channel 102								
1	11020.000	40.17	2.35	42.52	54.00	-11.48	Average	Horizontal
2	11020.000	58.18	2.35	60.53	74.00	-13.47	Peak	Horizontal
3	16530.000	30.82	8.04	38.86	--	--	Average	Horizontal
4	16530.000	43.48	8.04	51.52	68.20	-16.68	Peak	Horizontal
5	11020.000	42.20	2.35	44.55	54.00	-9.45	Average	Vertical
6	11020.000	58.03	2.35	60.38	74.00	-13.62	Peak	Vertical
7	16530.000	32.05	8.04	40.09	--	--	Average	Vertical
8	16530.000	49.99	8.04	58.03	68.20	-10.17	Peak	Vertical
IEEE 802.11ax-HE40_Channel 110								
1	11100.000	40.92	2.30	43.22	54.00	-10.78	Average	Horizontal
2	11100.000	56.85	2.30	59.15	74.00	-14.85	Peak	Horizontal
3	16650.000	29.86	8.20	38.06	--	--	Average	Horizontal
4	16650.000	42.67	8.20	50.87	68.20	-17.33	Peak	Horizontal
5	11100.000	42.29	2.30	44.59	54.00	-9.41	Average	Vertical
6	11100.000	57.66	2.30	59.96	74.00	-14.04	Peak	Vertical
7	16597.950	32.28	8.13	40.41	--	--	Average	Vertical
8	16597.950	46.62	8.13	54.75	68.20	-13.45	Peak	Vertical
IEEE 802.11ax-HE40_Channel 134								
1	11340.000	38.29	2.16	40.45	54.00	-13.55	Average	Horizontal
2	11340.000	51.73	2.16	53.89	74.00	-20.11	Peak	Horizontal
3	17010.000	30.52	8.67	39.19	--	--	Average	Horizontal
4	17010.000	43.55	8.67	52.22	68.20	-15.98	Peak	Horizontal
5	11340.000	40.17	2.16	42.33	54.00	-11.67	Average	Vertical
6	11340.000	53.69	2.16	55.85	74.00	-18.15	Peak	Vertical
7	16888.890	32.02	8.50	40.52	--	--	Average	Vertical
8	16888.890	45.70	8.50	54.20	68.20	-14.00	Peak	Vertical
IEEE 802.11ax-HE40_Channel 142								
1	11420.000	35.16	2.10	37.26	54.00	-16.74	Average	Horizontal
2	11420.000	50.94	2.10	53.04	74.00	-20.96	Peak	Horizontal
3	17130.000	30.24	8.84	39.08	--	--	Average	Horizontal
4	17130.000	42.55	8.84	51.39	68.20	-16.81	Peak	Horizontal
5	11420.000	37.01	2.10	39.11	54.00	-14.89	Average	Vertical
6	11420.000	52.88	2.10	54.98	74.00	-19.02	Peak	Vertical

7	17130.000	30.49	8.84	39.33	--	--	Average	Vertical
8	17130.000	43.07	8.84	51.91	68.20	-16.29	Peak	Vertical



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ax-HE40_Channel 151								
1	11510.000	37.02	2.05	39.07	54.00	-14.93	Average	Horizontal
2	11510.000	50.40	2.05	52.45	74.00	-21.55	Peak	Horizontal
3	17265.000	29.85	9.03	38.88	--	--	Average	Horizontal
4	17265.000	42.05	9.03	51.08	68.20	-17.12	Peak	Horizontal
5	11510.000	40.04	2.05	42.09	54.00	-11.91	Average	Vertical
6	11510.000	53.46	2.05	55.51	74.00	-18.49	Peak	Vertical
7	17265.000	29.80	9.03	38.83	--	--	Average	Vertical
8	17265.000	42.17	9.03	51.20	68.20	-17.00	Peak	Vertical
IEEE 802.11ax-HE40_Channel 159								
1	11590.000	36.28	2.07	38.35	54.00	-15.65	Average	Horizontal
2	11590.000	49.40	2.07	51.47	74.00	-22.53	Peak	Horizontal
3	17385.000	29.61	9.21	38.82	--	--	Average	Horizontal
4	17385.000	41.88	9.21	51.09	68.20	-17.11	Peak	Horizontal
5	11590.000	39.38	2.07	41.45	54.00	-12.55	Average	Vertical
6	11590.000	52.10	2.07	54.17	74.00	-19.83	Peak	Vertical
7	17385.000	29.57	9.21	38.78	--	--	Average	Vertical
8	17385.000	41.88	9.21	51.09	68.20	-17.11	Peak	Vertical

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit

Band Edge Measurements (Radiated)

IEEE 802.11a



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888



Fax: +86-755-28230886



E-mail: info@uttlab.com

<http://www.uttlab.com>



UTTR-RF-RSS247-V1.1







IEEE 802.11n-HT20



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888



Fax: +86-755-28230886


E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1











IEEE 802.11n-HT40



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888



Fax: +86-755-28230886


E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1











IEEE 802.11ax-HE20



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886


E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1











IEEE 802.11ax-HE40



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888



Fax: +86-755-28230886



E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1







Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

5.8 DYNAMIC FREQUENCY SELECTION

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (h)
RSS-247 Issue 3 Section 6.3

Test Method: KDB 905462 D03 Client Without DFS New Rules v01r02

EUT Operating Mode:

DFS Operational mode	Operating Frequency Range	
	5250 MHz to 5350 MHz	5470 MHz to 5725 MHz
Slave without radar Interference detection function	✓	✓

Applicability:

The following table from KDB905462 and the lists of the applicable requirements for the DFS testing.

Applicability of DFS Requirements Prior to Use of a Channel:

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
Non-Occupancy Period	✓	Not required	Yes
DFS Detection Threshold	✓	Not required	Yes
Channel Availability Check Time	✓	Not required	Not required
U-NII Detection Bandwidth	✓	Not required	Yes

Applicability of DFS requirements during normal operation:

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
DFS Detection Threshold	Yes	Not required
Channel Closing Transmission Time	Yes	Yes
Channel Move Time	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required
Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required
Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		

DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection:

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP ≥ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64dBm

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

DFS Radar Signal Parameter Values:

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds (See Note 1.)
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. (See Notes 1 and 2.)
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. (See Note 3.)

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

DFS Radar Signal Parameter:

Radar Type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time

Table 1-Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	See Note 1.	See Note 1.
1	1	Test A Test B	Roundup $\left\{ \left(\frac{1}{360} \right) \left(\frac{19 \cdot 10^6}{PRI_{\mu sec}} \right) \right\}$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.

Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a

Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A

A minimum of 30 unique waveforms are required for each of the Short Pulse Radar Types 2 through 4. If more than 30 waveforms are used for Short Pulse Radar Types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms.

If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B.

The aggregate is the average of the percentage of successful detections of short pulse radar types

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

1-4

Table 2-Long Pulse Radar Test Waveform

Radar Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Number of Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

Table 3-Frequency Hopping Radar Test Waveform

Radar Type	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	9	0.333	300	70%	30

In-Service Monitoring: Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period

Limit of In-Service Monitoring:

Reference to DFS Radar Signal Parameter Values.

Test Procedures:

- One frequency will be chosen from the Operating Channels of the EUT within the 5250-5350 MHz or 5470-5725 MHz bands. For 802.11 devices, the test frequency must contain control signals. This can be verified by disabling channel loading and monitoring the spectrum analyzer. If no control signals are detected, another frequency must be selected within the emission bandwidth where control signals are detected.
- In case the EUT is a Master Device, a U-NII device operating as a Client Device will be used and it is assumed that the Client will associate with the EUT (Master). For radiated tests, the emissions of the Radar Waveform generator will be directed towards the Master Device. If the Master Device has antenna gain, the main beam of the antenna will be directed toward the radar emitter. Vertical polarization is used for testing.
- The TCP protocol unicast data stream was generated by the iperf software command line with at least 17% activity ratio over any 100ms period.
- Timing plots are reported with calculations demonstrating a minimum channel loading of approximately 17% or greater. For example, channel loading can be estimated by setting the spectrum analyzer for zero span and approximate the Time On/ (Time On + Off Time).
- At time T_0 the Radar Waveform generator sends a Burst of pulses for one of the Short Pulse Radar Types 1-4 at DFS Detection Threshold levels on the Operating Channel. An additional 1 dB is added to the radar test signal to ensure it is at or above the DFS Detection Threshold, accounting for equipment variations/errors.
- Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel for duration greater than 10 seconds. Measure and record the transmissions from the EUT during the observation time (Channel Move Time). Measure and record the Channel Move Time and Channel Closing Transmission Time if radar detection occurs.
- When operating as a Master Device, monitor the EUT for more than 30 minutes following instant T_2 to verify that the EUT does not resume any transmissions on this Channel. Perform this test once and record the measurement result.





Figure 17: Channel Closing Transmission Time, Channel Move Time and Non-Occupancy Period

Conducted test setup



Setup for Client with injection at the Master

Equipment Used: Refer to section 3 for details.

Test Result: Please refer to Appendix A

The measurement data as follows:

5.9 AC POWER LINE CONDUCTED EMISSION

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(6)
FCC 47 CFR Part 15 Subpart C Section 15.207
RSS-Gen Issue 5, Section 8.8

Test Method: ANSI C63.10-2013, Section 6.2.

Limits:

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.5.2 for details.

Test Procedures:

Test frequency range :150KHz-30MHz

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The worst measurement data as follows:

Quasi Peak and Average:

Mode: WIFI Link

Live Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.1544	29.72	9.86	39.58	65.76	-26.18	QP
2	0.1544	11.02	9.86	20.88	55.76	-34.88	AVG
3	0.3795	35.05	9.78	44.83	58.29	-13.46	QP
4	0.3795	28.23	9.78	38.01	48.29	-10.28	AVG
5	0.7485	29.37	9.75	39.12	56.00	-16.88	QP
6	0.7485	15.80	9.75	25.55	46.00	-20.45	AVG
7	1.5180	32.55	9.71	42.26	56.00	-13.74	QP
8	1.5180	15.66	9.71	25.37	46.00	-20.63	AVG
9	4.9785	27.26	9.75	37.01	56.00	-18.99	QP
10	4.9785	16.90	9.75	26.65	46.00	-19.35	AVG
11	6.6345	28.76	9.74	38.50	60.00	-21.50	QP
12	6.6345	17.00	9.74	26.74	50.00	-23.26	AVG

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

APPENDIX A RF TEST DATA

A1. 99% BANDWIDTH

Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	17.705	5171.1036	5188.8086	---	---
11A	Ant1	5220	17.753	5211.0168	5228.7698	---	---
11A	Ant1	5240	17.626	5231.0577	5248.6837	---	---
11A	Ant1	5260	17.757	5250.9727	5268.7297	---	---
11A	Ant1	5300	17.742	5291.0035	5308.7455	---	---
11A	Ant1	5320	17.669	5311.0443	5328.7133	---	---
11A	Ant1	5500	18.011	5490.9459	5508.9569	---	---
11A	Ant1	5580	17.870	5571.0740	5588.9440	---	---
11A	Ant1	5700	17.976	5690.9373	5708.9133	---	---
11A	Ant1	5720	17.922	5710.9962	5728.9182	---	---
11A	Ant1	5720 UNII-2C	13.155	---	---	---	---
11A	Ant1	5720 UNII-3	4.4495	---	---	---	---
11A	Ant1	5745	17.788	5736.0632	5753.8512	---	---
11A	Ant1	5785	17.962	5775.9262	5793.8882	---	---
11A	Ant1	5825	17.927	5815.9383	5833.8653	---	---
11N20SISO	Ant1	5180	18.738	5170.6284	5189.3664	---	---
11N20SISO	Ant1	5220	18.847	5210.5336	5229.3806	---	---
11N20SISO	Ant1	5240	18.794	5230.5407	5249.3347	---	---
11N20SISO	Ant1	5260	18.840	5250.5140	5269.3540	---	---
11N20SISO	Ant1	5300	18.822	5290.5448	5309.3668	---	---
11N20SISO	Ant1	5320	18.812	5310.5166	5329.3286	---	---
11N20SISO	Ant1	5500	18.949	5490.4764	5509.4254	---	---
11N20SISO	Ant1	5580	19.052	5570.4924	5589.5444	---	---
11N20SISO	Ant1	5700	19.025	5690.4884	5709.5134	---	---
11N20SISO	Ant1	5720	19.090	5710.4575	5729.5475	---	---
11N20SISO	Ant1	5720 UNII-2C	13.758	---	---	---	---
11N20SISO	Ant1	5720 UNII-3	4.4928	---	---	---	---
11N20SISO	Ant1	5745	19.044	5735.4522	5754.4962	---	---
11N20SISO	Ant1	5785	19.039	5775.4514	5794.4904	---	---
11N20SISO	Ant1	5825	19.024	5815.4323	5834.4563	---	---
11N40SISO	Ant1	5190	37.316	5171.3275	5208.6435	---	---
11N40SISO	Ant1	5230	37.166	5211.3759	5248.5419	---	---
11N40SISO	Ant1	5270	37.333	5251.2524	5288.5854	---	---
11N40SISO	Ant1	5310	37.293	5291.2528	5328.5458	---	---
11N40SISO	Ant1	5510	37.709	5491.1376	5528.8466	---	---
11N40SISO	Ant1	5550	37.699	5531.1054	5568.8044	---	---
11N40SISO	Ant1	5670	37.650	5651.2031	5688.8531	---	---
11N40SISO	Ant1	5710	37.677	5691.2084	5728.8854	---	---
11N40SISO	Ant1	5710 UNII-2C	32.835	---	---	---	---
11N40SISO	Ant1	5710 UNII-3	4.8826	---	---	---	---
11N40SISO	Ant1	5755	37.538	5736.2863	5773.8243	---	---
11N40SISO	Ant1	5795	37.594	5776.1626	5813.7566	---	---
11AC20SISO	Ant1	5180	18.732	5170.5958	5189.3278	---	---
11AC20SISO	Ant1	5220	18.852	5210.5666	5229.4186	---	---
11AC20SISO	Ant1	5240	18.847	5230.5052	5249.3522	---	---
11AC20SISO	Ant1	5260	18.817	5250.5098	5269.3268	---	---
11AC20SISO	Ant1	5300	18.746	5290.5191	5309.2651	---	---
11AC20SISO	Ant1	5320	18.768	5310.5361	5329.3041	---	---
11AC20SISO	Ant1	5500	18.986	5490.4643	5509.4503	---	---
11AC20SISO	Ant1	5580	19.045	5570.4789	5589.5239	---	---
11AC20SISO	Ant1	5700	19.026	5690.4856	5709.5116	---	---
11AC20SISO	Ant1	5720	19.043	5710.4710	5729.5140	---	---
11AC20SISO	Ant1	5720 UNII-2C	13.730	---	---	---	---
11AC20SISO	Ant1	5720 UNII-3	4.5155	---	---	---	---
11AC20SISO	Ant1	5745	19.038	5735.4812	5754.5192	---	---
11AC20SISO	Ant1	5785	19.040	5775.4515	5794.4915	---	---
11AC20SISO	Ant1	5825	19.072	5815.4033	5834.4753	---	---
11AC40SISO	Ant1	5190	37.231	5171.3727	5208.6037	---	---

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

11AC40SISO	Ant1	5230	37.224	5211.3115	5248.5355	---	---
11AC40SISO	Ant1	5270	37.344	5251.2801	5288.6241	---	---
11AC40SISO	Ant1	5310	37.244	5291.2988	5328.5428	---	---
11AC40SISO	Ant1	5510	37.625	5491.1900	5528.8150	---	---
11AC40SISO	Ant1	5550	37.595	5531.2402	5568.8352	---	---
11AC40SISO	Ant1	5670	37.638	5651.1840	5688.8220	---	---
11AC40SISO	Ant1	5710	37.619	5691.3281	5728.9471	---	---
11AC40SISO	Ant1	5710 UNII-2C	32.823	---	---	---	---
11AC40SISO	Ant1	5710 UNII-3	4.6627	---	---	---	---
11AC40SISO	Ant1	5755	37.628	5736.2268	5773.8548	---	---
11AC40SISO	Ant1	5795	37.584	5776.1941	5813.7781	---	---
11AX20SISO	Ant1	5220	19.519	5210.1888	5229.7078	---	---
11AX20SISO	Ant1	5240	19.411	5230.2778	5249.6888	---	---
11AX20SISO	Ant1	5260	19.464	5250.1713	5269.6353	---	---
11AX20SISO	Ant1	5300	19.483	5290.2058	5309.6888	---	---
11AX20SISO	Ant1	5320	19.416	5310.2700	5329.6860	---	---
11AX20SISO	Ant1	5500	19.641	5490.2042	5509.8452	---	---
11AX20SISO	Ant1	5580	19.611	5570.1952	5589.8062	---	---
11AX20SISO	Ant1	5700	19.607	5690.1891	5709.7961	---	---
11AX20SISO	Ant1	5720	19.581	5710.2102	5729.7912	---	---
11AX20SISO	Ant1	5720 UNII-2C	13.743	---	---	---	---
11AX20SISO	Ant1	5720 UNII-3	4.3225	---	---	---	---
11AX20SISO	Ant1	5745	19.618	5735.1581	5754.7761	---	---
11AX20SISO	Ant1	5785	19.624	5775.1942	5794.8182	---	---
11AX20SISO	Ant1	5825	19.625	5815.1358	5834.7608	---	---
11AX40SISO	Ant1	5190	38.276	5170.8293	5209.1053	---	---
11AX40SISO	Ant1	5230	38.346	5210.8107	5249.1567	---	---
11AX40SISO	Ant1	5270	38.325	5250.7795	5289.1045	---	---
11AX40SISO	Ant1	5310	38.340	5290.7478	5329.0878	---	---
11AX40SISO	Ant1	5510	38.591	5490.7319	5529.3229	---	---
11AX40SISO	Ant1	5550	38.611	5530.6658	5569.2768	---	---
11AX40SISO	Ant1	5670	38.505	5650.7475	5689.2525	---	---
11AX40SISO	Ant1	5710	38.541	5690.8025	5729.3435	---	---
11AX40SISO	Ant1	5710 UNII-2C	32.814	---	---	---	---
11AX40SISO	Ant1	5710 UNII-3	4.7722	---	---	---	---
11AX40SISO	Ant1	5755	38.585	5735.7401	5774.3251	---	---
11AX40SISO	Ant1	5795	38.485	5775.7743	5814.2593	---	---

Test Graphs



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1







11A-Ant1-5300




11A-Ant1-5320





11A-Ant1-5700



11A-Ant1-5720

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



11A-5720_UNII-2C

Agilent Spectrum Analyzer - Occupied BW

Center Freq 5.74000000 GHz

Center Freq: 5.74000000 GHz

Trig: Free Run

Avg|Hold> 100/100

Radio Std: None

#IFGain:Low

#Atten: 30 dB

Radio Device: BTS

Ref Offset 14.96 dB

Ref 20.00 dBm

10 dB/div

Log

Center 5.74 GHz

#Res BW 300 kHz

#VBW 910 kHz

Span 30 MHz

#Sweep 1 ms

Occupied Bandwidth

4.4495 MHz

Total Power

12.5 dBm

Transmit Freq Error

-12.773 MHz

OBW Power

99.00 %

x dB Bandwidth

5.715 MHz

x dB

-26.00 dB

MSG

STATUS

Frequency

Center Freq

5.74000000 GHz

CF Step

3.000000 MHz


Auto

Man


Freq Offset

0 Hz

11A-5720_UNII-3



11A-Ant1-5745



11A-Ant1-5785

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



11A-Ant1-5825



11N20SISO-Ant1-5180

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886


E-mail: info@uttlab.com


<http://www.uttlab.com>


UTTR-RF-RSS247-V1.1











11N20SISO-Ant1-5720 UNII-3

Agilent Spectrum Analyzer - Occupied BW

Center Freq 5.745000000 GHz

Center Freq: 5.745000000 GHz

Trig: Free Run

Avg|Hold: 500/500

Radio Std: None

Radio Device: BTS

#IFGain: Low

#Atten: 30 dB

Ref Offset 15.01 dB

Ref 20.00 dBm

10 dB/div

Log

Center 5.745 GHz

#Res BW 430 kHz

#VBW 1.3 MHz

Span 40 MHz

Sweep 1 ms

Occupied Bandwidth

19.044 MHz

Total Power

23.2 dBm

Transmit Freq Error

-25.780 kHz

OBW Power

99.00 %

x dB Bandwidth

28.39 MHz

x dB

-26.00 dB

MSG

STATUS

Frequency

Center Freq

5.745000000 GHz

CF Step

4.000000 MHz

Auto

Man

Freq Offset

0 Hz

11N20SISO-Ant1-5745

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

