

TEST REPORT

Product Name: IP Phone
Trade Mark: GRANDSTREAM
Model No. / HVIN: GRP2624
Report Number: 200829033EMC-1
Test Standards: FCC 47 CFR Part 15 Subpart B
ICES-003 Issue 6
FCC ID: YZZGRP2624
IC: 11964A-GRP2624
Test Result: PASS
Date of Issue: December 14, 2020

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park,
Qingxiang Road No.1, Longhua New District, Shenzhen, China

TEL: +86-755-2823 0888

FAX: +86-755-2823 0886

Prepared by:



Henry Lu

Team Leader

Reviewed by:



Kevin Liang

Assistant Manager

Approved by:



Billy Li

Technical Director

Date:

December 14, 2020

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Version

Version No.	Date	Description
V1.0	December 14, 2020	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 DESCRIPTION OF SUPPORT UNITS	5
1.4 TEST LOCATION	5
1.5 TEST FACILITY	5
1.6 DEVIATION FROM STANDARDS	6
1.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
1.9 MEASUREMENT UNCERTAINTY	6
2. TEST SUMMARY	7
3. EQUIPMENT LIST	7
4. TEST CONFIGURATION	8
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	8
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	8
4.1.2 RECORD OF NORMAL ENVIRONMENT	8
4.2 TEST MODES	8
4.3 TEST SETUP	9
4.3.1 FOR RADIATED EMISSIONS TEST SETUP	9
4.3.2 FOR CONDUCTED EMISSIONS TEST SETUP	10
4.4 SYSTEM TEST CONFIGURATION	10
5. REFERENCE DOCUMENTS FOR TESTING	11
6. EMC REQUIREMENTS SPECIFICATION	11
6.1 RADIATED EMISSION	11
6.2 CONDUCTED EMISSION	33
APPENDIX 1 PHOTOS OF TEST SETUP	44
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	44

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	IP Phone
Model No. / HVIN:	GRP2624
Trade Mark:	GRANDSTREAM
DUT Stage:	Production Unit
Rated Voltage:	☒ 100-240V~50/60Hz ☒ Powered by POE port
Classification of digital devices:	Class B
Highest Internal Frequency:	5825 MHz
Sample Received Date:	November 3, 2020
Sample Tested Date:	November 7, 2020 to November 8, 2020

1.2.2 Description of Accessories

Adapter(1)	
Model No.:	GQ12-120100-AU
Input:	100-240 V~50/60 Hz 0.4A Max
Output:	12.0 V $\equiv$ 1.0 A
DC Cable:	2.5 Meter, Unshielded without ferrite

Adapter(2)	
Model No.:	DSA-12PFU-12 FUS 120100
Input:	100-240 V~50/60 Hz 0.5A
Output:	12.0 V $\equiv$ 1.0 A
DC Cable:	2.5 Meter, Unshielded without ferrite

Adapter(3)	
Model No.:	F12US1200100A
Input:	100-240 V~50/60 Hz 0.5A Max
Output:	12.0 V $\equiv$ 1.0 A
DC Cable:	2.5 Meter, Unshielded without ferrite

Cable(1)	
Connector:	Ethernet Cable
Cable Type:	Unshielded without ferrite
Length:	1.5 Meter

Cable(2)	
Connector:	Phone Cord
Cable Type:	Unshielded without ferrite
Length:	3.5 Meter

Others
1x Handset, 1x Phone Stand

1.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	Lenovo	B40-80	MP12NEQ6	UnionTrust
USB disk	Kingston	DTSE9	N/A	UnionTrust
Mouse	DELL	MS111	CN-011D3V-738	UnionTrust
Headset	YEE	VE120-MV	N/A	UnionTrust
Standard POE Power supply	TP-LINK	TL-POE160S	N/A	UnionTrust
IP Phone	GRANDSTREAM	GRP2634	N/A	Applicant
(Expansion Module)*4	GRANDSTREAM	GBX20	N/A	Applicant

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Ethernet Cable	RJ45	1.5 Unshielded without ferrite	UnionTrust
2	Ethernet Cable	RJ45	2.0 Unshielded without ferrite	UnionTrust
3	Ethernet Cable	RJ45	5.0 Unshielded without ferrite	UnionTrust

1.4 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.5 TEST FACILITY

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.6 DEVIATION FROM STANDARDS

None.

1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.9 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	±3.2 dB
2	Conducted emission 150KHz-30MHz	±2.7 dB
3	Radiated emission 9KHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.6 dB
5	Radiated emission 1GHz-18GHz	± 4.4 dB
6	Radiated emission 18GHz-26GHz	± 4.6 dB
7	Radiated emission 26GHz-40GHz	± 4.6 dB

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart B Test Cases			
Test Item	Test Requirement	Test Method	Result
Conducted Emission	FCC 47 CFR Part 15.107 ICES-003 Issue 6 Section 6.1	ANSI C63.4-2014	PASS
Radiated Emission	FCC 47 CFR Part 15.109 ICES-003 Issue 6 Section 6.2	ANSI C63.4-2014	PASS

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	3M Chamber & Accessory Equipment	ETS-LINDGREN	3M	N/A	Dec. 03, 2018	Dec. 03, 2021
☒	Receiver	R&S	ESIB26	100114	Nov. 24, 2019	Nov. 23, 2020
☐	Loop Antenna	ETS-LINDGREN	6502	00202525	Nov. 16, 2019	Nov. 15, 2020
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Nov. 16, 2019	Nov. 15, 2020
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	Nov. 16, 2019	Nov. 15, 2020
☒	Preamplifier	HP	8447F	2805A02960	Nov. 24, 2019	Nov. 23, 2020
☐	Broadband Antenna (Pre-amplifier)	ETS-LINDGREN	3142E-PA	00201891	Nov. 24, 2019	Nov. 23, 2020
☐	6dB Attenuator	Talent	RA6A5-N-18	18103002	Nov. 24, 2019	Nov. 23, 2020
☐	Horn Antenna	ETS-LINDGREN	3117	00164202	Nov. 16, 2019	Nov. 15, 2020
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201874	May. 30, 2020	May. 29, 2021
☐	Horn Antenna	ETS-LINDGREN	3116C	00200180	Jun. 19, 2020	Jun. 18, 2021
☐	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Nov. 16, 2019	Nov. 15, 2020
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☐	Highpass Filter (1.2GHz~18GHz)	Micro-Tronics	HPM50108	G552	Nov. 24, 2019	Nov. 23, 2020
☐	Highpass Filter (3GHz~18GHz)	Micro-Tronics	HPM50117	G005	Nov. 24, 2019	Nov. 23, 2020
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	Receiver	R&S	ESR7	1316.3003K07-101181-K3	Nov. 24, 2019	Nov. 23, 2020
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	Nov. 24, 2019	Nov. 23, 2020
☒	LISN	R&S	ESH2-Z5	860014/024	Nov. 24, 2019	Nov. 23, 2020
☒	LISN	ETS-Lindgren	3816/2SH	00201088	Nov. 24, 2019	Nov. 23, 2020
☒	Test Software	Audix	e3	Software Version: 9.160323		

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NT/NV	+15 to +35	Powered by POE Port or Powered by DC 12V/1.0A	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Tested by
Conducted Emission	24.6	56	99.75	Tripp Jiang
Radiated Emission	25.6	57	100.62	Fire Huo

4.2 TEST MODES

Test Item	EMI Test Modes
Radiated Emission	TM1: AC120V/60Hz (Adaptor1) + Hands Free TM2: AC120V/60Hz (Adaptor1) + Ringing TM3: AC120V/60Hz (Adaptor1) + Handset TM4: AC120V/60Hz (Adaptor1) + Headset TM5: AC240V/50Hz (Adaptor1) + Worse from mode 1~4 TM6: Worse from mode 1~5 (Adaptor2) TM7: Worse from mode 1~5 (Adaptor3) TM8: AC120V/60Hz (POE) +Worse from mode 1~4 TM9: Worse from mode 1~8 + Expansion Module x 4
Conducted Emission	TM1: AC120V/60Hz (Adaptor1) + Hands Free TM2: AC120V/60Hz (Adaptor1) + Ringing TM3: AC120V/60Hz (Adaptor1) + Handset TM4: AC120V/60Hz (Adaptor1) + Headset TM5: AC240V/50Hz (Adaptor1) + Worse from mode 1~4 TM6: Worse from mode 1~5 (Adaptor2) TM7: Worse from mode 1~5 (Adaptor3) TM8: AC120V/60Hz (POE) +Worse from mode 1~4 TM9: Worse from mode 1~8 + Expansion Module x 4
Remark: The above test modes in boldface were the worst cases.	

4.3 TEST SETUP

4.3.1 For Radiated Emissions test setup

Figure 1. 30MHz to 1GHz






Figure 2. Above 1GHz



4.3.2 For Conducted Emissions test setup

Figure 3. Conducted Emissions setup



4.4 SYSTEM TEST CONFIGURATION

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1 MHz or greater for frequencies above 1000MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic (according to KDB 896810 D02 SDoC FAQ v01r01) of the highest fundamental frequency or to 40 GHz, whichever is lower.

5. REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part15 Subpart B	Unintentional Radiators
2	ICES-003 Issue 6	Information Technology Equipment (Including Digital Apparatus) —Limits and Methods of Measurement
3	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
4	KDB 174176 D01 Line Conducted FAQ v01r01	AC power-line conducted emission frequency asked questions
5	KDB 896810 D02 SDoC FAQ v01r02	Supplier's Declaration of Conformity frequency asked questions

6. EMC REQUIREMENTS SPECIFICATION

6.1 RADIATED EMISSION

Test Requirement: FCC 47 CFR Part 15.109
ICES-003 Issue 6 Clause 6.2

Test Method: ANSI C63.4-2014

Receiver Setup:

Frequency: (f) (MHz)	Detector type	Measurement receiver bandwidth	
		RBW	VBW
$30 \leq f \leq 1\,000$	Quasi Peak	120 kHz	300 kHz
$f \geq 1000$	Peak	1 MHz	3 MHz
	Average	1 MHz	3 MHz

Measured frequency range

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705-108	1000.
108-500	2000.
500-1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Limits:

Limits for Class B devices

Frequency (MHz)	limits at 3m (dB μ V/m)		
	QP Detector	PK Detector	AV Detector
30-88	40.0	--	--
88-216	43.5	--	--
216-960	46.0	--	--
960 to 1000	54.0	--	--
Above 1000	--	74.0	54.0

Remark:

- The lower limit shall apply at the transition frequencies.
- Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
- For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Test Setup: Refer to section 4.3.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:

- 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
- 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 120 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- 3) For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.

2. Above 1GHz test procedure as below:

- 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
- 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 1MHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- 3) For each frequency whose maximum record was higher or close to limit, measure its AV value: rotate the turntable from 0 to 360 degrees to find the degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to AV value and specified bandwidth with Maximum Hold Mode, and record the maximum value.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The measurement data as follows:

Below 1GHz(Quasi Peak):


Mode3

Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	86.080	47.87	-13.36	34.51	40.00	-5.49	QP
2	92.997	52.36	-12.87	39.49	43.50	-4.01	QP
3	110.858	52.73	-12.41	40.32	43.50	-3.18	QP
4	245.261	38.29	-7.43	30.86	46.00	-15.14	QP
5	590.351	37.49	0.56	38.05	46.00	-7.95	QP
6	821.387	31.80	3.95	35.75	46.00	-10.25	QP

Vertical



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	31.292	39.97	-5.98	33.99	40.00	-6.01	QP
2	92.997	51.71	-12.87	38.84	43.50	-4.66	QP
3	106.281	52.81	-12.36	40.45	43.50	-3.05	QP
4	250.486	39.36	-7.13	32.23	46.00	-13.77	QP
5	590.351	39.06	0.21	39.27	46.00	-6.73	QP
6	815.635	37.38	3.60	40.98	46.00	-5.02	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Below 1GHz(Quasi Peak):
Mode6
Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	47.703	34.94	-13.34	21.60	40.00	-18.40	QP
2	90.420	38.04	-13.08	24.96	43.50	-18.54	QP
3	243.543	39.05	-7.54	31.51	46.00	-14.49	QP
4	502.247	37.33	-1.55	35.78	46.00	-10.22	QP
5	739.214	34.25	2.78	37.03	46.00	-8.97	QP
6	887.398	32.74	4.89	37.63	46.00	-8.37	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Vertical



No.	Frequency (MHz)	Reading (dB μ V/m)	Correction factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	31.073	35.60	-5.85	29.75	40.00	-10.25	QP
2	50.461	44.24	-14.64	29.60	40.00	-10.40	QP
3	94.314	47.62	-12.76	34.86	43.50	-8.64	QP
4	98.375	47.28	-12.42	34.86	43.50	-8.64	QP
5	250.486	37.47	-7.13	30.34	46.00	-15.66	QP
6	590.351	40.24	0.21	40.45	46.00	-5.55	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Below 1GHz(Quasi Peak):
Mode7
Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	33.335	29.09	-7.11	21.98	40.00	-18.02	QP
2	243.543	38.47	-7.54	30.93	46.00	-15.07	QP
3	502.247	35.76	-1.55	34.21	46.00	-11.79	QP
4	590.351	33.15	0.56	33.71	46.00	-12.29	QP
5	739.214	33.46	2.78	36.24	46.00	-9.76	QP
6	887.398	33.96	4.89	38.85	46.00	-7.15	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Vertical



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	32.411	36.81	-6.67	30.14	40.00	-9.86	QP
2	51.176	41.15	-14.62	26.53	40.00	-13.47	QP
3	94.314	48.04	-12.76	35.28	43.50	-8.22	QP
4	106.281	47.35	-12.36	34.99	43.50	-8.51	QP
5	590.351	39.90	0.21	40.11	46.00	-5.89	QP
6	906.304	35.40	5.11	40.51	46.00	-5.49	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Below 1GHz(Quasi Peak):
Mode8
Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.425	40.48	-5.70	34.78	40.00	-5.22	QP
2	39.459	44.91	-10.07	34.84	40.00	-5.16	QP
3	162.020	43.77	-10.35	33.42	43.50	-10.08	QP
4	296.502	44.17	-5.86	38.31	46.00	-7.69	QP
5	804.252	33.36	3.99	37.35	46.00	-8.65	QP
6	1000.000	34.87	6.44	41.31	54.00	-12.69	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Vertical



No.	Frequency (MHz)	Reading (dB μ V/m)	Correction factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	30.639	39.88	-5.59	34.29	40.00	-5.71	QP
2	39.459	45.07	-11.00	34.07	40.00	-5.93	QP
3	298.593	39.97	-5.81	34.16	46.00	-11.84	QP
4	398.296	38.04	-3.09	34.95	46.00	-11.05	QP
5	590.351	40.73	0.21	40.94	46.00	-5.06	QP
6	1000.000	37.23	5.64	42.87	54.00	-11.13	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Below 1GHz(Quasi Peak):
Mode9
Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	107.785	52.13	-12.37	39.76	43.50	-3.74	QP
2	120.612	53.06	-12.59	40.47	43.50	-3.03	QP
3	240.144	45.60	-7.74	37.86	46.00	-8.14	QP
4	754.963	39.01	2.96	41.97	46.00	-4.03	QP
5	815.635	38.61	3.96	42.57	46.00	-3.43	QP
6	965.474	34.60	6.52	41.12	54.00	-12.88	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Vertical



No.	Frequency (MHz)	Reading (dB μ V/m)	Correction factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	53.006	50.03	-14.59	35.44	40.00	-4.56	QP
2	59.313	50.06	-14.48	35.58	40.00	-4.42	QP
3	80.804	49.83	-13.69	36.14	40.00	-3.86	QP
4	106.281	52.07	-12.36	39.71	43.50	-3.79	QP
5	754.963	40.00	1.48	41.48	46.00	-4.52	QP
6	965.474	36.88	5.39	42.27	54.00	-11.73	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Above 1GHz(Peak & Average)
Mode3
Horizontal



No.	Frequency (MHz)	Reading (dB μ V/m)	Correction factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	1992.295	55.86	-9.89	45.97	74.00	-28.03	Peak
2	2384.166	57.26	-9.22	48.04	74.00	-25.96	Peak
3	2936.954	50.40	-7.48	42.92	74.00	-31.08	Peak
4	7726.777	45.01	1.66	46.67	74.00	-27.33	Peak
5	12715.630	41.01	9.48	50.49	74.00	-23.51	Peak
6	17385.170	40.34	13.42	53.76	74.00	-20.24	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Vertical



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1000.000	56.53	-10.81	45.72	74.00	-28.28	Peak
2	2185.761	54.62	-10.14	44.48	74.00	-29.52	Peak
3	2384.166	53.32	-9.65	43.67	74.00	-30.33	Peak
4	4109.610	48.17	-4.00	44.17	74.00	-29.83	Peak
5	12424.410	40.97	9.12	50.09	74.00	-23.91	Peak
6	16217.810	39.91	12.16	52.07	74.00	-21.93	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Above 1GHz(Peak & Average)
Mode6
Horizontal



No.	Frequency (MHz)	Reading (dB μ V/m)	Correction factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	1992.295	56.98	-9.89	47.09	74.00	-26.91	Peak
2	2384.166	55.90	-9.22	46.68	74.00	-27.32	Peak
3	6345.543	45.92	-0.23	45.69	74.00	-28.31	Peak
4	7682.150	44.58	1.57	46.15	74.00	-27.85	Peak
5	12715.630	39.67	9.48	49.15	74.00	-24.85	Peak
6	16124.140	39.05	11.78	50.83	74.00	-23.17	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Vertical



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1795.036	53.79	-11.47	42.32	74.00	-31.68	Peak
2	2173.137	56.21	-10.16	46.05	74.00	-27.95	Peak
3	2263.061	55.58	-9.97	45.61	74.00	-28.39	Peak
4	4109.610	47.66	-4.00	43.66	74.00	-30.34	Peak
5	5554.060	45.26	-0.38	44.88	74.00	-29.12	Peak
6	17385.170	38.93	13.46	52.39	74.00	-21.61	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Above 1GHz(Peak & Average)
Mode7
Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1260.733	54.36	-11.68	42.68	74.00	-31.32	Peak
2	1992.295	55.85	-9.89	45.96	74.00	-28.04	Peak
3	2384.166	56.97	-9.22	47.75	74.00	-26.25	Peak
4	10442.590	44.18	5.68	49.86	74.00	-24.14	Peak
5	12424.410	41.53	8.82	50.35	74.00	-23.65	Peak
6	16694.370	38.67	12.41	51.08	74.00	-22.92	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0



Above 1GHz(Peak & Average)
Mode8
Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1795.036	54.21	-10.81	43.40	74.00	-30.60	Peak
2	1980.788	53.97	-9.92	44.05	74.00	-29.95	Peak
3	2384.166	57.01	-9.22	47.79	74.00	-26.21	Peak
4	10144.500	42.51	5.33	47.84	74.00	-26.16	Peak
5	12569.170	39.96	9.18	49.14	74.00	-24.86	Peak
6	16791.350	38.92	12.34	51.26	74.00	-22.74	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Above 1GHz(Peak & Average)
Mode9
Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1992.295	57.23	-9.89	47.34	74.00	-26.66	Peak
2	2384.166	56.70	-9.22	47.48	74.00	-26.52	Peak
3	7291.932	44.87	0.95	45.82	74.00	-28.18	Peak
4	12424.410	40.07	8.82	48.89	74.00	-25.11	Peak
5	14612.070	37.47	12.50	49.97	74.00	-24.03	Peak
6	16791.350	38.73	12.34	51.07	74.00	-22.93	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Vertical



No.	Frequency (MHz)	Reading (dB μ V/m)	Correction factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	1000.000	56.59	-10.81	45.78	74.00	-28.22	Peak
2	1764.113	57.39	-11.69	45.70	74.00	-28.30	Peak
3	2211.230	56.16	-10.09	46.07	74.00	-27.93	Peak
4	4109.610	46.95	-4.00	42.95	74.00	-31.05	Peak
5	9854.908	42.40	5.35	47.75	74.00	-26.25	Peak
6	16502.090	38.58	12.86	51.44	74.00	-22.56	Peak

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.
5. For Radiated Emission above 18GHz, there was not any unwanted emission detected.
6. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

6.2 CONDUCTED EMISSION

Test Requirement: FCC 47 CFR Part 15.107
ICES-003 Issue 6 Section 6.1

Test Method: ANSI C63.4-2014

Limits:

Limits for Class B devices

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.3.2 for details.

Test Procedures:

- 1) The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- 2) The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- 3) For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The measurement data as follows:

Quasi Peak and Average:

Mode 2

Live Line



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.150	23.96	9.03	32.99	56.00	-23.01	Average
2	0.150	43.39	9.03	52.42	66.00	-13.58	QP
3	0.222	19.00	9.09	28.09	52.74	-24.65	Average
4	0.222	35.50	9.09	44.59	62.74	-18.15	QP
5	0.450	23.46	9.25	32.71	46.88	-14.17	Average
6	0.450	30.75	9.25	40.00	56.88	-16.88	QP
7	0.494	19.60	9.33	28.93	46.10	-17.17	Average
8	0.494	29.66	9.33	38.99	56.10	-17.11	QP
9	3.278	18.13	9.62	27.75	46.00	-18.25	Average
10	3.278	28.44	9.62	38.06	56.00	-17.94	QP
11	5.146	15.80	9.63	25.43	50.00	-24.57	Average
12	5.146	29.48	9.63	39.11	60.00	-20.89	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Mode 6

Live Line



No.	Frequency (MHz)	Reading (dB μ V)	Correction factor (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)	Detector
1	0.274	27.57	9.17	36.74	51.00	-14.26	Average
2	0.274	37.76	9.17	46.93	61.00	-14.07	QP
3	0.438	25.90	9.23	35.13	47.10	-11.97	Average
4	0.438	36.39	9.23	45.62	57.10	-11.48	QP
5	0.494	25.11	9.30	34.41	46.10	-11.69	Average
6	0.494	36.71	9.30	46.01	56.10	-10.09	QP
7	4.318	21.60	9.62	31.22	46.00	-14.78	Average
8	4.318	36.97	9.62	46.59	56.00	-9.41	QP
9	5.194	20.98	9.64	30.62	50.00	-19.38	Average
10	5.194	37.29	9.64	46.93	60.00	-13.07	QP
11	20.197	37.71	9.98	47.69	50.00	-2.31	Average
12	20.197	41.67	9.98	51.65	60.00	-8.35	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.274	24.45	9.15	33.60	51.00	-17.40	Average
2	0.274	37.85	9.15	47.00	61.00	-14.00	QP
3	0.494	21.95	9.33	31.28	46.10	-14.82	Average
4	0.494	34.47	9.33	43.80	56.10	-12.30	QP
5	1.586	22.01	9.53	31.54	46.00	-14.46	Average
6	1.586	35.30	9.53	44.83	56.00	-11.17	QP
7	2.406	19.34	9.60	28.94	46.00	-17.06	Average
8	2.406	34.24	9.60	43.84	56.00	-12.16	QP
9	5.522	18.68	9.64	28.32	50.00	-21.68	Average
10	5.522	33.47	9.64	43.11	60.00	-16.89	QP
11	17.693	36.98	9.93	46.91	50.00	-3.09	Average
12	17.693	43.39	9.93	53.32	60.00	-6.68	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Mode 7

Live Line



No.	Frequency (MHz)	Reading (dB μ V)	Correction factor (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)	Detector
1	0.162	21.54	9.04	30.58	55.36	-24.78	Average
2	0.162	36.35	9.04	45.39	65.36	-19.97	QP
3	0.274	24.13	9.17	33.30	51.00	-17.70	Average
4	0.274	33.91	9.17	43.08	61.00	-17.92	QP
5	0.338	24.67	9.19	33.86	49.25	-15.39	Average
6	0.338	33.77	9.19	42.96	59.25	-16.29	QP
7	0.490	22.87	9.30	32.17	46.17	-14.00	Average
8	0.490	30.99	9.30	40.29	56.17	-15.88	QP
9	1.134	19.19	9.43	28.62	46.00	-17.38	Average
10	1.134	31.52	9.43	40.95	56.00	-15.05	QP
11	10.029	19.62	9.67	29.29	50.00	-20.71	Average
12	10.029	26.96	9.67	36.63	60.00	-23.37	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.154	17.32	9.03	26.35	55.78	-29.43	Average
2	0.154	39.43	9.03	48.46	65.78	-17.32	QP
3	0.334	24.41	9.17	33.58	49.35	-15.77	Average
4	0.334	33.84	9.17	43.01	59.35	-16.34	QP
5	0.490	19.67	9.32	28.99	46.17	-17.18	Average
6	0.490	29.27	9.32	38.59	56.17	-17.58	QP
7	1.134	16.73	9.43	26.16	46.00	-19.84	Average
8	1.134	28.08	9.43	37.51	56.00	-18.49	QP
9	1.586	14.86	9.53	24.39	46.00	-21.61	Average
10	1.586	26.44	9.53	35.97	56.00	-20.03	QP
11	10.253	16.80	9.68	26.48	50.00	-23.52	Average
12	10.253	24.12	9.68	33.80	60.00	-26.20	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Mode 8

Live Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.162	40.62	9.04	49.66	55.36	-5.70	Average
2	0.162	52.46	9.04	61.50	65.36	-3.86	QP
3	0.274	33.26	9.17	42.43	51.00	-8.57	Average
4	0.274	44.92	9.17	54.09	61.00	-6.91	QP
5	0.330	33.70	9.19	42.89	49.45	-6.56	Average
6	0.330	44.79	9.19	53.98	59.45	-5.47	QP
7	0.398	29.70	9.18	38.88	47.90	-9.02	Average
8	0.398	45.17	9.18	54.35	57.90	-3.55	QP
9	0.498	33.11	9.31	42.42	46.03	-3.61	Average
10	0.498	44.71	9.31	54.02	56.03	-2.01	QP
11	8.789	29.42	9.68	39.10	50.00	-10.90	Average
12	8.789	40.13	9.68	49.81	60.00	-10.19	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Neutral Line



No.	Frequency (MHz)	Reading (dB μ V)	Correction factor (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)	Detector
1	0.166	38.99	9.05	48.04	55.16	-7.12	Average
2	0.166	51.99	9.05	61.04	65.16	-4.12	QP
3	0.246	29.87	9.12	38.99	51.89	-12.90	Average
4	0.246	43.69	9.12	52.81	61.89	-9.08	QP
5	0.274	31.62	9.15	40.77	51.00	-10.23	Average
6	0.274	43.06	9.15	52.21	61.00	-8.79	QP
7	0.334	28.15	9.17	37.32	49.35	-12.03	Average
8	0.334	42.22	9.17	51.39	59.35	-7.96	QP
9	0.490	29.76	9.32	39.08	46.17	-7.09	Average
10	0.490	41.18	9.32	50.50	56.17	-5.67	QP
11	8.797	31.67	9.67	41.34	50.00	-8.66	Average
12	8.797	42.36	9.67	52.03	60.00	-7.97	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Mode 9

Live Line



No.	Frequency (MHz)	Reading (dB μ V)	Correction factor (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)	Detector
1	0.162	41.76	9.04	50.80	55.36	-4.56	Average
2	0.162	50.37	9.04	59.41	65.36	-5.95	QP
3	0.242	36.39	9.13	45.52	52.03	-6.51	Average
4	0.242	44.84	9.13	53.97	62.03	-8.06	QP
5	0.326	36.07	9.19	45.26	49.55	-4.29	Average
6	0.326	42.91	9.19	52.10	59.55	-7.45	QP
7	0.486	33.10	9.29	42.39	46.24	-3.85	Average
8	0.486	40.91	9.29	50.20	56.24	-6.04	QP
9	1.062	29.38	9.42	38.80	46.00	-7.20	Average
10	1.062	37.23	9.42	46.65	56.00	-9.35	QP
11	9.117	32.49	9.68	42.17	50.00	-7.83	Average
12	9.117	41.74	9.68	51.42	60.00	-8.58	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.166	39.93	9.05	48.98	55.16	-6.18	Average
2	0.166	50.88	9.05	59.93	65.16	-5.23	QP
3	0.246	33.07	9.12	42.19	51.89	-9.70	Average
4	0.246	43.41	9.12	52.53	61.89	-9.36	QP
5	0.326	33.12	9.17	42.29	49.55	-7.26	Average
6	0.326	43.52	9.17	52.69	59.55	-6.86	QP
7	0.486	30.79	9.32	40.11	46.24	-6.13	Average
8	0.486	41.78	9.32	51.10	56.24	-5.14	QP
9	1.154	27.49	9.44	36.93	46.00	-9.07	Average
10	1.154	36.15	9.44	45.59	56.00	-10.41	QP
11	9.289	33.92	9.66	43.58	50.00	-6.42	Average
12	9.289	43.30	9.66	52.96	60.00	-7.04	QP

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.
5. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.0

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix for EUT external and internal photographs.

***** End of Report *****

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
