



Certificate #4312.01

FCC & ISCED TEST REPORT

Product Name: IP Phone
Trade Mark: GRANDSTREAM
Model No. / HVIN: GRP2650
Report Number: 220218001EMC-1
Test Standards: FCC 47 CFR Part 15 Subpart B
ICES-003 Issue 7
Test Result: PASS
Date of Issue: June 20, 2022

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and
technology park, Longhua district, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:

Calvin Chen
Senior Project Engineer

Reviewed by:

Eric Yu
Project Supervisor

Approved by:

Certified
Kevin Liang
Assistant Manager

Date:

June 20, 2022

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Version

Version No.	Date	Description
V1.0	June 20, 2022	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 DESCRIPTION OF SUPPORT UNITS	5
1.4 TEST LOCATION	5
1.5 TEST FACILITY	6
1.6 DEVIATION FROM STANDARDS	6
1.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
1.9 MEASUREMENT UNCERTAINTY	6
2. TEST SUMMARY	7
3. EQUIPMENT LIST	8
4. TEST CONFIGURATION	9
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	9
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	9
4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE	9
4.2 TEST MODES	9
4.3 TEST SETUP	10
4.3.1 FOR RADIATED EMISSIONS TEST SETUP	10
4.3.2 FOR CONDUCTED EMISSIONS TEST SETUP	11
4.4 SYSTEM TEST CONFIGURATION	11
5. REFERENCE DOCUMENTS FOR TESTING	12
6. EMC REQUIREMENTS SPECIFICATION	12
6.1 RADIATED EMISSION	12
6.2 CONDUCTED EMISSION	26
APPENDIX 1 PHOTOS OF TEST SETUP	31
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	31

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	IP Phone
Model No. / HVIN:	GRP2650
Trade Mark:	GRANDSTREAM
DUT Stage:	Identical Prototype
Rated Voltage:	☒ 100-240V~50/60Hz ☒ Powered by POE port
Classification of digital devices:	Class B
Highest Internal Frequency:	5825 MHz
Software Version:	1.0.7.9 (Provided by the customer)
Hardware Version:	V1.1 (Provided by the customer)
Sample Received Date:	February 18, 2022
Sample Tested Date:	March 31, 2022 to May 20, 2022

1.2.2 Description of Accessories

Adapter (1)	
Model No.:	F12US1200100A
Input:	100-240 V~50/60 Hz 0.5A max
Output:	12 V $\Rightarrow$ 1.0 A
DC Cable:	2.5 Meter, Unshielded without ferrite

Adapter (2)	
Model No.:	GQ12-120100-AU
Input:	100-240 V~50/60 Hz 0.4A Max
Output:	12 V $\Rightarrow$ 1.0 A
DC Cable:	2.5 Meter, Unshielded without ferrite

Adapter (3)	
Model No.:	DSA-12PFU-12 FUS 120100
Input:	100-240 V~50/60 Hz 0.5A
Output:	12 V $\Rightarrow$ 1.0 A 12.0W
DC Cable:	2.5 Meter, Unshielded without ferrite

Cable (1)	
Connector:	Ethernet Cable
Cable Type:	Unshielded without ferrite
Length:	1.5 Meter

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Cable (2)	
Connector:	Phone Cord
Cable Type:	Unshielded without ferrite
Length:	3.5 Meter

Others
1x Handset, 1x Phone Stand

1.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	Lenovo	B40-80	MP12NEQ6	UnionTrust
Notebook Adapter	Lenovo	ADLX65NLC3A	5A10J75114	UnionTrust
Mouse	DELL	MS111	CN-011D3V-738	UnionTrust
Headset	YEY	VE120-MV	N/A	UnionTrust
Standard POE Power supply	Social	TL-POE160SN/A	N/A	UnionTrust
IP Phone	GRANDSTREAM	GRP2615	N/A	Applicant
Expansion Module	GRANDSTREAM	GBX20	N/A	Applicant

2) Support Cable

Cable No.	Description	Connector	Length (m)	Supplied by
1	Ethernet Cable	RJ45	1.5 Unshielded without ferrite	Applicant
2	Ethernet Cable	RJ45	2.0 Unshielded without ferrite	UnionTrust
3	Ethernet Cable	RJ45	5.0 Unshielded without ferrite	UnionTrust
4	USB Micro-B Plug Cable	USB	0.2 Shielded without ferrite	Applicant

1.4 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

1.5 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.6 DEVIATION FROM STANDARDS

None.

1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.9 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	±3.2 dB
2	Conducted emission 150KHz-30MHz	±2.7 dB
3	Radiated emission 9KHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.6 dB
5	Radiated emission 1GHz-18GHz	± 4.4 dB
6	Radiated emission 18GHz-26GHz	± 4.6 dB
7	Radiated emission 26GHz-40GHz	± 4.6 dB

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart B Test Cases			
Test Item	Test Requirement	Test Method	Result
Conducted Emission	FCC 47 CFR Part 15.107 ICES-003 Issue 7 Section 3.2.1	ANSI C63.4-2014	PASS
Radiated Emission	FCC 47 CFR Part 15.109 ICES-003 Issue 7 Section 3.2.2	ANSI C63.4-2014	PASS

3. EQUIPMENT LIST

Radiated Emission Test - 3M Chamber						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	3m Chamber & Accessory Equipment	ETS-Lindgren	3m	Euroshiedpn-CT001270-1317	22-Jan-2021	21-Jan-2024
☒	Broadband Antenna	ETS-Lindgren	3142E	00201566	11-Nov-2021	10-Nov-2023
☒	Pre-amplifier	ETS-Lindgren	118490	00204683	6-Nov-2021	5-Nov-2022
☒	Double-Ridged Waveguide Horn Antenna	ETS-Lindgren	3117	00164202	11-Nov-2021	10-Nov-2023
☒	Pre-amplifier	ETS-Lindgren	118385	00201874	6-Nov-2021	5-Nov-2022
☒	Double-Ridged Waveguide Horn Antenna	ETS-Lindgren	3116C	00200180	19-Jun-2020	18-Jun-2022
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-Lindgren	3116C-PA	00202652	14-Nov-2020	13-Nov-2022
☒	Receiver	ROHDE & SCHWARZ	ESIB26	100114	5-Nov-2021	4-Nov-2022
☒	Pre-amplifier	HP	8447F	2805A02960	5-Nov-2021	4-Nov-2022
☒	Multi device Controller	ETS-Lindgren	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	LISN	R&S	ESH2-Z5	860014/024	5-Nov-2021	4-Nov-2022
☒	LISN	ETS-Lindgren	3816/2SH	00201088	5-Nov-2021	4-Nov-2022
☒	Receiver	R&S	ESR7	101181	5-Nov-2021	4-Nov-2022
☒	Shielding room	ETS-Lindgren	843	Euroshiedpn-CT001270-1246	5-Nov-2021	4-Nov-2024
☒	Test Software	Audix	e3	Software Version: 9.160323		

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NT/NV	+15 to +35	120V~ 60Hz 230V~ 50Hz	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test Sample

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (Kpa)	Sample No.	Tested by
Conducted Emission	25.2	49	101.1	220218001-A01/3	David Zhang
Radiated Emission	24.2	53	100.1	220218001-A01/3	Lucas Ouyang

4.2 TEST MODES

Test Item	EMI Test Modes
Radiated Emission	Test Mode1: AC120V/60Hz (Adaptor 1) +PC Port Link+ LAN Port Link + Expansion Module Link (USB Port) + Headset Link + Hands Free Test Mode 2: AC120V/60Hz (Adaptor 1) +PC Port Link+ LAN Port Link + Expansion Module Link (USB Port) + Headset Link + Ringing Test Mode 3: AC120V/60Hz (Adaptor 1) +PC Port Link+ LAN Port Link + Expansion Module Link (USB Port) + Headset Link + Handset Test Mode 4: AC120V/60Hz (Adaptor 1) +PC Port Link+ LAN Port Link + Expansion Module Link (USB Port) + Headset Link + Headset Test Mode 5: AC240V/50Hz (Adaptor 1) + Worse from mode 1 Test Mode 6: Worse from mode 1 (Adaptor 2) Test Mode 7: Worse from mode 1 (Adaptor 3) Test Mode 8: AC120V/60Hz (POE) + Worse from mode 1 Test Mode 9: AC240V/50Hz (POE) + Worse from mode 1
Conducted Emission	Test Mode1: AC120V/60Hz (Adaptor 1) +PC Port Link+ LAN Port Link + Expansion Module Link (USB Port) + Headset Link + Hands Free Test Mode 2: AC120V/60Hz (Adaptor 1) +PC Port Link+ LAN Port Link + Expansion Module Link (USB Port) + Headset Link + Ringing Test Mode 3: AC120V/60Hz (Adaptor 1) +PC Port Link+ LAN Port Link + Expansion Module Link (USB Port) + Headset Link + Handset Test Mode 4: AC120V/60Hz (Adaptor 1) +PC Port Link+ LAN Port Link + Expansion Module Link (USB Port) + Headset Link + Headset Test Mode 5: AC240V/50Hz (Adaptor 1) + Worse from mode 2 Test Mode 6: Worse from mode 2 (Adaptor 2) Test Mode 7: Worse from mode2 (Adaptor 3) Test Mode 8: AC120V/60Hz (POE) + Worse from mode 2 Test Mode 9: AC240V/50Hz (POE) + Worse from mode 2
Remark: The above test modes in boldface were the worst cases	

4.3 TEST SETUP

4.3.1 For Radiated Emissions test setup

Figure 1. 30MHz to 1GHz






Figure 2. Above 1GHz



4.3.2 For Conducted Emissions test setup

Figure 3. Conducted Emissions setup



4.4 SYSTEM TEST CONFIGURATION

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1 MHz or greater for frequencies above 1000MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic (according to KDB 896810 D02 SDoC FAQ v01r01) of the highest fundamental frequency or to 40 GHz, whichever is lower.

5. REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part15 Subpart B	Unintentional Radiators
2	ICES-003 Issue 7	Information Technology Equipment (Including Digital Apparatus)
3	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
4	KDB 174176 D01 Line Conducted FAQ v01r01	AC power-line conducted emission frequency asked questions
5	KDB 896810 D02 SDoC FAQ v01r02	Supplier's Declaration of Conformity frequency asked questions

6. EMC REQUIREMENTS SPECIFICATION

6.1 RADIATED EMISSION

Test Requirement: FCC 47 CFR Part 15.109
ICES-003 Issue 7 Clause 3.2.2

Test Method: ANSI C63.4-2014

Receiver Setup:

Frequency: (f) (MHz)	Detector type	Measurement receiver bandwidth	
		RBW	VBW
$30 \leq f \leq 1\,000$	Quasi Peak	120 kHz	300 kHz
$f \geq 1000$	Peak	1 MHz	3 MHz
	Average	1 MHz	3 MHz

Measured frequency range

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705-108	1000.
108-500	2000.
500-1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Limits:

Limits for Class B devices

FCC 47 CFR Part 15 Subpart B

Frequency (MHz)	limits at 3m (dBμV/m)		
	QP Detector	PK Detector	AV Detector
30 – 88	40.0	--	--
88 – 216	43.5	--	--
216 – 960	46.0		
960 – 1000	54.0	--	--
Above 1000	--	74.0	54.0

ICES-003 Issue 7

Frequency (MHz)	limits at 3m (dBμV/m)		
	QP Detector	PK Detector	AV Detector
30 – 88	40.0	--	--
88 – 216	43.5	--	--
216 – 230	46.0		

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

230 – 960	47.0	--	--
960 – 1000	54.0	--	--
Above 1000	--	74.0	54.0

Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.3.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:
 - 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
 - 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 120 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
 - 3) For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.
2. Above 1GHz test procedure as below:
 - 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
 - 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 1MHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
 - 3) For each frequency whose maximum record was higher or close to limit, measure its AV value: rotate the turntable from 0 to 360 degrees to find the degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to AV value and specified bandwidth with Maximum Hold Mode, and record the maximum value.

Equipment Used: Refer to section 3 for details.

Test Result: Pass


The measurement data as follows:

The measurement data for FCC 47 CFR Part 15 Subpart B as follows:


Below 1GHz (Quasi Peak):

Test Mode1: AC120V/60Hz (Adaptor 1) +PC Port Link+ LAN Port Link + Expansion Module Link (USB Port) + Headset Link + Hands Free

Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	368.668	40.42	-5.38	35.04	46.00	-10.96	QP
2	401.105	43.04	-4.43	38.61	46.00	-7.39	QP
3	442.572	44.06	-4.30	39.76	46.00	-6.24	QP
4	665.261	34.70	0.82	35.52	46.00	-10.48	QP
5	739.214	38.54	2.00	40.54	46.00	-5.46	QP
6	887.398	33.49	4.12	37.61	46.00	-8.39	QP



Below 1GHz (Quasi Peak):

Test Mode 8: AC120V/60Hz (POE) + Worse from mode 1

Horizontal



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	151.025	51.16	-15.01	36.15	43.50	-7.35	QP
2	171.389	47.39	-11.17	36.22	43.50	-7.28	QP
3	198.642	47.93	-10.48	37.45	43.50	-6.05	QP
4	442.572	45.61	-4.30	41.31	46.00	-4.69	QP
5	739.214	39.05	2.00	41.05	46.00	-4.95	QP
6	887.398	34.09	4.12	38.21	46.00	-7.79	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Vertical



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	31.292	41.04	-4.62	36.42	40.00	-3.58	QP
2	36.014	40.94	-5.43	35.51	40.00	-4.49	QP
3	49.757	51.25	-14.44	36.81	40.00	-3.19	QP
4	442.572	45.38	-4.30	41.08	46.00	-4.92	QP
5	739.214	36.45	2.00	38.45	46.00	-7.55	QP
6	887.398	36.73	4.12	40.85	46.00	-5.15	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>


UTTR-EMC-ICES003-V1.2

The measurement data for ICES-003 Issue 7 as follows:

Below 1GHz (Quasi Peak):


Test Mode1: AC120V/60Hz (Adaptor 1) +PC Port Link+ LAN Port Link + Expansion Module Link (USB Port) + Headset Link + Hands Free

Horizontal



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	368.668	40.42	-5.38	35.04	47.00	-11.96	QP
2	401.105	43.04	-4.43	38.61	47.00	-8.39	QP
3	442.572	44.06	-4.30	39.76	47.00	-7.24	QP
4	665.261	34.70	0.82	35.52	47.00	-11.48	QP
5	739.214	38.54	2.00	40.54	47.00	-6.46	QP
6	887.398	33.49	4.12	37.61	47.00	-9.39	QP

Vertical



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	56.864	49.43	-17.23	32.20	40.00	-7.80	QP
2	81.948	53.48	-17.43	36.05	40.00	-3.95	QP
3	112.427	49.62	-15.85	33.77	43.50	-9.73	QP
4	442.572	46.94	-4.30	42.64	47.00	-4.36	QP
5	739.214	36.58	2.00	38.58	47.00	-8.42	QP
6	887.398	35.34	4.12	39.46	47.00	-7.54	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Below 1GHz (Quasi Peak):

Test Mode 8: AC120V/60Hz (POE) + Worse from mode 1

Horizontal



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	151.025	51.16	-15.01	36.15	43.50	-7.35	QP
2	171.389	47.39	-11.17	36.22	43.50	-7.28	QP
3	198.642	47.93	-10.48	37.45	43.50	-6.05	QP
4	442.572	45.61	-4.30	41.31	47.00	-5.69	QP
5	739.214	39.05	2.00	41.05	47.00	-5.95	QP
6	887.398	34.09	4.12	38.21	47.00	-8.79	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Vertical



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	31.292	41.04	-4.62	36.42	40.00	-3.58	QP
2	36.014	40.94	-5.43	35.51	40.00	-4.49	QP
3	49.757	51.25	-14.44	36.81	40.00	-3.19	QP
4	442.572	45.38	-4.30	41.08	47.00	-5.92	QP
5	739.214	36.45	2.00	38.45	47.00	-8.55	QP
6	887.398	36.73	4.12	40.85	47.00	-6.15	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Above 1GHz (Peak & Average)

Test Mode1: AC120V/60Hz (Adaptor 1) +PC Port Link+ LAN Port Link + Expansion Module Link (USB Port) + Headset Link + Hands Free

Horizontal



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1029.385	59.98	-13.45	46.53	74.00	-27.47	Peak
2	1617.308	55.22	-11.74	43.48	74.00	-30.52	Peak
3	1891.095	55.43	-9.97	45.46	74.00	-28.54	Peak
4	10503.250	39.88	6.35	46.23	74.00	-27.77	Peak
5	14527.680	35.75	11.98	47.73	74.00	-26.27	Peak
6	16217.810	37.18	12.06	49.24	74.00	-24.76	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Vertical



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1029.385	59.07	-13.45	45.62	74.00	-28.38	Peak
2	1544.074	58.73	-12.11	46.62	74.00	-27.38	Peak
3	2123.366	54.16	-9.28	44.88	74.00	-29.12	Peak
4	2936.954	52.96	-6.93	46.03	74.00	-27.97	Peak
5	11001.420	38.55	7.42	45.97	74.00	-28.03	Peak
6	16124.140	38.25	11.97	50.22	74.00	-23.78	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Above 1GHz (Peak & Average)

Test Mode 8: AC120V/60Hz (POE) + Worse from mode 1

Horizontal



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1029.385	60.77	-13.45	47.32	74.00	-26.68	Peak
2	1902.081	56.44	-9.90	46.54	74.00	-27.46	Peak
3	2936.954	50.91	-6.93	43.98	74.00	-30.02	Peak
4	9087.293	40.02	5.09	45.11	74.00	-28.89	Peak
5	14277.410	36.88	11.80	48.68	74.00	-25.32	Peak
6	16791.350	36.29	12.61	48.90	74.00	-25.10	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Vertical



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1029.385	59.36	-13.45	45.91	74.00	-28.09	Peak
2	1580.267	57.75	-11.94	45.81	74.00	-28.19	Peak
3	2123.366	53.82	-9.28	44.54	74.00	-29.46	Peak
4	10937.880	39.22	7.29	46.51	74.00	-27.49	Peak
5	13396.090	36.40	11.30	47.70	74.00	-26.30	Peak
6	17284.770	36.10	13.19	49.29	74.00	-24.71	Peak

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit
4. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst-case emissions reported.
5. For Radiated Emission above 18GHz, there was not any unwanted emission detected.
6. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

6.2 CONDUCTED EMISSION

Test Requirement: FCC 47 CFR Part 15.107
ICES-003 Issue 7 Section 3.2.1

Test Method: ANSI C63.4-2014

Limits:

Limits for Class B devices

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.3.2 for details.

Test Procedures:

- 1) The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- 2) The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- 3) For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The measurement data as follows:

Quasi Peak and Average:


Test Mode 2: AC120V/60Hz (Adaptor 1) +PC Port Link+ LAN Port Link + Expansion Module Link (USB Port) + Headset Link + Ringing

Live Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.182	23.60	10.12	33.72	54.39	-20.67	Average
2	0.182	37.60	10.12	47.72	64.39	-16.67	QP
3	0.430	17.40	10.13	27.53	47.25	-19.72	Average
4	0.430	30.40	10.13	40.53	57.25	-16.72	QP
5	1.134	17.72	10.22	27.94	46.00	-18.06	Average
6	1.134	31.72	10.22	41.94	56.00	-14.06	QP
7	2.669	13.57	10.26	23.83	46.00	-22.17	Average
8	2.669	24.57	10.26	34.83	56.00	-21.17	QP
9	6.229	20.43	10.40	30.83	50.00	-19.17	Average
10	6.229	29.43	10.40	39.83	60.00	-20.17	QP
11	12.987	27.68	10.77	38.45	60.00	-21.55	QP
12	12.987	19.68	10.77	30.45	60.00	-29.55	QP

Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.182	20.39	10.11	30.50	54.39	-23.89	Average
2	0.182	35.39	10.11	45.50	64.39	-18.89	QP
3	0.438	17.00	10.12	27.12	47.10	-19.98	Average
4	0.438	32.00	10.12	42.12	57.10	-14.98	QP
5	1.134	16.55	10.15	26.70	46.00	-19.30	Average
6	1.134	32.55	10.15	42.70	56.00	-13.30	QP
7	2.757	14.70	10.25	24.95	46.00	-21.05	Average
8	2.757	23.70	10.25	33.95	56.00	-22.05	QP
9	6.229	19.52	10.43	29.95	50.00	-20.05	Average
10	6.229	29.52	10.43	39.95	60.00	-20.05	QP
11	14.379	17.01	10.80	27.81	50.00	-22.19	Average
12	14.379	24.01	10.80	34.81	60.00	-25.19	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Quasi Peak and Average:

Test Mode 9: AC240V/50Hz (POE) + Worse from mode 2

Live Line


No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.206	23.71	10.12	33.83	53.37	-19.54	Average
2	0.206	37.71	10.12	47.83	63.37	-15.54	QP
3	0.606	30.89	10.17	41.06	46.00	-4.94	Average
4*	0.606	40.89	10.17	51.06	56.00	-4.94	QP
5	0.814	19.84	10.19	30.03	46.00	-15.97	Average
6	0.814	37.84	10.19	48.03	56.00	-7.97	QP
7	1.782	16.48	10.23	26.71	46.00	-19.29	Average
8	1.782	33.48	10.23	43.71	56.00	-12.29	QP
9	2.997	16.73	10.26	26.99	46.00	-19.01	Average
10	2.997	31.73	10.26	41.99	56.00	-14.01	QP
11	21.362	20.22	10.97	31.19	50.00	-18.81	Average
12	21.362	32.22	10.97	43.19	60.00	-16.81	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.198	23.28	10.11	33.39	53.69	-20.30	Average
2	0.198	35.28	10.11	45.39	63.69	-18.30	QP
3	0.598	30.63	10.14	40.77	46.00	-5.23	Average
4*	0.598	41.63	10.14	51.77	56.00	-4.23	QP
5	0.822	37.36	10.14	47.50	56.00	-8.50	QP
6	0.822	22.36	10.14	32.50	46.00	-13.50	Average
7	1.702	21.61	10.18	31.79	46.00	-14.21	Average
8	1.702	36.61	10.18	46.79	56.00	-9.21	QP
9	2.741	20.23	10.25	30.48	46.00	-15.52	Average
10	2.741	34.23	10.25	44.48	56.00	-11.52	QP
11	29.816	32.54	10.92	43.46	50.00	-6.54	Average
12	29.816	39.54	10.92	50.46	60.00	-9.54	QP

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.
5. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

***** End of Report *****

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
