ACCREDITED
Certificate #4312.01

TEST REPORT

Product Name:	IP Phone
Trade Mark:	GRANDSTREAM
Model No.:	GRP2670
HVIN:	GRP2670V2
Report Number:	24032510313RFC-4
Test Standards:	FCC 47 CFR Part 15 Subpart E RSS-247 Issue 3 RSS-Gen Issue 5
FCC ID:	YZZGRP2670V2
IC:	11964A-GRP2670V2
Test Result:	PASS
Date of Issue:	July 25, 2024

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:	David Chen David Chen Senior Project Engineer	Reviewed by:	Henry Lu Henry Lu Team Leader
Approved by:	Robin Chen Robin Chen Assistant Manager	Date:	July 25, 2024

UnionTrust Quality Laboratories *Certified*

Version

Version No.	Date	Description
V1.0	July 25, 2024	Original

CONTENTS

1. GENERAL INFORMATION 4
   1.1 CLIENT INFORMATION 4
   1.2 EUT INFORMATION 4
      1.2.1 GENERAL DESCRIPTION OF EUT 4
      1.2.2 DESCRIPTION OF ACCESSORIES 4
   1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD 5
   1.4 OTHER INFORMATION 6
   1.5 DESCRIPTION OF SUPPORT UNITS 7
   1.6 TEST LOCATION 7
   1.7 TEST FACILITY 7
   1.8 DEVIATION FROM STANDARDS 8
   1.9 ABNORMALITIES FROM STANDARD CONDITIONS 8
   1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER 8
   1.11 MEASUREMENT UNCERTAINTY 8
2. TEST SUMMARY 9
3. EQUIPMENT LIST 10
4. TEST CONFIGURATION 11
   4.1 ENVIRONMENTAL CONDITIONS FOR TESTING 11
      4.1.1 NORMAL OR EXTREME TEST CONDITIONS 11
      4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE 11
   4.2 TEST CHANNELS 12
   4.3 EUT TEST STATUS 12
   4.4 PRE-SCAN 13
   4.5 TEST SETUP 14
      4.5.1 FOR RADIATED EMISSIONS TEST SETUP 14
      4.5.2 FOR CONDUCTED EMISSIONS TEST SETUP 15
      4.5.3 FOR CONDUCTED RF TEST SETUP 16
   4.6 SYSTEM TEST CONFIGURATION 17
   4.7 DUTY CYCLE 18
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION 22
   5.1 REFERENCE DOCUMENTS FOR TESTING 22
   5.2 ANTENNA REQUIREMENT 22
   5.3 26 DB BANDWIDTH & OCCUPIED BANDWIDTH 23
   5.4 6 DB BANDWIDTH & OCCUPIED BANDWIDTH 24
   5.5 MAXIMUM CONDUCTED OUTPUT POWER OR E.I.R.P 25
   5.6 PEAK POWER SPECTRAL DENSITY 32
   5.7 RADIATED EMISSIONS AND BAND EDGE MEASUREMENT 35
   5.8 DYNAMIC FREQUENCY SELECTION 74
   5.9 AC POWER LINE CONDUCTED EMISSION 84
APPENDIX A RF TEST DATA 87
   A.1 99% BANDWIDTH 87
   A.2 26DB BANDWIDTH 104
   A.3 PEAK POWER SPECTRAL DENSITY 117
   A.4 6DB BANDWIDTH 134
APPENDIX 1 PHOTOS OF TEST SETUP 138
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS 138

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	IP Phone		
Model No.:	GRP2670		
HVIN:	GRP2670V2		
Trade Mark:	GRANDSTREAM		
DUT Stage:	Identical Prototype		
EUT Supports Function: (Provided by the customer)	2.4 GHz ISM Band:	IEEE 802.11b/g/n/ax	
		Bluetooth V5.0	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac/ax
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac/ax
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac/ax
		5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac/ax
Sample Received Date:	March 23, 2024		
Sample Tested Date:	May 10, 2024 to June 22, 2024		

Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

1.2.2 Description of Accessories

Adapter (1)	
Model No.:	GQ12-120100-AU
Input:	100-240V~50/60Hz 0.4 A Max
Output:	12.0V⎓1.0 A
DC Cable	2.5 Meter, Unshielded without ferrite
Manufacture:	Dong Guan City GangQi Electronic Co., Ltd.

Adapter (2)	
Model No.:	F12US1200100A
Input:	100-240V~50/60Hz 0.5 A Max
Output:	12.0V⎓1.0 A
DC Cable	2.5 Meter, Unshielded without ferrite
Manufacture:	SHENZHEN SUNLIGHT ELECTRONIC TECHNOLOGY CO LTD

Adapter (3)	
Model No.:	DCT12W120100US-A2
Input:	100-240V~50/60Hz 0.3 A Max
Output:	12.0V⎓1.0 A
DC Cable	2.5 Meter, Unshielded without ferrite

Manufacture:	Zhuzhou Dachuan Electronic Technology Co., Ltd.

Cable(1)	
Description:	Ethernet Cable
Cable Type:	Unshielded without ferrite
Length:	1.5 Meter

Cable(2)	
Description:	Phone Cord
Cable Type:	Unshielded without ferrite
Length:	3.5 Meter

Others
1x Handset, 1x Phone Stand

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Bands:	5150 MHz to 5250 MHz (U-NII-1)
	5250 MHz to 5350 MHz (U-NII-2A)
	5470 MHz to 5725 MHz (U-NII-2C)
	5725 MHz to 5850 MHz (U-NII-3)
Frequency Ranges:	5180 MHz to 5240 MHz
	5260 MHz to 5320 MHz
	5500 MHz to 5720 MHz
	5745 MHz to 5825 MHz
Support Standards:	IEEE 802.11a/n/ac/ax
TPC Function:	Not Support
DFS Operational mode:	Slave without radar Interference detection function
Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11ax: OFDM /OFDMA Note 1 (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20: 20 MHz
	IEEE 802.11n-HT40/ac-VHT40/ax-HE40: 40 MHz
Data Rate:	IEEE 802.11a: Up to 54 Mbps
	IEEE 802.11n-HT20: Up to MCS7
	IEEE 802.11n-HT40: Up to MCS7
	IEEE 802.11ac-VHT20: Up to MCS8
	IEEE 802.11ac-VHT40: Up to MCS9
	IEEE 802.11ax-HE20/HE40: Up to MCS11
Number of Channels:	5150 MHz to 5250 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40)/ac-VHT40/ax-HE40
	5250 MHz to 5350 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40)/ac-VHT40/ax-HE40
	5470 MHz to 5725 MHz:

	12 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 6 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40				
	5725 MHz to 5850 MHz: 5 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40				
Antenna Type:	Dipole Antenna				
Antenna Gain: (Provided by the customer)	5150 MHz to 5250 MHz: 4.5 dBi				
	5250 MHz to 5350 MHz: 4.5 dBi				
	5470 MHz to 5725 MHz: 4.5 dBi				
	5725 MHz to 5850 MHz: 4.5 dBi				
Maximum conducted output power (dBm):		**U-NII-1**	**U-NII-2A**	**U-NII-2C**	**U-NII-3**
	IEEE 802.11a:	14.49	14.72	14.48	16.60
	IEEE 802.11n-HT20:	14.28	14.75	14.54	16.65
	IEEE 802.11n-HT40:	14.05	14.56	16.76	16.68
	IEEE 802.11ac-VHT20	14.27	14.72	14.62	16.61
	IEEE 802.11ac-VHT40	13.95	14.53	16.73	16.63
	IEEE 802.11ax-HE20	14.33	14.78	13.51	16.70
	IEEE 802.11ax-HE40	14.05	14.55	16.79	16.69
Maximum EIRP (dBm):		**U-NII-1**	**U-NII-2A**	**U-NII-2C**	**U-NII-3**
	IEEE 802.11a:	18.99	19.22	18.98	21.10
	IEEE 802.11n-HT20:	18.78	19.25	19.04	21.15
	IEEE 802.11n-HT40:	18.55	19.06	21.26	21.18
	IEEE 802.11ac-VHT20	18.77	19.22	19.12	21.11
	IEEE 802.11ac-VHT40	18.45	19.03	21.23	21.13
	IEEE 802.11ax-HE20	18.83	19.28	18.01	21.20
	IEEE 802.11ax-HE40	18.55	19.05	21.29	21.19
Normal Test Voltage:	12Vdc				
Note 1: For IEEE 802.11ax, the customer declaration the product supports only the SU mode.					

1.4 OTHER INFORMATION

Operation Frequency Each of Channel				
	U-NII-1	**U-NII-2A**	**U-NII-2C**	**U-NII-3**
IEEE 802.11a, IEEE 802.11n-HT20, IEEE 802.11ac-VHT20 IEEE 802.11ax-HE20	**f = 5000 + 5k, k = 32 + 4n**			**f = 5000 + 5k, k = 145 + 4n**
	n = 1,…, 4	**n = 5,…, 8**	**n = 17,…, 27**	**n = 1,…, 5**
IEEE 802.11n-HT40, IEEE 802.11ac-VHT40 IEEE 802.11ax-HE40	**f = 5000 + 5k, k = 30 + 8n**			**f = 5000 + 5k, k = 143 + 8n**
	n = 1, 2	**n = 1,…, 5**	**n = 9,…, 13**	**n = 1, 2**
Note: **f** is the operating frequency (MHz); **k** is the operating channel.				

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	FCC ID	Supplied by
Notebook	DELL	Latitude 3400	16238087894	N/A	UnionTrust
Mouse	DELL	MS111	CN-011D3V-738	N/A	UnionTrust
Wireless Home Router	SAGEMCOM	FAST5280	253703944	VW3FAST5280	UnionTrust
Key-Press Attenuator	Huaxin	KT2.5-90/1S-2S	UTTL-EN023	N/A	UnionTrust
4 Way Divider	WOKEN	0120A040560002D	UTTL-EN028	N/A	UnionTrust

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.1Meter	UnionTrust

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China
Telephone: +86 (0) 755 2823 0888
Fax: +86 (0) 755 2823 0886

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069
The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01
Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories
CAB identifier: CN0032

FCC Accredited Lab.
Designation Number: CN1194
Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.9 dB
5	Radiated emission 1GHz-18GHz	± 4.8 dB
6	Radiated emission 18GHz-26GHz	± 5.1 dB
7	Radiated emission 26GHz-40GHz	± 5.1 dB
8	Conducted spurious emissions	± 2.7 dB
9	RF Power, Conducted	± 0.68 dB
10	Occupied Bandwidth	± 1.86 %
11	Radio Frequency	5.6 GHz: ± 6.4 x 10^{-8}
12	Transmission Time	± 0.19 %

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart E Test Cases			
Test Item	**Test Requirement**	**Test Method**	**Result**
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203 FCC 47 CFR Part 15 Subpart E Section 15.407(a)(1) (2) RSS-Gen Issue 5, Section 6.8	N/A	PASS
26 dB emission bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(2)(5) RSS-247 Issue 3 Section 6.2.1.2	KDB 789033 D02 v02r01 Section C.1	PASS
6 dB bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (e) RSS-247 Issue 3 Section 6.2.4.1	KDB 789033 D02 v02r01 Section C.2	PASS
Occupied Bandwidth	RSS-Gen Issue 5, Section 6.7	RSS-Gen Issue 5, section 6.7	PASS
Maximum conducted output power	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3) RSS-247 Issue 3 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1	KDB 789033 D02 v02r01 Section E.3.a (Method PM)	PASS
Peak Power Spectral Density	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3) RSS-247 Issue 3 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1	KDB 789033 D02 v02r01 Section F	PASS
Radiated Emissions and Band Edge Measurement	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(1)(2)(3)(4)(6) FCC 47 CFR Part 15 Subpart C Section 15.209/205 RSS-247 Issue 3 Section 6.2.1.2/6.2.2.2/6.2.3.2/6.2.4.2	KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6	PASS
Dynamic Frequency Selection	FCC 47 CFR Part 15 Subpart E Section 15.407 (h) RSS-247 Issue 3 Section 6.3	KDB 905462 D03 Client Without DFS New Rules v01r02	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(6) FCC 47 CFR Part 15 Subpart C Section 15.207 RSS-Gen Issue 5, Section 8.8	ANSI C63.10-2013, Section 6.2.	PASS
Note: 1) N/A: In this whole report not applicable.			
Disclaimer and Explanations: The declared of product specification and data (e.g. antenna gain, RF specification, etc) for EUT presented in the report are provided by the customer, and the customer takes all the responsibilities for the accuracy of product specification.			

For Dynamic Frequency Selection

Test Case	Result
Channel Availability Check Time	N/A[1]
U-NII Detection Bandwidth	N/A[1]
Channel Closing Transmission Time	PASS
Channel Move Time	PASS
DFS Detection Threshold	N/A[1]
Non- Occupancy Period	N/A[1]
Note: 1) The EUT is slave, NA In this whole report not applicable.	

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	3m SAC	ETS-LINDGREN	3m	Euroshiedpn-CT001270-1317	11-Nov-2023	10-Nov-2026
☒	Receiver	R&S	ESIB26	100114	27-Oct-2023	26-Oct-2024
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	29-Mar-2024	28-Mar-2025
☒	Loop Antenna	ETS-LINDGREN	6502	00202525	30-Oct-2023	29-Oct-2024
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	30-Oct-2023	29-Oct-2024
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	30-Oct-2023	29-Oct-2024
☒	Preamplifier	HP	8447F	2805A02960	31-Oct-2023	30-Oct-2024
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201541	1-Apr-2024	31-Mar-2025
☒	Pre-amplifier	ETS-Lindgren	00118385	00201874	1-Apr-2024	31-Mar-2025
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	30-Oct-2023	29-Oct-2024
☒	Pre-amplifier	ETS-Lindgren	00118384	00202652	30-Oct-2023	29-Oct-2024
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Band Rejection Filter (5150MHz~5880MHz)	Micro-Tronics	BRM50716	G186	27-Oct-2023	26-Oct-2024
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	Receiver	R&S	ESR7	1316.3003K07-101181-K3	27-Oct-2023	26-Oct-2024
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	27-Oct-2023	26-Oct-2024
☒	LISN	R&S	ESH2-Z5	860014/024	27-Oct-2023	26-Oct-2024
☒	LISN	ETS-Lindgren	3816/2SH	00201088	27-Oct-2023	26-Oct-2024
☒	Test Software	EZ-EMC	EZ-CON	Software Version: EMC-CON 3A1.1		

Conducted RF test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	29-Mar-2024	28-Mar-2025
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	27-Oct-2023	26-Oct-2024
☒	MXG X-Series RF Vector Signal Generator	KEYSIGHT	N5182B	MY51350267	27-Oct-2023	26-Oct-2024

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NT/NV	+15 to +35	12	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test Sample

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
26 dB emission bandwidth	24.4	55.2	100.2	S202403232937-ZJA03/4	Allen Zhou
6 dB bandwidth					
Occupied Bandwidth					
Maximum conducted output power					
Peak Power Spectral Density					
Dynamic Frequency Selection					
Radiated Emissions and Band Edge Measurement	21.3	54.5	100.2	S202403232937-ZJA04/4	Fire Huo
AC Power Line Conducted Emission	23.3	62.4	100.4	S202403232937-ZJA02/4	Linson Xie

4.2 TEST CHANNELS

Mode	Tx/Rx Frequency	Test RF Channel Lists			
		Lowest(L)	Middle(M)	Highest(H)	Straddle band
IEEE 802.11a IEEE 802.11n-HT20 IEEE 802.11ac-VHT20 IEEE 802.11ax-HE20	5150 MHz to 5250 MHz	Channel 36	Channel 44	Channel 48	--
		5180 MHz	5220 MHz	5240 MHz	--
	5250 MHz to 5350 MHz	Channel 52	Channel 60	Channel 64	--
		5260 MHz	5300 MHz	5320 MHz	--
	5470 MHz to 5725 MHz	Channel 100	Channel 116	Channel 140	Channel 144
		5500 MHz	5580 MHz	5700 MHz	5720 MHz
	5725 MHz to 5850 MHz	Channel 149	Channel 157	Channel 165	--
		5745 MHz	5785 MHz	5825 MHz	--
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40 IEEE 802.11ax-HE40	5150 MHz to 5250 MHz	Channel 38	--	Channel 46	--
		5190 MHz	--	5230 MHz	--
	5250 MHz to 5350 MHz	Channel 54	--	Channel 62	--
		5270 MHz	--	5310 MHz	--
	5470 MHz to 5725 MHz	Channel 102	Channel 110	Channel 134	Channel 142
		5510 MHz	5550 MHz	5670 MHz	5710 MHz
	5725 MHz to 5850 MHz	Channel 151	--	Channel 159	--
		5755 MHz	--	5795 MHz	--
		--	5775 MHz	--	--

4.3 EUT TEST STATUS

Mode	Tx/Rx Function	Description
IEEE 802.11a/n/ac/ax	1Tx/1Rx	1. Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

Power Setting				
	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
IEEE 802.11a	Default	Default	3C	Default
IEEE 802.11n-HT20	Default	Default	3C	Default
IEEE 802.11n-HT40	Default	Default	Default	Default
IEEE 802.11ac-VHT20	Default	Default	3C	Default
IEEE 802.11ac-VHT40	Default	Default	Default	Default
IEEE 802.11ax-HE20	Default	Default	38	Default
IEEE 802.11ax-HE40	Default	Default	Default	Default

Test Software
Test software name: Command

4.4 PRE-SCAN

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate. Following data rate was (were) selected for the final test as listed below

Mode	Worst-case data rates
IEEE 802.11a	6 Mbps
IEEE 802.11n-HT20	MCS0
IEEE 802.11n-HT40	MCS0
IEEE 802.11ac-VHT20	MCS0
IEEE 802.11ac-VHT40	MCS0
IEEE 802.11ax-HE20	MCS0
IEEE 802.11ax-HE40	MCS0

4.5 TEST SETUP

4.5.1 For Radiated Emissions test setup

Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1GHz



4.5.2 For Conducted Emissions test setup



4.5.3 For Conducted RF test setup



Normal Environment

4.6 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in (see table below) orientation.

Frequency	Mode	Antenna Port	Worst-case axis positioning
Above 1GHz	1TX	Chain 0	Z axis

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.7 DUTY CYCLE

Test Procedure: ANSI C63.10-2013 Clause 12.2.

Test Results

Mode	Data Rates	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/T Minimum VBW (kHz)
IEEE 802.11a	6 Mbps	5.440	5.620	0.97	96.80	0.14	0.18
IEEE 802.11n-HT20	MCS 0	5.320	5.520	0.96	96.38	0.16	0.19
IEEE 802.11n-HT40	MCS 0	2.960	3.160	0.94	93.67	0.28	0.34
IEEE 802.11ac-VHT20	MCS 0	5.340	5.520	0.97	96.74	0.14	0.19
IEEE 802.11ac-VHT40	MCS 0	5.120	5.320	0.96	96.24	0.17	0.20
IEEE 802.11ax-HE20	MCS 0	4.620	4.800	0.96	96.25	0.17	0.22
IEEE 802.11ax-HE40	MCS 0	4.580	4.800	0.95	95.42	0.20	0.22

Remark:

1) Duty cycle= On Time/ Period;
2) Duty Cycle factor = 10 * log(1/ Duty cycle);
3) Average factor = 20 $\log_{10}$ Duty Cycle.

The test plots as follows

IEEE 802.11a



IEEE 802.11n-HT20



IEEE 802.11n-HT40



IEEE 802.11ac-VHT20



IEEE 802.11ac-VHT40



IEEE 802.11ax-HE20_SU



IEEE 802.11ax-HE40_SU



5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	RSS-247 Issue 3	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
4	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
5	ANSI C63.10-2013	American National Standard for Testing Unlicesed Wireless Devices
6	KDB 789033 D02 General UNII Test Procedures New Rules v02r01	Guidelines for compliance testing of unlicensed national information infrastructure (U-NII) device part 15, subpart E
7	KDB 905462 D06 802.11 Channel Plans New Rules v02	Operation in U-NII bands -802.11 channel PLAN(§15.407)
8	KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02	Compliance measurement procedures for Unlicensed –National Information Infrastructure devices operates in the frequency bands 5250 MHz to 5350 MHz and 5470 MHz to 5725 MHz bands incorporating dynamic frequency selection
9	KDB 905462 D03 Client Without DFS New Rules v01r02	U-NII client devices without radar detection capability

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. **15.407(a)(1) (2) requirement:** The conducted output power limit specified in paragraph (a) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (a) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power and the peak power spectral density shall be reduced by the by the amount in dB that the directional gain of the antenna exceeds 6 dBi. **RSS-Gen Issue 5, Section 6.8 requirement:** According to RSS-Gen Issue 5, Section 6.8, a transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns.
EUT Antenna:
Antenna in the interior of the equipment and no consideration of replacement. The gain of the antenna is 4.5 dBi.

5.3 26 DB BANDWIDTH & OCCUPIED BANDWIDTH

Test Requirement:	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(2)(5) RSS-247 Issue 3 Section 6.2.1.2
Test Method:	KDB 789033 D02 v02r01 Section C.1
Limit:	None; for reporting purposes only.
Test Procedure:	

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum analyzer.

Spectrum analyzer according to the following Settings:
a) Set RBW = approximately 1 % of the emission bandwidth.
b) Set the VBW > RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup:	Refer to section 4.5.3 for details.
Instruments Used:	Refer to section 3 for details
Test Mode:	Link mode
Test Results:	**Please refer to Appendix A**

5.46 DB BANDWIDTH & OCCUPIED BANDWIDTH

Test Requirement:	FCC 47 CFR Part 15 Subpart E Section 15.407 (e) RSS-247 Issue 3 Section 6.2.4.1
Test Method:	KDB 789033 D02 v02r01 Section C.2
Limit:	Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum Analyzer.

Spectrum analyzer according to the following Settings:

6dB Bandwidth

a) Set RBW = 100 kHz.
b) Set the video bandwidth (VBW) ≥ 3 * RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

a) Set RBW = 1% to 5% of the occupied bandwidth
b) Set the video bandwidth (VBW) ≥ 3 x RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup:	Refer to section 4.5.3 for details.
Instruments Used:	Refer to section 3 for details
Test Mode:	Transmitter mode
Test Results:	**Please refer to Appendix A**

5.5 MAXIMUM CONDUCTED OUTPUT POWER OR E.I.R.P

Test Requirement:	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3) RSS-247 Issue 3 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1
Test Method:	KDB 789033 D02 v02r01 Section E.3.a (Method PM)
Limits:	FCC 47 CFR Part 15 Subpart E

1. For the band 5.15-5.25 GHz.
   (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

   (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

   (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

   (iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3. For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Limits: RSS-247 Issue 3

1. **Frequency band 5150-5250 MHz**
For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or 1.76 + 10 $\log_{10}$B, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or 10 + 10 $\log_{10}$B, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

2. **Frequency band 5250-5350 MHz**
For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or 1.76 + 10 $\log_{10}$B, dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

a) The maximum conducted output power shall not exceed 250 mW or 11 + 10 $\log_{10}$B, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;

b) The maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 $\log_{10}$B, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

Additional requirements
In addition to the above requirements, devices shall comply with the following, where applicable:

a) Outdoor fixed devices with a maximum e.i.r.p. greater than 200 mW shall comply with the following e.i.r.p. at different elevations, where θ is the angle above the local horizontal plane (of the Earth) as shown below:

i. -13 dBW/MHz for $0^o \leq \theta < 8^o$

ii. -13 − 0.716 (θ-8) dBW/MHz for $8^o \leq \theta < 40^o$

iii. -35.9 − 1.22 (θ-40) dBW/MHz for $40^o \leq \theta \leq 45^o$

iv. -42 dBW/MHz for $\theta > 45^o$

The measurement procedure defined in Annex A of this document shall be used to verify the compliance to the e.i.r.p. at different elevations.

b) Devices, other than outdoor fixed devices, having an e.i.r.p. greater than 200 mW shall comply with either i. or ii. below:

i. devices shall comply with the e.i.r.p. elevation mask in 6.2.2.3(a); or

ii. devices shall implement a method to permanently reduce their e.i.r.p. via a firmwarefeature in the event that the Department requires it. The test report must demonstratehow the device's power table can be updated to meet this firmware requirement. Themanufacturer shall provide this firmware to update all systems automatically incompliance with the directions received from the Department.

3. **Frequency bands 5470-5600 MHz and 5650-5725 MHz**
The maximum conducted output power shall not exceed 250 mW or 11 + 10 $\log_{10}$B, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 $\log_{10}$B, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

4. **Frequency band 5725-5850 MHz**
The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices

operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint[3] systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

Test Procedure:

1. Connected the EUT's antenna port to measure device by 10dB attenuator.
2. Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of Tx on burst.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Gain and the maximum output power limit.

RSS-247 Issue 3

Frequency Band	Antenna Gain (dBi)	Power Limits (dBm)
U-NII-1	4.5	23.0
U-NII-2A	4.5	24.0
U-NII-2C	4.5	24.0
U-NII-3	4.5	30.0

FCC 47 CFR Part 15 Subpart E

Frequency Band	Antenna Gain (dBi)	Power Limits (dBm)
U-NII-1	4.5	24.0
U-NII-2A	4.5	24.0
U-NII-2C	4.5	24.0
U-NII-3	4.5	30.0

Frequency band 5150-5250 MHz
RSS-247 Issue 3:
For IEEE 802.11a, the minimum 99% emission bandwidth is 17.067MHz
10 dBm + $10\log_{10}$ (17.067) = 22.32 dBm < 23 dBm
So the 22.32 dBm limit applicable

For IEEE 802.11n-HT20/ ac-VHT20/ax-HE20, the minimum 99% emission bandwidth is 18.089 MHz
10 dBm + $10\log_{10}$ (18.089) = 22.57 dBm < 23 dBm
So the 22.57 dBm limit applicable

For IEEE 802.11n-HT40/ ac-VHT40/ax-HE40, the minimum 99% emission bandwidth is 36.439 MHz
10 dBm + $10\log_{10}$ (36.439) = 25.62 dBm > 23 dBm
So the 23 dBm limit applicable

Frequency band 5250-5350 MHz
RSS-247 Issue 3:
For IEEE 802.11 a, the minimum 99% emission bandwidth is 17.072 MHz
11 dBm + $10\log_{10}$ (17.072) = 23.32 dBm < 24dBm
So the 23.32 dBm limit applicable

For IEEE 802.11n-HT20/ ac-VHT20/ax-HE20, the minimum 99% emission bandwidth is 18.079 MHz
11 dBm + $10\log_{10}$ (18.079) = 23.57 dBm < 24dBm
So the 23.57 dBm limit applicable

For IEEE 802.11 n-HT40/ac-VHT40/ax-HE40, the minimum 99% emission bandwidth is 36.459 MHz
11 dBm + $10\log_{10}$ (36.459) = 26.62 dBm > 24 dBm
So the 24 dBm limit applicable

EIRP:
For IEEE 802.11 a/n-HT20/ac-VHT20/ax-HE20, the minimum 99% emission bandwidth is 17.072 MHz
17 dBm + $10\log_{10}$ (17.072) =29.32 dBm
29.32 dBm > 27 dBm
So the 27 dBm limit applicable

For IEEE 802.11 n-HT40/ac-VHT40/ax-HE40, the minimum 99% emission bandwidth is 36.459 MHz
17 dBm + $10\log_{10}$ (36.459) = 32.62 dBm > 27 dBm
So the 27 dBm limit applicable

FCC 47 CFR Part 15 Subpart E:
For IEEE 802.11 a/n/ac/ax, the minimum 26 dB emission bandwidth is 21.51 MHz
11 dBm + $10\log_{10}$ (21.51) = 24.33 dBm > 24 dBm
So the 24 dBm limit applicable

Frequency bands 5470-5725 MHz (RSS-247 Issue 3 Not including 5600-5650 MHz)
RSS-247 Issue 3:
For IEEE 802.11 a, the minimum 99% emission bandwidth is 17.073 MHz
11 dBm + $10\log_{10}$ (17.073) = 23.32 dBm < 24 dBm
So the 23.32 dBm limit applicable

For IEEE 802.11n-HT20/ac-VHT20/ax-HE20, the minimum 99% emission bandwidth is 18.080 MHz
11 dBm + $10\log_{10}$ (18.080) = 23.57 dBm < 24 dBm
So the 23.57 dBm limit applicable

For IEEE 802.11 n-HT40/ac-VHT40/ax-HE40, the minimum 99% emission bandwidth is 36.455 MHz
11 dBm + $10\log_{10}$ (36.455) = 26.62 dBm > 24 dBm
So the 24 dBm limit applicable

EIRP:
For IEEE 802.11 a/n-HT20/ac-VHT20/ax-HE20, the minimum 99% emission bandwidth is 17.073 MHz
17 dBm + $10\log_{10}$ (17.073) = 29.32 dBm
29.32 dBm > 27 dBm
So the 27 dBm limit applicable

For IEEE 802.11 n-HT40/ac-VHT40/ax-HE40, the minimum 99% emission bandwidth is 36.455 MHz
17 dBm + $10\log_{10}$ (36.455) = 32.62 dBm > 27 dBm
So the 27 dBm limit applicable

FCC 47 CFR Part 15 Subpart E:
For IEEE 802.11 a/n/ac/ax, the minimum 26 dB emission bandwidth is 21.57 MHz
11 dBm + $10\log_{10}$ (21.57) = 24.34 dBm > 24 dBm
So the 24 dBm limit applicable

IEEE 802.11a/n/ac

Mode	Band	Channel	CONDUCTED AVG POWER				EIRP		
			Meas Value (dBm)	Corr'd Value (dBm)	FCC Limit (dBm)	ISED Limit (dBm)	EIRP (dBm)	ISED Limit (dBm)	Result
IEEE 802.11a	U-NII-1	36	14.35	14.49	24.00	--	18.99	22.32	Pass
		44	13.60	13.74	24.00	--	18.24	22.32	Pass
		48	13.66	13.80	24.00	--	18.30	22.32	Pass
	U-NII-2A	52	14.55	14.69	24.00	23.32	19.19	27.00	Pass
		60	14.58	14.72	24.00	23.32	19.22	27.00	Pass
		64	14.41	14.55	24.00	23.32	19.05	27.00	Pass
	U-NII-2C	100	13.92	14.06	24.00	23.32	18.56	27.00	Pass
		116	13.64	13.78	24.00	23.32	18.28	27.00	Pass
		140	14.34	14.48	24.00	23.32	18.98	27.00	Pass
		144	14.32	14.46	24.00	23.32	18.96	27.00	Pass
	U-NII-3	149	16.46	16.60	30.00	30.00	21.10	--	Pass
		157	16.33	16.47	30.00	30.00	20.97	--	Pass
		165	15.98	16.12	30.00	30.00	20.62	--	Pass
IEEE 802.11n-HT20	U-NII-1	36	14.12	14.28	24.00	--	18.78	22.57	Pass
		44	13.55	13.71	24.00	--	18.21	22.57	Pass
		48	13.61	13.77	24.00	--	18.27	22.57	Pass
	U-NII-2A	52	14.58	14.74	24.00	23.57	19.24	27.00	Pass
		60	14.59	14.75	24.00	23.57	19.25	27.00	Pass
		64	14.47	14.63	24.00	23.57	19.13	27.00	Pass
	U-NII-2C	100	13.95	14.11	24.00	23.57	18.61	27.00	Pass
		116	13.67	13.83	24.00	23.57	18.33	27.00	Pass
		140	14.38	14.54	24.00	23.57	19.04	27.00	Pass
		144	14.36	14.52	24.00	23.57	19.02	27.00	Pass
	U-NII-3	149	16.49	16.65	30.00	30.00	21.15	--	Pass
		157	16.38	16.54	30.00	30.00	21.04	--	Pass
		165	16.03	16.19	30.00	30.00	20.69	--	Pass
IEEE 802.11n-HT40	U-NII-1	38	13.77	14.05	24.00	--	18.55	23.01	Pass
		46	13.55	13.83	24.00	--	18.33	23.01	Pass
	U-NII-2A	54	14.20	14.48	24.00	24.00	18.98	27.00	Pass
		62	14.28	14.56	24.00	24.00	19.06	27.00	Pass
	U-NII-2C	102	14.72	15.00	24.00	24.00	19.50	27.00	Pass
		110	14.77	15.05	24.00	24.00	19.55	27.00	Pass
		134	16.48	16.76	24.00	24.00	21.26	27.00	Pass
		142	16.08	16.36	24.00	24.00	20.86	27.00	Pass
	U-NII-3	151	16.40	16.68	30.00	30.00	21.18	--	Pass
		159	16.06	16.34	30.00	30.00	20.84	--	Pass
IEEE 802.11ac-VHT20	U-NII-1	36	14.13	14.27	24.00	--	18.77	22.57	Pass

Mode	Band	Channel	CONDUCTED AVG POWER				EIRP		
			Meas Value (dBm)	Corr'd Value (dBm)	FCC Limit (dBm)	ISED Limit (dBm)	EIRP (dBm)	ISED Limit (dBm)	Result
		44	13.52	13.66	24.00	--	18.16	22.57	Pass
		48	13.61	13.75	24.00	--	18.25	22.57	Pass
	U-NII-2A	52	14.53	14.67	24.00	23.57	19.17	27.00	Pass
		60	14.58	14.72	24.00	23.57	19.22	27.00	Pass
		64	14.45	14.59	24.00	23.57	19.09	27.00	Pass
	U-NII-2C	100	13.96	14.10	24.00	23.57	18.60	27.00	Pass
		116	13.85	13.99	24.00	23.57	18.49	27.00	Pass
		140	14.48	14.62	24.00	23.57	19.12	27.00	Pass
		144	14.42	14.56	24.00	23.57	19.06	27.00	Pass
	U-NII-3	149	16.47	16.61	30.00	30.00	21.11	--	Pass
		157	16.39	16.53	30.00	30.00	21.03	--	Pass
		165	16.00	16.14	30.00	30.00	20.64	--	Pass
IEEE 802.11ac-VHT40	U-NII-1	38	13.78	13.95	24.00	--	18.45	23.01	Pass
		46	13.58	13.75	24.00	--	18.25	23.01	Pass
	U-NII-2A	54	14.26	14.43	24.00	24.00	18.93	27.00	Pass
		62	14.36	14.53	24.00	24.00	19.03	27.00	Pass
	U-NII-2C	102	14.77	14.94	24.00	24.00	19.44	27.00	Pass
		110	14.79	14.96	24.00	24.00	19.46	27.00	Pass
		134	16.56	16.73	24.00	24.00	21.23	27.00	Pass
		142	16.13	16.30	24.00	24.00	20.80	27.00	Pass
	U-NII-3	151	16.46	16.63	30.00	30.00	21.13	--	Pass
		159	16.12	16.29	30.00	30.00	20.79	--	Pass

IEEE 802.11ax

Mode	Band	Channel	CONDUCTED AVG POWER				EIRP		
			Meas Value (dBm)	Corr'd Value (dBm)	FCC Limit (dBm)	ISED Limit (dBm)	EIRP (dBm)	ISED Limit (dBm)	Result
IEEE 802.11ax-HE20	U-NII-1	36	14.16	14.33	24.00	--	18.83	22.57	Pass
		44	13.55	13.72	24.00	--	18.22	22.57	Pass
		48	13.67	13.84	24.00	--	18.34	22.57	Pass
	U-NII-2A	52	14.55	14.72	24.00	23.57	19.22	27.00	Pass
		60	14.61	14.78	24.00	23.57	19.28	27.00	Pass
		64	14.48	14.65	24.00	23.57	19.15	27.00	Pass
	U-NII-2C	100	12.93	13.10	24.00	23.57	17.60	27.00	Pass
		116	12.75	12.92	24.00	23.57	17.42	27.00	Pass
		140	13.34	13.51	24.00	23.57	18.01	27.00	Pass
		144	13.32	13.49	24.00	23.57	17.99	27.00	Pass
	U-NII-3	149	16.53	16.70	30.00	30.00	21.20	36.02	Pass
		157	16.41	16.58	30.00	30.00	21.08	36.02	Pass
		165	16.03	16.20	30.00	30.00	20.70	36.02	Pass
IEEE 802.11ax-HE40	U-NII-1	38	13.85	14.05	24.00	--	18.55	23.01	Pass
		46	13.63	13.83	24.00	--	18.33	23.01	Pass
	U-NII-2A	54	14.28	14.48	24.00	24.00	18.98	27.00	Pass
		62	14.35	14.55	24.00	24.00	19.05	27.00	Pass
	U-NII-2C	102	14.81	15.01	24.00	24.00	19.51	27.00	Pass
		110	14.83	15.03	24.00	24.00	19.53	27.00	Pass
		134	16.59	16.79	24.00	24.00	21.29	27.00	Pass
		142	16.18	16.38	24.00	24.00	20.88	27.00	Pass
	U-NII-3	151	16.49	16.69	30.00	30.00	21.19	36.02	Pass
		159	16.15	16.35	30.00	30.00	20.85	36.02	Pass

5.6 PEAK POWER SPECTRAL DENSITY

Test Requirement:	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3) RSS-247 Issue 3 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1
Test Method:	KDB 789033 D02 v02r01 Section F
Limits:	FCC 47 CFR Part 15 Subpart E

1. For the band 5.15-5.25 GHz.
   (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

   (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

   (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

   (iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3. For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Limits: RSS-247 Issue 3

1. **Frequency band 5150-5250 MHz**
For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or 1.76 + 10 $\log_{10}$B, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or 10 + 10 $\log_{10}$B, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

2. **Frequency band 5250-5350 MHz**
For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or 1.76 + 10 $\log_{10}$B, dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

a) The maximum conducted output power shall not exceed 250 mW or 11 + 10 $\log_{10}$B, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;

b) The maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 $\log_{10}$B, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

Additional requirements
In addition to the above requirements, devices shall comply with the following, where applicable:

a) Outdoor fixed devices with a maximum e.i.r.p. greater than 200 mW shall comply with the following e.i.r.p. at different elevations, where θ is the angle above the local horizontal plane (of the Earth) as shown below:

i. -13 dBW/MHz for $0^o \leq \theta < 8^o$

ii. -13 − 0.716 (θ-8) dBW/MHz for $8^o \leq \theta < 40^o$

iii. -35.9 − 1.22 (θ-40) dBW/MHz for $40^o \leq \theta \leq 45^o$

iv. -42 dBW/MHz for $\theta > 45^o$

The measurement procedure defined in Annex A of this document shall be used to verify the compliance to the e.i.r.p. at different elevations.

b) Devices, other than outdoor fixed devices, having an e.i.r.p. greater than 200 mW shall comply with either i. or ii. below:

iii. devices shall comply with the e.i.r.p. elevation mask in 6.2.2.3(a); or

iv. devices shall implement a method to permanently reduce their e.i.r.p. via a firmwarefeature in the event that the Department requires it. The test report must demonstratehow the device's power table can be updated to meet this firmware requirement. Themanufacturer shall provide this firmware to update all systems automatically incompliance with the directions received from the Department.

3. **Frequency bands 5470-5600 MHz and 5650-5725 MHz**
The maximum conducted output power shall not exceed 250 mW or 11 + 10 $\log_{10}$B, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 $\log_{10}$B, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

4. **Frequency band 5725-5850 MHz**
The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices

operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint[3] systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum Analyzer.

Spectrum analyzer according to the following Settings:

1. For U-NII-1, U-NII-2A, U-NII-2C band:

Using method SA-2

a) Set span to encompass the entire emission bandwidth (EBW) of the signal.
b) Set RBW = 1 MHz, Set VBW ≥ 3 RBW, Detector = RMS
c) Sweep time = auto, trigger set to “free run”.
d) Trace average at least 100 traces in power averaging mode.
e) Record the max value and add 10 log (1/duty cycle)

2. For U-NII-3 band:

a) Set span to encompass the entire emission bandwidth (EBW) of the signal.
b) Set RBW = 500 kHz, Set VBW ≥ 3 RBW, Detector = RMS
c) Use the peak marker function to determine the maximum power level in any 500 kHz band segment within the fundamental EBW.
d) Sweep time = auto, trigger set to “free run”.
e) Trace average at least 100 traces in power averaging mode.
f) Record the max value and add 10 log (1/duty cycle)

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: **Please refer to Appendix A**

Test Data:

Gain and the maximum output power limit.

RSS-247 Issue 3:

Frequency Band	Antenna Gain (dBi)	PSD Limits (dBm/MHz or dBm/500kHz)
U-NII-1	4.5	10.0
U-NII-2A	4.5	11.0
U-NII-2C	4.5	11.0
U-NII-3	4.5	30.0

FCC 47 CFR Part 15 Subpart E:

Frequency Band	Antenna Gain (dBi)	PSD Limits (dBm/MHz or dBm/500kHz)
U-NII-1	4.5	11.0
U-NII-2A	4.5	11.0
U-NII-2C	4.5	11.0
U-NII-3	4.5	30.0

5.7 RADIATED EMISSIONS AND BAND EDGE MEASUREMENT

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(1)(2)(3)(4)(6)
FCC 47 CFR Part 15 Subpart C Section 15.209/205
RSS-247 Issue 3 Section 6.2.1.2/6.2.2.2/6.2.3.2/6.2.4.2

Test Method: KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

1. Limits of Radiated Emission and Band edge Measurement

Radiated emissions that fall in the restricted bands must comply with the general emissions limits in 15.209(a) as below table. Other emissions shall be at least 20 dB below the highest level of the desired power.

Frequency	Field strength (microvolt/meter)	Limit (dBμV/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

a. The lower limit shall apply at the transition frequencies.
b. Emission level (dBuV/m) = 20 log Emission level (uV/m).
c. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

2. Limits of Unwanted Emission Out of the Restricted Bands

Applicable To	Limit	
789033 D02 General U-NII Test Procedures New Rules v01r04	**Field Strength at 3 m**	
	PK: 74 (dBμV/m)	**AV: 54 (dBμV/m)**
Applicable To	EIRP Limit	Equivalent Field Strength at 3 m
RSS-247 Issue 3 Section 6.2.1.2	PK: -27 (dBm/MHz)	PK: 74 (dBμV/m)
RSS-247 Issue 3 Section 6.2.2.2	PK: -27 (dBm/MHz)	PK: 74 (dBμV/m)
RSS-247 Issue 3 Section 6.2.3.2	PK: -27 (dBm/MHz)	PK: 68.2 (dBμV/m)
RSS-247 Issue 3 Section 6.2.4.2	27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;	PK: 68.2 (dBμV/m)
	15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;	
	10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges;	
	-27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.	

Test Setup: Refer to section 4.5.1 for details.

Test Procedures:

1. The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
6. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Remark:

a) The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
b) The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
c) The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for RMS Average (Duty cycle < 98 %) for Average detection (AV) at frequency above 1 GHz, then the measurement results was added to a correction factor (10 log(1/duty cycle)).
d) The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz (Duty cycle ≥ 98 %) or ≥ 1/T(duty cycle is < 98%) for Average detection (AV) at frequency above 1 GHz.
e) All modes of operation were investigated and the worst-case emissions are reported.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

Radiated Emission Test Data (9 KHz ~ 30 MHz):

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Radiated Emission Test Data (30 MHz ~ 1 GHz):

Worst-Case Configuration(IEEE 802.11ax-HE40 Channel 134)

Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	34.285	34.75	-6.63	28.12	40.00	-11.88	QP
2	54.517	41.80	-16.10	25.70	40.00	-14.30	QP
3	108.546	48.19	-15.18	33.01	43.50	-10.49	QP
4	180.030	42.70	-11.83	30.87	43.50	-12.63	QP
5	590.351	41.09	-1.03	40.06	46.00	-5.94	QP
6	887.398	33.91	4.58	38.49	46.00	-7.51	QP

Vertical



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	41.448	43.28	-9.32	33.96	40.00	-6.04	QP
2	88.534	52.20	-16.36	35.84	43.50	-7.66	QP
3	177.518	40.99	-11.64	29.35	43.50	-14.15	QP
4	296.502	41.25	-9.10	32.15	46.00	-13.85	QP
5	590.351	40.37	-1.03	39.34	46.00	-6.66	QP
6	887.398	35.64	4.58	40.22	46.00	-5.78	QP

Radiated Emission Test Data (Above 1GHz): Worst-Case Configuration								
No.	Frequency (MHz)	Reading (dBµV)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11a_Channel 36								
1	10360	39.4	3.4	42.8	54	-11.3	Average	Horizontal
2	10360	55.8	3.4	59.2	68.2	-9.0	Peak	Horizontal
3	15540	31.6	7.6	39.1	54	-14.9	Average	Horizontal
4	15540	43.9	7.6	51.5	74	-22.5	Peak	Horizontal
5	10360	39.3	3.4	42.7	54	-11.4	Average	Vertical
6	10360	56.5	3.4	59.9	68.2	-8.3	Peak	Vertical
7	15540	31.5	7.6	39.1	54	-15.0	Average	Vertical
8	15540	44.7	7.6	52.3	74	-21.8	Peak	Vertical
IEEE 802.11a_Channel 44								
1	10440	39.2	3.4	42.6	54	-11.4	Average	Horizontal
2	10440	54.7	3.4	58.0	68.2	-10.2	Peak	Horizontal
3	15660	32.2	7.5	39.7	54	-14.3	Average	Horizontal
4	15660	44.2	7.5	51.6	74	-22.4	Peak	Horizontal
5	10440	38.3	3.4	41.7	54	-12.3	Average	Vertical
6	10440	54.9	3.4	58.3	68.2	-9.9	Peak	Vertical
7	15660	32.1	7.5	39.5	54	-14.5	Average	Vertical
8	15660	44.8	7.5	52.2	74	-21.8	Peak	Vertical
IEEE 802.11a_Channel 48								
1	10480	37.5	3.4	40.9	54	-13.1	Average	Horizontal
2	10480	55.6	3.4	59.0	68.2	-9.2	Peak	Horizontal
3	15720	32.0	7.4	39.4	54	-14.6	Average	Horizontal
4	15720	45.3	7.4	52.7	74	-21.3	Peak	Horizontal
5	10480	37.7	3.4	41.1	54	-12.9	Average	Vertical
6	10480	53.9	3.4	57.3	68.2	-10.9	Peak	Vertical
7	15720	31.9	7.4	39.3	54	-14.7	Average	Vertical
8	15720	44.3	7.4	51.7	74	-22.3	Peak	Vertical
IEEE 802.11a_Channel 52								
1	10520	37.8	3.4	41.2	54	-12.8	Average	Horizontal
2	10520	53.8	3.4	57.1	68.2	-11.1	Peak	Horizontal
3	15780	32.1	7.4	39.5	54	-14.6	Average	Horizontal
4	15780	45.4	7.4	52.8	74	-21.2	Peak	Horizontal
5	10520	37.7	3.4	41.1	54	-12.9	Average	Vertical
6	10520	54.2	3.4	57.5	68.2	-10.7	Peak	Vertical
7	15780	32.2	7.4	39.5	54	-14.5	Average	Vertical
8	15780	44.5	7.4	51.9	74	-22.1	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11a_Channel 60								
1	10600	37.3	3.2	40.5	54	-13.5	Average	Horizontal
2	10600	53.6	3.2	56.8	74	-17.2	Peak	Horizontal
3	15900	30.9	7.2	38.1	54	-15.9	Average	Horizontal
4	15900	43.8	7.2	51.1	74	-22.9	Peak	Horizontal
5	10600	37.2	3.2	40.4	54	-13.6	Average	Vertical
6	10600	53.1	3.2	56.3	74	-17.7	Peak	Vertical
7	15900	30.8	7.2	38.0	54	-16.0	Average	Vertical
8	15900	43.9	7.2	51.2	74	-22.8	Peak	Vertical
IEEE 802.11a_Channel 64								
1	10640	36.1	3.1	39.2	54	-14.8	Average	Horizontal
2	10640	50.7	3.1	53.8	74	-20.3	Peak	Horizontal
3	15960	30.9	7.2	38.0	54	-16.0	Average	Horizontal
4	15960	44.1	7.2	51.2	74	-22.8	Peak	Horizontal
5	10640	36.3	3.1	39.4	54	-14.6	Average	Vertical
6	10640	51.3	3.1	54.4	74	-19.6	Peak	Vertical
7	15960	30.9	7.2	38.0	54	-16.0	Average	Vertical
8	15960	43.3	7.2	50.5	74	-23.5	Peak	Vertical
IEEE 802.11a_Channel 100								
1	11000	35.8	2.4	38.1	54	-15.9	Average	Horizontal
2	11000	50.9	2.4	53.2	74	-20.8	Peak	Horizontal
3	16500	31.9	8.0	39.9	54	-14.1	Average	Horizontal
4	16500	44.6	8.0	52.6	68.2	-15.6	Peak	Horizontal
5	11000	35.1	2.4	37.5	54	-16.5	Average	Vertical
6	11000	48.5	2.4	50.9	74	-23.1	Peak	Vertical
7	16500	32.0	8.0	40.0	54	-14.0	Average	Vertical
8	16500	45.0	8.0	53.0	68.2	-15.2	Peak	Vertical
IEEE 802.11a_Channel 116								
1	11160	33.7	2.3	36.0	54	-18.0	Average	Horizontal
2	11160	48.1	2.3	50.4	74	-23.7	Peak	Horizontal
3	16740	31.1	8.3	39.4	54	-14.6	Average	Horizontal
4	16740	43.7	8.3	52.0	68.2	-16.2	Peak	Horizontal
5	11160	33.4	2.3	35.6	54	-18.4	Average	Vertical
6	11160	46.5	2.3	48.8	74	-25.3	Peak	Vertical
7	16740	31.2	8.3	39.5	54	-14.5	Average	Vertical
8	16740	44.2	8.3	52.5	68.2	-15.7	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11a_Channel 140								
1	11400	33.5	2.1	35.6	54	-18.4	Average	Horizontal
2	11400	46.5	2.1	48.6	74	-25.4	Peak	Horizontal
3	17100	31.8	8.8	40.6	54	-13.4	Average	Horizontal
4	17100	44.1	8.8	52.9	68.2	-15.3	Peak	Horizontal
5	11400	32.9	2.1	35.0	54	-19.0	Average	Vertical
6	11400	44.9	2.1	47.0	74	-27.0	Peak	Vertical
7	17100	31.8	8.8	40.6	54	-13.4	Average	Vertical
8	17100	44.1	8.8	52.8	68.2	-15.4	Peak	Vertical
IEEE 802.11a_Channel 144								
1	11440	33.2	2.1	35.3	54	-18.7	Average	Horizontal
2	11440	46.2	2.1	48.3	74	-25.7	Peak	Horizontal
3	17160	31.6	8.9	40.5	54	-13.5	Average	Horizontal
4	17160	44.0	8.9	52.9	68.2	-15.3	Peak	Horizontal
5	11440	32.4	2.1	34.5	54	-19.5	Average	Vertical
6	11440	44.5	2.1	46.6	74	-27.4	Peak	Vertical
7	17160	31.5	8.9	40.4	54	-13.6	Average	Vertical
8	17160	44.6	8.9	53.4	68.2	-14.8	Peak	Vertical
IEEE 802.11a_Channel 149								
1	11490	32.5	2.1	34.6	54	-19.5	Average	Horizontal
2	11490	45.7	2.1	47.8	74	-26.2	Peak	Horizontal
3	17235	30.9	9.0	39.9	54	-14.1	Average	Horizontal
4	17235	43.3	9.0	52.3	68.2	-16.0	Peak	Horizontal
5	11490	32.0	2.1	34.0	54	-20.0	Average	Vertical
6	11490	44.4	2.1	46.4	74	-27.6	Peak	Vertical
7	17235	30.9	9.0	39.9	54	-14.1	Average	Vertical
8	17235	43.3	9.0	52.3	68.2	-15.9	Peak	Vertical
IEEE 802.11a_Channel 157								
1	11570	33.1	2.1	35.1	54	-18.9	Average	Horizontal
2	11570	46.7	2.1	48.8	74	-25.3	Peak	Horizontal
3	17355	30.6	9.2	39.8	54	-14.2	Average	Horizontal
4	17355	42.9	9.2	52.1	68.2	-16.1	Peak	Horizontal
5	11570	31.7	2.1	33.8	54	-20.2	Average	Vertical
6	11570	44.0	2.1	46.1	74	-27.9	Peak	Vertical
7	17355	30.5	9.2	39.7	54	-14.3	Average	Vertical
8	17355	43.1	9.2	52.3	68.2	-15.9	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11a_Channel 165								
1	11650	33.8	2.1	35.9	54	-18.1	Average	Horizontal
2	11650	50.0	2.1	52.0	74	-22.0	Peak	Horizontal
3	17475	29.7	9.3	39.0	54	-15.0	Average	Horizontal
4	17475	42.5	9.3	51.8	68.2	-16.4	Peak	Horizontal
5	11650	32.4	2.1	34.5	54	-19.5	Average	Vertical
6	11650	44.7	2.1	46.8	74	-27.2	Peak	Vertical
7	17475	29.8	9.3	39.1	54	-14.9	Average	Vertical
8	17475	42.9	9.3	52.2	68.2	-16.0	Peak	Vertical
IEEE 802.11n-HT20_Channel 36								
1	10360	39.2	3.4	42.6	54	-11.4	Average	Horizontal
2	10360	56.6	3.4	60.0	68.2	-8.2	Peak	Horizontal
3	15540	31.9	7.6	39.5	54	-14.5	Average	Horizontal
4	15540	44.1	7.6	51.6	74	-22.4	Peak	Horizontal
5	10360	37.1	3.4	40.4	54	-13.6	Average	Vertical
6	10360	53.0	3.4	56.4	68.2	-11.8	Peak	Vertical
7	15540	32.0	7.6	39.6	54	-14.4	Average	Vertical
8	15540	45.6	7.6	53.2	74	-20.8	Peak	Vertical
IEEE 802.11n-HT20_Channel 44								
1	10440	39.3	3.4	42.7	54	-11.3	Average	Horizontal
2	10440	53.9	3.4	57.3	68.2	-10.9	Peak	Horizontal
3	15660	32.6	7.5	40.0	54	-14.0	Average	Horizontal
4	15660	44.9	7.5	52.3	74	-21.7	Peak	Horizontal
5	10440	37.2	3.4	40.5	54	-13.5	Average	Vertical
6	10440	51.7	3.4	55.0	68.2	-13.2	Peak	Vertical
7	15660	32.4	7.5	39.9	54	-14.1	Average	Vertical
8	15660	45.1	7.5	52.6	74	-21.4	Peak	Vertical
IEEE 802.11n-HT20_Channel 48								
1	10480	36.8	3.4	40.2	54	-13.8	Average	Horizontal
2	10480	53.7	3.4	57.1	68.2	-11.2	Peak	Horizontal
3	15720	32.0	7.4	39.4	54	-14.6	Average	Horizontal
4	15720	45.0	7.4	52.4	74	-21.6	Peak	Horizontal
5	10480	36.1	3.4	39.5	54	-14.5	Average	Vertical
6	10480	50.8	3.4	54.2	68.2	-14.0	Peak	Vertical
7	15720	32.1	7.4	39.5	54	-14.6	Average	Vertical
8	15720	45.1	7.4	52.5	74	-21.5	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT20_Channel 52								
1	10520	37.6	3.4	40.9	54	-13.1	Average	Horizontal
2	10520	53.1	3.4	56.4	68.2	-11.8	Peak	Horizontal
3	15780	32.2	7.4	39.5	54	-14.5	Average	Horizontal
4	15780	44.9	7.4	52.3	74	-21.7	Peak	Horizontal
5	10520	36.7	3.4	40.1	54	-13.9	Average	Vertical
6	10520	52.9	3.4	56.3	68.2	-11.9	Peak	Vertical
7	15780	32.2	7.4	39.5	54	-14.5	Average	Vertical
8	15780	46.1	7.4	53.4	74	-20.6	Peak	Vertical
IEEE 802.11n-HT20_Channel 60								
1	10600	36.3	3.2	39.5	54	-14.5	Average	Horizontal
2	10600	52.4	3.2	55.6	74	-18.4	Peak	Horizontal
3	15900	31.1	7.2	38.3	54	-15.7	Average	Horizontal
4	15900	43.8	7.2	51.0	74	-23.0	Peak	Horizontal
5	10600	35.2	3.2	38.4	54	-15.6	Average	Vertical
6	10600	50.6	3.2	53.8	74	-20.2	Peak	Vertical
7	15900	31.1	7.2	38.3	54	-15.7	Average	Vertical
8	15900	44.3	7.2	51.6	74	-22.5	Peak	Vertical
IEEE 802.11n-HT20 _Channel 64								
1	10640	35.5	3.1	38.6	54	-15.4	Average	Horizontal
2	10640	50.5	3.1	53.6	74	-20.4	Peak	Horizontal
3	15960	31.0	7.2	38.2	54	-15.8	Average	Horizontal
4	15960	43.6	7.2	50.8	74	-23.2	Peak	Horizontal
5	10640	34.3	3.1	37.4	54	-16.6	Average	Vertical
6	10640	49.8	3.1	52.9	74	-21.1	Peak	Vertical
7	15960	31.1	7.2	38.3	54	-15.7	Average	Vertical
8	15960	44.9	7.2	52.1	74	-21.9	Peak	Vertical
IEEE 802.11n-HT20_Channel 100								
1	11000	36.4	2.4	38.7	54	-15.3	Average	Horizontal
2	11000	50.0	2.4	52.3	74	-21.7	Peak	Horizontal
3	16500	31.7	8.0	39.7	54	-14.3	Average	Horizontal
4	16500	44.0	8.0	52.0	68.2	-16.2	Peak	Horizontal
5	11000	34.8	2.4	37.1	54	-16.9	Average	Vertical
6	11000	46.7	2.4	49.1	74	-25.0	Peak	Vertical
7	16500	31.8	8.0	39.8	54	-14.3	Average	Vertical
8	16500	44.7	8.0	52.7	68.2	-15.5	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT20_Channel 116								
1	11160	34.0	2.3	36.2	54	-17.8	Average	Horizontal
2	11160	49.0	2.3	51.3	74	-22.7	Peak	Horizontal
3	16740	31.2	8.3	39.5	54	-14.5	Average	Horizontal
4	16740	43.5	8.3	51.8	68.2	-16.4	Peak	Horizontal
5	11160	32.4	2.3	34.7	54	-19.3	Average	Vertical
6	11160	45.2	2.3	47.4	74	-26.6	Peak	Vertical
7	16740	31.0	8.3	39.3	54	-14.7	Average	Vertical
8	16740	44.2	8.3	52.5	68.2	-15.7	Peak	Vertical
IEEE 802.11n-HT20_Channel 140								
1	11400	33.6	2.1	35.7	54	-18.3	Average	Horizontal
2	11400	46.7	2.1	48.8	74	-25.2	Peak	Horizontal
3	17100	31.9	8.8	40.7	54	-13.3	Average	Horizontal
4	17100	44.7	8.8	53.5	68.2	-14.7	Peak	Horizontal
5	11400	32.1	2.1	34.2	54	-19.8	Average	Vertical
6	11400	44.2	2.1	46.3	74	-27.7	Peak	Vertical
7	17100	31.7	8.8	40.5	54	-13.5	Average	Vertical
8	17100	44.0	8.8	52.8	68.2	-15.4	Peak	Vertical
IEEE 802.11n-HT20_Channel 144								
1	11440	33.3	2.1	35.4	54	-18.6	Average	Horizontal
2	11440	47.3	2.1	49.4	74	-24.6	Peak	Horizontal
3	17160	31.6	8.9	40.5	54	-13.5	Average	Horizontal
4	17160	45.0	8.9	53.9	68.2	-14.3	Peak	Horizontal
5	11440	32.3	2.1	34.4	54	-19.6	Average	Vertical
6	11440	44.3	2.1	46.4	74	-27.6	Peak	Vertical
7	17160	31.6	8.9	40.4	54	-13.6	Average	Vertical
8	17160	44.0	8.9	52.9	68.2	-15.3	Peak	Vertical
IEEE 802.11n-HT20_Channel 149								
1	11490	32.6	2.1	34.7	54	-19.3	Average	Horizontal
2	11490	46.7	2.1	48.7	74	-25.3	Peak	Horizontal
3	17235	30.9	9.0	39.9	54	-14.1	Average	Horizontal
4	17235	43.1	9.0	52.1	68.2	-16.1	Peak	Horizontal
5	11490	31.8	2.1	33.8	54	-20.2	Average	Vertical
6	11490	45.0	2.1	47.1	74	-27.0	Peak	Vertical
7	17235	31.0	9.0	39.9	54	-14.1	Average	Vertical
8	17235	43.2	9.0	52.1	68.2	-16.1	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT20_Channel 157								
1	11570	33.0	2.1	35.1	54	-18.9	Average	Horizontal
2	11570	46.3	2.1	48.3	74	-25.7	Peak	Horizontal
3	17355	30.5	9.2	39.7	54	-14.3	Average	Horizontal
4	17355	43.0	9.2	52.1	68.2	-16.1	Peak	Horizontal
5	11570	31.7	2.1	33.7	54	-20.3	Average	Vertical
6	11570	44.8	2.1	46.8	74	-27.2	Peak	Vertical
7	17355	30.5	9.2	39.7	54	-14.3	Average	Vertical
8	17355	43.3	9.2	52.4	68.2	-15.8	Peak	Vertical
IEEE 802.11n-HT20_Channel 165								
1	11650	33.9	2.1	36.0	54	-18.0	Average	Horizontal
2	11650	48.7	2.1	50.7	74	-23.3	Peak	Horizontal
3	17475	29.7	9.3	39.0	54	-15.0	Average	Horizontal
4	17475	42.2	9.3	51.5	68.2	-16.7	Peak	Horizontal
5	11650	32.4	2.1	34.5	54	-19.5	Average	Vertical
6	11650	44.4	2.1	46.5	74	-27.5	Peak	Vertical
7	17475	29.8	9.3	39.1	54	-14.9	Average	Vertical
8	17475	41.8	9.3	51.2	68.2	-17.1	Peak	Vertical
IEEE 802.11n-HT40_Channel 38								
1	10380	40.6	3.4	44.0	54	-10.0	Average	Horizontal
2	10380	54.4	3.4	57.8	68.2	-10.5	Peak	Horizontal
3	15570	32.1	7.5	39.6	54	-14.4	Average	Horizontal
4	15570	44.6	7.5	52.1	74	-21.9	Peak	Horizontal
5	10380	37.8	3.4	41.2	54	-12.8	Average	Vertical
6	10380	49.8	3.4	53.2	68.2	-15.0	Peak	Vertical
7	15570	32.0	7.5	39.5	54	-14.5	Average	Vertical
8	15570	45.5	7.5	53.0	74	-21.0	Peak	Vertical
IEEE 802.11n-HT40_Channel 46								
1	10460	39.4	3.4	42.8	54	-11.2	Average	Horizontal
2	10460	53.5	3.4	56.9	68.2	-11.3	Peak	Horizontal
3	15690	32.6	7.4	40.0	54	-14.0	Average	Horizontal
4	15690	45.6	7.4	53.0	74	-21.0	Peak	Horizontal
5	10460	37.5	3.4	40.9	54	-13.1	Average	Vertical
6	10460	51.0	3.4	54.4	68.2	-13.8	Peak	Vertical
7	15690	32.6	7.4	40.0	54	-14.0	Average	Vertical
8	15690	45.7	7.4	53.1	74	-20.9	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT40_Channel 54								
1	10540	37.9	3.3	41.2	54	-12.8	Average	Horizontal
2	10540	50.8	3.3	54.1	68.2	-14.1	Peak	Horizontal
3	15810	31.4	7.3	38.7	54	-15.3	Average	Horizontal
4	15810	44.1	7.3	51.5	74	-22.5	Peak	Horizontal
5	10540	36.9	3.3	40.2	54	-13.8	Average	Vertical
6	10540	50.2	3.3	53.5	68.2	-14.7	Peak	Vertical
7	15810	31.4	7.3	38.8	54	-15.2	Average	Vertical
8	15810	43.6	7.3	51.0	74	-23.0	Peak	Vertical
IEEE 802.11n-HT40_Channel 62								
1	10620	38.2	3.1	41.3	54	-12.7	Average	Horizontal
2	10620	50.7	3.1	53.8	74	-20.2	Peak	Horizontal
3	15930	30.9	7.2	38.1	54	-15.9	Average	Horizontal
4	15930	43.5	7.2	50.7	74	-23.3	Peak	Horizontal
5	10620	36.7	3.1	39.8	54	-14.2	Average	Vertical
6	10620	49.9	3.1	53.0	74	-21.0	Peak	Vertical
7	15930	30.8	7.2	38.0	54	-16.0	Average	Vertical
8	15930	43.8	7.2	51.0	74	-23.0	Peak	Vertical
IEEE 802.11n-HT40_Channel 102								
1	11020	35.2	2.4	37.6	54	-16.5	Average	Horizontal
2	11020	49.1	2.4	51.5	74	-22.5	Peak	Horizontal
3	16530	31.7	8.0	39.8	54	-14.3	Average	Horizontal
4	16530	45.0	8.0	53.0	68.2	-15.2	Peak	Horizontal
5	11020	34.4	2.4	36.7	54	-17.3	Average	Vertical
6	11020	47.3	2.4	49.7	74	-24.3	Peak	Vertical
7	16530	31.7	8.0	39.8	54	-14.3	Average	Vertical
8	16530	44.5	8.0	52.5	68.2	-15.7	Peak	Vertical
IEEE 802.11n-HT40_Channel 110								
1	11100	34.2	2.3	36.5	54	-17.5	Average	Horizontal
2	11100	47.8	2.3	50.1	74	-23.9	Peak	Horizontal
3	16650	31.3	8.2	39.5	54	-14.5	Average	Horizontal
4	16650	43.9	8.2	52.1	68.2	-16.1	Peak	Horizontal
5	11100	33.6	2.3	35.9	54	-18.1	Average	Vertical
6	11100	45.5	2.3	47.8	74	-26.2	Peak	Vertical
7	16650	31.3	8.2	39.5	54	-14.5	Average	Vertical
8	16650	43.8	8.2	52.0	68.2	-16.2	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT40_Channel 134								
1	11340	34.5	2.2	36.7	54	-17.3	Average	Horizontal
2	11340	46.4	2.2	48.6	74	-25.5	Peak	Horizontal
3	17010	31.6	8.7	40.3	54	-13.7	Average	Horizontal
4	17010	44.5	8.7	53.2	68.2	-15.0	Peak	Horizontal
5	11340	32.9	2.2	35.0	54	-19.0	Average	Vertical
6	11340	45.6	2.2	47.8	74	-26.2	Peak	Vertical
7	17010	31.6	8.7	40.3	54	-13.7	Average	Vertical
8	17010	44.5	8.7	53.2	68.2	-15.1	Peak	Vertical
IEEE 802.11n-HT40_Channel 142								
1	11420	33.1	2.1	35.2	54	-18.8	Average	Horizontal
2	11420	45.1	2.1	47.2	74	-26.8	Peak	Horizontal
3	17130	31.5	8.8	40.3	54	-13.7	Average	Horizontal
4	17130	44.5	8.8	53.3	68.2	-14.9	Peak	Horizontal
5	11420	32.7	2.1	34.8	54	-19.3	Average	Vertical
6	11420	44.2	2.1	46.3	74	-27.7	Peak	Vertical
7	17130	31.5	8.8	40.3	54	-13.7	Average	Vertical
8	17130	44.2	8.8	53.0	68.2	-15.2	Peak	Vertical
IEEE 802.11n-HT40_Channel 151								
1	11510	33.7	2.1	35.8	54	-18.2	Average	Horizontal
2	11510	47.8	2.1	49.9	74	-24.1	Peak	Horizontal
3	17265	30.9	9.0	39.9	54	-14.1	Average	Horizontal
4	17265	43.1	9.0	52.1	68.2	-16.1	Peak	Horizontal
5	11510	32.8	2.1	34.9	54	-19.1	Average	Vertical
6	11510	45.8	2.1	47.9	74	-26.1	Peak	Vertical
7	17265	30.9	9.0	39.9	54	-14.1	Average	Vertical
8	17265	43.0	9.0	52.0	68.2	-16.2	Peak	Vertical
IEEE 802.11n-HT40_Channel 159								
1	11590	33.5	2.1	35.6	54	-18.4	Average	Horizontal
2	11590	45.8	2.1	47.8	74	-26.2	Peak	Horizontal
3	17385	30.9	9.2	40.1	54	-13.9	Average	Horizontal
4	17385	43.4	9.2	52.6	68.2	-15.6	Peak	Horizontal
5	11590	32.3	2.1	34.4	54	-19.6	Average	Vertical
6	11590	44.6	2.1	46.7	74	-27.3	Peak	Vertical
7	17385	30.8	9.2	40.0	54	-14.0	Average	Vertical
8	17385	43.2	9.2	52.4	68.2	-15.8	Peak	Vertical

Radiated Emission Test Data (Above 1GHz): Worst-Case Configuration								
No.	Frequency (MHz)	Reading (dBµV)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ax-HE20_Channel 36								
1	10360	38.6	3.4	42.0	54	-12.0	Average	Horizontal
2	10360	55.7	3.4	59.1	68.2	-9.1	Peak	Horizontal
3	15540	32.0	7.6	39.6	54	-14.4	Average	Horizontal
4	15540	44.2	7.6	51.7	74	-22.3	Peak	Horizontal
5	10360	37.3	3.4	40.6	54	-13.4	Average	Vertical
6	10360	51.5	3.4	54.9	68.2	-13.3	Peak	Vertical
7	15540	31.9	7.6	39.5	54	-14.5	Average	Vertical
8	15540	45.0	7.6	52.5	74	-21.5	Peak	Vertical
IEEE 802.11ax-HE20_Channel 44								
1	10440	39.3	3.4	42.7	54	-11.4	Average	Horizontal
2	10440	54.5	3.4	57.8	68.2	-10.4	Peak	Horizontal
3	15660	32.4	7.5	39.9	54	-14.1	Average	Horizontal
4	15660	45.3	7.5	52.8	74	-21.2	Peak	Horizontal
5	10440	37.5	3.4	40.9	54	-13.1	Average	Vertical
6	10440	52.2	3.4	55.6	68.2	-12.6	Peak	Vertical
7	15660	32.4	7.5	39.9	54	-14.1	Average	Vertical
8	15660	44.8	7.5	52.2	74	-21.8	Peak	Vertical
IEEE 802.11ax-HE20_Channel 48								
1	10480	37.7	3.4	41.1	54	-12.9	Average	Horizontal
2	10480	53.2	3.4	56.6	68.2	-11.7	Peak	Horizontal
3	15720	32.1	7.4	39.5	54	-14.5	Average	Horizontal
4	15720	44.9	7.4	52.3	74	-21.7	Peak	Horizontal
5	10480	35.8	3.4	39.2	54	-14.8	Average	Vertical
6	10480	52.0	3.4	55.4	68.2	-12.8	Peak	Vertical
7	15720	32.1	7.4	39.5	54	-14.5	Average	Vertical
8	15720	44.7	7.4	52.1	74	-21.9	Peak	Vertical
IEEE 802.11ax-HE20_Channel 52								
1	10520	37.4	3.4	40.8	54	-13.2	Average	Horizontal
2	10520	53.1	3.4	56.4	68.2	-11.8	Peak	Horizontal
3	15780	32.1	7.4	39.4	54	-14.6	Average	Horizontal
4	15780	44.2	7.4	51.6	74	-22.4	Peak	Horizontal
5	10520	36.6	3.4	39.9	54	-14.1	Average	Vertical
6	10520	50.3	3.4	53.7	68.2	-14.6	Peak	Vertical
7	15780	32.2	7.4	39.5	54	-14.5	Average	Vertical
8	15780	44.4	7.4	51.8	74	-22.2	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ax-HE20_Channel 60								
1	10600	36.1	3.2	39.3	54	-14.7	Average	Horizontal
2	10600	50.2	3.2	53.4	74	-20.6	Peak	Horizontal
3	15900	30.9	7.2	38.1	54	-15.9	Average	Horizontal
4	15900	43.7	7.2	50.9	74	-23.1	Peak	Horizontal
5	10600	35.3	3.2	38.5	54	-15.5	Average	Vertical
6	10600	50.2	3.2	53.4	74	-20.6	Peak	Vertical
7	15900	30.9	7.2	38.1	54	-15.9	Average	Vertical
8	15900	43.0	7.2	50.2	74	-23.8	Peak	Vertical
IEEE 802.11ax-HE20_Channel 64								
1	10640	35.2	3.1	38.3	54	-15.7	Average	Horizontal
2	10640	49.3	3.1	52.4	74	-21.6	Peak	Horizontal
3	15960	30.9	7.2	38.1	54	-15.9	Average	Horizontal
4	15960	43.3	7.2	50.4	74	-23.6	Peak	Horizontal
5	10640	34.7	3.1	37.8	54	-16.2	Average	Vertical
6	10640	49.0	3.1	52.1	74	-21.9	Peak	Vertical
7	15960	31.0	7.2	38.2	54	-15.8	Average	Vertical
8	15960	43.8	7.2	50.9	74	-23.1	Peak	Vertical
IEEE 802.11ax-HE20_Channel 100								
1	11000	36.1	2.4	38.5	54	-15.5	Average	Horizontal
2	11000	52.1	2.4	54.5	74	-19.5	Peak	Horizontal
3	16500	31.7	8.0	39.7	54	-14.3	Average	Horizontal
4	16500	44.6	8.0	52.6	68.2	-15.6	Peak	Horizontal
5	11000	34.7	2.4	37.1	54	-16.9	Average	Vertical
6	11000	48.1	2.4	50.5	74	-23.5	Peak	Vertical
7	16500	31.7	8.0	39.7	54	-14.3	Average	Vertical
8	16500	44.1	8.0	52.1	68.2	-16.1	Peak	Vertical
IEEE 802.11ax-HE20_Channel 116								
1	11160	33.8	2.3	36.1	54	-18.0	Average	Horizontal
2	11160	49.6	2.3	51.9	74	-22.1	Peak	Horizontal
3	16740	31.2	8.3	39.5	54	-14.5	Average	Horizontal
4	16740	43.8	8.3	52.1	68.2	-16.1	Peak	Horizontal
5	11160	32.9	2.3	35.2	54	-18.8	Average	Vertical
6	11160	45.8	2.3	48.0	74	-26.0	Peak	Vertical
7	16740	31.1	8.3	39.4	54	-14.6	Average	Vertical
8	16740	43.9	8.3	52.2	68.2	-16.0	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ax-HE20_Channel 140								
1	11400	34.1	2.1	36.2	54	-17.8	Average	Horizontal
2	11400	47.9	2.1	50.0	74	-24.0	Peak	Horizontal
3	17100	31.3	8.8	40.1	54	-13.9	Average	Horizontal
4	17100	43.5	8.8	52.3	68.2	-15.9	Peak	Horizontal
5	11400	33.4	2.1	35.5	54	-18.5	Average	Vertical
6	11400	46.0	2.1	48.1	74	-25.9	Peak	Vertical
7	17100	31.4	8.8	40.2	54	-13.8	Average	Vertical
8	17100	44.4	8.8	53.2	68.2	-15.0	Peak	Vertical
IEEE 802.11ax-HE20_Channel 144								
1	11440	33.3	2.1	35.4	54	-18.6	Average	Horizontal
2	11440	47.1	2.1	49.2	74	-24.8	Peak	Horizontal
3	17160	31.0	8.9	39.9	54	-14.1	Average	Horizontal
4	17160	44.0	8.9	52.9	68.2	-15.3	Peak	Horizontal
5	11440	33.0	2.1	35.1	54	-18.9	Average	Vertical
6	11440	46.0	2.1	48.0	74	-26.0	Peak	Vertical
7	17160	31.0	8.9	39.9	54	-14.1	Average	Vertical
8	17160	44.1	8.9	53.0	68.2	-15.3	Peak	Vertical
IEEE 802.11ax-HE20_Channel 149								
1	11490	32.8	2.1	34.8	54	-19.2	Average	Horizontal
2	11490	46.8	2.1	48.8	74	-25.2	Peak	Horizontal
3	17235	31.0	9.0	39.9	54	-14.1	Average	Horizontal
4	17235	43.3	9.0	52.3	68.2	-15.9	Peak	Horizontal
5	11490	32.2	2.1	34.3	54	-19.7	Average	Vertical
6	11490	44.2	2.1	46.3	74	-27.7	Peak	Vertical
7	17235	31.0	9.0	39.9	54	-14.1	Average	Vertical
8	17235	43.9	9.0	52.9	68.2	-15.3	Peak	Vertical
IEEE 802.11ax-HE20_Channel 157								
1	11570	33.4	2.1	35.4	54	-18.6	Average	Horizontal
2	11570	45.6	2.1	47.6	74	-26.4	Peak	Horizontal
3	17355	31.1	9.2	40.3	54	-13.8	Average	Horizontal
4	17355	43.9	9.2	53.1	68.2	-15.1	Peak	Horizontal
5	11570	32.3	2.1	34.4	54	-19.6	Average	Vertical
6	11570	44.2	2.1	46.3	74	-27.7	Peak	Vertical
7	17355	31.1	9.2	40.3	54	-13.8	Average	Vertical
8	17355	43.6	9.2	52.8	68.2	-15.4	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ax-HE20_Channel 165								
1	11650	34.0	2.1	36.1	54	-17.9	Average	Horizontal
2	11650	48.1	2.1	50.2	74	-23.8	Peak	Horizontal
3	17475	30.3	9.3	39.6	54	-14.4	Average	Horizontal
4	17475	42.8	9.3	52.1	68.2	-16.1	Peak	Horizontal
5	11650	33.3	2.1	35.3	54	-18.7	Average	Vertical
6	11650	45.7	2.1	47.8	74	-26.2	Peak	Vertical
7	17475	30.2	9.3	39.5	54	-14.5	Average	Vertical
8	17475	42.6	9.3	51.9	68.2	-16.3	Peak	Vertical
IEEE 802.11ax-HE40_Channel 38								
1	10380	40.5	3.4	43.9	54	-10.1	Average	Horizontal
2	10380	52.8	3.4	56.2	68.2	-12.0	Peak	Horizontal
3	15570	32.0	7.5	39.6	54	-14.4	Average	Horizontal
4	15570	45.1	7.5	52.7	74	-21.4	Peak	Horizontal
5	10380	37.3	3.4	40.7	54	-13.3	Average	Vertical
6	10380	49.9	3.4	53.3	68.2	-14.9	Peak	Vertical
7	15570	32.1	7.5	39.7	54	-14.3	Average	Vertical
8	15570	44.6	7.5	52.2	74	-21.8	Peak	Vertical
IEEE 802.11ax-HE40_Channel 46								
1	10460	39.4	3.4	42.8	54	-11.2	Average	Horizontal
2	10460	52.9	3.4	56.3	68.2	-11.9	Peak	Horizontal
3	15690	32.6	7.4	40.1	54	-14.0	Average	Horizontal
4	15690	45.2	7.4	52.6	74	-21.4	Peak	Horizontal
5	10460	37.5	3.4	40.9	54	-13.1	Average	Vertical
6	10460	50.5	3.4	53.9	68.2	-14.3	Peak	Vertical
7	15690	32.7	7.4	40.1	54	-13.9	Average	Vertical
8	15690	45.0	7.4	52.5	74	-21.5	Peak	Vertical
IEEE 802.11ax-HE40_Channel 54								
1	10540	38.0	3.3	41.3	54	-12.7	Average	Horizontal
2	10540	53.0	3.3	56.3	68.2	-11.9	Peak	Horizontal
3	15810	31.6	7.3	38.9	54	-15.1	Average	Horizontal
4	15810	44.9	7.3	52.2	74	-21.8	Peak	Horizontal
5	10540	37.0	3.3	40.3	54	-13.7	Average	Vertical
6	10540	51.4	3.3	54.7	68.2	-13.5	Peak	Vertical
7	15810	31.6	7.3	38.9	54	-15.1	Average	Vertical
8	15810	44.3	7.3	51.7	74	-22.3	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ax-HE40_Channel 62								
1	10620	38.0	3.1	41.1	54	-12.9	Average	Horizontal
2	10620	50.5	3.1	53.6	74	-20.4	Peak	Horizontal
3	15930	31.0	7.2	38.2	54	-15.8	Average	Horizontal
4	15930	43.6	7.2	50.8	74	-23.2	Peak	Horizontal
5	10620	36.9	3.1	40.1	54	-13.9	Average	Vertical
6	10620	49.0	3.1	52.2	74	-21.8	Peak	Vertical
7	15930	31.0	7.2	38.3	54	-15.8	Average	Vertical
8	15930	44.0	7.2	51.2	74	-22.8	Peak	Vertical
IEEE 802.11ax-HE40_Channel 102								
1	11020	35.3	2.4	37.6	54	-16.4	Average	Horizontal
2	11020	47.9	2.4	50.3	74	-23.8	Peak	Horizontal
3	16530	31.9	8.0	39.9	54	-14.1	Average	Horizontal
4	16530	44.0	8.0	52.0	68.2	-16.2	Peak	Horizontal
5	11020	34.5	2.4	36.8	54	-17.2	Average	Vertical
6	11020	46.5	2.4	48.9	74	-25.1	Peak	Vertical
7	16530	31.9	8.0	39.9	54	-14.1	Average	Vertical
8	16530	44.5	8.0	52.5	68.2	-15.7	Peak	Vertical
IEEE 802.11ax-HE40_Channel 110								
1	11100	34.4	2.3	36.7	54.	-17.3	Average	Horizontal
2	11100	47.4	2.3	49.7	74	-24.3	Peak	Horizontal
3	16650	31.3	8.2	39.5	54.	-14.5	Average	Horizontal
4	16650	44.0	8.2	52.2	68.2	-21.8	Peak	Horizontal
5	11100	33.5	2.3	35.8	54.	-18.2	Average	Vertical
6	11100	45.7	2.3	48.0	74	-26.0	Peak	Vertical
7	16650	31.3	8.2	39.5	54.	-14.5	Average	Vertical
8	16650	43.6	8.2	51.8	68.2	-22.2	Peak	Vertical
IEEE 802.11ax-HE40_Channel 134								
1	11340	34.2	2.2	36.4	54	-17.6	Average	Horizontal
2	11340	46.5	2.2	48.6	74	-25.4	Peak	Horizontal
3	17010	31.7	8.7	40.4	54	-13.6	Average	Horizontal
4	17010	44.2	8.7	52.9	68.2	-15.3	Peak	Horizontal
5	11340	33.0	2.2	35.2	54	-18.8	Average	Vertical
6	11340	45.5	2.2	47.7	74	-26.4	Peak	Vertical
7	17010	31.8	8.7	40.5	54	-13.6	Average	Vertical
8	17010	44.3	8.7	53.0	68.2	-15.2	Peak	Vertical
IEEE 802.11ax-HE40_Channel 142								
1	11420	33.2	2.1	35.3	54	-18.7	Average	Horizontal
2	11420	46.1	2.1	48.2	74	-25.8	Peak	Horizontal
3	17130	31.7	8.8	40.5	54	-13.5	Average	Horizontal
4	17130	44.9	8.8	53.7	68.2	-14.5	Peak	Horizontal
5	11420	32.8	2.1	34.9	54	-19.2	Average	Vertical
6	11420	44.7	2.1	46.8	74	-27.2	Peak	Vertical

7	17130	31.6	8.8	40.4	54	-13.6	Average	Vertical
8	17130	44.5	8.8	53.3	68.2	-14.9	Peak	Vertical

No.	Frequency (MHz)	Reading (dBµV)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ax-HE40_Channel 151								
1	11510	33.9	2.1	35.9	54	-18.1	Average	Horizontal
2	11510	46.1	2.1	48.1	74	-25.9	Peak	Horizontal
3	17265	31.0	9.0	40.0	54	-14.0	Average	Horizontal
4	17265	43.1	9.0	52.2	68.2	-16.0	Peak	Horizontal
5	11510	32.8	2.1	34.8	54	-19.2	Average	Vertical
6	11510	46.2	2.1	48.3	74	-25.8	Peak	Vertical
7	17265	31.0	9.0	40.0	54	-14.0	Average	Vertical
8	17265	44.2	9.0	53.3	68.2	-14.9	Peak	Vertical
IEEE 802.11ax-HE40_Channel 159								
1	11590	33.7	2.1	35.8	54	-18.3	Average	Horizontal
2	11590	45.6	2.1	47.7	74	-26.3	Peak	Horizontal
3	17385	31.0	9.2	40.2	54	-13.8	Average	Horizontal
4	17385	43.5	9.2	52.7	68.2	-15.5	Peak	Horizontal
5	11590	32.6	2.1	34.7	54	-19.3	Average	Vertical
6	11590	44.7	2.1	46.8	74	-27.2	Peak	Vertical
7	17385	31.0	9.2	40.2	54	-13.8	Average	Vertical
8	17385	44.2	9.2	53.4	68.2	-14.8	Peak	Vertical

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit

Band Edge Measurements (Radiated)

IEEE 802.11a

Test Channel:	Channel 36	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5150.000	65.82	74.00	45.91	54.00	Pass

Test Channel:	Channel 36	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5150.000	65.56	74.00	45.27	54.00	Pass

Test Channel:	Channel 64	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5350.000	67.18	74.00	46.45	54.00	Pass

Test Channel:	Channel 64	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5350.000	66.07	74.00	45.54	54.00	Pass

Test Channel:	Channel 100	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5460.000	62.57	68.20	44.62	54.00	Pass
5470.000	65.86	68.20	45.91	68.20	Pass

Test Channel:	Channel 100	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5460.000	62.04	68.20	45.18	54.00	Pass
5470.000	65.95	68.20	45.69	68.20	Pass

Test Channel:	Channel 165	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBm)	Peak Limit (dBm)	Conclusion
5850.000	-23.58	27.00	Pass
5925.000	-35.46	-27.00	Pass

Test Channel:	Channel 165	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBm)	Peak Limit (dBm)	Conclusion
5850.000	-25.88	27.00	Pass
5925.000	-35.20	-27.00	Pass

IEEE 802.11n-HT20

Test Channel:	Channel 36	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5150.000	64.91	74.00	45.94	54.00	Pass

Test Channel:	Channel 36	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5150.000	63.01	74.00	44.59	54.00	Pass

Test Channel:	Channel 64	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5350.000	65.84	74.00	46.38	54.00	Pass

Test Channel:	Channel 64	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5350.000	63.40	74.00	44.93	54.00	Pass

Test Channel:	Channel 100	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5460.000	60.15	68.20	44.31	54.00	Pass
5470.000	64.18	68.20	45.85	68.20	Pass

Test Channel:	Channel 100	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5460.000	60.34	68.20	43.69	54.00	Pass
5470.000	62.78	68.20	44.25	68.20	Pass

Test Channel:	Channel 165	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBm)	Peak Limit (dBm)	Conclusion
5850.000	-23.12	27.00	Pass
5925.000	-35.11	-27.00	Pass

Test Channel:	Channel 165	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBm)	Peak Limit (dBm)	Conclusion
5850.000	-24.27	27.00	Pass
5925.000	-35.74	-27.00	Pass

IEEE 802.11n-HT40

Test Channel:	Channel 38	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5150.000	65.39	74.00	47.48	54.00	Pass

Test Channel:	Channel 38	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5150.000	64.60	74.00	46.97	54.00	Pass

Test Channel:	Channel 62	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5350.000	71.21	74.00	50.02	54.00	Pass

Test Channel:	Channel 62	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5350.000	70.10	74.00	47.43	54.00	Pass

Test Channel:	Channel 102	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5460.000	61.54	68.20	45.66	54.00	Pass
5470.000	65.98	68.20	49.39	68.20	Pass

Test Channel:	Channel 102	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5460.000	60.66	68.20	45.07	54.00	Pass
5470.000	64.95	68.20	48.21	68.20	Pass

Test Channel:	Channel 159	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBm)	Peak Limit (dBm)	Conclusion
5850.000	-27.19	27.00	Pass
5925.000	-35.48	-27.00	Pass

Test Channel:	Channel 159	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBm)	Peak Limit (dBm)	Conclusion
5850.000	-29.86	27.00	Pass
5925.000	-35.47	-27.00	Pass

IEEE 802.11ax-HE20

Test Channel:	Channel 36	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5150.000	64.94	74.00	48.46	54.00	Pass

Test Channel:	Channel 36	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5150.000	63.76	74.00	46.50	54.00	Pass

Test Channel:	Channel 64	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5350.000	69.26	74.00	48.01	54.00	Pass

Test Channel:	Channel 64	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5350.000	66.07	74.00	46.55	54.00	Pass

Test Channel:	Channel 100	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5460.000	62.59	68.20	45.16	54.00	Pass
5470.000	65.29	68.20	48.39	68.20	Pass

Test Channel:	Channel 100	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5460.000	62.08	68.20	44.88	54.00	Pass
5470.000	64.69	68.20	47.63	68.20	Pass

Test Channel:	Channel 165	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBm)	Peak Limit (dBm)	Conclusion
5850.000	-25.33	27.00	Pass
5925.000	-35.23	-27.00	Pass

Test Channel:	Channel 165	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBm)	Peak Limit (dBm)	Conclusion
5850.000	-26.16	27.00	Pass
5925.000	-34.77	-27.00	Pass

IEEE 802.11ax-HE40

Test Channel:	Channel 38	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5150.000	64.00	74.00	46.46	54.00	Pass

Test Channel:	Channel 38	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5150.000	63.94	74.00	47.01	54.00	Pass

Test Channel:	Channel 62	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5350.000	68.76	74.00	46.03	54.00	Pass

Test Channel:	Channel 62	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5350.000	65.61	74.00	45.88	54.00	Pass

Test Channel:	Channel 102	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5460.000	62.86	68.20	46.47	54.00	Pass
5470.000	65.05	68.20	49.92	68.20	Pass

Test Channel:	Channel 102	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBμV/m)	Peak Limit (dBμV/m)	AV level (dBμV/m)	AV Limit (dBμV/m)	Conclusion
5460.000	62.04	68.20	44.72	54.00	Pass
5470.000	64.15	68.20	47.67	68.20	Pass

Test Channel:	Channel 159	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBm)	Peak Limit (dBm)	Conclusion
5850.000	-24.72	27.00	Pass
5925.000	-35.67	-27.00	Pass

Test Channel:	Channel 159	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBm)	Peak Limit (dBm)	Conclusion
5850.000	-28.31	27.00	Pass
5925.000	-35.20	-27.00	Pass

5.8 DYNAMIC FREQUENCY SELECTION

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (h)
RSS-247 Issue 3 Section 6.3

Test Method: KDB 905462 D03 Client Without DFS New Rules v01r02

EUT Operating Mode:

DFS Operational mode	Operating Frequency Range	
	5250 MHz to 5350 MHz	5470 MHz to 5725 MHz
Slave without radar Interference detection function	✓	✓

Applicability:

The following table from KDB905462 and the lists of the applicable requirements for the DFS testing.

Applicability of DFS Requirements Prior to Use of a Channel:

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
Non-Occupancy Period	✓	Not required	Yes
DFS Detection Threshold	✓	Not required	Yes
Channel Availability Check Time	✓	Not required	Not required
U-NII Detection Bandwidth	✓	Not required	Yes

Applicability of DFS requirements during normal operation:

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
DFS Detection Threshold	Yes	Not required
Channel Closing Transmission Time	Yes	Yes
Channel Move Time	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required
Additional requirements for devices with multiple bandwidth modes	**Master Device or Client with Radar Detection**	**Client Without Radar Detection**
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required
Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		

DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection:

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP ≥ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.
Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.
Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

DFS Radar Signal Parameter Values:

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds (See Note 1.)
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. (See Notes 1 and 2.)
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. (See Note 3.)

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.
Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.
Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

DFS Radar Signal Parameter:

Radar Type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time

Table 1-Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	See Note 1.	See Note 1.
1	1	Test A Test B	$\text{Roundup}\left\{\begin{matrix}\left(\frac{1}{360}\right)\\ \left(\frac{19\cdot 10^6}{\text{PRI}_{\mu sec}}\right)\end{matrix}\right\}$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.

Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a
Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A
A minimum of 30 unique waveforms are required for each of the Short Pulse Radar Types 2 through 4. If more than 30 waveforms are used for Short Pulse Radar Types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms.
If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B.
The aggregate is the average of the percentage of successful detections of short pulse radar types

1-4

Table 2-Long Pulse Radar Test Waveform

Radar Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Number of Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

Table 3-Frequency Hopping Radar Test Waveform

Radar Type	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	9	0.333	300	70%	30

In-Service Monitoring: Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period

Limit of In-Service Monitoring:

Reference to DFS Radar Signal Parameter Values.

Test Procedures:

a) One frequency will be chosen from the Operating Channels of the EUT within the 5250-5350 MHz or 5470-5725 MHz bands. For 802.11 devices, the test frequency must contain control signals. This can be verified by disabling channel loading and monitoring the spectrum analyzer. If no control signals are detected, another frequency must be selected within the emission bandwidth where control signals are detected.

b) In case the EUT is a Master Device, a U-NII device operating as a Client Device will be used and it is assumed that the Client will associate with the EUT (Master). For radiated tests, the emissions of the Radar Waveform generator will be directed towards the Master Device. If the Master Device has antenna gain, the main beam of the antenna will be directed toward the radar emitter. Vertical polarization is used for testing.

c) The TCP protocol unicast data stream was generated by the iperf software command line with at least 17% activity ratio over any 100ms period.

d) Timing plots are reported with calculations demonstrating a minimum channel loading of approximately 17% or greater. For example, channel loading can be estimated by setting the spectrum analyzer for zero span and approximate the Time On/ (Time On + Off Time).

e) At time T0 the Radar Waveform generator sends a Burst of pulses for one of the Short Pulse Radar Types 1-4 at DFS Detection Threshold levels on the Operating Channel. An additional 1 dB is added to the radar test signal to ensure it is at or above the DFS Detection Threshold, accounting for equipment variations/errors.

f) Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel for duration greater than 10 seconds. Measure and record the transmissions from the EUT during the observation time (Channel Move Time). Measure and record the Channel Move Time and Channel Closing Transmission Time if radar detection occurs.

g) When operating as a Master Device, monitor the EUT for more than 30 minutes following instant T2 to verify that the EUT does not resume any transmissions on this Channel. Perform this test once and record the measurement result.



Figure 17: Channel Closing Transmission Time, Channel Move Time and Non-Occupancy Period

Conducted test setup



Setup for Client with injection at the Master

Equipment Used: Refer to section 3 for details.

Test Result: Result of Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Tes

The measurement data as follows:

BW / Channel	Test Item	Test Result	Limit	Pass/Fail
20 MHz / 5300 MHz	Channel Move Time	0.9844 s	< 10s	Pass
	Channel Closing Transmission Time	9.9 ms	< 200+60ms	Pass
	Non-Occupancy Period	No transmission	30 minutes	Pass
20 MHz / 5500 MHz	Channel Move Time	0.9778 s	< 10s	Pass
	Channel Closing Transmission Time	6.9 ms	< 200+60ms	Pass
	Non-Occupancy Period	No transmission	30 minutes	Pass
40MHz / 5310 MHz	Channel Move Time	1.0132 s	< 10s	Pass
	Channel Closing Transmission Time	6.3 ms	< 200+60ms	Pass
	Non-Occupancy Period	No transmission	30 minutes	Pass
40MHz / 5510 MHz	Channel Move Time	0.9984 s	< 10s	Pass
	Channel Closing Transmission Time	4.5 ms	< 200+60ms	Pass
	Non-Occupancy Period	No transmission	30 minutes	Pass

Radar Waveform calibration Plot

Reference DFS test signal

5300 MHz



5500 MHz



5310 MHz



5510 MHz



Data Traffic Plot



Channel Move Time & Channel Closing Transmission Time
802.11a_5300 MHz



Note:

1) Mark1 Time: 438.6 ms, Mark2 Time: 10438.6 ms,Ontime Points: 33
2) Dwell = S/B = 12000 ms/40001 = 0.3 ms, C = N x Dwell = 33 x 0.3 = 9.9 ms
3) CMT =1.423 s – 0.4386 s = 0.9844 s

Non-Occupancy Period_802.11a_CH60_5300 MHz



Channel Move Time & Channel Closing Transmission Time
802.11a_5500 MHz



Note:

4) Mark1 Time: 391.2 ms, Mark2 Time: 10391.2 s,Ontime Points: 23
5) Dwell = S/B = 12000 ms/40001 = 0.3 ms, C = N x Dwell = 23 x 0.3 =6.9 ms
6) CMT = 1.369 s – 0.3912 s = 0.9778 s

Non-Occupancy Period_802.11a_CH100_5500 MHz



Channel Move Time & Channel Closing Transmission Time
802.11n_5310 MHz



Note:

7) Mark1 Time: 415.8 ms, Mark2 Time: 10415.8 ms,Ontime Points: 21
8) Dwell = S/B = 12000 ms/40001 = 0.3 ms, C = N x Dwell = 21 x 0.3 = 6.3ms
9) CMT = 1.429 s – 0.4158 s =1.0132 s

Non-Occupancy Period_802.11n_CH58_5310 MHz



Channel Move Time & Channel Closing Transmission Time
802.11n_5510 MHz



Note:

10) Mark1 Time: 351.6 ms, Mark2 Time: 10351.6 ms,Ontime Points: 15
11) Dwell = S/B = 12000 ms/40001 = 0.3 ms, C = N x Dwell = 15 x 0.3 = 4.5 ms
12) CMT = 1.350 s – 0.3516 s = 0.9984 s

Non-Occupancy Period_802.11n_CH106_5510 MHz



5.9 AC POWER LINE CONDUCTED EMISSION

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(6)
FCC 47 CFR Part 15 Subpart C Section 15.207
RSS-Gen Issue 5, Section 8.8

Test Method: ANSI C63.10-2013, Section 6.2.

Limits:

Frequency range (MHz)	Limits (dB(μV)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.5.2 for details.

Test Procedures:

Test frequency range :150KHz-30MHz

1) The mains terminal disturbance voltage test was conducted in a shielded room.
2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The worst measurement data as follows:
Quasi Peak and Average:
Mode: WIFI Link

Live Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.1500	46.17	10.20	56.37	66.00	-9.63	QP
2	0.1500	23.23	10.20	33.43	56.00	-22.57	AVG
3	0.3525	33.03	10.16	43.19	58.90	-15.71	QP
4	0.3525	24.87	10.16	35.03	48.90	-13.87	AVG
5	0.5370	23.46	10.19	33.65	56.00	-22.35	QP
6	0.5370	10.92	10.19	21.11	46.00	-24.89	AVG
7	4.9740	30.94	10.23	41.17	56.00	-14.83	QP
8	4.9740	20.39	10.23	30.62	46.00	-15.38	AVG
9	6.2835	33.22	10.41	43.63	60.00	-16.37	QP
10	6.2835	23.62	10.41	34.03	50.00	-15.97	AVG
11	7.5660	32.87	10.49	43.36	60.00	-16.64	QP
12	7.5660	23.34	10.49	33.83	50.00	-16.17	AVG

Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.1544	43.63	10.18	53.81	65.76	-11.95	QP
2	0.1544	26.51	10.18	36.69	55.76	-19.07	AVG
3	0.3570	35.13	10.15	45.28	58.80	-13.52	QP
4	0.3570	25.17	10.15	35.32	48.80	-13.48	AVG
5	0.6404	22.26	10.25	32.51	56.00	-23.49	QP
6	0.6404	9.45	10.25	19.70	46.00	-26.30	AVG
7	4.8750	28.78	10.27	39.05	56.00	-16.95	QP
8	4.8750	16.77	10.27	27.04	46.00	-18.96	AVG
9	5.9010	31.03	10.28	41.31	60.00	-18.69	QP
10	5.9010	21.49	10.28	31.77	50.00	-18.23	AVG
11	6.8864	31.88	10.29	42.17	60.00	-17.83	QP
12	6.8864	19.89	10.29	30.18	50.00	-19.82	AVG

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

APPENDIX A RF TEST DATA

A.1 99% BANDWIDTH

For U-NII-1, U-NII-2A, U-NII-2C band

Mode	Channel	RU & Index	Ant.	99% BW (MHz)
IEEE 802.11a	36	N/A	0	17.067
	44			17.085
	48			17.135
	52			17.073
	60			17.072
	64			17.091
	100			17.077
	116			17.073
	140			17.127
	144			13.653
IEEE 802.11n_20	36			18.111
	44			18.109
	48			18.142
	52			18.130
	60			18.080
	64			18.139
	100			18.120
	116			18.105
	140			18.081
	144			14.106
IEEE 802.11n_40	38			36.482
	46			36.470
	54			36.486
	62			36.459
	102			36.468
	110			36.455
	134			36.472
	142			33.100
IEEE 802.11ac_20	36			18.089
	44			18.114
	48			18.100
	52			18.100
	60			18.079
	64			18.102
	100			18.094
	116			18.093
	140			18.137
	144			14.144
IEEE 802.11ac_40	38			36.473
	46			36.439
	54			36.495
	62			36.483
	102			36.525
	110			36.520
	134			36.481
	142			33.086
IEEE 802.11ax_20	36	SU		19.158
	44			19.166
	48			19.165
	52			19.162
	60			19.124
	64			19.145
	100			19.112
	116			19.195
	140			19.190
	144			14.587
IEEE 802.11ax_40	38			37.919

	46			37.833
	54			37.857
	62			37.921
	102			37.857
	110			37.869
	134			37.842
	142			33.797

Test Graphs



IEEE 802.11a_Channel 36_20MHz_Antenna 0



IEEE 802.11a_Channel 44_20MHz_Antenna 0



IEEE 802.11a_Channel 48_20MHz_Antenna 0



IEEE 802.11a_Channel 52_20MHz_Antenna 0



IEEE 802.11a_Channel 60_20MHz_Antenna 0



IEEE 802.11a_Channel 64_20MHz_Antenna 0



IEEE 802.11a_Channel 100_20MHz_Antenna 0



IEEE 802.11a_Channel 116_20MHz_Antenna 0



IEEE 802.11a_Channel 140_20MHz_Antenna 0



IEEE 802.11a_Channel 144_20MHz_Antenna 0



IEEE 802.11n_Channel 36_20MHz_Antenna 0



IEEE 802.11n_Channel 44_20MHz_Antenna 0



IEEE 802.11n_Channel 48_20MHz_Antenna 0



IEEE 802.11n_Channel 52_20MHz_Antenna 0



IEEE 802.11n_Channel 60_20MHz_Antenna 0



IEEE 802.11n_Channel 64_20MHz_Antenna 0



IEEE 802.11n_Channel 100_20MHz_Antenna 0