



Certificate #4312.01

TEST REPORT

Product Name: HD Intercom & Facility Control Station
Trade Mark: GRANDSTREAM
Model No.: GSC3575
Add. Model No.: GSC3574
Report Number: 2401279067RFC-1
Test Standards: FCC 47 CFR Part 15 Subpart C
FCC ID: YZZGSC3575
Test Result: PASS
Date of Issue: May 11, 2024

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and
technology park, Longhua district, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:

David Chen

David Chen

Senior Project Engineer

Reviewed by:

*Robben chen*Robben Chen
Assistant Manager

Approved by:



Billy Li

Technical Director

Date:

May 11, 2024

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2

Version

Version No.	Date	Description
V1.0	May 11, 2024	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	5
1.4 OTHER INFORMATION	5
1.5 DESCRIPTION OF SUPPORT UNITS	5
1.6 TEST LOCATION	5
1.7 TEST FACILITY	5
1.8 DEVIATION FROM STANDARDS	6
1.9 ABNORMALITIES FROM STANDARD CONDITIONS	6
1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
1.11 MEASUREMENT UNCERTAINTY	6
2. TEST SUMMARY	7
3. EQUIPMENT LIST	8
4. TEST CONFIGURATION	9
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	9
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	9
4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE	9
4.2 TEST CHANNELS	9
4.3 EUT TEST STATUS	9
4.4 TEST SETUP	10
4.4.1 FOR RADIATED EMISSIONS TEST SETUP	10
4.4.2 FOR CONDUCTED EMISSIONS TEST SETUP	11
4.4.3 FOR CONDUCTED RF TEST SETUP	12
4.5 SYSTEM TEST CONFIGURATION	12
4.6 DUTY CYCLE	13
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION	16
5.1 REFERENCE DOCUMENTS FOR TESTING	16
5.2 ANTENNA REQUIREMENT	16
5.3 CONDUCTED PEAK OUTPUT POWER	17
5.4 6 dB BANDWIDTH & OCCUPIED BANDWIDTH	18
5.5 POWER SPECTRAL DENSITY	19
5.6 CONDUCTED OUT OF BAND EMISSION	20
5.7 RADIATED SPURIOUS EMISSIONS	21
5.8 BAND EDGE MEASUREMENTS (RADIATED)	28
5.9 CONDUCTED EMISSION	37
APPENDIX A RF TEST DATA	40
A.1 99% BANDWIDTH	40
A.2 6dB BANDWIDTH	43
A.3 CONDUCTED OUT OF BAND EMISSION	46
A.4 POWER SPECTRAL DENSITY	52
APPENDIX 1 PHOTOS OF TEST SETUP	55
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	55

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	HD Intercom & Facility Control Station		
Model No.:	GSC3575		
Add. Model No.:	GSC3574		
Trade Mark:	GRANDSTREAM		
DUT Stage:	Identical Prototype		
EUT Supports Function: (Provided by the customer)	2.4 GHz ISM Band:	IEEE 802.11b/g/n/ax	
		Bluetooth V5.0	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac/ax
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac/ax
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac/ax
		5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac/ax
Sample Received Date:	January 26, 2024		
Sample Tested Date:	February 27, 2024 to April 17, 2024		
Remark:	The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.		

1.2.2 Description of Accessories

Cable	
Connector:	USB Cable
Cable Type:	Unshielded without ferrite
Length:	1.0 Meter
Earphone	
	1.2 Meter

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth LE/2LE/LE Code
Type of Modulation:	GFSK
Number of Channels:	40
Channel Separation:	2 MHz
Antenna Type: (Provided by the customer)	PIFA Antenna
Antenna Gain: (Provided by the customer)	4.72 dBi
Maximum Peak Power:	9.36 dBm
Normal Test Voltage:	48 Vdc

1.4 OTHER INFORMATION

Operation Frequency Each of Channel	
$f = 2402 + 2k \text{ MHz}, k = 0, \dots, 39$	
Note:	
f	is the operating frequency (MHz);
k	is the operating channel.

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	DELL	Latitude 3400	16238087894	UnionTrust
Mouse	DELL	MS111	CN-011D3V-738	UnionTrust

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.1Meter	UnionTrust

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China, China 518109

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.9 dB
5	Radiated emission 1GHz-18GHz	± 4.8 dB
6	Radiated emission 18GHz-26GHz	± 5.1 dB
7	Radiated emission 26GHz-40GHz	± 5.1 dB
8	Conducted spurious emissions	± 2.7 dB
9	RF Power, Conducted	± 0.68 dB
10	Occupied Bandwidth	± 1.86 %
11	Radio Frequency	2.4 GHz: ± 6.5 x 10 ⁻⁸
12	Transmission Time	± 0.19 %

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart C Test Cases			
Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203/15.247 (b)	N/A	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013 Clause 6.2	PASS
Conducted Peak Output Power	FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3)	ANSI C63.10-2013 Clause 11.9.1.3	PASS
6dB Bandwidth	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2)	ANSI C63.10-2013 Clause 11.8.1	PASS
Power Spectral Density	FCC 47 CFR Part 15 Subpart C Section 15.247 (e)	ANSI C63.10-2013 Clause 11.10.2	PASS
Conducted Out of Band Emission	FCC 47 CFR Part 15 Subpart C Section 15.247(d)	ANSI C63.10-2013 Clause 11.11	PASS
Radiated Spurious Emissions	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013 Clause 11.11 & Clause 11.12	PASS
Band Edge Measurements (Radiated)	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013 Clause 11.13	PASS
Disclaimer and Explanations: The declared of product specification and data (e.g., antenna gain, RF specification, etc) for EUT presented in the report are provided by the customer, and the customer takes all the responsibilities for the accuracy of product specification.			

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	3m SAC	ETS-LINDGREN	3m	Euroshiedpn-CT001270-1317	11-Nov-2023	10-Nov-2026
☒	Receiver	R&S	ESIB26	100114	27-Oct-2023	26-Oct-2024
☒	Loop Antenna	ETS-LINDGREN	6502	00202525	30-Oct-2023	29-Oct-2024
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	30-Oct-2023	29-Oct-2024
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	30-Oct-2023	29-Oct-2024
☒	Preamplifier	HP	8447F	2805A02960	31-Oct-2023	30-Oct-2024
☒	Band Rejection Filter (2400MHz~2500MHz)	Micro-Tronics	BRM50702	G590	17-Jan-2024	16-Jan-2025
☒	Double-Ridged Waveguide Horn Antenna	ETS-LINDGREN	3117-PA	00201541	16-Apr-2023	15-Apr-2024
					01-Apr-2024	31-Mar-2025
☒	Pre-amplifier	ETS-Lindgren	00118385	00201874	31-Oct-2023	30-Oct-2024
☒	Double-Ridged Waveguide Horn Antenna	ETS-LINDGREN	3116C-PA	00202652	30-Oct-2023	29-Oct-2024
☒	Pre-amplifier	ETS-Lindgren	00118384	00202652	30-Oct-2023	29-Oct-2024
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	Receiver	R&S	ESR7	1316.3003K07-101181-K3	27-Oct-2023	26-Oct-2024
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	27-Oct-2023	26-Oct-2024
☒	LISN	R&S	ESH2-Z5	860014/024	27-Oct-2023	26-Oct-2024
☒	LISN	ETS-Lindgren	3816/2SH	00201088	27-Oct-2023	26-Oct-2024
☒	Test Software	EZ-EMC	EZ-CON	Software Version: EMC-CON 3A1.1		

Conducted RF test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	EXA Spectrum Analyzer	KEYSIGHT	N9020A	MY51286807	27-Oct-2023	26-Oct-2024
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	27-Oct-2023	26-Oct-2024
☐	MXG X-Series RF Vector Signal Generator	KEYSIGHT	N5182B	MY51350267	27-Oct-2023	26-Oct-2024

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NT/NV	+15 to +35	DC 12V 1.5A or DC 44-57V by PoE	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test Sample

Test Item	Temp. (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
AC Power Line Conducted Emission	21.1	43.0	100.1	S202401262671-ZJA01/4	Linson Xie
Conducted Peak Output Power	22.7	56.1	100.1	S202401262671-ZJA03/4	Allen Zhou
6dB Bandwidth					
Power Spectral Density					
Conducted Out of Band Emission	25.8	54.1	100.2	S202401262671-ZJA02/4	Fire Huo
Radiated Spurious Emissions Band Edge Measurements (Radiated)					

4.2 TEST CHANNELS

Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
GFSK	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 19	Channel 39
		2402 MHz	2440 MHz	2480 MHz

4.3 EUT TEST STATUS



Type of Modulation	Tx Function	Description
GFSK	1Tx	1. Keep the EUT in continuously transmitting with modulation test single.


Power Setting (Provided by the customer)
Power Setting: not applicable, test used software default power level.

Test Software (Provided by the customer)
Test software name: Command


4.4 TEST SETUP

4.4.1 For Radiated Emissions test setup






4.4.2 For Conducted Emissions test setup



4.4.3 For Conducted RF test setup



4.5 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in orientation.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.6 DUTY CYCLE

Test Procedure: ANSI C63.10-2013 Clause 11.6.


Test Results


Mode	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/T Minimum VBW (kHz)
LE	2.115	2.505	0.84	84.43	0.73	0.47
2LE	1.065	1.875	0.57	56.80	2.46	0.94
LE Code (S=2)	4.550	5.000	0.91	91.00	0.41	0.22
LE Code (S=8)	17.080	17.500	0.98	97.60	0.11	0.06

Remark:

- 1) Duty cycle= On Time/ Period;
- 2) Duty Cycle factor = $10 * \log(1/\text{Duty cycle})$;

The test plot as follows





Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2



5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
EUT Antenna: Antenna in the interior of the equipment and no consideration of replacement. The gain of the antenna is 4.72 dBi.

5.3 CONDUCTED PEAK OUTPUT POWER

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3)

Test Method: ANSI C63.10-2013 Clause 11.9.1.3

Limit: For systems using digital modulation in the 2400-2483.5 MHz bands: 1 Watt.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter.
2. Measure out each test modes' peak or average output power, record the power level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.4.3 for details.

Instruments Used: Refer to section 3 for details

Test Results: Pass

Mode	Channel	Frequency	Max. Peak Power		Peak Power Limit	Max. Avg. Power	Result
		(MHz)	(dBm)	(W)	(dBm)	(dBm)	
LE	0	2402	8.38	0.00689	30	7.31	Pass
	19	2440	8.96	0.00787	30	7.83	Pass
	39	2480	9.36	0.00863	30	8.23	Pass
2LE	0	2402	8.29	0.00675	30	5.58	Pass
	19	2440	8.88	0.00773	30	6.09	Pass
	39	2480	9.29	0.00849	30	6.52	Pass
LE Code (S=2)	0	2402	8.43	0.00697	30	7.58	Pass
	19	2440	8.92	0.00780	30	8.12	Pass
	39	2480	9.34	0.00859	30	8.53	Pass
LE Code (S=8)	0	2402	8.36	0.00685	30	7.88	Pass
	19	2440	8.89	0.00774	30	8.42	Pass
	39	2480	9.28	0.00847	30	8.82	Pass

Note: The antenna gain of 4.72 dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.

5.46 DB BANDWIDTH & OCCUPIED BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2)
Test Method: ANSI C63.10-2013 Clause 11.8.1
Limit: For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz
Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

6dB Bandwidth

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

- a) Set RBW = 1% to 5% of the occupied bandwidth
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.4.3 for details.
Instruments Used: Refer to section 3 for details
Test Mode: Link mode
Test Results: Please refer to Appendix A

5.5 POWER SPECTRAL DENSITY

Test Requirement:	FCC 47 CFR Part 15 Subpart C Section 15.247 (e)
Test Method:	ANSI C63.10-2013 Clause 11.10.2
Limit:	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
Test Procedure:	Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer. Use the following spectrum analyzer settings: a) Set analyzer center frequency to DTS channel center frequency. b) Set the span to 1.5 times the DTS bandwidth. c) Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$. d) Set the VBW $\geq 3 \times \text{RBW}$. e) Detector = peak. f) Sweep time = auto couple. g) Trace mode = max hold. h) Allow trace to fully stabilize. i) Use the peak marker function to determine the maximum amplitude level within the RBW. j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat. Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.
Test Setup:	Refer to section 4.4.3 for details.
Instruments Used:	Refer to section 3 for details
Test Mode:	Link mode
Test Results:	Please refer to Appendix A

5.6 CONDUCTED OUT OF BAND EMISSION

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247(d)

Test Method: ANSI C63.10-2013 Clause 11.11

Limit: In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Use the following spectrum analyzer settings:

Step 1: Measurement Procedure REF

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to ≥ 1.5 times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW $\geq 3 \times$ RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

Step 2: Measurement Procedure OOB

- a) Set RBW = 100 kHz.
- b) Set VBW ≥ 300 kHz.
- c) Detector = peak.
- d) Sweep = auto couple.
- e) Trace Mode = max hold.
- f) Allow trace to fully stabilize.
- g) Use the peak marker function to determine the maximum amplitude level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.4.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Please refer to Appendix A

5.7 RADIATED SPURIOUS EMISSIONS

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209

Test Method: ANSI C63.10-2013 Clause 11.11 & Clause 11.12

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

Spurious Emissions

Frequency	Field strength (microvolt/meter)	Limit (dB μ V/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB μ V/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.4.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:

- 1) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- 3) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- 6) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

2. Above 1GHz test procedure as below:

- 1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter (Above 18GHz the distance is 1 meter and table is 1.5 meter).

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2

- 2) Test the EUT in the lowest channel, middle channel, the Highest channel
- 3) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the Z axis positioning which it is worse case.
- 4) Repeat above procedures until all frequencies measured was complete.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:


Radiated Emission Test Data (9 kHz ~ 30 MHz):

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Radiated Emission Test Data (30 MHz ~ 1 GHz):


Worst-Case Configuration

Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	26.02	-4.08	21.94	40.00	-18.06	Peak
2	36.524	27.49	-6.87	20.62	40.00	-19.38	Peak
3	50.461	34.38	-13.75	20.63	40.00	-19.37	Peak
4	217.644	30.96	-10.90	20.06	46.00	-25.94	Peak
5	660.602	31.35	0.43	31.78	46.00	-14.22	Peak
6	787.475	37.94	2.72	40.66	46.00	-5.34	QP

Vertical



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.212	27.08	-4.47	22.61	40.00	-17.39	Peak
2	33.101	28.80	-6.42	22.38	40.00	-17.62	Peak
3	41.448	32.38	-9.32	23.06	40.00	-16.94	Peak
4	187.783	27.84	-12.07	15.77	43.50	-27.73	Peak
5	452.001	29.27	-4.10	25.17	46.00	-20.83	Peak
6	787.475	37.91	2.72	40.63	46.00	-5.37	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2

Radiated Emission Test Data (Above 1GHz):
LE_ Lowest Channel:

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.000	26.02	-0.86	25.16	54.00	-28.84	Average	Horizontal
2	4804.000	43.23	-0.86	42.37	74.00	-31.63	Peak	Horizontal
3	7206.000	25.80	2.86	28.66	54.00	-25.34	Average	Horizontal
4	7206.000	38.59	2.86	41.45	74.00	-32.55	Peak	Horizontal
5	4804.000	26.02	-0.86	25.16	54.00	-28.84	Average	Vertical
6	4804.000	38.94	-0.86	38.08	74.00	-35.92	Peak	Vertical
7	7206.000	25.87	2.86	28.73	54.00	-25.27	Average	Vertical
8	7206.000	38.84	2.86	41.70	74.00	-32.30	Peak	Vertical

LE_ Middle Channel:

1	4880.000	27.44	-0.77	26.67	54.00	-27.33	Average	Horizontal
2	4880.000	40.79	-0.77	40.02	74.00	-33.98	Peak	Horizontal
3	7320.000	26.03	2.95	28.98	54.00	-25.02	Average	Horizontal
4	7320.000	37.70	2.95	40.65	74.00	-33.35	Peak	Horizontal
5	4880.000	27.37	-0.77	26.60	54.00	-27.40	Average	Vertical
6	4880.000	40.17	-0.77	39.40	74.00	-34.60	Peak	Vertical
7	7320.000	25.74	2.95	28.69	54.00	-25.31	Average	Vertical
8	7320.000	37.44	2.95	40.39	74.00	-33.61	Peak	Vertical

LE_ Highest Channel:

1	4960.000	27.40	-0.67	26.73	54.00	-27.27	Average	Horizontal
2	4960.000	39.99	-0.67	39.32	74.00	-34.68	Peak	Horizontal
3	7440.000	25.48	3.05	28.53	54.00	-25.47	Average	Horizontal
4	7440.000	37.58	3.05	40.63	74.00	-33.37	Peak	Horizontal
5	4960.000	27.46	-0.67	26.79	54.00	-27.21	Average	Vertical
6	4960.000	40.15	-0.67	39.48	74.00	-34.52	Peak	Vertical
7	7440.000	25.09	3.05	28.14	54.00	-25.86	Average	Vertical
8	7440.000	37.15	3.05	40.20	74.00	-33.80	Peak	Vertical

2LE_ Lowest Channel:								
No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.000	26.23	-0.86	25.37	54.00	-28.63	Average	Horizontal
2	4804.000	43.63	-0.86	42.77	74.00	-31.23	Peak	Horizontal
3	7206.000	25.87	2.86	28.73	54.00	-25.27	Average	Horizontal
4	7206.000	39.18	2.86	42.04	74.00	-31.96	Peak	Horizontal
5	4804.000	26.30	-0.86	25.44	54.00	-28.56	Average	Vertical
6	4804.000	38.90	-0.86	38.04	74.00	-35.96	Peak	Vertical
7	7206.000	25.95	2.86	28.81	54.00	-25.19	Average	Vertical
8	7206.000	38.67	2.86	41.53	74.00	-32.47	Peak	Vertical
2LE_ Middle Channel:								
1	4880.000	27.50	-0.77	26.73	54.00	-27.27	Average	Horizontal
2	4880.000	40.72	-0.77	39.95	74.00	-34.05	Peak	Horizontal
3	7320.000	26.18	2.95	29.13	54.00	-24.87	Average	Horizontal
4	7320.000	37.91	2.95	40.86	74.00	-33.14	Peak	Horizontal
5	4880.000	27.50	-0.77	26.73	54.00	-27.27	Average	Vertical
6	4880.000	40.68	-0.77	39.91	74.00	-34.09	Peak	Vertical
7	7320.000	25.81	2.95	28.76	54.00	-25.24	Average	Vertical
8	7320.000	38.50	2.95	41.45	74.00	-32.55	Peak	Vertical
2LE_ Highest Channel:								
1	4960.000	27.46	-0.67	26.79	54.00	-27.21	Average	Horizontal
2	4960.000	40.40	-0.67	39.73	74.00	-34.27	Peak	Horizontal
3	7440.000	25.48	3.05	28.53	54.00	-25.47	Average	Horizontal
4	7440.000	37.84	3.05	40.89	74.00	-33.11	Peak	Horizontal
5	4960.000	27.40	-0.67	26.73	54.00	-27.27	Average	Vertical
6	4960.000	39.27	-0.67	38.60	74.00	-35.40	Peak	Vertical
7	7440.000	25.01	3.05	28.06	54.00	-25.94	Average	Vertical
8	7440.000	37.17	3.05	40.22	74.00	-33.78	Peak	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2

LE Code (S=2)_ Lowest Channel:								
No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.000	26.02	-0.86	25.16	54.00	-28.84	Average	Horizontal
2	4804.000	41.91	-0.86	41.05	74.00	-32.95	Peak	Horizontal
3	7206.000	25.87	2.86	28.73	54.00	-25.27	Average	Horizontal
4	7206.000	38.22	2.86	41.08	74.00	-32.92	Peak	Horizontal
5	4804.000	25.95	-0.86	25.09	54.00	-28.91	Average	Vertical
6	4804.000	39.58	-0.86	38.72	74.00	-35.28	Peak	Vertical
7	7206.000	25.72	2.86	28.58	54.00	-25.42	Average	Vertical
8	7206.000	38.76	2.86	41.62	74.00	-32.38	Peak	Vertical
LE Code (S=2)_ Middle Channel:								
1	4880.000	27.37	-0.77	26.60	54.00	-27.40	Average	Horizontal
2	4880.000	41.35	-0.77	40.58	74.00	-33.42	Peak	Horizontal
3	7320.000	26.18	2.95	29.13	54.00	-24.87	Average	Horizontal
4	7320.000	38.06	2.95	41.01	74.00	-32.99	Peak	Horizontal
5	4880.000	27.37	-0.77	26.60	54.00	-27.40	Average	Vertical
6	4880.000	40.67	-0.77	39.90	74.00	-34.10	Peak	Vertical
7	7320.000	25.74	2.95	28.69	54.00	-25.31	Average	Vertical
8	7320.000	37.93	2.95	40.88	74.00	-33.12	Peak	Vertical
LE Code (S=2)_ Highest Channel:								
1	4960.000	27.64	-0.67	26.97	54.00	-27.03	Average	Horizontal
2	4960.000	39.47	-0.67	38.80	74.00	-35.20	Peak	Horizontal
3	7440.000	25.40	3.05	28.45	54.00	-25.55	Average	Horizontal
4	7440.000	38.03	3.05	41.08	74.00	-32.92	Peak	Horizontal
5	4960.000	27.40	-0.67	26.73	54.00	-27.27	Average	Vertical
6	4960.000	40.07	-0.67	39.40	74.00	-34.60	Peak	Vertical
7	7440.000	24.92	3.05	27.97	54.00	-26.03	Average	Vertical
8	7440.000	37.15	3.05	40.20	74.00	-33.80	Peak	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2

LE Code (S=8)_ Lowest Channel:								
No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.000	26.02	-0.86	25.16	54.00	-28.84	Average	Horizontal
2	4804.000	44.17	-0.86	43.31	74.00	-30.69	Peak	Horizontal
3	7206.000	25.87	2.86	28.73	54.00	-25.27	Average	Horizontal
4	7206.000	38.54	2.86	41.40	74.00	-32.60	Peak	Horizontal
5	4804.000	26.16	-0.86	25.30	54.00	-28.70	Average	Vertical
6	4804.000	39.00	-0.86	38.14	74.00	-35.86	Peak	Vertical
7	7206.000	25.65	2.86	28.51	54.00	-25.49	Average	Vertical
8	7206.000	38.45	2.86	41.31	74.00	-32.69	Peak	Vertical
LE Code (S=8)_ Middle Channel:								
1	4880.000	27.50	-0.77	26.73	54.00	-27.27	Average	Horizontal
2	4880.000	40.03	-0.77	39.26	74.00	-34.74	Peak	Horizontal
3	7320.000	26.10	2.95	29.05	54.00	-24.95	Average	Horizontal
4	7320.000	38.31	2.95	41.26	74.00	-32.74	Peak	Horizontal
5	4880.000	27.50	-0.77	26.73	54.00	-27.27	Average	Vertical
6	4880.000	40.09	-0.77	39.32	74.00	-34.68	Peak	Vertical
7	7320.000	25.66	2.95	28.61	54.00	-25.39	Average	Vertical
8	7320.000	38.65	2.95	41.60	74.00	-32.40	Peak	Vertical
LE Code (S=8)_ Highest Channel:								
1	4960.000	27.70	-0.67	27.03	54.00	-26.97	Average	Horizontal
2	4960.000	39.38	-0.67	38.71	74.00	-35.29	Peak	Horizontal
3	7440.000	25.33	3.05	28.38	54.00	-25.62	Average	Horizontal
4	7440.000	37.62	3.05	40.67	74.00	-33.33	Peak	Horizontal
5	4960.000	27.52	-0.67	26.85	54.00	-27.15	Average	Vertical
6	4960.000	39.62	-0.67	38.95	74.00	-35.05	Peak	Vertical
7	7440.000	24.76	3.05	27.81	54.00	-26.19	Average	Vertical
8	7440.000	36.55	3.05	39.60	74.00	-34.40	Peak	Vertical

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2

5.8 BAND EDGE MEASUREMENTS (RADIATED)

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209

Test Method: ANSI C63.10-2013 Clause 11.13

Limits:

Radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).

Frequency	Limit (dBμV/m @3m)	Remark
30 MHz-88 MHz	40.0	Quasi-peak Value
88 MHz-216 MHz	43.5	Quasi-peak Value
216 MHz-960 MHz	46.0	Quasi-peak Value
960 MHz-1 GHz	54.0	Quasi-peak Value
Above 1 GHz	54.0	Average Value
	74.0	Peak Value

Test Setup: Refer to section 4.4.1 for details.

Test Procedures:

Radiated band edge measurements at 2390 MHz and 2483.5 MHz were made with the unit transmitting in the low end of the channel range and the high end closest to the restricted bands respectively. The emissions were made on the 966 Semi-Chamber. Use (resolution bandwidth (RBW) = 1 MHz, video bandwidth (VBW) = 3 MHz for peak levels and RBW = 1 MHz and VBW = 10 Hz or 1/T for average levels).



1. Use radiated spurious emission test procedure described in clause 5.10. The transmitter output (antenna port) was connected to the test receiver.
2. Set the PK and AV limit line.
3. Record the fundamental emission and emissions out of the band-edge.
4. Determine band-edge compliance as required.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

LE Mode:



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2

2LE Mode:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2

LE Code (S=2) Mode:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2

LE Code (S=8) Mode:

Shenzhen UnionTrust Quality and Technology Co., Ltd.



Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2



5.9 CONDUCTED EMISSION

Test Requirement: 47 CFR Part 15C Section 15.207

Test Method: ANSI C63.10-2013 Section 6.2

Limits:

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.4.2 for details.

Test Procedures:

Test frequency range :150KHz-30MHz

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The worst measurement data as follows:

Quasi Peak and Average:


Mode: BT Link

Live Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.1500	42.24	10.20	52.44	66.00	-13.56	QP
2	0.1500	26.33	10.20	36.53	56.00	-19.47	AVG
3	0.1768	18.02	10.18	28.20	54.63	-26.43	AVG
4	0.1777	34.04	10.18	44.22	64.59	-20.37	QP
5	0.4260	30.10	10.14	40.24	57.33	-17.09	QP
6	0.4260	21.15	10.14	31.29	47.33	-16.04	AVG
7	10.7900	30.17	10.49	40.66	60.00	-19.34	QP
8	10.7900	19.33	10.49	29.82	50.00	-20.18	AVG
9	23.0181	31.45	10.81	42.26	60.00	-17.74	QP
10	23.0181	24.80	10.81	35.61	50.00	-14.39	AVG
11	26.5581	30.50	10.85	41.35	60.00	-18.65	QP
12	26.5581	25.25	10.85	36.10	50.00	-13.90	AVG

Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.1500	42.50	10.19	52.69	66.00	-13.31	QP
2	0.1500	28.42	10.19	38.61	56.00	-17.39	AVG
3	0.1770	35.14	10.12	45.26	64.63	-19.37	QP
4	0.1770	21.33	10.12	31.45	54.63	-23.18	AVG
5	0.4244	31.09	10.21	41.30	57.36	-16.06	QP
6	0.4244	22.88	10.21	33.09	47.36	-14.27	AVG
7	10.6710	30.26	10.44	40.70	60.00	-19.30	QP
8	10.6710	20.82	10.44	31.26	50.00	-18.74	AVG
9	23.1314	31.73	10.77	42.50	60.00	-17.50	QP
10	23.1314	24.69	10.77	35.46	50.00	-14.54	AVG
11	26.6100	31.14	10.82	41.96	60.00	-18.04	QP
12	26.6100	25.46	10.82	36.28	50.00	-13.72	AVG

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2


APPENDIX A RF TEST DATA

A.1 99% BANDWIDTH


Mode	Channel	99% BW (MHz)
LE	0	1.0306
LE	19	1.0311
LE	39	1.0348
2LE	0	2.0548
2LE	19	2.0564
2LE	39	2.0601
LE Coded (S=2)	0	1.0214
LE Coded (S=2)	19	1.0238
LE Coded (S=2)	39	1.0207
LE Coded (S=8)	0	1.0588
LE Coded (S=8)	19	1.0730
LE Coded (S=8)	39	1.0724

Test Graphs







LE_Channel 39




2LE_Channel 39




LE Coded (S=2)_Channel 0




LE Coded (S=8)_Channel 0



LE Coded (S=2)_Channel 19



LE Coded (S=8)_Channel 19




Shenzhen UnionTrust Quality and Technology Co., Ltd.


A.2 6DB BANDWIDTH

Mode	Channel	Center Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	Result
LE	0	2402	0.6685	0.5	PASS
	19	2440	0.6575		PASS
	39	2480	0.6628		PASS
2LE	0	2402	1.245		PASS
	19	2440	1.253		PASS
	39	2480	1.240		PASS
LE Coded (S=2)	0	2402	0.6664		PASS
	19	2440	0.6694		PASS
	39	2480	0.6652		PASS
LE Coded (S=8)	0	2402	0.6786		PASS
	19	2440	0.6783		PASS
	39	2480	0.6768		PASS


Test Graphs




LE Channel 0




2LE Channel 0




LE Channel 19



2LE Channel 19





Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com




<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2


A.3 CONDUCTED OUT OF BAND EMISSION

Mode	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
LE	0	2400.00	-49.342	-12.02	-37.322	PASS
		4803.13	-44.442	-12.02	-32.422	PASS
	19	4879.30	-46.623	-11.42	-35.203	PASS
	39	2483.50	-51.378	-11.03	-40.348	PASS
		4959.20	-50.923	-11.03	-39.893	PASS
2LE	0	2400.00	-26.347	-13.13	-13.217	PASS
		4803.13	-45.605	-13.13	-32.475	PASS
	19	4879.30	-47.886	-12.62	-35.267	PASS
	39	2483.50	-49.656	-12.22	-37.436	PASS
		24326.4	-52.636	-12.22	-40.416	PASS
LE Coded (S=2)	0	2400.00	-45.770	-12.09	-33.680	PASS
		4803.13	-42.560	-12.09	-30.470	PASS
	19	4880.54	-46.506	-11.45	-35.056	PASS
	39	2483.50	-50.897	-11.11	-39.787	PASS
		4960.45	-53.061	-11.11	-41.951	PASS
LE Coded (S=8)	0	2400.00	-48.126	-15.16	-32.966	PASS
		4804.38	-45.462	-15.16	-30.302	PASS
	19	4880.54	-49.354	-14.49	-34.864	PASS
	39	2483.50	-51.673	-14.08	-37.593	PASS
		4959.20	-53.326	-14.08	-39.246	PASS

Test Graphs

In-Band Reference Level
LE Channel 0In-Band Reference Level
2LE Channel 0

Out Of Band Emission



Out Of Band Emission

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.2






In-Band Reference Level
LE Channel 39




In-Band Reference Level
2LE Channel 39




Out Of Band Emission
LE Channel 39




Out Of Band Emission
2LE Channel 39




Spurious Emission
LE Channel 39




Spurious Emission
2LE Channel 39




In-Band Reference Level
LE Coded (S=2) Channel 0




In-Band Reference Level
LE Coded (S=8) Channel 0




Out Of Band Emission
LE Coded (S=2) Channel 0




Out Of Band Emission
LE Coded (S=8) Channel 0




Spurious Emission
LE Coded (S=2) Channel 0




Spurious Emission
LE Coded (S=8) Channel 0




In-Band Reference Level
LE Coded (S=2) Channel 19




In-Band Reference Level
LE Coded (S=8) Channel 19




Spurious Emissions
LE Coded (S=2) Channel 19




Spurious Emissions
LE Coded (S=8) Channel 19




In-Band Reference Level
LE Coded (S=2) Channel 39




In-Band Reference Level
LE Coded (S=8) Channel 39




Out Of Band Emission
LE Coded (S=2) Channel 39



Out Of Band Emission
LE Coded (S=8) Channel 39



Spurious Emission
LE Coded (S=2) Channel 39





Spurious Emission
LE Coded (S=8) Channel 39

A.4 POWER SPECTRAL DENSITY


Mode	Channel	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
LE	0	-8.111	8	PASS
LE	19	-7.893	8	PASS
LE	39	-6.822	8	PASS
2LE	0	-11.949	8	PASS
2LE	19	-11.251	8	PASS
2LE	39	-10.599	8	PASS
LE Coded (S=2)	0	1.024	8	PASS
LE Coded (S=2)	19	2.112	8	PASS
LE Coded (S=2)	39	-5.755	8	PASS
LE Coded (S=8)	0	1.772	8	PASS
LE Coded (S=8)	19	2.349	8	PASS
LE Coded (S=8)	39	2.737	8	PASS

Test Graphs







LE_Channel 39




2LE_Channel 39




LE Coded (S=2)_Channel 0




LE Coded (S=8)_Channel 0



LE Coded (S=2)_Channel 19



LE Coded (S=8)_Channel 19



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>
UTTR-RF-FCCPART15.247-V1.2

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
