

TEST REPORT

Applicant Name: Grandstream Networks, Inc.
Address: 126 Brookline Ave., 3rd Floor Boston, MA 02215, USA
Report Number: 2601P12244E-RF-00
FCC ID: YZZGWN7670E

Test Standard (s)

FCC PART 15.407

Sample Description

Product Type: Dual-Band Wi-Fi 7 Access Point
Model No.: GWN7670E
Multiple Model(s) No.: N/A
Trade Mark: GRANDSTREAM
Date Received: 2026-01-16
Issue Date: 2026-04-16

Test Result:

Pass[▲]

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Ekko Wu

Ekko Wu
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked * is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, Futian Free Trade Zone, Shenzhen, China
Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY.....	4
GENERAL INFORMATION	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE	7
SUMMARY OF TEST RESULTS.....	8
TEST EQUIPMENT LIST	9
APPLICABLE STANDARDS	10
DFS REQUIREMENT	10
DFS MEASUREMENT SYSTEM.....	14
SYSTEM BLOCK DIAGRAM.....	14
CONDUCTED METHOD	15
RADIATED METHOD.....	16
TEST PROCEDURE	16
TEST RESULTS	17
DESCRIPTION OF EUT	17
RADAR WAVEFORM CALIBRATION	17
TEST DATA	17
CHANNEL AVAILABILITY CHECK TIME (CAC).....	18
TEST PROCEDURE	18
TEST DATA	18
CHANNEL MOVE TIME AND CHANNEL CLOSING TRANSMISSION TIME.....	19
TEST PROCEDURE	19
TEST DATA	19
NON-OCCUPANCY PERIOD	20
TEST PROCEDURE	20
TEST DATA	20
DETECTION BANDWIDTH	21
TEST PROCEDURE	21
TEST DATA	21
STATISTICAL PERFORMANCE CHECK	22
TEST PROCEDURE	22
TEST DATA	22
CHANNEL LOADING	23

BRIDGE AND/OR MESH MODE.....	24
TEST PROCEDURE	24
TEST DATA	24
EUT PHOTOGRAPHS.....	25
TEST SETUP PHOTOGRAPHS.....	26
APPENDIX	27

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2601P12244E-RF-00	Original Report	2026-04-16

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	5GHz Wi-Fi: 5250-5350 MHz; 5470-5725MHz
Mode	802.11a/n20/n40/ac20/ac40/ac80/ac160/ax20/ax40/ax80/ax160/ be20/be40/be80/be160
Modulation Technique	OFDM, OFDMA
Antenna Specification#	Ant0 5.73, Ant1 5.85, Ant2 5.48dBi, Beamforming gain: 0dB (It is provided by the applicant)
Voltage Range	DC 48V from POE
Sample serial number	3GAV-5 (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts E of the Federal Communications Commission's rules.

The objective is to determine compliance with FCC Part 15, Subpart E, section 15.407 Dynamic Frequency Selection (DFS) for devices operating in the bands 5250-5350 MHz, 5470-5725 MHz.

Test Methodology

FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter	Uncertainty
Time	$\pm 1\%$ ($k=2$, 95% level of confidence)
Temperature	$\pm 0.4^{\circ}\text{C}$
Humidity	$\pm 2\%$
Supply voltages	DC $\pm 0.4\%$; AC $\pm 1\%$

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, test firm registration No.: 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

EUT Exercise Software

“Lan Test[#]” exercise software was used.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Lenovo	PC	TIANYI510Pro-18ICB	R3NO28B21001
Lenovo	LED display	L2364A	U310FZR9
Lenovo	Keyboard	EKB-536A	811A19A5
DELL	Mouse	Ms116P	Ms116P
DELL	Notebook	Latitude E6410	11429208685
TP-Link	WiFi dongle	EZC-5201BS	Unknown
GOSPEL	POE	G0720-480-050	200200019

External I/O Cable

Cable Description	Length (m)	From Port	To
Unshielded Un-detachable AC cable	1.2	Receptacle	AC Mains
Unshielded Un-detachable AC cable	1.5	Receptacle	POE
Unshielded detachable RJ45 cable	1.0	POE	EUT
Unshielded detachable RJ45 cable	1.5	POE	Notebook
Unshielded Un-detachable USB Cable	1	WiFi dongle	PC

SUMMARY OF TEST RESULTS

The following result table represents the list of measurements required under the CFR §47 Part 15.407(h), and KDB: 905462 D02 UNII DFS Compliance Procedures New Rules v02

Items	Description of Test	Result
Detection Bandwidth	UNII Detection Bandwidth	Compliant
Performance Requirements Check	Initial Channel Availability Check Time (CAC)	Compliant
	Radar Burst at the Beginning of the CAC	Compliant
	Radar Burst at the End of the CAC	Compliant
In-Service Monitoring	Channel Move Time	Compliant
	Channel Closing Transmission Time	Compliant
	Non-Occupancy Period	Compliant
Radar Detection	Statistical Performance Check	Compliant
Channel Loading	Channel Loading	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Tonscend	RF control Unit	JS0806-2	19D8060154	2025/07/18	2026/07/17
Tonscend	Test software	JS1120-3	V3.3.38	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40	101473	2025/09/01	2026/08/31
Keysight	MXG Vector Signal Generator	N5182B	MY53051503	2025/09/18	2026/09/17
Unknown	RF Cable	Cable RF1	Cable RF1	2025/09/17	2026/09/16
Unknown	10dB Attenuator	Unknown	F-03-EM190	2025/06/26	2026/06/25
narda	Power divider	4324-4	F-03-EM247	2025/06/26	2026/06/25

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

APPLICABLE STANDARDS

DFS Requirement

CFR §47 Part 15.407(h)

FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
<i>Non-Occupancy Period</i>	Yes	Not required	Yes
<i>DFS Detection Threshold</i>	Yes	Not required	Yes
<i>Channel Availability Check Time</i>	Yes	Not required	Not required
<i>U-NII Detection Bandwidth</i>	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>DFS Detection Threshold</i>	Yes	Not required
<i>Channel Closing Transmission Time</i>	Yes	Yes
<i>Channel Move Time</i>	Yes	Yes
<i>U-NII Detection Bandwidth</i>	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>U-NII Detection Bandwidth and Statistical Performance Check</i>	All BW modes must be tested	Not required
<i>Channel Move Time and Channel Closing Transmission Time</i>	Test using widest BW mode available	Test using the widest BW mode available for the link
<i>All other tests</i>	Any single BW mode	Not required
Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		

Table 3: DFS Detection Thresholds for Master Devices and Client Devices With Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.	

Table 4: DFS Response Requirement Values

Parameter	Value
<i>Non-occupancy period</i>	Minimum 30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds See Note 1.
<i>Channel Closing Transmission Time</i>	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U- NII 99% transmission power bandwidth. See Note 3.
Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel move</i> (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	

Table 5 – Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a	Roundup $\left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{SEC}}} \right) \right\}$	60%	30
		Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.					

A minimum of 30 unique waveforms are required for each of the Short Pulse Radar Types 2 through 4. If more than 30 waveforms are used for Short Pulse Radar Types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms. If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B.

For example if in Short Pulse Radar Type 1 Test B a PRI of 3066 usec is selected, the number of pulses

would be $\text{Roundup} \left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{3066} \right) \right\} = \text{Roundup} \{17.2\} = 18.$

Table 5a - Pulse Repetition Intervals Values for Test A

Pulse Repetition Frequency Number	Pulse Repetition Frequency (Pulses Per Second)	Pulse Repetition Interval (Microseconds)
1	1930.5	518
2	1858.7	538
3	1792.1	558
4	1730.1	578
5	1672.2	598
6	1618.1	618
7	1567.4	638
8	1519.8	658
9	1474.9	678
10	1432.7	698
11	1392.8	718
12	1355	738
13	1319.3	758
14	1285.3	778
15	1253.1	798
16	1222.5	818
17	1193.3	838
18	1165.6	858
19	1139	878
20	1113.6	898
21	1089.3	918
22	1066.1	938
23	326.2	3066

The aggregate is the average of the percentage of successful detections of Short Pulse Radar Types 1-4. For example, the following table indicates how to compute the aggregate of percentage of successful detections.

Radar Type	Number of Trials	Number of Successful Detections	Minimum Percentage of Successful Detection
1	35	29	82.9%
2	30	18	60%
3	30	27	90%
4	50	44	88%
Aggregate $(82.9\% + 60\% + 90\% + 88\%)/4 = 80.2\%$			

Table 6 – Long Pulse Radar Test Waveform

Radar Type	Pulse Width (μ sec)	Chirp Width (MHz)	PRI (μ sec)	Number of Pulses per <i>Burst</i>	Number of <i>Bursts</i>	Minimum Percentage of Successful Detection	Minimum Number of Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30


Table 7 – Frequency Hopping Radar Test Waveform

Radar Type	Pulse Width (μ sec)	PRI (μ sec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Number of Trials
6	1	333	9	0.333	300	70%	30


DFS Measurement System

DFS measurement system consists of two subsystems: (1) The radar signal generating subsystem and (2) the traffic monitoring subsystem.


System Block Diagram




Conducted Method



Setup for Master with injection at the Master




Setup for Client with injection at the Master



Setup for Client with injection at the Client

Radiated Method



Test Procedure


A spectrum analyzer is used as a monitor verifies that the EUT status including Channel Closing Transmission Time and Channel Move Time, and does not transmit on a Channel during the Non-Occupancy Period after the diction and Channel move. It is also used to monitor EUT transmissions during the Channel Availability Check Time.

TEST RESULTS

Description of EUT

The maximum EIRP is great than 200mW. The calibrated radiated DFS detection threshold level is set to -64 dBm.

Radar Waveform Calibration



Test Data

Environmental Conditions

Temperature:	25.2~25.4 °C
Relative Humidity:	52~56 %
ATM Pressure:	101.5 kPa

The testing was performed by Bonnie Zhang from 2026-04-01 to 2026-04-03.

EUT operation mode: Transmitting

Test Result: Compliant

Please refer to the Appendix.

CHANNEL AVAILABILITY CHECK TIME (CAC)

Test Procedure

1. Initial Channel Availability Check Time

The U-NII devices will be powered on and be instructed to operate on the appropriate U-NII Channel that must incorporate DFS functions. At the same time the UUT is powered on, the spectrum analyzer will be set to zero span and the spectrum analyzer's sweep will be started at the same time power is applied to the U-NII device.

The UUT should not transmit any beacon or data transmissions until at least 1 minute after the completion of the power-on cycle.

Confirm that the UUT initiates transmission on the channel

2. Radar Burst at the Beginning of the Channel Availability Check Time

A single Burst of one of the Short Pulse Radar Types 0-4 will commence within a 6 second window at the beginning of CAC time. Visual indication or measured results on the UUT of successful detection of the radar Burst will be recorded and reported.

3. Radar Burst at the End of the Channel Availability Check Time

A single Burst of one of the Short Pulse Radar Types 0-4 will commence within a 6 second window at the end of CAC time. Visual indication or measured results on the UUT of successful detection of the radar Burst will be recorded and reported.

Test Data

Environmental Conditions

Temperature:	25.2~25.4 °C
Relative Humidity:	52~56 %
ATM Pressure:	101.5 kPa

The testing was performed by Bonnie Zhang from 2026-04-01 to 2026-04-03.

EUT operation mode: Transmitting

Test Result: Compliant

Please refer to the Appendix.

CHANNEL MOVE TIME AND CHANNEL CLOSING TRANSMISSION TIME

Test Procedure

Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time = $N \times \text{Dwell Time}$

N is the number of spectrum analyzer bins showing a device transmission Dwell Time is the dwell time per bin (i.e. $\text{Dwell Time} = S/B$, S is the sweep time and B is the number of bin, i.e. 8192)

Test Data

Environmental Conditions

Temperature:	25.2~25.4 °C
Relative Humidity:	52~56 %
ATM Pressure:	101.5 kPa

The testing was performed by Bonnie Zhang from 2026-04-01 to 2026-04-03.

EUT operation mode: Transmitting

Test Result: Compliant

Please refer to the Appendix.

NON-OCCUPANCY PERIOD

Test Procedure

Measure the EUT for more than 30 minutes following the channel close/move time to verify that the EUT does not resume any transmissions on this channel. Provide one plot to demonstrate no transmission on the channel for the non-occupancy period (30 minutes observation time)

Test Data

Environmental Conditions

Temperature:	25.2~25.4 °C
Relative Humidity:	52~56 %
ATM Pressure:	101.5 kPa

The testing was performed by Bonnie Zhang from 2026-04-01 to 2026-04-03.

EUT operation mode: Transmitting

Test Result: Compliant

Please refer to the Appendix.

DETECTION BANDWIDTH

Test Procedure

Performed with Type 0 radar waveforms

Starting at the center frequency of the UUT operating Channel, increase the radar frequency in 5 MHz steps, repeating the above test sequence, until the detection rate falls below the *U-NII Detection Bandwidth* criterion specified in Table 4. Repeat this measurement in 1MHz steps at frequencies 5 MHz below where the detection rate begins to fall. Record the highest frequency (denote as F_H) at which detection is greater than or equal to the *U-NII Detection Bandwidth* criterion. Recording the detection rate at frequencies above F_H is not required to demonstrate compliance.

Starting at the center frequency of the UUT operating Channel, decrease the radar frequency in 5 MHz steps, repeating the above test sequence, until the detection rate falls below the *U-NII Detection Bandwidth* criterion specified in Table 4. Repeat this measurement in 1MHz steps at frequencies 5 MHz above where the detection rate begins to fall. Record the lowest frequency (denote as F_L) at which detection is greater than or equal to the *U-NII Detection Bandwidth* criterion. Recording the detection rate at frequencies below F_L is not required to demonstrate compliance

The *U-NII Detection Bandwidth* is calculated as follows: $U-NII\ Detection\ Bandwidth = F_H - F_L$

The *U-NII Detection Bandwidth* must meet the *U-NII Detection Bandwidth* criterion specified in Table 4. Otherwise, the UUT does not comply with DFS requirements. This is essential to ensure that the UUT is capable of detecting *Radar Waveforms* across the same frequency spectrum that contains the significant energy from the system. In the case that the *U-NII Detection Bandwidth* is greater than or equal to the 99 percent power bandwidth for the measured F_H and F_L , the test can be truncated and the *U-NII Detection Bandwidth* can be reported as the measured F_H and F_L .

Test Data

Environmental Conditions

Temperature:	25.2~25.4 °C
Relative Humidity:	52~56 %
ATM Pressure:	101.5 kPa

The testing was performed by Bonnie Zhang from 2026-04-01 to 2026-04-03.

EUT operation mode: Transmitting

Test Result: Compliant

Please refer to the Appendix.

STATISTICAL PERFORMANCE CHECK

Test Procedure

The steps below define the procedure to determine the minimum percentage of successful detection requirements found in **Tables 5-7** when a radar burst with a level equal to the *DFS Detection Threshold + 1dB* is generated on the *Operating Channel* of the U-NII device (*In-Service Monitoring*).

- a) One frequency will be chosen from the *Operating Channels* of the UUT within the 5250-5350 MHz or 5470-5725 MHz bands.
- b) In case the UUT is a U-NII device operating as a *Client Device* (with or without Radar Detection), a U-NII device operating as a *Master Device* will be used to allow the UUT (Client device) to *Associate* with the *Master Device*. In case the UUT is a *Master Device*, a U-NII device operating as a *Client Device* will be used and it is assumed that the Client will *Associate* with the UUT (Master). In both cases for conducted tests, the *Radar Waveform* generator will be connected to the *Master Device*. For radiated tests, the emissions of the *Radar Waveform* generator will be directed towards the *Master Device*. If the *Master Device* has antenna gain, the main beam of the antenna will be directed toward the radar emitter. Vertical polarization is used for testing.
- c) Stream the channel loading test file from the *Master Device* to the Client Device on the test *Channel* for the entire period of the test.
- d) At time T_0 the *Radar Waveform* generator sends the individual waveform for each of the Radar Types 1-6 in **Tables 5-7**, at levels defined in **Table 3**, on the *Operating Channel*. An additional 1 dB is added to the radar test signal to ensure it is at or above the *DFS Detection Threshold*, accounting for equipment variations/errors.
- e) Observe the transmissions of the UUT at the end of the Burst on the *Operating Channel* for duration greater than 10 seconds for Radar Type 0 to ensure detection occurs.
- f) Observe the transmissions of the UUT at the end of the Burst on the *Operating Channel* for duration greater than 22 seconds for Long Pulse Radar Type 5 to ensure detection occurs.
- g) In case the UUT is a U-NII device operating as a *Client Device* with *In-Service Monitoring*, perform steps a) to f).

Test Data

Environmental Conditions

Temperature:	25.2~25.4 °C
Relative Humidity:	52~56 %
ATM Pressure:	101.5 kPa

The testing was performed by Bonnie Zhang from 2026-04-01 to 2026-04-03.

EUT operation mode: Transmitting

Test Result: Compliant

Please refer to the Appendix.

CHANNEL LOADING

Test Procedure

System testing will be performed with channel-loading using means appropriate to the data types that are used by the unlicensed device. The following requirements apply:

- a) The data file must be of a type that is typical for the device (i.e., MPEG-2, MPEG-4, WAV, MP3, MP4, AVI, etc.) and must generally be transmitting in a streaming mode.
- b) Software to ping the client is permitted to simulate data transfer but must have random ping intervals.
- c) Timing plots are required with calculations demonstrating a minimum channel loading of approximately 17% or greater. For example, channel loading can be estimated by setting the spectrum analyzer for zero span and approximate the Time On/ (Time On + Off Time). This can be done with any appropriate channel BW and modulation type.
- d) Unicast or Multicast protocols are preferable but other protocols may be used. The appropriate protocol used must be described in the test procedures.

Test Data

Environmental Conditions

Temperature:	25.2~25.4 °C
Relative Humidity:	52~56 %
ATM Pressure:	101.5 kPa

The testing was performed by Bonnie Zhang from 2026-04-01 to 2026-04-03.

EUT operation mode: Transmitting

Test Result: Compliant

Please refer to the Appendix.

BRIDGE AND/OR MESH MODE

Test Procedure

Networks Access Points with Bridge and/or MESH modes of operation are permitted to operate in the DFS bands but must employ a DFS function. The functionality of the Bridge mode as specified in §15.403(a) must be validated in the DFS test report. Devices operating as relays where they act as master and client must also employ DFS function for the master. The method used to validate the functionality must be documented and validation data must be documented. Bridge mode can be validated by performing a test statistical performance check (Section 7.8.4) on any one of the radar types. This is an abbreviated test to verify DFS functionality. MESH mode operational methodology must be submitted in the application for certification for evaluation by the FCC.

Test Data

Environmental Conditions

Temperature:	25.2~25.4 °C
Relative Humidity:	52~56 %
ATM Pressure:	101.5 kPa

The testing was performed by Bonnie Zhang from 2026-04-01 to 2026-04-03.

EUT operation mode: Transmitting

Test Result: Compliant

Please refer to the Appendix.

EUT PHOTOGRAPHS

Please refer to the attachment 2601P12244E-RF-EXP External photo and 2601P12244E-RF-INP Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2601P12244E-RFB-TSP Test Setup photo.

APPENDIX


Appendix A: DFS Detection Thresholds


Test Result


Test Mode	Freq.(MHz)	Radar Type	Result[dBm]	Limit[dBm]	Verdict
11AX20MIMO	5260	Type0	-64.04	-64.00	PASS
		Type1	-64.19	-64.00	PASS
		Type2	-64.21	-64.00	PASS
		Type3	-64.39	-64.00	PASS
		Type4	-64.09	-64.00	PASS
		Type5	-64.12	-64.00	PASS
	5500	Type6	-64.17	-64.00	PASS
		Type0	-64.09	-64.00	PASS
		Type1	-64.07	-64.00	PASS
		Type2	-64.10	-64.00	PASS
		Type3	-64.04	-64.00	PASS
		Type4	-64.20	-64.00	PASS
11AX40MIMO	5270	Type5	-64.26	-64.00	PASS
		Type6	-64.37	-64.00	PASS
		Type0	-64.38	-64.00	PASS
		Type1	-64.48	-64.00	PASS
		Type2	-64.24	-64.00	PASS
		Type3	-64.05	-64.00	PASS
	5510	Type4	-64.26	-64.00	PASS
		Type5	-64.31	-64.00	PASS
		Type6	-64.09	-64.00	PASS
		Type0	-64.26	-64.00	PASS
		Type1	-64.26	-64.00	PASS
		Type2	-64.23	-64.00	PASS
11AX80MIMO	5290	Type3	-64.21	-64.00	PASS
		Type4	-64.21	-64.00	PASS
		Type5	-64.22	-64.00	PASS
		Type6	-64.01	-64.00	PASS
		Type0	-64.00	-64.00	PASS
		Type1	-64.13	-64.00	PASS
	5530	Type2	-64.08	-64.00	PASS
		Type3	-64.07	-64.00	PASS
		Type4	-64.31	-64.00	PASS
		Type5	-64.26	-64.00	PASS
		Type6	-64.25	-64.00	PASS
		Type0	-64.08	-64.00	PASS
11AX160MIMO	5250	Type1	-64.08	-64.00	PASS
		Type2	-64.22	-64.00	PASS
		Type3	-64.48	-64.00	PASS
		Type4	-64.28	-64.00	PASS
		Type5	-64.16	-64.00	PASS
		Type6	-64.29	-64.00	PASS
	5570	Type0	-64.01	-64.00	PASS
		Type1	-64.12	-64.00	PASS
		Type2	-64.33	-64.00	PASS
		Type3	-64.14	-64.00	PASS
		Type0	-64.23	-64.00	PASS
		Type1	-64.12	-64.00	PASS
		Type2	-64.13	-64.00	PASS


		Type4	-64.21	-64.00	PASS
		Type5	-64.24	-64.00	PASS
		Type6	-64.15	-64.00	PASS


Test Graphs






































































11AX160MIMO 5250 Type5


DFS Detection Threshold


Project No.: 2601P12244E-RF Tester: Bonnie Zhang


Marker: -64.12 dBm












Bridge Mode**Test Result**


Test Mode	Freq.(MHz)	Radar Type	Result[dBm]	Limit[dBm]	Verdict
11AX20MIMO	5260	Type1	-64.07	-64.00	PASS


Test Graphs

Appendix B: Channel Loading**Test Result**

Test Mode	Freq.(MHz)	Result	Limit [%]	Verdict
11AX20MIMO	5260	17.28	17	PASS
	5500	45.02	17	PASS
11AX160MIMO	5250	21.89	17	PASS
	5570	21.71	17	PASS

Test Graphs





Appendix C: Channel Availability Check Time**Test Result****Initial Channel Availability Check Time**

Test Mode	Freq.(MHz)	Result	Verdict
11AX20MIMO	5260	See test Graph	PASS
	5500	See test Graph	PASS
11AX160MIMO	5250	See test Graph	PASS
	5570	See test Graph	PASS


Beginning of Channel Availability Check Time


Test Mode	Freq.(MHz)	Result	Verdict
11AX20MIMO	5260	See test Graph	PASS
	5500	See test Graph	PASS
11AX160MIMO	5250	See test Graph	PASS
	5570	See test Graph	PASS

End of Channel Availability Check Time

Test Mode	Freq.(MHz)	Result	Verdict
11AX20MIMO	5260	See test Graph	PASS
	5500	See test Graph	PASS
11AX160MIMO	5250	See test Graph	PASS
	5570	See test Graph	PASS


Test Graphs







Beginning of Channel Availability Check Time

11AX20MIMO 5260




11AX20MIMO 5500







End of Channel Availability Check Time

11AX20MIMO 5260



11AX20MIMO 5500







Appendix D: Channel Move Time and Channel Closing Transmission Time**Test Result**

Test Mode	Freq.(MHz)	CCTT[ms]	Limit[ms]	CMT[ms]	Limit[ms]	Verdict
11AX20MIMO	5260	200+14.3	200+60	887.9	10000	PASS
	5500	200+15.6	200+60	1042.6	10000	PASS
11AX160MIMO	5250	200+9.1	200+60	677.3	10000	PASS
	5570	200+15.6	200+60	1062.1	10000	PASS

Test Graphs







Appendix E: Non-Occupancy Period**Test Result**

Test Mode	Freq.(MHz)	Result	Limit[s]	Verdict
11AX20MIMO	5260	see test graph	≥ 1800	PASS
	5500	see test graph	≥ 1800	PASS
11AX160MIMO	5250	see test graph	≥ 1800	PASS
	5570	see test graph	≥ 1800	PASS

Test Graphs





Appendix F: U-NII Detection Bandwidth**Test Result**

Test Mode	Freq.(MHz)	FL[MHz]	FH[MHz]	Detection Bandwidth [MHz]	OCB [MHz]	Ratio [%]	Limit [%]	Verdict
11AX20MIMO	5260	5249	5270	21	18.85	111.41	≥100	PASS
	5500	5489	5511	22	18.85	116.71	≥100	PASS
11AX40MIMO	5270	5249	5291	42	37.6	111.70	≥100	PASS
	5510	5489	5531	42	37.6	111.70	≥100	PASS
11AX80MIMO	5290	5248	5332	84	76.8	109.38	≥100	PASS
	5530	5488	5572	84	77	109.09	≥100	PASS
11AX160MIMO	5250	5160	5340	180	156	115.38	≥100	PASS
	5570	5489	5651	162	156	103.85	≥100	PASS

Test Mode	Freq(MHz)	Radar Freq.	Trial 1	Trial 2	Trial 3	Trial 4	Trial 5	Trial 6	Trial 7	Trial 8	Trial 9	Trial 10	Ratio (%)
11AX20MIMO	5260	5248	0	0	0	0	0	0	0	0	0	0	0
		5249	1	1	1	1	1	1	1	1	1	1	100
		5250	1	1	1	1	1	1	1	1	1	1	100
		5255	1	1	1	1	1	1	1	1	1	1	100
		5260	1	1	1	1	1	1	1	1	1	1	100
		5265	1	1	1	1	1	1	1	1	1	1	100
		5270	1	1	1	1	1	1	1	1	1	1	100
		5271	0	0	0	0	0	0	0	0	0	0	0
	5500	5488	0	0	0	0	0	0	0	0	0	0	0
		5489	1	1	1	1	1	1	1	1	1	1	100
		5490	1	1	1	1	1	1	1	1	1	1	100
		5495	1	1	1	1	1	1	1	1	1	1	100
		5500	1	1	1	1	1	1	1	1	1	1	100
		5505	1	1	1	1	1	1	1	1	1	1	100
		5510	1	1	1	1	1	1	1	1	1	1	100
		5511	1	1	1	1	1	1	1	1	1	1	100
		5512	0	0	0	0	0	0	0	0	0	0	0
11AX40MIMO	5270	5248	1	0	0	0	0	0	0	0	0	0	10
		5249	1	1	1	1	1	1	1	1	1	1	100
		5250	1	1	1	1	1	1	1	1	1	1	100
		5255	1	1	1	1	1	1	1	1	1	1	100
		5260	1	1	1	1	1	1	1	1	1	1	100
		5265	1	1	1	1	1	1	1	1	1	1	100
		5270	1	1	1	1	1	1	1	1	1	1	100
		5275	1	1	1	1	1	1	1	1	1	1	100
		5280	1	1	1	1	1	1	1	1	1	1	100
		5285	1	1	1	1	1	1	1	1	1	1	100
		5290	1	1	1	1	1	1	1	1	1	1	100
		5291	1	1	1	1	1	1	1	1	1	1	100
		5292	1	0	0	0	0	0	0	0	0	0	10
	5510	5488	0	0	0	0	0	0	0	0	0	0	0
		5489	1	1	1	1	1	1	1	1	1	1	100
		5490	1	1	1	1	1	1	1	1	1	1	100
		5495	1	1	1	1	1	1	1	1	1	1	100
		5500	1	1	1	1	1	1	1	1	1	1	100
		5505	1	1	1	1	1	1	1	1	1	1	100
		5510	1	1	1	1	1	1	1	1	1	1	100
		5515	1	1	1	1	1	1	1	1	1	1	100
		5520	1	1	1	1	1	1	1	1	1	1	100
		5525	1	1	1	1	1	1	1	1	1	1	100
		5530	1	1	1	1	1	1	1	1	1	1	100
		5531	1	1	1	1	1	1	1	1	1	1	100
		5532	0	0	0	0	0	0	0	0	0	0	0

Test Mode	Freq(MHz)	Radar Freq.	Trial 1	Trial 2	Trial 3	Trial 4	Trial 5	Trial 6	Trial 7	Trial 8	Trial 9	Trial 10	Ratio (%)
11AX80MIMO	5290	5247	0	0	0	0	0	0	0	0	0	0	0
		5248	1	1	1	1	1	1	1	1	1	1	100
		5249	1	1	1	1	1	1	1	1	1	1	100
		5250	1	1	1	1	1	1	1	1	1	1	100
		5255	1	1	1	1	1	1	1	1	1	1	100
		5260	1	1	1	1	1	1	1	1	1	1	100
		5265	1	1	1	1	1	1	1	1	1	1	100
		5270	1	1	1	1	1	1	1	1	1	1	100
		5275	1	1	1	1	1	1	1	1	1	1	100
		5280	1	1	1	1	1	1	1	1	1	1	100
		5285	1	1	1	1	1	1	1	1	1	1	100
		5290	1	1	1	1	1	1	1	1	1	1	100
		5295	1	1	1	1	1	1	1	1	1	1	100
		5300	1	1	1	1	1	1	1	1	1	1	100
		5305	1	1	1	1	1	1	1	1	1	1	100
		5310	1	1	1	1	1	1	1	1	1	1	100
		5315	1	1	1	1	1	1	1	1	1	1	100
		5320	1	1	1	1	1	1	1	1	1	1	100
		5325	1	1	1	1	1	1	1	1	1	1	100
		5330	1	1	1	1	1	1	1	1	1	1	100
		5331	1	1	1	1	1	1	1	1	1	1	100
		5332	1	1	1	1	1	1	1	1	1	1	100
		5333	0	0	0	0	0	0	0	0	0	0	0
	5530	5487	0	0	0	0	0	0	0	0	0	0	0
		5488	1	1	1	1	1	1	1	1	1	1	100
		5489	1	1	1	1	1	1	1	1	1	1	100
		5490	1	1	1	1	1	1	1	1	1	1	100
		5495	1	1	1	1	1	1	1	1	1	1	100
		5500	1	1	1	1	1	1	1	1	1	1	100
		5505	1	1	1	1	1	1	1	1	1	1	100
		5510	1	1	1	1	1	1	1	1	1	1	100
		5515	1	1	1	1	1	1	1	1	1	1	100
		5520	1	1	1	1	1	1	1	1	1	1	100
		5525	1	1	1	1	1	1	1	1	1	1	100
		5530	1	1	1	1	1	1	1	1	1	1	100
		5535	1	1	1	1	1	1	1	1	1	1	100
		5540	1	1	1	1	1	1	1	1	1	1	100
		5545	1	1	1	1	1	1	1	1	1	1	100
		5550	1	1	1	1	1	1	1	1	1	1	100
		5555	1	1	1	1	1	1	1	1	1	1	100
		5560	1	1	1	1	1	1	1	1	1	1	100
		5565	1	1	1	1	1	1	1	1	1	1	100
		5570	1	1	1	1	1	1	1	1	1	1	100
		5571	1	1	1	1	1	1	1	1	1	1	100
		5572	1	1	1	1	1	1	1	1	1	1	100
		5573	0	0	0	0	0	0	0	0	0	0	0

Test Mode	Freq.(MHz)	Radar Freq.	Trial 1	Trial 2	Trial 3	Trial 4	Trial 5	Trial 6	Trial 7	Trial 8	Trial 9	Trial 10	Ratio (%)
11AX160MI MO	5250	5159	1	1	0	0	1	1	1	1	1	0	70
		5160	1	1	1	1	1	1	1	1	1	1	100
		5165	1	1	1	1	1	1	1	1	1	1	100
		5170	1	1	1	1	1	1	1	1	1	1	100
		5175	1	1	1	1	1	1	1	1	1	1	100
		5180	1	1	1	1	1	1	1	1	1	1	100
		5185	1	1	1	1	1	1	1	1	1	1	100
		5190	1	1	1	1	1	1	1	1	1	1	100
		5195	1	1	1	1	1	1	1	1	1	1	100
		5200	1	1	1	1	1	1	1	1	1	1	100
		5205	1	1	1	1	1	1	1	1	1	1	100
		5210	1	1	1	1	1	1	1	1	1	1	100
		5215	1	1	1	1	1	1	1	1	1	1	100
		5220	1	1	1	1	1	1	1	1	1	1	100
		5225	1	1	1	1	1	1	1	1	1	1	100
		5230	1	1	1	1	1	1	1	1	1	1	100
		5235	1	1	1	1	1	1	1	1	1	1	100
		5240	1	1	1	1	1	1	1	1	1	1	100
		5245	1	1	1	1	1	1	1	1	1	1	100
		5250	1	1	1	1	1	1	1	1	1	1	100
		5255	1	1	1	1	1	1	1	1	1	1	100
		5260	1	1	1	1	1	1	1	1	1	1	100
		5265	1	1	1	1	1	1	1	1	1	1	100
		5270	1	1	1	1	1	1	1	1	1	1	100
		5275	1	1	1	1	1	1	1	1	1	1	100
		5280	1	1	1	1	1	1	1	1	1	1	100
		5285	1	1	1	1	1	1	1	1	1	1	100
		5290	1	1	1	1	1	1	1	1	1	1	100
		5295	1	1	1	1	1	1	1	1	1	1	100
		5300	1	1	1	1	1	1	1	1	1	1	100
		5305	1	1	1	1	1	1	1	1	1	1	100
		5310	1	1	1	1	1	1	1	1	1	1	100
		5315	1	1	1	1	1	1	1	1	1	1	100
		5320	1	1	1	1	1	1	1	1	1	1	100
		5325	1	1	1	1	1	1	1	1	1	1	100
		5330	1	1	1	1	1	1	1	1	1	1	100
		5335	1	1	1	1	1	1	1	1	1	1	100
		5340	1	1	1	1	1	1	1	1	1	1	100
		5341	0	0	0	0	0	0	0	0	0	0	0

Test Mode	Freq(MHz)	Radar Freq.	Trial 1	Trial 2	Trial 3	Trial 4	Trial 5	Trial 6	Trial 7	Trial 8	Trial 9	Trial 10	Ratio (%)
11AX160MI MO	5570	5488	0	0	0	0	0	0	0	0	0	0	0
		5489	1	1	1	1	1	1	1	1	1	1	100
		5490	1	1	1	1	1	1	1	1	1	1	100
		5495	1	1	1	1	1	1	1	1	1	1	100
		5500	1	1	1	1	1	1	1	1	1	1	100
		5505	1	1	1	1	1	1	1	1	1	1	100
		5510	1	1	1	1	1	1	1	1	1	1	100
		5515	1	1	1	1	1	1	1	1	1	1	100
		5520	1	1	1	1	1	1	1	1	1	1	100
		5525	1	1	1	1	1	1	1	1	1	1	100
		5530	1	1	1	1	1	1	1	1	1	1	100
		5535	1	1	1	1	1	1	1	1	1	1	100
		5540	1	1	1	1	1	1	1	1	1	1	100
		5545	1	1	1	1	1	1	1	1	1	1	100
		5550	1	1	1	1	1	1	1	1	1	1	100
		5555	1	1	1	1	1	1	1	1	1	1	100
		5560	1	1	1	1	1	1	1	1	1	1	100
		5565	1	1	1	1	1	1	1	1	1	1	100
		5570	1	1	1	1	1	1	1	1	1	1	100
		5575	1	1	1	1	1	1	1	1	1	1	100
		5580	1	1	1	1	1	1	1	1	1	1	100
		5585	1	1	1	1	1	1	1	1	1	1	100
		5590	1	1	1	1	1	1	1	1	1	1	100
		5595	1	1	1	1	1	1	1	1	1	1	100
		5600	1	1	1	1	1	1	1	1	1	1	100
		5605	1	1	1	1	1	1	1	1	1	1	100
		5610	1	1	1	1	1	1	1	1	1	1	100
		5615	1	1	1	1	1	1	1	1	1	1	100
		5620	1	1	1	1	1	1	1	1	1	1	100
		5625	1	1	1	1	1	1	1	1	1	1	100
		5630	1	1	1	1	1	1	1	1	1	1	100
		5635	1	1	1	1	1	1	1	1	1	1	100
		5640	1	1	1	1	1	1	1	1	1	1	100
		5645	1	1	1	1	1	1	1	1	1	1	100
		5650	1	1	1	1	1	1	1	1	1	1	100
		5651	1	1	1	1	1	1	1	1	1	1	100
		5652	0	0	0	0	0	0	0	0	0	0	0

Appendix G: Statistical Performance check**Test Result**

Test Mode	Freq.(MHz)	Radar Type	Pass Times	Fail Times	Probability (%)	Limit (%)	Verdict
11AX20MIMO	5260	Type1	23	7	76.67	60	PASS
		Type2	20	10	66.67	60	PASS
		Type3	27	3	90.00	60	PASS
		Type4	27	3	90.00	60	PASS
		Type 1-4	---	---	80.84	80	PASS
		Type5	27	3	90.00	80	PASS
		Type6	26	4	86.67	70	PASS
	5500	Type1	28	2	93.33	60	PASS
		Type2	27	3	90.00	60	PASS
		Type3	27	3	90.00	60	PASS
		Type4	26	4	86.67	60	PASS
		Type 1-4	---	---	90.00	80	PASS
		Type5	25	5	83.33	80	PASS
11AX40MIMO	5270	Type1	27	3	90.00	60	PASS
		Type2	25	5	83.33	60	PASS
		Type3	26	4	86.67	60	PASS
		Type4	26	4	86.67	60	PASS
		Type 1-4	---	---	86.67	80	PASS
		Type5	27	3	90.00	80	PASS
	5510	Type6	27	3	90.00	70	PASS
		Type1	28	2	93.33	60	PASS
		Type2	27	3	90.00	60	PASS
		Type3	27	3	90.00	60	PASS
		Type4	27	3	90.00	60	PASS
		Type 1-4	---	---	90.83	80	PASS
11AX80MIMO	5290	Type5	26	4	86.67	80	PASS
		Type6	26	4	86.67	70	PASS
		Type1	28	2	93.33	60	PASS
		Type2	26	4	86.67	60	PASS
		Type3	28	2	93.33	60	PASS
		Type4	26	4	86.67	60	PASS
	5530	Type 1-4	---	---	90.00	80	PASS
		Type1	27	3	90.00	60	PASS
		Type2	26	4	86.67	60	PASS
		Type3	28	2	93.33	60	PASS
		Type4	28	2	93.33	60	PASS
		Type 1-4	---	---	90.83	80	PASS
11AX160MIMO	5250	Type5	26	4	86.67	80	PASS
		Type6	27	3	90.00	70	PASS
		Type1	26	4	86.67	60	PASS
		Type2	23	7	76.67	60	PASS
		Type3	27	3	90.00	60	PASS
		Type4	27	3	90.00	60	PASS
	5570	Type 1-4	---	---	85.84	80	PASS
		Type5	24	6	80.00	80	PASS
		Type6	29	1	96.67	70	PASS
		Type1	28	2	93.33	60	PASS
		Type2	27	3	90.00	60	PASS
		Type3	27	3	90.00	60	PASS
	5570	Type4	25	5	83.33	60	PASS
		Type 1-4	---	---	89.17	80	PASS
		Type5	25	5	83.33	80	PASS
		Type6	28	2	93.33	70	PASS

Test Mode	Channel	Radar Type	Trial ID	Pulse width(μs)	PRI(μs)	Pulses per Burst	Detection (1: Yes; 0: No)
11AX20MIMO	5260	Type1	0	1.0	938.0	57	0
		Type1	1	1.0	698.0	76	1
		Type1	2	1.0	618.0	86	1
		Type1	3	1.0	538.0	99	0
		Type1	4	1.0	878.0	61	1
		Type1	5	1.0	3066.0	18	1
		Type1	6	1.0	638.0	83	1
		Type1	7	1.0	918.0	58	1
		Type1	8	1.0	838.0	63	1
		Type1	9	1.0	858.0	62	1
		Type1	10	1.0	798.0	67	1
		Type1	11	1.0	718.0	74	0
		Type1	12	1.0	578.0	92	0
		Type1	13	1.0	598.0	89	0
		Type1	14	1.0	558.0	95	1
		Type1	15	1.0	2536.0	21	1
		Type1	16	1.0	966.0	55	1
		Type1	17	1.0	827.0	64	1
		Type1	18	1.0	2501.0	22	1
		Type1	19	1.0	2595.0	21	1
		Type1	20	1.0	1114.0	48	1
		Type1	21	1.0	1302.0	41	1
		Type1	22	1.0	3045.0	18	1
		Type1	23	1.0	1624.0	33	0
		Type1	24	1.0	2878.0	19	1
		Type1	25	1.0	1027.0	52	0
		Type1	26	1.0	2485.0	22	1
		Type1	27	1.0	1600.0	33	1
		Type1	28	1.0	1172.0	46	1
		Type1	29	1.0	1177.0	45	1
		Type2	0	3.2	179.0	26	1
		Type2	1	1.1	207.0	23	0
		Type2	2	2.1	230.0	24	0
		Type2	3	4.8	200.0	29	0
		Type2	4	3.9	214.0	28	0
		Type2	5	2.9	222.0	26	0
		Type2	6	3.2	204.0	26	1
		Type2	7	2.5	192.0	25	1
		Type2	8	3.1	164.0	26	1
		Type2	9	1.2	156.0	23	0
		Type2	10	3.9	210.0	27	1
		Type2	11	4.6	201.0	29	1
		Type2	12	3.2	162.0	26	1
		Type2	13	2.2	197.0	25	1
		Type2	14	4.5	163.0	29	1
		Type2	15	3.0	203.0	26	1
		Type2	16	5.0	168.0	29	1
		Type2	17	2.4	217.0	25	1
		Type2	18	2.9	191.0	26	0
		Type2	19	2.3	166.0	25	0
		Type2	20	3.7	150.0	27	1
		Type2	21	2.2	176.0	25	1
		Type2	22	4.9	195.0	29	0
		Type2	23	2.9	202.0	26	1
		Type2	24	2.5	178.0	25	1

11AX20MIMO	5260	Type2	25	1.1	206.0	23	1
		Type2	26	3.8	155.0	27	0
		Type2	27	4.7	157.0	29	1
		Type2	28	2.4	224.0	25	1
		Type2	29	4.2	159.0	28	1
		Type3	0	8.2	355.0	17	1
		Type3	1	6.1	487.0	16	1
		Type3	2	7.1	344.0	16	1
		Type3	3	9.8	288.0	18	1
		Type3	4	8.9	230.0	18	1
		Type3	5	7.9	432.0	17	1
		Type3	6	8.2	207.0	17	0
		Type3	7	7.5	443.0	17	1
		Type3	8	8.1	439.0	17	1
		Type3	9	6.2	223.0	16	1
		Type3	10	8.9	208.0	18	1
		Type3	11	9.6	463.0	18	1
		Type3	12	8.2	441.0	17	1
		Type3	13	7.2	323.0	16	1
		Type3	14	9.5	297.0	18	1
		Type3	15	8.0	412.0	17	0
		Type3	16	10.0	324.0	18	0
		Type3	17	7.4	271.0	17	1
		Type3	18	7.9	349.0	17	1
		Type3	19	7.3	409.0	16	1
		Type3	20	8.7	373.0	18	1
		Type3	21	7.2	254.0	16	1
		Type3	22	9.9	274.0	18	1
		Type3	23	7.9	278.0	17	1
		Type3	24	7.5	317.0	17	1
		Type3	25	6.1	260.0	16	1
		Type3	26	8.8	211.0	18	1
		Type3	27	9.7	272.0	18	1
		Type3	28	7.4	264.0	17	1
		Type3	29	9.2	284.0	18	1
		Type4	0	16.0	355.0	14	1
		Type4	1	11.3	487.0	12	1
		Type4	2	13.5	344.0	13	1
		Type4	3	19.4	288.0	16	1
		Type4	4	17.5	230.0	15	1
		Type4	5	15.3	432.0	14	1
		Type4	6	15.9	207.0	14	1
		Type4	7	14.3	443.0	13	1
		Type4	8	15.8	439.0	14	1
		Type4	9	11.5	223.0	12	0
		Type4	10	17.4	208.0	15	1
		Type4	11	19.0	463.0	16	0
		Type4	12	16.0	441.0	14	1
		Type4	13	13.8	323.0	13	1
		Type4	14	18.9	297.0	16	1
		Type4	15	15.5	412.0	14	1
		Type4	16	19.9	324.0	16	1
		Type4	17	14.1	271.0	13	1
		Type4	18	15.2	349.0	14	1
		Type4	19	13.8	409.0	13	1
		Type4	20	17.1	373.0	15	1
		Type4	21	13.8	254.0	13	1
		Type4	22	19.8	274.0	16	1

		Type4	23	15.3	278.0	14	1
		Type4	24	14.5	317.0	13	1
		Type4	25	11.3	260.0	12	0
		Type4	26	17.3	211.0	15	1
		Type4	27	19.2	272.0	16	1
		Type4	28	14.2	264.0	13	1
		Type4	29	18.2	284.0	15	1
11AX20MIMO	5500	Type1	0	1.0	938.0	57	1
		Type1	1	1.0	698.0	76	1
		Type1	2	1.0	618.0	86	1
		Type1	3	1.0	538.0	99	1
		Type1	4	1.0	878.0	61	1
		Type1	5	1.0	3066.0	18	1
		Type1	6	1.0	638.0	83	1
		Type1	7	1.0	918.0	58	1
		Type1	8	1.0	838.0	63	1
		Type1	9	1.0	858.0	62	1
		Type1	10	1.0	798.0	67	1
		Type1	11	1.0	718.0	74	1
		Type1	12	1.0	578.0	92	0
		Type1	13	1.0	598.0	89	1
		Type1	14	1.0	558.0	95	1
		Type1	15	1.0	2536.0	21	1
		Type1	16	1.0	966.0	55	1
		Type1	17	1.0	827.0	64	1
		Type1	18	1.0	2501.0	22	1
		Type1	19	1.0	2595.0	21	1
		Type1	20	1.0	1114.0	48	1
		Type1	21	1.0	1302.0	41	1
		Type1	22	1.0	3045.0	18	1
		Type1	23	1.0	1624.0	33	1
		Type1	24	1.0	2878.0	19	0
		Type1	25	1.0	1027.0	52	1
		Type1	26	1.0	2485.0	22	1
		Type1	27	1.0	1600.0	33	1
		Type1	28	1.0	1172.0	46	1
		Type1	29	1.0	1177.0	45	1
		Type2	0	3.2	179.0	26	1
		Type2	1	1.1	207.0	23	1
		Type2	2	2.1	230.0	24	1
		Type2	3	4.8	200.0	29	1
		Type2	4	3.9	214.0	28	1
		Type2	5	2.9	222.0	26	1
		Type2	6	3.2	204.0	26	1
		Type2	7	2.5	192.0	25	1
		Type2	8	3.1	164.0	26	1
		Type2	9	1.2	156.0	23	0
		Type2	10	3.9	210.0	27	1
		Type2	11	4.6	201.0	29	1
		Type2	12	3.2	162.0	26	1
		Type2	13	2.2	197.0	25	1
		Type2	14	4.5	163.0	29	1
		Type2	15	3.0	203.0	26	1
		Type2	16	5.0	168.0	29	1
		Type2	17	2.4	217.0	25	1
		Type2	18	2.9	191.0	26	0
		Type2	19	2.3	166.0	25	1
		Type2	20	3.7	150.0	27	1

		Type2	21	2.2	176.0	25	1
		Type2	22	4.9	195.0	29	1
		Type2	23	2.9	202.0	26	1
		Type2	24	2.5	178.0	25	1
		Type2	25	1.1	206.0	23	1
		Type2	26	3.8	155.0	27	0
		Type2	27	4.7	157.0	29	1
		Type2	28	2.4	224.0	25	1
		Type2	29	4.2	159.0	28	1
11AX20MIMO	5500	Type3	0	8.2	355.0	17	1
		Type3	1	6.1	487.0	16	1
		Type3	2	7.1	344.0	16	1
		Type3	3	9.8	288.0	18	1
		Type3	4	8.9	230.0	18	1
		Type3	5	7.9	432.0	17	1
		Type3	6	8.2	207.0	17	1
		Type3	7	7.5	443.0	17	1
		Type3	8	8.1	439.0	17	1
		Type3	9	6.2	223.0	16	1
		Type3	10	8.9	208.0	18	1
		Type3	11	9.6	463.0	18	1
		Type3	12	8.2	441.0	17	1
		Type3	13	7.2	323.0	16	1
		Type3	14	9.5	297.0	18	0
		Type3	15	8.0	412.0	17	0
		Type3	16	10.0	324.0	18	1
		Type3	17	7.4	271.0	17	1
		Type3	18	7.9	349.0	17	1
		Type3	19	7.3	409.0	16	1
		Type3	20	8.7	373.0	18	1
		Type3	21	7.2	254.0	16	1
		Type3	22	9.9	274.0	18	1
		Type3	23	7.9	278.0	17	1
		Type3	24	7.5	317.0	17	1
		Type3	25	6.1	260.0	16	1
		Type3	26	8.8	211.0	18	0
		Type3	27	9.7	272.0	18	1
		Type3	28	7.4	264.0	17	1
		Type3	29	9.2	284.0	18	1
		Type4	0	16.0	355.0	14	1
		Type4	1	11.3	487.0	12	1
		Type4	2	13.5	344.0	13	1
		Type4	3	19.4	288.0	16	1
		Type4	4	17.5	230.0	15	1
		Type4	5	15.3	432.0	14	1
		Type4	6	15.9	207.0	14	1
		Type4	7	14.3	443.0	13	1
		Type4	8	15.8	439.0	14	0
		Type4	9	11.5	223.0	12	1
		Type4	10	17.4	208.0	15	1
		Type4	11	19.0	463.0	16	1
		Type4	12	16.0	441.0	14	1
		Type4	13	13.8	323.0	13	1
		Type4	14	18.9	297.0	16	0
		Type4	15	15.5	412.0	14	1
		Type4	16	19.9	324.0	16	1
		Type4	17	14.1	271.0	13	1
		Type4	18	15.2	349.0	14	1

		Type4	19	13.8	409.0	13	1
		Type4	20	17.1	373.0	15	1
		Type4	21	13.8	254.0	13	1
		Type4	22	19.8	274.0	16	1
		Type4	23	15.3	278.0	14	1
		Type4	24	14.5	317.0	13	0
		Type4	25	11.3	260.0	12	1
		Type4	26	17.3	211.0	15	0
		Type4	27	19.2	272.0	16	1
		Type4	28	14.2	264.0	13	1
11AX40MIMO	5270	Type4	29	18.2	284.0	15	1
		Type1	0	1.0	938.0	57	1
		Type1	1	1.0	698.0	76	1
		Type1	2	1.0	618.0	86	1
		Type1	3	1.0	538.0	99	0
		Type1	4	1.0	878.0	61	1
		Type1	5	1.0	3066.0	18	1
		Type1	6	1.0	638.0	83	1
		Type1	7	1.0	918.0	58	1
		Type1	8	1.0	838.0	63	1
		Type1	9	1.0	858.0	62	1
		Type1	10	1.0	798.0	67	1
		Type1	11	1.0	718.0	74	1
		Type1	12	1.0	578.0	92	1
		Type1	13	1.0	598.0	89	0
		Type1	14	1.0	558.0	95	0
		Type1	15	1.0	2536.0	21	1
		Type1	16	1.0	966.0	55	1
		Type1	17	1.0	827.0	64	1
		Type1	18	1.0	2501.0	22	1
		Type1	19	1.0	2595.0	21	1
		Type1	20	1.0	1114.0	48	1
		Type1	21	1.0	1302.0	41	1
		Type1	22	1.0	3045.0	18	1
		Type1	23	1.0	1624.0	33	1
		Type1	24	1.0	2878.0	19	1
		Type1	25	1.0	1027.0	52	1
		Type1	26	1.0	2485.0	22	1
		Type1	27	1.0	1600.0	33	1
		Type1	28	1.0	1172.0	46	1
		Type1	29	1.0	1177.0	45	1
		Type2	0	3.2	179.0	26	1
		Type2	1	1.1	207.0	23	1
		Type2	2	2.1	230.0	24	1
		Type2	3	4.8	200.0	29	0
		Type2	4	3.9	214.0	28	0
		Type2	5	2.9	222.0	26	0
		Type2	6	3.2	204.0	26	1
		Type2	7	2.5	192.0	25	1
		Type2	8	3.1	164.0	26	1
		Type2	9	1.2	156.0	23	1
		Type2	10	3.9	210.0	27	1
		Type2	11	4.6	201.0	29	1
		Type2	12	3.2	162.0	26	1
		Type2	13	2.2	197.0	25	1
		Type2	14	4.5	163.0	29	1
		Type2	15	3.0	203.0	26	1
		Type2	16	5.0	168.0	29	1

11AX40MIMO	5270	Type2	17	2.4	217.0	25	1
		Type2	18	2.9	191.0	26	1
		Type2	19	2.3	166.0	25	1
		Type2	20	3.7	150.0	27	1
		Type2	21	2.2	176.0	25	1
		Type2	22	4.9	195.0	29	1
		Type2	23	2.9	202.0	26	0
		Type2	24	2.5	178.0	25	1
		Type2	25	1.1	206.0	23	1
		Type2	26	3.8	155.0	27	1
		Type2	27	4.7	157.0	29	1
		Type2	28	2.4	224.0	25	0
		Type2	29	4.2	159.0	28	1
		Type3	0	8.2	355.0	17	1
		Type3	1	6.1	487.0	16	1
		Type3	2	7.1	344.0	16	1
		Type3	3	9.8	288.0	18	0
		Type3	4	8.9	230.0	18	0
		Type3	5	7.9	432.0	17	1
		Type3	6	8.2	207.0	17	1
		Type3	7	7.5	443.0	17	1
		Type3	8	8.1	439.0	17	1
		Type3	9	6.2	223.0	16	1
		Type3	10	8.9	208.0	18	1
		Type3	11	9.6	463.0	18	1
		Type3	12	8.2	441.0	17	1
		Type3	13	7.2	323.0	16	1
		Type3	14	9.5	297.0	18	0
		Type3	15	8.0	412.0	17	1
		Type3	16	10.0	324.0	18	1
		Type3	17	7.4	271.0	17	1
		Type3	18	7.9	349.0	17	1
		Type3	19	7.3	409.0	16	1
		Type3	20	8.7	373.0	18	1
		Type3	21	7.2	254.0	16	1
		Type3	22	9.9	274.0	18	1
		Type3	23	7.9	278.0	17	1
		Type3	24	7.5	317.0	17	1
		Type3	25	6.1	260.0	16	1
		Type3	26	8.8	211.0	18	0
		Type3	27	9.7	272.0	18	1
		Type3	28	7.4	264.0	17	1
		Type3	29	9.2	284.0	18	1
		Type4	0	16.0	355.0	14	1
		Type4	1	11.3	487.0	12	1
		Type4	2	13.5	344.0	13	1
		Type4	3	19.4	288.0	16	1
		Type4	4	17.5	230.0	15	0
		Type4	5	15.3	432.0	14	1
		Type4	6	15.9	207.0	14	1
		Type4	7	14.3	443.0	13	1
		Type4	8	15.8	439.0	14	1
		Type4	9	11.5	223.0	12	1
		Type4	10	17.4	208.0	15	1
		Type4	11	19.0	463.0	16	0
		Type4	12	16.0	441.0	14	1
		Type4	13	13.8	323.0	13	1
		Type4	14	18.9	297.0	16	1

		Type4	15	15.5	412.0	14	1
		Type4	16	19.9	324.0	16	1
		Type4	17	14.1	271.0	13	1
		Type4	18	15.2	349.0	14	0
		Type4	19	13.8	409.0	13	1
		Type4	20	17.1	373.0	15	1
		Type4	21	13.8	254.0	13	1
		Type4	22	19.8	274.0	16	1
		Type4	23	15.3	278.0	14	1
		Type4	24	14.5	317.0	13	1
		Type4	25	11.3	260.0	12	1
		Type4	26	17.3	211.0	15	1
		Type4	27	19.2	272.0	16	0
		Type4	28	14.2	264.0	13	1
		Type4	29	18.2	284.0	15	1
11AX40MIMO	5510	Type1	0	1.0	938.0	57	1
		Type1	1	1.0	698.0	76	1
		Type1	2	1.0	618.0	86	1
		Type1	3	1.0	538.0	99	1
		Type1	4	1.0	878.0	61	1
		Type1	5	1.0	3066.0	18	1
		Type1	6	1.0	638.0	83	1
		Type1	7	1.0	918.0	58	1
		Type1	8	1.0	838.0	63	1
		Type1	9	1.0	858.0	62	1
		Type1	10	1.0	798.0	67	1
		Type1	11	1.0	718.0	74	1
		Type1	12	1.0	578.0	92	1
		Type1	13	1.0	598.0	89	1
		Type1	14	1.0	558.0	95	1
		Type1	15	1.0	2536.0	21	1
		Type1	16	1.0	966.0	55	1
		Type1	17	1.0	827.0	64	1
		Type1	18	1.0	2501.0	22	0
		Type1	19	1.0	2595.0	21	1
		Type1	20	1.0	1114.0	48	1
		Type1	21	1.0	1302.0	41	1
		Type1	22	1.0	3045.0	18	1
		Type1	23	1.0	1624.0	33	1
		Type1	24	1.0	2878.0	19	1
		Type1	25	1.0	1027.0	52	1
		Type1	26	1.0	2485.0	22	1
		Type1	27	1.0	1600.0	33	1
		Type1	28	1.0	1172.0	46	0
		Type1	29	1.0	1177.0	45	1
		Type2	0	3.2	179.0	26	1
		Type2	1	1.1	207.0	23	1
		Type2	2	2.1	230.0	24	1
		Type2	3	4.8	200.0	29	1
		Type2	4	3.9	214.0	28	1
		Type2	5	2.9	222.0	26	1
		Type2	6	3.2	204.0	26	1
		Type2	7	2.5	192.0	25	1
		Type2	8	3.1	164.0	26	1
		Type2	9	1.2	156.0	23	1
		Type2	10	3.9	210.0	27	1
		Type2	11	4.6	201.0	29	1
		Type2	12	3.2	162.0	26	0

11AX40MIMO	5510	Type2	13	2.2	197.0	25	1
		Type2	14	4.5	163.0	29	1
		Type2	15	3.0	203.0	26	1
		Type2	16	5.0	168.0	29	1
		Type2	17	2.4	217.0	25	1
		Type2	18	2.9	191.0	26	1
		Type2	19	2.3	166.0	25	1
		Type2	20	3.7	150.0	27	0
		Type2	21	2.2	176.0	25	1
		Type2	22	4.9	195.0	29	1
		Type2	23	2.9	202.0	26	1
		Type2	24	2.5	178.0	25	1
		Type2	25	1.1	206.0	23	1
		Type2	26	3.8	155.0	27	0
		Type2	27	4.7	157.0	29	1
		Type2	28	2.4	224.0	25	1
		Type2	29	4.2	159.0	28	1
		Type3	0	8.2	355.0	17	1
		Type3	1	6.1	487.0	16	1
		Type3	2	7.1	344.0	16	1
		Type3	3	9.8	288.0	18	1
		Type3	4	8.9	230.0	18	1
		Type3	5	7.9	432.0	17	1
		Type3	6	8.2	207.0	17	1
		Type3	7	7.5	443.0	17	1
		Type3	8	8.1	439.0	17	1
		Type3	9	6.2	223.0	16	1
		Type3	10	8.9	208.0	18	1
		Type3	11	9.6	463.0	18	1
		Type3	12	8.2	441.0	17	0
		Type3	13	7.2	323.0	16	1
		Type3	14	9.5	297.0	18	1
		Type3	15	8.0	412.0	17	1
		Type3	16	10.0	324.0	18	1
		Type3	17	7.4	271.0	17	1
		Type3	18	7.9	349.0	17	1
		Type3	19	7.3	409.0	16	1
		Type3	20	8.7	373.0	18	0
		Type3	21	7.2	254.0	16	0
		Type3	22	9.9	274.0	18	1
		Type3	23	7.9	278.0	17	1
		Type3	24	7.5	317.0	17	1
		Type3	25	6.1	260.0	16	1
		Type3	26	8.8	211.0	18	1
		Type3	27	9.7	272.0	18	1
		Type3	28	7.4	264.0	17	1
		Type3	29	9.2	284.0	18	1
		Type4	0	16.0	355.0	14	1
		Type4	1	11.3	487.0	12	1
		Type4	2	13.5	344.0	13	1
		Type4	3	19.4	288.0	16	1
		Type4	4	17.5	230.0	15	1
		Type4	5	15.3	432.0	14	1
		Type4	6	15.9	207.0	14	1
		Type4	7	14.3	443.0	13	1
		Type4	8	15.8	439.0	14	1
		Type4	9	11.5	223.0	12	1
		Type4	10	17.4	208.0	15	1

11AX40MIMO	5510	Type4	11	19.0	463.0	16	1
		Type4	12	16.0	441.0	14	1
		Type4	13	13.8	323.0	13	1
		Type4	14	18.9	297.0	16	0
		Type4	15	15.5	412.0	14	1
		Type4	16	19.9	324.0	16	1
		Type4	17	14.1	271.0	13	1
		Type4	18	15.2	349.0	14	1
		Type4	19	13.8	409.0	13	1
		Type4	20	17.1	373.0	15	1
		Type4	21	13.8	254.0	13	1
		Type4	22	19.8	274.0	16	0
		Type4	23	15.3	278.0	14	0
		Type4	24	14.5	317.0	13	1
		Type4	25	11.3	260.0	12	1
		Type4	26	17.3	211.0	15	1
		Type4	27	19.2	272.0	16	1
		Type4	28	14.2	264.0	13	1
		Type4	29	18.2	284.0	15	1
11AX80MIMO	5290	Type1	0	1.0	938.0	57	1
		Type1	1	1.0	698.0	76	1
		Type1	2	1.0	618.0	86	1
		Type1	3	1.0	538.0	99	1
		Type1	4	1.0	878.0	61	1
		Type1	5	1.0	3066.0	18	1
		Type1	6	1.0	638.0	83	1
		Type1	7	1.0	918.0	58	1
		Type1	8	1.0	838.0	63	1
		Type1	9	1.0	858.0	62	1
		Type1	10	1.0	798.0	67	1
		Type1	11	1.0	718.0	74	0
		Type1	12	1.0	578.0	92	1
		Type1	13	1.0	598.0	89	1
		Type1	14	1.0	558.0	95	0
		Type1	15	1.0	2536.0	21	1
		Type1	16	1.0	966.0	55	1
		Type1	17	1.0	827.0	64	1
		Type1	18	1.0	2501.0	22	1
		Type1	19	1.0	2595.0	21	1
		Type1	20	1.0	1114.0	48	1
		Type1	21	1.0	1302.0	41	1
		Type1	22	1.0	3045.0	18	1
		Type1	23	1.0	1624.0	33	1
		Type1	24	1.0	2878.0	19	1
		Type1	25	1.0	1027.0	52	1
		Type1	26	1.0	2485.0	22	1
		Type1	27	1.0	1600.0	33	1
		Type1	28	1.0	1172.0	46	1
		Type1	29	1.0	1177.0	45	1
		Type2	0	3.2	179.0	26	1
		Type2	1	1.1	207.0	23	1
		Type2	2	2.1	230.0	24	1
		Type2	3	4.8	200.0	29	1
		Type2	4	3.9	214.0	28	1
		Type2	5	2.9	222.0	26	1
		Type2	6	3.2	204.0	26	1
		Type2	7	2.5	192.0	25	1
		Type2	8	3.1	164.0	26	1

11AX80MIMO	5290	Type2	9	1.2	156.0	23	1
		Type2	10	3.9	210.0	27	1
		Type2	11	4.6	201.0	29	1
		Type2	12	3.2	162.0	26	0
		Type2	13	2.2	197.0	25	1
		Type2	14	4.5	163.0	29	1
		Type2	15	3.0	203.0	26	1
		Type2	16	5.0	168.0	29	1
		Type2	17	2.4	217.0	25	1
		Type2	18	2.9	191.0	26	1
		Type2	19	2.3	166.0	25	1
		Type2	20	3.7	150.0	27	0
		Type2	21	2.2	176.0	25	1
		Type2	22	4.9	195.0	29	0
		Type2	23	2.9	202.0	26	1
		Type2	24	2.5	178.0	25	0
		Type2	25	1.1	206.0	23	1
		Type2	26	3.8	155.0	27	1
		Type2	27	4.7	157.0	29	1
		Type2	28	2.4	224.0	25	1
		Type2	29	4.2	159.0	28	1
		Type3	0	8.2	355.0	17	1
		Type3	1	6.1	487.0	16	1
		Type3	2	7.1	344.0	16	1
		Type3	3	9.8	288.0	18	1
		Type3	4	8.9	230.0	18	1
		Type3	5	7.9	432.0	17	1
		Type3	6	8.2	207.0	17	1
		Type3	7	7.5	443.0	17	1
		Type3	8	8.1	439.0	17	1
		Type3	9	6.2	223.0	16	1
		Type3	10	8.9	208.0	18	1
		Type3	11	9.6	463.0	18	1
		Type3	12	8.2	441.0	17	1
		Type3	13	7.2	323.0	16	0
		Type3	14	9.5	297.0	18	1
		Type3	15	8.0	412.0	17	1
		Type3	16	10.0	324.0	18	1
		Type3	17	7.4	271.0	17	1
		Type3	18	7.9	349.0	17	1
		Type3	19	7.3	409.0	16	1
		Type3	20	8.7	373.0	18	1
		Type3	21	7.2	254.0	16	1
		Type3	22	9.9	274.0	18	1
		Type3	23	7.9	278.0	17	1
		Type3	24	7.5	317.0	17	1
		Type3	25	6.1	260.0	16	1
		Type3	26	8.8	211.0	18	1
		Type3	27	9.7	272.0	18	1
		Type3	28	7.4	264.0	17	1
		Type3	29	9.2	284.0	18	0
		Type4	0	16.0	355.0	14	1
		Type4	1	11.3	487.0	12	1
		Type4	2	13.5	344.0	13	1
		Type4	3	19.4	288.0	16	1
		Type4	4	17.5	230.0	15	1
		Type4	5	15.3	432.0	14	1
		Type4	6	15.9	207.0	14	0

11AX80MIMO	5290	Type4	7	14.3	443.0	13	1
		Type4	8	15.8	439.0	14	1
		Type4	9	11.5	223.0	12	1
		Type4	10	17.4	208.0	15	1
		Type4	11	19.0	463.0	16	1
		Type4	12	16.0	441.0	14	1
		Type4	13	13.8	323.0	13	1
		Type4	14	18.9	297.0	16	1
		Type4	15	15.5	412.0	14	1
		Type4	16	19.9	324.0	16	1
		Type4	17	14.1	271.0	13	0
		Type4	18	15.2	349.0	14	0
		Type4	19	13.8	409.0	13	1
		Type4	20	17.1	373.0	15	1
		Type4	21	13.8	254.0	13	1
		Type4	22	19.8	274.0	16	1
		Type4	23	15.3	278.0	14	1
		Type4	24	14.5	317.0	13	0
		Type4	25	11.3	260.0	12	1
		Type4	26	17.3	211.0	15	1
		Type4	27	19.2	272.0	16	1
		Type4	28	14.2	264.0	13	1
		Type4	29	18.2	284.0	15	1
11AX80MIMO	5530	Type1	0	1.0	938.0	57	1
		Type1	1	1.0	698.0	76	1
		Type1	2	1.0	618.0	86	1
		Type1	3	1.0	538.0	99	1
		Type1	4	1.0	878.0	61	1
		Type1	5	1.0	3066.0	18	1
		Type1	6	1.0	638.0	83	1
		Type1	7	1.0	918.0	58	1
		Type1	8	1.0	838.0	63	1
		Type1	9	1.0	858.0	62	1
		Type1	10	1.0	798.0	67	0
		Type1	11	1.0	718.0	74	1
		Type1	12	1.0	578.0	92	1
		Type1	13	1.0	598.0	89	1
		Type1	14	1.0	558.0	95	1
		Type1	15	1.0	2536.0	21	1
		Type1	16	1.0	966.0	55	1
		Type1	17	1.0	827.0	64	1
		Type1	18	1.0	2501.0	22	1
		Type1	19	1.0	2595.0	21	0
		Type1	20	1.0	1114.0	48	1
		Type1	21	1.0	1302.0	41	1
		Type1	22	1.0	3045.0	18	1
		Type1	23	1.0	1624.0	33	1
		Type1	24	1.0	2878.0	19	1
		Type1	25	1.0	1027.0	52	1
		Type1	26	1.0	2485.0	22	0
		Type1	27	1.0	1600.0	33	1
		Type1	28	1.0	1172.0	46	1
		Type1	29	1.0	1177.0	45	1
		Type2	0	3.2	179.0	26	1
		Type2	1	1.1	207.0	23	1
		Type2	2	2.1	230.0	24	1
		Type2	3	4.8	200.0	29	1
		Type2	4	3.9	214.0	28	1

11AX80MIMO	5530	Type2	5	2.9	222.0	26	1
		Type2	6	3.2	204.0	26	1
		Type2	7	2.5	192.0	25	0
		Type2	8	3.1	164.0	26	0
		Type2	9	1.2	156.0	23	1
		Type2	10	3.9	210.0	27	1
		Type2	11	4.6	201.0	29	1
		Type2	12	3.2	162.0	26	0
		Type2	13	2.2	197.0	25	1
		Type2	14	4.5	163.0	29	1
		Type2	15	3.0	203.0	26	1
		Type2	16	5.0	168.0	29	1
		Type2	17	2.4	217.0	25	1
		Type2	18	2.9	191.0	26	1
		Type2	19	2.3	166.0	25	1
		Type2	20	3.7	150.0	27	1
		Type2	21	2.2	176.0	25	1
		Type2	22	4.9	195.0	29	1
		Type2	23	2.9	202.0	26	1
		Type2	24	2.5	178.0	25	1
		Type2	25	1.1	206.0	23	1
		Type2	26	3.8	155.0	27	0
		Type2	27	4.7	157.0	29	1
		Type2	28	2.4	224.0	25	1
		Type2	29	4.2	159.0	28	1
		Type3	0	8.2	355.0	17	1
		Type3	1	6.1	487.0	16	1
		Type3	2	7.1	344.0	16	1
		Type3	3	9.8	288.0	18	1
		Type3	4	8.9	230.0	18	1
		Type3	5	7.9	432.0	17	1
		Type3	6	8.2	207.0	17	0
		Type3	7	7.5	443.0	17	1
		Type3	8	8.1	439.0	17	1
		Type3	9	6.2	223.0	16	1
		Type3	10	8.9	208.0	18	1
		Type3	11	9.6	463.0	18	1
		Type3	12	8.2	441.0	17	1
		Type3	13	7.2	323.0	16	1
		Type3	14	9.5	297.0	18	1
		Type3	15	8.0	412.0	17	1
		Type3	16	10.0	324.0	18	1
		Type3	17	7.4	271.0	17	1
		Type3	18	7.9	349.0	17	1
		Type3	19	7.3	409.0	16	1
		Type3	20	8.7	373.0	18	1
		Type3	21	7.2	254.0	16	1
		Type3	22	9.9	274.0	18	0
		Type3	23	7.9	278.0	17	1

11AX80MIMO	5530	Type3	24	7.5	317.0	17	1
		Type3	25	6.1	260.0	16	1
		Type3	26	8.8	211.0	18	1
		Type3	27	9.7	272.0	18	1
		Type3	28	7.4	264.0	17	1
		Type3	29	9.2	284.0	18	1
		Type4	0	16.0	355.0	14	1
		Type4	1	11.3	487.0	12	1
		Type4	2	13.5	344.0	13	1
		Type4	3	19.4	288.0	16	1
		Type4	4	17.5	230.0	15	1
		Type4	5	15.3	432.0	14	1
		Type4	6	15.9	207.0	14	1
		Type4	7	14.3	443.0	13	0
		Type4	8	15.8	439.0	14	1
		Type4	9	11.5	223.0	12	1
		Type4	10	17.4	208.0	15	1
		Type4	11	19.0	463.0	16	1
		Type4	12	16.0	441.0	14	1
		Type4	13	13.8	323.0	13	1
		Type4	14	18.9	297.0	16	1
		Type4	15	15.5	412.0	14	1
		Type4	16	19.9	324.0	16	1
		Type4	17	14.1	271.0	13	1
		Type4	18	15.2	349.0	14	1
		Type4	19	13.8	409.0	13	1
		Type4	20	17.1	373.0	15	1
		Type4	21	13.8	254.0	13	1
		Type4	22	19.8	274.0	16	1
		Type4	23	15.3	278.0	14	0
		Type4	24	14.5	317.0	13	1
		Type4	25	11.3	260.0	12	1
		Type4	26	17.3	211.0	15	1
		Type4	27	19.2	272.0	16	1
		Type4	28	14.2	264.0	13	1
		Type4	29	18.2	284.0	15	1
11AX160MIMO	5250	Type1	0	1.0	938.0	57	1
		Type1	1	1.0	698.0	76	1
		Type1	2	1.0	618.0	86	1
		Type1	3	1.0	538.0	99	0
		Type1	4	1.0	878.0	61	1
		Type1	5	1.0	3066.0	18	1
		Type1	6	1.0	638.0	83	1
		Type1	7	1.0	918.0	58	1
		Type1	8	1.0	838.0	63	1
		Type1	9	1.0	858.0	62	1
		Type1	10	1.0	798.0	67	1

11AX160MIMO	5250	Type1	11	1.0	718.0	74	1
		Type1	12	1.0	578.0	92	0
		Type1	13	1.0	598.0	89	0
		Type1	14	1.0	558.0	95	0
		Type1	15	1.0	2536.0	21	1
		Type1	16	1.0	966.0	55	1
		Type1	17	1.0	827.0	64	1
		Type1	18	1.0	2501.0	22	1
		Type1	19	1.0	2595.0	21	1
		Type1	20	1.0	1114.0	48	1
		Type1	21	1.0	1302.0	41	1
		Type1	22	1.0	3045.0	18	1
		Type1	23	1.0	1624.0	33	1
		Type1	24	1.0	2878.0	19	1
		Type1	25	1.0	1027.0	52	1
		Type1	26	1.0	2485.0	22	1
		Type1	27	1.0	1600.0	33	1
		Type1	28	1.0	1172.0	46	1
		Type1	29	1.0	1177.0	45	1
		Type2	0	3.2	179.0	26	1
		Type2	1	1.1	207.0	23	1
		Type2	2	2.1	230.0	24	1
		Type2	3	4.8	200.0	29	1
		Type2	4	3.9	214.0	28	1
		Type2	5	2.9	222.0	26	1
		Type2	6	3.2	204.0	26	1
		Type2	7	2.5	192.0	25	1
		Type2	8	3.1	164.0	26	1
		Type2	9	1.2	156.0	23	0
		Type2	10	3.9	210.0	27	1
		Type2	11	4.6	201.0	29	1
		Type2	12	3.2	162.0	26	1
		Type2	13	2.2	197.0	25	1
		Type2	14	4.5	163.0	29	0
		Type2	15	3.0	203.0	26	0
		Type2	16	5.0	168.0	29	0
		Type2	17	2.4	217.0	25	1
		Type2	18	2.9	191.0	26	1
		Type2	19	2.3	166.0	25	1
		Type2	20	3.7	150.0	27	0
		Type2	21	2.2	176.0	25	0
		Type2	22	4.9	195.0	29	1
		Type2	23	2.9	202.0	26	1
		Type2	24	2.5	178.0	25	1
		Type2	25	1.1	206.0	23	1
		Type2	26	3.8	155.0	27	0
		Type2	27	4.7	157.0	29	1
		Type2	28	2.4	224.0	25	1
		Type2	29	4.2	159.0	28	1

11AX160MIMO	5250	Type3	0	8.2	355.0	17	1
		Type3	1	6.1	487.0	16	1
		Type3	2	7.1	344.0	16	1
		Type3	3	9.8	288.0	18	0
		Type3	4	8.9	230.0	18	1
		Type3	5	7.9	432.0	17	1
		Type3	6	8.2	207.0	17	1
		Type3	7	7.5	443.0	17	1
		Type3	8	8.1	439.0	17	1
		Type3	9	6.2	223.0	16	1
		Type3	10	8.9	208.0	18	1
		Type3	11	9.6	463.0	18	1
		Type3	12	8.2	441.0	17	1
		Type3	13	7.2	323.0	16	1
		Type3	14	9.5	297.0	18	1
		Type3	15	8.0	412.0	17	0
		Type3	16	10.0	324.0	18	0
		Type3	17	7.4	271.0	17	1
		Type3	18	7.9	349.0	17	1
		Type3	19	7.3	409.0	16	1
		Type3	20	8.7	373.0	18	1
		Type3	21	7.2	254.0	16	1
		Type3	22	9.9	274.0	18	1
		Type3	23	7.9	278.0	17	1
		Type3	24	7.5	317.0	17	1
		Type3	25	6.1	260.0	16	1
		Type3	26	8.8	211.0	18	1
		Type3	27	9.7	272.0	18	1
		Type3	28	7.4	264.0	17	1
		Type3	29	9.2	284.0	18	1
		Type4	0	16.0	355.0	14	1
		Type4	1	11.3	487.0	12	1
		Type4	2	13.5	344.0	13	1
		Type4	3	19.4	288.0	16	1
		Type4	4	17.5	230.0	15	1
		Type4	5	15.3	432.0	14	1
		Type4	6	15.9	207.0	14	1
		Type4	7	14.3	443.0	13	1
		Type4	8	15.8	439.0	14	1
		Type4	9	11.5	223.0	12	1
		Type4	10	17.4	208.0	15	1

11AX160MIMO	5250	Type4	11	19.0	463.0	16	1
		Type4	12	16.0	441.0	14	0
		Type4	13	13.8	323.0	13	1
		Type4	14	18.9	297.0	16	1
		Type4	15	15.5	412.0	14	1
		Type4	16	19.9	324.0	16	1
		Type4	17	14.1	271.0	13	1
		Type4	18	15.2	349.0	14	1
		Type4	19	13.8	409.0	13	1
		Type4	20	17.1	373.0	15	1
		Type4	21	13.8	254.0	13	1
		Type4	22	19.8	274.0	16	1
		Type4	23	15.3	278.0	14	1
		Type4	24	14.5	317.0	13	0
		Type4	25	11.3	260.0	12	0
		Type4	26	17.3	211.0	15	1
		Type4	27	19.2	272.0	16	1
		Type4	28	14.2	264.0	13	1
		Type4	29	18.2	284.0	15	1
	5570	Type1	0	1.0	938.0	57	1
		Type1	1	1.0	698.0	76	1
		Type1	2	1.0	618.0	86	1
		Type1	3	1.0	538.0	99	1
		Type1	4	1.0	878.0	61	1
		Type1	5	1.0	3066.0	18	1
		Type1	6	1.0	638.0	83	1
		Type1	7	1.0	918.0	58	1
		Type1	8	1.0	838.0	63	1
		Type1	9	1.0	858.0	62	1
		Type1	10	1.0	798.0	67	1
		Type1	11	1.0	718.0	74	1
		Type1	12	1.0	578.0	92	1
		Type1	13	1.0	598.0	89	0
		Type1	14	1.0	558.0	95	1
		Type1	15	1.0	2536.0	21	1
		Type1	16	1.0	966.0	55	1
		Type1	17	1.0	827.0	64	1
		Type1	18	1.0	2501.0	22	1
		Type1	19	1.0	2595.0	21	1
		Type1	20	1.0	1114.0	48	1
		Type1	21	1.0	1302.0	41	1
		Type1	22	1.0	3045.0	18	0
		Type1	23	1.0	1624.0	33	1
		Type1	24	1.0	2878.0	19	1
		Type1	25	1.0	1027.0	52	1
		Type1	26	1.0	2485.0	22	1
		Type1	27	1.0	1600.0	33	1
		Type1	28	1.0	1172.0	46	1
		Type1	29	1.0	1177.0	45	1

11AX160MIMO	5570	Type2	0	3.2	179.0	26	1
		Type2	1	1.1	207.0	23	1
		Type2	2	2.1	230.0	24	1
		Type2	3	4.8	200.0	29	1
		Type2	4	3.9	214.0	28	1
		Type2	5	2.9	222.0	26	1
		Type2	6	3.2	204.0	26	1
		Type2	7	2.5	192.0	25	1
		Type2	8	3.1	164.0	26	1
		Type2	9	1.2	156.0	23	1
		Type2	10	3.9	210.0	27	1
		Type2	11	4.6	201.0	29	1
		Type2	12	3.2	162.0	26	1
		Type2	13	2.2	197.0	25	1
		Type2	14	4.5	163.0	29	1
		Type2	15	3.0	203.0	26	1
		Type2	16	5.0	168.0	29	1
		Type2	17	2.4	217.0	25	0
		Type2	18	2.9	191.0	26	0
		Type2	19	2.3	166.0	25	1
		Type2	20	3.7	150.0	27	1
		Type2	21	2.2	176.0	25	1
		Type2	22	4.9	195.0	29	1
		Type2	23	2.9	202.0	26	1
		Type2	24	2.5	178.0	25	1
		Type2	25	1.1	206.0	23	1
		Type2	26	3.8	155.0	27	1
		Type2	27	4.7	157.0	29	0
		Type2	28	2.4	224.0	25	1
		Type2	29	4.2	159.0	28	1
		Type3	0	8.2	355.0	17	1
		Type3	1	6.1	487.0	16	1
		Type3	2	7.1	344.0	16	1
		Type3	3	9.8	288.0	18	1
		Type3	4	8.9	230.0	18	1
		Type3	5	7.9	432.0	17	0
		Type3	6	8.2	207.0	17	1
		Type3	7	7.5	443.0	17	1
		Type3	8	8.1	439.0	17	1
		Type3	9	6.2	223.0	16	1
		Type3	10	8.9	208.0	18	1
		Type3	11	9.6	463.0	18	1
		Type3	12	8.2	441.0	17	1
		Type3	13	7.2	323.0	16	0
		Type3	14	9.5	297.0	18	1
		Type3	15	8.0	412.0	17	1
		Type3	16	10.0	324.0	18	1
		Type3	17	7.4	271.0	17	1
		Type3	18	7.9	349.0	17	1
		Type3	19	7.3	409.0	16	1
		Type3	20	8.7	373.0	18	1

11AX160MIMO	5570	Type3	21	7.2	254.0	16	1
		Type3	22	9.9	274.0	18	0
		Type3	23	7.9	278.0	17	1
		Type3	24	7.5	317.0	17	1
		Type3	25	6.1	260.0	16	1
		Type3	26	8.8	211.0	18	1
		Type3	27	9.7	272.0	18	1
		Type3	28	7.4	264.0	17	1
		Type3	29	9.2	284.0	18	1
		Type4	0	16.0	355.0	14	1
		Type4	1	11.3	487.0	12	1
		Type4	2	13.5	344.0	13	1
		Type4	3	19.4	288.0	16	1
		Type4	4	17.5	230.0	15	1
		Type4	5	15.3	432.0	14	1
		Type4	6	15.9	207.0	14	1
		Type4	7	14.3	443.0	13	1
		Type4	8	15.8	439.0	14	1
		Type4	9	11.5	223.0	12	1
		Type4	10	17.4	208.0	15	1
		Type4	11	19.0	463.0	16	1
		Type4	12	16.0	441.0	14	1
		Type4	13	13.8	323.0	13	1
		Type4	14	18.9	297.0	16	1
		Type4	15	15.5	412.0	14	1
		Type4	16	19.9	324.0	16	1
		Type4	17	14.1	271.0	13	0
		Type4	18	15.2	349.0	14	0
		Type4	19	13.8	409.0	13	1
		Type4	20	17.1	373.0	15	1
		Type4	21	13.8	254.0	13	1
		Type4	22	19.8	274.0	16	1
		Type4	23	15.3	278.0	14	1
		Type4	24	14.5	317.0	13	1
		Type4	25	11.3	260.0	12	1
		Type4	26	17.3	211.0	15	0
		Type4	27	19.2	272.0	16	0
		Type4	28	14.2	264.0	13	0
		Type4	29	18.2	284.0	15	1

Test Mode	Channel	Radar Type	Trial ID	Number Of Bursts	Waveform Length (s)	Radar Frequency	Detection (1: Yes; 0: No)
11AX20MIMO	5260	Type5	0	15	12	5260	1
		Type5	1	8	12	5260	1
		Type5	2	11	12	5260	1
		Type5	3	20	12	5260	1
		Type5	4	17	12	5260	1
		Type5	5	14	12	5260	0
		Type5	6	15	12	5260	1
		Type5	7	12	12	5260	1
		Type5	8	14	12	5260	1
		Type5	9	8	12	5260	1
		Type5	10	17	12	5229	1
		Type5	11	19	12	5230	0
		Type5	12	15	12	5228	1
		Type5	13	12	12	5226	1
		Type5	14	19	12	5230	1
		Type5	15	14	12	5227	1
		Type5	16	20	12	5230	1
		Type5	17	12	12	5226	1
		Type5	18	14	12	5227	1
		Type5	19	12	12	5226	0
		Type5	20	16	12	5292	1
		Type5	21	12	12	5294	1
		Type5	22	20	12	5290	1
		Type5	23	14	12	5293	1
		Type5	24	13	12	5293	1
		Type5	25	8	12	5296	1
		Type5	26	17	12	5291	1
		Type5	27	19	12	5290	1
		Type5	28	12	12	5294	1
		Type5	29	18	12	5291	1
	5500	Type5	0	15	12	5500	1
		Type5	1	8	12	5500	1
		Type5	2	11	12	5500	1
		Type5	3	20	12	5500	1
		Type5	4	17	12	5500	1
		Type5	5	14	12	5500	1
		Type5	6	15	12	5500	1
		Type5	7	12	12	5500	1
		Type5	8	14	12	5500	1
		Type5	9	8	12	5500	0
		Type5	10	17	12	5469	0
		Type5	11	19	12	5470	1
		Type5	12	15	12	5468	1
		Type5	13	12	12	5466	1
		Type5	14	19	12	5470	1
		Type5	15	14	12	5467	1
		Type5	16	20	12	5470	1
		Type5	17	12	12	5466	1
		Type5	18	14	12	5467	1
		Type5	19	12	12	5466	1
		Type5	20	16	12	5532	1

11AX20MIMO	5500	Type5	21	12	12	5534	1
		Type5	22	20	12	5530	0
		Type5	23	14	12	5533	0
		Type5	24	13	12	5533	1
		Type5	25	8	12	5536	1
		Type5	26	17	12	5531	1
		Type5	27	19	12	5530	0
		Type5	28	12	12	5534	1
		Type5	29	18	12	5531	1
11AX40MIMO	5270	Type5	0	15	12	5270	1
		Type5	1	8	12	5270	1
		Type5	2	11	12	5270	1
		Type5	3	20	12	5270	1
		Type5	4	17	12	5270	1
		Type5	5	14	12	5270	1
		Type5	6	15	12	5270	0
		Type5	7	12	12	5270	1
		Type5	8	14	12	5270	1
		Type5	9	8	12	5270	1
		Type5	10	17	12	5239	1
		Type5	11	19	12	5240	1
		Type5	12	15	12	5238	0
		Type5	13	12	12	5236	1
		Type5	14	19	12	5240	1
		Type5	15	14	12	5237	1
		Type5	16	20	12	5240	1
		Type5	17	12	12	5236	1
		Type5	18	14	12	5237	1
		Type5	19	12	12	5236	1
		Type5	20	16	12	5302	1
		Type5	21	12	12	5304	0
		Type5	22	20	12	5300	1
		Type5	23	14	12	5303	1
		Type5	24	13	12	5303	1
		Type5	25	8	12	5306	1
		Type5	26	17	12	5301	1
		Type5	27	19	12	5300	1
		Type5	28	12	12	5304	1
		Type5	29	18	12	5301	1
	5510	Type5	0	15	12	5510	1
		Type5	1	8	12	5510	1
		Type5	2	11	12	5510	1
		Type5	3	20	12	5510	1
		Type5	4	17	12	5510	0
		Type5	5	14	12	5510	1
		Type5	6	15	12	5510	1
		Type5	7	12	12	5510	1
		Type5	8	14	12	5510	1
		Type5	9	8	12	5510	1
		Type5	10	17	12	5479	1

11AX40MIMO	5510	Type5	11	19	12	5480	1
		Type5	12	15	12	5478	0
		Type5	13	12	12	5476	1
		Type5	14	19	12	5480	0
		Type5	15	14	12	5477	1
		Type5	16	20	12	5480	1
		Type5	17	12	12	5476	1
		Type5	18	14	12	5477	1
		Type5	19	12	12	5476	1
		Type5	20	16	12	5542	1
		Type5	21	12	12	5544	1
		Type5	22	20	12	5540	1
		Type5	23	14	12	5543	1
		Type5	24	13	12	5543	0
		Type5	25	8	12	5546	1
		Type5	26	17	12	5541	1
		Type5	27	19	12	5540	1
		Type5	28	12	12	5544	1
		Type5	29	18	12	5541	1
11AX80MIMO	5290	Type5	0	15	12	5290	1
		Type5	1	8	12	5290	1
		Type5	2	11	12	5290	1
		Type5	3	20	12	5290	1
		Type5	4	17	12	5290	1
		Type5	5	14	12	5290	0
		Type5	6	15	12	5290	1
		Type5	7	12	12	5290	1
		Type5	8	14	12	5290	1
		Type5	9	8	12	5290	0
		Type5	10	17	12	5259	1
		Type5	11	19	12	5260	1
		Type5	12	15	12	5258	0
		Type5	13	12	12	5256	1
		Type5	14	19	12	5260	1
		Type5	15	14	12	5257	0
		Type5	16	20	12	5260	1
		Type5	17	12	12	5256	1
		Type5	18	14	12	5257	1
		Type5	19	12	12	5256	1
		Type5	20	16	12	5322	1
		Type5	21	12	12	5324	1
		Type5	22	20	12	5320	1
		Type5	23	14	12	5323	1
		Type5	24	13	12	5323	1
		Type5	25	8	12	5326	1
		Type5	26	17	12	5321	1
		Type5	27	19	12	5320	1
		Type5	28	12	12	5324	1
		Type5	29	18	12	5321	1

11AX80MIMO	5530	Type5	0	15	12	5530	1
		Type5	1	8	12	5530	1
		Type5	2	11	12	5530	1
		Type5	3	20	12	5530	1
		Type5	4	17	12	5530	1
		Type5	5	14	12	5530	1
		Type5	6	15	12	5530	1
		Type5	7	12	12	5530	1
		Type5	8	14	12	5530	1
		Type5	9	8	12	5530	1
		Type5	10	17	12	5499	0
		Type5	11	19	12	5500	0
		Type5	12	15	12	5498	1
		Type5	13	12	12	5496	1
		Type5	14	19	12	5500	0
		Type5	15	14	12	5497	1
		Type5	16	20	12	5500	1
		Type5	17	12	12	5496	1
		Type5	18	14	12	5497	1
		Type5	19	12	12	5496	1
		Type5	20	16	12	5562	1
		Type5	21	12	12	5564	1
		Type5	22	20	12	5560	0
		Type5	23	14	12	5563	1
		Type5	24	13	12	5563	1
		Type5	25	8	12	5566	1
		Type5	26	17	12	5561	1
		Type5	27	19	12	5560	1
		Type5	28	12	12	5564	1
		Type5	29	18	12	5561	1
11AX160MIMO	5250	Type5	0	15	12	5260	0
		Type5	1	8	12	5260	1
		Type5	2	11	12	5260	1
		Type5	3	20	12	5260	1
		Type5	4	17	12	5260	0
		Type5	5	14	12	5260	1
		Type5	6	15	12	5260	1
		Type5	7	12	12	5260	1
		Type5	8	14	12	5260	1
		Type5	9	8	12	5260	1
		Type5	10	17	12	5229	0
		Type5	11	19	12	5230	1
		Type5	12	15	12	5228	1
		Type5	13	12	12	5226	1
		Type5	14	19	12	5230	1
		Type5	15	14	12	5227	0
		Type5	16	20	12	5230	1
		Type5	17	12	12	5226	1
		Type5	18	14	12	5227	1
		Type5	19	12	12	5226	1
		Type5	20	16	12	5292	1

11AX160MIMO	5250	Type5	21	12	12	5294	0
		Type5	22	20	12	5290	1
		Type5	23	14	12	5293	1
		Type5	24	13	12	5293	1
		Type5	25	8	12	5296	1
		Type5	26	17	12	5291	0
		Type5	27	19	12	5290	1
		Type5	28	12	12	5294	1
		Type5	29	18	12	5291	1
	5570	Type5	0	15	12	5570	1
		Type5	1	8	12	5570	1
		Type5	2	11	12	5570	1
		Type5	3	20	12	5570	1
		Type5	4	17	12	5570	0
		Type5	5	14	12	5570	1
		Type5	6	15	12	5570	1
		Type5	7	12	12	5570	1
		Type5	8	14	12	5570	1
		Type5	9	8	12	5570	1
		Type5	10	17	12	5539	0
		Type5	11	19	12	5540	1
		Type5	12	15	12	5538	1
		Type5	13	12	12	5536	1
		Type5	14	19	12	5540	1
		Type5	15	14	12	5537	1
		Type5	16	20	12	5540	1
		Type5	17	12	12	5536	1
		Type5	18	14	12	5537	1
		Type5	19	12	12	5536	0
		Type5	20	16	12	5602	0
		Type5	21	12	12	5604	0
		Type5	22	20	12	5600	1
		Type5	23	14	12	5603	1
		Type5	24	13	12	5603	1
		Type5	25	8	12	5606	1
		Type5	26	17	12	5601	1
		Type5	27	19	12	5600	1
		Type5	28	12	12	5604	1
		Type5	29	18	12	5601	1

Test Mode	Channel	Radar Type	Trial ID	Pulse width (μs)	PRI (μs)	Pulses per Hop	Detection (1: Yes; 0: No)
11AX20MIMO	5260	Type6	0	1	333.3	9	1
		Type6	1	1	333.3	9	1
		Type6	2	1	333.3	9	1
		Type6	3	1	333.3	9	1
		Type6	4	1	333.3	9	1
		Type6	5	1	333.3	9	1
		Type6	6	1	333.3	9	1
		Type6	7	1	333.3	9	1
		Type6	8	1	333.3	9	1
		Type6	9	1	333.3	9	1
		Type6	10	1	333.3	9	1
		Type6	11	1	333.3	9	1
		Type6	12	1	333.3	9	1
		Type6	13	1	333.3	9	1
		Type6	14	1	333.3	9	1
		Type6	15	1	333.3	9	1
		Type6	16	1	333.3	9	0
		Type6	17	1	333.3	9	1
		Type6	18	1	333.3	9	1
		Type6	19	1	333.3	9	1
		Type6	20	1	333.3	9	1
		Type6	21	1	333.3	9	1
		Type6	22	1	333.3	9	1
		Type6	23	1	333.3	9	1
		Type6	24	1	333.3	9	0
		Type6	25	1	333.3	9	0
		Type6	26	1	333.3	9	1
		Type6	27	1	333.3	9	0
		Type6	28	1	333.3	9	1
		Type6	29	1	333.3	9	1
	5500	Type6	0	1	333.3	9	1
		Type6	1	1	333.3	9	1
		Type6	2	1	333.3	9	1
		Type6	3	1	333.3	9	1
		Type6	4	1	333.3	9	1
		Type6	5	1	333.3	9	1
		Type6	6	1	333.3	9	1
		Type6	7	1	333.3	9	1
		Type6	8	1	333.3	9	1
		Type6	9	1	333.3	9	1
		Type6	10	1	333.3	9	1
		Type6	11	1	333.3	9	1
		Type6	12	1	333.3	9	1
		Type6	13	1	333.3	9	1
		Type6	14	1	333.3	9	1
		Type6	15	1	333.3	9	1
		Type6	16	1	333.3	9	1
		Type6	17	1	333.3	9	0
		Type6	18	1	333.3	9	1
		Type6	19	1	333.3	9	1
		Type6	20	1	333.3	9	1

11AX20MIMO	5500	Type6	21	1	333.3	9	1
		Type6	22	1	333.3	9	0
		Type6	23	1	333.3	9	1
		Type6	24	1	333.3	9	1
		Type6	25	1	333.3	9	1
		Type6	26	1	333.3	9	0
		Type6	27	1	333.3	9	1
		Type6	28	1	333.3	9	1
		Type6	29	1	333.3	9	1
11AX40MIMO	5270	Type6	0	1	333.3	9	1
		Type6	1	1	333.3	9	1
		Type6	2	1	333.3	9	1
		Type6	3	1	333.3	9	1
		Type6	4	1	333.3	9	1
		Type6	5	1	333.3	9	1
		Type6	6	1	333.3	9	1
		Type6	7	1	333.3	9	1
		Type6	8	1	333.3	9	0
		Type6	9	1	333.3	9	1
		Type6	10	1	333.3	9	1
		Type6	11	1	333.3	9	1
		Type6	12	1	333.3	9	1
		Type6	13	1	333.3	9	1
		Type6	14	1	333.3	9	1
		Type6	15	1	333.3	9	0
		Type6	16	1	333.3	9	1
		Type6	17	1	333.3	9	0
		Type6	18	1	333.3	9	1
		Type6	19	1	333.3	9	1
		Type6	20	1	333.3	9	1
		Type6	21	1	333.3	9	1
		Type6	22	1	333.3	9	1
		Type6	23	1	333.3	9	1
		Type6	24	1	333.3	9	1
		Type6	25	1	333.3	9	1
		Type6	26	1	333.3	9	1
		Type6	27	1	333.3	9	1
		Type6	28	1	333.3	9	1
		Type6	29	1	333.3	9	1
	5510	Type6	0	1	333.3	9	1
		Type6	1	1	333.3	9	1
		Type6	2	1	333.3	9	1
		Type6	3	1	333.3	9	1
		Type6	4	1	333.3	9	0
		Type6	5	1	333.3	9	1
		Type6	6	1	333.3	9	1
		Type6	7	1	333.3	9	1
		Type6	8	1	333.3	9	1
		Type6	9	1	333.3	9	1
		Type6	10	1	333.3	9	1

11AX40MIMO	5510	Type6	11	1	333.3	9	1
		Type6	12	1	333.3	9	1
		Type6	13	1	333.3	9	1
		Type6	14	1	333.3	9	0
		Type6	15	1	333.3	9	1
		Type6	16	1	333.3	9	1
		Type6	17	1	333.3	9	1
		Type6	18	1	333.3	9	1
		Type6	19	1	333.3	9	1
		Type6	20	1	333.3	9	1
		Type6	21	1	333.3	9	1
		Type6	22	1	333.3	9	1
		Type6	23	1	333.3	9	1
		Type6	24	1	333.3	9	0
		Type6	25	1	333.3	9	0
		Type6	26	1	333.3	9	1
		Type6	27	1	333.3	9	1
		Type6	28	1	333.3	9	1
		Type6	29	1	333.3	9	1
11AX80MIMO	5290	Type6	0	1	333.3	9	1
		Type6	1	1	333.3	9	1
		Type6	2	1	333.3	9	1
		Type6	3	1	333.3	9	1
		Type6	4	1	333.3	9	1
		Type6	5	1	333.3	9	0
		Type6	6	1	333.3	9	1
		Type6	7	1	333.3	9	1
		Type6	8	1	333.3	9	0
		Type6	9	1	333.3	9	1
		Type6	10	1	333.3	9	1
		Type6	11	1	333.3	9	1
		Type6	12	1	333.3	9	1
		Type6	13	1	333.3	9	0
		Type6	14	1	333.3	9	1
		Type6	15	1	333.3	9	1
		Type6	16	1	333.3	9	1
		Type6	17	1	333.3	9	1
		Type6	18	1	333.3	9	1
		Type6	19	1	333.3	9	1
		Type6	20	1	333.3	9	1
		Type6	21	1	333.3	9	1
		Type6	22	1	333.3	9	1
		Type6	23	1	333.3	9	1
		Type6	24	1	333.3	9	1
		Type6	25	1	333.3	9	1
		Type6	26	1	333.3	9	1
		Type6	27	1	333.3	9	1
		Type6	28	1	333.3	9	1
		Type6	29	1	333.3	9	1

11AX80MIMO	5530	Type6	0	1	333.3	9	1
		Type6	1	1	333.3	9	1
		Type6	2	1	333.3	9	1
		Type6	3	1	333.3	9	1
		Type6	4	1	333.3	9	1
		Type6	5	1	333.3	9	1
		Type6	6	1	333.3	9	1
		Type6	7	1	333.3	9	1
		Type6	8	1	333.3	9	1
		Type6	9	1	333.3	9	1
		Type6	10	1	333.3	9	1
		Type6	11	1	333.3	9	0
		Type6	12	1	333.3	9	1
		Type6	13	1	333.3	9	1
		Type6	14	1	333.3	9	1
		Type6	15	1	333.3	9	1
		Type6	16	1	333.3	9	1
		Type6	17	1	333.3	9	1
		Type6	18	1	333.3	9	1
		Type6	19	1	333.3	9	1
		Type6	20	1	333.3	9	1
		Type6	21	1	333.3	9	0
		Type6	22	1	333.3	9	1
		Type6	23	1	333.3	9	1
		Type6	24	1	333.3	9	0
		Type6	25	1	333.3	9	1
		Type6	26	1	333.3	9	1
		Type6	27	1	333.3	9	1
		Type6	28	1	333.3	9	1
		Type6	29	1	333.3	9	1
11AX160MIMO	5250	Type6	0	1	333.3	9	1
		Type6	1	1	333.3	9	1
		Type6	2	1	333.3	9	1
		Type6	3	1	333.3	9	1
		Type6	4	1	333.3	9	1
		Type6	5	1	333.3	9	1
		Type6	6	1	333.3	9	1
		Type6	7	1	333.3	9	1
		Type6	8	1	333.3	9	1
		Type6	9	1	333.3	9	1
		Type6	10	1	333.3	9	1
		Type6	11	1	333.3	9	1
		Type6	12	1	333.3	9	1
		Type6	13	1	333.3	9	1
		Type6	14	1	333.3	9	1
		Type6	15	1	333.3	9	1
		Type6	16	1	333.3	9	1
		Type6	17	1	333.3	9	1
		Type6	18	1	333.3	9	1
		Type6	19	1	333.3	9	1
		Type6	20	1	333.3	9	0

11AX160MIMO	5250	Type6	21	1	333.3	9	1
		Type6	22	1	333.3	9	1
		Type6	23	1	333.3	9	1
		Type6	24	1	333.3	9	1
		Type6	25	1	333.3	9	1
		Type6	26	1	333.3	9	1
		Type6	27	1	333.3	9	1
		Type6	28	1	333.3	9	1
		Type6	29	1	333.3	9	1
	5570	Type6	0	1	333.3	9	1
		Type6	1	1	333.3	9	1
		Type6	2	1	333.3	9	1
		Type6	3	1	333.3	9	1
		Type6	4	1	333.3	9	1
		Type6	5	1	333.3	9	1
		Type6	6	1	333.3	9	1
		Type6	7	1	333.3	9	1
		Type6	8	1	333.3	9	1
		Type6	9	1	333.3	9	1
		Type6	10	1	333.3	9	1
		Type6	11	1	333.3	9	0
		Type6	12	1	333.3	9	1
		Type6	13	1	333.3	9	1
		Type6	14	1	333.3	9	1
		Type6	15	1	333.3	9	1
		Type6	16	1	333.3	9	1
		Type6	17	1	333.3	9	1
		Type6	18	1	333.3	9	1
		Type6	19	1	333.3	9	1
		Type6	20	1	333.3	9	0
		Type6	21	1	333.3	9	1
		Type6	22	1	333.3	9	1
		Type6	23	1	333.3	9	1
		Type6	24	1	333.3	9	1
		Type6	25	1	333.3	9	1
		Type6	26	1	333.3	9	1
		Type6	27	1	333.3	9	1
		Type6	28	1	333.3	9	1
		Type6	29	1	333.3	9	1

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MIMO	5260	Type5	0	9	783794.0	13	1	53.2	1147.0	---	---
		Type5	0	0	636185.0	13	2	77.8	1665.0	1477.0	---
		Type5	0	13	759583.0	13	1	65.7	1512.0	---	---
		Type5	0	12	564893.0	13	2	77.6	1294.0	1671.0	---
		Type5	0	10	177933.0	13	3	85.7	1433.0	1695.0	1394.0
		Type5	0	14	154262.0	13	3	93.5	1444.0	1130.0	1468.0
		Type5	0	8	588564.0	13	2	76.7	2000.0	1155.0	---
		Type5	0	7	395530.0	13	2	68.4	1587.0	1114.0	---
		Type5	0	6	201917.0	13	2	77.2	1837.0	1819.0	---
		Type5	0	5	8789.0	13	2	73.7	1198.0	1549.0	---
		Type5	0	4	611152.0	13	3	85.9	1795.0	1215.0	1729.0
		Type5	0	3	417976.0	13	3	96.6	1682.0	1786.0	1843.0
		Type5	0	2	226294.0	13	1	63.8	1584.0	---	---
		Type5	0	1	32674.0	13	1	51.9	1074.0	---	---
		Type5	0	11	370624.0	13	3	94.3	1670.0	1426.0	1935.0
	5500	Type5	0	7	395530.0	13	2	68.4	1587.0	1114.0	---
		Type5	0	12	564893.0	13	2	77.6	1294.0	1671.0	---
		Type5	0	11	370624.0	13	3	94.3	1670.0	1426.0	1935.0
		Type5	0	10	177933.0	13	3	85.7	1433.0	1695.0	1394.0
		Type5	0	9	783794.0	13	1	53.2	1147.0	---	---
		Type5	0	8	588564.0	13	2	76.7	2000.0	1155.0	---
		Type5	0	6	201917.0	13	2	77.2	1837.0	1819.0	---
		Type5	0	5	8789.0	13	2	73.7	1198.0	1549.0	---
		Type5	0	4	611152.0	13	3	85.9	1795.0	1215.0	1729.0
		Type5	0	3	417976.0	13	3	96.6	1682.0	1786.0	1843.0
		Type5	0	2	226294.0	13	1	63.8	1584.0	---	---
		Type5	0	13	759583.0	13	1	65.7	1512.0	---	---
		Type5	0	0	636185.0	13	2	77.8	1665.0	1477.0	---
		Type5	0	14	154262.0	13	3	93.5	1444.0	1130.0	1468.0
		Type5	0	1	32674.0	13	1	51.9	1074.0	---	---
11AX40MIMO	5270	Type5	0	14	154262.0	13	3	93.5	1444.0	1130.0	1468.0
		Type5	0	0	636185.0	13	2	77.8	1665.0	1477.0	---
		Type5	0	1	32674.0	13	1	51.9	1074.0	---	---
		Type5	0	2	226294.0	13	1	63.8	1584.0	---	---
		Type5	0	3	417976.0	13	3	96.6	1682.0	1786.0	1843.0
		Type5	0	4	611152.0	13	3	85.9	1795.0	1215.0	1729.0
		Type5	0	5	8789.0	13	2	73.7	1198.0	1549.0	---
		Type5	0	6	201917.0	13	2	77.2	1837.0	1819.0	---
		Type5	0	7	395530.0	13	2	68.4	1587.0	1114.0	---
		Type5	0	8	588564.0	13	2	76.7	2000.0	1155.0	---
		Type5	0	9	783794.0	13	1	53.2	1147.0	---	---
		Type5	0	10	177933.0	13	3	85.7	1433.0	1695.0	1394.0
		Type5	0	11	370624.0	13	3	94.3	1670.0	1426.0	1935.0
		Type5	0	12	564893.0	13	2	77.6	1294.0	1671.0	---
		Type5	0	13	759583.0	13	1	65.7	1512.0	---	---
	5510	Type5	0	2	226294.0	13	1	63.8	1584.0	---	---
		Type5	0	14	154262.0	13	3	93.5	1444.0	1130.0	1468.0
		Type5	0	13	759583.0	13	1	65.7	1512.0	---	---
		Type5	0	12	564893.0	13	2	77.6	1294.0	1671.0	---
		Type5	0	11	370624.0	13	3	94.3	1670.0	1426.0	1935.0
		Type5	0	10	177933.0	13	3	85.7	1433.0	1695.0	1394.0
		Type5	0	9	783794.0	13	1	53.2	1147.0	---	---
		Type5	0	8	588564.0	13	2	76.7	2000.0	1155.0	---
		Type5	0	7	395530.0	13	2	68.4	1587.0	1114.0	---

		Type5	0	6	201917.0	13	2	77.2	1837.0	1819.0	---
		Type5	0	5	8789.0	13	2	73.7	1198.0	1549.0	---
		Type5	0	3	417976.0	13	3	96.6	1682.0	1786.0	1843.0
		Type5	0	1	32674.0	13	1	51.9	1074.0	---	---
		Type5	0	0	636185.0	13	2	77.8	1665.0	1477.0	---
		Type5	0	4	611152.0	13	3	85.9	1795.0	1215.0	1729.0
11AX80MIMO	5290	Type5	0	8	588564.0	13	2	76.7	2000.0	1155.0	---
		Type5	0	13	759583.0	13	1	65.7	1512.0	---	---
		Type5	0	0	636185.0	13	2	77.8	1665.0	1477.0	---
		Type5	0	12	564893.0	13	2	77.6	1294.0	1671.0	---
		Type5	0	11	370624.0	13	3	94.3	1670.0	1426.0	1935.0
		Type5	0	9	783794.0	13	1	53.2	1147.0	---	---
		Type5	0	7	395530.0	13	2	68.4	1587.0	1114.0	---
		Type5	0	6	201917.0	13	2	77.2	1837.0	1819.0	---
		Type5	0	5	8789.0	13	2	73.7	1198.0	1549.0	---
		Type5	0	4	611152.0	13	3	85.9	1795.0	1215.0	1729.0
		Type5	0	14	154262.0	13	3	93.5	1444.0	1130.0	1468.0
		Type5	0	3	417976.0	13	3	96.6	1682.0	1786.0	1843.0
		Type5	0	2	226294.0	13	1	63.8	1584.0	---	---
		Type5	0	1	32674.0	13	1	51.9	1074.0	---	---
		Type5	0	10	177933.0	13	3	85.7	1433.0	1695.0	1394.0
	5530	Type5	0	13	759583.0	13	1	65.7	1512.0	---	---
		Type5	0	5	8789.0	13	2	73.7	1198.0	1549.0	---
		Type5	0	12	564893.0	13	2	77.6	1294.0	1671.0	---
		Type5	0	11	370624.0	13	3	94.3	1670.0	1426.0	1935.0
		Type5	0	10	177933.0	13	3	85.7	1433.0	1695.0	1394.0
		Type5	0	9	783794.0	13	1	53.2	1147.0	---	---
		Type5	0	8	588564.0	13	2	76.7	2000.0	1155.0	---
		Type5	0	4	611152.0	13	3	85.9	1795.0	1215.0	1729.0
		Type5	0	3	417976.0	13	3	96.6	1682.0	1786.0	1843.0
		Type5	0	2	226294.0	13	1	63.8	1584.0	---	---
		Type5	0	1	32674.0	13	1	51.9	1074.0	---	---
		Type5	0	0	636185.0	13	2	77.8	1665.0	1477.0	---
		Type5	0	14	154262.0	13	3	93.5	1444.0	1130.0	1468.0
		Type5	0	7	395530.0	13	2	68.4	1587.0	1114.0	---
		Type5	0	6	201917.0	13	2	77.2	1837.0	1819.0	---
11AX160MIMO	5250	Type5	0	4	611152.0	13	3	85.9	1795.0	1215.0	1729.0
		Type5	0	0	636185.0	13	2	77.8	1665.0	1477.0	---
		Type5	0	1	32674.0	13	1	51.9	1074.0	---	---
		Type5	0	3	417976.0	13	3	96.6	1682.0	1786.0	1843.0
		Type5	0	5	8789.0	13	2	73.7	1198.0	1549.0	---
		Type5	0	6	201917.0	13	2	77.2	1837.0	1819.0	---
		Type5	0	7	395530.0	13	2	68.4	1587.0	1114.0	---
		Type5	0	9	783794.0	13	1	53.2	1147.0	---	---
		Type5	0	10	177933.0	13	3	85.7	1433.0	1695.0	1394.0
		Type5	0	11	370624.0	13	3	94.3	1670.0	1426.0	1935.0
		Type5	0	12	564893.0	13	2	77.6	1294.0	1671.0	---
		Type5	0	13	759583.0	13	1	65.7	1512.0	---	---
		Type5	0	14	154262.0	13	3	93.5	1444.0	1130.0	1468.0
		Type5	0	8	588564.0	13	2	76.7	2000.0	1155.0	---
		Type5	0	2	226294.0	13	1	63.8	1584.0	---	---
	5570	Type5	0	2	226294.0	13	1	63.8	1584.0	---	---
		Type5	0	13	759583.0	13	1	65.7	1512.0	---	---
		Type5	0	12	564893.0	13	2	77.6	1294.0	1671.0	---
		Type5	0	11	370624.0	13	3	94.3	1670.0	1426.0	1935.0
		Type5	0	10	177933.0	13	3	85.7	1433.0	1695.0	1394.0
		Type5	0	9	783794.0	13	1	53.2	1147.0	---	---
		Type5	0	8	588564.0	13	2	76.7	2000.0	1155.0	---
		Type5	0	8	588564.0	13	2	76.7	2000.0	1155.0	---
		Type5	0	8	588564.0	13	2	76.7	2000.0	1155.0	---

	Type5	0	7	395530.0	13	2	68.4	1587.0	1114.0	---
	Type5	0	6	201917.0	13	2	77.2	1837.0	1819.0	---
	Type5	0	5	8789.0	13	2	73.7	1198.0	1549.0	---
	Type5	0	3	417976.0	13	3	96.6	1682.0	1786.0	1843.0
	Type5	0	1	32674.0	13	1	51.9	1074.0	---	---
	Type5	0	0	636185.0	13	2	77.8	1665.0	1477.0	---
	Type5	0	14	154262.0	13	3	93.5	1444.0	1130.0	1468.0
	Type5	0	4	611152.0	13	3	85.9	1795.0	1215.0	1729.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	1	7	200406.0	5	3	98.6	1548.0	1796.0	1728.0
		Type5	1	1	1015643.0	5	3	99.4	1401.0	1262.0	1257.0
		Type5	1	2	1379398.0	5	2	67.4	1531.0	1403.0	---
		Type5	1	3	245489.0	5	2	73.6	1449.0	1041.0	---
		Type5	1	4	609113.0	5	1	65.9	1432.0	---	---
		Type5	1	5	970852.0	5	3	83.8	1356.0	1292.0	1419.0
		Type5	1	6	1335913.0	5	1	65.5	1543.0	---	---
		Type5	1	0	653020.0	5	2	75.0	1880.0	1527.0	---
	5500	Type5	1	5	970852.0	5	3	83.8	1356.0	1292.0	1419.0
		Type5	1	4	609113.0	5	1	65.9	1432.0	---	---
		Type5	1	3	245489.0	5	2	73.6	1449.0	1041.0	---
		Type5	1	2	1379398.0	5	2	67.4	1531.0	1403.0	---
		Type5	1	6	1335913.0	5	1	65.5	1543.0	---	---
		Type5	1	0	653020.0	5	2	75.0	1880.0	1527.0	---
		Type5	1	7	200406.0	5	3	98.6	1548.0	1796.0	1728.0
11AX40MIMO	5270	Type5	1	1	1015643.0	5	3	99.4	1401.0	1262.0	1257.0
		Type5	1	7	200406.0	5	3	98.6	1548.0	1796.0	1728.0
		Type5	1	0	653020.0	5	2	75.0	1880.0	1527.0	---
		Type5	1	1	1015643.0	5	3	99.4	1401.0	1262.0	1257.0
		Type5	1	2	1379398.0	5	2	67.4	1531.0	1403.0	---
		Type5	1	3	245489.0	5	2	73.6	1449.0	1041.0	---
		Type5	1	4	609113.0	5	1	65.9	1432.0	---	---
		Type5	1	5	970852.0	5	3	83.8	1356.0	1292.0	1419.0
		Type5	1	6	1335913.0	5	1	65.5	1543.0	---	---
	5510	Type5	1	1	1015643.0	5	3	99.4	1401.0	1262.0	1257.0
		Type5	1	7	200406.0	5	3	98.6	1548.0	1796.0	1728.0
		Type5	1	6	1335913.0	5	1	65.5	1543.0	---	---
		Type5	1	5	970852.0	5	3	83.8	1356.0	1292.0	1419.0
		Type5	1	4	609113.0	5	1	65.9	1432.0	---	---
		Type5	1	2	1379398.0	5	2	67.4	1531.0	1403.0	---
		Type5	1	0	653020.0	5	2	75.0	1880.0	1527.0	---
11AX80MIMO	5290	Type5	1	3	245489.0	5	2	73.6	1449.0	1041.0	---
		Type5	1	1	1015643.0	5	3	99.4	1401.0	1262.0	1257.0
		Type5	1	2	1379398.0	5	2	67.4	1531.0	1403.0	---
		Type5	1	7	200406.0	5	3	98.6	1548.0	1796.0	1728.0
		Type5	1	3	245489.0	5	2	73.6	1449.0	1041.0	---
		Type5	1	4	609113.0	5	1	65.9	1432.0	---	---
		Type5	1	5	970852.0	5	3	83.8	1356.0	1292.0	1419.0
	5530	Type5	1	6	1335913.0	5	1	65.5	1543.0	---	---
		Type5	1	0	653020.0	5	2	75.0	1880.0	1527.0	---
		Type5	1	6	1335913.0	5	1	65.5	1543.0	---	---
		Type5	1	2	1379398.0	5	2	67.4	1531.0	1403.0	---
		Type5	1	5	970852.0	5	3	83.8	1356.0	1292.0	1419.0
		Type5	1	3	245489.0	5	2	73.6	1449.0	1041.0	---
		Type5	1	0	653020.0	5	2	75.0	1880.0	1527.0	---
11AX160MIMO	5250	Type5	1	7	200406.0	5	3	98.6	1548.0	1796.0	1728.0
		Type5	1	4	609113.0	5	1	65.9	1432.0	---	---
		Type5	1	1	1015643.0	5	3	99.4	1401.0	1262.0	1257.0
		Type5	1	2	1379398.0	5	2	67.4	1531.0	1403.0	---
		Type5	1	3	245489.0	5	2	73.6	1449.0	1041.0	---
		Type5	1	6	1335913.0	5	1	65.5	1543.0	---	---

		Type5	1	7	200406.0	5	3	98.6	1548.0	1796.0	1728.0
		Type5	1	0	653020.0	5	2	75.0	1880.0	1527.0	---
	5570	Type5	1	7	200406.0	5	3	98.6	1548.0	1796.0	1728.0
		Type5	1	0	653020.0	5	2	75.0	1880.0	1527.0	---
		Type5	1	1	1015643.0	5	3	99.4	1401.0	1262.0	1257.0
		Type5	1	2	1379398.0	5	2	67.4	1531.0	1403.0	---
		Type5	1	3	245489.0	5	2	73.6	1449.0	1041.0	---
		Type5	1	4	609113.0	5	1	65.9	1432.0	---	---
		Type5	1	5	970852.0	5	3	83.8	1356.0	1292.0	1419.0
		Type5	1	6	1335913.0	5	1	65.5	1543.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	2	10	871542.0	9	3	91.3	1961.0	1106.0	1001.0
		Type5	2	1	673692.0	9	2	69.5	1117.0	1649.0	---
		Type5	2	2	938562.0	9	1	51.9	1651.0	---	---
		Type5	2	3	113209.0	9	3	84.6	1976.0	1032.0	1271.0
		Type5	2	4	376726.0	9	3	95.4	1060.0	1903.0	1388.0
		Type5	2	5	641212.0	9	2	68.0	1368.0	1351.0	---
		Type5	2	6	903714.0	9	3	89.6	1338.0	1514.0	1573.0
		Type5	2	7	80863.0	9	2	81.9	1022.0	1689.0	---
		Type5	2	8	344067.0	9	3	88.3	1810.0	1330.0	1838.0
		Type5	2	9	609331.0	9	1	53.7	1597.0	---	---
		Type5	2	0	409565.0	9	2	73.8	1806.0	1538.0	---
	5500	Type5	2	8	344067.0	9	3	88.3	1810.0	1330.0	1838.0
		Type5	2	7	80863.0	9	2	81.9	1022.0	1689.0	---
		Type5	2	6	903714.0	9	3	89.6	1338.0	1514.0	1573.0
		Type5	2	5	641212.0	9	2	68.0	1368.0	1351.0	---
		Type5	2	4	376726.0	9	3	95.4	1060.0	1903.0	1388.0
		Type5	2	3	113209.0	9	3	84.6	1976.0	1032.0	1271.0
		Type5	2	2	938562.0	9	1	51.9	1651.0	---	---
		Type5	2	9	609331.0	9	1	53.7	1597.0	---	---
		Type5	2	0	409565.0	9	2	73.8	1806.0	1538.0	---
		Type5	2	10	871542.0	9	3	91.3	1961.0	1106.0	1001.0
		Type5	2	1	673692.0	9	2	69.5	1117.0	1649.0	---
11AX40MIMO	5270	Type5	2	10	871542.0	9	3	91.3	1961.0	1106.0	1001.0
		Type5	2	0	409565.0	9	2	73.8	1806.0	1538.0	---
		Type5	2	1	673692.0	9	2	69.5	1117.0	1649.0	---
		Type5	2	2	938562.0	9	1	51.9	1651.0	---	---
		Type5	2	3	113209.0	9	3	84.6	1976.0	1032.0	1271.0
		Type5	2	4	376726.0	9	3	95.4	1060.0	1903.0	1388.0
		Type5	2	5	641212.0	9	2	68.0	1368.0	1351.0	---
		Type5	2	6	903714.0	9	3	89.6	1338.0	1514.0	1573.0
		Type5	2	7	80863.0	9	2	81.9	1022.0	1689.0	---
		Type5	2	8	344067.0	9	3	88.3	1810.0	1330.0	1838.0
	5510	Type5	2	9	609331.0	9	1	53.7	1597.0	---	---
		Type5	2	1	673692.0	9	2	69.5	1117.0	1649.0	---
		Type5	2	10	871542.0	9	3	91.3	1961.0	1106.0	1001.0
		Type5	2	9	609331.0	9	1	53.7	1597.0	---	---
		Type5	2	8	344067.0	9	3	88.3	1810.0	1330.0	1838.0
		Type5	2	7	80863.0	9	2	81.9	1022.0	1689.0	---
		Type5	2	6	903714.0	9	3	89.6	1338.0	1514.0	1573.0
		Type5	2	5	641212.0	9	2	68.0	1368.0	1351.0	---
		Type5	2	4	376726.0	9	3	95.4	1060.0	1903.0	1388.0
		Type5	2	2	938562.0	9	1	51.9	1651.0	---	---
		Type5	2	0	409565.0	9	2	73.8	1806.0	1538.0	---
11AX80MIMO	5290	Type5	2	3	113209.0	9	3	84.6	1976.0	1032.0	1271.0
		Type5	2	5	641212.0	9	2	68.0	1368.0	1351.0	---
		Type5	2	9	609331.0	9	1	53.7	1597.0	---	---
		Type5	2	0	409565.0	9	2	73.8	1806.0	1538.0	---
		Type5	2	8	344067.0	9	3	88.3	1810.0	1330.0	1838.0
		Type5	2	6	903714.0	9	3	89.6	1338.0	1514.0	1573.0
		Type5	2	4	376726.0	9	3	95.4	1060.0	1903.0	1388.0
		Type5	2	3	113209.0	9	3	84.6	1976.0	1032.0	1271.0
		Type5	2	10	871542.0	9	3	91.3	1961.0	1106.0	1001.0
		Type5	2	2	938562.0	9	1	51.9	1651.0	---	---
		Type5	2	1	673692.0	9	2	69.5	1117.0	1649.0	---

	5530	Type5	2	7	80863.0	9	2	81.9	1022.0	1689.0	---
		Type5	2	9	609331.0	9	1	53.7	1597.0	---	---
		Type5	2	8	344067.0	9	3	88.3	1810.0	1330.0	1838.0
		Type5	2	7	80863.0	9	2	81.9	1022.0	1689.0	---
		Type5	2	3	113209.0	9	3	84.6	1976.0	1032.0	1271.0
		Type5	2	6	903714.0	9	3	89.6	1338.0	1514.0	1573.0
		Type5	2	2	938562.0	9	1	51.9	1651.0	---	---
		Type5	2	1	673692.0	9	2	69.5	1117.0	1649.0	---
		Type5	2	0	409565.0	9	2	73.8	1806.0	1538.0	---
		Type5	2	10	871542.0	9	3	91.3	1961.0	1106.0	1001.0
		Type5	2	5	641212.0	9	2	68.0	1368.0	1351.0	---
		Type5	2	4	376726.0	9	3	95.4	1060.0	1903.0	1388.0
11AX160MIMO	5250	Type5	2	3	113209.0	9	3	84.6	1976.0	1032.0	1271.0
		Type5	2	0	409565.0	9	2	73.8	1806.0	1538.0	---
		Type5	2	2	938562.0	9	1	51.9	1651.0	---	---
		Type5	2	4	376726.0	9	3	95.4	1060.0	1903.0	1388.0
		Type5	2	5	641212.0	9	2	68.0	1368.0	1351.0	---
		Type5	2	7	80863.0	9	2	81.9	1022.0	1689.0	---
		Type5	2	8	344067.0	9	3	88.3	1810.0	1330.0	1838.0
		Type5	2	9	609331.0	9	1	53.7	1597.0	---	---
		Type5	2	10	871542.0	9	3	91.3	1961.0	1106.0	1001.0
		Type5	2	6	903714.0	9	3	89.6	1338.0	1514.0	1573.0
	5570	Type5	2	1	673692.0	9	2	69.5	1117.0	1649.0	---
		Type5	2	1	673692.0	9	2	69.5	1117.0	1649.0	---
		Type5	2	9	609331.0	9	1	53.7	1597.0	---	---
		Type5	2	8	344067.0	9	3	88.3	1810.0	1330.0	1838.0
		Type5	2	7	80863.0	9	2	81.9	1022.0	1689.0	---
		Type5	2	6	903714.0	9	3	89.6	1338.0	1514.0	1573.0
		Type5	2	5	641212.0	9	2	68.0	1368.0	1351.0	---
		Type5	2	4	376726.0	9	3	95.4	1060.0	1903.0	1388.0
		Type5	2	2	938562.0	9	1	51.9	1651.0	---	---
		Type5	2	0	409565.0	9	2	73.8	1806.0	1538.0	---
		Type5	2	10	871542.0	9	3	91.3	1961.0	1106.0	1001.0
		Type5	2	3	113209.0	9	3	84.6	1976.0	1032.0	1271.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	3	13	117439.0	19	3	95.3	1171.0	1955.0	1775.0
		Type5	3	0	26541.0	19	2	68.1	1339.0	1355.0	---
		Type5	3	18	244095.0	19	3	91.6	1878.0	1445.0	1325.0
		Type5	3	17	99799.0	19	3	85.4	1011.0	1637.0	1425.0
		Type5	3	16	553328.0	19	1	65.0	1767.0	---	---
		Type5	3	14	262502.0	19	2	81.9	1690.0	1545.0	---
		Type5	3	19	390012.0	19	2	67.3	1091.0	1218.0	---
		Type5	3	12	570132.0	19	2	70.4	1526.0	1360.0	---
		Type5	3	11	424279.0	19	3	93.2	1207.0	1907.0	1223.0
		Type5	3	10	279928.0	19	3	88.0	1061.0	1928.0	1101.0
		Type5	3	2	316229.0	19	2	75.3	1136.0	1640.0	---
		Type5	3	15	406573.0	19	3	98.5	1975.0	1169.0	1062.0
		Type5	3	1	171821.0	19	1	58.7	1251.0	---	---
		Type5	3	9	135674.0	19	2	82.8	1883.0	1005.0	---
		Type5	3	3	461864.0	19	1	56.4	1753.0	---	---
		Type5	3	4	8677.0	19	3	99.7	1196.0	1708.0	1159.0
		Type5	3	5	153995.0	19	1	57.7	1013.0	---	---
		Type5	3	6	299238.0	19	1	59.5	1072.0	---	---
		Type5	3	7	443177.0	19	2	80.0	1482.0	1369.0	---
		Type5	3	8	587671.0	19	2	82.0	1993.0	1197.0	---
	5500	Type5	3	9	135674.0	19	2	82.8	1883.0	1005.0	---
		Type5	3	16	553328.0	19	1	65.0	1767.0	---	---
		Type5	3	15	406573.0	19	3	98.5	1975.0	1169.0	1062.0
		Type5	3	14	262502.0	19	2	81.9	1690.0	1545.0	---
		Type5	3	13	117439.0	19	3	95.3	1171.0	1955.0	1775.0
		Type5	3	12	570132.0	19	2	70.4	1526.0	1360.0	---
		Type5	3	11	424279.0	19	3	93.2	1207.0	1907.0	1223.0
		Type5	3	10	279928.0	19	3	88.0	1061.0	1928.0	1101.0
		Type5	3	17	99799.0	19	3	85.4	1011.0	1637.0	1425.0
		Type5	3	8	587671.0	19	2	82.0	1993.0	1197.0	---
		Type5	3	7	443177.0	19	2	80.0	1482.0	1369.0	---
		Type5	3	6	299238.0	19	1	59.5	1072.0	---	---
		Type5	3	5	153995.0	19	1	57.7	1013.0	---	---
		Type5	3	4	8677.0	19	3	99.7	1196.0	1708.0	1159.0
		Type5	3	3	461864.0	19	1	56.4	1753.0	---	---
		Type5	3	2	316229.0	19	2	75.3	1136.0	1640.0	---
		Type5	3	18	244095.0	19	3	91.6	1878.0	1445.0	1325.0
		Type5	3	0	26541.0	19	2	68.1	1339.0	1355.0	---
		Type5	3	19	390012.0	19	2	67.3	1091.0	1218.0	---
		Type5	3	1	171821.0	19	1	58.7	1251.0	---	---
11AX40MIMO	5270	Type5	3	8	587671.0	19	2	82.0	1993.0	1197.0	---
		Type5	3	17	99799.0	19	3	85.4	1011.0	1637.0	1425.0
		Type5	3	16	553328.0	19	1	65.0	1767.0	---	---
		Type5	3	15	406573.0	19	3	98.5	1975.0	1169.0	1062.0
		Type5	3	14	262502.0	19	2	81.9	1690.0	1545.0	---
		Type5	3	13	117439.0	19	3	95.3	1171.0	1955.0	1775.0
		Type5	3	12	570132.0	19	2	70.4	1526.0	1360.0	---
		Type5	3	11	424279.0	19	3	93.2	1207.0	1907.0	1223.0
		Type5	3	18	244095.0	19	3	91.6	1878.0	1445.0	1325.0
		Type5	3	9	135674.0	19	2	82.8	1883.0	1005.0	---
		Type5	3	19	390012.0	19	2	67.3	1091.0	1218.0	---
		Type5	3	7	443177.0	19	2	80.0	1482.0	1369.0	---
		Type5	3	6	299238.0	19	1	59.5	1072.0	---	---
		Type5	3	5	153995.0	19	1	57.7	1013.0	---	---

11AX80MIMO		Type5	3	4	8677.0	19	3	99.7	1196.0	1708.0	1159.0
		Type5	3	3	461864.0	19	1	56.4	1753.0	---	---
		Type5	3	2	316229.0	19	2	75.3	1136.0	1640.0	---
		Type5	3	1	171821.0	19	1	58.7	1251.0	---	---
		Type5	3	0	26541.0	19	2	68.1	1339.0	1355.0	---
		Type5	3	10	279928.0	19	3	88.0	1061.0	1928.0	1101.0
	5510	Type5	3	12	570132.0	19	2	70.4	1526.0	1360.0	---
		Type5	3	1	171821.0	19	1	58.7	1251.0	---	---
		Type5	3	2	316229.0	19	2	75.3	1136.0	1640.0	---
		Type5	3	3	461864.0	19	1	56.4	1753.0	---	---
		Type5	3	5	153995.0	19	1	57.7	1013.0	---	---
		Type5	3	7	443177.0	19	2	80.0	1482.0	1369.0	---
		Type5	3	8	587671.0	19	2	82.0	1993.0	1197.0	---
		Type5	3	9	135674.0	19	2	82.8	1883.0	1005.0	---
		Type5	3	0	26541.0	19	2	68.1	1339.0	1355.0	---
		Type5	3	11	424279.0	19	3	93.2	1207.0	1907.0	1223.0
		Type5	3	4	8677.0	19	3	99.7	1196.0	1708.0	1159.0
		Type5	3	13	117439.0	19	3	95.3	1171.0	1955.0	1775.0
		Type5	3	14	262502.0	19	2	81.9	1690.0	1545.0	---
		Type5	3	15	406573.0	19	3	98.5	1975.0	1169.0	1062.0
		Type5	3	16	553328.0	19	1	65.0	1767.0	---	---
		Type5	3	17	99799.0	19	3	85.4	1011.0	1637.0	1425.0
		Type5	3	18	244095.0	19	3	91.6	1878.0	1445.0	1325.0
		Type5	3	19	390012.0	19	2	67.3	1091.0	1218.0	---
		Type5	3	10	279928.0	19	3	88.0	1061.0	1928.0	1101.0
		Type5	3	6	299238.0	19	1	59.5	1072.0	---	---
	5290	Type5	3	12	570132.0	19	2	70.4	1526.0	1360.0	---
		Type5	3	18	244095.0	19	3	91.6	1878.0	1445.0	1325.0
		Type5	3	0	26541.0	19	2	68.1	1339.0	1355.0	---
		Type5	3	17	99799.0	19	3	85.4	1011.0	1637.0	1425.0
		Type5	3	16	553328.0	19	1	65.0	1767.0	---	---
		Type5	3	15	406573.0	19	3	98.5	1975.0	1169.0	1062.0
		Type5	3	13	117439.0	19	3	95.3	1171.0	1955.0	1775.0
		Type5	3	11	424279.0	19	3	93.2	1207.0	1907.0	1223.0
		Type5	3	10	279928.0	19	3	88.0	1061.0	1928.0	1101.0
		Type5	3	9	135674.0	19	2	82.8	1883.0	1005.0	---
		Type5	3	2	316229.0	19	2	75.3	1136.0	1640.0	---
		Type5	3	7	443177.0	19	2	80.0	1482.0	1369.0	---
		Type5	3	6	299238.0	19	1	59.5	1072.0	---	---
		Type5	3	19	390012.0	19	2	67.3	1091.0	1218.0	---
		Type5	3	5	153995.0	19	1	57.7	1013.0	---	---
		Type5	3	1	171821.0	19	1	58.7	1251.0	---	---
		Type5	3	4	8677.0	19	3	99.7	1196.0	1708.0	1159.0
		Type5	3	3	461864.0	19	1	56.4	1753.0	---	---
		Type5	3	8	587671.0	19	2	82.0	1993.0	1197.0	---
		Type5	3	14	262502.0	19	2	81.9	1690.0	1545.0	---
	5530	Type5	3	9	135674.0	19	2	82.8	1883.0	1005.0	---
		Type5	3	11	424279.0	19	3	93.2	1207.0	1907.0	1223.0
		Type5	3	12	570132.0	19	2	70.4	1526.0	1360.0	---
		Type5	3	13	117439.0	19	3	95.3	1171.0	1955.0	1775.0
		Type5	3	14	262502.0	19	2	81.9	1690.0	1545.0	---
		Type5	3	15	406573.0	19	3	98.5	1975.0	1169.0	1062.0
		Type5	3	17	99799.0	19	3	85.4	1011.0	1637.0	1425.0
		Type5	3	8	587671.0	19	2	82.0	1993.0	1197.0	---
		Type5	3	18	244095.0	19	3	91.6	1878.0	1445.0	1325.0
		Type5	3	16	553328.0	19	1	65.0	1767.0	---	---
		Type5	3	19	390012.0	19	2	67.3	1091.0	1218.0	---
		Type5	3	6	299238.0	19	1	59.5	1072.0	---	---

		Type5	3	5	153995.0	19	1	57.7	1013.0	---	---
		Type5	3	4	8677.0	19	3	99.7	1196.0	1708.0	1159.0
11AX160MIMO		Type5	3	3	461864.0	19	1	56.4	1753.0	---	---
		Type5	3	2	316229.0	19	2	75.3	1136.0	1640.0	---
		Type5	3	1	171821.0	19	1	58.7	1251.0	---	---
		Type5	3	0	26541.0	19	2	68.1	1339.0	1355.0	---
		Type5	3	7	443177.0	19	2	80.0	1482.0	1369.0	---
		Type5	3	10	279928.0	19	3	88.0	1061.0	1928.0	1101.0
		Type5	3	8	587671.0	19	2	82.0	1993.0	1197.0	---
		Type5	3	7	443177.0	19	2	80.0	1482.0	1369.0	---
	5250	Type5	3	6	299238.0	19	1	59.5	1072.0	---	---
		Type5	3	4	8677.0	19	3	99.7	1196.0	1708.0	1159.0
		Type5	3	2	316229.0	19	2	75.3	1136.0	1640.0	---
		Type5	3	9	135674.0	19	2	82.8	1883.0	1005.0	---
		Type5	3	0	26541.0	19	2	68.1	1339.0	1355.0	---
		Type5	3	5	153995.0	19	1	57.7	1013.0	---	---
		Type5	3	1	171821.0	19	1	58.7	1251.0	---	---
		Type5	3	19	390012.0	19	2	67.3	1091.0	1218.0	---
		Type5	3	11	424279.0	19	3	93.2	1207.0	1907.0	1223.0
		Type5	3	12	570132.0	19	2	70.4	1526.0	1360.0	---
		Type5	3	13	117439.0	19	3	95.3	1171.0	1955.0	1775.0
		Type5	3	14	262502.0	19	2	81.9	1690.0	1545.0	---
		Type5	3	15	406573.0	19	3	98.5	1975.0	1169.0	1062.0
		Type5	3	16	553328.0	19	1	65.0	1767.0	---	---
		Type5	3	17	99799.0	19	3	85.4	1011.0	1637.0	1425.0
		Type5	3	18	244095.0	19	3	91.6	1878.0	1445.0	1325.0
		Type5	3	3	461864.0	19	1	56.4	1753.0	---	---
		Type5	3	10	279928.0	19	3	88.0	1061.0	1928.0	1101.0
	5570	Type5	3	11	424279.0	19	3	93.2	1207.0	1907.0	1223.0
		Type5	3	12	570132.0	19	2	70.4	1526.0	1360.0	---
		Type5	3	13	117439.0	19	3	95.3	1171.0	1955.0	1775.0
		Type5	3	14	262502.0	19	2	81.9	1690.0	1545.0	---
		Type5	3	15	406573.0	19	3	98.5	1975.0	1169.0	1062.0
		Type5	3	16	553328.0	19	1	65.0	1767.0	---	---
		Type5	3	10	279928.0	19	3	88.0	1061.0	1928.0	1101.0
		Type5	3	18	244095.0	19	3	91.6	1878.0	1445.0	1325.0
		Type5	3	3	461864.0	19	1	56.4	1753.0	---	---
		Type5	3	17	99799.0	19	3	85.4	1011.0	1637.0	1425.0
		Type5	3	9	135674.0	19	2	82.8	1883.0	1005.0	---
		Type5	3	8	587671.0	19	2	82.0	1993.0	1197.0	---
		Type5	3	7	443177.0	19	2	80.0	1482.0	1369.0	---
		Type5	3	6	299238.0	19	1	59.5	1072.0	---	---
		Type5	3	4	8677.0	19	3	99.7	1196.0	1708.0	1159.0
		Type5	3	2	316229.0	19	2	75.3	1136.0	1640.0	---
		Type5	3	1	171821.0	19	1	58.7	1251.0	---	---
		Type5	3	0	26541.0	19	2	68.1	1339.0	1355.0	---
		Type5	3	19	390012.0	19	2	67.3	1091.0	1218.0	---
		Type5	3	5	153995.0	19	1	57.7	1013.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	4	11	394825.0	16	3	97.5	1884.0	1465.0	1132.0
		Type5	4	0	629614.0	16	2	67.9	1320.0	1133.0	---
		Type5	4	15	373812.0	16	3	84.7	1021.0	1718.0	1854.0
		Type5	4	14	203957.0	16	3	97.6	1365.0	1073.0	1361.0
		Type5	4	12	565361.0	16	3	90.6	1561.0	1040.0	1354.0
		Type5	4	16	544060.0	16	3	99.7	1150.0	1244.0	1988.0
		Type5	4	10	225175.0	16	2	71.3	1225.0	1815.0	---
		Type5	4	9	54571.0	16	3	87.1	1116.0	1996.0	1756.0
		Type5	4	2	267719.0	16	1	53.3	1592.0	---	---
		Type5	4	13	33643.0	16	3	86.3	1596.0	1183.0	1792.0
		Type5	4	1	96856.0	16	1	62.3	1957.0	---	---
		Type5	4	8	588736.0	16	1	50.3	1075.0	---	---
		Type5	4	3	436784.0	16	3	90.0	1900.0	1153.0	1346.0
		Type5	4	4	608289.0	16	2	77.1	1166.0	1646.0	---
		Type5	4	5	75610.0	16	3	83.9	1278.0	1232.0	1459.0
		Type5	4	6	245638.0	16	3	89.1	1240.0	1384.0	1939.0
	5500	Type5	4	7	416355.0	16	2	81.8	1833.0	1676.0	---
		Type5	4	8	588736.0	16	1	50.3	1075.0	---	---
		Type5	4	13	33643.0	16	3	86.3	1596.0	1183.0	1792.0
		Type5	4	12	565361.0	16	3	90.6	1561.0	1040.0	1354.0
		Type5	4	11	394825.0	16	3	97.5	1884.0	1465.0	1132.0
		Type5	4	10	225175.0	16	2	71.3	1225.0	1815.0	---
		Type5	4	9	54571.0	16	3	87.1	1116.0	1996.0	1756.0
		Type5	4	14	203957.0	16	3	97.6	1365.0	1073.0	1361.0
		Type5	4	7	416355.0	16	2	81.8	1833.0	1676.0	---
		Type5	4	6	245638.0	16	3	89.1	1240.0	1384.0	1939.0
		Type5	4	5	75610.0	16	3	83.9	1278.0	1232.0	1459.0
		Type5	4	4	608289.0	16	2	77.1	1166.0	1646.0	---
		Type5	4	3	436784.0	16	3	90.0	1900.0	1153.0	1346.0
		Type5	4	2	267719.0	16	1	53.3	1592.0	---	---
		Type5	4	15	373812.0	16	3	84.7	1021.0	1718.0	1854.0
		Type5	4	0	629614.0	16	2	67.9	1320.0	1133.0	---
11AX40MIMO	5270	Type5	4	16	544060.0	16	3	99.7	1150.0	1244.0	1988.0
		Type5	4	1	96856.0	16	1	62.3	1957.0	---	---
		Type5	4	6	245638.0	16	3	89.1	1240.0	1384.0	1939.0
		Type5	4	14	203957.0	16	3	97.6	1365.0	1073.0	1361.0
		Type5	4	13	33643.0	16	3	86.3	1596.0	1183.0	1792.0
		Type5	4	12	565361.0	16	3	90.6	1561.0	1040.0	1354.0
		Type5	4	11	394825.0	16	3	97.5	1884.0	1465.0	1132.0
		Type5	4	10	225175.0	16	2	71.3	1225.0	1815.0	---
		Type5	4	9	54571.0	16	3	87.1	1116.0	1996.0	1756.0
		Type5	4	15	373812.0	16	3	84.7	1021.0	1718.0	1854.0
		Type5	4	7	416355.0	16	2	81.8	1833.0	1676.0	---
		Type5	4	16	544060.0	16	3	99.7	1150.0	1244.0	1988.0
		Type5	4	5	75610.0	16	3	83.9	1278.0	1232.0	1459.0
		Type5	4	4	608289.0	16	2	77.1	1166.0	1646.0	---
		Type5	4	3	436784.0	16	3	90.0	1900.0	1153.0	1346.0
		Type5	4	2	267719.0	16	1	53.3	1592.0	---	---
		Type5	4	1	96856.0	16	1	62.3	1957.0	---	---
		Type5	4	0	629614.0	16	2	67.9	1320.0	1133.0	---
		Type5	4	8	588736.0	16	1	50.3	1075.0	---	---
	5510	Type5	4	10	225175.0	16	2	71.3	1225.0	1815.0	---
		Type5	4	1	96856.0	16	1	62.3	1957.0	---	---
		Type5	4	2	267719.0	16	1	53.3	1592.0	---	---
		Type5	4	2	267719.0	16	1	53.3	1592.0	---	---

		Type5	4	4	608289.0	16	2	77.1	1166.0	1646.0	---
		Type5	4	6	245638.0	16	3	89.1	1240.0	1384.0	1939.0
		Type5	4	7	416355.0	16	2	81.8	1833.0	1676.0	---
		Type5	4	0	629614.0	16	2	67.9	1320.0	1133.0	---
		Type5	4	9	54571.0	16	3	87.1	1116.0	1996.0	1756.0
		Type5	4	3	436784.0	16	3	90.0	1900.0	1153.0	1346.0
		Type5	4	11	394825.0	16	3	97.5	1884.0	1465.0	1132.0
		Type5	4	12	565361.0	16	3	90.6	1561.0	1040.0	1354.0
		Type5	4	13	33643.0	16	3	86.3	1596.0	1183.0	1792.0
		Type5	4	14	203957.0	16	3	97.6	1365.0	1073.0	1361.0
		Type5	4	15	373812.0	16	3	84.7	1021.0	1718.0	1854.0
		Type5	4	16	544060.0	16	3	99.7	1150.0	1244.0	1988.0
		Type5	4	8	588736.0	16	1	50.3	1075.0	---	---
		Type5	4	5	75610.0	16	3	83.9	1278.0	1232.0	1459.0
11AX80MIMO	5290	Type5	4	10	225175.0	16	2	71.3	1225.0	1815.0	---
		Type5	4	15	373812.0	16	3	84.7	1021.0	1718.0	1854.0
		Type5	4	0	629614.0	16	2	67.9	1320.0	1133.0	---
		Type5	4	14	203957.0	16	3	97.6	1365.0	1073.0	1361.0
		Type5	4	13	33643.0	16	3	86.3	1596.0	1183.0	1792.0
		Type5	4	11	394825.0	16	3	97.5	1884.0	1465.0	1132.0
		Type5	4	9	54571.0	16	3	87.1	1116.0	1996.0	1756.0
		Type5	4	8	588736.0	16	1	50.3	1075.0	---	---
		Type5	4	3	436784.0	16	3	90.0	1900.0	1153.0	1346.0
		Type5	4	6	245638.0	16	3	89.1	1240.0	1384.0	1939.0
		Type5	4	5	75610.0	16	3	83.9	1278.0	1232.0	1459.0
		Type5	4	1	96856.0	16	1	62.3	1957.0	---	---
		Type5	4	16	544060.0	16	3	99.7	1150.0	1244.0	1988.0
		Type5	4	4	608289.0	16	2	77.1	1166.0	1646.0	---
		Type5	4	7	416355.0	16	2	81.8	1833.0	1676.0	---
		Type5	4	12	565361.0	16	3	90.6	1561.0	1040.0	1354.0
		Type5	4	2	267719.0	16	1	53.3	1592.0	---	---
	5530	Type5	4	9	54571.0	16	3	87.1	1116.0	1996.0	1756.0
		Type5	4	10	225175.0	16	2	71.3	1225.0	1815.0	---
		Type5	4	11	394825.0	16	3	97.5	1884.0	1465.0	1132.0
		Type5	4	12	565361.0	16	3	90.6	1561.0	1040.0	1354.0
		Type5	4	14	203957.0	16	3	97.6	1365.0	1073.0	1361.0
		Type5	4	6	245638.0	16	3	89.1	1240.0	1384.0	1939.0
		Type5	4	15	373812.0	16	3	84.7	1021.0	1718.0	1854.0
		Type5	4	13	33643.0	16	3	86.3	1596.0	1183.0	1792.0
		Type5	4	16	544060.0	16	3	99.7	1150.0	1244.0	1988.0
		Type5	4	5	75610.0	16	3	83.9	1278.0	1232.0	1459.0
		Type5	4	4	608289.0	16	2	77.1	1166.0	1646.0	---
		Type5	4	3	436784.0	16	3	90.0	1900.0	1153.0	1346.0
		Type5	4	2	267719.0	16	1	53.3	1592.0	---	---
		Type5	4	1	96856.0	16	1	62.3	1957.0	---	---
		Type5	4	0	629614.0	16	2	67.9	1320.0	1133.0	---
		Type5	4	7	416355.0	16	2	81.8	1833.0	1676.0	---
		Type5	4	8	588736.0	16	1	50.3	1075.0	---	---
11AX160MIMO	5250	Type5	4	7	416355.0	16	2	81.8	1833.0	1676.0	---
		Type5	4	6	245638.0	16	3	89.1	1240.0	1384.0	1939.0
		Type5	4	4	608289.0	16	2	77.1	1166.0	1646.0	---
		Type5	4	2	267719.0	16	1	53.3	1592.0	---	---
		Type5	4	8	588736.0	16	1	50.3	1075.0	---	---
		Type5	4	0	629614.0	16	2	67.9	1320.0	1133.0	---
		Type5	4	5	75610.0	16	3	83.9	1278.0	1232.0	1459.0
		Type5	4	1	96856.0	16	1	62.3	1957.0	---	---
		Type5	4	16	544060.0	16	3	99.7	1150.0	1244.0	1988.0
		Type5	4	10	225175.0	16	2	71.3	1225.0	1815.0	---

		Type5	4	11	394825.0	16	3	97.5	1884.0	1465.0	1132.0
		Type5	4	12	565361.0	16	3	90.6	1561.0	1040.0	1354.0
		Type5	4	13	33643.0	16	3	86.3	1596.0	1183.0	1792.0
		Type5	4	14	203957.0	16	3	97.6	1365.0	1073.0	1361.0
		Type5	4	15	373812.0	16	3	84.7	1021.0	1718.0	1854.0
		Type5	4	3	436784.0	16	3	90.0	1900.0	1153.0	1346.0
	5570	Type5	4	9	54571.0	16	3	87.1	1116.0	1996.0	1756.0
		Type5	4	10	225175.0	16	2	71.3	1225.0	1815.0	---
		Type5	4	11	394825.0	16	3	97.5	1884.0	1465.0	1132.0
		Type5	4	12	565361.0	16	3	90.6	1561.0	1040.0	1354.0
		Type5	4	13	33643.0	16	3	86.3	1596.0	1183.0	1792.0
		Type5	4	9	54571.0	16	3	87.1	1116.0	1996.0	1756.0
		Type5	4	15	373812.0	16	3	84.7	1021.0	1718.0	1854.0
		Type5	4	3	436784.0	16	3	90.0	1900.0	1153.0	1346.0
		Type5	4	14	203957.0	16	3	97.6	1365.0	1073.0	1361.0
		Type5	4	8	588736.0	16	1	50.3	1075.0	---	---
		Type5	4	7	416355.0	16	2	81.8	1833.0	1676.0	---
		Type5	4	6	245638.0	16	3	89.1	1240.0	1384.0	1939.0
		Type5	4	4	608289.0	16	2	77.1	1166.0	1646.0	---
		Type5	4	2	267719.0	16	1	53.3	1592.0	---	---
		Type5	4	1	96856.0	16	1	62.3	1957.0	---	---
		Type5	4	0	629614.0	16	2	67.9	1320.0	1133.0	---
		Type5	4	16	544060.0	16	3	99.7	1150.0	1244.0	1988.0
		Type5	4	5	75610.0	16	3	83.9	1278.0	1232.0	1459.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	5	9	171459.0	12	2	81.5	1891.0	1714.0	---
		Type5	5	0	15438.0	12	3	92.9	1085.0	1564.0	1407.0
		Type5	5	12	792834.0	12	2	69.6	1307.0	1925.0	---
		Type5	5	10	377969.0	12	3	89.4	1310.0	1594.0	1827.0
		Type5	5	13	146044.0	12	2	74.5	1264.0	1846.0	---
		Type5	5	8	818057.0	12	2	76.3	1606.0	1926.0	---
		Type5	5	7	610711.0	12	3	85.9	1134.0	1034.0	1808.0
		Type5	5	6	404955.0	12	1	65.8	1519.0	---	---
		Type5	5	5	196720.0	12	3	83.5	1679.0	1930.0	1025.0
		Type5	5	4	845342.0	12	1	53.7	1727.0	---	---
		Type5	5	3	637784.0	12	1	56.3	1851.0	---	---
		Type5	5	2	430731.0	12	1	65.8	1092.0	---	---
		Type5	5	1	222486.0	12	2	67.7	1744.0	1747.0	---
		Type5	5	11	586875.0	12	1	63.4	1568.0	---	---
	5500	Type5	5	6	404955.0	12	1	65.8	1519.0	---	---
		Type5	5	11	586875.0	12	1	63.4	1568.0	---	---
		Type5	5	10	377969.0	12	3	89.4	1310.0	1594.0	1827.0
		Type5	5	9	171459.0	12	2	81.5	1891.0	1714.0	---
		Type5	5	8	818057.0	12	2	76.3	1606.0	1926.0	---
		Type5	5	7	610711.0	12	3	85.9	1134.0	1034.0	1808.0
		Type5	5	5	196720.0	12	3	83.5	1679.0	1930.0	1025.0
		Type5	5	4	845342.0	12	1	53.7	1727.0	---	---
		Type5	5	3	637784.0	12	1	56.3	1851.0	---	---
		Type5	5	2	430731.0	12	1	65.8	1092.0	---	---
		Type5	5	12	792834.0	12	2	69.6	1307.0	1925.0	---
		Type5	5	0	15438.0	12	3	92.9	1085.0	1564.0	1407.0
11AX40MIMO	5270	Type5	5	13	146044.0	12	2	74.5	1264.0	1846.0	---
		Type5	5	0	15438.0	12	3	92.9	1085.0	1564.0	1407.0
		Type5	5	1	222486.0	12	2	67.7	1744.0	1747.0	---
		Type5	5	2	430731.0	12	1	65.8	1092.0	---	---
		Type5	5	3	637784.0	12	1	56.3	1851.0	---	---
		Type5	5	4	845342.0	12	1	53.7	1727.0	---	---
		Type5	5	5	196720.0	12	3	83.5	1679.0	1930.0	1025.0
		Type5	5	6	404955.0	12	1	65.8	1519.0	---	---
		Type5	5	7	610711.0	12	3	85.9	1134.0	1034.0	1808.0
		Type5	5	8	818057.0	12	2	76.3	1606.0	1926.0	---
		Type5	5	9	171459.0	12	2	81.5	1891.0	1714.0	---
		Type5	5	10	377969.0	12	3	89.4	1310.0	1594.0	1827.0
	5510	Type5	5	11	586875.0	12	1	63.4	1568.0	---	---
		Type5	5	12	792834.0	12	2	69.6	1307.0	1925.0	---
		Type5	5	2	430731.0	12	1	65.8	1092.0	---	---
		Type5	5	13	146044.0	12	2	74.5	1264.0	1846.0	---
		Type5	5	12	792834.0	12	2	69.6	1307.0	1925.0	---
		Type5	5	11	586875.0	12	1	63.4	1568.0	---	---
		Type5	5	10	377969.0	12	3	89.4	1310.0	1594.0	1827.0
		Type5	5	9	171459.0	12	2	81.5	1891.0	1714.0	---
		Type5	5	8	818057.0	12	2	76.3	1606.0	1926.0	---
		Type5	5	7	610711.0	12	3	85.9	1134.0	1034.0	1808.0
		Type5	5	6	404955.0	12	1	65.8	1519.0	---	---
		Type5	5	5	196720.0	12	3	83.5	1679.0	1930.0	1025.0
		Type5	5	3	637784.0	12	1	56.3	1851.0	---	---
		Type5	5	1	222486.0	12	2	67.7	1744.0	1747.0	---

11AX80MIMO	5290	Type5	5	0	15438.0	12	3	92.9	1085.0	1564.0	1407.0
		Type5	5	4	845342.0	12	1	53.7	1727.0	---	---
		Type5	5	8	818057.0	12	2	76.3	1606.0	1926.0	---
		Type5	5	12	792834.0	12	2	69.6	1307.0	1925.0	---
		Type5	5	0	15438.0	12	3	92.9	1085.0	1564.0	1407.0
		Type5	5	11	586875.0	12	1	63.4	1568.0	---	---
		Type5	5	9	171459.0	12	2	81.5	1891.0	1714.0	---
		Type5	5	7	610711.0	12	3	85.9	1134.0	1034.0	1808.0
		Type5	5	6	404955.0	12	1	65.8	1519.0	---	---
		Type5	5	5	196720.0	12	3	83.5	1679.0	1930.0	1025.0
		Type5	5	4	845342.0	12	1	53.7	1727.0	---	---
		Type5	5	13	146044.0	12	2	74.5	1264.0	1846.0	---
		Type5	5	3	637784.0	12	1	56.3	1851.0	---	---
		Type5	5	2	430731.0	12	1	65.8	1092.0	---	---
		Type5	5	1	222486.0	12	2	67.7	1744.0	1747.0	---
	5530	Type5	5	10	377969.0	12	3	89.4	1310.0	1594.0	1827.0
		Type5	5	12	792834.0	12	2	69.6	1307.0	1925.0	---
		Type5	5	5	196720.0	12	3	83.5	1679.0	1930.0	1025.0
		Type5	5	11	586875.0	12	1	63.4	1568.0	---	---
		Type5	5	10	377969.0	12	3	89.4	1310.0	1594.0	1827.0
		Type5	5	9	171459.0	12	2	81.5	1891.0	1714.0	---
		Type5	5	8	818057.0	12	2	76.3	1606.0	1926.0	---
		Type5	5	6	404955.0	12	1	65.8	1519.0	---	---
		Type5	5	3	637784.0	12	1	56.3	1851.0	---	---
		Type5	5	2	430731.0	12	1	65.8	1092.0	---	---
		Type5	5	1	222486.0	12	2	67.7	1744.0	1747.0	---
		Type5	5	0	15438.0	12	3	92.9	1085.0	1564.0	1407.0
		Type5	5	13	146044.0	12	2	74.5	1264.0	1846.0	---
		Type5	5	7	610711.0	12	3	85.9	1134.0	1034.0	1808.0
		Type5	5	4	845342.0	12	1	53.7	1727.0	---	---
11AX160MIMO	5250	Type5	5	4	845342.0	12	1	53.7	1727.0	---	---
		Type5	5	0	15438.0	12	3	92.9	1085.0	1564.0	1407.0
		Type5	5	1	222486.0	12	2	67.7	1744.0	1747.0	---
		Type5	5	3	637784.0	12	1	56.3	1851.0	---	---
		Type5	5	5	196720.0	12	3	83.5	1679.0	1930.0	1025.0
		Type5	5	6	404955.0	12	1	65.8	1519.0	---	---
		Type5	5	8	818057.0	12	2	76.3	1606.0	1926.0	---
		Type5	5	9	171459.0	12	2	81.5	1891.0	1714.0	---
		Type5	5	10	377969.0	12	3	89.4	1310.0	1594.0	1827.0
		Type5	5	11	586875.0	12	1	63.4	1568.0	---	---
		Type5	5	12	792834.0	12	2	69.6	1307.0	1925.0	---
		Type5	5	13	146044.0	12	2	74.5	1264.0	1846.0	---
		Type5	5	7	610711.0	12	3	85.9	1134.0	1034.0	1808.0
		Type5	5	2	430731.0	12	1	65.8	1092.0	---	---
	5570	Type5	5	2	430731.0	12	1	65.8	1092.0	---	---
		Type5	5	12	792834.0	12	2	69.6	1307.0	1925.0	---
		Type5	5	11	586875.0	12	1	63.4	1568.0	---	---
		Type5	5	10	377969.0	12	3	89.4	1310.0	1594.0	1827.0
		Type5	5	9	171459.0	12	2	81.5	1891.0	1714.0	---
		Type5	5	8	818057.0	12	2	76.3	1606.0	1926.0	---
		Type5	5	7	610711.0	12	3	85.9	1134.0	1034.0	1808.0
		Type5	5	6	404955.0	12	1	65.8	1519.0	---	---
		Type5	5	5	196720.0	12	3	83.5	1679.0	1930.0	1025.0
		Type5	5	3	637784.0	12	1	56.3	1851.0	---	---
		Type5	5	1	222486.0	12	2	67.7	1744.0	1747.0	---
		Type5	5	0	15438.0	12	3	92.9	1085.0	1564.0	1407.0
		Type5	5	13	146044.0	12	2	74.5	1264.0	1846.0	---
		Type5	5	4	845342.0	12	1	53.7	1727.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	6	9	475842.0	13	2	68.6	1008.0	1028.0	---
		Type5	6	0	329022.0	13	3	96.6	1182.0	1609.0	1581.0
		Type5	6	13	452335.0	13	1	61.4	1451.0	---	---
		Type5	6	12	257755.0	13	3	94.9	1830.0	1070.0	1349.0
		Type5	6	10	667887.0	13	2	77.7	1972.0	1835.0	---
		Type5	6	14	643395.0	13	3	90.6	1233.0	1562.0	1887.0
		Type5	6	8	282508.0	13	1	65.7	1476.0	---	---
		Type5	6	7	88645.0	13	2	79.4	1344.0	1893.0	---
		Type5	6	6	690932.0	13	3	85.3	1336.0	1504.0	1820.0
		Type5	6	5	500239.0	13	1	55.4	1145.0	---	---
		Type5	6	4	306283.0	13	1	55.8	1688.0	---	---
		Type5	6	3	112450.0	13	2	73.3	1908.0	1318.0	---
	5500	Type5	6	2	714222.0	13	3	86.5	1923.0	1396.0	1865.0
		Type5	6	1	521718.0	13	3	96.7	1829.0	1799.0	1154.0
		Type5	6	11	64845.0	13	2	79.6	1882.0	1331.0	---
		Type5	6	7	88645.0	13	2	79.4	1344.0	1893.0	---
		Type5	6	12	257755.0	13	3	94.9	1830.0	1070.0	1349.0
		Type5	6	11	64845.0	13	2	79.6	1882.0	1331.0	---
		Type5	6	10	667887.0	13	2	77.7	1972.0	1835.0	---
		Type5	6	9	475842.0	13	2	68.6	1008.0	1028.0	---
		Type5	6	8	282508.0	13	1	65.7	1476.0	---	---
		Type5	6	6	690932.0	13	3	85.3	1336.0	1504.0	1820.0
		Type5	6	5	500239.0	13	1	55.4	1145.0	---	---
		Type5	6	4	306283.0	13	1	55.8	1688.0	---	---
11AX40MIMO	5270	Type5	6	3	112450.0	13	2	73.3	1908.0	1318.0	---
		Type5	6	2	714222.0	13	3	86.5	1923.0	1396.0	1865.0
		Type5	6	4	306283.0	13	1	55.8	1688.0	---	---
		Type5	6	5	500239.0	13	1	55.4	1145.0	---	---
		Type5	6	6	690932.0	13	3	85.3	1336.0	1504.0	1820.0
		Type5	6	7	88645.0	13	2	79.4	1344.0	1893.0	---
		Type5	6	8	282508.0	13	1	65.7	1476.0	---	---
		Type5	6	9	475842.0	13	2	68.6	1008.0	1028.0	---
		Type5	6	10	667887.0	13	2	77.7	1972.0	1835.0	---
		Type5	6	11	64845.0	13	2	79.6	1882.0	1331.0	---
		Type5	6	12	257755.0	13	3	94.9	1830.0	1070.0	1349.0
		Type5	6	13	452335.0	13	1	61.4	1451.0	---	---
	5510	Type5	6	2	714222.0	13	3	86.5	1923.0	1396.0	1865.0
		Type5	6	14	643395.0	13	3	90.6	1233.0	1562.0	1887.0
		Type5	6	13	452335.0	13	1	61.4	1451.0	---	---
		Type5	6	12	257755.0	13	3	94.9	1830.0	1070.0	1349.0
		Type5	6	11	64845.0	13	2	79.6	1882.0	1331.0	---
		Type5	6	10	667887.0	13	2	77.7	1972.0	1835.0	---
		Type5	6	9	475842.0	13	2	68.6	1008.0	1028.0	---
		Type5	6	8	282508.0	13	1	65.7	1476.0	---	---
		Type5	6	7	88645.0	13	2	79.4	1344.0	1893.0	---

		Type5	6	6	690932.0	13	3	85.3	1336.0	1504.0	1820.0
		Type5	6	5	500239.0	13	1	55.4	1145.0	---	---
		Type5	6	3	112450.0	13	2	73.3	1908.0	1318.0	---
		Type5	6	1	521718.0	13	3	96.7	1829.0	1799.0	1154.0
		Type5	6	0	329022.0	13	3	96.6	1182.0	1609.0	1581.0
		Type5	6	4	306283.0	13	1	55.8	1688.0	---	---
11AX80MIMO	5290	Type5	6	8	282508.0	13	1	65.7	1476.0	---	---
		Type5	6	13	452335.0	13	1	61.4	1451.0	---	---
		Type5	6	0	329022.0	13	3	96.6	1182.0	1609.0	1581.0
		Type5	6	12	257755.0	13	3	94.9	1830.0	1070.0	1349.0
		Type5	6	11	64845.0	13	2	79.6	1882.0	1331.0	---
		Type5	6	9	475842.0	13	2	68.6	1008.0	1028.0	---
		Type5	6	7	88645.0	13	2	79.4	1344.0	1893.0	---
		Type5	6	6	690932.0	13	3	85.3	1336.0	1504.0	1820.0
		Type5	6	5	500239.0	13	1	55.4	1145.0	---	---
		Type5	6	4	306283.0	13	1	55.8	1688.0	---	---
		Type5	6	14	643395.0	13	3	90.6	1233.0	1562.0	1887.0
		Type5	6	3	112450.0	13	2	73.3	1908.0	1318.0	---
		Type5	6	2	714222.0	13	3	86.5	1923.0	1396.0	1865.0
		Type5	6	1	521718.0	13	3	96.7	1829.0	1799.0	1154.0
		Type5	6	10	667887.0	13	2	77.7	1972.0	1835.0	---
	5530	Type5	6	13	452335.0	13	1	61.4	1451.0	---	---
		Type5	6	5	500239.0	13	1	55.4	1145.0	---	---
		Type5	6	12	257755.0	13	3	94.9	1830.0	1070.0	1349.0
		Type5	6	11	64845.0	13	2	79.6	1882.0	1331.0	---
		Type5	6	10	667887.0	13	2	77.7	1972.0	1835.0	---
		Type5	6	9	475842.0	13	2	68.6	1008.0	1028.0	---
		Type5	6	8	282508.0	13	1	65.7	1476.0	---	---
		Type5	6	4	306283.0	13	1	55.8	1688.0	---	---
		Type5	6	3	112450.0	13	2	73.3	1908.0	1318.0	---
		Type5	6	2	714222.0	13	3	86.5	1923.0	1396.0	1865.0
		Type5	6	1	521718.0	13	3	96.7	1829.0	1799.0	1154.0
		Type5	6	0	329022.0	13	3	96.6	1182.0	1609.0	1581.0
		Type5	6	14	643395.0	13	3	90.6	1233.0	1562.0	1887.0
		Type5	6	7	88645.0	13	2	79.4	1344.0	1893.0	---
		Type5	6	6	690932.0	13	3	85.3	1336.0	1504.0	1820.0
11AX160MIMO	5250	Type5	6	4	306283.0	13	1	55.8	1688.0	---	---
		Type5	6	0	329022.0	13	3	96.6	1182.0	1609.0	1581.0
		Type5	6	1	521718.0	13	3	96.7	1829.0	1799.0	1154.0
		Type5	6	3	112450.0	13	2	73.3	1908.0	1318.0	---
		Type5	6	5	500239.0	13	1	55.4	1145.0	---	---
		Type5	6	6	690932.0	13	3	85.3	1336.0	1504.0	1820.0
		Type5	6	7	88645.0	13	2	79.4	1344.0	1893.0	---
		Type5	6	9	475842.0	13	2	68.6	1008.0	1028.0	---
		Type5	6	10	667887.0	13	2	77.7	1972.0	1835.0	---
		Type5	6	11	64845.0	13	2	79.6	1882.0	1331.0	---
		Type5	6	12	257755.0	13	3	94.9	1830.0	1070.0	1349.0
		Type5	6	13	452335.0	13	1	61.4	1451.0	---	---
		Type5	6	14	643395.0	13	3	90.6	1233.0	1562.0	1887.0
		Type5	6	8	282508.0	13	1	65.7	1476.0	---	---
		Type5	6	2	714222.0	13	3	86.5	1923.0	1396.0	1865.0
	5570	Type5	6	2	714222.0	13	3	86.5	1923.0	1396.0	1865.0
		Type5	6	13	452335.0	13	1	61.4	1451.0	---	---
		Type5	6	12	257755.0	13	3	94.9	1830.0	1070.0	1349.0
		Type5	6	11	64845.0	13	2	79.6	1882.0	1331.0	---
		Type5	6	10	667887.0	13	2	77.7	1972.0	1835.0	---
		Type5	6	9	475842.0	13	2	68.6	1008.0	1028.0	---
		Type5	6	8	282508.0	13	1	65.7	1476.0	---	---
		Type5	6	8	282508.0	13	1	65.7	1476.0	---	---

	Type5	6	7	88645.0	13	2	79.4	1344.0	1893.0	---
	Type5	6	6	690932.0	13	3	85.3	1336.0	1504.0	1820.0
	Type5	6	5	500239.0	13	1	55.4	1145.0	---	---
	Type5	6	3	112450.0	13	2	73.3	1908.0	1318.0	---
	Type5	6	1	521718.0	13	3	96.7	1829.0	1799.0	1154.0
	Type5	6	0	329022.0	13	3	96.6	1182.0	1609.0	1581.0
	Type5	6	14	643395.0	13	3	90.6	1233.0	1562.0	1887.0
	Type5	6	4	306283.0	13	1	55.8	1688.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	7	7	747058.0	10	2	75.7	1026.0	1871.0	---
		Type5	7	0	51446.0	10	1	52.6	1210.0	---	---
		Type5	7	10	475207.0	10	2	78.8	1784.0	1604.0	---
		Type5	7	8	989976.0	10	1	60.9	1798.0	---	---
		Type5	7	11	715825.0	10	3	87.5	1511.0	1712.0	1683.0
		Type5	7	6	505581.0	10	2	67.6	1175.0	1027.0	---
		Type5	7	5	263385.0	10	2	72.2	1771.0	1184.0	---
		Type5	7	4	21542.0	10	3	98.8	1544.0	1386.0	1302.0
		Type5	7	3	775564.0	10	3	97.3	1341.0	1446.0	1755.0
		Type5	7	2	533989.0	10	3	97.7	1139.0	1868.0	1805.0
	5500	Type5	7	1	292696.0	10	3	84.1	1314.0	1725.0	1529.0
		Type5	7	9	234024.0	10	1	64.2	1138.0	---	---
		Type5	7	5	263385.0	10	2	72.2	1771.0	1184.0	---
		Type5	7	9	234024.0	10	1	64.2	1138.0	---	---
		Type5	7	8	989976.0	10	1	60.9	1798.0	---	---
		Type5	7	7	747058.0	10	2	75.7	1026.0	1871.0	---
		Type5	7	6	505581.0	10	2	67.6	1175.0	1027.0	---
		Type5	7	4	21542.0	10	3	98.8	1544.0	1386.0	1302.0
		Type5	7	3	775564.0	10	3	97.3	1341.0	1446.0	1755.0
		Type5	7	2	533989.0	10	3	97.7	1139.0	1868.0	1805.0
11AX40MIMO	5270	Type5	7	10	475207.0	10	2	78.8	1784.0	1604.0	---
		Type5	7	0	51446.0	10	1	52.6	1210.0	---	---
		Type5	7	11	715825.0	10	3	87.5	1511.0	1712.0	1683.0
		Type5	7	1	292696.0	10	3	84.1	1314.0	1725.0	1529.0
		Type5	7	11	715825.0	10	3	87.5	1511.0	1712.0	1683.0
		Type5	7	0	51446.0	10	1	52.6	1210.0	---	---
		Type5	7	1	292696.0	10	3	84.1	1314.0	1725.0	1529.0
		Type5	7	2	533989.0	10	3	97.7	1139.0	1868.0	1805.0
		Type5	7	3	775564.0	10	3	97.3	1341.0	1446.0	1755.0
		Type5	7	4	21542.0	10	3	98.8	1544.0	1386.0	1302.0
	5510	Type5	7	5	263385.0	10	2	72.2	1771.0	1184.0	---
		Type5	7	6	505581.0	10	2	67.6	1175.0	1027.0	---
		Type5	7	7	747058.0	10	2	75.7	1026.0	1871.0	---
		Type5	7	8	989976.0	10	1	60.9	1798.0	---	---
		Type5	7	9	234024.0	10	1	64.2	1138.0	---	---
		Type5	7	10	475207.0	10	2	78.8	1784.0	1604.0	---
		Type5	7	2	533989.0	10	3	97.7	1139.0	1868.0	1805.0
		Type5	7	11	715825.0	10	3	87.5	1511.0	1712.0	1683.0
		Type5	7	10	475207.0	10	2	78.8	1784.0	1604.0	---
		Type5	7	9	234024.0	10	1	64.2	1138.0	---	---
11AX80MIMO	5290	Type5	7	8	989976.0	10	1	60.9	1798.0	---	---
		Type5	7	7	747058.0	10	2	75.7	1026.0	1871.0	---
		Type5	7	6	505581.0	10	2	67.6	1175.0	1027.0	---
		Type5	7	5	263385.0	10	2	72.2	1771.0	1184.0	---
		Type5	7	3	775564.0	10	3	97.3	1341.0	1446.0	1755.0
		Type5	7	1	292696.0	10	3	84.1	1314.0	1725.0	1529.0
		Type5	7	0	51446.0	10	1	52.6	1210.0	---	---
		Type5	7	4	21542.0	10	3	98.8	1544.0	1386.0	1302.0

		Type5	7	4	21542.0	10	3	98.8	1544.0	1386.0	1302.0
		Type5	7	11	715825.0	10	3	87.5	1511.0	1712.0	1683.0
		Type5	7	3	775564.0	10	3	97.3	1341.0	1446.0	1755.0
		Type5	7	2	533989.0	10	3	97.7	1139.0	1868.0	1805.0
		Type5	7	1	292696.0	10	3	84.1	1314.0	1725.0	1529.0
		Type5	7	8	989976.0	10	1	60.9	1798.0	---	---
	5530	Type5	7	10	475207.0	10	2	78.8	1784.0	1604.0	---
		Type5	7	4	21542.0	10	3	98.8	1544.0	1386.0	1302.0
		Type5	7	9	234024.0	10	1	64.2	1138.0	---	---
		Type5	7	8	989976.0	10	1	60.9	1798.0	---	---
		Type5	7	7	747058.0	10	2	75.7	1026.0	1871.0	---
		Type5	7	5	263385.0	10	2	72.2	1771.0	1184.0	---
		Type5	7	2	533989.0	10	3	97.7	1139.0	1868.0	1805.0
		Type5	7	1	292696.0	10	3	84.1	1314.0	1725.0	1529.0
		Type5	7	0	51446.0	10	1	52.6	1210.0	---	---
		Type5	7	11	715825.0	10	3	87.5	1511.0	1712.0	1683.0
		Type5	7	6	505581.0	10	2	67.6	1175.0	1027.0	---
		Type5	7	3	775564.0	10	3	97.3	1341.0	1446.0	1755.0
11AX160MIMO	5250	Type5	7	3	775564.0	10	3	97.3	1341.0	1446.0	1755.0
		Type5	7	0	51446.0	10	1	52.6	1210.0	---	---
		Type5	7	2	533989.0	10	3	97.7	1139.0	1868.0	1805.0
		Type5	7	4	21542.0	10	3	98.8	1544.0	1386.0	1302.0
		Type5	7	5	263385.0	10	2	72.2	1771.0	1184.0	---
		Type5	7	7	747058.0	10	2	75.7	1026.0	1871.0	---
		Type5	7	8	989976.0	10	1	60.9	1798.0	---	---
		Type5	7	9	234024.0	10	1	64.2	1138.0	---	---
		Type5	7	10	475207.0	10	2	78.8	1784.0	1604.0	---
		Type5	7	11	715825.0	10	3	87.5	1511.0	1712.0	1683.0
		Type5	7	6	505581.0	10	2	67.6	1175.0	1027.0	---
		Type5	7	1	292696.0	10	3	84.1	1314.0	1725.0	1529.0
	5570	Type5	7	1	292696.0	10	3	84.1	1314.0	1725.0	1529.0
		Type5	7	10	475207.0	10	2	78.8	1784.0	1604.0	---
		Type5	7	9	234024.0	10	1	64.2	1138.0	---	---
		Type5	7	8	989976.0	10	1	60.9	1798.0	---	---
		Type5	7	7	747058.0	10	2	75.7	1026.0	1871.0	---
		Type5	7	6	505581.0	10	2	67.6	1175.0	1027.0	---
		Type5	7	5	263385.0	10	2	72.2	1771.0	1184.0	---
		Type5	7	4	21542.0	10	3	98.8	1544.0	1386.0	1302.0
		Type5	7	2	533989.0	10	3	97.7	1139.0	1868.0	1805.0
		Type5	7	0	51446.0	10	1	52.6	1210.0	---	---
		Type5	7	11	715825.0	10	3	87.5	1511.0	1712.0	1683.0
		Type5	7	3	775564.0	10	3	97.3	1341.0	1446.0	1755.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	8	9	123796.0	13	1	54.0	1417.0	---	---
		Type5	8	0	823112.0	13	1	54.1	1415.0	---	---
		Type5	8	12	744805.0	13	2	79.3	1274.0	1992.0	---
		Type5	8	10	331215.0	13	1	63.0	1730.0	---	---
		Type5	8	13	98172.0	13	1	64.3	1937.0	---	---
		Type5	8	8	772314.0	13	1	50.8	1049.0	---	---
		Type5	8	7	563824.0	13	2	74.8	1149.0	1204.0	---
		Type5	8	6	356750.0	13	1	62.5	1778.0	---	---
		Type5	8	5	149042.0	13	2	80.8	1736.0	1505.0	---
		Type5	8	4	796897.0	13	2	68.4	1014.0	1099.0	---
		Type5	8	3	587395.0	13	3	99.8	1558.0	1696.0	1949.0
		Type5	8	2	382216.0	13	1	52.3	1974.0	---	---
		Type5	8	1	174965.0	13	1	50.7	1221.0	---	---
		Type5	8	11	537402.0	13	3	91.8	1143.0	1270.0	1347.0
	5500	Type5	8	6	356750.0	13	1	62.5	1778.0	---	---
		Type5	8	11	537402.0	13	3	91.8	1143.0	1270.0	1347.0
		Type5	8	10	331215.0	13	1	63.0	1730.0	---	---
		Type5	8	9	123796.0	13	1	54.0	1417.0	---	---
		Type5	8	8	772314.0	13	1	50.8	1049.0	---	---
		Type5	8	7	563824.0	13	2	74.8	1149.0	1204.0	---
		Type5	8	5	149042.0	13	2	80.8	1736.0	1505.0	---
		Type5	8	4	796897.0	13	2	68.4	1014.0	1099.0	---
		Type5	8	3	587395.0	13	3	99.8	1558.0	1696.0	1949.0
		Type5	8	2	382216.0	13	1	52.3	1974.0	---	---
		Type5	8	12	744805.0	13	2	79.3	1274.0	1992.0	---
		Type5	8	0	823112.0	13	1	54.1	1415.0	---	---
11AX40MIMO	5270	Type5	8	13	98172.0	13	1	64.3	1937.0	---	---
		Type5	8	13	98172.0	13	1	64.3	1937.0	---	---
		Type5	8	0	823112.0	13	1	54.1	1415.0	---	---
		Type5	8	1	174965.0	13	1	50.7	1221.0	---	---
		Type5	8	2	382216.0	13	1	52.3	1974.0	---	---
		Type5	8	3	587395.0	13	3	99.8	1558.0	1696.0	1949.0
		Type5	8	4	796897.0	13	2	68.4	1014.0	1099.0	---
		Type5	8	5	149042.0	13	2	80.8	1736.0	1505.0	---
		Type5	8	6	356750.0	13	1	62.5	1778.0	---	---
		Type5	8	7	563824.0	13	2	74.8	1149.0	1204.0	---
		Type5	8	8	772314.0	13	1	50.8	1049.0	---	---
		Type5	8	9	123796.0	13	1	54.0	1417.0	---	---
	5510	Type5	8	10	331215.0	13	1	63.0	1730.0	---	---
		Type5	8	11	537402.0	13	3	91.8	1143.0	1270.0	1347.0
		Type5	8	12	744805.0	13	2	79.3	1274.0	1992.0	---
		Type5	8	2	382216.0	13	1	52.3	1974.0	---	---
		Type5	8	13	98172.0	13	1	64.3	1937.0	---	---
		Type5	8	12	744805.0	13	2	79.3	1274.0	1992.0	---
		Type5	8	11	537402.0	13	3	91.8	1143.0	1270.0	1347.0
		Type5	8	10	331215.0	13	1	63.0	1730.0	---	---
		Type5	8	9	123796.0	13	1	54.0	1417.0	---	---
		Type5	8	8	772314.0	13	1	50.8	1049.0	---	---
		Type5	8	7	563824.0	13	2	74.8	1149.0	1204.0	---
		Type5	8	6	356750.0	13	1	62.5	1778.0	---	---
		Type5	8	5	149042.0	13	2	80.8	1736.0	1505.0	---
		Type5	8	3	587395.0	13	3	99.8	1558.0	1696.0	1949.0
		Type5	8	1	174965.0	13	1	50.7	1221.0	---	---

11AX80MIMO	5290	Type5	8	0	823112.0	13	1	54.1	1415.0	---	---
		Type5	8	4	796897.0	13	2	68.4	1014.0	1099.0	---
		Type5	8	8	772314.0	13	1	50.8	1049.0	---	---
		Type5	8	12	744805.0	13	2	79.3	1274.0	1992.0	---
		Type5	8	0	823112.0	13	1	54.1	1415.0	---	---
		Type5	8	11	537402.0	13	3	91.8	1143.0	1270.0	1347.0
		Type5	8	9	123796.0	13	1	54.0	1417.0	---	---
		Type5	8	7	563824.0	13	2	74.8	1149.0	1204.0	---
		Type5	8	6	356750.0	13	1	62.5	1778.0	---	---
		Type5	8	5	149042.0	13	2	80.8	1736.0	1505.0	---
		Type5	8	4	796897.0	13	2	68.4	1014.0	1099.0	---
		Type5	8	13	98172.0	13	1	64.3	1937.0	---	---
		Type5	8	3	587395.0	13	3	99.8	1558.0	1696.0	1949.0
		Type5	8	2	382216.0	13	1	52.3	1974.0	---	---
		Type5	8	1	174965.0	13	1	50.7	1221.0	---	---
	5530	Type5	8	10	331215.0	13	1	63.0	1730.0	---	---
		Type5	8	12	744805.0	13	2	79.3	1274.0	1992.0	---
		Type5	8	5	149042.0	13	2	80.8	1736.0	1505.0	---
		Type5	8	11	537402.0	13	3	91.8	1143.0	1270.0	1347.0
		Type5	8	10	331215.0	13	1	63.0	1730.0	---	---
		Type5	8	9	123796.0	13	1	54.0	1417.0	---	---
		Type5	8	8	772314.0	13	1	50.8	1049.0	---	---
		Type5	8	6	356750.0	13	1	62.5	1778.0	---	---
		Type5	8	3	587395.0	13	3	99.8	1558.0	1696.0	1949.0
		Type5	8	2	382216.0	13	1	52.3	1974.0	---	---
		Type5	8	1	174965.0	13	1	50.7	1221.0	---	---
		Type5	8	0	823112.0	13	1	54.1	1415.0	---	---
		Type5	8	13	98172.0	13	1	64.3	1937.0	---	---
		Type5	8	7	563824.0	13	2	74.8	1149.0	1204.0	---
		Type5	8	4	796897.0	13	2	68.4	1014.0	1099.0	---
11AX160MIMO	5250	Type5	8	4	796897.0	13	2	68.4	1014.0	1099.0	---
		Type5	8	0	823112.0	13	1	54.1	1415.0	---	---
		Type5	8	1	174965.0	13	1	50.7	1221.0	---	---
		Type5	8	3	587395.0	13	3	99.8	1558.0	1696.0	1949.0
		Type5	8	5	149042.0	13	2	80.8	1736.0	1505.0	---
		Type5	8	6	356750.0	13	1	62.5	1778.0	---	---
		Type5	8	8	772314.0	13	1	50.8	1049.0	---	---
		Type5	8	9	123796.0	13	1	54.0	1417.0	---	---
		Type5	8	10	331215.0	13	1	63.0	1730.0	---	---
		Type5	8	11	537402.0	13	3	91.8	1143.0	1270.0	1347.0
		Type5	8	12	744805.0	13	2	79.3	1274.0	1992.0	---
		Type5	8	13	98172.0	13	1	64.3	1937.0	---	---
		Type5	8	7	563824.0	13	2	74.8	1149.0	1204.0	---
		Type5	8	2	382216.0	13	1	52.3	1974.0	---	---
	5570	Type5	8	2	382216.0	13	1	52.3	1974.0	---	---
		Type5	8	12	744805.0	13	2	79.3	1274.0	1992.0	---
		Type5	8	11	537402.0	13	3	91.8	1143.0	1270.0	1347.0
		Type5	8	10	331215.0	13	1	63.0	1730.0	---	---
		Type5	8	9	123796.0	13	1	54.0	1417.0	---	---
		Type5	8	8	772314.0	13	1	50.8	1049.0	---	---
		Type5	8	7	563824.0	13	2	74.8	1149.0	1204.0	---
		Type5	8	6	356750.0	13	1	62.5	1778.0	---	---
		Type5	8	5	149042.0	13	2	80.8	1736.0	1505.0	---
		Type5	8	3	587395.0	13	3	99.8	1558.0	1696.0	1949.0
		Type5	8	1	174965.0	13	1	50.7	1221.0	---	---
		Type5	8	0	823112.0	13	1	54.1	1415.0	---	---
		Type5	8	13	98172.0	13	1	64.3	1937.0	---	---
		Type5	8	4	796897.0	13	2	68.4	1014.0	1099.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	9	7	82296.0	6	3	95.4	1580.0	1555.0	1791.0
		Type5	9	1	898668.0	6	1	52.0	1863.0	---	---
		Type5	9	2	1259235.0	6	3	97.2	1973.0	1605.0	1583.0
		Type5	9	3	127106.0	6	2	78.7	1466.0	1743.0	---
		Type5	9	4	490358.0	6	2	74.2	1280.0	1219.0	---
		Type5	9	5	852409.0	6	3	88.7	1293.0	1934.0	1273.0
		Type5	9	6	1217152.0	6	1	54.3	1991.0	---	---
		Type5	9	0	535615.0	6	1	63.4	1043.0	---	---
	5500	Type5	9	5	852409.0	6	3	88.7	1293.0	1934.0	1273.0
		Type5	9	4	490358.0	6	2	74.2	1280.0	1219.0	---
		Type5	9	3	127106.0	6	2	78.7	1466.0	1743.0	---
		Type5	9	2	1259235.0	6	3	97.2	1973.0	1605.0	1583.0
		Type5	9	6	1217152.0	6	1	54.3	1991.0	---	---
		Type5	9	0	535615.0	6	1	63.4	1043.0	---	---
		Type5	9	7	82296.0	6	3	95.4	1580.0	1555.0	1791.0
		Type5	9	1	898668.0	6	1	52.0	1863.0	---	---
11AX40MIMO	5270	Type5	9	7	82296.0	6	3	95.4	1580.0	1555.0	1791.0
		Type5	9	0	535615.0	6	1	63.4	1043.0	---	---
		Type5	9	1	898668.0	6	1	52.0	1863.0	---	---
		Type5	9	2	1259235.0	6	3	97.2	1973.0	1605.0	1583.0
		Type5	9	3	127106.0	6	2	78.7	1466.0	1743.0	---
		Type5	9	4	490358.0	6	2	74.2	1280.0	1219.0	---
		Type5	9	5	852409.0	6	3	88.7	1293.0	1934.0	1273.0
		Type5	9	6	1217152.0	6	1	54.3	1991.0	---	---
	5510	Type5	9	1	898668.0	6	1	52.0	1863.0	---	---
		Type5	9	7	82296.0	6	3	95.4	1580.0	1555.0	1791.0
		Type5	9	6	1217152.0	6	1	54.3	1991.0	---	---
		Type5	9	5	852409.0	6	3	88.7	1293.0	1934.0	1273.0
		Type5	9	4	490358.0	6	2	74.2	1280.0	1219.0	---
		Type5	9	2	1259235.0	6	3	97.2	1973.0	1605.0	1583.0
		Type5	9	0	535615.0	6	1	63.4	1043.0	---	---
		Type5	9	3	127106.0	6	2	78.7	1466.0	1743.0	---
11AX80MIMO	5290	Type5	9	1	898668.0	6	1	52.0	1863.0	---	---
		Type5	9	2	1259235.0	6	3	97.2	1973.0	1605.0	1583.0
		Type5	9	7	82296.0	6	3	95.4	1580.0	1555.0	1791.0
		Type5	9	3	127106.0	6	2	78.7	1466.0	1743.0	---
		Type5	9	4	490358.0	6	2	74.2	1280.0	1219.0	---
		Type5	9	5	852409.0	6	3	88.7	1293.0	1934.0	1273.0
		Type5	9	6	1217152.0	6	1	54.3	1991.0	---	---
		Type5	9	0	535615.0	6	1	63.4	1043.0	---	---
	5530	Type5	9	6	1217152.0	6	1	54.3	1991.0	---	---
		Type5	9	2	1259235.0	6	3	97.2	1973.0	1605.0	1583.0
		Type5	9	5	852409.0	6	3	88.7	1293.0	1934.0	1273.0
		Type5	9	3	127106.0	6	2	78.7	1466.0	1743.0	---
		Type5	9	0	535615.0	6	1	63.4	1043.0	---	---
		Type5	9	7	82296.0	6	3	95.4	1580.0	1555.0	1791.0
		Type5	9	4	490358.0	6	2	74.2	1280.0	1219.0	---
		Type5	9	1	898668.0	6	1	52.0	1863.0	---	---
11AX160MIMO	5250	Type5	9	2	1259235.0	6	3	97.2	1973.0	1605.0	1583.0
		Type5	9	1	898668.0	6	1	52.0	1863.0	---	---
		Type5	9	3	127106.0	6	2	78.7	1466.0	1743.0	---
		Type5	9	4	490358.0	6	2	74.2	1280.0	1219.0	---
		Type5	9	5	852409.0	6	3	88.7	1293.0	1934.0	1273.0
		Type5	9	6	1217152.0	6	1	54.3	1991.0	---	---

		Type5	9	7	82296.0	6	3	95.4	1580.0	1555.0	1791.0
		Type5	9	0	535615.0	6	1	63.4	1043.0	---	---
	5570	Type5	9	7	82296.0	6	3	95.4	1580.0	1555.0	1791.0
		Type5	9	0	535615.0	6	1	63.4	1043.0	---	---
		Type5	9	1	898668.0	6	1	52.0	1863.0	---	---
		Type5	9	2	1259235.0	6	3	97.2	1973.0	1605.0	1583.0
		Type5	9	3	127106.0	6	2	78.7	1466.0	1743.0	---
		Type5	9	4	490358.0	6	2	74.2	1280.0	1219.0	---
		Type5	9	5	852409.0	6	3	88.7	1293.0	1934.0	1273.0
		Type5	9	6	1217152.0	6	1	54.3	1991.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	10	11	678689.0	16	2	67.9	1803.0	1083.0	---
		Type5	10	0	209249.0	16	2	73.7	1208.0	1497.0	---
		Type5	10	15	657326.0	16	2	68.9	1849.0	1423.0	---
		Type5	10	14	488056.0	16	1	63.3	1634.0	---	---
		Type5	10	12	146031.0	16	2	81.2	1720.0	1932.0	---
		Type5	10	16	125509.0	16	1	59.3	1093.0	---	---
		Type5	10	10	508324.0	16	2	77.0	1397.0	1304.0	---
		Type5	10	9	338262.0	16	1	59.1	1697.0	---	---
		Type5	10	2	548411.0	16	3	91.7	1999.0	1702.0	1462.0
		Type5	10	13	316923.0	16	2	78.7	1247.0	1121.0	---
		Type5	10	1	378386.0	16	3	97.4	1942.0	1754.0	1613.0
		Type5	10	8	167197.0	16	2	75.6	1437.0	1430.0	---
		Type5	10	3	17733.0	16	1	66.2	1393.0	---	---
		Type5	10	4	187952.0	16	2	70.8	1968.0	1821.0	---
		Type5	10	5	359277.0	16	1	52.3	1740.0	---	---
		Type5	10	6	528886.0	16	2	78.9	1308.0	1984.0	---
		Type5	10	7	700166.0	16	2	70.9	1050.0	1358.0	---
	5500	Type5	10	8	167197.0	16	2	75.6	1437.0	1430.0	---
		Type5	10	13	316923.0	16	2	78.7	1247.0	1121.0	---
		Type5	10	12	146031.0	16	2	81.2	1720.0	1932.0	---
		Type5	10	11	678689.0	16	2	67.9	1803.0	1083.0	---
		Type5	10	10	508324.0	16	2	77.0	1397.0	1304.0	---
		Type5	10	9	338262.0	16	1	59.1	1697.0	---	---
		Type5	10	14	488056.0	16	1	63.3	1634.0	---	---
		Type5	10	7	700166.0	16	2	70.9	1050.0	1358.0	---
		Type5	10	6	528886.0	16	2	78.9	1308.0	1984.0	---
		Type5	10	5	359277.0	16	1	52.3	1740.0	---	---
		Type5	10	4	187952.0	16	2	70.8	1968.0	1821.0	---
		Type5	10	3	17733.0	16	1	66.2	1393.0	---	---
		Type5	10	2	548411.0	16	3	91.7	1999.0	1702.0	1462.0
		Type5	10	15	657326.0	16	2	68.9	1849.0	1423.0	---
		Type5	10	0	209249.0	16	2	73.7	1208.0	1497.0	---
		Type5	10	16	125509.0	16	1	59.3	1093.0	---	---
		Type5	10	1	378386.0	16	3	97.4	1942.0	1754.0	1613.0
11AX40MIMO	5270	Type5	10	6	528886.0	16	2	78.9	1308.0	1984.0	---
		Type5	10	14	488056.0	16	1	63.3	1634.0	---	---
		Type5	10	13	316923.0	16	2	78.7	1247.0	1121.0	---
		Type5	10	12	146031.0	16	2	81.2	1720.0	1932.0	---
		Type5	10	11	678689.0	16	2	67.9	1803.0	1083.0	---
		Type5	10	10	508324.0	16	2	77.0	1397.0	1304.0	---
		Type5	10	9	338262.0	16	1	59.1	1697.0	---	---
		Type5	10	15	657326.0	16	2	68.9	1849.0	1423.0	---
		Type5	10	7	700166.0	16	2	70.9	1050.0	1358.0	---
		Type5	10	16	125509.0	16	1	59.3	1093.0	---	---
		Type5	10	5	359277.0	16	1	52.3	1740.0	---	---
		Type5	10	4	187952.0	16	2	70.8	1968.0	1821.0	---
		Type5	10	3	17733.0	16	1	66.2	1393.0	---	---
		Type5	10	2	548411.0	16	3	91.7	1999.0	1702.0	1462.0
		Type5	10	1	378386.0	16	3	97.4	1942.0	1754.0	1613.0
		Type5	10	0	209249.0	16	2	73.7	1208.0	1497.0	---
		Type5	10	8	167197.0	16	2	75.6	1437.0	1430.0	---
	5510	Type5	10	10	508324.0	16	2	77.0	1397.0	1304.0	---
		Type5	10	1	378386.0	16	3	97.4	1942.0	1754.0	1613.0
		Type5	10	2	548411.0	16	3	91.7	1999.0	1702.0	1462.0
		Type5	10	2	548411.0	16	3	91.7	1999.0	1702.0	1462.0

		Type5	10	4	187952.0	16	2	70.8	1968.0	1821.0	---
		Type5	10	6	528886.0	16	2	78.9	1308.0	1984.0	---
		Type5	10	7	700166.0	16	2	70.9	1050.0	1358.0	---
		Type5	10	0	209249.0	16	2	73.7	1208.0	1497.0	---
		Type5	10	9	338262.0	16	1	59.1	1697.0	---	---
		Type5	10	3	17733.0	16	1	66.2	1393.0	---	---
		Type5	10	11	678689.0	16	2	67.9	1803.0	1083.0	---
		Type5	10	12	146031.0	16	2	81.2	1720.0	1932.0	---
		Type5	10	13	316923.0	16	2	78.7	1247.0	1121.0	---
		Type5	10	14	488056.0	16	1	63.3	1634.0	---	---
		Type5	10	15	657326.0	16	2	68.9	1849.0	1423.0	---
		Type5	10	16	125509.0	16	1	59.3	1093.0	---	---
		Type5	10	8	167197.0	16	2	75.6	1437.0	1430.0	---
		Type5	10	5	359277.0	16	1	52.3	1740.0	---	---
11AX80MIMO	5290	Type5	10	10	508324.0	16	2	77.0	1397.0	1304.0	---
		Type5	10	15	657326.0	16	2	68.9	1849.0	1423.0	---
		Type5	10	0	209249.0	16	2	73.7	1208.0	1497.0	---
		Type5	10	14	488056.0	16	1	63.3	1634.0	---	---
		Type5	10	13	316923.0	16	2	78.7	1247.0	1121.0	---
		Type5	10	11	678689.0	16	2	67.9	1803.0	1083.0	---
		Type5	10	9	338262.0	16	1	59.1	1697.0	---	---
		Type5	10	8	167197.0	16	2	75.6	1437.0	1430.0	---
		Type5	10	3	17733.0	16	1	66.2	1393.0	---	---
		Type5	10	6	528886.0	16	2	78.9	1308.0	1984.0	---
		Type5	10	5	359277.0	16	1	52.3	1740.0	---	---
		Type5	10	1	378386.0	16	3	97.4	1942.0	1754.0	1613.0
		Type5	10	16	125509.0	16	1	59.3	1093.0	---	---
		Type5	10	4	187952.0	16	2	70.8	1968.0	1821.0	---
		Type5	10	7	700166.0	16	2	70.9	1050.0	1358.0	---
		Type5	10	12	146031.0	16	2	81.2	1720.0	1932.0	---
		Type5	10	2	548411.0	16	3	91.7	1999.0	1702.0	1462.0
	5530	Type5	10	9	338262.0	16	1	59.1	1697.0	---	---
		Type5	10	10	508324.0	16	2	77.0	1397.0	1304.0	---
		Type5	10	11	678689.0	16	2	67.9	1803.0	1083.0	---
		Type5	10	12	146031.0	16	2	81.2	1720.0	1932.0	---
		Type5	10	14	488056.0	16	1	63.3	1634.0	---	---
		Type5	10	6	528886.0	16	2	78.9	1308.0	1984.0	---
		Type5	10	15	657326.0	16	2	68.9	1849.0	1423.0	---
		Type5	10	13	316923.0	16	2	78.7	1247.0	1121.0	---
		Type5	10	16	125509.0	16	1	59.3	1093.0	---	---
		Type5	10	5	359277.0	16	1	52.3	1740.0	---	---
		Type5	10	4	187952.0	16	2	70.8	1968.0	1821.0	---
		Type5	10	3	17733.0	16	1	66.2	1393.0	---	---
		Type5	10	2	548411.0	16	3	91.7	1999.0	1702.0	1462.0
		Type5	10	1	378386.0	16	3	97.4	1942.0	1754.0	1613.0
		Type5	10	0	209249.0	16	2	73.7	1208.0	1497.0	---
		Type5	10	7	700166.0	16	2	70.9	1050.0	1358.0	---
		Type5	10	8	167197.0	16	2	75.6	1437.0	1430.0	---
11AX160MIMO	5250	Type5	10	7	700166.0	16	2	70.9	1050.0	1358.0	---
		Type5	10	6	528886.0	16	2	78.9	1308.0	1984.0	---
		Type5	10	4	187952.0	16	2	70.8	1968.0	1821.0	---
		Type5	10	2	548411.0	16	3	91.7	1999.0	1702.0	1462.0
		Type5	10	8	167197.0	16	2	75.6	1437.0	1430.0	---
		Type5	10	0	209249.0	16	2	73.7	1208.0	1497.0	---
		Type5	10	5	359277.0	16	1	52.3	1740.0	---	---
		Type5	10	1	378386.0	16	3	97.4	1942.0	1754.0	1613.0
		Type5	10	16	125509.0	16	1	59.3	1093.0	---	---
		Type5	10	10	508324.0	16	2	77.0	1397.0	1304.0	---

		Type5	10	11	678689.0	16	2	67.9	1803.0	1083.0	---
		Type5	10	12	146031.0	16	2	81.2	1720.0	1932.0	---
		Type5	10	13	316923.0	16	2	78.7	1247.0	1121.0	---
		Type5	10	14	488056.0	16	1	63.3	1634.0	---	---
		Type5	10	15	657326.0	16	2	68.9	1849.0	1423.0	---
		Type5	10	3	17733.0	16	1	66.2	1393.0	---	---
		Type5	10	9	338262.0	16	1	59.1	1697.0	---	---
	5570	Type5	10	10	508324.0	16	2	77.0	1397.0	1304.0	---
		Type5	10	11	678689.0	16	2	67.9	1803.0	1083.0	---
		Type5	10	12	146031.0	16	2	81.2	1720.0	1932.0	---
		Type5	10	13	316923.0	16	2	78.7	1247.0	1121.0	---
		Type5	10	9	338262.0	16	1	59.1	1697.0	---	---
		Type5	10	15	657326.0	16	2	68.9	1849.0	1423.0	---
		Type5	10	3	17733.0	16	1	66.2	1393.0	---	---
		Type5	10	14	488056.0	16	1	63.3	1634.0	---	---
		Type5	10	8	167197.0	16	2	75.6	1437.0	1430.0	---
		Type5	10	7	700166.0	16	2	70.9	1050.0	1358.0	---
		Type5	10	6	528886.0	16	2	78.9	1308.0	1984.0	---
		Type5	10	4	187952.0	16	2	70.8	1968.0	1821.0	---
		Type5	10	2	548411.0	16	3	91.7	1999.0	1702.0	1462.0
		Type5	10	1	378386.0	16	3	97.4	1942.0	1754.0	1613.0
		Type5	10	0	209249.0	16	2	73.7	1208.0	1497.0	---
		Type5	10	16	125509.0	16	1	59.3	1093.0	---	---
		Type5	10	5	359277.0	16	1	52.3	1740.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	11	12	207876.0	19	2	82.3	1845.0	1686.0	---
		Type5	11	0	263736.0	19	3	98.9	1381.0	1680.0	1488.0
		Type5	11	17	341809.0	19	2	77.0	1187.0	1657.0	---
		Type5	11	16	189652.0	19	1	58.8	1742.0	---	---
		Type5	11	15	36803.0	19	2	83.1	1943.0	1406.0	---
		Type5	11	13	359771.0	19	3	90.1	1938.0	1071.0	1266.0
		Type5	11	18	495737.0	19	1	55.0	1012.0	---	---
		Type5	11	11	55547.0	19	2	78.5	1911.0	1704.0	---
		Type5	11	10	533408.0	19	1	65.6	1017.0	---	---
		Type5	11	2	567902.0	19	3	86.7	1211.0	1400.0	1919.0
		Type5	11	14	511297.0	19	3	90.2	1989.0	1089.0	1950.0
		Type5	11	1	416459.0	19	2	82.3	1716.0	1855.0	---
		Type5	11	9	380056.0	19	1	58.8	1715.0	---	---
		Type5	11	3	92979.0	19	3	89.7	1861.0	1068.0	1282.0
		Type5	11	4	245155.0	19	3	98.6	1507.0	1194.0	1461.0
		Type5	11	5	397609.0	19	2	71.1	1921.0	1789.0	---
		Type5	11	6	551431.0	19	1	55.9	1947.0	---	---
		Type5	11	7	74413.0	19	2	67.9	1350.0	1372.0	---
		Type5	11	8	226559.0	19	3	84.4	1203.0	1107.0	1443.0
	5500	Type5	11	9	380056.0	19	1	58.8	1715.0	---	---
		Type5	11	15	36803.0	19	2	83.1	1943.0	1406.0	---
		Type5	11	14	511297.0	19	3	90.2	1989.0	1089.0	1950.0
		Type5	11	13	359771.0	19	3	90.1	1938.0	1071.0	1266.0
		Type5	11	12	207876.0	19	2	82.3	1845.0	1686.0	---
		Type5	11	11	55547.0	19	2	78.5	1911.0	1704.0	---
		Type5	11	10	533408.0	19	1	65.6	1017.0	---	---
		Type5	11	16	189652.0	19	1	58.8	1742.0	---	---
		Type5	11	8	226559.0	19	3	84.4	1203.0	1107.0	1443.0
		Type5	11	7	74413.0	19	2	67.9	1350.0	1372.0	---
		Type5	11	6	551431.0	19	1	55.9	1947.0	---	---
		Type5	11	5	397609.0	19	2	71.1	1921.0	1789.0	---
		Type5	11	4	245155.0	19	3	98.6	1507.0	1194.0	1461.0
		Type5	11	3	92979.0	19	3	89.7	1861.0	1068.0	1282.0
		Type5	11	2	567902.0	19	3	86.7	1211.0	1400.0	1919.0
		Type5	11	17	341809.0	19	2	77.0	1187.0	1657.0	---
		Type5	11	0	263736.0	19	3	98.9	1381.0	1680.0	1488.0
		Type5	11	18	495737.0	19	1	55.0	1012.0	---	---
		Type5	11	1	416459.0	19	2	82.3	1716.0	1855.0	---
11AX40MIMO	5270	Type5	11	7	74413.0	19	2	67.9	1350.0	1372.0	---
		Type5	11	16	189652.0	19	1	58.8	1742.0	---	---
		Type5	11	15	36803.0	19	2	83.1	1943.0	1406.0	---
		Type5	11	14	511297.0	19	3	90.2	1989.0	1089.0	1950.0
		Type5	11	13	359771.0	19	3	90.1	1938.0	1071.0	1266.0
		Type5	11	12	207876.0	19	2	82.3	1845.0	1686.0	---
		Type5	11	11	55547.0	19	2	78.5	1911.0	1704.0	---
		Type5	11	10	533408.0	19	1	65.6	1017.0	---	---
		Type5	11	17	341809.0	19	2	77.0	1187.0	1657.0	---
		Type5	11	8	226559.0	19	3	84.4	1203.0	1107.0	1443.0
		Type5	11	18	495737.0	19	1	55.0	1012.0	---	---
		Type5	11	6	551431.0	19	1	55.9	1947.0	---	---
		Type5	11	5	397609.0	19	2	71.1	1921.0	1789.0	---
		Type5	11	4	245155.0	19	3	98.6	1507.0	1194.0	1461.0
		Type5	11	3	92979.0	19	3	89.7	1861.0	1068.0	1282.0
		Type5	11	2	567902.0	19	3	86.7	1211.0	1400.0	1919.0

	5510	Type5	11	1	416459.0	19	2	82.3	1716.0	1855.0	---
		Type5	11	0	263736.0	19	3	98.9	1381.0	1680.0	1488.0
		Type5	11	9	380056.0	19	1	58.8	1715.0	---	---
		Type5	11	11	55547.0	19	2	78.5	1911.0	1704.0	---
		Type5	11	1	416459.0	19	2	82.3	1716.0	1855.0	---
		Type5	11	2	567902.0	19	3	86.7	1211.0	1400.0	1919.0
		Type5	11	4	245155.0	19	3	98.6	1507.0	1194.0	1461.0
		Type5	11	6	551431.0	19	1	55.9	1947.0	---	---
		Type5	11	7	74413.0	19	2	67.9	1350.0	1372.0	---
		Type5	11	8	226559.0	19	3	84.4	1203.0	1107.0	1443.0
		Type5	11	0	263736.0	19	3	98.9	1381.0	1680.0	1488.0
		Type5	11	10	533408.0	19	1	65.6	1017.0	---	---
		Type5	11	3	92979.0	19	3	89.7	1861.0	1068.0	1282.0
		Type5	11	12	207876.0	19	2	82.3	1845.0	1686.0	---
		Type5	11	13	359771.0	19	3	90.1	1938.0	1071.0	1266.0
		Type5	11	14	511297.0	19	3	90.2	1989.0	1089.0	1950.0
		Type5	11	15	36803.0	19	2	83.1	1943.0	1406.0	---
		Type5	11	16	189652.0	19	1	58.8	1742.0	---	---
		Type5	11	17	341809.0	19	2	77.0	1187.0	1657.0	---
		Type5	11	18	495737.0	19	1	55.0	1012.0	---	---
		Type5	11	9	380056.0	19	1	58.8	1715.0	---	---
11AX80MIMO	5290	Type5	11	5	397609.0	19	2	71.1	1921.0	1789.0	---
		Type5	11	11	55547.0	19	2	78.5	1911.0	1704.0	---
		Type5	11	17	341809.0	19	2	77.0	1187.0	1657.0	---
		Type5	11	0	263736.0	19	3	98.9	1381.0	1680.0	1488.0
		Type5	11	16	189652.0	19	1	58.8	1742.0	---	---
		Type5	11	15	36803.0	19	2	83.1	1943.0	1406.0	---
		Type5	11	14	511297.0	19	3	90.2	1989.0	1089.0	1950.0
		Type5	11	12	207876.0	19	2	82.3	1845.0	1686.0	---
		Type5	11	10	533408.0	19	1	65.6	1017.0	---	---
		Type5	11	9	380056.0	19	1	58.8	1715.0	---	---
		Type5	11	3	92979.0	19	3	89.7	1861.0	1068.0	1282.0
		Type5	11	7	74413.0	19	2	67.9	1350.0	1372.0	---
		Type5	11	6	551431.0	19	1	55.9	1947.0	---	---
		Type5	11	1	416459.0	19	2	82.3	1716.0	1855.0	---
		Type5	11	5	397609.0	19	2	71.1	1921.0	1789.0	---
		Type5	11	18	495737.0	19	1	55.0	1012.0	---	---
		Type5	11	4	245155.0	19	3	98.6	1507.0	1194.0	1461.0
		Type5	11	8	226559.0	19	3	84.4	1203.0	1107.0	1443.0
		Type5	11	13	359771.0	19	3	90.1	1938.0	1071.0	1266.0
		Type5	11	2	567902.0	19	3	86.7	1211.0	1400.0	1919.0
	5530	Type5	11	10	533408.0	19	1	65.6	1017.0	---	---
		Type5	11	11	55547.0	19	2	78.5	1911.0	1704.0	---
		Type5	11	12	207876.0	19	2	82.3	1845.0	1686.0	---
		Type5	11	13	359771.0	19	3	90.1	1938.0	1071.0	1266.0
		Type5	11	14	511297.0	19	3	90.2	1989.0	1089.0	1950.0
		Type5	11	16	189652.0	19	1	58.8	1742.0	---	---
		Type5	11	7	74413.0	19	2	67.9	1350.0	1372.0	---
		Type5	11	17	341809.0	19	2	77.0	1187.0	1657.0	---
		Type5	11	15	36803.0	19	2	83.1	1943.0	1406.0	---
		Type5	11	18	495737.0	19	1	55.0	1012.0	---	---
		Type5	11	6	551431.0	19	1	55.9	1947.0	---	---
		Type5	11	5	397609.0	19	2	71.1	1921.0	1789.0	---
		Type5	11	4	245155.0	19	3	98.6	1507.0	1194.0	1461.0
		Type5	11	3	92979.0	19	3	89.7	1861.0	1068.0	1282.0
		Type5	11	2	567902.0	19	3	86.7	1211.0	1400.0	1919.0
		Type5	11	1	416459.0	19	2	82.3	1716.0	1855.0	---
		Type5	11	0	263736.0	19	3	98.9	1381.0	1680.0	1488.0

11AX160MIMO		Type5	11	8	226559.0	19	3	84.4	1203.0	1107.0	1443.0
		Type5	11	9	380056.0	19	1	58.8	1715.0	---	---
	5250	Type5	11	8	226559.0	19	3	84.4	1203.0	1107.0	1443.0
		Type5	11	7	74413.0	19	2	67.9	1350.0	1372.0	---
		Type5	11	6	551431.0	19	1	55.9	1947.0	---	---
		Type5	11	4	245155.0	19	3	98.6	1507.0	1194.0	1461.0
		Type5	11	2	567902.0	19	3	86.7	1211.0	1400.0	1919.0
		Type5	11	9	380056.0	19	1	58.8	1715.0	---	---
		Type5	11	0	263736.0	19	3	98.9	1381.0	1680.0	1488.0
		Type5	11	5	397609.0	19	2	71.1	1921.0	1789.0	---
		Type5	11	1	416459.0	19	2	82.3	1716.0	1855.0	---
		Type5	11	18	495737.0	19	1	55.0	1012.0	---	---
		Type5	11	11	55547.0	19	2	78.5	1911.0	1704.0	---
		Type5	11	12	207876.0	19	2	82.3	1845.0	1686.0	---
		Type5	11	13	359771.0	19	3	90.1	1938.0	1071.0	1266.0
		Type5	11	14	511297.0	19	3	90.2	1989.0	1089.0	1950.0
		Type5	11	15	36803.0	19	2	83.1	1943.0	1406.0	---
		Type5	11	16	189652.0	19	1	58.8	1742.0	---	---
		Type5	11	17	341809.0	19	2	77.0	1187.0	1657.0	---
		Type5	11	3	92979.0	19	3	89.7	1861.0	1068.0	1282.0
		Type5	11	10	533408.0	19	1	65.6	1017.0	---	---
	5570	Type5	11	11	55547.0	19	2	78.5	1911.0	1704.0	---
		Type5	11	12	207876.0	19	2	82.3	1845.0	1686.0	---
		Type5	11	13	359771.0	19	3	90.1	1938.0	1071.0	1266.0
		Type5	11	14	511297.0	19	3	90.2	1989.0	1089.0	1950.0
		Type5	11	15	36803.0	19	2	83.1	1943.0	1406.0	---
		Type5	11	10	533408.0	19	1	65.6	1017.0	---	---
		Type5	11	17	341809.0	19	2	77.0	1187.0	1657.0	---
		Type5	11	3	92979.0	19	3	89.7	1861.0	1068.0	1282.0
		Type5	11	16	189652.0	19	1	58.8	1742.0	---	---
		Type5	11	9	380056.0	19	1	58.8	1715.0	---	---
		Type5	11	8	226559.0	19	3	84.4	1203.0	1107.0	1443.0
		Type5	11	7	74413.0	19	2	67.9	1350.0	1372.0	---
		Type5	11	6	551431.0	19	1	55.9	1947.0	---	---
		Type5	11	4	245155.0	19	3	98.6	1507.0	1194.0	1461.0
		Type5	11	2	567902.0	19	3	86.7	1211.0	1400.0	1919.0
		Type5	11	1	416459.0	19	2	82.3	1716.0	1855.0	---
		Type5	11	0	263736.0	19	3	98.9	1381.0	1680.0	1488.0
		Type5	11	18	495737.0	19	1	55.0	1012.0	---	---
		Type5	11	5	397609.0	19	2	71.1	1921.0	1789.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	12	9	168898.0	13	1	61.4	1390.0	---	---
		Type5	12	0	22911.0	13	1	58.1	1929.0	---	---
		Type5	12	13	144710.0	13	2	78.3	1258.0	1951.0	---
		Type5	12	12	747241.0	13	3	88.7	1703.0	1528.0	1058.0
		Type5	12	10	361606.0	13	2	83.2	1692.0	1858.0	---
		Type5	12	14	337856.0	13	2	69.3	1731.0	1717.0	---
		Type5	12	8	773423.0	13	1	64.7	1800.0	---	---
		Type5	12	7	579862.0	13	1	53.8	1763.0	---	---
		Type5	12	6	385590.0	13	2	78.5	1238.0	1917.0	---
		Type5	12	5	192251.0	13	2	79.9	1626.0	1859.0	---
		Type5	12	4	794160.0	13	3	95.9	1399.0	1906.0	1608.0
		Type5	12	3	603671.0	13	1	60.2	1812.0	---	---
		Type5	12	2	410004.0	13	1	59.9	1971.0	---	---
		Type5	12	1	216473.0	13	1	52.1	1910.0	---	---
		Type5	12	11	553866.0	13	3	84.7	1533.0	1677.0	1638.0
	5500	Type5	12	7	579862.0	13	1	53.8	1763.0	---	---
		Type5	12	12	747241.0	13	3	88.7	1703.0	1528.0	1058.0
		Type5	12	11	553866.0	13	3	84.7	1533.0	1677.0	1638.0
		Type5	12	10	361606.0	13	2	83.2	1692.0	1858.0	---
		Type5	12	9	168898.0	13	1	61.4	1390.0	---	---
		Type5	12	8	773423.0	13	1	64.7	1800.0	---	---
		Type5	12	6	385590.0	13	2	78.5	1238.0	1917.0	---
		Type5	12	5	192251.0	13	2	79.9	1626.0	1859.0	---
		Type5	12	4	794160.0	13	3	95.9	1399.0	1906.0	1608.0
		Type5	12	3	603671.0	13	1	60.2	1812.0	---	---
		Type5	12	2	410004.0	13	1	59.9	1971.0	---	---
		Type5	12	13	144710.0	13	2	78.3	1258.0	1951.0	---
11AX40MIMO	5270	Type5	12	0	22911.0	13	1	58.1	1929.0	---	---
		Type5	12	1	216473.0	13	1	52.1	1910.0	---	---
		Type5	12	2	410004.0	13	1	59.9	1971.0	---	---
		Type5	12	3	603671.0	13	1	60.2	1812.0	---	---
		Type5	12	4	794160.0	13	3	95.9	1399.0	1906.0	1608.0
		Type5	12	5	192251.0	13	2	79.9	1626.0	1859.0	---
		Type5	12	6	385590.0	13	2	78.5	1238.0	1917.0	---
		Type5	12	7	579862.0	13	1	53.8	1763.0	---	---
		Type5	12	8	773423.0	13	1	64.7	1800.0	---	---
		Type5	12	9	168898.0	13	1	61.4	1390.0	---	---
		Type5	12	10	361606.0	13	2	83.2	1692.0	1858.0	---
		Type5	12	11	553866.0	13	3	84.7	1533.0	1677.0	1638.0
	5510	Type5	12	12	747241.0	13	3	88.7	1703.0	1528.0	1058.0
		Type5	12	13	144710.0	13	2	78.3	1258.0	1951.0	---
		Type5	12	2	410004.0	13	1	59.9	1971.0	---	---
		Type5	12	14	337856.0	13	2	69.3	1731.0	1717.0	---
		Type5	12	13	144710.0	13	2	78.3	1258.0	1951.0	---
		Type5	12	12	747241.0	13	3	88.7	1703.0	1528.0	1058.0
		Type5	12	11	553866.0	13	3	84.7	1533.0	1677.0	1638.0
		Type5	12	10	361606.0	13	2	83.2	1692.0	1858.0	---
		Type5	12	9	168898.0	13	1	61.4	1390.0	---	---
		Type5	12	8	773423.0	13	1	64.7	1800.0	---	---
		Type5	12	7	579862.0	13	1	53.8	1763.0	---	---

		Type5	12	6	385590.0	13	2	78.5	1238.0	1917.0	---
		Type5	12	5	192251.0	13	2	79.9	1626.0	1859.0	---
		Type5	12	3	603671.0	13	1	60.2	1812.0	---	---
		Type5	12	1	216473.0	13	1	52.1	1910.0	---	---
		Type5	12	0	22911.0	13	1	58.1	1929.0	---	---
		Type5	12	4	794160.0	13	3	95.9	1399.0	1906.0	1608.0
11AX80MIMO	5290	Type5	12	8	773423.0	13	1	64.7	1800.0	---	---
		Type5	12	13	144710.0	13	2	78.3	1258.0	1951.0	---
		Type5	12	0	22911.0	13	1	58.1	1929.0	---	---
		Type5	12	12	747241.0	13	3	88.7	1703.0	1528.0	1058.0
		Type5	12	11	553866.0	13	3	84.7	1533.0	1677.0	1638.0
		Type5	12	9	168898.0	13	1	61.4	1390.0	---	---
		Type5	12	7	579862.0	13	1	53.8	1763.0	---	---
		Type5	12	6	385590.0	13	2	78.5	1238.0	1917.0	---
		Type5	12	5	192251.0	13	2	79.9	1626.0	1859.0	---
		Type5	12	4	794160.0	13	3	95.9	1399.0	1906.0	1608.0
		Type5	12	14	337856.0	13	2	69.3	1731.0	1717.0	---
		Type5	12	3	603671.0	13	1	60.2	1812.0	---	---
		Type5	12	2	410004.0	13	1	59.9	1971.0	---	---
		Type5	12	1	216473.0	13	1	52.1	1910.0	---	---
		Type5	12	10	361606.0	13	2	83.2	1692.0	1858.0	---
	5530	Type5	12	13	144710.0	13	2	78.3	1258.0	1951.0	---
		Type5	12	5	192251.0	13	2	79.9	1626.0	1859.0	---
		Type5	12	12	747241.0	13	3	88.7	1703.0	1528.0	1058.0
		Type5	12	11	553866.0	13	3	84.7	1533.0	1677.0	1638.0
		Type5	12	10	361606.0	13	2	83.2	1692.0	1858.0	---
		Type5	12	9	168898.0	13	1	61.4	1390.0	---	---
		Type5	12	8	773423.0	13	1	64.7	1800.0	---	---
		Type5	12	4	794160.0	13	3	95.9	1399.0	1906.0	1608.0
		Type5	12	3	603671.0	13	1	60.2	1812.0	---	---
		Type5	12	2	410004.0	13	1	59.9	1971.0	---	---
		Type5	12	1	216473.0	13	1	52.1	1910.0	---	---
		Type5	12	0	22911.0	13	1	58.1	1929.0	---	---
		Type5	12	14	337856.0	13	2	69.3	1731.0	1717.0	---
		Type5	12	7	579862.0	13	1	53.8	1763.0	---	---
		Type5	12	6	385590.0	13	2	78.5	1238.0	1917.0	---
11AX160MIMO	5250	Type5	12	4	794160.0	13	3	95.9	1399.0	1906.0	1608.0
		Type5	12	0	22911.0	13	1	58.1	1929.0	---	---
		Type5	12	1	216473.0	13	1	52.1	1910.0	---	---
		Type5	12	3	603671.0	13	1	60.2	1812.0	---	---
		Type5	12	5	192251.0	13	2	79.9	1626.0	1859.0	---
		Type5	12	6	385590.0	13	2	78.5	1238.0	1917.0	---
		Type5	12	7	579862.0	13	1	53.8	1763.0	---	---
		Type5	12	9	168898.0	13	1	61.4	1390.0	---	---
		Type5	12	10	361606.0	13	2	83.2	1692.0	1858.0	---
		Type5	12	11	553866.0	13	3	84.7	1533.0	1677.0	1638.0
		Type5	12	12	747241.0	13	3	88.7	1703.0	1528.0	1058.0
		Type5	12	13	144710.0	13	2	78.3	1258.0	1951.0	---
		Type5	12	14	337856.0	13	2	69.3	1731.0	1717.0	---
		Type5	12	8	773423.0	13	1	64.7	1800.0	---	---
		Type5	12	2	410004.0	13	1	59.9	1971.0	---	---
	5570	Type5	12	2	410004.0	13	1	59.9	1971.0	---	---
		Type5	12	13	144710.0	13	2	78.3	1258.0	1951.0	---
		Type5	12	12	747241.0	13	3	88.7	1703.0	1528.0	1058.0
		Type5	12	11	553866.0	13	3	84.7	1533.0	1677.0	1638.0
		Type5	12	10	361606.0	13	2	83.2	1692.0	1858.0	---
		Type5	12	9	168898.0	13	1	61.4	1390.0	---	---
		Type5	12	8	773423.0	13	1	64.7	1800.0	---	---

	Type5	12	7	579862.0	13	1	53.8	1763.0	---	---
	Type5	12	6	385590.0	13	2	78.5	1238.0	1917.0	---
	Type5	12	5	192251.0	13	2	79.9	1626.0	1859.0	---
	Type5	12	3	603671.0	13	1	60.2	1812.0	---	---
	Type5	12	1	216473.0	13	1	52.1	1910.0	---	---
	Type5	12	0	22911.0	13	1	58.1	1929.0	---	---
	Type5	12	14	337856.0	13	2	69.3	1731.0	1717.0	---
	Type5	12	4	794160.0	13	3	95.9	1399.0	1906.0	1608.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	13	7	362696.0	10	3	98.4	1873.0	1550.0	1249.0
		Type5	13	0	664275.0	10	2	75.3	1994.0	1612.0	---
		Type5	13	10	91871.0	10	1	63.3	1328.0	---	---
		Type5	13	8	604342.0	10	3	86.4	1779.0	1439.0	1046.0
		Type5	13	11	333050.0	10	3	92.4	1412.0	1673.0	1322.0
		Type5	13	6	121278.0	10	3	85.7	1547.0	1362.0	1924.0
		Type5	13	5	876993.0	10	2	76.3	1359.0	1305.0	---
		Type5	13	4	635093.0	10	2	75.2	1421.0	1267.0	---
		Type5	13	3	393746.0	10	1	55.6	1337.0	---	---
		Type5	13	2	151316.0	10	2	67.7	1617.0	1185.0	---
	5500	Type5	13	1	907886.0	10	1	56.3	1456.0	---	---
		Type5	13	9	846453.0	10	3	93.6	1059.0	1031.0	1452.0
		Type5	13	5	876993.0	10	2	76.3	1359.0	1305.0	---
		Type5	13	9	846453.0	10	3	93.6	1059.0	1031.0	1452.0
		Type5	13	8	604342.0	10	3	86.4	1779.0	1439.0	1046.0
		Type5	13	7	362696.0	10	3	98.4	1873.0	1550.0	1249.0
		Type5	13	6	121278.0	10	3	85.7	1547.0	1362.0	1924.0
		Type5	13	4	635093.0	10	2	75.2	1421.0	1267.0	---
		Type5	13	3	393746.0	10	1	55.6	1337.0	---	---
		Type5	13	2	151316.0	10	2	67.7	1617.0	1185.0	---
11AX40MIMO	5270	Type5	13	10	91871.0	10	1	63.3	1328.0	---	---
		Type5	13	0	664275.0	10	2	75.3	1994.0	1612.0	---
		Type5	13	11	333050.0	10	3	92.4	1412.0	1673.0	1322.0
		Type5	13	1	907886.0	10	1	56.3	1456.0	---	---
		Type5	13	11	333050.0	10	3	92.4	1412.0	1673.0	1322.0
		Type5	13	0	664275.0	10	2	75.3	1994.0	1612.0	---
		Type5	13	1	907886.0	10	1	56.3	1456.0	---	---
		Type5	13	2	151316.0	10	2	67.7	1617.0	1185.0	---
		Type5	13	3	393746.0	10	1	55.6	1337.0	---	---
		Type5	13	4	635093.0	10	2	75.2	1421.0	1267.0	---
	5510	Type5	13	5	876993.0	10	2	76.3	1359.0	1305.0	---
		Type5	13	6	121278.0	10	3	85.7	1547.0	1362.0	1924.0
		Type5	13	7	362696.0	10	3	98.4	1873.0	1550.0	1249.0
		Type5	13	8	604342.0	10	3	86.4	1779.0	1439.0	1046.0
		Type5	13	9	846453.0	10	3	93.6	1059.0	1031.0	1452.0
		Type5	13	10	91871.0	10	1	63.3	1328.0	---	---
		Type5	13	2	151316.0	10	2	67.7	1617.0	1185.0	---
		Type5	13	11	333050.0	10	3	92.4	1412.0	1673.0	1322.0
		Type5	13	10	91871.0	10	1	63.3	1328.0	---	---
		Type5	13	9	846453.0	10	3	93.6	1059.0	1031.0	1452.0
11AX80MIMO	5290	Type5	13	8	604342.0	10	3	86.4	1779.0	1439.0	1046.0
		Type5	13	7	362696.0	10	3	98.4	1873.0	1550.0	1249.0
		Type5	13	6	121278.0	10	3	85.7	1547.0	1362.0	1924.0
		Type5	13	5	876993.0	10	2	76.3	1359.0	1305.0	---
		Type5	13	3	393746.0	10	1	55.6	1337.0	---	---
		Type5	13	1	907886.0	10	1	56.3	1456.0	---	---

11AX160MIMO		Type5	13	4	635093.0	10	2	75.2	1421.0	1267.0	---
		Type5	13	11	333050.0	10	3	92.4	1412.0	1673.0	1322.0
		Type5	13	3	393746.0	10	1	55.6	1337.0	---	---
		Type5	13	2	151316.0	10	2	67.7	1617.0	1185.0	---
		Type5	13	1	907886.0	10	1	56.3	1456.0	---	---
		Type5	13	8	604342.0	10	3	86.4	1779.0	1439.0	1046.0
	5530	Type5	13	10	91871.0	10	1	63.3	1328.0	---	---
		Type5	13	4	635093.0	10	2	75.2	1421.0	1267.0	---
		Type5	13	9	846453.0	10	3	93.6	1059.0	1031.0	1452.0
		Type5	13	8	604342.0	10	3	86.4	1779.0	1439.0	1046.0
		Type5	13	7	362696.0	10	3	98.4	1873.0	1550.0	1249.0
		Type5	13	5	876993.0	10	2	76.3	1359.0	1305.0	---
		Type5	13	2	151316.0	10	2	67.7	1617.0	1185.0	---
		Type5	13	1	907886.0	10	1	56.3	1456.0	---	---
		Type5	13	0	664275.0	10	2	75.3	1994.0	1612.0	---
		Type5	13	11	333050.0	10	3	92.4	1412.0	1673.0	1322.0
		Type5	13	6	121278.0	10	3	85.7	1547.0	1362.0	1924.0
		Type5	13	3	393746.0	10	1	55.6	1337.0	---	---
	5250	Type5	13	3	393746.0	10	1	55.6	1337.0	---	---
		Type5	13	0	664275.0	10	2	75.3	1994.0	1612.0	---
		Type5	13	2	151316.0	10	2	67.7	1617.0	1185.0	---
		Type5	13	4	635093.0	10	2	75.2	1421.0	1267.0	---
		Type5	13	5	876993.0	10	2	76.3	1359.0	1305.0	---
		Type5	13	7	362696.0	10	3	98.4	1873.0	1550.0	1249.0
		Type5	13	8	604342.0	10	3	86.4	1779.0	1439.0	1046.0
		Type5	13	9	846453.0	10	3	93.6	1059.0	1031.0	1452.0
		Type5	13	10	91871.0	10	1	63.3	1328.0	---	---
		Type5	13	11	333050.0	10	3	92.4	1412.0	1673.0	1322.0
		Type5	13	6	121278.0	10	3	85.7	1547.0	1362.0	1924.0
		Type5	13	1	907886.0	10	1	56.3	1456.0	---	---
	5570	Type5	13	1	907886.0	10	1	56.3	1456.0	---	---
		Type5	13	10	91871.0	10	1	63.3	1328.0	---	---
		Type5	13	9	846453.0	10	3	93.6	1059.0	1031.0	1452.0
		Type5	13	8	604342.0	10	3	86.4	1779.0	1439.0	1046.0
		Type5	13	7	362696.0	10	3	98.4	1873.0	1550.0	1249.0
		Type5	13	6	121278.0	10	3	85.7	1547.0	1362.0	1924.0
		Type5	13	5	876993.0	10	2	76.3	1359.0	1305.0	---
		Type5	13	4	635093.0	10	2	75.2	1421.0	1267.0	---
		Type5	13	2	151316.0	10	2	67.7	1617.0	1185.0	---
		Type5	13	0	664275.0	10	2	75.3	1994.0	1612.0	---
		Type5	13	11	333050.0	10	3	92.4	1412.0	1673.0	1322.0
		Type5	13	3	393746.0	10	1	55.6	1337.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	14	12	307096.0	18	1	59.8	1552.0	---	---
		Type5	14	0	361323.0	18	3	93.3	1983.0	1912.0	1535.0
		Type5	14	17	441296.0	18	1	51.2	1237.0	---	---
		Type5	14	16	288306.0	18	1	56.5	1483.0	---	---
		Type5	14	15	134759.0	18	3	91.2	1382.0	1832.0	1661.0
		Type5	14	13	458804.0	18	2	70.0	1759.0	1291.0	---
		Type5	14	18	592780.0	18	2	74.1	1471.0	1245.0	---
		Type5	14	11	153647.0	18	3	90.9	1261.0	1566.0	1370.0
		Type5	14	10	1489.0	18	2	72.0	1909.0	1297.0	---
		Type5	14	2	39025.0	18	3	86.9	1044.0	1152.0	1148.0
		Type5	14	14	610798.0	18	2	67.2	1625.0	1881.0	---
		Type5	14	1	515261.0	18	2	69.1	1102.0	1794.0	---
		Type5	14	9	475841.0	18	3	88.9	1886.0	1964.0	1489.0
		Type5	14	3	190900.0	18	3	84.9	1894.0	1948.0	1118.0
		Type5	14	4	343941.0	18	2	72.3	1094.0	1916.0	---
		Type5	14	5	497624.0	18	1	51.7	1447.0	---	---
		Type5	14	6	20319.0	18	1	58.3	1429.0	---	---
		Type5	14	7	172999.0	18	1	60.8	1979.0	---	---
		Type5	14	8	325872.0	18	1	57.1	1641.0	---	---
	5500	Type5	14	9	475841.0	18	3	88.9	1886.0	1964.0	1489.0
		Type5	14	15	134759.0	18	3	91.2	1382.0	1832.0	1661.0
		Type5	14	14	610798.0	18	2	67.2	1625.0	1881.0	---
		Type5	14	13	458804.0	18	2	70.0	1759.0	1291.0	---
		Type5	14	12	307096.0	18	1	59.8	1552.0	---	---
		Type5	14	11	153647.0	18	3	90.9	1261.0	1566.0	1370.0
		Type5	14	10	1489.0	18	2	72.0	1909.0	1297.0	---
		Type5	14	16	288306.0	18	1	56.5	1483.0	---	---
		Type5	14	8	325872.0	18	1	57.1	1641.0	---	---
		Type5	14	7	172999.0	18	1	60.8	1979.0	---	---
		Type5	14	6	20319.0	18	1	58.3	1429.0	---	---
		Type5	14	5	497624.0	18	1	51.7	1447.0	---	---
		Type5	14	4	343941.0	18	2	72.3	1094.0	1916.0	---
		Type5	14	3	190900.0	18	3	84.9	1894.0	1948.0	1118.0
		Type5	14	2	39025.0	18	3	86.9	1044.0	1152.0	1148.0
		Type5	14	17	441296.0	18	1	51.2	1237.0	---	---
		Type5	14	0	361323.0	18	3	93.3	1983.0	1912.0	1535.0
		Type5	14	18	592780.0	18	2	74.1	1471.0	1245.0	---
		Type5	14	1	515261.0	18	2	69.1	1102.0	1794.0	---
11AX40MIMO	5270	Type5	14	7	172999.0	18	1	60.8	1979.0	---	---
		Type5	14	16	288306.0	18	1	56.5	1483.0	---	---
		Type5	14	15	134759.0	18	3	91.2	1382.0	1832.0	1661.0
		Type5	14	14	610798.0	18	2	67.2	1625.0	1881.0	---
		Type5	14	13	458804.0	18	2	70.0	1759.0	1291.0	---
		Type5	14	12	307096.0	18	1	59.8	1552.0	---	---
		Type5	14	11	153647.0	18	3	90.9	1261.0	1566.0	1370.0
		Type5	14	10	1489.0	18	2	72.0	1909.0	1297.0	---
		Type5	14	17	441296.0	18	1	51.2	1237.0	---	---
		Type5	14	8	325872.0	18	1	57.1	1641.0	---	---
		Type5	14	18	592780.0	18	2	74.1	1471.0	1245.0	---
		Type5	14	6	20319.0	18	1	58.3	1429.0	---	---
		Type5	14	5	497624.0	18	1	51.7	1447.0	---	---
		Type5	14	4	343941.0	18	2	72.3	1094.0	1916.0	---
		Type5	14	3	190900.0	18	3	84.9	1894.0	1948.0	1118.0
		Type5	14	2	39025.0	18	3	86.9	1044.0	1152.0	1148.0

	5510	Type5	14	1	515261.0	18	2	69.1	1102.0	1794.0	---
		Type5	14	0	361323.0	18	3	93.3	1983.0	1912.0	1535.0
		Type5	14	9	475841.0	18	3	88.9	1886.0	1964.0	1489.0
		Type5	14	11	153647.0	18	3	90.9	1261.0	1566.0	1370.0
		Type5	14	1	515261.0	18	2	69.1	1102.0	1794.0	---
		Type5	14	2	39025.0	18	3	86.9	1044.0	1152.0	1148.0
		Type5	14	4	343941.0	18	2	72.3	1094.0	1916.0	---
		Type5	14	6	20319.0	18	1	58.3	1429.0	---	---
		Type5	14	7	172999.0	18	1	60.8	1979.0	---	---
		Type5	14	8	325872.0	18	1	57.1	1641.0	---	---
		Type5	14	0	361323.0	18	3	93.3	1983.0	1912.0	1535.0
		Type5	14	10	1489.0	18	2	72.0	1909.0	1297.0	---
		Type5	14	3	190900.0	18	3	84.9	1894.0	1948.0	1118.0
		Type5	14	12	307096.0	18	1	59.8	1552.0	---	---
		Type5	14	13	458804.0	18	2	70.0	1759.0	1291.0	---
		Type5	14	14	610798.0	18	2	67.2	1625.0	1881.0	---
		Type5	14	15	134759.0	18	3	91.2	1382.0	1832.0	1661.0
		Type5	14	16	288306.0	18	1	56.5	1483.0	---	---
		Type5	14	17	441296.0	18	1	51.2	1237.0	---	---
		Type5	14	18	592780.0	18	2	74.1	1471.0	1245.0	---
11AX80MIMO	5290	Type5	14	9	475841.0	18	3	88.9	1886.0	1964.0	1489.0
		Type5	14	5	497624.0	18	1	51.7	1447.0	---	---
		Type5	14	11	153647.0	18	3	90.9	1261.0	1566.0	1370.0
		Type5	14	17	441296.0	18	1	51.2	1237.0	---	---
		Type5	14	0	361323.0	18	3	93.3	1983.0	1912.0	1535.0
		Type5	14	16	288306.0	18	1	56.5	1483.0	---	---
		Type5	14	15	134759.0	18	3	91.2	1382.0	1832.0	1661.0
		Type5	14	14	610798.0	18	2	67.2	1625.0	1881.0	---
		Type5	14	12	307096.0	18	1	59.8	1552.0	---	---
		Type5	14	10	1489.0	18	2	72.0	1909.0	1297.0	---
		Type5	14	9	475841.0	18	3	88.9	1886.0	1964.0	1489.0
		Type5	14	3	190900.0	18	3	84.9	1894.0	1948.0	1118.0
		Type5	14	7	172999.0	18	1	60.8	1979.0	---	---
		Type5	14	6	20319.0	18	1	58.3	1429.0	---	---
		Type5	14	1	515261.0	18	2	69.1	1102.0	1794.0	---
		Type5	14	5	497624.0	18	1	51.7	1447.0	---	---
		Type5	14	18	592780.0	18	2	74.1	1471.0	1245.0	---
		Type5	14	4	343941.0	18	2	72.3	1094.0	1916.0	---
		Type5	14	8	325872.0	18	1	57.1	1641.0	---	---
		Type5	14	13	458804.0	18	2	70.0	1759.0	1291.0	---
		Type5	14	2	39025.0	18	3	86.9	1044.0	1152.0	1148.0
	5530	Type5	14	10	1489.0	18	2	72.0	1909.0	1297.0	---
		Type5	14	11	153647.0	18	3	90.9	1261.0	1566.0	1370.0
		Type5	14	12	307096.0	18	1	59.8	1552.0	---	---
		Type5	14	13	458804.0	18	2	70.0	1759.0	1291.0	---
		Type5	14	14	610798.0	18	2	67.2	1625.0	1881.0	---
		Type5	14	16	288306.0	18	1	56.5	1483.0	---	---
		Type5	14	7	172999.0	18	1	60.8	1979.0	---	---
		Type5	14	17	441296.0	18	1	51.2	1237.0	---	---
		Type5	14	15	134759.0	18	3	91.2	1382.0	1832.0	1661.0
		Type5	14	18	592780.0	18	2	74.1	1471.0	1245.0	---
		Type5	14	6	20319.0	18	1	58.3	1429.0	---	---
		Type5	14	5	497624.0	18	1	51.7	1447.0	---	---
		Type5	14	4	343941.0	18	2	72.3	1094.0	1916.0	---
		Type5	14	3	190900.0	18	3	84.9	1894.0	1948.0	1118.0
		Type5	14	2	39025.0	18	3	86.9	1044.0	1152.0	1148.0
		Type5	14	1	515261.0	18	2	69.1	1102.0	1794.0	---
		Type5	14	0	361323.0	18	3	93.3	1983.0	1912.0	1535.0

11AX160MIMO	5250	Type5	14	8	325872.0	18	1	57.1	1641.0	---	---
		Type5	14	9	475841.0	18	3	88.9	1886.0	1964.0	1489.0
		Type5	14	8	325872.0	18	1	57.1	1641.0	---	---
		Type5	14	7	172999.0	18	1	60.8	1979.0	---	---
		Type5	14	6	20319.0	18	1	58.3	1429.0	---	---
		Type5	14	4	343941.0	18	2	72.3	1094.0	1916.0	---
		Type5	14	2	39025.0	18	3	86.9	1044.0	1152.0	1148.0
		Type5	14	9	475841.0	18	3	88.9	1886.0	1964.0	1489.0
		Type5	14	0	361323.0	18	3	93.3	1983.0	1912.0	1535.0
		Type5	14	5	497624.0	18	1	51.7	1447.0	---	---
		Type5	14	1	515261.0	18	2	69.1	1102.0	1794.0	---
		Type5	14	18	592780.0	18	2	74.1	1471.0	1245.0	---
		Type5	14	11	153647.0	18	3	90.9	1261.0	1566.0	1370.0
		Type5	14	12	307096.0	18	1	59.8	1552.0	---	---
		Type5	14	13	458804.0	18	2	70.0	1759.0	1291.0	---
		Type5	14	14	610798.0	18	2	67.2	1625.0	1881.0	---
		Type5	14	15	134759.0	18	3	91.2	1382.0	1832.0	1661.0
		Type5	14	16	288306.0	18	1	56.5	1483.0	---	---
		Type5	14	17	441296.0	18	1	51.2	1237.0	---	---
		Type5	14	3	190900.0	18	3	84.9	1894.0	1948.0	1118.0
		Type5	14	10	1489.0	18	2	72.0	1909.0	1297.0	---
	5570	Type5	14	11	153647.0	18	3	90.9	1261.0	1566.0	1370.0
		Type5	14	12	307096.0	18	1	59.8	1552.0	---	---
		Type5	14	13	458804.0	18	2	70.0	1759.0	1291.0	---
		Type5	14	14	610798.0	18	2	67.2	1625.0	1881.0	---
		Type5	14	15	134759.0	18	3	91.2	1382.0	1832.0	1661.0
		Type5	14	10	1489.0	18	2	72.0	1909.0	1297.0	---
		Type5	14	17	441296.0	18	1	51.2	1237.0	---	---
		Type5	14	3	190900.0	18	3	84.9	1894.0	1948.0	1118.0
		Type5	14	16	288306.0	18	1	56.5	1483.0	---	---
		Type5	14	9	475841.0	18	3	88.9	1886.0	1964.0	1489.0
		Type5	14	8	325872.0	18	1	57.1	1641.0	---	---
		Type5	14	7	172999.0	18	1	60.8	1979.0	---	---
		Type5	14	6	20319.0	18	1	58.3	1429.0	---	---
		Type5	14	4	343941.0	18	2	72.3	1094.0	1916.0	---
		Type5	14	2	39025.0	18	3	86.9	1044.0	1152.0	1148.0
		Type5	14	1	515261.0	18	2	69.1	1102.0	1794.0	---
		Type5	14	0	361323.0	18	3	93.3	1983.0	1912.0	1535.0
		Type5	14	18	592780.0	18	2	74.1	1471.0	1245.0	---
		Type5	14	5	497624.0	18	1	51.7	1447.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MIMO	5260	Type5	15	9	314500.0	12	2	72.4	1030.0	1343.0	---
		Type5	15	0	158286.0	12	2	76.9	1110.0	1140.0	---
		Type5	15	12	81611.0	12	2	66.7	1722.0	1122.0	---
		Type5	15	10	522447.0	12	1	53.8	1327.0	---	---
		Type5	15	13	288948.0	12	2	82.5	1404.0	1019.0	---
		Type5	15	8	107117.0	12	2	78.7	1804.0	1168.0	---
		Type5	15	7	755333.0	12	1	51.7	1603.0	---	---
		Type5	15	6	548208.0	12	1	53.2	1024.0	---	---
		Type5	15	5	340207.0	12	1	65.4	1944.0	---	---
		Type5	15	4	132455.0	12	3	83.8	1410.0	1097.0	1621.0
		Type5	15	3	780619.0	12	1	64.7	1902.0	---	---
		Type5	15	2	573452.0	12	1	62.9	1520.0	---	---
		Type5	15	1	366024.0	12	1	50.2	1316.0	---	---
		Type5	15	11	728517.0	12	2	73.6	1524.0	1553.0	---
	5500	Type5	15	6	548208.0	12	1	53.2	1024.0	---	---
		Type5	15	11	728517.0	12	2	73.6	1524.0	1553.0	---
		Type5	15	10	522447.0	12	1	53.8	1327.0	---	---
		Type5	15	9	314500.0	12	2	72.4	1030.0	1343.0	---
		Type5	15	8	107117.0	12	2	78.7	1804.0	1168.0	---
		Type5	15	7	755333.0	12	1	51.7	1603.0	---	---
		Type5	15	5	340207.0	12	1	65.4	1944.0	---	---
		Type5	15	4	132455.0	12	3	83.8	1410.0	1097.0	1621.0
		Type5	15	3	780619.0	12	1	64.7	1902.0	---	---
		Type5	15	2	573452.0	12	1	62.9	1520.0	---	---
		Type5	15	12	81611.0	12	2	66.7	1722.0	1122.0	---
		Type5	15	0	158286.0	12	2	76.9	1110.0	1140.0	---
11AX40MIMO	5270	Type5	15	13	288948.0	12	2	82.5	1404.0	1019.0	---
		Type5	15	0	158286.0	12	2	76.9	1110.0	1140.0	---
		Type5	15	1	366024.0	12	1	50.2	1316.0	---	---
		Type5	15	2	573452.0	12	1	62.9	1520.0	---	---
		Type5	15	3	780619.0	12	1	64.7	1902.0	---	---
		Type5	15	4	132455.0	12	3	83.8	1410.0	1097.0	1621.0
		Type5	15	5	340207.0	12	1	65.4	1944.0	---	---
		Type5	15	6	548208.0	12	1	53.2	1024.0	---	---
		Type5	15	7	755333.0	12	1	51.7	1603.0	---	---
		Type5	15	8	107117.0	12	2	78.7	1804.0	1168.0	---
		Type5	15	9	314500.0	12	2	72.4	1030.0	1343.0	---
		Type5	15	10	522447.0	12	1	53.8	1327.0	---	---
	5510	Type5	15	11	728517.0	12	2	73.6	1524.0	1553.0	---
		Type5	15	12	81611.0	12	2	66.7	1722.0	1122.0	---
		Type5	15	2	573452.0	12	1	62.9	1520.0	---	---
		Type5	15	13	288948.0	12	2	82.5	1404.0	1019.0	---
		Type5	15	12	81611.0	12	2	66.7	1722.0	1122.0	---
		Type5	15	11	728517.0	12	2	73.6	1524.0	1553.0	---
		Type5	15	10	522447.0	12	1	53.8	1327.0	---	---
		Type5	15	9	314500.0	12	2	72.4	1030.0	1343.0	---
		Type5	15	8	107117.0	12	2	78.7	1804.0	1168.0	---
		Type5	15	7	755333.0	12	1	51.7	1603.0	---	---
		Type5	15	6	548208.0	12	1	53.2	1024.0	---	---
		Type5	15	5	340207.0	12	1	65.4	1944.0	---	---
		Type5	15	3	780619.0	12	1	64.7	1902.0	---	---
		Type5	15	1	366024.0	12	1	50.2	1316.0	---	---

11AX80MIMO	5290	Type5	15	0	158286.0	12	2	76.9	1110.0	1140.0	---
		Type5	15	4	132455.0	12	3	83.8	1410.0	1097.0	1621.0
		Type5	15	8	107117.0	12	2	78.7	1804.0	1168.0	---
		Type5	15	12	81611.0	12	2	66.7	1722.0	1122.0	---
		Type5	15	0	158286.0	12	2	76.9	1110.0	1140.0	---
		Type5	15	11	728517.0	12	2	73.6	1524.0	1553.0	---
		Type5	15	9	314500.0	12	2	72.4	1030.0	1343.0	---
		Type5	15	7	755333.0	12	1	51.7	1603.0	---	---
		Type5	15	6	548208.0	12	1	53.2	1024.0	---	---
		Type5	15	5	340207.0	12	1	65.4	1944.0	---	---
		Type5	15	4	132455.0	12	3	83.8	1410.0	1097.0	1621.0
		Type5	15	13	288948.0	12	2	82.5	1404.0	1019.0	---
		Type5	15	3	780619.0	12	1	64.7	1902.0	---	---
		Type5	15	2	573452.0	12	1	62.9	1520.0	---	---
		Type5	15	1	366024.0	12	1	50.2	1316.0	---	---
	5530	Type5	15	10	522447.0	12	1	53.8	1327.0	---	---
		Type5	15	12	81611.0	12	2	66.7	1722.0	1122.0	---
		Type5	15	5	340207.0	12	1	65.4	1944.0	---	---
		Type5	15	11	728517.0	12	2	73.6	1524.0	1553.0	---
		Type5	15	10	522447.0	12	1	53.8	1327.0	---	---
		Type5	15	9	314500.0	12	2	72.4	1030.0	1343.0	---
		Type5	15	8	107117.0	12	2	78.7	1804.0	1168.0	---
		Type5	15	6	548208.0	12	1	53.2	1024.0	---	---
		Type5	15	3	780619.0	12	1	64.7	1902.0	---	---
		Type5	15	2	573452.0	12	1	62.9	1520.0	---	---
		Type5	15	1	366024.0	12	1	50.2	1316.0	---	---
		Type5	15	0	158286.0	12	2	76.9	1110.0	1140.0	---
		Type5	15	13	288948.0	12	2	82.5	1404.0	1019.0	---
		Type5	15	7	755333.0	12	1	51.7	1603.0	---	---
		Type5	15	4	132455.0	12	3	83.8	1410.0	1097.0	1621.0
11AX160MIMO	5250	Type5	15	4	132455.0	12	3	83.8	1410.0	1097.0	1621.0
		Type5	15	0	158286.0	12	2	76.9	1110.0	1140.0	---
		Type5	15	1	366024.0	12	1	50.2	1316.0	---	---
		Type5	15	3	780619.0	12	1	64.7	1902.0	---	---
		Type5	15	5	340207.0	12	1	65.4	1944.0	---	---
		Type5	15	6	548208.0	12	1	53.2	1024.0	---	---
		Type5	15	8	107117.0	12	2	78.7	1804.0	1168.0	---
		Type5	15	9	314500.0	12	2	72.4	1030.0	1343.0	---
		Type5	15	10	522447.0	12	1	53.8	1327.0	---	---
		Type5	15	11	728517.0	12	2	73.6	1524.0	1553.0	---
		Type5	15	12	81611.0	12	2	66.7	1722.0	1122.0	---
		Type5	15	13	288948.0	12	2	82.5	1404.0	1019.0	---
		Type5	15	7	755333.0	12	1	51.7	1603.0	---	---
		Type5	15	2	573452.0	12	1	62.9	1520.0	---	---
	5570	Type5	15	2	573452.0	12	1	62.9	1520.0	---	---
		Type5	15	12	81611.0	12	2	66.7	1722.0	1122.0	---
		Type5	15	11	728517.0	12	2	73.6	1524.0	1553.0	---
		Type5	15	10	522447.0	12	1	53.8	1327.0	---	---
		Type5	15	9	314500.0	12	2	72.4	1030.0	1343.0	---
		Type5	15	8	107117.0	12	2	78.7	1804.0	1168.0	---
		Type5	15	7	755333.0	12	1	51.7	1603.0	---	---
		Type5	15	6	548208.0	12	1	53.2	1024.0	---	---
		Type5	15	5	340207.0	12	1	65.4	1944.0	---	---
		Type5	15	3	780619.0	12	1	64.7	1902.0	---	---
		Type5	15	1	366024.0	12	1	50.2	1316.0	---	---
		Type5	15	0	158286.0	12	2	76.9	1110.0	1140.0	---
		Type5	15	13	288948.0	12	2	82.5	1404.0	1019.0	---
		Type5	15	4	132455.0	12	3	83.8	1410.0	1097.0	1621.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	16	13	436922.0	20	3	95.8	1192.0	1298.0	1844.0
		Type5	16	0	345766.0	20	3	87.6	1565.0	1055.0	1840.0
		Type5	16	18	563464.0	20	3	85.2	1732.0	1551.0	1189.0
		Type5	16	17	418579.0	20	3	91.9	1970.0	1978.0	1165.0
		Type5	16	16	274684.0	20	3	94.5	1296.0	1700.0	1283.0
		Type5	16	14	584015.0	20	1	55.2	1644.0	---	---
		Type5	16	19	112787.0	20	2	69.5	1038.0	1224.0	---
		Type5	16	12	293225.0	20	2	76.9	1226.0	1537.0	---
		Type5	16	11	147928.0	20	3	84.3	1593.0	1188.0	1788.0
		Type5	16	10	3515.0	20	3	86.4	1773.0	1966.0	1263.0
		Type5	16	2	39073.0	20	3	84.8	1534.0	1889.0	1463.0
		Type5	16	15	130832.0	20	1	59.0	1402.0	---	---
		Type5	16	1	490019.0	20	3	85.2	1735.0	1541.0	1408.0
		Type5	16	9	456884.0	20	1	62.1	1495.0	---	---
		Type5	16	3	183923.0	20	2	77.9	1749.0	1460.0	---
		Type5	16	4	328777.0	20	2	76.5	1518.0	1485.0	---
		Type5	16	5	474728.0	20	1	60.9	1540.0	---	---
		Type5	16	6	21394.0	20	2	83.0	1080.0	1010.0	---
		Type5	16	7	165992.0	20	2	80.4	1824.0	1752.0	---
		Type5	16	8	310973.0	20	2	67.5	1764.0	1181.0	---
	5500	Type5	16	9	456884.0	20	1	62.1	1495.0	---	---
		Type5	16	16	274684.0	20	3	94.5	1296.0	1700.0	1283.0
		Type5	16	15	130832.0	20	1	59.0	1402.0	---	---
		Type5	16	14	584015.0	20	1	55.2	1644.0	---	---
		Type5	16	13	436922.0	20	3	95.8	1192.0	1298.0	1844.0
		Type5	16	12	293225.0	20	2	76.9	1226.0	1537.0	---
		Type5	16	11	147928.0	20	3	84.3	1593.0	1188.0	1788.0
		Type5	16	10	3515.0	20	3	86.4	1773.0	1966.0	1263.0
		Type5	16	17	418579.0	20	3	91.9	1970.0	1978.0	1165.0
		Type5	16	8	310973.0	20	2	67.5	1764.0	1181.0	---
		Type5	16	7	165992.0	20	2	80.4	1824.0	1752.0	---
		Type5	16	6	21394.0	20	2	83.0	1080.0	1010.0	---
		Type5	16	5	474728.0	20	1	60.9	1540.0	---	---
		Type5	16	4	328777.0	20	2	76.5	1518.0	1485.0	---
		Type5	16	3	183923.0	20	2	77.9	1749.0	1460.0	---
		Type5	16	2	39073.0	20	3	84.8	1534.0	1889.0	1463.0
		Type5	16	18	563464.0	20	3	85.2	1732.0	1551.0	1189.0
		Type5	16	0	345766.0	20	3	87.6	1565.0	1055.0	1840.0
		Type5	16	19	112787.0	20	2	69.5	1038.0	1224.0	---
		Type5	16	1	490019.0	20	3	85.2	1735.0	1541.0	1408.0
11AX40MIMO	5270	Type5	16	8	310973.0	20	2	67.5	1764.0	1181.0	---
		Type5	16	17	418579.0	20	3	91.9	1970.0	1978.0	1165.0
		Type5	16	16	274684.0	20	3	94.5	1296.0	1700.0	1283.0
		Type5	16	15	130832.0	20	1	59.0	1402.0	---	---
		Type5	16	14	584015.0	20	1	55.2	1644.0	---	---
		Type5	16	13	436922.0	20	3	95.8	1192.0	1298.0	1844.0
		Type5	16	12	293225.0	20	2	76.9	1226.0	1537.0	---
		Type5	16	11	147928.0	20	3	84.3	1593.0	1188.0	1788.0
		Type5	16	18	563464.0	20	3	85.2	1732.0	1551.0	1189.0
		Type5	16	9	456884.0	20	1	62.1	1495.0	---	---
		Type5	16	19	112787.0	20	2	69.5	1038.0	1224.0	---
		Type5	16	7	165992.0	20	2	80.4	1824.0	1752.0	---
		Type5	16	6	21394.0	20	2	83.0	1080.0	1010.0	---
		Type5	16	5	474728.0	20	1	60.9	1540.0	---	---

11AX80MIMO		Type5	16	4	328777.0	20	2	76.5	1518.0	1485.0	---
		Type5	16	3	183923.0	20	2	77.9	1749.0	1460.0	---
		Type5	16	2	39073.0	20	3	84.8	1534.0	1889.0	1463.0
		Type5	16	1	490019.0	20	3	85.2	1735.0	1541.0	1408.0
		Type5	16	0	345766.0	20	3	87.6	1565.0	1055.0	1840.0
		Type5	16	10	3515.0	20	3	86.4	1773.0	1966.0	1263.0
	5510	Type5	16	12	293225.0	20	2	76.9	1226.0	1537.0	---
		Type5	16	1	490019.0	20	3	85.2	1735.0	1541.0	1408.0
		Type5	16	2	39073.0	20	3	84.8	1534.0	1889.0	1463.0
		Type5	16	3	183923.0	20	2	77.9	1749.0	1460.0	---
		Type5	16	5	474728.0	20	1	60.9	1540.0	---	---
		Type5	16	7	165992.0	20	2	80.4	1824.0	1752.0	---
		Type5	16	8	310973.0	20	2	67.5	1764.0	1181.0	---
		Type5	16	9	456884.0	20	1	62.1	1495.0	---	---
		Type5	16	0	345766.0	20	3	87.6	1565.0	1055.0	1840.0
		Type5	16	11	147928.0	20	3	84.3	1593.0	1188.0	1788.0
		Type5	16	4	328777.0	20	2	76.5	1518.0	1485.0	---
		Type5	16	13	436922.0	20	3	95.8	1192.0	1298.0	1844.0
		Type5	16	14	584015.0	20	1	55.2	1644.0	---	---
		Type5	16	15	130832.0	20	1	59.0	1402.0	---	---
		Type5	16	16	274684.0	20	3	94.5	1296.0	1700.0	1283.0
		Type5	16	17	418579.0	20	3	91.9	1970.0	1978.0	1165.0
		Type5	16	18	563464.0	20	3	85.2	1732.0	1551.0	1189.0
		Type5	16	19	112787.0	20	2	69.5	1038.0	1224.0	---
		Type5	16	10	3515.0	20	3	86.4	1773.0	1966.0	1263.0
		Type5	16	6	21394.0	20	2	83.0	1080.0	1010.0	---
	5290	Type5	16	12	293225.0	20	2	76.9	1226.0	1537.0	---
		Type5	16	18	563464.0	20	3	85.2	1732.0	1551.0	1189.0
		Type5	16	0	345766.0	20	3	87.6	1565.0	1055.0	1840.0
		Type5	16	17	418579.0	20	3	91.9	1970.0	1978.0	1165.0
		Type5	16	16	274684.0	20	3	94.5	1296.0	1700.0	1283.0
		Type5	16	15	130832.0	20	1	59.0	1402.0	---	---
		Type5	16	13	436922.0	20	3	95.8	1192.0	1298.0	1844.0
		Type5	16	11	147928.0	20	3	84.3	1593.0	1188.0	1788.0
		Type5	16	10	3515.0	20	3	86.4	1773.0	1966.0	1263.0
		Type5	16	9	456884.0	20	1	62.1	1495.0	---	---
		Type5	16	2	39073.0	20	3	84.8	1534.0	1889.0	1463.0
		Type5	16	7	165992.0	20	2	80.4	1824.0	1752.0	---
		Type5	16	6	21394.0	20	2	83.0	1080.0	1010.0	---
		Type5	16	19	112787.0	20	2	69.5	1038.0	1224.0	---
		Type5	16	5	474728.0	20	1	60.9	1540.0	---	---
		Type5	16	1	490019.0	20	3	85.2	1735.0	1541.0	1408.0
		Type5	16	4	328777.0	20	2	76.5	1518.0	1485.0	---
		Type5	16	3	183923.0	20	2	77.9	1749.0	1460.0	---
		Type5	16	8	310973.0	20	2	67.5	1764.0	1181.0	---
		Type5	16	14	584015.0	20	1	55.2	1644.0	---	---
	5530	Type5	16	9	456884.0	20	1	62.1	1495.0	---	---
		Type5	16	11	147928.0	20	3	84.3	1593.0	1188.0	1788.0
		Type5	16	12	293225.0	20	2	76.9	1226.0	1537.0	---
		Type5	16	13	436922.0	20	3	95.8	1192.0	1298.0	1844.0
		Type5	16	14	584015.0	20	1	55.2	1644.0	---	---
		Type5	16	15	130832.0	20	1	59.0	1402.0	---	---
		Type5	16	17	418579.0	20	3	91.9	1970.0	1978.0	1165.0
		Type5	16	8	310973.0	20	2	67.5	1764.0	1181.0	---
		Type5	16	18	563464.0	20	3	85.2	1732.0	1551.0	1189.0
		Type5	16	16	274684.0	20	3	94.5	1296.0	1700.0	1283.0
		Type5	16	19	112787.0	20	2	69.5	1038.0	1224.0	---
		Type5	16	6	21394.0	20	2	83.0	1080.0	1010.0	---

		Type5	16	5	474728.0	20	1	60.9	1540.0	---	---
		Type5	16	4	328777.0	20	2	76.5	1518.0	1485.0	---
		Type5	16	3	183923.0	20	2	77.9	1749.0	1460.0	---
		Type5	16	2	39073.0	20	3	84.8	1534.0	1889.0	1463.0
		Type5	16	1	490019.0	20	3	85.2	1735.0	1541.0	1408.0
		Type5	16	0	345766.0	20	3	87.6	1565.0	1055.0	1840.0
		Type5	16	7	165992.0	20	2	80.4	1824.0	1752.0	---
		Type5	16	10	3515.0	20	3	86.4	1773.0	1966.0	1263.0
11AX160MIMO	5250	Type5	16	8	310973.0	20	2	67.5	1764.0	1181.0	---
		Type5	16	7	165992.0	20	2	80.4	1824.0	1752.0	---
		Type5	16	6	21394.0	20	2	83.0	1080.0	1010.0	---
		Type5	16	4	328777.0	20	2	76.5	1518.0	1485.0	---
		Type5	16	2	39073.0	20	3	84.8	1534.0	1889.0	1463.0
		Type5	16	9	456884.0	20	1	62.1	1495.0	---	---
		Type5	16	0	345766.0	20	3	87.6	1565.0	1055.0	1840.0
		Type5	16	5	474728.0	20	1	60.9	1540.0	---	---
		Type5	16	1	490019.0	20	3	85.2	1735.0	1541.0	1408.0
		Type5	16	19	112787.0	20	2	69.5	1038.0	1224.0	---
		Type5	16	11	147928.0	20	3	84.3	1593.0	1188.0	1788.0
		Type5	16	12	293225.0	20	2	76.9	1226.0	1537.0	---
		Type5	16	13	436922.0	20	3	95.8	1192.0	1298.0	1844.0
		Type5	16	14	584015.0	20	1	55.2	1644.0	---	---
		Type5	16	15	130832.0	20	1	59.0	1402.0	---	---
		Type5	16	16	274684.0	20	3	94.5	1296.0	1700.0	1283.0
		Type5	16	17	418579.0	20	3	91.9	1970.0	1978.0	1165.0
		Type5	16	18	563464.0	20	3	85.2	1732.0	1551.0	1189.0
		Type5	16	3	183923.0	20	2	77.9	1749.0	1460.0	---
		Type5	16	10	3515.0	20	3	86.4	1773.0	1966.0	1263.0
	5570	Type5	16	11	147928.0	20	3	84.3	1593.0	1188.0	1788.0
		Type5	16	12	293225.0	20	2	76.9	1226.0	1537.0	---
		Type5	16	13	436922.0	20	3	95.8	1192.0	1298.0	1844.0
		Type5	16	14	584015.0	20	1	55.2	1644.0	---	---
		Type5	16	15	130832.0	20	1	59.0	1402.0	---	---
		Type5	16	16	274684.0	20	3	94.5	1296.0	1700.0	1283.0
		Type5	16	10	3515.0	20	3	86.4	1773.0	1966.0	1263.0
		Type5	16	18	563464.0	20	3	85.2	1732.0	1551.0	1189.0
		Type5	16	3	183923.0	20	2	77.9	1749.0	1460.0	---
		Type5	16	17	418579.0	20	3	91.9	1970.0	1978.0	1165.0
		Type5	16	9	456884.0	20	1	62.1	1495.0	---	---
		Type5	16	8	310973.0	20	2	67.5	1764.0	1181.0	---
		Type5	16	7	165992.0	20	2	80.4	1824.0	1752.0	---
		Type5	16	6	21394.0	20	2	83.0	1080.0	1010.0	---
		Type5	16	4	328777.0	20	2	76.5	1518.0	1485.0	---
		Type5	16	2	39073.0	20	3	84.8	1534.0	1889.0	1463.0
		Type5	16	1	490019.0	20	3	85.2	1735.0	1541.0	1408.0
		Type5	16	0	345766.0	20	3	87.6	1565.0	1055.0	1840.0
		Type5	16	19	112787.0	20	2	69.5	1038.0	1224.0	---
		Type5	16	5	474728.0	20	1	60.9	1540.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	17	7	128373.0	10	3	100.0	1375.0	1438.0	1595.0
		Type5	17	0	429224.0	10	3	86.4	1259.0	1918.0	1455.0
		Type5	17	10	855665.0	10	1	53.3	1016.0	---	---
		Type5	17	8	370379.0	10	2	79.6	1239.0	1705.0	---
		Type5	17	11	98897.0	10	1	65.3	1709.0	---	---
		Type5	17	6	883823.0	10	2	69.1	1279.0	1639.0	---
		Type5	17	5	641915.0	10	2	69.4	1503.0	1546.0	---
		Type5	17	4	400824.0	10	1	53.1	1303.0	---	---
		Type5	17	3	158603.0	10	1	54.3	1335.0	---	---
		Type5	17	2	912880.0	10	2	80.4	1816.0	1899.0	---
	5500	Type5	17	1	670241.0	10	3	92.2	1598.0	1719.0	1895.0
		Type5	17	9	611194.0	10	3	88.4	1374.0	1579.0	1623.0
		Type5	17	5	641915.0	10	2	69.4	1503.0	1546.0	---
		Type5	17	9	611194.0	10	3	88.4	1374.0	1579.0	1623.0
		Type5	17	8	370379.0	10	2	79.6	1239.0	1705.0	---
		Type5	17	7	128373.0	10	3	100.0	1375.0	1438.0	1595.0
		Type5	17	6	883823.0	10	2	69.1	1279.0	1639.0	---
		Type5	17	4	400824.0	10	1	53.1	1303.0	---	---
		Type5	17	3	158603.0	10	1	54.3	1335.0	---	---
		Type5	17	2	912880.0	10	2	80.4	1816.0	1899.0	---
11AX40MIMO	5270	Type5	17	10	855665.0	10	1	53.3	1016.0	---	---
		Type5	17	0	429224.0	10	3	86.4	1259.0	1918.0	1455.0
		Type5	17	1	670241.0	10	3	92.2	1598.0	1719.0	1895.0
		Type5	17	2	912880.0	10	2	80.4	1816.0	1899.0	---
		Type5	17	3	158603.0	10	1	54.3	1335.0	---	---
		Type5	17	4	400824.0	10	1	53.1	1303.0	---	---
		Type5	17	5	641915.0	10	2	69.4	1503.0	1546.0	---
		Type5	17	6	883823.0	10	2	69.1	1279.0	1639.0	---
		Type5	17	7	128373.0	10	3	100.0	1375.0	1438.0	1595.0
		Type5	17	8	370379.0	10	2	79.6	1239.0	1705.0	---
	5510	Type5	17	9	611194.0	10	3	88.4	1374.0	1579.0	1623.0
		Type5	17	10	855665.0	10	1	53.3	1016.0	---	---
		Type5	17	2	912880.0	10	2	80.4	1816.0	1899.0	---
		Type5	17	11	98897.0	10	1	65.3	1709.0	---	---
		Type5	17	10	855665.0	10	1	53.3	1016.0	---	---
		Type5	17	9	611194.0	10	3	88.4	1374.0	1579.0	1623.0
		Type5	17	8	370379.0	10	2	79.6	1239.0	1705.0	---
		Type5	17	7	128373.0	10	3	100.0	1375.0	1438.0	1595.0
		Type5	17	6	883823.0	10	2	69.1	1279.0	1639.0	---
		Type5	17	5	641915.0	10	2	69.4	1503.0	1546.0	---
11AX80MIMO	5290	Type5	17	3	158603.0	10	1	54.3	1335.0	---	---
		Type5	17	1	670241.0	10	3	92.2	1598.0	1719.0	1895.0
		Type5	17	0	429224.0	10	3	86.4	1259.0	1918.0	1455.0
		Type5	17	4	400824.0	10	1	53.1	1303.0	---	---
		Type5	17	6	883823.0	10	2	69.1	1279.0	1639.0	---
		Type5	17	5	641915.0	10	2	69.4	1503.0	1546.0	---

		Type5	17	4	400824.0	10	1	53.1	1303.0	---	---
		Type5	17	11	98897.0	10	1	65.3	1709.0	---	---
		Type5	17	3	158603.0	10	1	54.3	1335.0	---	---
		Type5	17	2	912880.0	10	2	80.4	1816.0	1899.0	---
		Type5	17	1	670241.0	10	3	92.2	1598.0	1719.0	1895.0
		Type5	17	8	370379.0	10	2	79.6	1239.0	1705.0	---
	5530	Type5	17	10	855665.0	10	1	53.3	1016.0	---	---
		Type5	17	4	400824.0	10	1	53.1	1303.0	---	---
		Type5	17	9	611194.0	10	3	88.4	1374.0	1579.0	1623.0
		Type5	17	8	370379.0	10	2	79.6	1239.0	1705.0	---
		Type5	17	7	128373.0	10	3	100.0	1375.0	1438.0	1595.0
		Type5	17	5	641915.0	10	2	69.4	1503.0	1546.0	---
		Type5	17	2	912880.0	10	2	80.4	1816.0	1899.0	---
		Type5	17	1	670241.0	10	3	92.2	1598.0	1719.0	1895.0
		Type5	17	0	429224.0	10	3	86.4	1259.0	1918.0	1455.0
		Type5	17	11	98897.0	10	1	65.3	1709.0	---	---
		Type5	17	6	883823.0	10	2	69.1	1279.0	1639.0	---
		Type5	17	3	158603.0	10	1	54.3	1335.0	---	---
11AX160MIMO	5250	Type5	17	3	158603.0	10	1	54.3	1335.0	---	---
		Type5	17	0	429224.0	10	3	86.4	1259.0	1918.0	1455.0
		Type5	17	2	912880.0	10	2	80.4	1816.0	1899.0	---
		Type5	17	4	400824.0	10	1	53.1	1303.0	---	---
		Type5	17	5	641915.0	10	2	69.4	1503.0	1546.0	---
		Type5	17	7	128373.0	10	3	100.0	1375.0	1438.0	1595.0
		Type5	17	8	370379.0	10	2	79.6	1239.0	1705.0	---
		Type5	17	9	611194.0	10	3	88.4	1374.0	1579.0	1623.0
		Type5	17	10	855665.0	10	1	53.3	1016.0	---	---
		Type5	17	11	98897.0	10	1	65.3	1709.0	---	---
		Type5	17	6	883823.0	10	2	69.1	1279.0	1639.0	---
		Type5	17	1	670241.0	10	3	92.2	1598.0	1719.0	1895.0
	5570	Type5	17	1	670241.0	10	3	92.2	1598.0	1719.0	1895.0
		Type5	17	10	855665.0	10	1	53.3	1016.0	---	---
		Type5	17	9	611194.0	10	3	88.4	1374.0	1579.0	1623.0
		Type5	17	8	370379.0	10	2	79.6	1239.0	1705.0	---
		Type5	17	7	128373.0	10	3	100.0	1375.0	1438.0	1595.0
		Type5	17	6	883823.0	10	2	69.1	1279.0	1639.0	---
		Type5	17	5	641915.0	10	2	69.4	1503.0	1546.0	---
		Type5	17	4	400824.0	10	1	53.1	1303.0	---	---
		Type5	17	2	912880.0	10	2	80.4	1816.0	1899.0	---
		Type5	17	0	429224.0	10	3	86.4	1259.0	1918.0	1455.0
		Type5	17	11	98897.0	10	1	65.3	1709.0	---	---
		Type5	17	3	158603.0	10	1	54.3	1335.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	18	9	447400.0	12	3	96.6	1525.0	1036.0	1385.0
		Type5	18	0	292143.0	12	1	55.3	1920.0	---	---
		Type5	18	12	215435.0	12	2	78.4	1047.0	1109.0	---
		Type5	18	10	654516.0	12	2	82.7	1710.0	1990.0	---
		Type5	18	13	421325.0	12	3	99.5	1299.0	1965.0	1869.0
		Type5	18	8	240319.0	12	3	91.1	1539.0	1783.0	1172.0
		Type5	18	7	33519.0	12	3	90.3	1660.0	1853.0	1123.0
		Type5	18	6	680544.0	12	2	80.0	1119.0	1913.0	---
		Type5	18	5	474469.0	12	1	63.3	1095.0	---	---
		Type5	18	4	266161.0	12	2	82.5	1875.0	1431.0	---
		Type5	18	3	58989.0	12	3	84.8	1131.0	1761.0	1721.0
		Type5	18	2	706377.0	12	2	72.3	1610.0	1039.0	---
		Type5	18	1	499633.0	12	1	58.3	1797.0	---	---
		Type5	18	11	8083.0	12	1	50.7	1234.0	---	---
	5500	Type5	18	6	680544.0	12	2	80.0	1119.0	1913.0	---
		Type5	18	11	8083.0	12	1	50.7	1234.0	---	---
		Type5	18	10	654516.0	12	2	82.7	1710.0	1990.0	---
		Type5	18	9	447400.0	12	3	96.6	1525.0	1036.0	1385.0
		Type5	18	8	240319.0	12	3	91.1	1539.0	1783.0	1172.0
		Type5	18	7	33519.0	12	3	90.3	1660.0	1853.0	1123.0
		Type5	18	5	474469.0	12	1	63.3	1095.0	---	---
		Type5	18	4	266161.0	12	2	82.5	1875.0	1431.0	---
		Type5	18	3	58989.0	12	3	84.8	1131.0	1761.0	1721.0
		Type5	18	2	706377.0	12	2	72.3	1610.0	1039.0	---
		Type5	18	12	215435.0	12	2	78.4	1047.0	1109.0	---
		Type5	18	0	292143.0	12	1	55.3	1920.0	---	---
11AX40MIMO	5270	Type5	18	13	421325.0	12	3	99.5	1299.0	1965.0	1869.0
		Type5	18	0	292143.0	12	1	55.3	1920.0	---	---
		Type5	18	1	499633.0	12	1	58.3	1797.0	---	---
		Type5	18	2	706377.0	12	2	72.3	1610.0	1039.0	---
		Type5	18	3	58989.0	12	3	84.8	1131.0	1761.0	1721.0
		Type5	18	4	266161.0	12	2	82.5	1875.0	1431.0	---
		Type5	18	5	474469.0	12	1	63.3	1095.0	---	---
		Type5	18	6	680544.0	12	2	80.0	1119.0	1913.0	---
		Type5	18	7	33519.0	12	3	90.3	1660.0	1853.0	1123.0
		Type5	18	8	240319.0	12	3	91.1	1539.0	1783.0	1172.0
		Type5	18	9	447400.0	12	3	96.6	1525.0	1036.0	1385.0
		Type5	18	10	654516.0	12	2	82.7	1710.0	1990.0	---
	5510	Type5	18	11	8083.0	12	1	50.7	1234.0	---	---
		Type5	18	12	215435.0	12	2	78.4	1047.0	1109.0	---
		Type5	18	2	706377.0	12	2	72.3	1610.0	1039.0	---
		Type5	18	13	421325.0	12	3	99.5	1299.0	1965.0	1869.0
		Type5	18	12	215435.0	12	2	78.4	1047.0	1109.0	---
		Type5	18	11	8083.0	12	1	50.7	1234.0	---	---
		Type5	18	10	654516.0	12	2	82.7	1710.0	1990.0	---
		Type5	18	9	447400.0	12	3	96.6	1525.0	1036.0	1385.0
		Type5	18	8	240319.0	12	3	91.1	1539.0	1783.0	1172.0
		Type5	18	7	33519.0	12	3	90.3	1660.0	1853.0	1123.0
		Type5	18	6	680544.0	12	2	80.0	1119.0	1913.0	---
		Type5	18	5	474469.0	12	1	63.3	1095.0	---	---
		Type5	18	3	58989.0	12	3	84.8	1131.0	1761.0	1721.0
		Type5	18	1	499633.0	12	1	58.3	1797.0	---	---

11AX80MIMO	5290	Type5	18	0	292143.0	12	1	55.3	1920.0	---	---
		Type5	18	4	266161.0	12	2	82.5	1875.0	1431.0	---
		Type5	18	8	240319.0	12	3	91.1	1539.0	1783.0	1172.0
		Type5	18	12	215435.0	12	2	78.4	1047.0	1109.0	---
		Type5	18	0	292143.0	12	1	55.3	1920.0	---	---
		Type5	18	11	8083.0	12	1	50.7	1234.0	---	---
		Type5	18	9	447400.0	12	3	96.6	1525.0	1036.0	1385.0
		Type5	18	7	33519.0	12	3	90.3	1660.0	1853.0	1123.0
		Type5	18	6	680544.0	12	2	80.0	1119.0	1913.0	---
		Type5	18	5	474469.0	12	1	63.3	1095.0	---	---
		Type5	18	4	266161.0	12	2	82.5	1875.0	1431.0	---
		Type5	18	13	421325.0	12	3	99.5	1299.0	1965.0	1869.0
		Type5	18	3	58989.0	12	3	84.8	1131.0	1761.0	1721.0
		Type5	18	2	706377.0	12	2	72.3	1610.0	1039.0	---
		Type5	18	1	499633.0	12	1	58.3	1797.0	---	---
	5530	Type5	18	10	654516.0	12	2	82.7	1710.0	1990.0	---
		Type5	18	12	215435.0	12	2	78.4	1047.0	1109.0	---
		Type5	18	5	474469.0	12	1	63.3	1095.0	---	---
		Type5	18	11	8083.0	12	1	50.7	1234.0	---	---
		Type5	18	10	654516.0	12	2	82.7	1710.0	1990.0	---
		Type5	18	9	447400.0	12	3	96.6	1525.0	1036.0	1385.0
		Type5	18	8	240319.0	12	3	91.1	1539.0	1783.0	1172.0
		Type5	18	6	680544.0	12	2	80.0	1119.0	1913.0	---
		Type5	18	3	58989.0	12	3	84.8	1131.0	1761.0	1721.0
		Type5	18	2	706377.0	12	2	72.3	1610.0	1039.0	---
		Type5	18	1	499633.0	12	1	58.3	1797.0	---	---
		Type5	18	0	292143.0	12	1	55.3	1920.0	---	---
		Type5	18	13	421325.0	12	3	99.5	1299.0	1965.0	1869.0
		Type5	18	7	33519.0	12	3	90.3	1660.0	1853.0	1123.0
		Type5	18	4	266161.0	12	2	82.5	1875.0	1431.0	---
11AX160MIMO	5250	Type5	18	4	266161.0	12	2	82.5	1875.0	1431.0	---
		Type5	18	0	292143.0	12	1	55.3	1920.0	---	---
		Type5	18	1	499633.0	12	1	58.3	1797.0	---	---
		Type5	18	3	58989.0	12	3	84.8	1131.0	1761.0	1721.0
		Type5	18	5	474469.0	12	1	63.3	1095.0	---	---
		Type5	18	6	680544.0	12	2	80.0	1119.0	1913.0	---
		Type5	18	8	240319.0	12	3	91.1	1539.0	1783.0	1172.0
		Type5	18	9	447400.0	12	3	96.6	1525.0	1036.0	1385.0
		Type5	18	10	654516.0	12	2	82.7	1710.0	1990.0	---
		Type5	18	11	8083.0	12	1	50.7	1234.0	---	---
		Type5	18	12	215435.0	12	2	78.4	1047.0	1109.0	---
		Type5	18	13	421325.0	12	3	99.5	1299.0	1965.0	1869.0
		Type5	18	7	33519.0	12	3	90.3	1660.0	1853.0	1123.0
		Type5	18	2	706377.0	12	2	72.3	1610.0	1039.0	---
	5570	Type5	18	2	706377.0	12	2	72.3	1610.0	1039.0	---
		Type5	18	12	215435.0	12	2	78.4	1047.0	1109.0	---
		Type5	18	11	8083.0	12	1	50.7	1234.0	---	---
		Type5	18	10	654516.0	12	2	82.7	1710.0	1990.0	---
		Type5	18	9	447400.0	12	3	96.6	1525.0	1036.0	1385.0
		Type5	18	8	240319.0	12	3	91.1	1539.0	1783.0	1172.0
		Type5	18	7	33519.0	12	3	90.3	1660.0	1853.0	1123.0
		Type5	18	6	680544.0	12	2	80.0	1119.0	1913.0	---
		Type5	18	5	474469.0	12	1	63.3	1095.0	---	---
		Type5	18	3	58989.0	12	3	84.8	1131.0	1761.0	1721.0
		Type5	18	1	499633.0	12	1	58.3	1797.0	---	---
		Type5	18	0	292143.0	12	1	55.3	1920.0	---	---
		Type5	18	13	421325.0	12	3	99.5	1299.0	1965.0	1869.0
		Type5	18	4	266161.0	12	2	82.5	1875.0	1431.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	19	7	432561.0	10	3	97.3	1790.0	1896.0	1367.0
		Type5	19	0	733725.0	10	3	88.6	1501.0	1067.0	1927.0
		Type5	19	10	162176.0	10	1	54.8	1084.0	---	---
		Type5	19	8	674004.0	10	3	96.2	1391.0	1787.0	1672.0
		Type5	19	11	403553.0	10	2	80.4	1850.0	1436.0	---
		Type5	19	6	191373.0	10	3	88.4	1997.0	1077.0	1366.0
		Type5	19	5	947923.0	10	1	62.0	1866.0	---	---
		Type5	19	4	705071.0	10	2	77.9	1642.0	1317.0	---
		Type5	19	3	462915.0	10	2	69.7	1751.0	1945.0	---
		Type5	19	2	221197.0	10	3	96.6	1086.0	1658.0	1324.0
		Type5	19	1	977882.0	10	1	57.4	1723.0	---	---
		Type5	19	9	915842.0	10	3	95.4	1020.0	1892.0	1414.0
	5500	Type5	19	5	947923.0	10	1	62.0	1866.0	---	---
		Type5	19	9	915842.0	10	3	95.4	1020.0	1892.0	1414.0
		Type5	19	8	674004.0	10	3	96.2	1391.0	1787.0	1672.0
		Type5	19	7	432561.0	10	3	97.3	1790.0	1896.0	1367.0
		Type5	19	6	191373.0	10	3	88.4	1997.0	1077.0	1366.0
		Type5	19	4	705071.0	10	2	77.9	1642.0	1317.0	---
		Type5	19	3	462915.0	10	2	69.7	1751.0	1945.0	---
		Type5	19	2	221197.0	10	3	96.6	1086.0	1658.0	1324.0
		Type5	19	10	162176.0	10	1	54.8	1084.0	---	---
		Type5	19	0	733725.0	10	3	88.6	1501.0	1067.0	1927.0
		Type5	19	11	403553.0	10	2	80.4	1850.0	1436.0	---
		Type5	19	1	977882.0	10	1	57.4	1723.0	---	---
11AX40MIMO	5270	Type5	19	11	403553.0	10	2	80.4	1850.0	1436.0	---
		Type5	19	0	733725.0	10	3	88.6	1501.0	1067.0	1927.0
		Type5	19	1	977882.0	10	1	57.4	1723.0	---	---
		Type5	19	2	221197.0	10	3	96.6	1086.0	1658.0	1324.0
		Type5	19	3	462915.0	10	2	69.7	1751.0	1945.0	---
		Type5	19	4	705071.0	10	2	77.9	1642.0	1317.0	---
		Type5	19	5	947923.0	10	1	62.0	1866.0	---	---
		Type5	19	6	191373.0	10	3	88.4	1997.0	1077.0	1366.0
		Type5	19	7	432561.0	10	3	97.3	1790.0	1896.0	1367.0
		Type5	19	8	674004.0	10	3	96.2	1391.0	1787.0	1672.0
		Type5	19	9	915842.0	10	3	95.4	1020.0	1892.0	1414.0
		Type5	19	10	162176.0	10	1	54.8	1084.0	---	---
	5510	Type5	19	2	221197.0	10	3	96.6	1086.0	1658.0	1324.0
		Type5	19	11	403553.0	10	2	80.4	1850.0	1436.0	---
		Type5	19	10	162176.0	10	1	54.8	1084.0	---	---
		Type5	19	9	915842.0	10	3	95.4	1020.0	1892.0	1414.0
		Type5	19	8	674004.0	10	3	96.2	1391.0	1787.0	1672.0
		Type5	19	7	432561.0	10	3	97.3	1790.0	1896.0	1367.0
		Type5	19	6	191373.0	10	3	88.4	1997.0	1077.0	1366.0
		Type5	19	5	947923.0	10	1	62.0	1866.0	---	---
		Type5	19	3	462915.0	10	2	69.7	1751.0	1945.0	---
		Type5	19	1	977882.0	10	1	57.4	1723.0	---	---
		Type5	19	0	733725.0	10	3	88.6	1501.0	1067.0	1927.0
		Type5	19	4	705071.0	10	2	77.9	1642.0	1317.0	---
11AX80MIMO	5290	Type5	19	6	191373.0	10	3	88.4	1997.0	1077.0	1366.0
		Type5	19	10	162176.0	10	1	54.8	1084.0	---	---
		Type5	19	0	733725.0	10	3	88.6	1501.0	1067.0	1927.0
		Type5	19	9	915842.0	10	3	95.4	1020.0	1892.0	1414.0
		Type5	19	7	432561.0	10	3	97.3	1790.0	1896.0	1367.0
		Type5	19	5	947923.0	10	1	62.0	1866.0	---	---

		Type5	19	4	705071.0	10	2	77.9	1642.0	1317.0	---
		Type5	19	11	403553.0	10	2	80.4	1850.0	1436.0	---
		Type5	19	3	462915.0	10	2	69.7	1751.0	1945.0	---
		Type5	19	2	221197.0	10	3	96.6	1086.0	1658.0	1324.0
		Type5	19	1	977882.0	10	1	57.4	1723.0	---	---
		Type5	19	8	674004.0	10	3	96.2	1391.0	1787.0	1672.0
	5530	Type5	19	10	162176.0	10	1	54.8	1084.0	---	---
		Type5	19	4	705071.0	10	2	77.9	1642.0	1317.0	---
		Type5	19	9	915842.0	10	3	95.4	1020.0	1892.0	1414.0
		Type5	19	8	674004.0	10	3	96.2	1391.0	1787.0	1672.0
		Type5	19	7	432561.0	10	3	97.3	1790.0	1896.0	1367.0
		Type5	19	5	947923.0	10	1	62.0	1866.0	---	---
		Type5	19	2	221197.0	10	3	96.6	1086.0	1658.0	1324.0
		Type5	19	1	977882.0	10	1	57.4	1723.0	---	---
		Type5	19	0	733725.0	10	3	88.6	1501.0	1067.0	1927.0
		Type5	19	11	403553.0	10	2	80.4	1850.0	1436.0	---
		Type5	19	6	191373.0	10	3	88.4	1997.0	1077.0	1366.0
		Type5	19	3	462915.0	10	2	69.7	1751.0	1945.0	---
11AX160MIMO	5250	Type5	19	3	462915.0	10	2	69.7	1751.0	1945.0	---
		Type5	19	0	733725.0	10	3	88.6	1501.0	1067.0	1927.0
		Type5	19	2	221197.0	10	3	96.6	1086.0	1658.0	1324.0
		Type5	19	4	705071.0	10	2	77.9	1642.0	1317.0	---
		Type5	19	5	947923.0	10	1	62.0	1866.0	---	---
		Type5	19	7	432561.0	10	3	97.3	1790.0	1896.0	1367.0
		Type5	19	8	674004.0	10	3	96.2	1391.0	1787.0	1672.0
		Type5	19	9	915842.0	10	3	95.4	1020.0	1892.0	1414.0
		Type5	19	10	162176.0	10	1	54.8	1084.0	---	---
		Type5	19	11	403553.0	10	2	80.4	1850.0	1436.0	---
		Type5	19	6	191373.0	10	3	88.4	1997.0	1077.0	1366.0
		Type5	19	1	977882.0	10	1	57.4	1723.0	---	---
	5570	Type5	19	1	977882.0	10	1	57.4	1723.0	---	---
		Type5	19	10	162176.0	10	1	54.8	1084.0	---	---
		Type5	19	9	915842.0	10	3	95.4	1020.0	1892.0	1414.0
		Type5	19	8	674004.0	10	3	96.2	1391.0	1787.0	1672.0
		Type5	19	7	432561.0	10	3	97.3	1790.0	1896.0	1367.0
		Type5	19	6	191373.0	10	3	88.4	1997.0	1077.0	1366.0
		Type5	19	5	947923.0	10	1	62.0	1866.0	---	---
		Type5	19	4	705071.0	10	2	77.9	1642.0	1317.0	---
		Type5	19	2	221197.0	10	3	96.6	1086.0	1658.0	1324.0
		Type5	19	0	733725.0	10	3	88.6	1501.0	1067.0	1927.0
		Type5	19	11	403553.0	10	2	80.4	1850.0	1436.0	---
		Type5	19	3	462915.0	10	2	69.7	1751.0	1945.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	20	10	54310.0	15	2	73.5	1904.0	1352.0	---
		Type5	20	0	483470.0	15	2	74.7	1619.0	1611.0	---
		Type5	20	14	32086.0	15	1	61.8	1277.0	---	---
		Type5	20	13	597974.0	15	2	81.2	1160.0	1675.0	---
		Type5	20	11	235506.0	15	2	70.5	1864.0	1115.0	---
		Type5	20	15	212751.0	15	3	94.9	1450.0	1206.0	1860.0
		Type5	20	9	620397.0	15	2	68.5	1284.0	1428.0	---
		Type5	20	8	438554.0	15	2	79.0	1777.0	1960.0	---
		Type5	20	7	257785.0	15	2	71.0	1521.0	1567.0	---
		Type5	20	6	76831.0	15	1	58.7	1186.0	---	---
		Type5	20	5	642324.0	15	2	79.2	1574.0	1600.0	---
		Type5	20	4	462536.0	15	1	50.7	1003.0	---	---
		Type5	20	3	279914.0	15	2	83.1	1809.0	1772.0	---
		Type5	20	2	98810.0	15	3	91.9	1392.0	1475.0	1276.0
		Type5	20	1	666072.0	15	1	57.1	1560.0	---	---
		Type5	20	12	417036.0	15	2	76.6	1045.0	1300.0	---
	5500	Type5	20	7	257785.0	15	2	71.0	1521.0	1567.0	---
		Type5	20	13	597974.0	15	2	81.2	1160.0	1675.0	---
		Type5	20	12	417036.0	15	2	76.6	1045.0	1300.0	---
		Type5	20	11	235506.0	15	2	70.5	1864.0	1115.0	---
		Type5	20	10	54310.0	15	2	73.5	1904.0	1352.0	---
		Type5	20	9	620397.0	15	2	68.5	1284.0	1428.0	---
		Type5	20	8	438554.0	15	2	79.0	1777.0	1960.0	---
		Type5	20	6	76831.0	15	1	58.7	1186.0	---	---
		Type5	20	5	642324.0	15	2	79.2	1574.0	1600.0	---
		Type5	20	4	462536.0	15	1	50.7	1003.0	---	---
		Type5	20	3	279914.0	15	2	83.1	1809.0	1772.0	---
		Type5	20	2	98810.0	15	3	91.9	1392.0	1475.0	1276.0
		Type5	20	14	32086.0	15	1	61.8	1277.0	---	---
		Type5	20	0	483470.0	15	2	74.7	1619.0	1611.0	---
		Type5	20	15	212751.0	15	3	94.9	1450.0	1206.0	1860.0
		Type5	20	1	666072.0	15	1	57.1	1560.0	---	---
11AX40MIMO	5270	Type5	20	6	76831.0	15	1	58.7	1186.0	---	---
		Type5	20	13	597974.0	15	2	81.2	1160.0	1675.0	---
		Type5	20	12	417036.0	15	2	76.6	1045.0	1300.0	---
		Type5	20	11	235506.0	15	2	70.5	1864.0	1115.0	---
		Type5	20	10	54310.0	15	2	73.5	1904.0	1352.0	---
		Type5	20	9	620397.0	15	2	68.5	1284.0	1428.0	---
		Type5	20	14	32086.0	15	1	61.8	1277.0	---	---
		Type5	20	7	257785.0	15	2	71.0	1521.0	1567.0	---
		Type5	20	15	212751.0	15	3	94.9	1450.0	1206.0	1860.0
		Type5	20	5	642324.0	15	2	79.2	1574.0	1600.0	---
		Type5	20	4	462536.0	15	1	50.7	1003.0	---	---
		Type5	20	3	279914.0	15	2	83.1	1809.0	1772.0	---
		Type5	20	2	98810.0	15	3	91.9	1392.0	1475.0	1276.0
		Type5	20	1	666072.0	15	1	57.1	1560.0	---	---
		Type5	20	0	483470.0	15	2	74.7	1619.0	1611.0	---
		Type5	20	8	438554.0	15	2	79.0	1777.0	1960.0	---
	5510	Type5	20	3	279914.0	15	2	83.1	1809.0	1772.0	---
		Type5	20	15	212751.0	15	3	94.9	1450.0	1206.0	1860.0
		Type5	20	14	32086.0	15	1	61.8	1277.0	---	---
		Type5	20	13	597974.0	15	2	81.2	1160.0	1675.0	---
		Type5	20	12	417036.0	15	2	76.6	1045.0	1300.0	---
		Type5	20	11	235506.0	15	2	70.5	1864.0	1115.0	---

		Type5	20	10	54310.0	15	2	73.5	1904.0	1352.0	---
		Type5	20	9	620397.0	15	2	68.5	1284.0	1428.0	---
		Type5	20	8	438554.0	15	2	79.0	1777.0	1960.0	---
		Type5	20	7	257785.0	15	2	71.0	1521.0	1567.0	---
		Type5	20	6	76831.0	15	1	58.7	1186.0	---	---
		Type5	20	4	462536.0	15	1	50.7	1003.0	---	---
		Type5	20	2	98810.0	15	3	91.9	1392.0	1475.0	1276.0
		Type5	20	1	666072.0	15	1	57.1	1560.0	---	---
		Type5	20	0	483470.0	15	2	74.7	1619.0	1611.0	---
		Type5	20	5	642324.0	15	2	79.2	1574.0	1600.0	---
11AX80MIMO	5290	Type5	20	9	620397.0	15	2	68.5	1284.0	1428.0	---
		Type5	20	14	32086.0	15	1	61.8	1277.0	---	---
		Type5	20	0	483470.0	15	2	74.7	1619.0	1611.0	---
		Type5	20	13	597974.0	15	2	81.2	1160.0	1675.0	---
		Type5	20	12	417036.0	15	2	76.6	1045.0	1300.0	---
		Type5	20	10	54310.0	15	2	73.5	1904.0	1352.0	---
		Type5	20	8	438554.0	15	2	79.0	1777.0	1960.0	---
		Type5	20	7	257785.0	15	2	71.0	1521.0	1567.0	---
		Type5	20	2	98810.0	15	3	91.9	1392.0	1475.0	1276.0
		Type5	20	5	642324.0	15	2	79.2	1574.0	1600.0	---
		Type5	20	15	212751.0	15	3	94.9	1450.0	1206.0	1860.0
		Type5	20	4	462536.0	15	1	50.7	1003.0	---	---
		Type5	20	1	666072.0	15	1	57.1	1560.0	---	---
		Type5	20	3	279914.0	15	2	83.1	1809.0	1772.0	---
		Type5	20	6	76831.0	15	1	58.7	1186.0	---	---
	5530	Type5	20	11	235506.0	15	2	70.5	1864.0	1115.0	---
		Type5	20	7	257785.0	15	2	71.0	1521.0	1567.0	---
		Type5	20	9	620397.0	15	2	68.5	1284.0	1428.0	---
		Type5	20	10	54310.0	15	2	73.5	1904.0	1352.0	---
		Type5	20	11	235506.0	15	2	70.5	1864.0	1115.0	---
		Type5	20	13	597974.0	15	2	81.2	1160.0	1675.0	---
		Type5	20	6	76831.0	15	1	58.7	1186.0	---	---
		Type5	20	14	32086.0	15	1	61.8	1277.0	---	---
		Type5	20	12	417036.0	15	2	76.6	1045.0	1300.0	---
		Type5	20	4	462536.0	15	1	50.7	1003.0	---	---
		Type5	20	3	279914.0	15	2	83.1	1809.0	1772.0	---
		Type5	20	2	98810.0	15	3	91.9	1392.0	1475.0	1276.0
		Type5	20	1	666072.0	15	1	57.1	1560.0	---	---
		Type5	20	0	483470.0	15	2	74.7	1619.0	1611.0	---
		Type5	20	15	212751.0	15	3	94.9	1450.0	1206.0	1860.0
11AX160MIMO	5250	Type5	20	8	438554.0	15	2	79.0	1777.0	1960.0	---
		Type5	20	5	642324.0	15	2	79.2	1574.0	1600.0	---
		Type5	20	4	462536.0	15	1	50.7	1003.0	---	---
		Type5	20	0	483470.0	15	2	74.7	1619.0	1611.0	---
		Type5	20	1	666072.0	15	1	57.1	1560.0	---	---
		Type5	20	3	279914.0	15	2	83.1	1809.0	1772.0	---
		Type5	20	5	642324.0	15	2	79.2	1574.0	1600.0	---
		Type5	20	6	76831.0	15	1	58.7	1186.0	---	---
		Type5	20	7	257785.0	15	2	71.0	1521.0	1567.0	---
		Type5	20	15	212751.0	15	3	94.9	1450.0	1206.0	1860.0
		Type5	20	9	620397.0	15	2	68.5	1284.0	1428.0	---
		Type5	20	10	54310.0	15	2	73.5	1904.0	1352.0	---
		Type5	20	11	235506.0	15	2	70.5	1864.0	1115.0	---
		Type5	20	12	417036.0	15	2	76.6	1045.0	1300.0	---
		Type5	20	13	597974.0	15	2	81.2	1160.0	1675.0	---
		Type5	20	14	32086.0	15	1	61.8	1277.0	---	---
		Type5	20	2	98810.0	15	3	91.9	1392.0	1475.0	1276.0
		Type5	20	8	438554.0	15	2	79.0	1777.0	1960.0	---

	5570	Type5	20	9	620397.0	15	2	68.5	1284.0	1428.0	---
		Type5	20	10	54310.0	15	2	73.5	1904.0	1352.0	---
		Type5	20	11	235506.0	15	2	70.5	1864.0	1115.0	---
		Type5	20	12	417036.0	15	2	76.6	1045.0	1300.0	---
		Type5	20	8	438554.0	15	2	79.0	1777.0	1960.0	---
		Type5	20	14	32086.0	15	1	61.8	1277.0	---	---
		Type5	20	2	98810.0	15	3	91.9	1392.0	1475.0	1276.0
		Type5	20	13	597974.0	15	2	81.2	1160.0	1675.0	---
		Type5	20	7	257785.0	15	2	71.0	1521.0	1567.0	---
		Type5	20	6	76831.0	15	1	58.7	1186.0	---	---
		Type5	20	5	642324.0	15	2	79.2	1574.0	1600.0	---
		Type5	20	3	279914.0	15	2	83.1	1809.0	1772.0	---
		Type5	20	1	666072.0	15	1	57.1	1560.0	---	---
		Type5	20	0	483470.0	15	2	74.7	1619.0	1611.0	---
		Type5	20	15	212751.0	15	3	94.9	1450.0	1206.0	1860.0
		Type5	20	4	462536.0	15	1	50.7	1003.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	21	7	225249.0	9	1	61.6	1724.0	---	---
		Type5	21	0	526149.0	9	2	78.5	1653.0	1698.0	---
		Type5	21	10	951847.0	9	1	60.4	1453.0	---	---
		Type5	21	8	467279.0	9	1	53.4	1901.0	---	---
		Type5	21	11	194839.0	9	3	91.4	1768.0	1726.0	1227.0
		Type5	21	6	980872.0	9	2	80.9	1220.0	1053.0	---
		Type5	21	5	739728.0	9	1	53.6	1144.0	---	---
		Type5	21	4	496588.0	9	2	76.0	1112.0	1811.0	---
		Type5	21	3	254612.0	9	2	79.6	1633.0	1890.0	---
		Type5	21	2	12955.0	9	1	59.4	1982.0	---	---
	5500	Type5	21	1	767135.0	9	3	89.8	1174.0	1962.0	1167.0
		Type5	21	9	709720.0	9	1	59.9	1379.0	---	---
		Type5	21	5	739728.0	9	1	53.6	1144.0	---	---
		Type5	21	9	709720.0	9	1	59.9	1379.0	---	---
		Type5	21	8	467279.0	9	1	53.4	1901.0	---	---
		Type5	21	7	225249.0	9	1	61.6	1724.0	---	---
		Type5	21	6	980872.0	9	2	80.9	1220.0	1053.0	---
		Type5	21	4	496588.0	9	2	76.0	1112.0	1811.0	---
		Type5	21	3	254612.0	9	2	79.6	1633.0	1890.0	---
		Type5	21	2	12955.0	9	1	59.4	1982.0	---	---
11AX40MIMO	5270	Type5	21	10	951847.0	9	1	60.4	1453.0	---	---
		Type5	21	0	526149.0	9	2	78.5	1653.0	1698.0	---
		Type5	21	1	767135.0	9	3	89.8	1174.0	1962.0	1167.0
		Type5	21	2	12955.0	9	1	59.4	1982.0	---	---
		Type5	21	3	254612.0	9	2	79.6	1633.0	1890.0	---
		Type5	21	4	496588.0	9	2	76.0	1112.0	1811.0	---
		Type5	21	5	739728.0	9	1	53.6	1144.0	---	---
		Type5	21	6	980872.0	9	2	80.9	1220.0	1053.0	---
		Type5	21	7	225249.0	9	1	61.6	1724.0	---	---
		Type5	21	8	467279.0	9	1	53.4	1901.0	---	---
	5510	Type5	21	9	709720.0	9	1	59.9	1379.0	---	---
		Type5	21	10	951847.0	9	1	60.4	1453.0	---	---
		Type5	21	2	12955.0	9	1	59.4	1982.0	---	---
		Type5	21	11	194839.0	9	3	91.4	1768.0	1726.0	1227.0
		Type5	21	10	951847.0	9	1	60.4	1453.0	---	---
		Type5	21	9	709720.0	9	1	59.9	1379.0	---	---
		Type5	21	8	467279.0	9	1	53.4	1901.0	---	---
		Type5	21	7	225249.0	9	1	61.6	1724.0	---	---
		Type5	21	6	980872.0	9	2	80.9	1220.0	1053.0	---
		Type5	21	5	739728.0	9	1	53.6	1144.0	---	---
		Type5	21	3	254612.0	9	2	79.6	1633.0	1890.0	---
11AX80MIMO	5290	Type5	21	1	767135.0	9	3	89.8	1174.0	1962.0	1167.0
		Type5	21	0	526149.0	9	2	78.5	1653.0	1698.0	---
		Type5	21	4	496588.0	9	2	76.0	1112.0	1811.0	---
		Type5	21	5	739728.0	9	1	53.6	1144.0	---	---
		Type5	21	7	225249.0	9	1	61.6	1724.0	---	---
		Type5	21	9	709720.0	9	1	59.9	1379.0	---	---

		Type5	21	4	496588.0	9	2	76.0	1112.0	1811.0	---
		Type5	21	11	194839.0	9	3	91.4	1768.0	1726.0	1227.0
		Type5	21	3	254612.0	9	2	79.6	1633.0	1890.0	---
		Type5	21	2	12955.0	9	1	59.4	1982.0	---	---
		Type5	21	1	767135.0	9	3	89.8	1174.0	1962.0	1167.0
		Type5	21	8	467279.0	9	1	53.4	1901.0	---	---
	5530	Type5	21	10	951847.0	9	1	60.4	1453.0	---	---
		Type5	21	4	496588.0	9	2	76.0	1112.0	1811.0	---
		Type5	21	9	709720.0	9	1	59.9	1379.0	---	---
		Type5	21	8	467279.0	9	1	53.4	1901.0	---	---
		Type5	21	7	225249.0	9	1	61.6	1724.0	---	---
		Type5	21	5	739728.0	9	1	53.6	1144.0	---	---
		Type5	21	2	12955.0	9	1	59.4	1982.0	---	---
		Type5	21	1	767135.0	9	3	89.8	1174.0	1962.0	1167.0
		Type5	21	0	526149.0	9	2	78.5	1653.0	1698.0	---
		Type5	21	11	194839.0	9	3	91.4	1768.0	1726.0	1227.0
		Type5	21	6	980872.0	9	2	80.9	1220.0	1053.0	---
		Type5	21	3	254612.0	9	2	79.6	1633.0	1890.0	---
11AX160MIMO	5250	Type5	21	3	254612.0	9	2	79.6	1633.0	1890.0	---
		Type5	21	0	526149.0	9	2	78.5	1653.0	1698.0	---
		Type5	21	2	12955.0	9	1	59.4	1982.0	---	---
		Type5	21	4	496588.0	9	2	76.0	1112.0	1811.0	---
		Type5	21	5	739728.0	9	1	53.6	1144.0	---	---
		Type5	21	7	225249.0	9	1	61.6	1724.0	---	---
		Type5	21	8	467279.0	9	1	53.4	1901.0	---	---
		Type5	21	9	709720.0	9	1	59.9	1379.0	---	---
		Type5	21	10	951847.0	9	1	60.4	1453.0	---	---
		Type5	21	11	194839.0	9	3	91.4	1768.0	1726.0	1227.0
		Type5	21	6	980872.0	9	2	80.9	1220.0	1053.0	---
		Type5	21	1	767135.0	9	3	89.8	1174.0	1962.0	1167.0
	5570	Type5	21	1	767135.0	9	3	89.8	1174.0	1962.0	1167.0
		Type5	21	10	951847.0	9	1	60.4	1453.0	---	---
		Type5	21	9	709720.0	9	1	59.9	1379.0	---	---
		Type5	21	8	467279.0	9	1	53.4	1901.0	---	---
		Type5	21	7	225249.0	9	1	61.6	1724.0	---	---
		Type5	21	6	980872.0	9	2	80.9	1220.0	1053.0	---
		Type5	21	5	739728.0	9	1	53.6	1144.0	---	---
		Type5	21	4	496588.0	9	2	76.0	1112.0	1811.0	---
		Type5	21	2	12955.0	9	1	59.4	1982.0	---	---
		Type5	21	0	526149.0	9	2	78.5	1653.0	1698.0	---
		Type5	21	11	194839.0	9	3	91.4	1768.0	1726.0	1227.0
		Type5	21	3	254612.0	9	2	79.6	1633.0	1890.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	22	13	353638.0	20	1	57.3	1834.0	---	---
		Type5	22	0	261858.0	20	2	77.0	1191.0	1363.0	---
		Type5	22	18	478825.0	20	3	93.2	1985.0	1018.0	1340.0
		Type5	22	17	335330.0	20	2	76.1	1557.0	1057.0	---
		Type5	22	16	189821.0	20	3	84.0	1765.0	1630.0	1176.0
		Type5	22	14	497515.0	20	2	70.5	1684.0	1586.0	---
		Type5	22	19	27594.0	20	3	96.8	1760.0	1614.0	1817.0
		Type5	22	12	207510.0	20	3	92.0	1745.0	1654.0	1458.0
		Type5	22	11	63561.0	20	1	53.5	1162.0	---	---
		Type5	22	10	514197.0	20	3	95.9	1659.0	1870.0	1066.0
		Type5	22	2	552319.0	20	1	62.1	1836.0	---	---
		Type5	22	15	45553.0	20	2	70.0	1042.0	1664.0	---
		Type5	22	1	407646.0	20	1	58.1	1248.0	---	---
		Type5	22	9	371906.0	20	1	57.9	1193.0	---	---
		Type5	22	3	99107.0	20	2	76.9	1334.0	1236.0	---
		Type5	22	4	243514.0	20	2	80.0	1914.0	1852.0	---
		Type5	22	5	389464.0	20	1	52.0	1701.0	---	---
		Type5	22	6	531093.0	20	3	88.6	1693.0	1995.0	1905.0
		Type5	22	7	81159.0	20	2	72.9	1922.0	1387.0	---
		Type5	22	8	225245.0	20	3	98.5	1839.0	1746.0	1389.0
	5500	Type5	22	9	371906.0	20	1	57.9	1193.0	---	---
		Type5	22	16	189821.0	20	3	84.0	1765.0	1630.0	1176.0
		Type5	22	15	45553.0	20	2	70.0	1042.0	1664.0	---
		Type5	22	14	497515.0	20	2	70.5	1684.0	1586.0	---
		Type5	22	13	353638.0	20	1	57.3	1834.0	---	---
		Type5	22	12	207510.0	20	3	92.0	1745.0	1654.0	1458.0
		Type5	22	11	63561.0	20	1	53.5	1162.0	---	---
		Type5	22	10	514197.0	20	3	95.9	1659.0	1870.0	1066.0
		Type5	22	17	335330.0	20	2	76.1	1557.0	1057.0	---
		Type5	22	8	225245.0	20	3	98.5	1839.0	1746.0	1389.0
		Type5	22	7	81159.0	20	2	72.9	1922.0	1387.0	---
		Type5	22	6	531093.0	20	3	88.6	1693.0	1995.0	1905.0
		Type5	22	5	389464.0	20	1	52.0	1701.0	---	---
		Type5	22	4	243514.0	20	2	80.0	1914.0	1852.0	---
		Type5	22	3	99107.0	20	2	76.9	1334.0	1236.0	---
		Type5	22	2	552319.0	20	1	62.1	1836.0	---	---
		Type5	22	18	478825.0	20	3	93.2	1985.0	1018.0	1340.0
		Type5	22	0	261858.0	20	2	77.0	1191.0	1363.0	---
		Type5	22	19	27594.0	20	3	96.8	1760.0	1614.0	1817.0
		Type5	22	1	407646.0	20	1	58.1	1248.0	---	---
11AX40MIMO	5270	Type5	22	8	225245.0	20	3	98.5	1839.0	1746.0	1389.0
		Type5	22	17	335330.0	20	2	76.1	1557.0	1057.0	---
		Type5	22	16	189821.0	20	3	84.0	1765.0	1630.0	1176.0
		Type5	22	15	45553.0	20	2	70.0	1042.0	1664.0	---
		Type5	22	14	497515.0	20	2	70.5	1684.0	1586.0	---
		Type5	22	13	353638.0	20	1	57.3	1834.0	---	---
		Type5	22	12	207510.0	20	3	92.0	1745.0	1654.0	1458.0
		Type5	22	11	63561.0	20	1	53.5	1162.0	---	---
		Type5	22	18	478825.0	20	3	93.2	1985.0	1018.0	1340.0
		Type5	22	9	371906.0	20	1	57.9	1193.0	---	---
		Type5	22	19	27594.0	20	3	96.8	1760.0	1614.0	1817.0
		Type5	22	7	81159.0	20	2	72.9	1922.0	1387.0	---
		Type5	22	6	531093.0	20	3	88.6	1693.0	1995.0	1905.0
		Type5	22	5	389464.0	20	1	52.0	1701.0	---	---

11AX80MIMO		Type5	22	4	243514.0	20	2	80.0	1914.0	1852.0	---
		Type5	22	3	99107.0	20	2	76.9	1334.0	1236.0	---
		Type5	22	2	552319.0	20	1	62.1	1836.0	---	---
		Type5	22	1	407646.0	20	1	58.1	1248.0	---	---
		Type5	22	0	261858.0	20	2	77.0	1191.0	1363.0	---
		Type5	22	10	514197.0	20	3	95.9	1659.0	1870.0	1066.0
	5510	Type5	22	12	207510.0	20	3	92.0	1745.0	1654.0	1458.0
		Type5	22	1	407646.0	20	1	58.1	1248.0	---	---
		Type5	22	2	552319.0	20	1	62.1	1836.0	---	---
		Type5	22	3	99107.0	20	2	76.9	1334.0	1236.0	---
		Type5	22	5	389464.0	20	1	52.0	1701.0	---	---
		Type5	22	7	81159.0	20	2	72.9	1922.0	1387.0	---
		Type5	22	8	225245.0	20	3	98.5	1839.0	1746.0	1389.0
		Type5	22	9	371906.0	20	1	57.9	1193.0	---	---
		Type5	22	0	261858.0	20	2	77.0	1191.0	1363.0	---
		Type5	22	11	63561.0	20	1	53.5	1162.0	---	---
		Type5	22	4	243514.0	20	2	80.0	1914.0	1852.0	---
		Type5	22	13	353638.0	20	1	57.3	1834.0	---	---
		Type5	22	14	497515.0	20	2	70.5	1684.0	1586.0	---
		Type5	22	15	45553.0	20	2	70.0	1042.0	1664.0	---
		Type5	22	16	189821.0	20	3	84.0	1765.0	1630.0	1176.0
		Type5	22	17	335330.0	20	2	76.1	1557.0	1057.0	---
		Type5	22	18	478825.0	20	3	93.2	1985.0	1018.0	1340.0
		Type5	22	19	27594.0	20	3	96.8	1760.0	1614.0	1817.0
		Type5	22	10	514197.0	20	3	95.9	1659.0	1870.0	1066.0
		Type5	22	6	531093.0	20	3	88.6	1693.0	1995.0	1905.0
	5290	Type5	22	12	207510.0	20	3	92.0	1745.0	1654.0	1458.0
		Type5	22	18	478825.0	20	3	93.2	1985.0	1018.0	1340.0
		Type5	22	0	261858.0	20	2	77.0	1191.0	1363.0	---
		Type5	22	17	335330.0	20	2	76.1	1557.0	1057.0	---
		Type5	22	16	189821.0	20	3	84.0	1765.0	1630.0	1176.0
		Type5	22	15	45553.0	20	2	70.0	1042.0	1664.0	---
		Type5	22	13	353638.0	20	1	57.3	1834.0	---	---
		Type5	22	11	63561.0	20	1	53.5	1162.0	---	---
		Type5	22	10	514197.0	20	3	95.9	1659.0	1870.0	1066.0
		Type5	22	9	371906.0	20	1	57.9	1193.0	---	---
		Type5	22	2	552319.0	20	1	62.1	1836.0	---	---
		Type5	22	7	81159.0	20	2	72.9	1922.0	1387.0	---
		Type5	22	6	531093.0	20	3	88.6	1693.0	1995.0	1905.0
		Type5	22	19	27594.0	20	3	96.8	1760.0	1614.0	1817.0
		Type5	22	5	389464.0	20	1	52.0	1701.0	---	---
		Type5	22	1	407646.0	20	1	58.1	1248.0	---	---
		Type5	22	4	243514.0	20	2	80.0	1914.0	1852.0	---
		Type5	22	3	99107.0	20	2	76.9	1334.0	1236.0	---
		Type5	22	8	225245.0	20	3	98.5	1839.0	1746.0	1389.0
		Type5	22	14	497515.0	20	2	70.5	1684.0	1586.0	---
	5530	Type5	22	9	371906.0	20	1	57.9	1193.0	---	---
		Type5	22	11	63561.0	20	1	53.5	1162.0	---	---
		Type5	22	12	207510.0	20	3	92.0	1745.0	1654.0	1458.0
		Type5	22	13	353638.0	20	1	57.3	1834.0	---	---
		Type5	22	14	497515.0	20	2	70.5	1684.0	1586.0	---
		Type5	22	15	45553.0	20	2	70.0	1042.0	1664.0	---
		Type5	22	17	335330.0	20	2	76.1	1557.0	1057.0	---
		Type5	22	8	225245.0	20	3	98.5	1839.0	1746.0	1389.0
		Type5	22	18	478825.0	20	3	93.2	1985.0	1018.0	1340.0
		Type5	22	16	189821.0	20	3	84.0	1765.0	1630.0	1176.0
		Type5	22	19	27594.0	20	3	96.8	1760.0	1614.0	1817.0
		Type5	22	6	531093.0	20	3	88.6	1693.0	1995.0	1905.0

		Type5	22	5	389464.0	20	1	52.0	1701.0	---	---
		Type5	22	4	243514.0	20	2	80.0	1914.0	1852.0	---
		Type5	22	3	99107.0	20	2	76.9	1334.0	1236.0	---
		Type5	22	2	552319.0	20	1	62.1	1836.0	---	---
		Type5	22	1	407646.0	20	1	58.1	1248.0	---	---
		Type5	22	0	261858.0	20	2	77.0	1191.0	1363.0	---
		Type5	22	7	81159.0	20	2	72.9	1922.0	1387.0	---
		Type5	22	10	514197.0	20	3	95.9	1659.0	1870.0	1066.0
11AX160MIMO	5250	Type5	22	8	225245.0	20	3	98.5	1839.0	1746.0	1389.0
		Type5	22	7	81159.0	20	2	72.9	1922.0	1387.0	---
		Type5	22	6	531093.0	20	3	88.6	1693.0	1995.0	1905.0
		Type5	22	4	243514.0	20	2	80.0	1914.0	1852.0	---
		Type5	22	2	552319.0	20	1	62.1	1836.0	---	---
		Type5	22	9	371906.0	20	1	57.9	1193.0	---	---
		Type5	22	0	261858.0	20	2	77.0	1191.0	1363.0	---
		Type5	22	5	389464.0	20	1	52.0	1701.0	---	---
		Type5	22	1	407646.0	20	1	58.1	1248.0	---	---
		Type5	22	19	27594.0	20	3	96.8	1760.0	1614.0	1817.0
		Type5	22	11	63561.0	20	1	53.5	1162.0	---	---
		Type5	22	12	207510.0	20	3	92.0	1745.0	1654.0	1458.0
		Type5	22	13	353638.0	20	1	57.3	1834.0	---	---
		Type5	22	14	497515.0	20	2	70.5	1684.0	1586.0	---
		Type5	22	15	45553.0	20	2	70.0	1042.0	1664.0	---
		Type5	22	16	189821.0	20	3	84.0	1765.0	1630.0	1176.0
		Type5	22	17	335330.0	20	2	76.1	1557.0	1057.0	---
		Type5	22	18	478825.0	20	3	93.2	1985.0	1018.0	1340.0
		Type5	22	3	99107.0	20	2	76.9	1334.0	1236.0	---
		Type5	22	10	514197.0	20	3	95.9	1659.0	1870.0	1066.0
	5570	Type5	22	11	63561.0	20	1	53.5	1162.0	---	---
		Type5	22	12	207510.0	20	3	92.0	1745.0	1654.0	1458.0
		Type5	22	13	353638.0	20	1	57.3	1834.0	---	---
		Type5	22	14	497515.0	20	2	70.5	1684.0	1586.0	---
		Type5	22	15	45553.0	20	2	70.0	1042.0	1664.0	---
		Type5	22	16	189821.0	20	3	84.0	1765.0	1630.0	1176.0
		Type5	22	10	514197.0	20	3	95.9	1659.0	1870.0	1066.0
		Type5	22	18	478825.0	20	3	93.2	1985.0	1018.0	1340.0
		Type5	22	3	99107.0	20	2	76.9	1334.0	1236.0	---
		Type5	22	17	335330.0	20	2	76.1	1557.0	1057.0	---
		Type5	22	9	371906.0	20	1	57.9	1193.0	---	---
		Type5	22	8	225245.0	20	3	98.5	1839.0	1746.0	1389.0
		Type5	22	7	81159.0	20	2	72.9	1922.0	1387.0	---
		Type5	22	6	531093.0	20	3	88.6	1693.0	1995.0	1905.0
		Type5	22	4	243514.0	20	2	80.0	1914.0	1852.0	---
		Type5	22	2	552319.0	20	1	62.1	1836.0	---	---
		Type5	22	1	407646.0	20	1	58.1	1248.0	---	---
		Type5	22	0	261858.0	20	2	77.0	1191.0	1363.0	---
		Type5	22	19	27594.0	20	3	96.8	1760.0	1614.0	1817.0
		Type5	22	5	389464.0	20	1	52.0	1701.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MIMO	5260	Type5	23	9	403231.0	12	2	80.2	1098.0	1209.0	---
		Type5	23	0	247117.0	12	1	50.1	1841.0	---	---
		Type5	23	12	170267.0	12	2	68.7	1377.0	1441.0	---
		Type5	23	10	610202.0	12	2	79.7	1588.0	1214.0	---
		Type5	23	13	377306.0	12	2	67.4	1872.0	1313.0	---
		Type5	23	8	195585.0	12	2	76.2	1940.0	1770.0	---
		Type5	23	7	843157.0	12	2	71.1	1329.0	1243.0	---
		Type5	23	6	636681.0	12	1	54.4	1517.0	---	---
		Type5	23	5	428367.0	12	2	75.2	1572.0	1536.0	---
		Type5	23	4	220734.0	12	3	86.0	1953.0	1108.0	1987.0
		Type5	23	3	14140.0	12	1	56.3	1056.0	---	---
		Type5	23	2	660875.0	12	2	68.8	1707.0	1577.0	---
	5500	Type5	23	1	453362.0	12	3	93.5	1590.0	1081.0	1413.0
		Type5	23	11	815229.0	12	3	90.9	1615.0	1862.0	1601.0
		Type5	23	6	636681.0	12	1	54.4	1517.0	---	---
		Type5	23	11	815229.0	12	3	90.9	1615.0	1862.0	1601.0
		Type5	23	10	610202.0	12	2	79.7	1588.0	1214.0	---
		Type5	23	9	403231.0	12	2	80.2	1098.0	1209.0	---
		Type5	23	8	195585.0	12	2	76.2	1940.0	1770.0	---
		Type5	23	7	843157.0	12	2	71.1	1329.0	1243.0	---
		Type5	23	5	428367.0	12	2	75.2	1572.0	1536.0	---
		Type5	23	4	220734.0	12	3	86.0	1953.0	1108.0	1987.0
		Type5	23	3	14140.0	12	1	56.3	1056.0	---	---
		Type5	23	2	660875.0	12	2	68.8	1707.0	1577.0	---
11AX40MIMO	5270	Type5	23	12	170267.0	12	2	68.7	1377.0	1441.0	---
		Type5	23	0	247117.0	12	1	50.1	1841.0	---	---
		Type5	23	13	377306.0	12	2	67.4	1872.0	1313.0	---
		Type5	23	1	453362.0	12	3	93.5	1590.0	1081.0	1413.0
		Type5	23	13	377306.0	12	2	67.4	1872.0	1313.0	---
		Type5	23	0	247117.0	12	1	50.1	1841.0	---	---
		Type5	23	1	453362.0	12	3	93.5	1590.0	1081.0	1413.0
		Type5	23	2	660875.0	12	2	68.8	1707.0	1577.0	---
		Type5	23	3	14140.0	12	1	56.3	1056.0	---	---
		Type5	23	4	220734.0	12	3	86.0	1953.0	1108.0	1987.0
		Type5	23	5	428367.0	12	2	75.2	1572.0	1536.0	---
		Type5	23	6	636681.0	12	1	54.4	1517.0	---	---
	5510	Type5	23	7	843157.0	12	2	71.1	1329.0	1243.0	---
		Type5	23	8	195585.0	12	2	76.2	1940.0	1770.0	---
		Type5	23	9	403231.0	12	2	80.2	1098.0	1209.0	---
		Type5	23	10	610202.0	12	2	79.7	1588.0	1214.0	---
		Type5	23	11	815229.0	12	3	90.9	1615.0	1862.0	1601.0
		Type5	23	12	170267.0	12	2	68.7	1377.0	1441.0	---
		Type5	23	2	660875.0	12	2	68.8	1707.0	1577.0	---
		Type5	23	13	377306.0	12	2	67.4	1872.0	1313.0	---
		Type5	23	12	170267.0	12	2	68.7	1377.0	1441.0	---
		Type5	23	11	815229.0	12	3	90.9	1615.0	1862.0	1601.0
		Type5	23	10	610202.0	12	2	79.7	1588.0	1214.0	---
		Type5	23	9	403231.0	12	2	80.2	1098.0	1209.0	---
		Type5	23	8	195585.0	12	2	76.2	1940.0	1770.0	---
		Type5	23	7	843157.0	12	2	71.1	1329.0	1243.0	---
		Type5	23	6	636681.0	12	1	54.4	1517.0	---	---
		Type5	23	5	428367.0	12	2	75.2	1572.0	1536.0	---
		Type5	23	3	14140.0	12	1	56.3	1056.0	---	---
		Type5	23	1	453362.0	12	3	93.5	1590.0	1081.0	1413.0

11AX80MIMO	5290	Type5	23	0	247117.0	12	1	50.1	1841.0	---	---
		Type5	23	4	220734.0	12	3	86.0	1953.0	1108.0	1987.0
		Type5	23	8	195585.0	12	2	76.2	1940.0	1770.0	---
		Type5	23	12	170267.0	12	2	68.7	1377.0	1441.0	---
		Type5	23	0	247117.0	12	1	50.1	1841.0	---	---
		Type5	23	11	815229.0	12	3	90.9	1615.0	1862.0	1601.0
		Type5	23	9	403231.0	12	2	80.2	1098.0	1209.0	---
		Type5	23	7	843157.0	12	2	71.1	1329.0	1243.0	---
		Type5	23	6	636681.0	12	1	54.4	1517.0	---	---
		Type5	23	5	428367.0	12	2	75.2	1572.0	1536.0	---
		Type5	23	4	220734.0	12	3	86.0	1953.0	1108.0	1987.0
		Type5	23	13	377306.0	12	2	67.4	1872.0	1313.0	---
		Type5	23	3	14140.0	12	1	56.3	1056.0	---	---
		Type5	23	2	660875.0	12	2	68.8	1707.0	1577.0	---
		Type5	23	1	453362.0	12	3	93.5	1590.0	1081.0	1413.0
	5530	Type5	23	10	610202.0	12	2	79.7	1588.0	1214.0	---
		Type5	23	12	170267.0	12	2	68.7	1377.0	1441.0	---
		Type5	23	5	428367.0	12	2	75.2	1572.0	1536.0	---
		Type5	23	11	815229.0	12	3	90.9	1615.0	1862.0	1601.0
		Type5	23	10	610202.0	12	2	79.7	1588.0	1214.0	---
		Type5	23	9	403231.0	12	2	80.2	1098.0	1209.0	---
		Type5	23	8	195585.0	12	2	76.2	1940.0	1770.0	---
		Type5	23	6	636681.0	12	1	54.4	1517.0	---	---
		Type5	23	3	14140.0	12	1	56.3	1056.0	---	---
		Type5	23	2	660875.0	12	2	68.8	1707.0	1577.0	---
		Type5	23	1	453362.0	12	3	93.5	1590.0	1081.0	1413.0
		Type5	23	0	247117.0	12	1	50.1	1841.0	---	---
		Type5	23	13	377306.0	12	2	67.4	1872.0	1313.0	---
		Type5	23	7	843157.0	12	2	71.1	1329.0	1243.0	---
		Type5	23	4	220734.0	12	3	86.0	1953.0	1108.0	1987.0
11AX160MIMO	5250	Type5	23	4	220734.0	12	3	86.0	1953.0	1108.0	1987.0
		Type5	23	0	247117.0	12	1	50.1	1841.0	---	---
		Type5	23	1	453362.0	12	3	93.5	1590.0	1081.0	1413.0
		Type5	23	3	14140.0	12	1	56.3	1056.0	---	---
		Type5	23	5	428367.0	12	2	75.2	1572.0	1536.0	---
		Type5	23	6	636681.0	12	1	54.4	1517.0	---	---
		Type5	23	8	195585.0	12	2	76.2	1940.0	1770.0	---
		Type5	23	9	403231.0	12	2	80.2	1098.0	1209.0	---
		Type5	23	10	610202.0	12	2	79.7	1588.0	1214.0	---
		Type5	23	11	815229.0	12	3	90.9	1615.0	1862.0	1601.0
		Type5	23	12	170267.0	12	2	68.7	1377.0	1441.0	---
		Type5	23	13	377306.0	12	2	67.4	1872.0	1313.0	---
		Type5	23	7	843157.0	12	2	71.1	1329.0	1243.0	---
		Type5	23	2	660875.0	12	2	68.8	1707.0	1577.0	---
	5570	Type5	23	2	660875.0	12	2	68.8	1707.0	1577.0	---
		Type5	23	12	170267.0	12	2	68.7	1377.0	1441.0	---
		Type5	23	11	815229.0	12	3	90.9	1615.0	1862.0	1601.0
		Type5	23	10	610202.0	12	2	79.7	1588.0	1214.0	---
		Type5	23	9	403231.0	12	2	80.2	1098.0	1209.0	---
		Type5	23	8	195585.0	12	2	76.2	1940.0	1770.0	---
		Type5	23	7	843157.0	12	2	71.1	1329.0	1243.0	---
		Type5	23	6	636681.0	12	1	54.4	1517.0	---	---
		Type5	23	5	428367.0	12	2	75.2	1572.0	1536.0	---
		Type5	23	3	14140.0	12	1	56.3	1056.0	---	---
		Type5	23	1	453362.0	12	3	93.5	1590.0	1081.0	1413.0
		Type5	23	0	247117.0	12	1	50.1	1841.0	---	---
		Type5	23	13	377306.0	12	2	67.4	1872.0	1313.0	---
		Type5	23	4	220734.0	12	3	86.0	1953.0	1108.0	1987.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	24	8	573425.0	11	3	96.5	1607.0	1822.0	1602.0
		Type5	24	0	628071.0	11	3	94.0	1643.0	1748.0	1941.0
		Type5	24	11	324661.0	11	1	55.8	1290.0	---	---
		Type5	24	9	798431.0	11	2	70.5	1141.0	1178.0	---
		Type5	24	12	546278.0	11	3	87.7	1435.0	1963.0	1164.0
		Type5	24	7	351161.0	11	3	89.0	1493.0	1135.0	1380.0
		Type5	24	6	128265.0	11	3	92.6	1065.0	1669.0	1222.0
		Type5	24	5	825462.0	11	2	74.5	1569.0	1281.0	---
		Type5	24	4	601331.0	11	3	90.6	1217.0	1582.0	1498.0
		Type5	24	3	378734.0	11	3	96.7	1230.0	1163.0	1332.0
		Type5	24	2	156223.0	11	1	56.3	1006.0	---	---
		Type5	24	1	853391.0	11	2	70.8	1177.0	1201.0	---
	5500	Type5	24	10	100737.0	11	3	94.0	1009.0	1629.0	1956.0
		Type5	24	6	128265.0	11	3	92.6	1065.0	1669.0	1222.0
		Type5	24	10	100737.0	11	3	94.0	1009.0	1629.0	1956.0
		Type5	24	9	798431.0	11	2	70.5	1141.0	1178.0	---
		Type5	24	8	573425.0	11	3	96.5	1607.0	1822.0	1602.0
		Type5	24	7	351161.0	11	3	89.0	1493.0	1135.0	1380.0
		Type5	24	5	825462.0	11	2	74.5	1569.0	1281.0	---
		Type5	24	4	601331.0	11	3	90.6	1217.0	1582.0	1498.0
		Type5	24	3	378734.0	11	3	96.7	1230.0	1163.0	1332.0
		Type5	24	2	156223.0	11	1	56.3	1006.0	---	---
		Type5	24	11	324661.0	11	1	55.8	1290.0	---	---
		Type5	24	0	628071.0	11	3	94.0	1643.0	1748.0	1941.0
11AX40MIMO	5270	Type5	24	12	546278.0	11	3	87.7	1435.0	1963.0	1164.0
		Type5	24	0	628071.0	11	3	94.0	1643.0	1748.0	1941.0
		Type5	24	1	853391.0	11	2	70.8	1177.0	1201.0	---
		Type5	24	2	156223.0	11	1	56.3	1006.0	---	---
		Type5	24	3	378734.0	11	3	96.7	1230.0	1163.0	1332.0
		Type5	24	4	601331.0	11	3	90.6	1217.0	1582.0	1498.0
		Type5	24	5	825462.0	11	2	74.5	1569.0	1281.0	---
		Type5	24	6	128265.0	11	3	92.6	1065.0	1669.0	1222.0
		Type5	24	7	351161.0	11	3	89.0	1493.0	1135.0	1380.0
		Type5	24	8	573425.0	11	3	96.5	1607.0	1822.0	1602.0
		Type5	24	9	798431.0	11	2	70.5	1141.0	1178.0	---
		Type5	24	10	100737.0	11	3	94.0	1009.0	1629.0	1956.0
	5510	Type5	24	11	324661.0	11	1	55.8	1290.0	---	---
		Type5	24	2	156223.0	11	1	56.3	1006.0	---	---
		Type5	24	12	546278.0	11	3	87.7	1435.0	1963.0	1164.0
		Type5	24	11	324661.0	11	1	55.8	1290.0	---	---
		Type5	24	10	100737.0	11	3	94.0	1009.0	1629.0	1956.0
		Type5	24	9	798431.0	11	2	70.5	1141.0	1178.0	---
		Type5	24	8	573425.0	11	3	96.5	1607.0	1822.0	1602.0
		Type5	24	7	351161.0	11	3	89.0	1493.0	1135.0	1380.0
		Type5	24	6	128265.0	11	3	92.6	1065.0	1669.0	1222.0
		Type5	24	5	825462.0	11	2	74.5	1569.0	1281.0	---
		Type5	24	3	378734.0	11	3	96.7	1230.0	1163.0	1332.0
		Type5	24	1	853391.0	11	2	70.8	1177.0	1201.0	---
11AX80MIMO	5290	Type5	24	0	628071.0	11	3	94.0	1643.0	1748.0	1941.0
		Type5	24	4	601331.0	11	3	90.6	1217.0	1582.0	1498.0
		Type5	24	7	351161.0	11	3	89.0	1493.0	1135.0	1380.0
		Type5	24	11	324661.0	11	1	55.8	1290.0	---	---

		Type5	24	0	628071.0	11	3	94.0	1643.0	1748.0	1941.0
		Type5	24	10	100737.0	11	3	94.0	1009.0	1629.0	1956.0
		Type5	24	8	573425.0	11	3	96.5	1607.0	1822.0	1602.0
		Type5	24	6	128265.0	11	3	92.6	1065.0	1669.0	1222.0
		Type5	24	5	825462.0	11	2	74.5	1569.0	1281.0	---
		Type5	24	4	601331.0	11	3	90.6	1217.0	1582.0	1498.0
		Type5	24	12	546278.0	11	3	87.7	1435.0	1963.0	1164.0
		Type5	24	3	378734.0	11	3	96.7	1230.0	1163.0	1332.0
		Type5	24	2	156223.0	11	1	56.3	1006.0	---	---
		Type5	24	1	853391.0	11	2	70.8	1177.0	1201.0	---
		Type5	24	9	798431.0	11	2	70.5	1141.0	1178.0	---
		Type5	24	11	324661.0	11	1	55.8	1290.0	---	---
		Type5	24	4	601331.0	11	3	90.6	1217.0	1582.0	1498.0
		Type5	24	10	100737.0	11	3	94.0	1009.0	1629.0	1956.0
		Type5	24	9	798431.0	11	2	70.5	1141.0	1178.0	---
		Type5	24	8	573425.0	11	3	96.5	1607.0	1822.0	1602.0
		Type5	24	7	351161.0	11	3	89.0	1493.0	1135.0	1380.0
		Type5	24	3	378734.0	11	3	96.7	1230.0	1163.0	1332.0
		Type5	24	2	156223.0	11	1	56.3	1006.0	---	---
		Type5	24	1	853391.0	11	2	70.8	1177.0	1201.0	---
		Type5	24	0	628071.0	11	3	94.0	1643.0	1748.0	1941.0
		Type5	24	12	546278.0	11	3	87.7	1435.0	1963.0	1164.0
		Type5	24	6	128265.0	11	3	92.6	1065.0	1669.0	1222.0
		Type5	24	5	825462.0	11	2	74.5	1569.0	1281.0	---
		Type5	24	4	601331.0	11	3	90.6	1217.0	1582.0	1498.0
		Type5	24	0	628071.0	11	3	94.0	1643.0	1748.0	1941.0
		Type5	24	1	853391.0	11	2	70.8	1177.0	1201.0	---
		Type5	24	3	378734.0	11	3	96.7	1230.0	1163.0	1332.0
		Type5	24	5	825462.0	11	2	74.5	1569.0	1281.0	---
		Type5	24	6	128265.0	11	3	92.6	1065.0	1669.0	1222.0
		Type5	24	8	573425.0	11	3	96.5	1607.0	1822.0	1602.0
		Type5	24	9	798431.0	11	2	70.5	1141.0	1178.0	---
		Type5	24	10	100737.0	11	3	94.0	1009.0	1629.0	1956.0
		Type5	24	11	324661.0	11	1	55.8	1290.0	---	---
		Type5	24	12	546278.0	11	3	87.7	1435.0	1963.0	1164.0
		Type5	24	7	351161.0	11	3	89.0	1493.0	1135.0	1380.0
		Type5	24	2	156223.0	11	1	56.3	1006.0	---	---
		Type5	24	2	156223.0	11	1	56.3	1006.0	---	---
		Type5	24	11	324661.0	11	1	55.8	1290.0	---	---
		Type5	24	10	100737.0	11	3	94.0	1009.0	1629.0	1956.0
		Type5	24	9	798431.0	11	2	70.5	1141.0	1178.0	---
		Type5	24	8	573425.0	11	3	96.5	1607.0	1822.0	1602.0
		Type5	24	7	351161.0	11	3	89.0	1493.0	1135.0	1380.0
		Type5	24	6	128265.0	11	3	92.6	1065.0	1669.0	1222.0
		Type5	24	5	825462.0	11	2	74.5	1569.0	1281.0	---
		Type5	24	3	378734.0	11	3	96.7	1230.0	1163.0	1332.0
		Type5	24	1	853391.0	11	2	70.8	1177.0	1201.0	---
		Type5	24	0	628071.0	11	3	94.0	1643.0	1748.0	1941.0
		Type5	24	12	546278.0	11	3	87.7	1435.0	1963.0	1164.0
		Type5	24	4	601331.0	11	3	90.6	1217.0	1582.0	1498.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	25	7	800152.0	5	3	91.2	1409.0	1681.0	1275.0
		Type5	25	1	119486.0	5	2	83.1	1420.0	1315.0	---
		Type5	25	2	482958.0	5	1	60.9	1687.0	---	---
		Type5	25	3	845641.0	5	2	77.7	1776.0	1158.0	---
		Type5	25	4	1208428.0	5	2	77.4	1793.0	1510.0	---
		Type5	25	5	74748.0	5	2	66.8	1576.0	1323.0	---
		Type5	25	6	438300.0	5	1	63.7	1333.0	---	---
		Type5	25	0	1253842.0	5	2	68.6	1306.0	1161.0	---
	5500	Type5	25	5	74748.0	5	2	66.8	1576.0	1323.0	---
		Type5	25	4	1208428.0	5	2	77.4	1793.0	1510.0	---
		Type5	25	3	845641.0	5	2	77.7	1776.0	1158.0	---
		Type5	25	2	482958.0	5	1	60.9	1687.0	---	---
		Type5	25	6	438300.0	5	1	63.7	1333.0	---	---
		Type5	25	0	1253842.0	5	2	68.6	1306.0	1161.0	---
		Type5	25	7	800152.0	5	3	91.2	1409.0	1681.0	1275.0
11AX40MIMO	5270	Type5	25	1	119486.0	5	2	83.1	1420.0	1315.0	---
		Type5	25	7	800152.0	5	3	91.2	1409.0	1681.0	1275.0
		Type5	25	0	1253842.0	5	2	68.6	1306.0	1161.0	---
		Type5	25	1	119486.0	5	2	83.1	1420.0	1315.0	---
		Type5	25	2	482958.0	5	1	60.9	1687.0	---	---
		Type5	25	3	845641.0	5	2	77.7	1776.0	1158.0	---
		Type5	25	4	1208428.0	5	2	77.4	1793.0	1510.0	---
		Type5	25	5	74748.0	5	2	66.8	1576.0	1323.0	---
		Type5	25	6	438300.0	5	1	63.7	1333.0	---	---
	5510	Type5	25	1	119486.0	5	2	83.1	1420.0	1315.0	---
		Type5	25	7	800152.0	5	3	91.2	1409.0	1681.0	1275.0
		Type5	25	6	438300.0	5	1	63.7	1333.0	---	---
		Type5	25	5	74748.0	5	2	66.8	1576.0	1323.0	---
		Type5	25	4	1208428.0	5	2	77.4	1793.0	1510.0	---
		Type5	25	2	482958.0	5	1	60.9	1687.0	---	---
		Type5	25	0	1253842.0	5	2	68.6	1306.0	1161.0	---
11AX80MIMO	5290	Type5	25	3	845641.0	5	2	77.7	1776.0	1158.0	---
		Type5	25	1	119486.0	5	2	83.1	1420.0	1315.0	---
		Type5	25	2	482958.0	5	1	60.9	1687.0	---	---
		Type5	25	7	800152.0	5	3	91.2	1409.0	1681.0	1275.0
		Type5	25	3	845641.0	5	2	77.7	1776.0	1158.0	---
		Type5	25	4	1208428.0	5	2	77.4	1793.0	1510.0	---
		Type5	25	5	74748.0	5	2	66.8	1576.0	1323.0	---
		Type5	25	6	438300.0	5	1	63.7	1333.0	---	---
		Type5	25	0	1253842.0	5	2	68.6	1306.0	1161.0	---
	5530	Type5	25	6	438300.0	5	1	63.7	1333.0	---	---
		Type5	25	2	482958.0	5	1	60.9	1687.0	---	---
		Type5	25	5	74748.0	5	2	66.8	1576.0	1323.0	---
		Type5	25	3	845641.0	5	2	77.7	1776.0	1158.0	---
		Type5	25	0	1253842.0	5	2	68.6	1306.0	1161.0	---
		Type5	25	7	800152.0	5	3	91.2	1409.0	1681.0	1275.0
		Type5	25	4	1208428.0	5	2	77.4	1793.0	1510.0	---
11AX160MIMO	5250	Type5	25	1	119486.0	5	2	83.1	1420.0	1315.0	---
		Type5	25	2	482958.0	5	1	60.9	1687.0	---	---
		Type5	25	1	119486.0	5	2	83.1	1420.0	1315.0	---
		Type5	25	3	845641.0	5	2	77.7	1776.0	1158.0	---
		Type5	25	4	1208428.0	5	2	77.4	1793.0	1510.0	---
		Type5	25	5	74748.0	5	2	66.8	1576.0	1323.0	---
		Type5	25	6	438300.0	5	1	63.7	1333.0	---	---

		Type5	25	7	800152.0	5	3	91.2	1409.0	1681.0	1275.0
		Type5	25	0	1253842.0	5	2	68.6	1306.0	1161.0	---
	5570	Type5	25	7	800152.0	5	3	91.2	1409.0	1681.0	1275.0
		Type5	25	0	1253842.0	5	2	68.6	1306.0	1161.0	---
		Type5	25	1	119486.0	5	2	83.1	1420.0	1315.0	---
		Type5	25	2	482958.0	5	1	60.9	1687.0	---	---
		Type5	25	3	845641.0	5	2	77.7	1776.0	1158.0	---
		Type5	25	4	1208428.0	5	2	77.4	1793.0	1510.0	---
		Type5	25	5	74748.0	5	2	66.8	1576.0	1323.0	---
		Type5	25	6	438300.0	5	1	63.7	1333.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	26	11	312479.0	16	3	84.9	1129.0	1936.0	1199.0
		Type5	26	0	545865.0	16	3	83.6	1632.0	1195.0	1000.0
		Type5	26	15	292606.0	16	1	63.6	1647.0	---	---
		Type5	26	14	121457.0	16	3	99.8	1035.0	1515.0	1120.0
		Type5	26	12	482953.0	16	2	74.6	1959.0	1856.0	---
		Type5	26	16	461322.0	16	3	87.3	1931.0	1051.0	1831.0
		Type5	26	10	142890.0	16	1	55.0	1427.0	---	---
		Type5	26	9	675297.0	16	2	78.3	1591.0	1082.0	---
		Type5	26	2	184953.0	16	1	55.8	1532.0	---	---
		Type5	26	13	655022.0	16	1	63.3	1885.0	---	---
		Type5	26	1	14067.0	16	3	89.4	1173.0	1627.0	1656.0
		Type5	26	8	504006.0	16	2	68.3	1750.0	1954.0	---
		Type5	26	3	353759.0	16	3	90.9	1981.0	1554.0	1998.0
		Type5	26	4	526388.0	16	1	54.7	1825.0	---	---
		Type5	26	5	694806.0	16	3	97.7	1734.0	1202.0	1250.0
		Type5	26	6	163568.0	16	2	67.5	1571.0	1434.0	---
		Type5	26	7	333410.0	16	3	96.7	1589.0	1469.0	1268.0
	5500	Type5	26	8	504006.0	16	2	68.3	1750.0	1954.0	---
		Type5	26	13	655022.0	16	1	63.3	1885.0	---	---
		Type5	26	12	482953.0	16	2	74.6	1959.0	1856.0	---
		Type5	26	11	312479.0	16	3	84.9	1129.0	1936.0	1199.0
		Type5	26	10	142890.0	16	1	55.0	1427.0	---	---
		Type5	26	9	675297.0	16	2	78.3	1591.0	1082.0	---
		Type5	26	14	121457.0	16	3	99.8	1035.0	1515.0	1120.0
		Type5	26	7	333410.0	16	3	96.7	1589.0	1469.0	1268.0
		Type5	26	6	163568.0	16	2	67.5	1571.0	1434.0	---
		Type5	26	5	694806.0	16	3	97.7	1734.0	1202.0	1250.0
		Type5	26	4	526388.0	16	1	54.7	1825.0	---	---
		Type5	26	3	353759.0	16	3	90.9	1981.0	1554.0	1998.0
		Type5	26	2	184953.0	16	1	55.8	1532.0	---	---
		Type5	26	15	292606.0	16	1	63.6	1647.0	---	---
		Type5	26	0	545865.0	16	3	83.6	1632.0	1195.0	1000.0
		Type5	26	16	461322.0	16	3	87.3	1931.0	1051.0	1831.0
		Type5	26	1	14067.0	16	3	89.4	1173.0	1627.0	1656.0
11AX40MIMO	5270	Type5	26	6	163568.0	16	2	67.5	1571.0	1434.0	---
		Type5	26	14	121457.0	16	3	99.8	1035.0	1515.0	1120.0
		Type5	26	13	655022.0	16	1	63.3	1885.0	---	---
		Type5	26	12	482953.0	16	2	74.6	1959.0	1856.0	---
		Type5	26	11	312479.0	16	3	84.9	1129.0	1936.0	1199.0
		Type5	26	10	142890.0	16	1	55.0	1427.0	---	---
		Type5	26	9	675297.0	16	2	78.3	1591.0	1082.0	---
		Type5	26	15	292606.0	16	1	63.6	1647.0	---	---
		Type5	26	7	333410.0	16	3	96.7	1589.0	1469.0	1268.0
		Type5	26	16	461322.0	16	3	87.3	1931.0	1051.0	1831.0
		Type5	26	5	694806.0	16	3	97.7	1734.0	1202.0	1250.0
		Type5	26	4	526388.0	16	1	54.7	1825.0	---	---
		Type5	26	3	353759.0	16	3	90.9	1981.0	1554.0	1998.0
		Type5	26	2	184953.0	16	1	55.8	1532.0	---	---
		Type5	26	1	14067.0	16	3	89.4	1173.0	1627.0	1656.0
		Type5	26	0	545865.0	16	3	83.6	1632.0	1195.0	1000.0
		Type5	26	8	504006.0	16	2	68.3	1750.0	1954.0	---
	5510	Type5	26	10	142890.0	16	1	55.0	1427.0	---	---
		Type5	26	1	14067.0	16	3	89.4	1173.0	1627.0	1656.0
		Type5	26	2	184953.0	16	1	55.8	1532.0	---	---
		Type5	26	2	184953.0	16	1	55.8	1532.0	---	---

		Type5	26	4	526388.0	16	1	54.7	1825.0	---	---
		Type5	26	6	163568.0	16	2	67.5	1571.0	1434.0	---
		Type5	26	7	333410.0	16	3	96.7	1589.0	1469.0	1268.0
		Type5	26	0	545865.0	16	3	83.6	1632.0	1195.0	1000.0
		Type5	26	9	675297.0	16	2	78.3	1591.0	1082.0	---
		Type5	26	3	353759.0	16	3	90.9	1981.0	1554.0	1998.0
		Type5	26	11	312479.0	16	3	84.9	1129.0	1936.0	1199.0
		Type5	26	12	482953.0	16	2	74.6	1959.0	1856.0	---
		Type5	26	13	655022.0	16	1	63.3	1885.0	---	---
		Type5	26	14	121457.0	16	3	99.8	1035.0	1515.0	1120.0
		Type5	26	15	292606.0	16	1	63.6	1647.0	---	---
		Type5	26	16	461322.0	16	3	87.3	1931.0	1051.0	1831.0
		Type5	26	8	504006.0	16	2	68.3	1750.0	1954.0	---
		Type5	26	5	694806.0	16	3	97.7	1734.0	1202.0	1250.0
11AX80MIMO	5290	Type5	26	10	142890.0	16	1	55.0	1427.0	---	---
		Type5	26	15	292606.0	16	1	63.6	1647.0	---	---
		Type5	26	0	545865.0	16	3	83.6	1632.0	1195.0	1000.0
		Type5	26	14	121457.0	16	3	99.8	1035.0	1515.0	1120.0
		Type5	26	13	655022.0	16	1	63.3	1885.0	---	---
		Type5	26	11	312479.0	16	3	84.9	1129.0	1936.0	1199.0
		Type5	26	9	675297.0	16	2	78.3	1591.0	1082.0	---
		Type5	26	8	504006.0	16	2	68.3	1750.0	1954.0	---
		Type5	26	3	353759.0	16	3	90.9	1981.0	1554.0	1998.0
		Type5	26	6	163568.0	16	2	67.5	1571.0	1434.0	---
		Type5	26	5	694806.0	16	3	97.7	1734.0	1202.0	1250.0
		Type5	26	1	14067.0	16	3	89.4	1173.0	1627.0	1656.0
		Type5	26	16	461322.0	16	3	87.3	1931.0	1051.0	1831.0
		Type5	26	4	526388.0	16	1	54.7	1825.0	---	---
		Type5	26	7	333410.0	16	3	96.7	1589.0	1469.0	1268.0
	5530	Type5	26	12	482953.0	16	2	74.6	1959.0	1856.0	---
		Type5	26	2	184953.0	16	1	55.8	1532.0	---	---
		Type5	26	9	675297.0	16	2	78.3	1591.0	1082.0	---
		Type5	26	10	142890.0	16	1	55.0	1427.0	---	---
		Type5	26	11	312479.0	16	3	84.9	1129.0	1936.0	1199.0
		Type5	26	12	482953.0	16	2	74.6	1959.0	1856.0	---
		Type5	26	14	121457.0	16	3	99.8	1035.0	1515.0	1120.0
		Type5	26	6	163568.0	16	2	67.5	1571.0	1434.0	---
		Type5	26	15	292606.0	16	1	63.6	1647.0	---	---
		Type5	26	13	655022.0	16	1	63.3	1885.0	---	---
		Type5	26	16	461322.0	16	3	87.3	1931.0	1051.0	1831.0
		Type5	26	5	694806.0	16	3	97.7	1734.0	1202.0	1250.0
		Type5	26	4	526388.0	16	1	54.7	1825.0	---	---
		Type5	26	3	353759.0	16	3	90.9	1981.0	1554.0	1998.0
		Type5	26	2	184953.0	16	1	55.8	1532.0	---	---
		Type5	26	1	14067.0	16	3	89.4	1173.0	1627.0	1656.0
		Type5	26	0	545865.0	16	3	83.6	1632.0	1195.0	1000.0
		Type5	26	7	333410.0	16	3	96.7	1589.0	1469.0	1268.0
11AX160MIMO	5250	Type5	26	8	504006.0	16	2	68.3	1750.0	1954.0	---
		Type5	26	7	333410.0	16	3	96.7	1589.0	1469.0	1268.0
		Type5	26	6	163568.0	16	2	67.5	1571.0	1434.0	---
		Type5	26	4	526388.0	16	1	54.7	1825.0	---	---
		Type5	26	2	184953.0	16	1	55.8	1532.0	---	---
		Type5	26	8	504006.0	16	2	68.3	1750.0	1954.0	---
		Type5	26	0	545865.0	16	3	83.6	1632.0	1195.0	1000.0
		Type5	26	5	694806.0	16	3	97.7	1734.0	1202.0	1250.0
		Type5	26	1	14067.0	16	3	89.4	1173.0	1627.0	1656.0
		Type5	26	16	461322.0	16	3	87.3	1931.0	1051.0	1831.0
		Type5	26	10	142890.0	16	1	55.0	1427.0	---	---

		Type5	26	11	312479.0	16	3	84.9	1129.0	1936.0	1199.0
		Type5	26	12	482953.0	16	2	74.6	1959.0	1856.0	---
		Type5	26	13	655022.0	16	1	63.3	1885.0	---	---
		Type5	26	14	121457.0	16	3	99.8	1035.0	1515.0	1120.0
		Type5	26	15	292606.0	16	1	63.6	1647.0	---	---
		Type5	26	3	353759.0	16	3	90.9	1981.0	1554.0	1998.0
		Type5	26	9	675297.0	16	2	78.3	1591.0	1082.0	---
	5570	Type5	26	10	142890.0	16	1	55.0	1427.0	---	---
		Type5	26	11	312479.0	16	3	84.9	1129.0	1936.0	1199.0
		Type5	26	12	482953.0	16	2	74.6	1959.0	1856.0	---
		Type5	26	13	655022.0	16	1	63.3	1885.0	---	---
		Type5	26	9	675297.0	16	2	78.3	1591.0	1082.0	---
		Type5	26	15	292606.0	16	1	63.6	1647.0	---	---
		Type5	26	3	353759.0	16	3	90.9	1981.0	1554.0	1998.0
		Type5	26	14	121457.0	16	3	99.8	1035.0	1515.0	1120.0
		Type5	26	8	504006.0	16	2	68.3	1750.0	1954.0	---
		Type5	26	7	333410.0	16	3	96.7	1589.0	1469.0	1268.0
		Type5	26	6	163568.0	16	2	67.5	1571.0	1434.0	---
		Type5	26	4	526388.0	16	1	54.7	1825.0	---	---
		Type5	26	2	184953.0	16	1	55.8	1532.0	---	---
		Type5	26	1	14067.0	16	3	89.4	1173.0	1627.0	1656.0
		Type5	26	0	545865.0	16	3	83.6	1632.0	1195.0	1000.0
		Type5	26	16	461322.0	16	3	87.3	1931.0	1051.0	1831.0
		Type5	26	5	694806.0	16	3	97.7	1734.0	1202.0	1250.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	27	12	510977.0	19	1	52.5	1470.0	---	---
		Type5	27	0	565136.0	19	3	85.6	1946.0	1078.0	1015.0
		Type5	27	17	14858.0	19	1	60.4	1758.0	---	---
		Type5	27	16	491053.0	19	2	76.2	1376.0	1502.0	---
		Type5	27	15	339327.0	19	1	54.9	1479.0	---	---
		Type5	27	13	33698.0	19	1	52.3	1312.0	---	---
		Type5	27	18	167387.0	19	2	81.5	1491.0	1103.0	---
		Type5	27	11	357941.0	19	1	65.3	1848.0	---	---
		Type5	27	10	204582.0	19	3	88.1	1023.0	1124.0	1631.0
		Type5	27	2	243121.0	19	1	54.2	1111.0	---	---
		Type5	27	14	186023.0	19	2	74.1	1915.0	1200.0	---
		Type5	27	1	89970.0	19	2	68.6	1029.0	1780.0	---
		Type5	27	9	52247.0	19	3	85.8	1847.0	1348.0	1472.0
		Type5	27	3	396034.0	19	1	61.2	1104.0	---	---
		Type5	27	4	546225.0	19	3	97.1	1157.0	1969.0	1100.0
		Type5	27	5	70998.0	19	3	98.3	1142.0	1699.0	1622.0
		Type5	27	6	224093.0	19	1	62.4	1655.0	---	---
		Type5	27	7	376127.0	19	2	80.2	1126.0	1769.0	---
		Type5	27	8	527806.0	19	3	87.5	1216.0	1448.0	1179.0
	5500	Type5	27	9	52247.0	19	3	85.8	1847.0	1348.0	1472.0
		Type5	27	15	339327.0	19	1	54.9	1479.0	---	---
		Type5	27	14	186023.0	19	2	74.1	1915.0	1200.0	---
		Type5	27	13	33698.0	19	1	52.3	1312.0	---	---
		Type5	27	12	510977.0	19	1	52.5	1470.0	---	---
		Type5	27	11	357941.0	19	1	65.3	1848.0	---	---
		Type5	27	10	204582.0	19	3	88.1	1023.0	1124.0	1631.0
		Type5	27	16	491053.0	19	2	76.2	1376.0	1502.0	---
		Type5	27	8	527806.0	19	3	87.5	1216.0	1448.0	1179.0
		Type5	27	7	376127.0	19	2	80.2	1126.0	1769.0	---
		Type5	27	6	224093.0	19	1	62.4	1655.0	---	---
		Type5	27	5	70998.0	19	3	98.3	1142.0	1699.0	1622.0
		Type5	27	4	546225.0	19	3	97.1	1157.0	1969.0	1100.0
		Type5	27	3	396034.0	19	1	61.2	1104.0	---	---
		Type5	27	2	243121.0	19	1	54.2	1111.0	---	---
		Type5	27	17	14858.0	19	1	60.4	1758.0	---	---
		Type5	27	0	565136.0	19	3	85.6	1946.0	1078.0	1015.0
		Type5	27	18	167387.0	19	2	81.5	1491.0	1103.0	---
		Type5	27	1	89970.0	19	2	68.6	1029.0	1780.0	---
11AX40MIMO	5270	Type5	27	7	376127.0	19	2	80.2	1126.0	1769.0	---
		Type5	27	16	491053.0	19	2	76.2	1376.0	1502.0	---
		Type5	27	15	339327.0	19	1	54.9	1479.0	---	---
		Type5	27	14	186023.0	19	2	74.1	1915.0	1200.0	---
		Type5	27	13	33698.0	19	1	52.3	1312.0	---	---
		Type5	27	12	510977.0	19	1	52.5	1470.0	---	---
		Type5	27	11	357941.0	19	1	65.3	1848.0	---	---
		Type5	27	10	204582.0	19	3	88.1	1023.0	1124.0	1631.0
		Type5	27	17	14858.0	19	1	60.4	1758.0	---	---
		Type5	27	8	527806.0	19	3	87.5	1216.0	1448.0	1179.0
		Type5	27	18	167387.0	19	2	81.5	1491.0	1103.0	---
		Type5	27	6	224093.0	19	1	62.4	1655.0	---	---
		Type5	27	5	70998.0	19	3	98.3	1142.0	1699.0	1622.0
		Type5	27	4	546225.0	19	3	97.1	1157.0	1969.0	1100.0
		Type5	27	3	396034.0	19	1	61.2	1104.0	---	---
		Type5	27	2	243121.0	19	1	54.2	1111.0	---	---

	5510	Type5	27	1	89970.0	19	2	68.6	1029.0	1780.0	---
		Type5	27	0	565136.0	19	3	85.6	1946.0	1078.0	1015.0
		Type5	27	9	52247.0	19	3	85.8	1847.0	1348.0	1472.0
		Type5	27	11	357941.0	19	1	65.3	1848.0	---	---
		Type5	27	1	89970.0	19	2	68.6	1029.0	1780.0	---
		Type5	27	2	243121.0	19	1	54.2	1111.0	---	---
		Type5	27	4	546225.0	19	3	97.1	1157.0	1969.0	1100.0
		Type5	27	6	224093.0	19	1	62.4	1655.0	---	---
		Type5	27	7	376127.0	19	2	80.2	1126.0	1769.0	---
		Type5	27	8	527806.0	19	3	87.5	1216.0	1448.0	1179.0
		Type5	27	0	565136.0	19	3	85.6	1946.0	1078.0	1015.0
		Type5	27	10	204582.0	19	3	88.1	1023.0	1124.0	1631.0
		Type5	27	3	396034.0	19	1	61.2	1104.0	---	---
		Type5	27	12	510977.0	19	1	52.5	1470.0	---	---
		Type5	27	13	33698.0	19	1	52.3	1312.0	---	---
		Type5	27	14	186023.0	19	2	74.1	1915.0	1200.0	---
		Type5	27	15	339327.0	19	1	54.9	1479.0	---	---
		Type5	27	16	491053.0	19	2	76.2	1376.0	1502.0	---
		Type5	27	17	14858.0	19	1	60.4	1758.0	---	---
		Type5	27	18	167387.0	19	2	81.5	1491.0	1103.0	---
		Type5	27	9	52247.0	19	3	85.8	1847.0	1348.0	1472.0
		Type5	27	5	70998.0	19	3	98.3	1142.0	1699.0	1622.0
11AX80MIMO	5290	Type5	27	11	357941.0	19	1	65.3	1848.0	---	---
		Type5	27	17	14858.0	19	1	60.4	1758.0	---	---
		Type5	27	0	565136.0	19	3	85.6	1946.0	1078.0	1015.0
		Type5	27	16	491053.0	19	2	76.2	1376.0	1502.0	---
		Type5	27	15	339327.0	19	1	54.9	1479.0	---	---
		Type5	27	14	186023.0	19	2	74.1	1915.0	1200.0	---
		Type5	27	12	510977.0	19	1	52.5	1470.0	---	---
		Type5	27	10	204582.0	19	3	88.1	1023.0	1124.0	1631.0
		Type5	27	9	52247.0	19	3	85.8	1847.0	1348.0	1472.0
		Type5	27	3	396034.0	19	1	61.2	1104.0	---	---
		Type5	27	7	376127.0	19	2	80.2	1126.0	1769.0	---
		Type5	27	6	224093.0	19	1	62.4	1655.0	---	---
		Type5	27	1	89970.0	19	2	68.6	1029.0	1780.0	---
		Type5	27	5	70998.0	19	3	98.3	1142.0	1699.0	1622.0
		Type5	27	18	167387.0	19	2	81.5	1491.0	1103.0	---
		Type5	27	4	546225.0	19	3	97.1	1157.0	1969.0	1100.0
		Type5	27	8	527806.0	19	3	87.5	1216.0	1448.0	1179.0
		Type5	27	13	33698.0	19	1	52.3	1312.0	---	---
		Type5	27	2	243121.0	19	1	54.2	1111.0	---	---
	5530	Type5	27	10	204582.0	19	3	88.1	1023.0	1124.0	1631.0
		Type5	27	11	357941.0	19	1	65.3	1848.0	---	---
		Type5	27	12	510977.0	19	1	52.5	1470.0	---	---
		Type5	27	13	33698.0	19	1	52.3	1312.0	---	---
		Type5	27	14	186023.0	19	2	74.1	1915.0	1200.0	---
		Type5	27	16	491053.0	19	2	76.2	1376.0	1502.0	---
		Type5	27	7	376127.0	19	2	80.2	1126.0	1769.0	---
		Type5	27	17	14858.0	19	1	60.4	1758.0	---	---
		Type5	27	15	339327.0	19	1	54.9	1479.0	---	---
		Type5	27	18	167387.0	19	2	81.5	1491.0	1103.0	---
		Type5	27	6	224093.0	19	1	62.4	1655.0	---	---
		Type5	27	5	70998.0	19	3	98.3	1142.0	1699.0	1622.0
		Type5	27	4	546225.0	19	3	97.1	1157.0	1969.0	1100.0
		Type5	27	3	396034.0	19	1	61.2	1104.0	---	---
		Type5	27	2	243121.0	19	1	54.2	1111.0	---	---
		Type5	27	1	89970.0	19	2	68.6	1029.0	1780.0	---
		Type5	27	0	565136.0	19	3	85.6	1946.0	1078.0	1015.0

11AX160MIMO	5250	Type5	27	8	527806.0	19	3	87.5	1216.0	1448.0	1179.0
		Type5	27	9	52247.0	19	3	85.8	1847.0	1348.0	1472.0
		Type5	27	8	527806.0	19	3	87.5	1216.0	1448.0	1179.0
		Type5	27	7	376127.0	19	2	80.2	1126.0	1769.0	---
		Type5	27	6	224093.0	19	1	62.4	1655.0	---	---
		Type5	27	4	546225.0	19	3	97.1	1157.0	1969.0	1100.0
		Type5	27	2	243121.0	19	1	54.2	1111.0	---	---
		Type5	27	9	52247.0	19	3	85.8	1847.0	1348.0	1472.0
		Type5	27	0	565136.0	19	3	85.6	1946.0	1078.0	1015.0
		Type5	27	5	70998.0	19	3	98.3	1142.0	1699.0	1622.0
		Type5	27	1	89970.0	19	2	68.6	1029.0	1780.0	---
		Type5	27	18	167387.0	19	2	81.5	1491.0	1103.0	---
		Type5	27	11	357941.0	19	1	65.3	1848.0	---	---
		Type5	27	12	510977.0	19	1	52.5	1470.0	---	---
		Type5	27	13	33698.0	19	1	52.3	1312.0	---	---
		Type5	27	14	186023.0	19	2	74.1	1915.0	1200.0	---
		Type5	27	15	339327.0	19	1	54.9	1479.0	---	---
		Type5	27	16	491053.0	19	2	76.2	1376.0	1502.0	---
		Type5	27	17	14858.0	19	1	60.4	1758.0	---	---
		Type5	27	3	396034.0	19	1	61.2	1104.0	---	---
		Type5	27	10	204582.0	19	3	88.1	1023.0	1124.0	1631.0
	5570	Type5	27	11	357941.0	19	1	65.3	1848.0	---	---
		Type5	27	12	510977.0	19	1	52.5	1470.0	---	---
		Type5	27	13	33698.0	19	1	52.3	1312.0	---	---
		Type5	27	14	186023.0	19	2	74.1	1915.0	1200.0	---
		Type5	27	15	339327.0	19	1	54.9	1479.0	---	---
		Type5	27	10	204582.0	19	3	88.1	1023.0	1124.0	1631.0
		Type5	27	17	14858.0	19	1	60.4	1758.0	---	---
		Type5	27	3	396034.0	19	1	61.2	1104.0	---	---
		Type5	27	16	491053.0	19	2	76.2	1376.0	1502.0	---
		Type5	27	9	52247.0	19	3	85.8	1847.0	1348.0	1472.0
		Type5	27	8	527806.0	19	3	87.5	1216.0	1448.0	1179.0
		Type5	27	7	376127.0	19	2	80.2	1126.0	1769.0	---
		Type5	27	6	224093.0	19	1	62.4	1655.0	---	---
		Type5	27	4	546225.0	19	3	97.1	1157.0	1969.0	1100.0
		Type5	27	2	243121.0	19	1	54.2	1111.0	---	---
		Type5	27	1	89970.0	19	2	68.6	1029.0	1780.0	---
		Type5	27	0	565136.0	19	3	85.6	1946.0	1078.0	1015.0
		Type5	27	18	167387.0	19	2	81.5	1491.0	1103.0	---
		Type5	27	5	70998.0	19	3	98.3	1142.0	1699.0	1622.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	28	7	205370.0	10	3	92.2	1898.0	1252.0	1713.0
		Type5	28	0	507709.0	10	1	50.5	1857.0	---	---
		Type5	28	10	932305.0	10	1	63.1	1782.0	---	---
		Type5	28	8	446940.0	10	3	89.0	1260.0	1706.0	1411.0
		Type5	28	11	176231.0	10	1	55.3	1522.0	---	---
		Type5	28	6	960895.0	10	2	78.1	1301.0	1757.0	---
		Type5	28	5	718312.0	10	3	92.3	1180.0	1486.0	1492.0
		Type5	28	4	477675.0	10	2	75.1	1254.0	1052.0	---
		Type5	28	3	235634.0	10	2	76.9	1125.0	1474.0	---
		Type5	28	2	989003.0	10	3	85.8	1774.0	1002.0	1967.0
	5500	Type5	28	1	750249.0	10	1	55.7	1246.0	---	---
		Type5	28	9	689225.0	10	2	70.9	1578.0	1620.0	---
		Type5	28	5	718312.0	10	3	92.3	1180.0	1486.0	1492.0
		Type5	28	9	689225.0	10	2	70.9	1578.0	1620.0	---
		Type5	28	8	446940.0	10	3	89.0	1260.0	1706.0	1411.0
		Type5	28	7	205370.0	10	3	92.2	1898.0	1252.0	1713.0
		Type5	28	6	960895.0	10	2	78.1	1301.0	1757.0	---
		Type5	28	4	477675.0	10	2	75.1	1254.0	1052.0	---
		Type5	28	3	235634.0	10	2	76.9	1125.0	1474.0	---
		Type5	28	2	989003.0	10	3	85.8	1774.0	1002.0	1967.0
11AX40MIMO	5270	Type5	28	10	932305.0	10	1	63.1	1782.0	---	---
		Type5	28	0	507709.0	10	1	50.5	1857.0	---	---
		Type5	28	11	176231.0	10	1	55.3	1522.0	---	---
		Type5	28	1	750249.0	10	1	55.7	1246.0	---	---
		Type5	28	11	176231.0	10	1	55.3	1522.0	---	---
		Type5	28	11	176231.0	10	1	55.3	1522.0	---	---
		Type5	28	11	176231.0	10	1	55.3	1522.0	---	---
		Type5	28	11	176231.0	10	1	55.3	1522.0	---	---
		Type5	28	11	176231.0	10	1	55.3	1522.0	---	---
		Type5	28	11	176231.0	10	1	55.3	1522.0	---	---
	5510	Type5	28	11	176231.0	10	1	55.3	1522.0	---	---
		Type5	28	0	507709.0	10	1	50.5	1857.0	---	---
		Type5	28	1	750249.0	10	1	55.7	1246.0	---	---
		Type5	28	2	989003.0	10	3	85.8	1774.0	1002.0	1967.0
		Type5	28	3	235634.0	10	2	76.9	1125.0	1474.0	---
		Type5	28	4	477675.0	10	2	75.1	1254.0	1052.0	---
		Type5	28	5	718312.0	10	3	92.3	1180.0	1486.0	1492.0
		Type5	28	6	960895.0	10	2	78.1	1301.0	1757.0	---
		Type5	28	7	205370.0	10	3	92.2	1898.0	1252.0	1713.0
		Type5	28	8	446940.0	10	3	89.0	1260.0	1706.0	1411.0
11AX80MIMO	5290	Type5	28	9	689225.0	10	2	70.9	1578.0	1620.0	---
		Type5	28	10	932305.0	10	1	63.1	1782.0	---	---
		Type5	28	6	960895.0	10	2	78.1	1301.0	1757.0	---
		Type5	28	10	932305.0	10	1	63.1	1782.0	---	---
		Type5	28	0	507709.0	10	1	50.5	1857.0	---	---
		Type5	28	9	689225.0	10	2	70.9	1578.0	1620.0	---
		Type5	28	8	446940.0	10	3	89.0	1260.0	1706.0	1411.0
		Type5	28	7	205370.0	10	3	92.2	1898.0	1252.0	1713.0
		Type5	28	6	960895.0	10	2	78.1	1301.0	1757.0	---
		Type5	28	5	718312.0	10	3	92.3	1180.0	1486.0	1492.0

		Type5	28	4	477675.0	10	2	75.1	1254.0	1052.0	---
		Type5	28	11	176231.0	10	1	55.3	1522.0	---	---
		Type5	28	3	235634.0	10	2	76.9	1125.0	1474.0	---
		Type5	28	2	989003.0	10	3	85.8	1774.0	1002.0	1967.0
		Type5	28	1	750249.0	10	1	55.7	1246.0	---	---
		Type5	28	8	446940.0	10	3	89.0	1260.0	1706.0	1411.0
	5530	Type5	28	10	932305.0	10	1	63.1	1782.0	---	---
		Type5	28	4	477675.0	10	2	75.1	1254.0	1052.0	---
		Type5	28	9	689225.0	10	2	70.9	1578.0	1620.0	---
		Type5	28	8	446940.0	10	3	89.0	1260.0	1706.0	1411.0
		Type5	28	7	205370.0	10	3	92.2	1898.0	1252.0	1713.0
		Type5	28	5	718312.0	10	3	92.3	1180.0	1486.0	1492.0
		Type5	28	2	989003.0	10	3	85.8	1774.0	1002.0	1967.0
		Type5	28	1	750249.0	10	1	55.7	1246.0	---	---
		Type5	28	0	507709.0	10	1	50.5	1857.0	---	---
		Type5	28	11	176231.0	10	1	55.3	1522.0	---	---
		Type5	28	6	960895.0	10	2	78.1	1301.0	1757.0	---
		Type5	28	3	235634.0	10	2	76.9	1125.0	1474.0	---
11AX160MIMO	5250	Type5	28	3	235634.0	10	2	76.9	1125.0	1474.0	---
		Type5	28	0	507709.0	10	1	50.5	1857.0	---	---
		Type5	28	2	989003.0	10	3	85.8	1774.0	1002.0	1967.0
		Type5	28	4	477675.0	10	2	75.1	1254.0	1052.0	---
		Type5	28	5	718312.0	10	3	92.3	1180.0	1486.0	1492.0
		Type5	28	7	205370.0	10	3	92.2	1898.0	1252.0	1713.0
		Type5	28	8	446940.0	10	3	89.0	1260.0	1706.0	1411.0
		Type5	28	9	689225.0	10	2	70.9	1578.0	1620.0	---
		Type5	28	10	932305.0	10	1	63.1	1782.0	---	---
		Type5	28	11	176231.0	10	1	55.3	1522.0	---	---
		Type5	28	6	960895.0	10	2	78.1	1301.0	1757.0	---
		Type5	28	1	750249.0	10	1	55.7	1246.0	---	---
	5570	Type5	28	1	750249.0	10	1	55.7	1246.0	---	---
		Type5	28	10	932305.0	10	1	63.1	1782.0	---	---
		Type5	28	9	689225.0	10	2	70.9	1578.0	1620.0	---
		Type5	28	8	446940.0	10	3	89.0	1260.0	1706.0	1411.0
		Type5	28	7	205370.0	10	3	92.2	1898.0	1252.0	1713.0
		Type5	28	6	960895.0	10	2	78.1	1301.0	1757.0	---
		Type5	28	5	718312.0	10	3	92.3	1180.0	1486.0	1492.0
		Type5	28	4	477675.0	10	2	75.1	1254.0	1052.0	---
		Type5	28	2	989003.0	10	3	85.8	1774.0	1002.0	1967.0
		Type5	28	0	507709.0	10	1	50.5	1857.0	---	---
		Type5	28	11	176231.0	10	1	55.3	1522.0	---	---
		Type5	28	3	235634.0	10	2	76.9	1125.0	1474.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PR11 (μs)	PR12 (μs)	PR13 (μs)
11AX20MIMO	5260	Type5	29	12	219083.0	17	1	61.8	1585.0	---	---
		Type5	29	0	277485.0	17	3	83.4	1454.0	1205.0	1801.0
		Type5	29	16	198794.0	17	2	76.0	1733.0	1255.0	---
		Type5	29	15	37916.0	17	1	65.7	1496.0	---	---
		Type5	29	13	379234.0	17	2	79.4	1933.0	1667.0	---
		Type5	29	17	359754.0	17	2	81.0	1326.0	1668.0	---
		Type5	29	11	57684.0	17	2	67.2	1288.0	1405.0	---
		Type5	29	10	562025.0	17	1	60.7	1033.0	---	---
		Type5	29	9	398605.0	17	3	93.5	1867.0	1373.0	1087.0
		Type5	29	2	598445.0	17	3	90.4	1079.0	1986.0	1674.0
		Type5	29	14	540896.0	17	2	81.4	1096.0	1464.0	---
		Type5	29	1	437880.0	17	3	97.3	1319.0	1826.0	1635.0
		Type5	29	8	238032.0	17	3	91.1	1105.0	1599.0	1442.0
		Type5	29	3	97088.0	17	3	91.8	1563.0	1151.0	1802.0
		Type5	29	4	257251.0	17	3	98.2	1876.0	1977.0	1766.0
		Type5	29	5	419893.0	17	1	59.5	1952.0	---	---
		Type5	29	6	580724.0	17	2	80.0	1253.0	1137.0	---
		Type5	29	7	77366.0	17	3	86.5	1054.0	1128.0	1828.0
	5500	Type5	29	8	238032.0	17	3	91.1	1105.0	1599.0	1442.0
		Type5	29	14	540896.0	17	2	81.4	1096.0	1464.0	---
		Type5	29	13	379234.0	17	2	79.4	1933.0	1667.0	---
		Type5	29	12	219083.0	17	1	61.8	1585.0	---	---
		Type5	29	11	57684.0	17	2	67.2	1288.0	1405.0	---
		Type5	29	10	562025.0	17	1	60.7	1033.0	---	---
		Type5	29	9	398605.0	17	3	93.5	1867.0	1373.0	1087.0
		Type5	29	15	37916.0	17	1	65.7	1496.0	---	---
		Type5	29	7	77366.0	17	3	86.5	1054.0	1128.0	1828.0
		Type5	29	6	580724.0	17	2	80.0	1253.0	1137.0	---
		Type5	29	5	419893.0	17	1	59.5	1952.0	---	---
		Type5	29	4	257251.0	17	3	98.2	1876.0	1977.0	1766.0
		Type5	29	3	97088.0	17	3	91.8	1563.0	1151.0	1802.0
		Type5	29	2	598445.0	17	3	90.4	1079.0	1986.0	1674.0
		Type5	29	16	198794.0	17	2	76.0	1733.0	1255.0	---
		Type5	29	0	277485.0	17	3	83.4	1454.0	1205.0	1801.0
		Type5	29	17	359754.0	17	2	81.0	1326.0	1668.0	---
		Type5	29	1	437880.0	17	3	97.3	1319.0	1826.0	1635.0
11AX40MIMO	5270	Type5	29	7	77366.0	17	3	86.5	1054.0	1128.0	1828.0
		Type5	29	15	37916.0	17	1	65.7	1496.0	---	---
		Type5	29	14	540896.0	17	2	81.4	1096.0	1464.0	---
		Type5	29	13	379234.0	17	2	79.4	1933.0	1667.0	---
		Type5	29	12	219083.0	17	1	61.8	1585.0	---	---
		Type5	29	11	57684.0	17	2	67.2	1288.0	1405.0	---
		Type5	29	10	562025.0	17	1	60.7	1033.0	---	---
		Type5	29	16	198794.0	17	2	76.0	1733.0	1255.0	---
		Type5	29	8	238032.0	17	3	91.1	1105.0	1599.0	1442.0
		Type5	29	17	359754.0	17	2	81.0	1326.0	1668.0	---
		Type5	29	6	580724.0	17	2	80.0	1253.0	1137.0	---
		Type5	29	5	419893.0	17	1	59.5	1952.0	---	---
		Type5	29	4	257251.0	17	3	98.2	1876.0	1977.0	1766.0
		Type5	29	3	97088.0	17	3	91.8	1563.0	1151.0	1802.0
		Type5	29	2	598445.0	17	3	90.4	1079.0	1986.0	1674.0
		Type5	29	1	437880.0	17	3	97.3	1319.0	1826.0	1635.0
		Type5	29	0	277485.0	17	3	83.4	1454.0	1205.0	1801.0
		Type5	29	9	398605.0	17	3	93.5	1867.0	1373.0	1087.0

	5510	Type5	29	11	57684.0	17	2	67.2	1288.0	1405.0	---
		Type5	29	1	437880.0	17	3	97.3	1319.0	1826.0	1635.0
		Type5	29	2	598445.0	17	3	90.4	1079.0	1986.0	1674.0
		Type5	29	4	257251.0	17	3	98.2	1876.0	1977.0	1766.0
		Type5	29	6	580724.0	17	2	80.0	1253.0	1137.0	---
		Type5	29	7	77366.0	17	3	86.5	1054.0	1128.0	1828.0
		Type5	29	8	238032.0	17	3	91.1	1105.0	1599.0	1442.0
		Type5	29	0	277485.0	17	3	83.4	1454.0	1205.0	1801.0
		Type5	29	10	562025.0	17	1	60.7	1033.0	---	---
		Type5	29	3	97088.0	17	3	91.8	1563.0	1151.0	1802.0
		Type5	29	12	219083.0	17	1	61.8	1585.0	---	---
		Type5	29	13	379234.0	17	2	79.4	1933.0	1667.0	---
		Type5	29	14	540896.0	17	2	81.4	1096.0	1464.0	---
		Type5	29	15	37916.0	17	1	65.7	1496.0	---	---
		Type5	29	16	198794.0	17	2	76.0	1733.0	1255.0	---
		Type5	29	17	359754.0	17	2	81.0	1326.0	1668.0	---
		Type5	29	9	398605.0	17	3	93.5	1867.0	1373.0	1087.0
11AX80MIMO	5290	Type5	29	5	419893.0	17	1	59.5	1952.0	---	---
		Type5	29	11	57684.0	17	2	67.2	1288.0	1405.0	---
		Type5	29	16	198794.0	17	2	76.0	1733.0	1255.0	---
		Type5	29	0	277485.0	17	3	83.4	1454.0	1205.0	1801.0
		Type5	29	15	37916.0	17	1	65.7	1496.0	---	---
		Type5	29	14	540896.0	17	2	81.4	1096.0	1464.0	---
		Type5	29	12	219083.0	17	1	61.8	1585.0	---	---
		Type5	29	10	562025.0	17	1	60.7	1033.0	---	---
		Type5	29	9	398605.0	17	3	93.5	1867.0	1373.0	1087.0
		Type5	29	8	238032.0	17	3	91.1	1105.0	1599.0	1442.0
		Type5	29	2	598445.0	17	3	90.4	1079.0	1986.0	1674.0
		Type5	29	6	580724.0	17	2	80.0	1253.0	1137.0	---
		Type5	29	5	419893.0	17	1	59.5	1952.0	---	---
		Type5	29	17	359754.0	17	2	81.0	1326.0	1668.0	---
		Type5	29	4	257251.0	17	3	98.2	1876.0	1977.0	1766.0
		Type5	29	1	437880.0	17	3	97.3	1319.0	1826.0	1635.0
		Type5	29	3	97088.0	17	3	91.8	1563.0	1151.0	1802.0
		Type5	29	7	77366.0	17	3	86.5	1054.0	1128.0	1828.0
		Type5	29	13	379234.0	17	2	79.4	1933.0	1667.0	---
	5530	Type5	29	8	238032.0	17	3	91.1	1105.0	1599.0	1442.0
		Type5	29	10	562025.0	17	1	60.7	1033.0	---	---
		Type5	29	11	57684.0	17	2	67.2	1288.0	1405.0	---
		Type5	29	12	219083.0	17	1	61.8	1585.0	---	---
		Type5	29	13	379234.0	17	2	79.4	1933.0	1667.0	---
		Type5	29	15	37916.0	17	1	65.7	1496.0	---	---
		Type5	29	7	77366.0	17	3	86.5	1054.0	1128.0	1828.0
		Type5	29	16	198794.0	17	2	76.0	1733.0	1255.0	---
		Type5	29	14	540896.0	17	2	81.4	1096.0	1464.0	---
		Type5	29	17	359754.0	17	2	81.0	1326.0	1668.0	---
		Type5	29	5	419893.0	17	1	59.5	1952.0	---	---
		Type5	29	4	257251.0	17	3	98.2	1876.0	1977.0	1766.0
		Type5	29	3	97088.0	17	3	91.8	1563.0	1151.0	1802.0
		Type5	29	2	598445.0	17	3	90.4	1079.0	1986.0	1674.0
		Type5	29	1	437880.0	17	3	97.3	1319.0	1826.0	1635.0
		Type5	29	0	277485.0	17	3	83.4	1454.0	1205.0	1801.0
		Type5	29	6	580724.0	17	2	80.0	1253.0	1137.0	---
		Type5	29	9	398605.0	17	3	93.5	1867.0	1373.0	1087.0
11AX160MIMO	5250	Type5	29	7	77366.0	17	3	86.5	1054.0	1128.0	1828.0
		Type5	29	6	580724.0	17	2	80.0	1253.0	1137.0	---
		Type5	29	4	257251.0	17	3	98.2	1876.0	1977.0	1766.0
		Type5	29	2	598445.0	17	3	90.4	1079.0	1986.0	1674.0

		Type5	29	8	238032.0	17	3	91.1	1105.0	1599.0	1442.0
		Type5	29	0	277485.0	17	3	83.4	1454.0	1205.0	1801.0
		Type5	29	5	419893.0	17	1	59.5	1952.0	---	---
		Type5	29	1	437880.0	17	3	97.3	1319.0	1826.0	1635.0
		Type5	29	17	359754.0	17	2	81.0	1326.0	1668.0	---
		Type5	29	10	562025.0	17	1	60.7	1033.0	---	---
		Type5	29	11	57684.0	17	2	67.2	1288.0	1405.0	---
		Type5	29	12	219083.0	17	1	61.8	1585.0	---	---
		Type5	29	13	379234.0	17	2	79.4	1933.0	1667.0	---
		Type5	29	14	540896.0	17	2	81.4	1096.0	1464.0	---
		Type5	29	15	37916.0	17	1	65.7	1496.0	---	---
		Type5	29	16	198794.0	17	2	76.0	1733.0	1255.0	---
		Type5	29	3	97088.0	17	3	91.8	1563.0	1151.0	1802.0
		Type5	29	9	398605.0	17	3	93.5	1867.0	1373.0	1087.0
	5570	Type5	29	10	562025.0	17	1	60.7	1033.0	---	---
		Type5	29	11	57684.0	17	2	67.2	1288.0	1405.0	---
		Type5	29	12	219083.0	17	1	61.8	1585.0	---	---
		Type5	29	13	379234.0	17	2	79.4	1933.0	1667.0	---
		Type5	29	14	540896.0	17	2	81.4	1096.0	1464.0	---
		Type5	29	9	398605.0	17	3	93.5	1867.0	1373.0	1087.0
		Type5	29	16	198794.0	17	2	76.0	1733.0	1255.0	---
		Type5	29	3	97088.0	17	3	91.8	1563.0	1151.0	1802.0
		Type5	29	15	37916.0	17	1	65.7	1496.0	---	---
		Type5	29	8	238032.0	17	3	91.1	1105.0	1599.0	1442.0
		Type5	29	7	77366.0	17	3	86.5	1054.0	1128.0	1828.0
		Type5	29	6	580724.0	17	2	80.0	1253.0	1137.0	---
		Type5	29	4	257251.0	17	3	98.2	1876.0	1977.0	1766.0
		Type5	29	2	598445.0	17	3	90.4	1079.0	1986.0	1674.0
		Type5	29	1	437880.0	17	3	97.3	1319.0	1826.0	1635.0
		Type5	29	0	277485.0	17	3	83.4	1454.0	1205.0	1801.0
		Type5	29	17	359754.0	17	2	81.0	1326.0	1668.0	---
		Type5	29	5	419893.0	17	1	59.5	1952.0	---	---

Bridge Mode**Test Result**

Test Mode	Frequency[MHz]	Radar Type	Pass Times	Fail Times	Probability (%)	Limit (%)	Verdict
11AX20MIMO	5260	Type1	26	4	86.67	60	PASS

Test Mode	Channel	Radar Type	Trial ID	Pulse width(μ s)	PRI(μ s)	Pulses per Burst	Detection (1: Yes; 0: No)
11AX20MI MO	5260	Type1	0	8.2	355.0	17	1
		Type1	1	6.1	487.0	16	1
		Type1	2	7.1	344.0	16	1
		Type1	3	9.8	288.0	18	0
		Type1	4	8.9	230.0	18	0
		Type1	5	7.9	432.0	17	1
		Type1	6	8.2	207.0	17	1
		Type1	7	7.5	443.0	17	1
		Type1	8	8.1	439.0	17	1
		Type1	9	6.2	223.0	16	1
		Type1	10	8.9	208.0	18	1
		Type1	11	9.6	463.0	18	1
		Type1	12	8.2	441.0	17	1
		Type1	13	7.2	323.0	16	1
		Type1	14	9.5	297.0	18	0
		Type1	15	8.0	412.0	17	1
		Type1	16	10.0	324.0	18	1
		Type1	17	7.4	271.0	17	1
		Type1	18	7.9	349.0	17	1
		Type1	19	7.3	409.0	16	1
		Type1	20	8.7	373.0	18	1
		Type1	21	7.2	254.0	16	1
		Type1	22	9.9	274.0	18	1
		Type1	23	7.9	278.0	17	1
		Type1	24	7.5	317.0	17	1
		Type1	25	6.1	260.0	16	1
		Type1	26	8.8	211.0	18	0
		Type1	27	9.7	272.0	18	1
		Type1	28	7.4	264.0	17	1
		Type1	29	9.2	284.0	18	1

***** END OF REPORT *****