FCC PART 15.247

TEST REPORT

For

Grandstream Networks, Inc.

126 Brookline Ave, 3rd Floor Boston, MA 02215, USA

FCC ID: YZZGXV3240V3

Report Type:	**Product Type:**
Original Report	IP Multimedia Phone

Report Number: RSZ170927001-00B

Report Date: 2017-12-26

Reviewed By: Candy Li, RF Engineer

Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen)
6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China
Tel: +86-755-33320018
Fax: +86-755-33320008
www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★". This report may contain data were produced under the subcontractor and shall be marked with an asterisk "△".

TABLE OF CONTENTS

GENERAL INFORMATION **4**
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
OBJECTIVE 4
RELATED SUBMITTAL(S)/GRANT(S) 4
TEST METHODOLOGY 4
MEASUREMENT UNCERTAINTY 5
TEST FACILITY 5
SYSTEM TEST CONFIGURATION **6**
DESCRIPTION OF TEST CONFIGURATION 6
EUT EXERCISE SOFTWARE 6
SPECIAL ACCESSORIES 6
EQUIPMENT MODIFICATIONS 6
SUPPORT EQUIPMENT LIST AND DETAILS 6
EXTERNAL I/O CABLE 6
BLOCK DIAGRAM OF TEST SETUP 7
SUMMARY OF TEST RESULTS **8**
TEST EQUIPMENT LIST **9**
FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE) **11**
APPLICABLE STANDARD 11
RESULT 11
FCC §15.203 – ANTENNA REQUIREMENT **12**
APPLICABLE STANDARD 12
ANTENNA CONNECTOR CONSTRUCTION 12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS **13**
APPLICABLE STANDARD 13
EUT SETUP 13
EMI TEST RECEIVER SETUP 13
TEST PROCEDURE 13
CORRECTED FACTOR & MARGIN CALCULATION 14
TEST RESULTS SUMMARY 14
TEST DATA 14
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS **21**
APPLICABLE STANDARD 21
EUT SETUP 21
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP 22
TEST PROCEDURE 22
CORRECTED AMPLITUDE & MARGIN CALCULATION 22
TEST RESULTS SUMMARY 23
TEST DATA 23
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST **28**
APPLICABLE STANDARD 28
TEST PROCEDURE 28
TEST DATA 28

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH 35
APPLICABLE STANDARD 35
TEST PROCEDURE 35
TEST DATA 35
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST 41
APPLICABLE STANDARD 41
TEST PROCEDURE 41
TEST DATA 41
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME) 44
APPLICABLE STANDARD 44
TEST PROCEDURE 44
TEST DATA 44
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT 60
APPLICABLE STANDARD 60
TEST PROCEDURE 60
TEST DATA 60
FCC §15.247(d) - BAND EDGES TESTING 62
APPLICABLE STANDARD 62
TEST PROCEDURE 62
TEST DATA 62

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Grandstream Networks, Inc.'s* product, model number: *GXV3240 (FCC ID: YZZGXV3240V3)* in this report was an *IP Multimedia Phone,* which was measured approximately:20.62 cm (L) × 19.65 cm (W) ×8.52 cm (H), rated with input voltage: DC 12V from adapter or DC 48V powered by POE supply.

Adapter 1 Information:
Model: F18W8-120150SPAUY
Input: AC 100-240V, 50/60Hz, 0.6A
Output: DC 12V, 1.5 A

Adapter 2 Information:
Model: H18US1200150A
Input: AC 100-240V, 50/60Hz, 0.8A
Output: DC 12V, 1.5 A

**All measurement and test data in this report was gathered from production sample serial number: 1702161 (Assigned by BACL, shenzhen).The EUT supplied by the applicant was received on 2017-09-27.*

Objective

This test report is prepared on behalf of *Grandstream Networks, Inc. i*n accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS and Part 15B JBP submissions with FCC ID: YZZGXV3240V3.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.5dB
RF conducted test with spectrum		±1.5dB
AC Power Lines Conducted Emissions		±1.95dB
Radiated Emissions	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		-30~60 ℃
Humidity		±6%
Supply voltages		±0.4%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

Bay Area Compliance Laboratories Corp. (Shenzhen) has been accredited to ISO/IEC 17025 by CNAS (Lab code: L2408). And accredited to ISO/IEC 17025 by NVLAP (Lab code: 200707-0), the FCC Designation No. CN5001 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Shenzhen) was registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

‘‘RF test tool” software was made to the EUT tested.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
N/A	N/A	N/A	N/A

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielded Un-detachable DC Cable	2.5	EUT	Adapter
Un-shielded Un-detachable AC cable	1.0	Socket	LISN

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i) & §1.1307 (b) (1) & §2.1091	Maximum Permissible exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2017-08-04	2018-08-04
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2016-12-07	2017-12-07
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2017-05-21	2017-11-19
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
N/A	Conducted Emission Cable	N/A	UF A210B-1-0720-504504	2017-05-12	2017-11-12
Radiated Emission Test					
Sunol Sciences	Horn Antenna	DRH-118	A052604	2014-12-29	2017-12-28
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2017-04-24	2018-04-24
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2017-05-21	2018-05-21
HP	Amplifier	HP8447E	1937A01046	2017-05-21	2017-11-19
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2014-12-17	2017-12-16
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2016-12-07	2017-12-07
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	104PEA	218124002	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	RG-214	1	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	RG-214	2	2017-05-22	2017-11-22
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2014-12-29	2017-12-28
Ducommun Technologies	Pre-amplifier	ALN-22093530-01	991373-01	2017-08-03	2018-08-03
Sinoscite	Band Reject Filter	BSF2402-2480MN-0898-001	N/A	2017-05-21	2018-05-21

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Agilent	P-Series Power Meter	N1912A	MY5000448	2016-12-05	2017-12-05
Agilent	Wideband Power Sensor	N1921A	MY54210016	2016-12-05	2017-12-05
WEINSCHEL	3 dB Attenuator	N/A	N/A	2017-05-21	2017-11-19
WEINSCHEL	3 dB Attenuator	N/A	N/A	2017-11-19	2018-05-21
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2016-12-05	2017-12-05
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2017-12-05	2018-12-05
Ducommun technologies	RF Cable	RG-214	3	2017-05-22	2017-11-22
Ducommun technologies	RF Cable	RG-214	3	2017-11-22	2018-05-22

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	**Electric Field Strength (V/m)**	**Magnetic Field Strength (A/m)**	**Power Density (mW/cm^2)**	**Averaging Time (Minutes)**
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*($180/f^2$)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz
* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm^2)
P = power input to the antenna (in appropriate units, e.g., mW).
G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Turn up Power		Evaluation Distance (cm)	Power Density (mW/cm^2)	MPE Limit (mW/cm^2)
	(dBi)	(numeric)	(dBm)	(mW)			
2402-2480	2	1.58	3.5	2.24	20	0.0007	1

Note: The conducted power is the tune-up power of the Max Conducted Output Power

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 2 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr}, if L_m is less than L_{lim}, it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-10-09.

EUT operation mode: Transmitting

Powered by adapter 1

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.971570	34.7	20.1	56.0	21.3	QP
4.852290	33.9	20.1	56.0	22.1	QP
4.951510	34.9	20.1	56.0	21.1	QP
5.613550	38.2	20.1	60.0	21.8	QP
11.974210	37.2	20.0	60.0	22.8	QP
14.585670	35.9	20.1	60.0	24.1	QP
0.971570	28.3	20.1	46.0	17.7	Ave.
4.852290	27.2	20.1	46.0	18.8	Ave.
4.951510	28.0	20.1	46.0	18.0	Ave.
5.613550	31.0	20.1	50.0	19.0	Ave.
11.974210	30.6	20.0	50.0	19.4	Ave.
14.585670	30.3	20.1	50.0	19.7	Ave.

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.158500	46.2	20.2	65.5	19.3	QP
0.845130	34.4	20.0	56.0	21.6	QP
0.967270	35.3	20.1	56.0	20.7	QP
5.691990	38.8	20.1	60.0	21.2	QP
6.105570	37.7	20.0	60.0	22.3	QP
12.195570	37.5	20.0	60.0	22.5	QP
0.158500	30.4	20.2	55.5	25.1	Ave.
0.845130	28.7	20.0	46.0	17.3	Ave.
0.967270	28.7	20.1	46.0	17.3	Ave.
5.691990	31.7	20.1	50.0	18.3	Ave.
6.105570	31.1	20.0	50.0	18.9	Ave.
12.195570	31.0	20.0	50.0	19.0	Ave.

Powered by adapter 2

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.253500	40.9	20.2	61.6	20.7	QP
0.257500	40.3	20.2	61.5	21.2	QP
0.908410	35.1	20.1	56.0	20.9	QP
0.935990	35.7	20.1	56.0	20.3	QP
1.089710	35.4	20.1	56.0	20.6	QP
1.109110	36.2	20.1	56.0	19.8	QP
0.253500	34.4	20.2	51.6	17.2	Ave.
0.257500	32.1	20.2	51.5	19.4	Ave.
0.908410	27.3	20.1	46.0	18.7	Ave.
0.935990	28.2	20.1	46.0	17.8	Ave.
1.089710	29.6	20.1	46.0	16.4	Ave.
1.109110	29.3	20.1	46.0	16.7	Ave.

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.301470	36.4	20.2	60.2	23.8	QP
0.809790	33.2	20.0	56.0	22.8	QP
0.849070	32.6	20.0	56.0	23.4	QP
0.931930	36.4	20.1	56.0	19.6	QP
1.050250	38.1	20.1	56.0	17.9	QP
1.188330	34.0	20.1	56.0	22.0	QP
0.301470	31.7	20.2	50.2	18.5	Ave.
0.809790	26.9	20.0	46.0	19.1	Ave.
0.849070	26.2	20.0	46.0	19.8	Ave.
0.931930	29.2	20.1	46.0	16.8	Ave.
1.050250	31.6	20.1	46.0	14.4	Ave.
1.188330	28.6	20.1	46.0	17.4	Ave.

Powered by POE

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.161500	45.4	20.2	65.4	20.0	QP
0.963510	44.2	20.1	56.0	11.8	QP
1.018490	42.6	20.1	56.0	13.4	QP
1.172330	40.6	20.1	56.0	15.4	QP
10.792090	48.8	20.0	60.0	11.2	QP
11.464150	47.8	20.0	60.0	12.2	QP
0.161500	28.1	20.2	55.4	27.3	Ave.
0.963510	36.3	20.1	46.0	9.7	Ave.
1.018490	35.2	20.1	46.0	10.8	Ave.
1.172330	33.7	20.1	46.0	12.3	Ave.
10.792090	44.8	20.0	50.0	5.2	Ave.
11.464150	43.4	20.0	50.0	6.6	Ave.

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.829550	38.6	20.0	56.0	17.4	QP
0.959510	49.0	20.1	56.0	7.0	QP
1.037330	46.7	20.1	56.0	9.3	QP
1.151010	48.9	20.1	56.0	7.1	QP
10.796090	52.4	20.0	60.0	7.6	QP
11.891590	52.0	20.0	60.0	8.0	QP
0.829550	31.4	20.0	46.0	14.6	Ave.
0.959510	39.8	20.1	46.0	6.2	Ave.
1.037330	40.1	20.1	46.0	5.9	Ave.
1.151010	41.8	20.1	46.0	4.2	Ave.
10.796090	45.1	20.0	50.0	4.9	Ave.
11.891590	45.6	20.0	50.0	4.4	Ave.

Note:
1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
2) Corrected Amplitude = Reading + Correction Factor
3) Margin = Limit – Corrected Amplitude

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard

FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Average

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr}, if L_m is less than L_{lim}, it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-10-25 and 2017-10-26.

EUT operation mode: Transmitting (Pre-scan with powered by adapters and POE, and worst case as below)

30 MHz~1 GHz (BDR mode, Low channel)



Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
240.182625	34.23	127.0	H	44.0	-4.6	46.00	11.77
331.727125	36.69	116.0	H	84.0	-2.7	46.00	9.31
380.860375	39.56	106.0	H	88.0	-0.9	46.00	6.44
675.020875	34.78	100.0	V	144.0	5.5	46.00	11.22
798.272125	31.35	390.0	H	342.0	9.0	46.00	14.65
899.913625	31.40	284.0	H	223.0	9.7	46.00	14.60

1 GHz-25 GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBµV/m)	FCC Part 15.247/205/209	
	Reading (dBµV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBµV/m)	Margin (dB)
Low Channel (2402 MHz)									
2402.00	65.28	PK	115	1.4	H	33.92	99.20	/	/
2402.00	54.58	Ave.	115	1.4	H	33.92	88.50	/	/
2402.00	63.65	PK	81	2.4	V	33.92	97.57	/	/
2402.00	52.75	Ave.	81	2.4	V	33.92	86.67	/	/
2341.26	27.67	PK	317	2.3	H	33.83	61.50	74	12.50
2341.26	13.86	Ave.	317	2.3	H	33.83	47.69	54	6.31
2331.32	28.65	PK	213	2.1	H	33.83	62.48	74	11.52
2331.32	13.85	Ave.	213	2.1	H	33.83	47.68	54	6.32
2491.50	26.66	PK	299	1.6	H	34.08	60.74	74	13.26
2491.50	13.24	Ave.	299	1.6	H	34.08	47.32	54	6.68
4804.00	43.22	PK	251	2.0	H	5.84	49.06	74	24.94
4804.00	28.99	Ave.	251	2.0	H	5.84	34.83	54	19.17

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Middle Channel (2441 MHz)									
2441.00	65.41	PK	109	2.3	H	33.92	99.33	/	/
2441.00	54.65	Ave.	109	2.3	H	33.92	88.57	/	/
2441.00	63.41	PK	309	1.3	V	33.92	97.33	/	/
2441.00	52.49	Ave.	309	1.3	V	33.92	86.41	/	/
2341.26	27.30	PK	145	1.1	H	33.83	61.13	74	12.87
2341.26	13.67	Ave.	145	1.1	H	33.83	47.50	54	6.50
2385.31	26.89	PK	97	1.2	H	33.92	60.81	74	13.19
2385.31	13.70	Ave.	97	1.2	H	33.92	47.62	54	6.38
2488.19	26.53	PK	144	1.2	H	34.08	60.61	74	13.39
2488.19	13.21	Ave.	144	1.2	H	34.08	47.29	54	6.71
4882.00	43.82	PK	119	1.5	H	6.21	50.03	74	23.97
4882.00	29.17	Ave.	119	1.5	H	6.21	35.38	54	18.62
High Channel (2480 MHz)									
2480.00	64.89	PK	82	2.5	H	34.08	98.97	/	/
2480.00	53.73	Ave.	82	2.5	H	34.08	87.81	/	/
2480.00	61.55	PK	282	1.1	V	34.08	95.63	/	/
2480.00	50.41	Ave.	282	1.1	V	34.08	84.49	/	/
2342.06	27.44	PK	270	2.4	H	33.83	61.27	74	12.73
2342.06	13.71	Ave.	270	2.4	H	33.83	47.54	54	6.46
2483.50	27.24	PK	351	1.2	H	34.08	61.32	74	12.68
2483.50	14.26	Ave.	351	1.2	H	34.08	48.34	54	5.66
2483.56	27.68	PK	31	1.7	H	34.08	61.76	74	12.24
2483.56	14.59	Ave.	31	1.7	H	34.08	48.67	54	5.33
4960.00	43.17	PK	67	1.2	H	7.82	50.99	74	23.01
4960.00	29.34	Ave.	67	1.2	H	7.82	37.16	54	16.84

Note:
Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude
The other spurious emission which is 20dB to the limit was not recorded.

Plots for Pre-scan

Horizontal





Vertical



Date: 25.OCT.2017 23:57:33



Date: 26.OCT.2017 0:21:44

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-10-10.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	≥Limit (MHz)	Result
BDR (GFSK)	Low	2402	1.000	0.700	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.700	Pass
	Adjacent	2442			
	High	2480	1.000	0.707	Pass
	Adjacent	2479			
EDR (π/4-DQPSK)	Low	2402	1.000	0.900	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.900	Pass
	Adjacent	2442			
	High	2480	1.000	0.900	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	1.000	0.880	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.880	Pass
	Adjacent	2442			
	High	2480	1.000	0.887	Pass
	Adjacent	2479			

Note: Limit = 20 dB bandwidth *2/3

BDR (GFSK): Low Channel



Date: 10.OCT.2017 15:44:25

BDR (GFSK): Middle Channel



Date: 10.OCT.2017 15:43:42

BDR (GFSK): High Channel



Date: 10.OCT.2017 15:41:28

EDR (π/4-DQPSK): Low Channel



Date: 10.OCT.2017 15:45:52

EDR (π/4-DQPSK): Middle Channel



Date: 10.OCT.2017 15:40:02

EDR (π/4-DQPSK): High Channel



Date: 10.OCT.2017 15:42:44

EDR (8DPSK): Low Channel



Date: 10.OCT.2017 15:38:26

EDR (8DPSK): Middle Channel



Date: 10.OCT.2017 15:37:42

EDR (8DPSK): High Channel



Date: 10.OCT.2017 15:36:14

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-10-10.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	1.05
	Middle	2441	1.05
	High	2480	1.06
EDR (π/4-DQPSK)	Low	2402	1.35
	Middle	2441	1.35
	High	2480	1.35
EDR (8DPSK)	Low	2402	1.32
	Middle	2441	1.32
	High	2480	1.33

BDR (GFSK): Low Channel



Date: 10.OCT.2017 15:24:05

BDR (GFSK): Middle Channel



Date: 10.OCT.2017 15:22:46

BDR (GFSK): High Channel



Date: 10.OCT.2017 15:21:41

EDR (π/4-DQPSK): Low Channel



Date: 10.OCT.2017 15:18:19

EDR (π/4-DQPSK): Middle Channel



Date: 10.OCT.2017 15:19:34

EDR (π/4-DQPSK): High Channel



Date: 10.OCT.2017 15:20:37

EDR (8DPSK): Low Channel



Date: 10.OCT.2017 15:17:04

EDR (8DPSK): Middle Channel



Date: 10.OCT.2017 15:16:09

EDR (8DPSK): High Channel



Date: 10.OCT.2017 15:14:20

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

2. Set the EUT in hopping mode from first channel to last.

3. By using the max-hold function record the quantity of the channel.

Test Data

Environmental Conditions

Temperature:	23~25 ℃
Relative Humidity:	50~54 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by Dylan Li on 2017-10-10 and 2017-12-26.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15

BDR (GFSK): Number of Hopping Channels



Date: 10.OCT.2017 15:49:27

EDR (π/4-DQPSK): Number of Hopping Channels



Date: 26.DEC.2017 18:41:55

EDR (8DPSK): Number of Hopping Channels



Date: 10.OCT.2017 15:56:03

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW ≥ 3×RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-10-10.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots

Mode		Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
BDR (GFSK)	DH 1	Low	0.431	0.138	0.4	Pass
		Middle	0.431	0.138	0.4	Pass
		High	0.431	0.138	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.72	0.275	0.4	Pass
		Middle	1.72	0.275	0.4	Pass
		High	1.72	0.275	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	2.90	0.309	0.4	Pass
		Middle	2.90	0.309	0.4	Pass
		High	2.90	0.309	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (π/4-DQPSK)	2DH 1	Low	0.441	0.141	0.4	Pass
		Middle	0.441	0.141	0.4	Pass
		High	0.441	0.141	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH 3	Low	1.72	0.275	0.4	Pass
		Middle	1.72	0.275	0.4	Pass
		High	1.72	0.275	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH 5	Low	2.97	0.317	0.4	Pass
		Middle	2.97	0.317	0.4	Pass
		High	2.97	0.317	0.4	Pass
		Note:2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH 1	Low	0.441	0.141	0.4	Pass
		Middle	0.441	0.141	0.4	Pass
		High	0.441	0.141	0.4	Pass
		Note: 3DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH 3	Low	1.72	0.275	0.4	Pass
		Middle	1.72	0.275	0.4	Pass
		High	1.72	0.275	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH 5	Low	2.97	0.317	0.4	Pass
		Middle	2.97	0.317	0.4	Pass
		High	2.97	0.317	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				

BDR (GFSK):
Pulse time, Low Channel, DH1



Date: 10.OCT.2017 15:58:27

Pulse time, Middle Channel, DH1



Date: 10.OCT.2017 15:59:01

Pulse time, High Channel, DH1



Date: 10.OCT.2017 15:59:32

Pulse time, Low Channel, DH3



Date: 10.OCT.2017 16:07:18

Pulse time, Middle Channel, DH3



Date: 10.OCT.2017 16:07:37

Pulse time, High Channel, DH3



Date: 10.OCT.2017 16:07:49

Pulse time, Low Channel, DH5



Date: 10.OCT.2017 16:12:19

Pulse time, Middle Channel, DH5



Date: 10.OCT.2017 16:12:33

Pulse time, High Channel, DH5



Date: 10.OCT.2017 16:11:59

EDR (π/4-DQPSK):
Pulse time, Low Channel, 2DH1



Date: 10.OCT.2017 16:00:57

Pulse time, Middle Channel, 2DH1



Date: 10.OCT.2017 16:01:15

Pulse time, High Channel, 2DH1



Date: 10.OCT.2017 16:01:31

Pulse time, Low Channel, 2DH3



Date: 10.OCT.2017 16:10:03

Pulse time, Middle Channel, 2DH3



Date: 10.OCT.2017 16:10:18

Pulse time, High Channel, 2DH3



Date: 10.OCT.2017 16:10:29

Pulse time, Low Channel, 2DH5



Date: 10.OCT.2017 16:14:57

Pulse time, Middle Channel, 2DH5



Date: 10.OCT.2017 16:14:46

Pulse time, High Channel, 2DH5



Date: 10.OCT.2017 16:14:20

EDR (8DPSK):
Pulse time, Low Channel, 3DH1



Date: 10.OCT.2017 16:02:42

Pulse time, Middle Channel, 3DH1



Date: 10.OCT.2017 16:02:27

Pulse time, High Channel, 3DH1



Date: 10.OCT.2017 16:02:14

Pulse time, Low Channel, 3DH3



Date: 10.OCT.2017 16:09:13

Pulse time, Middle Channel, 3DH3



Date: 10.OCT.2017 16:09:28

Pulse time, High Channel, 3DH3



Date: 10.OCT.2017 16:08:57

Pulse time, Low Channel, 3DH5



Date: 10.OCT.2017 16:13:21

Pulse time, Middle Channel, 3DH5



Date: 10.OCT.2017 16:13:38

Pulse time, High Channel, 3DH5



Date: 10.OCT.2017 16:13:50

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-10-10.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table.

Mode	Channel	Frequency (MHz)	Peak Output Power		Limit (mW)
			(dBm)	(mW)	
BDR (GFSK)	Low	2402	3.08	2.03	1000
	Middle	2441	2.81	1.91	1000
	High	2480	2.41	1.74	1000
EDR (π/4-DQPSK)	Low	2402	0.99	1.26	1000
	Middle	2441	0.59	1.15	1000
	High	2480	0.69	1.17	1000
EDR (8DPSK)	Low	2402	1.48	1.41	1000
	Middle	2441	1.09	1.29	1000
	High	2480	1.30	1.35	1000

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	23~25 ℃
Relative Humidity:	20~56 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by Dylan Li on 2017-10-10 and 2017-12-26.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following plots.

BDR (GFSK): Band Edge-Left Side



Date: 26.DEC.2017 18:48:54



Date: 10.OCT.2017 15:27:22

BDR (GFSK): Band Edge-Right Side



Date: 26.DEC.2017 18:52:05



Date: 10.OCT.2017 15:28:30

EDR (π/4-DQPSK): Band Edge-Left Side



Date: 26.DEC.2017 18:57:49



Date: 10.OCT.2017 15:30:42

EDR (π/4-DQPSK): Band Edge-Right Side



Date: 26.DEC.2017 18:55:08



Date: 10.OCT.2017 15:29:30

EDR (8DPSK): Band Edge-Left Side



Date: 26.DEC.2017 19:00:07



Date: 10.OCT.2017 15:31:42

EDR (8DPSK): Band Edge-Right Side



Date: 26.DEC.2017 19:04:54



Date: 10.OCT.2017 15:32:27

******* END OF REPORT *******