

TEST REPORT

Applicant : ARCTIC (HK) Ltd.

Address : Unit 3001-3007, The Octagon, 6 Sha Tsui Road, Tsuen Wan, N.T., Hong Kong, China

Manufacturer : ARCTIC (HK) Ltd.

Address : Unit 3001-3007, The Octagon, 6 Sha Tsui Road, Tsuen Wan, N.T., Hong Kong, China

Factory : ARCTIC (HK) Ltd.

Address : Unit 3001-3007, The Octagon, 6 Sha Tsui Road, Tsuen Wan, N.T., Hong Kong, China

Product Name : Senza

Model Number : AI 370

Trademark : 

FCC ID : Z3ASENZAAI370

Test Date : Oct. 08, 2025 - Sep. 03, 2026

Date of Report : Sep. 03, 2026

Test Result : This device described above has been tested by BKC, and the test results show that the equipment under test (EUT) is in compliance with the Standard requirements. And it is applicable only to the tested sample identified in the report.

Test Procedure Used:

Standards : FCC CFR47 Part 15 Section 15.407
ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

Prepared by(Test Engineer):
Sten Huang



Reviewer(Supervisor):
Casey Wang



Approved(Manager):
Jerry Liao



TABLE OF CONTENT

1. General Information	4
1.1. Description of Device (EUT)	4
1.2. Channel List	4
1.3. Summary of test result	5
1.4. Special Accessories and Auxiliary Equipment	6
1.5. Test mode	6
1.6. Block Diagram	7
1.7. Test Conditions	7
1.8. Measurement Uncertainty (95% confidence levels, k=2)	7
1.9. Test Facility	8
1.10. Test Equipment	9
2. Conducted emission at the mains terminals test	12
2.1. Limit	12
2.2. Test Setup	12
2.3. Test Procedure	12
2.4. Test Result	13
3. Radiated Spurious Emissions	15
3.1. Limit	15
3.2. Test Setup	16
3.3. Test Procedure	18
3.4. Test Result	19
4. Maximum Peak Output Power	28
4.1. Limit	28
4.2. Test Setup	28
4.3. Test Procedure	28
4.4. Test Result	29
5. -26 dB Bandwidth, -6dB Bandwidth and 99% Bandwidth Measurement	30
5.1. Limit	30
5.2. Test Setup	30
5.3. Test Procedure	30
5.4. Test Result	30
6. Power Spectral density	31
6.1. Limit	31
6.2. Test Setup	32
6.3. Test Procedure	32
6.4. Test Result	32
7. Out of Band Emissions and Spurious Emission	33
7.1. Limit	33
7.2. Test Setup	33
7.3. Test Procedure	33
7.4. Test Result	33
8. Frequency Stability Measurement	34
8.1. Limit	34
8.2. Test setup	34
8.3. Test Procedure	34
8.4. Test Result	34
9. Antenna Requirement	38

[illegible]

1. General Information

1.1. Description of Device (EUT)

EUT Name : Senza

Model No. : AI 370

Model Difference : /

Power supply : Input: 19.0V $\pm$ 6.3A

SWITCHING ADAPTER : Model: SOY-1900630-410-B
Information Input: 100-240V~ 50/60Hz 2.5A Max
Output 19.0V $\pm$ 6.3A 119.7W
Manufacturer: Shenzhen SOY Technology Co., Ltd.

Wi-Fi Specification : IEEE 802.11a/n/ac

Operation frequency : IEEE 802.11a/n/ac(20M): 5150MHz ~5250MHz/ 4 channel
IEEE 802.11n/ac(40M): 5150MHz ~5250MHz/ 2 channel
IEEE 802.11ac(80M): 5150MHz ~5250MHz/ 1 channel
IEEE 802.11ac(160M): 5150MHz ~5250MHz/ 1 channel

IEEE 802.11a/n/ac(20M): 5250MHz ~5350MHz/ 4 channel
IEEE802.11n/ac(40M): 5250MHz ~5350MHz/ 2 channel
IEEE802.11ac(80M): 5250MHz ~5350MHz/ 1 channel

IEEE 802.11a/n/ac(20M): 5470MHz ~5725MHz/ 12 channel
IEEE802.11n/ac(40M): 5470MHz ~5725MHz/ 5 channel
IEEE802.11ac(80M): 5470MHz ~5725MHz/ 3 channel
IEEE802.11ac(160M): 5470MHz ~5725MHz/ 1 channel

IEEE 802.11a/n/ac(20M): 5725MHz ~5875MHz/ 5 channel
IEEE 802.11n/ac(40M): 5725MHz ~5875MHz/ 2 channel
IEEE 802.11ac(80M): 5725MHz ~5875MHz/ 1 channel

Max. RF output power: : 13.59dBm

Modulation : Orthogonal Frequency Division Multiplexing(OFDM)

Antenna Type : Antenna 0: FPC antenna, Maximum Gain is 9.66dBi
Antenna 1: FPC antenna, Maximum Gain is 8.8dBi

Device type : Slave Device(without Radar Detection)

System : SISO

wireless router : The restart time for the router and the module is 120 seconds

1.2. Channel List

U-NII-1 (5.15-5.25GHz)			
channel	Frequency(MHz)	channel	Frequency(MHz)
36	5180	38	5190
40	5200	42	5210
44	5220	46	5230

48	5240	50	5250
----	------	----	------

U-NII-2A (5.25-5.35GHz)			
channel	Frequency(MHz)	channel	Frequency(MHz)
52	5260	54	5270
56	5280	58	5290
60	5300	62	5310
64	5320		

U-NII-2C (5.47-5.725GHz)			
channel	Frequency(MHz)	channel	Frequency(MHz)
100	5500	102	5510
104	5520	106	5530
108	5540	110	5550
112	5560	114	5570
116	5580	118	5590
120	5600	122	5610
124	5620	126	5630
128	5640	132	5660
134	5670	136	5680
138	5690	140	5700
144	5720		

U-NII-3 (5.725-5.875GHz)			
channel	Frequency(MHz)	channel	Frequency(MHz)
149	5745	151	5755
153	5765	155	5775
157	5785	159	5795
161	5805	165	5825

1.3.Summary of test result

RF PART		
Test Items	Test Requirement	Result
15.407(b), 15.209	Radiated Spurious Emission	PASS
15.207	Conducted Emission	PASS
15.407 (a) 15.407 (e)	99% , 6dB and 26dB Bandwidth	PASS
15.407 (a)	Maximum Conducted Output Power	PASS

15.407(b)	Band Edge	PASS
15.407 (a)	Power Spectral Density	PASS
15.407(g)	Frequency Stability	PASS
15.203	Antenna Requirement	PASS
Remark: N/A is an abbreviation for Not Applicable. Measurement Uncertainty is not taken into account for conformity statement		

1.4.Special Accessories and Auxiliary Equipment

Description	Manufacturer	Model No.	Serial Number
SWITCHING ADAPTER	SOY	SOY-1900630-410-B	N/A
Hub	ARCTIC	Senza AI 370	N/A

1.5.Test mode

The special RF test software was used to control EUT work in Continuous WIFI TX mode, and select test channel, wireless mode.

For 802.11a/n/ac(HT20):

channel	Frequency(MHz)	channel	Frequency(MHz)
36	5180	40	5200
48	5240		
channel	Frequency(MHz)	channel	Frequency(MHz)
52	5260	56	5280
64	5320		
channel	Frequency(MHz)	channel	Frequency(MHz)
100	5500	120	5600
144	5720		
channel	Frequency(MHz)	channel	Frequency(MHz)
149	5745	157	5785
165	5825		

For 802.11n/ac(HT40)/ ac(HT80):

channel	Frequency(MHz)	channel	Frequency(MHz)
38	5190	42	5210
46	5230		
channel	Frequency(MHz)	channel	Frequency(MHz)
54	5270	58	5290
62	5310		
channel	Frequency(MHz)	channel	Frequency(MHz)
102	5510	106	5530

118	5590	122	5610
134	5670	138	5690


channel	Frequency(MHz)	channel	Frequency(MHz)
151	5755	155	5775
159	5795		

For 802.11ac(HT160):


channel	Frequency(MHz)	channel	Frequency(MHz)
50	5250		
channel	Frequency(MHz)	channel	Frequency(MHz)
114	5570		

1.6.Block Diagram


Conducted Emission



Radiated Emission



RF Conducted Test



1.7.Test Conditions

Category	Normal Conditions	Extreme Conditions
Temperature range	15-35℃	N/A
Humidity range	20-75%	N/A
Pressure range	86-106kPa	N/A
Power supply	120VAC/60Hz by adapter	N/A

Note: N/A is an abbreviation for Not Applicable.

1.8.Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
------	----	--------

Uncertainty for radio frequency	$\pm 7 \times 10^{-8}$	
Conducted Emissions (150kHz~30MHz)	$\pm 2.54\text{dB}$	
Radiated Emission(9KHz~30MHz)	$\pm 1.6\text{ dB}$	
Radiated Emission(30MHz~1GHz)	Vertical: $\pm 4.14\text{dB}$ Horizontal: $\pm 4.25\text{dB}$	
Radiated Emission(1GHz~6GHz)	$\pm 3.9\text{dB}$	
Radiated Emission(6GHz~18GHz)	$\pm 4.3\text{dB}$	
Radiated Emission(18GHz~40GHz)	$\pm 3.38\text{dB}$	
Uncertainty for conducted RF Power	$\pm 0.20\text{dB}$	
Conducted spurious emissions	$\pm 0.24\text{dB}$	
Uncertainty for temperature	0.6°C	
Uncertainty for humidity	1%	
Bandwidth	$\pm 1.5 \times 10^{-6}$	
Time	$\pm 2\%$	
Duty Cycle	$\pm 2\%$	

Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%

1.9.Test Facility

Site Description		
Name of Firm	:	Shenzhen BKC Testing Co., Ltd.
Site Location	:	Room 103, 1/F, Huaya Building, Huaya Industrial Park, Longhua Community, Longhua District, Shenzhen, Guangdong, China.
ISED CAB identifier	:	CN0188
ISED Company Number	:	34333
FCC Designation Number	:	CN1416
FCC Test Firm Registration Number	:	701543

1.10.Test Equipment

Conducted Test Site

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	102762	Mar. 10. 2025	Mar. 09. 2026
					Mar. 11. 2026	Mar. 10. 2027
2	EMI Test Receiver	R&S	ESCI	101424	Mar. 10. 2025	Mar. 09. 2026
					Mar. 11. 2026	Mar. 10. 2027
3	Rf cables	HTEC	HCE 2M-CE	N/A	Mar. 10. 2025	Mar. 09. 2026
					Mar. 11. 2026	Mar. 10. 2027
4	Coupling/ Decoupling Network	Diamond	CX210	N/A	Mar. 10. 2025	Mar. 09. 2026
					Mar. 11. 2026	Mar. 10. 2027
5	10 db attenuator	N/A	DC-6G-10DB-N -JK	N/A	May. 27. 2025	May. 26. 2026
					May. 18. 2026	May. 17. 2027
6	CE Testing software	EZ	EZ-EMC	/	/	/

Radiated Test Site(Below 1G and Above 1G)

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Antenna	Schwarzbeck	VULB 9168	01321	Mar. 20. 2025	Mar. 19. 2028
2	EMI Test Receiver	R&S	ESRP	101478	Mar. 10. 2025	Mar. 09. 2026
					Mar. 11. 2026	Mar. 10. 2027
3	Preamplifier	HP	8447D	2727A05345	Mar. 10. 2025	Mar. 09. 2026
					Mar. 11. 2026	Mar. 10. 2027
4	Double Ridged Broadband	SCHWARZBEC K	BBHA 9120D	02621	Mar. 10. 2025	Mar. 19. 2028
5	Preamplifier	Schwarzbeck	BBV 9718D	00041	Mar. 10. 2025	Mar. 09. 2026
					Mar. 11. 2026	Mar. 10. 2027
6	Rf cables	HUBER+SUHNE R	8M-RE	N/A	Mar. 10. 2025	Mar. 09. 2026
					Mar. 11. 2026	Mar. 10. 2027
7	Rf cables	HUBER+SUHNE R	1.5M-RE	N/A	Mar. 10. 2025	Mar. 09. 2026
					Mar. 11. 2026	Mar. 10. 2027
8	Rf cables	HUBER+SUHNE R	1.5M-AP-RE	N/A	Mar. 10. 2025	Mar. 09. 2026
					Mar. 09. 2026	Mar. 10. 2027
9	Spectrum	Agilent	N9020A	MY50510311	Mar. 09. 2025	Mar. 10. 2026
					Mar. 11. 2026	Mar. 10. 2027
10	Spectrum analyzer	R&S	FSP40	200061	Feb. 13. 2025	Feb. 12. 2026

					Mar. 11. 2026	Mar. 10. 2027
11	Double Ridged Broadband Horn Antenna	COM-POWER	AH-1840	10100009	Mar. 09. 2025	Mar. 10. 2026
					Mar. 11. 2026	Mar. 10. 2027
12	RE Testing software	EZ	EZ-EMC	/		/

RF Test Site

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum	Agilent	N9020A	MY50510311	Mar. 09. 2025	Mar. 10. 2026
					Mar. 11. 2026	Mar. 10. 2027
2	Vector source	Agilent	N5182A	MY47420223	Mar. 09. 2025	Mar. 10. 2026
					Mar. 11. 2026	Mar. 10. 2027
3	All instrument	Rohde & Schwarz	CMW 500	101131	Mar. 09. 2025	Mar. 10. 2026
					Mar. 11. 2026	Mar. 10. 2027
4	control unit	MW	MW100-RFCB	MW200411BK-34	Mar. 09. 2025	Mar. 10. 2026
					Mar. 11. 2026	Mar. 10. 2027
5	RF Testing software	MW	MTS 8310	/	/	/
6	Spectrum analyzer	R&S	FSP40	200061	Feb. 13. 2025	Feb. 12. 2026
					Mar. 11. 2026	Mar. 10. 2027

Test software

Software name	RF Testing software
Software version	2.0.0.0
Software name	RE Testing software
Software version	EMEC-03A2 RE+
Software name	CE Testing software
Software version	EMEC-3A1+



2. Conducted emission at the mains terminals test


2.1.Limit

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

2.2.Test Setup




2.3.Test Procedure

1. The EUT was placed 0.1 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
2. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
3. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
4. LISN at least 80 cm from nearest part of EUT chassis.
5. For the actual test configuration, please refer to the related Item - EUT Test Photos.

2.4.Test Result


Conducted Emission At The Mains Terminals Test Data			
Temperature:	25.1℃	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Line
Test Voltage :	AC 120V/60Hz	Test Mode:	Working



No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1980	17.40	19.54	36.94	63.69	-26.75	QP
2	0.1980	8.48	19.54	28.02	53.69	-25.67	AVG
3	0.4941	20.76	19.54	40.30	56.10	-15.80	QP
4	0.4941	13.74	19.54	33.28	46.10	-12.82	AVG
5	0.5700	28.60	19.54	48.14	56.00	-7.86	QP
6	0.5700	21.99	19.54	41.53	46.00	-4.47	AVG
7	0.6500	17.67	19.54	37.21	56.00	-18.79	QP
8	0.6500	12.01	19.54	31.55	46.00	-14.45	AVG
9	0.8740	13.59	19.56	33.15	56.00	-22.85	QP
10	0.8740	8.39	19.56	27.95	46.00	-18.05	AVG
11	6.5220	21.65	19.63	41.28	60.00	-18.72	QP
12	6.5220	14.63	19.63	34.26	50.00	-15.74	AVG

Conducted Emission At The Mains Terminals Test Data

Temperature:	25.1℃	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Neutral
Test Voltage :	AC 120V/60Hz	Test Mode:	Working



No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1860	16.73	19.54	36.27	64.21	-27.94	QP
2	0.1860	12.04	19.54	31.58	54.21	-22.63	AVG
3	0.5060	21.40	19.54	40.94	56.00	-15.06	QP
4	0.5060	14.17	19.54	33.71	46.00	-12.29	AVG
5	0.5620	27.72	19.54	47.26	56.00	-8.74	QP
6	0.5620	22.29	19.54	41.83	46.00	-4.17	AVG
7	0.9900	14.12	19.55	33.67	56.00	-22.33	QP
8	0.9900	8.46	19.55	28.01	46.00	-17.99	AVG
9	1.3260	12.77	19.55	32.32	56.00	-23.68	QP
10	1.3260	8.45	19.55	28.00	46.00	-18.00	AVG
11	6.7260	21.32	19.63	40.95	60.00	-19.05	QP
12	6.7260	14.47	19.63	34.10	50.00	-15.90	AVG

3. Radiated Spurious Emissions

3.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.407

Test Method: ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

Test Result: PASS

Measurement Distance: 3m

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	20log(2400/F(kHz)) + 80
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	20log(24000/F(kHz)) + 40
1.705 ~ 30	30	30	100 * 30	20log(30) + 40
30 ~ 88	100	3	100	20log(100)
88 ~ 216	150	3	150	20log(150)
216 ~ 960	200	3	200	20log(200)
Above 960	500	3	500	20log(500)

Undesirable emission limits

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.


(4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge

Requirement	Limit(EIRP)	Limit (Field strength at 3m)
15.407(b)(1)	PK:-27(dBm/MHz)	PK:68.2(dB μ V/m)
15.407(b)(2)		
15.407(b)(3)		
15.407(b)(4)		


3.2.Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.




The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.





3.3. Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high - pass filter is used during radiated emissions above 1GHz measurement.

3.4. Test Result

Test Frequency: 9KHz~30MHz

The measurements were more than 20 dB below the limit and not reported.

Note: Only the worst Data (Ant 0: 802.11a_5180MHz) mode Record in the report.

Test Frequency : 30MHz ~ 1GHz

Radiation Emission Test Data			
Temperature:	25.1℃	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Horizontal
Test Voltage :	AC 120V/60Hz	Test Mode	Working



No.	Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark			
1	90.2205	38.99	-8.79	30.20	43.50	-13.30	QP			
2	97.1148	35.32	-5.96	29.36	43.50	-14.14	QP			
3	116.1321	36.17	-3.57	32.60	43.50	-10.90	QP			
4	169.5990	30.59	-5.23	25.36	43.50	-18.14	QP			
5	200.6881	32.83	-7.04	25.79	43.50	-17.71	QP			
6	301.4224	21.65	-1.29	20.36	46.00	-25.64	QP			

Radiation Emission Test Data			
Temperature:	25.1℃	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Vertical
Test Voltage :	AC 120V/60Hz	Test Mode	Working



No.	Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark			
1	36.6375	29.03	-2.05	26.98	40.00	-13.02	QP			
2	51.8430	28.12	-6.56	21.56	40.00	-18.44	QP			
3	93.4402	40.45	-7.47	32.98	43.50	-10.52	QP			
4	105.2718	32.56	-4.46	28.10	43.50	-15.40	QP			
5	118.6014	33.52	-3.32	30.20	43.50	-13.30	QP			
6	167.2368	31.02	-5.04	25.98	43.50	-17.52	QP			

All the modes 802.11a/n/ac has been tested and the worst result (Ant 0 : 802.11a) recorded as below:

Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

U-NII-1 802.11a

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampl ifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dBuV /m)	Detect or Type
Low Channel:5180MHz									
V	10360.00	54.40	33.13	2.73	31.60	55.60	74.00	-18.40	Pk
V	10360.00	43.09	33.13	2.73	31.60	44.29	54.00	-9.71	AV
V	15540.00	50.21	32.31	3.31	32.40	53.61	74.00	-20.39	Pk
V	15540.00	43.31	32.31	3.31	32.40	46.71	54.00	-7.29	AV
V	20720.00	52.24	34.84	4.42	33.90	55.72	74.00	-18.28	Pk
V	20720.00	43.22	34.84	4.42	33.90	46.70	54.00	-7.30	AV
V	25900.00	52.29	36.01	5.39	34.10	55.77	74.00	-18.23	Pk
V	25900.00	43.09	36.01	5.39	34.10	46.57	54.00	-7.43	AV
H	10360.00	51.63	33.13	2.73	31.60	52.83	74.00	-21.17	Pk
H	10360.00	43.35	33.13	2.73	31.60	44.55	54.00	-9.45	AV
H	15540.00	53.71	32.31	3.31	32.40	57.11	74.00	-16.89	Pk
H	15540.00	43.89	32.31	3.31	32.40	47.29	54.00	-6.71	AV
H	20720.00	54.06	34.84	4.42	33.90	57.54	74.00	-16.46	Pk
H	20720.00	43.42	34.84	4.42	33.90	46.90	54.00	-7.10	AV
H	25900.00	51.83	36.01	5.39	34.10	55.31	74.00	-18.69	Pk
H	25900.00	43.49	36.01	5.39	34.10	46.97	54.00	-7.03	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampl ifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dBuV /m)	Detect or Type
Middle Channel: 5200MHz									
V	10400.00	54.33	33.11	2.75	31.61	55.58	74.00	-18.42	Pk
V	10400.00	43.18	33.11	2.75	31.61	44.43	54.00	-9.57	AV
V	15600.00	50.27	32.27	3.32	32.41	53.73	74.00	-20.27	Pk
V	15600.00	43.86	32.27	3.32	32.41	47.32	54.00	-6.68	AV
V	20800.00	50.10	34.87	4.44	33.92	53.59	74.00	-20.41	Pk
V	20800.00	43.31	34.87	4.44	33.92	46.80	54.00	-7.20	AV
V	26000.00	54.02	36.11	5.41	34.13	57.45	74.00	-16.55	Pk
V	26000.00	43.47	36.11	5.41	34.13	46.90	54.00	-7.10	AV
H	10400.00	52.16	33.11	2.75	31.61	53.41	74.00	-20.59	Pk
H	10400.00	43.36	33.11	2.75	31.61	44.61	54.00	-9.39	AV
H	15600.00	51.89	32.27	3.32	32.41	55.35	74.00	-18.65	Pk
H	15600.00	43.61	32.27	3.32	32.41	47.07	54.00	-6.93	AV
H	20800.00	50.28	34.87	4.44	33.92	53.77	74.00	-20.23	Pk
H	20800.00	43.34	34.87	4.44	33.92	46.83	54.00	-7.17	AV
H	26000.00	54.14	36.11	5.41	34.13	57.57	74.00	-16.43	Pk
H	26000.00	43.43	36.11	5.41	34.13	46.86	54.00	-7.14	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amp lifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dBuV/m)	Detect or Type
High Channel:5240MHz									
V	10480.00	52.95	33.13	2.76	31.63	54.21	74.00	-19.79	Pk
V	10480.00	43.85	33.13	2.76	31.63	45.11	54.00	-8.89	AV
V	15720.00	54.66	32.29	3.33	32.42	58.12	74.00	-15.88	Pk
V	15720.00	43.60	32.29	3.33	32.42	47.06	54.00	-6.94	AV
V	20960.00	51.38	34.90	4.45	33.94	54.87	74.00	-19.13	Pk
V	20960.00	43.33	34.90	4.45	33.94	46.82	54.00	-7.18	AV
V	26200.00	51.80	36.13	5.44	34.15	55.26	74.00	-18.74	Pk
V	26200.00	43.13	36.13	5.44	34.15	46.59	54.00	-7.41	AV
H	10480.00	54.05	33.13	2.76	31.63	55.31	74.00	-18.69	Pk
H	10480.00	43.25	33.13	2.76	31.63	44.51	54.00	-9.49	AV
H	15720.00	53.60	32.29	3.33	32.42	57.06	74.00	-16.94	Pk
H	15720.00	43.18	32.29	3.33	32.42	46.64	54.00	-7.36	AV
H	20960.00	50.20	34.90	4.45	33.94	53.69	74.00	-20.31	Pk
H	20960.00	43.31	34.90	4.45	33.94	46.80	54.00	-7.20	AV
H	26200.00	51.92	36.13	5.44	34.15	55.38	74.00	-18.62	Pk
H	26200.00	43.03	36.13	5.44	34.15	46.49	54.00	-7.51	AV

U-NII-2A 802.11a

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dBuV/m)	Detect or Type
Low Channel:5260MHz									
V	10520.00	50.65	33.14	2.78	31.64	51.93	74.00	-22.07	Pk
V	10520.00	43.47	33.14	2.78	31.64	44.75	54.00	-9.25	AV
V	15780.00	50.08	32.31	3.34	32.43	53.54	74.00	-20.46	Pk
V	15780.00	43.19	32.31	3.34	32.43	46.65	54.00	-7.35	AV
V	21040.00	50.70	34.91	4.46	33.94	54.19	74.00	-19.81	Pk
V	21040.00	43.48	34.91	4.46	33.94	46.97	54.00	-7.03	AV
V	26300.00	51.58	36.15	5.45	34.16	55.04	74.00	-18.96	Pk
V	26300.00	43.13	36.15	5.45	34.16	46.59	54.00	-7.41	AV
H	10520.00	50.54	33.14	2.78	31.64	51.82	74.00	-22.18	Pk
H	10520.00	43.00	33.14	2.78	31.64	44.28	54.00	-9.72	AV
H	15780.00	53.66	32.31	3.34	32.43	57.12	74.00	-16.88	Pk
H	15780.00	43.54	32.31	3.34	32.43	47.00	54.00	-7.00	AV
H	21040.00	52.37	34.91	4.46	33.94	55.86	74.00	-18.14	Pk
H	21040.00	43.85	34.91	4.46	33.94	47.34	54.00	-6.66	AV
H	26300.00	50.18	36.15	5.45	34.16	53.64	74.00	-20.36	Pk
H	26300.00	43.55	36.15	5.45	34.16	47.01	54.00	-6.99	AV



Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dBuV /m)	
Middle Channel: 5280MHz									
V	10560.00	51.28	33.13	2.79	31.64	52.58	74.00	-21.42	Pk
V	10560.00	43.46	33.13	2.79	31.64	44.76	54.00	-9.24	AV
V	15840.00	51.00	32.32	3.35	32.44	54.47	74.00	-19.53	Pk
V	15840.00	43.35	32.32	3.35	32.44	46.82	54.00	-7.18	AV
V	21120.00	51.60	34.92	4.45	33.95	55.08	74.00	-18.92	Pk
V	21120.00	43.01	34.92	4.45	33.95	46.49	54.00	-7.51	AV
V	26400.00	53.28	36.14	5.46	34.15	56.75	74.00	-17.25	Pk
V	26400.00	43.33	36.14	5.46	34.15	46.80	54.00	-7.20	AV
H	10560.00	51.73	33.13	2.79	31.64	53.03	74.00	-20.97	Pk
H	10560.00	43.20	33.13	2.79	31.64	44.50	54.00	-9.50	AV
H	15840.00	51.16	32.32	3.35	32.44	54.63	74.00	-19.37	Pk
H	15840.00	43.83	32.32	3.35	32.44	47.30	54.00	-6.70	AV
H	21120.00	51.69	34.92	4.45	33.95	55.17	74.00	-18.83	Pk
H	21120.00	43.02	34.92	4.45	33.95	46.50	54.00	-7.50	AV
H	26400.00	52.12	36.14	5.46	34.15	55.59	74.00	-18.41	Pk
H	26400.00	43.32	36.14	5.46	34.15	46.79	54.00	-7.21	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dBuV /m)	
High Channel:5320MHz									
V	10640.00	52.49	33.15	2.81	31.67	53.82	74.00	-20.18	Pk
V	10640.00	43.67	33.15	2.81	31.67	45.00	54.00	-9.00	AV
V	15960.00	53.47	32.31	3.34	32.43	56.93	74.00	-17.07	Pk
V	15960.00	43.37	32.31	3.34	32.43	46.83	54.00	-7.17	AV
V	21280.00	54.66	34.92	4.47	33.97	58.18	74.00	-15.82	Pk
V	21280.00	43.69	34.92	4.47	33.97	47.21	54.00	-6.79	AV
V	26600.00	52.00	36.15	5.47	34.17	55.49	74.00	-18.51	Pk
V	26600.00	43.48	36.15	5.47	34.17	46.97	54.00	-7.03	AV
H	10640.00	52.16	33.15	2.81	31.67	53.49	74.00	-20.51	Pk
H	10640.00	43.74	33.15	2.81	31.67	45.07	54.00	-8.93	AV
H	15960.00	54.44	32.31	3.34	32.43	57.90	74.00	-16.10	Pk
H	15960.00	43.45	32.31	3.34	32.43	46.91	54.00	-7.09	AV
H	21280.00	54.46	34.92	4.47	33.97	57.98	74.00	-16.02	Pk
H	21280.00	43.55	34.92	4.47	33.97	47.07	54.00	-6.93	AV
H	26600.00	51.91	36.15	5.47	34.17	55.40	74.00	-18.60	Pk
H	26600.00	43.44	36.15	5.47	34.17	46.93	54.00	-7.07	AV

U-NII-2C 802.11a

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dBuV /m)	
Low Channel:5500MHz									
V	11000.00	50.74	33.17	2.86	31.63	52.06	74.00	-21.94	Pk
V	11000.00	43.73	33.17	2.86	31.63	45.05	54.00	-8.95	AV
V	16500.00	52.41	32.35	3.38	32.43	55.87	74.00	-18.13	Pk
V	16500.00	43.53	32.35	3.38	32.43	46.99	54.00	-7.01	AV
V	22000.00	54.83	34.94	4.49	33.93	58.31	74.00	-15.69	Pk
V	22000.00	43.92	34.94	4.49	33.93	47.40	54.00	-6.60	AV
V	27500.00	51.50	36.18	5.47	34.20	54.99	74.00	-19.01	Pk
V	27500.00	43.63	36.18	5.47	34.20	47.12	54.00	-6.88	AV
H	11000.00	52.38	33.17	2.86	31.63	53.70	74.00	-20.30	Pk
H	11000.00	43.97	33.17	2.86	31.63	45.29	54.00	-8.71	AV
H	16500.00	52.80	32.35	3.38	32.43	56.26	74.00	-17.74	Pk
H	16500.00	43.43	32.35	3.38	32.43	46.89	54.00	-7.11	AV
H	22000.00	53.39	34.94	4.49	33.93	56.87	74.00	-17.13	Pk
H	22000.00	43.32	34.94	4.49	33.93	46.80	54.00	-7.20	AV
H	27500.00	50.19	36.18	5.47	34.20	53.68	74.00	-20.32	Pk
H	27500.00	43.63	36.18	5.47	34.20	47.12	54.00	-6.88	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dBuV /m)	
Middle Channel: 5600MHz									
V	11200.00	54.02	33.21	2.93	31.63	55.37	74.00	-18.63	Pk
V	11200.00	43.38	33.21	2.93	31.63	44.73	54.00	-9.27	AV
V	16800.00	50.04	32.41	3.40	32.43	53.46	74.00	-20.54	Pk
V	16800.00	43.98	32.41	3.40	32.43	47.40	54.00	-6.60	AV
V	22400.00	50.49	34.98	4.51	33.97	53.99	74.00	-20.01	Pk
V	22400.00	43.07	34.98	4.51	33.97	46.57	54.00	-7.43	AV
V	28000.00	53.18	36.21	5.51	34.16	56.64	74.00	-17.36	Pk
V	28000.00	43.58	36.21	5.51	34.16	47.04	54.00	-6.96	AV
H	11200.00	50.25	33.21	2.93	31.63	51.60	74.00	-22.40	Pk
H	11200.00	43.74	33.21	2.93	31.63	45.09	54.00	-8.91	AV
H	16800.00	51.95	32.41	3.40	32.43	55.37	74.00	-18.63	Pk
H	16800.00	43.14	32.41	3.40	32.43	46.56	54.00	-7.44	AV
H	22400.00	51.49	34.98	4.51	33.97	54.99	74.00	-19.01	Pk
H	22400.00	43.59	34.98	4.51	33.97	47.09	54.00	-6.91	AV
H	28000.00	51.33	36.21	5.51	34.16	54.79	74.00	-19.21	Pk
H	28000.00	43.84	36.21	5.51	34.16	47.30	54.00	-6.70	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dBuV /m)	
High Channel:5700MHz									
V	11400.00	50.63	33.15	2.95	31.73	52.16	74.00	-21.84	Pk
V	11400.00	43.40	33.15	2.95	31.73	44.93	54.00	-9.07	AV
V	17100.00	52.25	32.29	3.43	32.46	55.85	74.00	-18.15	Pk
V	17100.00	43.05	32.29	3.43	32.46	46.65	54.00	-7.35	AV
V	22800.00	54.44	34.91	4.52	33.98	58.03	74.00	-15.97	Pk
V	22800.00	43.76	34.91	4.52	33.98	47.35	54.00	-6.65	AV
V	28500.00	50.62	36.13	5.53	34.21	54.23	74.00	-19.77	Pk
V	28500.00	43.59	36.13	5.53	34.21	47.20	54.00	-6.80	AV
H	11400.00	54.51	33.15	2.95	31.73	56.04	74.00	-17.96	Pk
H	11400.00	43.40	33.15	2.95	31.73	44.93	54.00	-9.07	AV
H	17100.00	52.55	32.29	3.43	32.46	56.15	74.00	-17.85	Pk
H	17100.00	43.16	32.29	3.43	32.46	46.76	54.00	-7.24	AV
H	22800.00	51.77	34.91	4.52	33.98	55.36	74.00	-18.64	Pk
H	22800.00	43.88	34.91	4.52	33.98	47.47	54.00	-6.53	AV
H	28500.00	52.38	36.13	5.53	34.21	55.99	74.00	-18.01	Pk
H	28500.00	43.08	36.13	5.53	34.21	46.69	54.00	-7.31	AV

U-NII-3 802.11a

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
Low Channel:5745MHz									
V	11490.00	51.66	33.13	2.93	32.61	54.07	74.00	-19.93	Pk
V	11490.00	43.64	33.13	2.93	32.61	46.05	54.00	-7.95	AV
V	17235.00	51.22	32.31	3.51	33.43	55.85	74.00	-18.15	Pk
V	17235.00	43.53	32.31	3.51	33.43	48.16	54.00	-5.84	AV
V	22980.00	51.49	34.84	4.62	34.90	56.17	74.00	-17.83	Pk
V	22980.00	43.58	34.84	4.62	34.90	48.26	54.00	-5.74	AV
V	28725.00	54.49	36.01	5.59	35.13	59.20	74.00	-14.80	Pk
V	28725.00	43.81	36.01	5.59	35.13	48.52	54.00	-5.48	AV
H	11490.00	51.43	33.13	2.93	32.61	53.84	74.00	-20.16	Pk
H	11490.00	43.52	33.13	2.93	32.61	45.93	54.00	-8.07	AV
H	17235.00	54.83	32.31	3.51	33.43	59.46	74.00	-14.54	Pk
H	17235.00	43.12	32.31	3.51	33.43	47.75	54.00	-6.25	AV
H	22980.00	52.45	34.84	4.62	34.90	57.13	74.00	-16.87	Pk
H	22980.00	43.93	34.84	4.62	34.90	48.61	54.00	-5.39	AV
H	28725.00	50.51	36.01	5.59	35.13	55.22	74.00	-18.78	Pk
H	28725.00	43.46	36.01	5.59	35.13	48.17	54.00	-5.83	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dBuV /m)	
Middle Channel: 5785MHz									
V	11570.00	54.50	33.11	2.95	32.62	56.96	74.00	-17.04	Pk
V	11570.00	43.27	33.11	2.95	32.62	45.73	54.00	-8.27	AV
V	17355.00	54.94	32.27	3.52	33.45	59.64	74.00	-14.36	Pk
V	17355.00	43.47	32.27	3.52	33.45	48.17	54.00	-5.83	AV
V	23140.00	50.15	34.87	4.64	34.93	54.85	74.00	-19.15	Pk
V	23140.00	43.56	34.87	4.64	34.93	48.26	54.00	-5.74	AV
V	28925.00	53.69	36.11	5.61	35.17	58.36	74.00	-15.64	Pk
V	28925.00	43.70	36.11	5.61	35.17	48.37	54.00	-5.63	AV
H	11570.00	53.19	33.11	2.95	32.62	55.65	74.00	-18.35	Pk
H	11570.00	43.83	33.11	2.95	32.62	46.29	54.00	-7.71	AV
H	17355.00	53.36	32.27	3.52	33.45	58.06	74.00	-15.94	Pk
H	17355.00	43.51	32.27	3.52	33.45	48.21	54.00	-5.79	AV
H	23140.00	54.68	34.87	4.64	34.93	59.38	74.00	-14.62	Pk
H	23140.00	43.21	34.87	4.64	34.93	47.91	54.00	-6.09	AV
H	28925.00	50.52	36.11	5.61	35.17	55.19	74.00	-18.81	Pk
H	28925.00	43.73	36.11	5.61	35.17	48.40	54.00	-5.60	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dBuV /m)	
High Channel:5825MHz									
V	11650.00	51.65	33.13	2.96	32.63	54.11	74.00	-19.89	Pk
V	11650.00	43.09	33.13	2.96	32.63	45.55	54.00	-8.45	AV
V	17475.00	51.61	32.29	3.53	33.47	56.32	74.00	-17.68	Pk
V	17475.00	43.10	32.29	3.53	33.47	47.81	54.00	-6.19	AV
V	23300.00	52.60	34.90	4.65	34.95	57.30	74.00	-16.70	Pk
V	23300.00	43.65	34.90	4.65	34.95	48.35	54.00	-5.65	AV
V	29125.00	53.32	36.13	5.64	35.19	58.02	74.00	-15.98	Pk
V	29125.00	43.24	36.13	5.64	35.19	47.94	54.00	-6.06	AV
H	11650.00	53.41	33.13	2.96	32.63	55.87	74.00	-18.13	Pk
H	11650.00	43.22	33.13	2.96	32.63	45.68	54.00	-8.32	AV
H	17475.00	51.66	32.29	3.53	33.47	56.37	74.00	-17.63	Pk
H	17475.00	43.85	32.29	3.53	33.47	48.56	54.00	-5.44	AV
H	23300.00	53.50	34.90	4.65	34.95	58.20	74.00	-15.80	Pk
H	23300.00	43.71	34.90	4.65	34.95	48.41	54.00	-5.59	AV
H	29125.00	54.73	36.13	5.64	35.19	59.43	74.00	-14.57	Pk
H	29125.00	43.95	36.13	5.64	35.19	48.65	54.00	-5.35	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss - Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Restrict Band EMISSION MEASUREMENT

All the modes have tested and recorded the worst mode (Ant 0, 802.11a) in the report.

U-NII-1

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Detector Type	Result
802.11a	Low Channel: 5180MHz									
	H	5150.00	53.29	34.57	5.73	24.51	48.96	74.00	PK	PASS
	H	5150.00	44.10	34.57	5.73	24.51	39.77	54.00	AV	PASS
	V	5150.00	54.18	34.57	5.73	24.51	49.85	74.00	PK	PASS
	V	5150.00	44.96	34.57	5.73	24.51	40.63	54.00	AV	PASS
	High Channel: 5240MHz									
	H	5350.00	54.48	34.22	5.85	24.98	51.09	74.00	PK	PASS
	H	5350.00	44.95	34.22	5.85	24.98	41.56	54.00	AV	PASS
	V	5350.00	53.81	34.22	5.85	24.98	50.42	74.00	PK	PASS
	V	5350.00	44.20	34.22	5.85	24.98	40.81	54.00	AV	PASS

U-NII-2A

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Detector Type	Result
802.11a	Low Channel: 5260MHz									
	H	5150.00	53.21	34.57	5.73	24.51	48.88	74.00	PK	PASS
	H	5150.00	44.64	34.57	5.73	24.51	40.31	54.00	AV	PASS
	V	5150.00	54.73	34.57	5.73	24.51	50.40	74.00	PK	PASS
	V	5150.00	44.56	34.57	5.73	24.51	40.23	54.00	AV	PASS
	High Channel: 5320MHz									
	H	5350.00	54.58	34.22	5.85	24.98	51.19	74.00	PK	PASS
	H	5350.00	44.41	34.22	5.85	24.98	41.02	54.00	AV	PASS
	V	5350.00	54.55	34.22	5.85	24.98	51.16	74.00	PK	PASS
	V	5350.00	44.81	34.22	5.85	24.98	41.42	54.00	AV	PASS

U-NII-2C

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Detector Type	Result
802.11a	Low Channel: 5500MHz									
	H	5460.00	53.07	34.55	5.71	24.52	48.75	74.00	PK	PASS
	H	5460.00	44.59	34.55	5.71	24.52	40.27	54.00	AV	PASS
	V	5460.00	54.82	34.55	5.71	24.52	50.50	74.00	PK	PASS
	V	5460.00	44.74	34.55	5.71	24.52	40.42	54.00	AV	PASS
	High Channel: 5700MHz									
	H	5460.00	53.18	34.55	5.71	24.52	48.86	74.00	PK	PASS
	H	5460.00	44.12	34.55	5.71	24.52	39.80	54.00	AV	PASS
	V	5460.00	53.32	34.55	5.71	24.52	49.00	74.00	PK	PASS
	V	5460.00	44.55	34.55	5.71	24.52	40.23	54.00	AV	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

4. Maximum Peak Output Power

4.1.Limit

According to FCC §15.407

For an outdoor access point operating in the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

For the band 5.725–5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

4.2.Test Setup



4.3.Test Procedure

The EUT was directly connected to the Power meter

1. Device Configuration

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level (see section II.B.).

The intent is to test at 100 percent duty cycle; however a small reduction in duty cycle (to no lower than 98 percent) is permitted if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.

b) If continuous transmission (or at least 98 percent duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level with the transmit duration as long as possible and the duty cycle as high as possible.

2. Measurement using a Spectrum Analyzer or EMI Receiver (SA)

Measurement of maximum conducted output power using a spectrum analyzer requires integrating the spectrum across a frequency span that encompasses, at a minimum, either the EBW or the 99-percent occupied bandwidth of the signal.¹ However, the EBW must be used to determine bandwidth dependent limits on maximum conducted output power in accordance with § 15.407(a).

a) The test method shall be selected as follows: (i) Method SA-1 or SA-1 Alternative (averaging with the EUT transmitting at full power throughout each sweep) shall be applied if either of the following conditions can be satisfied:

- The EUT transmits continuously (or with a duty cycle ≥ 98 percent).
- Sweep triggering or gating can be implemented in a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep (with the analyzer configured as in Method SA-1, below) is equal to or shorter than the duration T of each transmission from the EUT and if those transmissions exhibit full power throughout their durations.

(ii) Method SA-2 or SA-2 Alternative (averaging across on and off times of the EUT transmissions, followed by duty cycle correction) shall be applied if the conditions of (i) cannot be achieved and the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than ± 2 percent.

(iii) Method SA-3 (RMS detection with max hold) or SA-3 Alternative (reduced VBW with max hold) shall be applied if the conditions of (i) and (ii) cannot be achieved.

b) Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep): (i) Set span

to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW $\geq$ 3 MHz.

(iv) Number of points in sweep $\geq$ 2 Span / RBW. (This ensures that bin-to-bin spacing is $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq$ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum

4.4. Test Result

Please see the attachment for WIFI 5G data.




5. -26 dB Bandwidth, -6dB Bandwidth and 99% Bandwidth Measurement

5.1. Limit

Test Standard	FCC Part15 C Section 15.407
	The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band, the minimum bandwidth 6 dB bandwidth of U-NII devices shall be at least 500KHz. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

5.2. Test Setup



5.3. Test Procedure

- Set RBW = shall be in the range of 1% to 5% of the emission bandwidth..
 - Set the VBW > RBW.
 - Detector = Peak.
 - Trace mode = max hold.
 - Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.
- The following procedure shall be used for measuring (99 %) power bandwidth:
- Set center frequency to the nominal EUT channel center frequency.
 - Set span = 1.5 times to 5 times the OBW.
 - Set RBW = 1 % to 5 % of the OBW
 - Set VBW $\geq 3 \cdot$ RBW
 - Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
 - Use the 99 % power bandwidth function of the instrument (if available).
 - If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

5.4. Test Result

Please see the attachment for WIFI 5G data.

6. Power Spectral density

6.1.Limit

According to FCC § 15.407(3)

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum

power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

6.2. Test Setup



6.3. Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above,
2. The testing follows FCC KDB 789033 D02.
3. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to Spectrum.
4. For U-NII1, U-NII-2A, U-NII-2C Band:
Set RBW=1MHz, VBW=3MHz, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
For U-NII-3 Band:
Set RBW=510 kHz, VBW=3*RBW, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
5. Use the cursor on spectrum to peak search the highest level of trace
6. Record the max. reading and add 10 log(1/duty cycle).

6.4. Test Result

Please see the attachment for WIFI 5G data for test data.

7. Out of Band Emissions and Spurious Emission

7.1.Limit


According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

7.2.Test Setup



7.3.Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

7.4.Test Result

Please see the attachment for WIFI 5G data for test data.

8. Frequency Stability Measurement

8.1.Limit

FCC

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band(IEEE802.11n specification).

8.2.Test setup



8.3.Test Procedure

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. fc is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 106$ ppm and the limit is less than ± 20 ppm (IEEE 802.11nspecification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
Extreme temperature is -20°C~50°C.

8.4.Test Result

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	19VDC
Test Mode :	TX		

U-NII-1

Reference Frequency(Middle Channel): 5200MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency Error (Hz)	Error (ppm)
20	19	-40000	-7.69
-20	19	-20000	-3.85
-10	19	0	0
0	19	0	0
10	19	-40000	-7.69
30	19	0	0

40	19	-40000	-7.69
50	19	-60000	-11.54

U-NII-2A

Reference Frequency(Middle Channel): 5280MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency Error (Hz)	Error (ppm)
20	19	-20000	-3.79
-20	19	-40000	-7.58
-10	19	-40000	-7.58
0	19	0	0
10	19	-40000	-7.58
30	19	-40000	-7.58
40	19	-40000	-7.58
50	19	-40000	-7.58

U-NII-2C

Reference Frequency(Middle Channel): 5600MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency Error (Hz)	Error (ppm)
20	19	-40000	-7.14
-20	19	-40000	-7.14
-10	19	-40000	-7.14
0	19	-40000	-7.14
10	19	-40000	-7.14
30	19	0	0
40	19	20000	3.57
50	19	0	0

U-NII-3

Reference Frequency(Middle Channel): 5785 MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency Error (Hz)	Error (ppm)
20	19	-40000	-6.91
-20	19	-20000	-3.46
-10	19	-20000	-3.46

0	19	-40000	-6.91
10	19	-40000	-6.91
30	19	-60000	-10.37
40	19	-20000	-3.46
50	19	-20000	-3.46

So, Frequency Stability Versus Input Voltage is:

U-NII-1

Reference Frequency(Middle Channel): 5180 MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency Error (Hz)	Error (ppm)
20	16.15	-20000	-3.86
	19	-20000	-3.86
	21.85	-20000	-3.86

U-NII-2A

Reference Frequency(Middle Channel): 5280 MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency Error (Hz)	Error (ppm)
20	16.15	-20000	-3.79
	19	-20000	-3.79
	21.85	20000	3.79

U-NII-2C

Reference Frequency(Middle Channel): 5600 MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency Error (Hz)	Error (ppm)
20	16.15	-40000	-7.14
	19	-40000	-7.14
	21.85	-40000	-7.14

U-NII-3

Reference Frequency(Middle Channel): 5785 MHz			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency Error (Hz)	Error (ppm)
20	16.15	-20000	-3.46
	19	-40000	-6.91
	21.85	-20000	-3.46

All the modes have tested and recorded the worst mode(802.11a Middle Channel) in the report



9. Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an ceramic antenna fulfill the requirement of this section.

