



Project No: TM-2603000406P
Report No.: TMWK2603001360KR FCC ID: Z3K-CTX



Page 1 / 29
Rev. 01

FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

CUP HOLDER LIGHT-TRANSMITTER

Model: R115500700T

Trade Name: JET OPTOELECTRONICS CO., LTD.

Issued to

JET OPTOELECTRONICS CO.,LTD.
7F-2, No. 300, Yangguang St., Neihu Dist., Taipei City 11491,Taiwan

Issued by

Compliance Certification Services Inc.
Wugu Laboratory
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City, Taiwan
Issued Date: June 9, 2026

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Project No: TM-2603000406P
Report No.: TMWK2603001360KR

Page 2 / 29
Rev. 01

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	May 13, 2026	Initial Issue	ALL	Peggy Tsai
01	June 9, 2026	See the following Note Rev.(01)	P. 17	Peggy Tsai

Rev. (01)

1. Modify Test Data in section 7.1.

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION	4
2. EUT DESCRIPTION	5
3. TEST SUMMARY	6
4. TEST METHODOLOGY	7
4.1 EUT CONFIGURATION	7
4.2 EUT EXERCISE	7
4.3 GENERAL TEST PROCEDURES	7
4.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	8
4.5 DESCRIPTION OF TEST MODES	9
5. INSTRUMENT CALIBRATION	10
5.1 MEASURING INSTRUMENT CALIBRATION	10
5.2 MEASUREMENT EQUIPMENT USED	11
5.3 MEASUREMENT UNCERTAINTY	12
5.4 FACILITIES AND TEST LOCATION	12
6. SETUP OF EQUIPMENT UNDER TEST	13
6.1 SUPPORT AND EUT ACCESSORIES EQUIPMENT	13
6.2 TEST SETUP DIAGRAM	14
6.3 TEST PROGRAM	14
7. TEST REQUIREMENTS	15
7.1 20DB BANDWIDTH	15
7.2 TRANSMITTER RADIATED EMISSION	18
7.3 AC POWER-LINE CONDUCTED EMISSION	28
7.4 COIL RULERS AND SPECIFICATIONS	29
APPENDIX A PHOTOGRAPHS OF TEST SETUP	A-1
APPENDIX 1 - PHOTOGRAPHS OF EUT	

1. TEST RESULT CERTIFICATION

Applicant: JET OPTOELECTRONICS CO.,LTD.
7F-2, No. 300, Yangguang St., Neihu Dist., Taipei City
11491, Taiwan

Manufacturer: JET OPTOELECTRONICS CO.,LTD.
7F-2, No. 300, Yangguang St., Neihu Dist., Taipei City
11491, Taiwan

Equipment Under Test: CUP HOLDER LIGHT-TRANSMITTER

Trade Name: JET OPTOELECTRONICS CO., LTD.

Model: R115500700T

Date of Test: April 9 ~ June 9, 2026

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	Compliance
Statements of Conformity	
Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.	


We hereby certify that:

All test results conform to above mentioned standards.

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2020 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part15.203, Part15.207, Part15.209. Part15.215.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:



Sehni Hu
Supervisor



Project No: TM-2603000406P
Report No.: TMWK2603001360KR

Page 5 / 29
Rev. 01

2. EUT DESCRIPTION

Product	CUP HOLDER LIGHT-TRANSMITTER
Trade Name	JET OPTOELECTRONICS CO., LTD.
Model Number	R115500700T
Model Discrepancy	N/A
Received Date	March 25, 2026
Power Supply	Power from Power Supply (DC 12V)
Operating frequency range	81 ~ 89 kHz
Operating frequency	81 / 85 / 89 kHz
Antenna Specification	Antenna Type: Coil Antenna
Modulation information	FSK
Hardware Version	P01 20250721
Software Version	v2.6

Remark:

1. For more details, refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.



Project No: TM-2603000406P
Report No.: TMWK2603001360KR

Page 6 / 29
Rev. 01

3. TEST SUMMARY

Standard Sec.	Chapter	Test Item	Result
15.215	7.1	20dB Bandwidth	Pass
15.209 & 15.205	7.2	Transmitter Radiated Emission	Pass
15.207	7.3	AC Power-line Conducted Emission	Not applicable
15.203	7.4	Coil Rulers and Specifications	Pass

Remark: Permanent coil antenna and an unique coupler to intentional radiator, meet the 15.203 requirement

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Mains Power Port (150kHz-30MHz)	47 CFR Part 15, Subpart C	ANSI C63.10-2020 Section 6.2	47 CFR Part 15, Subpart C 15.207	Not applicable
Radiated Emissions (30MHz-1GHz)		ANSI C63.10-2020 Section 6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Emissions (9kHz-30MHz)		ANSI C63.10-2020 Section 6.4	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
20dB Bandwidth		ANSI C63.10-2020 Section 6.9	47 CFR Part 15, Subpart C 15.215	Pass

4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2020, ANSI C63.4 2014 and FCC CFR 47 Part 15.203, 15.207, 15.209, 15.215.

4.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT EXERCISE

Place a load in the wireless charging area to enable it to fix the TX frequency for measurement purposes.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.207, 15.209, 15.215 under the FCC Rules Part 15 Subpart C and ANSI C63.10-2020.

4.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in ANSI C63.10-2020, Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz was using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. The EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in ANSI C63.10-2020.

4.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in other rules, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided by other rules, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



Project No: TM-2603000406P
Report No.: TMWK2603001360KR

Page 9 / 29
Rev. 01

4.5 DESCRIPTION OF TEST MODES

The EUT (model: R115500700T) had been tested under operating condition.

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Power Supply
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(X-Plane) were recorded in this report.

5. INSTRUMENT CALIBRATION

5.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

5.2 MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

Conducted_FCC/IC/NCC (All)					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Cable	Woken	WC12	SS01	2025-06-26	2026-06-25
Active Loop Antenna	COM-POWER	AL-130	121051	2026-02-04	2027-02-03
EXA Signal Analyzer	Keysight	N9010B	MY55460167	2025-06-13	2026-06-12
DC Blocks	Marvelous Microwave	MVE6411	MVE-001	2025-08-06	2026-08-05
DC Power Source	GWINSTEK	SPS-3610	GPE880163	2025-11-06	2026-11-05
Software	N/A				

966A_Radiated					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Signal Analyzer	Agilent	N9010A	MY52220817	2026-03-13	2027-03-12
Active Loop Antenna	COM-POWER	AL-130	121051	2026-02-04	2027-02-03
Thermo-Hygro Meter	HTC	HTC-1	HTC-D06	2025-05-26	2026-05-25
Bi-Log Antenna	Sunol Sciences	JB3	A030105&532	2025-06-26	2026-06-25
Preamplifier	EMEC	EM330	060609	2026-02-13	2027-02-12
Cable	Huber+Suhner	104PEA	20995+21000+182330	2025-08-06	2026-08-05
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Software	e3 V9-210616c				

Remark:

- Each piece of equipment is scheduled for calibration once a year.
- N.C.R. = No Calibration Required.

5.3 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	$\pm 2.37\text{dB}$
Channel Bandwidth	$\pm 2.85\text{dB}$
Radiated Emission_9kHz-30MHz	$\pm 2.750\text{ dB}$
Radiated Emission_30MHz-200MHz	$\pm 3.874\text{ dB}$
Radiated Emission_200MHz-1GHz	$\pm 4.065\text{ dB}$

Remark: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

5.4 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan.

CAB identifier: TW1309

Test site	Test Engineer	Remark
AC Conduction Room	-	Not applicable, because EUT not connect to AC Main Source direct.
Radiation	Tony Chao	-
Conducted	David Li	-

Remark: The lab has been recognized as the FCC accredited lab. under the KDB 974614 D01 and is listed in the FCC public Access Link (PAL) database, FCC Registration No. :444940, the FCC Designation No.:TW1309, MRA: APEC TEL.

6. SETUP OF EQUIPMENT UNDER TEST


6.1 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC
	N/A					

Support Equipment (Conducted)						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC
1	DC Cable	N/A	N/A	N/A	N/A	N/A
A	Rear Footwell Light assembly	N/A	N/A	N/A	N/A	N/A
B	Front Footwell Light assembly	N/A	N/A	N/A	N/A	N/A
C	Control module	N/A	N/A	N/A	N/A	N/A
D	Switch Cable	N/A	N/A	N/A	N/A	N/A
E	Power Cable	N/A	N/A	N/A	N/A	N/A
F	strip light	N/A	N/A	N/A	N/A	N/A
G	CUP Holder light Receiver assembly	N/A	N/A	N/A	N/A	N/A
H	CUP Holder light Receiver	N/A	N/A	N/A	N/A	N/A

Support Equipment (Conduction, RSE)						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC
A	CUP Holder light Receiver	N/A	N/A	N/A	N/A	N/A
B	Control module	N/A	4361101	N/A	N/A	N/A
C	Front Footwell Light assembly	N/A	4361108	N/A	N/A	N/A
D	Rear Footwell Light assembly	N/A	4361110	N/A	N/A	N/A
E	Switch Cable	N/A	4361103	N/A	N/A	N/A
F	Light assembly-LH	N/A	4361094	N/A	N/A	N/A
G	Light assembly-RH	N/A	4361095	N/A	N/A	N/A
H	Power Cable	N/A	N/A	N/A	N/A	N/A
I	CUP Holder light Receiver assembly	N/A	4361112	N/A	N/A	N/A

6.2 TEST SETUP DIAGRAM



6.3 TEST PROGRAM

This EUT powered to set the frequency, modulation, and power to allow the sample to continuously transmit.


7. TEST REQUIREMENTS

7.1 20DB BANDWIDTH

Definition

According to FCC Part 15.215 (c) ,Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Configuration



TEST PROCEDURE

The Loop antenna connected to the spectrum analyzer, was touching to the transmitter antenna. Set the RBW=1% to 5% of the anticipated emission bandwidth, VBW=3*RBW, Detector = Peak, Trace mode = Max hold. Measure the maximum width of the emission that is constrained by the frequencies associated with the Occupied Bandwidth.

TEST RESULTS

Compliance


Temperature: 26.1°C
Humidity: 58% RH

Test Date: April 9, 2026
Tested By: David Li

Occupied Channel Bandwidth Result						
Modulation Mode	Frequency (Fc)	99% Bandwidth (kHz)	F _L BW (kHz)	F _H BW (kHz)	F _{SL} at 20dB BW (kHz)	F _{SH} at 20dB BW (kHz)
Full charging loading	84.652	0.352	84.478	84.83	84.457	84.818
Result		Complied				

Note: Based on ANSI C63.10a-2024, the RBW configuration is between 9kHz and 30MHz, and shall not be less than 100Hz

Test Data 20dB & 99%OBW



Temperature: 23.6°C
Humidity: 62% RH

Test Date: June 9, 2026
Tested By: David Li

Occupied Channel Bandwidth Result						
Modulation Mode	Frequency (Fc)	99% Bandwidth (kHz)	F _L BW (kHz)	F _H BW (kHz)	F _{SL} at 20dB BW (kHz)	F _{SH} at 20dB BW (kHz)
Full charging loading	89.248	0.226	89.121	89.347	89.102	89.366
Result		Complied				

Note: Based on ANSI C63.10a-2024, the RBW configuration is between 9kHz and 30MHz, and shall not be less than 100Hz

Test Data 20dB & 99%OBW



7.2 TRANSMITTER RADIATED EMISSION

LIMIT

1. According to FCC PART 15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Remark: Except as provided in other rules, fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

Above 30MHz


Frequency (MHz)	Field Strength		Measurement Distance (meter)
	(μV/m)	(dBμV/m)	
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Test Configuration

9kHz ~ 30MHz



30MHz ~ 1GHz



TEST PROCEDURE

For 9kHz ~ 30MHz

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both parallel, perpendicular, and ground-parallel.
6. Set the spectrum analyzer in the following setting as:

(1)

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz

(2) $VBW=3*RBW$


7. Repeat above procedures until the measurements for all frequencies are complete.
8. Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

For 30MHz ~ 1GHz

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both vertical and horizontal.
6. Set the spectrum analyzer in the following setting as:
RBW=100kHz / VBW=300kHz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

Main

Project No	: TM-2603000406P	Test Date	: 2026-04-13
Operation Band	: WPT	Temp./Humi.	: 25.7/51
Frequency	: 85 KHz	Antenna Pol.	: HORIZONTAL
Operation Mode	: Main	Engineer	: Tony.Chao
EUT Pol	: E2	Test Chamber	: 966A
Setting	:		




Freq	Read Level @3m	Factor @3m	Actual @3m	Factor @30m @300m	Actual @30m @300m	Limit	Margin	Detector Mode
----- MHz	----- dBuV	----- dB	----- dBuV/m	----- dB	----- dBuV/m	----- dBuV/m	----- dB	----- PK/QP/AV
0.085	36.48	12.88	49.36	-80.00	-30.64	29.02	-59.66	Peak

Remark:

- Factor = Antenna factor + Cable loss + Distance conversion factor
- Ant. Pol. (V/H/G): V=perpendicular, H=parallel, G=ground-parallel.
- Since the Factor included the distance conversion factor, the distance of Actual FS is 300m or 30m. (9kHz~490kHz is 300m, 490kHz~30MHz is 30m)
- Actual@30m or @300m=Read Level + factor
- Margin=Actual@30m or @300m-Limit

Project No : TM-2603000406P
Operation Band : WPT
Frequency : 85 KHz
Operation Mode : Main
EUT Pol : E2
Setting :

Test Date : 2026-04-13
Temp./Humi. : 25.7/51
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level @3m	Factor @3m	Actual @3m	Factor @30m @300m	Actual @30m @300m	Limit	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
0.085	39.70	12.88	52.58	-80.00	-27.42	29.06	-56.48	Peak

Remark:

- Factor = Antenna factor + Cable loss + Distance conversion factor
- Ant. Pol. (V/H/G): V=perpendicular, H=parallel, G=ground-parallel.
- Since the Factor included the distance conversion factor, the distance of Actual FS is 300m or 30m. (9kHz~490kHz is 300m, 490kHz~30MHz is 30m)
- Actual@30m or @300m=Read Level + factor
- Margin=Actual@30m or @300m-Limit

Project No : TM-2603000406P
Operation Band : WPT
Frequency : 85 KHz
Operation Mode : Main
EUT Pol : E2
Setting :

Test Date : 2026-04-13
Temp./Humi. : 25.7/51
Antenna Pol. : Ground
Engineer : Tony.Chao
Test Chamber : 966A



Freq	Read Level @3m	Factor @3m	Actual @3m	Factor @30m @300m	Actual @30m @300m	Limit	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
0.085	33.86	12.88	46.74	-80.00	-33.26	29.02	-62.28	Peak


Remark:

- Factor = Antenna factor + Cable loss + Distance conversion factor
- Ant. Pol. (V/H/G): V=perpendicular, H=parallel, G=ground-parallel.
- Since the Factor included the distance conversion factor, the distance of Actual FS is 300m or 30m. (9kHz~490kHz is 300m, 490kHz~30MHz is 30m)
- Actual@30m or @300m=Read Level + factor
- Margin=Actual@30m or @300m-Limit

9 kHz – 30MHz

Project No : TM-2603000406P
Operation Band : WPT
Frequency : 85 KHz
Operation Mode : TX
EUT Pol : E2
Setting :

Test Date : 2026-04-13
Temp./Humi. : 25.7/51
Antenna Pol. : Vertical
Engineer : Tony.Chao
Test Chamber : 966A



Freq	Read Level	Factor	Actual	Factor	Actual	Limit	Margin	Detector Mode
MHz	@3m	@3m	@3m	@300m	@300m	dBuV/m	dB	PK/QP/AV
0.062	40.30	13.35	53.65	-80.00	-26.35	31.77	-58.12	Peak
0.508	36.33	13.73	50.06	-40.00	10.06	33.48	-23.42	Peak
4.936	21.03	14.98	36.01	-40.00	-3.99	29.54	-33.53	Peak
9.284	26.65	15.65	42.30	-40.00	2.30	29.54	-27.24	Peak
18.279	27.71	17.10	44.81	-40.00	4.81	29.54	-24.73	Peak
22.199	20.06	16.84	36.90	-40.00	-3.10	29.54	-32.64	Peak


Remark:

- The frequency bands 9-90 kHz, 110-490 kHz measurements employing an average detector and other below 1GHz measurements employing a CISPR quasi-peak detector.
- For 9-90kHz, 110kHz-490kHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.
For other frequencies, the Peak value was under the Quasi-peak limit, therefore the Quasi-peak value compliance with the limit. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit.
- Factor = Antenna factor + Cable loss + Distance conversion factor
- Since the Factor included the distance conversion factor, the distance of Actual FS is 300m or 30m. (9kHz~490kHz is 300m, 490kHz~30MHz is 30m)
- The worst receiver antenna pol. is Vertical.
- Actual@30m or @300m=Read Level + factor
- Margin=Actual@30m or @300m-Limit

Below 1 GHz

Project No : TM-2603000406P
Operation Band : WPT
Frequency : 85 KHz
Operation Mode : TX
EUT Pol : E2
Setting :

Test Date : 2026-04-13
Temp./Humi. : 25.7/51
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
30.12	29.22	-2.81	26.41	40.00	-13.59	Peak
42.97	37.29	-12.18	25.11	40.00	-14.89	Peak
80.93	37.05	-16.37	20.68	40.00	-19.32	Peak
298.57	31.59	-9.25	22.34	46.00	-23.66	Peak
490.39	30.36	-4.32	26.04	46.00	-19.96	Peak
639.16	30.62	-1.62	29.00	46.00	-17.00	Peak

Remark:

- Factor = Antenna factor + Cable loss – Amp gain
- Actual=Read Level + factor
- Margin=Actual FS -Limit

Project No : TM-2603000406P
Operation Band : WPT
Frequency : 85 KHz
Operation Mode : TX
EUT Pol : E2
Setting :

Test Date : 2026-04-13
Temp./Humi. : 25.7/51
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A



Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
31.33	29.24	-3.60	25.64	40.00	-14.36	Peak
115.24	31.38	-10.07	21.31	43.50	-22.19	Peak
296.14	32.69	-9.32	23.37	46.00	-22.63	Peak
421.40	32.17	-6.04	26.13	46.00	-19.87	Peak
488.81	31.09	-4.32	26.77	46.00	-19.23	Peak
721.97	32.74	-0.65	32.09	46.00	-13.91	Peak

Remark:

1. Factor = Antenna factor + Cable loss – Amp gain
2. Actual=Read Level + factor
3. Margin=Actual FS -Limit

7.3 AC POWER-LINE CONDUCTED EMISSION

LIMIT

According to §15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

Test Configuration

See test photographs attached in Appendix A for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

Compliance.

TEST DATA

Not applicable, because EUT not connect to AC Main Source direct.



Project No: TM-2603000406P
Report No.: TMWK2603001360KR

Page 29 / 29
Rev. 01

7.4 COIL RULERS AND SPECIFICATIONS

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Antenna Type	Coil Antenna
---------------------	--------------

Remark:

1.The antenna(s) of the EUT are permanently attached and there are no provisions for connection to an external antenna. So the EUT complies with the requirements of §15.203.

- End of Test Report -