

FCC TEST REPORT

Client Name : Seeed Technology Co., Ltd.
Address : 9F, G3 Building, TCL International E City,
Zhongshanyuan Road, Nanshan District, Shenzhen,
China 518055
Product Name : WM1303 LoRaWAN Gateway Module(USB) - US915
Date : Jul. 22, 2021



Shenzhen Anbotech Compliance Laboratory Limited



Contents

1. General Information.....	5
1.1. Client Information.....	5
1.2. Description of Device (EUT).....	5
1.3. Auxiliary Equipment Used During Test.....	6
1.4. Description of Test Configuration.....	6
1.5. Description Of Test Setup.....	7
1.6. Test Equipment List.....	8
1.7. Measurement Uncertainty.....	9
1.8. Description of Test Facility.....	9
2. Summary of Test Results.....	10
3. Conducted Emission Test.....	11
3.1. Test Standard and Limit.....	11
3.2. Test Setup.....	11
3.3. Test Procedure.....	11
3.4. Test Data.....	11
4. Radiation Spurious Emission and Band Edge.....	14
4.1. Test Standard and Limit.....	14
4.2. Test Setup.....	14
4.3. Test Procedure.....	15
4.4. Test Data.....	16
5. Maximum Peak Output Power Test.....	22
5.1. Test Standard and Limit.....	22
5.2. Test Setup.....	22
5.3. Test Procedure.....	22
5.4. Test Data.....	22
6. 6DB Occupy Bandwidth Test.....	23
6.1. Test Standard and Limit.....	23
6.2. Test Setup.....	23
6.3. Test Procedure.....	23
6.4. Test Data.....	23
7. Power Spectral Density Test.....	26
7.1. Test Standard and Limit.....	26
7.2. Test Setup.....	26
7.3. Test Procedure.....	26
7.4. Test Data.....	26
8. 100kHz Bandwidth of Frequency Band Edge Requirement.....	29
8.1. Test Standard and Limit.....	29
8.2. Test Setup.....	29
8.3. Test Procedure.....	29

8.4. Test Data.....	29
9. Antenna Requirement.....	33
9.1. Test Standard and Requirement.....	33
9.2. Antenna Connected Construction.....	33
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	34
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	36
APPENDIX III -- INTERNAL PHOTOGRAPH.....	40

TEST REPORT

Applicant : Seeed Technology Co., Ltd.
Manufacturer : Seeed Technology Co., Ltd.
Product Name : WM1303 LoRaWAN Gateway Module(USB) - US915
Model No. : WM1303-USB-US915
Trade Mark : Seeed Studio
Rating(s) : Input: DC 3.3V/420mA

Test Standard(s) : FCC Part15 Subpart, Section 15.247

Test Method(s) : ANSI C63.10: 2013, KDB558074 D01 DTS Meas Guidance v05r02

The device described above is tested by Shenzhen Anbotech Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotech Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotech Compliance Laboratory Limited.

Date of receipt

Jun. 02, 2021

Date of Test

Jun. 02~Jul. 20, 2021

Prepared By

Ella Liang

(Ella Liang)

Approved & Authorized Signer

Kingkong Jin

(Kingkong Jin)

1. General Information

1.1. Client Information

Applicant	:	Seeed Technology Co., Ltd.
Address	:	9F, G3 Building, TCL International E City, Zhongshanyuan Road, Nanshan District, Shenzhen, China 518055
Manufacturer	:	Seeed Technology Co., Ltd.
Address	:	9F, G3 Building, TCL International E City, Zhongshanyuan Road, Nanshan District, Shenzhen, China 518055
Factory	:	Shenzhen Xinxian Technology Co; Limited
Address	:	F5, Building B17, Hengfeng Industrial City, No. 739 Zhoushi Rd, Baoan District, Shenzhen, Guangdong, P.R.C.

1.2. Description of Device (EUT)

Product Name	:	WM1303 LoRaWAN Gateway Module(USB) - US915
Model No.	:	WM1303-USB-US915
Trade Mark	:	Seeed Studio
Test Power Supply	:	DC 3.3V by Debug board
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Product Description	Operation Frequency:	902~928MHz
	Number of Channel:	DTS: 16 Channels FHSS: 64 Channels
	Modulation Type:	LoRa Chirp Spread Spectrum
	Antenna Type:	Cylindrical antenna
	Antenna Gain(Peak):	2.6 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2) This report for DTS only.		

1.3. Auxiliary Equipment Used During Test

Adapter	:	M/N: SAW12-050-2100UB Input: 100-240V~ 50/60Hz, 0.3A Output: DC 5V, 2100mA
---------	---	--

1.4. Description of Test Configuration



The system was configured for testing in testing mode, which was provided by manufacturer.

For LoRa mode, Detailed Frequency as below:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	903.0	9	923.3
2	904.6	10	923.9
3	906.2	11	924.5
4	907.8	12	925.1
5	909.4	13	925.7
6	911.0	14	926.3
7	912.6	15	926.9
8	914.2	16	927.5

Note: EUT was tested with Channel 1, 8 and 16.

1.5. Description Of Test Setup



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 26, 2020	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 26, 2020	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 26, 2020	1 Year
4.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 26, 2020	1 Year
5.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 26, 2020	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30 D	KD17503	Oct. 26, 2020	1 Year
7.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 02, 2020	2 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 02, 2020	2 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Nov. 02, 2020	2 Year
10.	Horn Antenna	A-INFO	LB-180400- KF	J211060628	Nov. 02, 2020	2 Year
11.	Pre-amplifier	SONOMA	310N	186860	Oct. 26, 2020	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	RF Test Control System	YIHENG	YH3000	2017430	Oct. 26, 2020	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN045	Oct. 26, 2020	1 Year
15.	Power Sensor	DAER	RPR3006W	15I00041SN046	Oct. 26, 2020	1 Year
16.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 26, 2020	1 Year
17.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 26, 2020	1 Year
18.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 26, 2020	1 Year
19.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 26, 2020	1 Year
20.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Oct. 26, 2020	1 Year

1.7. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, September 30, 2020.

ISED-Registration No.: 8058A

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A, September 30, 2020.

Test Location

Shenzhen Anbotech Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(3)	Conducted Peak Output Power	PASS
15.247(a)(2)	6dB Occupied Bandwidth	PASS
15.247(e)	Power Spectral Density	PASS
15.247(d)	Band Edge	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		

3. Conducted Emission Test


3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.


3.4. Test Data

During the test, pre-scan all the modes, and found CH08 (TX) which is the worst case, only the worst case is recorded in the report.

Please to see the following pages.

Conducted Emission Test Data


Test Site: 1# Shielded Room
 Operating Condition: CH08
 Test Specification: AC 120V, 60Hz
 Comment: Live Line
 Tem.: 24.5°C Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.4780	26.60	19.97	46.57	56.37	-9.80	QP	
2	0.4780	10.85	19.97	30.82	46.37	-15.55	AVG	
3	0.6300	1.68	20.02	21.70	46.00	-24.30	AVG	
4	1.1340	17.17	20.12	37.29	56.00	-18.71	QP	
5	1.1620	2.52	20.12	22.64	46.00	-23.36	AVG	
6	1.4420	14.56	20.13	34.69	56.00	-21.31	QP	
7	1.8580	1.73	20.14	21.87	46.00	-24.13	AVG	
8	1.9260	17.02	20.14	37.16	56.00	-18.84	QP	
9	2.6060	16.78	20.15	36.93	56.00	-19.07	QP	
10	3.3460	0.76	20.17	20.93	46.00	-25.07	AVG	
11	4.7460	15.12	20.20	35.32	56.00	-20.68	QP	
12	4.7460	0.12	20.20	20.32	46.00	-25.68	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: CH08
Test Specification: AC 120V, 60Hz
Comment: Neutral Line
Tem.: 24.5°C Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.4740	22.55	19.97	42.52	56.44	-13.92	QP	
2	0.4820	7.23	19.97	27.20	46.30	-19.10	AVG	
3	0.6580	-0.63	20.03	19.40	46.00	-26.60	AVG	
4	1.1940	15.89	20.12	36.01	56.00	-19.99	QP	
5	1.2460	0.92	20.12	21.04	46.00	-24.96	AVG	
6	1.8260	14.77	20.14	34.91	56.00	-21.09	QP	
7	1.8940	0.27	20.14	20.41	46.00	-25.59	AVG	
8	2.5579	13.89	20.15	34.04	56.00	-21.96	QP	
9	2.5860	-0.44	20.15	19.71	46.00	-26.29	AVG	
10	3.9660	-0.63	20.18	19.55	46.00	-26.45	AVG	
11	4.7460	13.58	20.20	33.78	56.00	-22.22	QP	
12	6.3100	11.05	20.24	31.29	60.00	-28.71	QP	

Note: The EUT received input Voltage DC 3.3V from Debug board, and the Debug board received input Voltage AC 120V/60Hz from Adapter.

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Shenzhen Anbotech Compliance Laboratory Limited

Code:AB-RF-05-a

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.

Tel:(86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotech.com

Hotline
400-003-0500
www.anbotech.com

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW = 1MHz, VBW = 10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS


During the test, pre-scan all the modes, and found the CH08 (TX) which is the worst case, only the worst case is recorded in the report.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.



Test Results (30~1000MHz)


Test Mode: CH08
Power Source: AC 120V, 60Hz
Polarization: Vertical
Temp.(°C)/Hum.(%RH): 24.3°C Hum.: 46%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	30.8535	44.11	-17.04	27.07	40.00	-12.93	peak			
2	53.8818	38.12	-16.15	21.97	40.00	-18.03	peak			
3	74.9191	43.53	-18.37	25.16	40.00	-14.84	peak			
4	175.0368	38.79	-18.54	20.25	43.50	-23.25	peak			
5	225.3080	35.86	-16.23	19.63	46.00	-26.37	peak			
6	750.1083	34.20	-5.22	28.98	46.00	-17.02	peak			

Test Results (30~1000MHz)

Test Mode: CH08
Power Source: AC 120V, 60Hz
Polarization: Horizontal
Temp.(°C)/Hum.(%RH): 24.3°C Hum.: 46%



Note: The EUT received input Voltage DC 3.3V from Debug board, and the Debug board received input Voltage AC 120V/60Hz from Adapter.

Test Results (1GHz-25GHz)

Test Mode: CH01					Test channel: Lowest				
Frequency (MHz)	Antenna Pol.	Reading (dBuV/m)	Cable Loss (dB)	Ant Factor (dB)	Amplifier (dB)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Det. Mode
1806.0000	H	42.74	7.39	28.73	26.31	52.55	74	-21.45	PK
1806.0000	H	34.74	7.39	28.73	26.31	44.55	54	-9.45	AV
2709.0000	H	41.30	8.10	29.71	27.01	52.10	74	-21.90	PK
2709.0000	H	33.60	8.10	29.71	27.01	44.40	54	-9.60	AV
3612.0000	H	--	--	--	--	--	--	--	PK
3612.0000	H	--	--	--	--	--	--	--	AV
1806.0000	V	42.57	7.39	28.73	26.31	52.38	74	-21.62	PK
1806.0000	V	35.36	7.39	28.73	26.31	45.17	54	-8.83	AV
2709.0000	V	42.08	8.10	29.71	27.01	52.88	74	-21.12	PK
2709.0000	V	35.10	8.10	29.71	27.01	45.90	54	-8.10	AV
3612.0000	V	--	--	--	--	--	--	--	PK
3612.0000	V	--	--	--	--	--	--	--	AV

Test Mode: CH01					Test channel: Middle				
Frequency (MHz)	Antenna Pol.	Reading (dBuV/m)	Cable Loss (dB)	Ant Factor (dB)	Amplifier (dB)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Det. Mode
1846.6000	H	43.47	7.39	28.73	26.31	53.28	74	-20.72	PK
1846.6000	H	35.60	7.39	28.73	26.31	45.41	54	-8.59	AV
2769.9000	H	42.47	8.10	29.71	27.01	53.27	74	-20.73	PK
2769.9000	H	33.91	8.10	29.71	27.01	44.71	54	-9.29	AV
3693.2000	H	--	--	--	--	--	--	--	PK
3693.2000	H	--	--	--	--	--	--	--	AV
1846.6000	V	43.42	7.39	28.73	26.31	53.23	74	-20.77	PK
1846.6000	V	34.36	7.39	28.73	26.31	44.17	54	-9.83	AV
2769.9000	V	42.29	8.10	29.71	27.01	53.09	74	-20.91	PK
2769.9000	V	34.42	8.10	29.71	27.01	45.22	54	-8.78	AV
3693.2000	V	--	--	--	--	--	--	--	PK
3693.2000	V	--	--	--	--	--	--	--	AV

Test Mode: CH08					Test channel: High				
Frequency (MHz)	Antenna Pol.	Reading (dBuV/m)	Cable Loss (dB)	Ant Factor (dB)	Amplifier (dB)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Det. Mode
1855.0000	H	48.10	7.43	28.69	26.31	57.91	74	-16.09	PK
1855.0000	H	36.05	7.43	28.69	26.31	45.86	54	-8.14	AV
2782.5000	H	45.06	8.15	29.84	27.01	56.04	74	-17.96	PK
2782.5000	H	34.35	8.15	29.84	27.01	45.33	54	-8.67	AV
3710.0000	H	--	--	--	--	--	--	--	PK
3710.0000	H	--	--	--	--	--	--	--	AV
1855.0000	V	47.51	7.43	28.69	26.31	57.32	74	-16.68	PK
1855.0000	V	35.99	7.43	28.69	26.31	45.80	54	-8.20	AV
2782.5000	V	46.62	8.15	29.84	27.01	57.60	74	-16.40	PK
2782.5000	V	35.12	8.15	29.84	27.01	46.10	54	-7.90	AV
3710.0000	V	--	--	--	--	--	--	--	PK
3710.0000	V	--	--	--	--	--	--	--	AV

Remark:

1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

2. “--” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Band Edge:

Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Det.
902.0000	44.20	22.45	4.48	31.33	39.80	46.00	-6.20	H	QP
928.0000	41.17	22.59	4.54	31.35	36.95	46.00	-9.05	H	QP
902.0000	43.20	22.45	4.48	31.33	38.80	46.00	-7.20	V	QP
928.0000	40.52	22.59	4.54	31.35	36.30	46.00	-9.70	V	QP

Remark:


1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	30dBm

5.2. Test Setup



5.3. Test Procedure

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

1. Set the RBW $\geq$ DTS bandwidth.
2. Set the VBW $\geq 3 \times$ RBW.
3. Set the span $\geq 3 \times$ RBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.

5.4. Test Data

Test Item	:	Max. peak output power
Test Voltage	:	DC 3.3V
Test Result	:	PASS

Test Mode	:	CH Low ~ CH High
Temperature	:	23.6°C
Humidity	:	53 %


Channel Frequency (MHz)	Peak Power output (dBm)	Limit (dBm)	Results
903.0	25.081	30	PASS
923.3	25.066	30	PASS
927.5	25.939	30	PASS

6. 6DB Occupy Bandwidth Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(2)
Test Limit	>500kHz

6.2. Test Setup



6.3. Test Procedure


1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
RBW = 100kHz, VBW $\geq$ 3*RBW =300kHz,
Detector= Peak
Trace mode= Max hold.
Sweep- auto couple.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

6.4. Test Data


Test Item : 6dB Bandwidth
Test Voltage : DC 3.3V
Test Result : PASS

Test Mode : CH Low ~ CH High
Temperature : 23.6℃
Humidity : 53 %

Channel	Frequency(MHz)	Bandwidth (kHz)	Limit (kHz)	Results
Low	903.0	634.7	>500	PASS
Middle	923.3	637.6		PASS
High	927.5	638.7		PASS



CH: Low



CH: Middle




CH: High

7. Power Spectral Density Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (e)
Test Limit	8dBm/3KHz

7.2. Test Setup



7.3. Test Procedure


1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 1.5xDTSS BW
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

7.4. Test Data


Test Item	: Power Spectral Density
Test Voltage	: DC 3.3V
Test Result	: PASS

Test Mode	: CH Low ~ CH High
Temperature	: 23.6℃
Humidity	: 53 %


Channel	Frequency (MHz)	PSD (dBm/3KHz)	Limit (dBm/3KHz)	Results
Low	903.0	7.327	8.00	PASS
Middle	923.3	7.499	8.00	PASS
High	927.5	6.568	8.00	PASS



CH: Low



CH: Middle




CH: High

8. 100kHz Bandwidth of Frequency Band Edge Requirement

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

8.2. Test Setup



8.3. Test Procedure


Using the following spectrum analyzer setting:

1. Set the RBW = 100KHz.
2. Set the VBW = 300KHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.


8.4. Test Data

Test Item	:	Band edge
Test Voltage	:	DC 3.3V
Test Result	:	PASS

Test Mode	:	CH Low ~ CH High
Temperature	:	23.6℃
Humidity	:	53 %



CH: Low



CH: High


Shenzhen Anbotech Compliance Laboratory Limited

Code:AB-RF-05-a


Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.

Tel: (86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotech.com


Hotline
400-003-0500
www.anbotech.com



CH: Low



CH: Middle



CH: High

9. Antenna Requirement

9.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna

9.2. Antenna Connected Construction


The antenna is a Cylindrical antenna which permanently attached, and the best case gain of the antenna is 2.6 dBi. It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Photo of Conducted Emission Measurement




Photo of Radiation Emission Test









APPENDIX II -- EXTERNAL PHOTOGRAPH









APPENDIX III -- INTERNAL PHOTOGRAPH

----- End of Report -----