

FCC & IC REPORT

Applicant: REACH Tech (Xiamen) Co., Ltd.

Address of Applicant: RM.303,#18,Guanri Road, Software Park II, Xiamen,361008, China

Equipment Under Test (EUT)

Product Name: Smart Phone

Model No.: R55

FCC ID: Z5JREACH-Q887R

Canada IC: 11908A-Q887R

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247
RSS-Gen Issue 3, December 2010
RSS 210 Issue 8, December 2010

Date of sample receipt: 20 Mar., 2014

Date of Test: 21 Mar., to 14 Apr., 2014

Date of report issued: 15 Apr., 2014

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	15 Apr.,2014	Original

Prepared by:

Sera Xiang

Report Clerk

Date:

15 Apr.,2014

Reviewed by:

Abimb Yang

Project Engineer

Date:

15 Apr.,2014

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T.	5
5.3 TEST MODE	7
5.4 LABORATORY FACILITY	7
5.5 LABORATORY LOCATION	7
5.6 TEST INSTRUMENTS LIST	8
6 TEST RESULTS AND MEASUREMENT DATA	9
6.1 ANTENNA REQUIREMENT	9
6.2 CONDUCTED EMISSIONS	11
6.3 CONDUCTED OUTPUT POWER.....	14
6.4 OCCUPY BANDWIDTH.....	18
6.5 CARRIER FREQUENCIES SEPARATION.....	25
6.6 HOPPING CHANNEL NUMBER	30
6.7 DWELL TIME.....	32
6.8 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	36
6.9 BAND EDGE.....	37
6.9.1 Conducted Emission Method	37
6.9.2 Radiated Emission Method.....	41
6.10 SPURIOUS EMISSION	54
6.10.1 Conducted Emission Method.....	54
6.10.2 Radiated Emission Method	58
6.11 RECEIVER SPURIOUS EMISSIONS	63
7 TEST SETUP PHOTO	67
8 EUT CONSTRUCTIONAL DETAILS	68

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247 (c) RSS Gen section 7.1.2	Pass
AC Power Line Conducted Emission	15.207 RSS Gen section 7.1.4	Pass
Conducted Peak Output Power	15.247 (b)(1) RSS 210 section A8.4	Pass
20dB Occupied Bandwidth	15.247 (a)(1) RSS 210 section A8.1 (a)	Pass
Carrier Frequencies Separation	15.247 (a)(1) RSS 210 section A8.1 (b)	Pass
Hopping Channel Number	15.247 (a)(1) RSS 210 section A8.1 (d)	Pass
Dwell Time	15.247 (a)(1) RSS 210 section A8.1 (d)	Pass
Radiated Emission	15.205/15.209 RSS 210 section A8.5	Pass
Band Edge	15.247(d) RSS 210 section A8.5	Pass
Pseudorandom Frequency Hopping Sequence	RSS 210 section A8.1	Pass
Receiver spurious emissions	RSS Gen section 4.10	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	REACH Tech (Xiamen) Co., Ltd.
Address of Applicant:	RM.303,#18,Guanri Road, Software Park II, Xiamen,361008, China
Manufacturer:	REACH Tech (Xiamen) Co., Ltd.
Address of Manufacturer:	RM.303,#18,Guanri Road, Software Park II, Xiamen,361008,China
Factory:	REACH Tech (Xiamen) Co., Ltd.
Address of Factory:	5/F,#51,Wanghai Road, Software Park II,Xiamen,361008, China

5.2 General Description of E.U.T.

Product Name:	Smart Phone
Model No.:	R55
Operation Frequency:	2402MHz~2480MHz
Transfer rate:	1/2/3 Mbits/s
Number of channel:	79
Modulation type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Modulation technology:	FHSS
Antenna Type:	Internal Antenna
Antenna gain:	-0.33 dBi
Power supply:	Rechargeable Li-ion Battery DC3.7V-2100mAh
AC adapter:	Model:SKL-5WU-U050-0700 Input:100-240V AC,50/60Hz 150mA Output:5.0V DC MAX700mA

Operation Frequency each of channel for GFSK, $\pi/4$ -DQPSK, 8DPSK							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		
Remark: Channel 0, 39 & 78 selected for GFSK, $\pi/4$ -DQPSK and 8DPSK.							

5.3 Test mode

Transmitting mode:	Keep the EUT in transmitting mode with worst case data rate.
Remark	GFSK (1 Mbps) is the worst case mode.
The sample was placed 0.8m above the ground plane of 3m chamber*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working with a fresh battery, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

5.4 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 817957, February 27, 2012.

● **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.5 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282

Fax: +86-755-23116366

5.6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	June 09 2013	June 08 2014
2	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	CCIS0005	May 25 2013	May 24 2014
3	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	CCIS0006	May 25 2013	May 24 2014
4	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
5	Coaxial Cable	CCIS	N/A	CCIS0016	Feb. 01 2014	Feb. 31 2015
6	Coaxial Cable	CCIS	N/A	CCIS0017	Feb. 01 2014	Feb. 31 2015
7	Coaxial cable	CCIS	N/A	CCIS0018	Feb. 01 2014	Feb. 31 2015
8	Coaxial Cable	CCIS	N/A	CCIS0019	Feb. 01 2014	Feb. 31 2015
9	Coaxial Cable	CCIS	N/A	CCIS0087	Feb. 01 2014	Feb. 31 2015
10	Amplifier(10kHz-1.3GHz)	HP	8447D	CCIS0003	Feb. 01 2014	Feb. 31 2015
11	Amplifier(1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	June 09 2013	June 08 2014
12	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	Feb. 01 2014	Feb. 31 2015
13	Horn Antenna	ETS-LINDGREN	3160	GTS217	Feb. 30 2014	Feb. 29 2015
14	Printer	HP	HP LaserJet P1007	N/A	N/A	N/A
15	Positioning Controller	UC	UC3000	CCIS0015	N/A	N/A
16	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP	CCIS0023	May. 25 2013	May. 24 2014
17	EMI Test Receiver	Rohde & Schwarz	ESPI	CCIS0022	Feb 01 2014	Feb. 31 2015
18	Loop antenna	Laplace instrument	RF300	EMC0701	Aug. 12 2013	Aug. 11 2014
19	Universal radio communication tester	Rhode & Schwarz	CMU200	CCIS0069	May. 25 2013	May. 24 2014
20	Signal Analyzer	Rohde & Schwarz	FSIQ3	CCIS0088	May. 25 2013	May. 24 2014

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	June 09 2013	June 08 2014
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	May 25 2013	May 24 2014
3	LISN	CHASE	MN2050D	CCIS0074	Feb 01 2014	Feb. 31 2015
4	Coaxial Cable	CCIS	N/A	CCIS0086	Feb. 01 2014	Feb. 31 2015
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

6 Test results and Measurement Data

6.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c) RSS Gen section 7.1.2
1. 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi. 2. RSS Gen section 7.1.2 A transmitter can only be sold or operated with antennas with which it was approved. Transmitter may be approved with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns. Testing shall be performed using the highest gain antenna of each combination of transmitter and antenna type for which approval is being sought, with the transmitter output power set at the maximum level. Any antenna of the same type having equal or lesser gain as an antenna that had been successfully tested with the transmitter, will also be considered approved with the transmitter, and may be used and marketed with the transmitter. For Category I transmitters, the manufacturer shall include with the application for certification a list of acceptable antenna types to be used with the transmitter. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer. For transmitters of RF output power of 10 milliwatts or less, only the portion of the antenna gain that is in excess of 6 dBi (6 dB above isotropic gain) shall be added to the measured RF output power to demonstrate compliance with the radiated power limits specified in the applicable standard. For transmitters of output power greater than 10 milliwatts, the total antenna gain shall be added to the measured RF output power to demonstrate compliance to the specified radiated power limits. User manuals for transmitters shall display the following notice in a conspicuous location: Under Industry Canada regulations, this radio transmitter may only operate using an antenna of a type and maximum (or lesser) gain approved for the transmitter by Industry Canada. To reduce potential radio interference to other users, the antenna type and its gain should be so chosen that the equivalent isotropically radiated power (e.i.r.p.) is not more than that necessary for successful communication. The above notice may be affixed to the device instead of displayed in the user manual. User manuals for transmitters equipped with detachable antennas shall also contain the following notice in a conspicuous location: This radio transmitter (identify the device by certification number, or model number if Category II) has been approved by Industry Canada to operate with the antenna types listed below with the maximum permissible gain and required antenna impedance for each antenna type indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device. Immediately following the above notice, the manufacturer shall provide a list of all antenna types approved for use with the transmitter, indicating the maximum permissible antenna gain (in dBi) and required impedance for each.	


E.U.T Antenna:	
The Bluetooth antenna is an integral antenna which permanently attached, and the best case gain of the antenna is -0.33 dBi.	
	

6.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207 RSS Gen section 7.1.4																
Test Method:	ANSI C63.4:2003 ANSI C63.4:2003																
Test Frequency Range:	150 kHz to 30 MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto																
Limit:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table> * Decreases with the logarithm of the frequency.			Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															
Test setup:	Reference Plane Test table/Insulation plane <i>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</i>																
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.																
Test Instruments:	Refer to section 5.6 for details																
Test mode:	Bluetooth (Continuous transmitting) mode																
Test results:	Pass																

Measurement Data

Line:




Trace: 39

Site : CCIS Conducted test Site
 Condition : FCC PART15 B QP LISN LINE
 Job No. : 154RF
 EUT : Smart Phone
 Model : R55
 Test Mode : BT Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: A-bomb
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.162	35.85	0.27	10.77	46.89	65.34	-18.45	QP
2	0.162	28.87	0.27	10.77	39.91	55.34	-15.43	Average
3	0.266	33.92	0.27	10.75	44.94	61.25	-16.31	QP
4	0.369	44.53	0.27	10.73	55.53	58.52	-2.99	QP
5	0.369	35.60	0.27	10.73	46.60	48.52	-1.92	Average
6	0.421	39.94	0.28	10.73	50.95	57.42	-6.47	QP
7	0.421	29.01	0.28	10.73	40.02	47.42	-7.40	Average
8	0.582	40.10	0.26	10.77	51.13	56.00	-4.87	QP
9	0.582	30.55	0.26	10.77	41.58	46.00	-4.42	Average
10	0.844	26.63	0.24	10.82	37.69	46.00	-8.31	Average
11	0.848	38.55	0.24	10.82	49.61	56.00	-6.39	QP
12	1.060	25.86	0.25	10.88	36.99	46.00	-9.01	Average

Neutral:



Trace: 37


Site : CCIS Conducted test Site
 Condition : FCC PART15 B QP LISN NEUTRAL
 Job No. : 154RF
 EUT : Smart Phone
 Model : R55
 Test Mode : BT Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: A-bomb
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.158	37.06	0.25	10.78	48.09	65.56	-17.47	QP
2	0.158	29.46	0.25	10.78	40.49	55.56	-15.07	Average
3	0.313	35.64	0.26	10.74	46.64	59.88	-13.24	QP
4	0.369	41.67	0.25	10.73	52.65	58.52	-5.87	QP
5	0.369	34.61	0.25	10.73	45.59	48.52	-2.93	Average
6	0.421	31.69	0.26	10.73	42.68	47.42	-4.74	Average
7	0.426	38.31	0.26	10.73	49.30	57.33	-8.03	QP
8	0.579	38.97	0.24	10.77	49.98	56.00	-6.02	QP
9	0.582	32.29	0.24	10.77	43.30	46.00	-2.70	Average
10	0.792	27.69	0.19	10.81	38.69	46.00	-7.31	Average
11	0.844	27.54	0.20	10.82	38.56	46.00	-7.44	Average
12	1.000	36.99	0.22	10.87	48.08	56.00	-7.92	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss

6.3 Conducted Output Power


Test Requirement:	FCC Part15 C Section 15.247 (b)(3) RSS 210 section A8.4
Test Method:	ANSI C63.4:2003 and DA00-705 RSS Gen section 4.8
Receiver setup:	RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW $\leq$ 1 MHz) RBW=3MHz, VBW=10MHz, Detector=Peak (If 20dB BW > 1 MHz and < 3MHz)
Limit:	125 mW(21 dBm)
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 5.6 for details
Test mode:	Non-hopping mode
Test results:	Pass

Measurement Data


GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	1.29	21.00	Pass
Middle	2.65	21.00	Pass
Highest	3.70	21.00	Pass
$\pi/4$ -DQPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	2.19	21.00	Pass
Middle	3.31	21.00	Pass
Highest	4.40	21.00	Pass
8DPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	2.65	21.00	Pass
Middle	3.70	21.00	Pass
Highest	4.69	21.00	Pass

Test plot as follows:


Modulation mode:	GFSK
------------------	------



Lowest channel




Middle channel




Highest channel


Modulation mode:	$\pi/4$ -DQPSK
------------------	----------------



Lowest channel




Middle channel




Highest channel


Modulation mode:	8DPSK
------------------	-------



Lowest channel




Middle channel



Highest channel

6.4 Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(1) RSS 210 section A8.1 (a)
Test Method:	ANSI C63.4:2003 and DA00-705 RSS Gen section 4.6
Receiver setup:	RBW=30 kHz, VBW=100 kHz, detector=Peak
Limit:	NA
Test setup:	
Test Instruments:	Refer to section 5.6 for details
Test mode:	Non-hopping mode
Test results:	Pass


Measurement Data

Test channel	20dB Occupy Bandwidth (kHz)		
	GFSK	$\pi/4$ -DQPSK	8DPSK
Lowest	1114.23	1414.83	1386.77
Middle	1118.24	1422.85	1386.77
Highest	1098.20	1430.86	1414.83


Test channel	99% Occupy Bandwidth (kHz)		
	GFSK	$\pi/4$ -DQPSK	8DPSK
Lowest	969.94	1218.44	1218.44
Middle	957.92	1222.44	1210.42
Highest	957.92	1222.44	1214.42

Test plot as follows:


Modulation mode:	GFSK
------------------	------



Lowest channel




Middle channel




Highest channel


Modulation mode:	$\pi/4$ -DQPSK
------------------	----------------



Lowest channel




Middle channel




Highest channel


Modulation mode:	8DPSK
------------------	-------



Lowest channel




Middle channel




Highest channel


Modulation mode: 99% Occupy Bandwidth	GFSK
---------------------------------------	------



Lowest channel




Middle channel




Highest channel


Modulation mode:99% Occupy Bandwidth	$\pi/4$ -DQPSK
--------------------------------------	----------------



Lowest channel




Middle channel




Highest channel


Modulation mode: 99% Occupy Bandwidth	8DPSK
---------------------------------------	-------



Lowest channel




Middle channel



Highest channel

6.5 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1) RSS 210 section A8.1 (b)
Test Method:	ANSI C63.4:2003 and DA00-705 RSS 210 section A8.1 (b)
Receiver setup:	RBW=100 kHz, VBW=300 kHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 5.6 for details
Test mode:	Hopping mode
Test results:	Pass

Measurement Data


GFSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1002	745.49	Pass
Middle	1002	745.49	Pass
Highest	1002	745.49	Pass
$\pi/4$ -DQPSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1002	953.91	Pass
Middle	1002	953.91	Pass
Highest	1002	953.91	Pass
8DPSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1002	943.22	Pass
Middle	1002	943.22	Pass
Highest	1002	943.22	Pass

Note: According to section 6.4


Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	1118.24	745.49
$\pi/4$ -DQPSK	1430.86	953.91
8DPSK	1414.83	943.22

Test plot as follows:


Modulation mode:	GFSK
------------------	------



Lowest channel




Middle channel




Highest channel


Modulation mode:	$\pi/4$ -DQPSK
------------------	----------------



Lowest channel




Middle channel




Highest channel


Modulation mode:	8DPSK
------------------	-------



Lowest channel




Middle channel



Highest channel


6.6 Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (a)(1) RSS 210 section A8.1 (d)
Test Method:	ANSI C63.4:2003 and DA00-705 RSS 210 section A8.1 (d)
Receiver setup:	RBW=100 kHz, VBW=300 kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer and an E.U.T. (Equipment Under Test) are connected by a red cable. They are positioned on a table labeled 'Non-Conducted Table'. Below this table is a 'Ground Reference Plane'.
Test Instruments:	Refer to section 5.6 for details
Test mode:	Hopping mode
Test results:	Pass


Measurement Data:

Mode	Hopping channel numbers	Limit	Result
GFSK, $\pi/4$ -DQPSK, 8DPSK	79	15	Pass


GFSK




$\pi/4$ -DQPSK



8DPSK



6.7 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1) RSS 210 section A8.1 (d)
Test Method:	ANSI C63.4:2003 and KDB DA00-705 RSS 210 section A8.1 (d)
Receiver setup:	RBW=1 MHz, VBW=1 MHz, Span=0 Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 5.6 for details
Test mode:	Hopping mode
Test results:	Pass

Measurement Data (Worse case)

Mode	Packet	Dwell time (second)	Limit (second)	Result
GFSK	DH1	0.12448	0.4	Pass
	DH3	0.26448		
	DH5	0.31040		
$\pi/4$ -DQPSK	2-DH1	0.12704	0.4	Pass
	2-DH3	0.26544		
	2-DH5	0.31125		
8DPSK	3-DH1	0.12704	0.4	Pass
	3-DH3	0.26448		
	3-DH5	0.31125		

For GFSK, $\pi/4$ -DQPSK and 8DPSK:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

DH1 time slot = $0.389 \times (1600 / (2 \times 79)) \times 31.6 = 124.48 \text{ ms}$

DH3 time slot = $1.653 \times (1600 / (4 \times 79)) \times 31.6 = 264.48 \text{ ms}$

DH5 time slot = $2.910 \times (1600 / (6 \times 79)) \times 31.6 = 310.40 \text{ ms}$

2-DH1 time slot = $0.397 \times (1600 / (2 \times 79)) \times 31.6 = 127.04 \text{ ms}$

2-DH3 time slot = $1.659 \times (1600 / (4 \times 79)) \times 31.6 = 265.44 \text{ ms}$

2-DH5 time slot = $2.918 \times (1600 / (6 \times 79)) \times 31.6 = 311.25 \text{ ms}$


3-DH1 time slot = $0.397 \times (1600 / (2 \times 79)) \times 31.6 = 127.04 \text{ ms}$

3-DH3 time slot = $1.653 \times (1600 / (4 \times 79)) \times 31.6 = 264.48 \text{ ms}$


3-DH5 time slot = $2.918 \times (1600 / (6 \times 79)) \times 31.6 = 311.25 \text{ ms}$

Test plot as follows:


Modulation mode:	GFSK
------------------	------



DH1




DH3




DH5


Modulation mode:	$\pi/4$ -DQPSK
------------------	----------------



2-DH1




2-DH3




2-DH5


Modulation mode:	8DPSK
------------------	-------



3-DH1




3-DH3




3-DH5

6.8 Pseudorandom Frequency Hopping Sequence

Test Requirement:	FCC Part15 C Section 15.247 (a)(1) requirement: RSS 210 section A8.1																												
Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.																													
EUT Pseudorandom Frequency Hopping Sequence																													
The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones. • Number of shift register stages: 9 • Length of pseudo-random sequence: $2^9 - 1 = 511$ bits • Longest sequence of zeros: 8 (non-inverted signal)  <i>Linear Feedback Shift Register for Generation of the PRBS sequence</i> An example of Pseudorandom Frequency Hopping Sequence as follow: <table style="width: 100%; text-align: center; border-collapse: collapse;"><tr><td style="width: 15%;">0</td><td style="width: 15%;">2</td><td style="width: 15%;">4</td><td style="width: 15%;">6</td><td style="width: 15%;"></td><td style="width: 15%;">62</td><td style="width: 15%;">64</td><td style="width: 15%;"></td><td style="width: 15%;">78</td><td style="width: 15%;">1</td><td style="width: 15%;"></td><td style="width: 15%;">73</td><td style="width: 15%;">75</td><td style="width: 15%;">77</td></tr><tr><td style="height: 40px; width: 15%;"></td><td style="height: 40px; width: 15%;"></td><td style="height: 40px; width: 15%;"></td><td style="height: 40px; width: 15%;"></td><td style="width: 15%;"></td><td style="height: 40px; width: 15%;"></td><td style="height: 40px; width: 15%;"></td><td style="width: 15%;"></td><td style="height: 40px; width: 15%;"></td><td style="height: 40px; width: 15%;"></td><td style="width: 15%;"></td><td style="height: 40px; width: 15%;"></td><td style="height: 40px; width: 15%;"></td><td style="height: 40px; width: 15%;"></td></tr></table>		0	2	4	6		62	64		78	1		73	75	77														
0	2	4	6		62	64		78	1		73	75	77																
Each frequency used equally on the average by each transmitter. The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.																													



6.9 Band Edge

6.9.1 Conducted Emission Method



Test Requirement:	FCC Part15 C Section 15.247 (d) RSS 210 section A8.5
Test Method:	ANSI C63.4:2003 and DA00-705 RSS Gen section 4.9
Receiver setup:	RBW=100 kHz, VBW=300 kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 5.6 for details
Test mode:	Non-hopping mode and hopping mode
Test results:	Pass

Test plot as follows:



GFSK




$\pi/4$ -DQPSK



8DPSK




6.9.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205 RSS 210 section A8.5 & RSS Gen section 7.2.2				
Test Method:	ANSI C63.4: 2003 RSS Gen section 4.9				
Test Frequency Range:	2.3GHz to 2.5GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	Above 1GHz		54.00		Average Value
			74.00		Peak Value
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test Instruments:	Refer to section 5.6 for details				
Test mode:	Non-hopping mode				
Test results:	Passed				

Remark:

1. During the test, pre-scan the GFSK, $\pi/4$ -DQPSK, 8DPSK, and all data were shown in report.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.


GFSK mode
Test channel: Lowest
Horizontal:



Trace: 171
Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
EUT : Smart phone
Model : R55
Test mode : BT mode BE DH1-L
Power Rating : AC120V/60Hz
Environment : Temp:25.5°C Humi:55%
Test Engineer: A-bomb
REMARK :

	Freq	ReadAntenna		Cable	Preamp		Limit	Over	
		Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	18.77	27.58	5.67	0.00	52.02	74.00	-21.98	Peak
2	2390.000	6.49	27.58	5.67	0.00	39.74	54.00	-14.26	Average

Vertical:




Trace: 173
 Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Smart phone
 Model : R55
 Test mode : BT mode BE DH1-L
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

	Freq	ReadAntenna Level	Cable Factor	Preamp Loss	Level	Limit	Over	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	18.84	27.58	5.67	0.00	52.09	74.00	-21.91 Peak
2	2390.000	6.53	27.58	5.67	0.00	39.78	54.00	-14.22 Average

Test channel: Highest


Horizontal:



Trace: 161
 Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : Smart phone
 Model : R55
 Test mode : BT mode BE DH1-H
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier	Level	Limit	Over	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1	2483.500	17.49	27.52	5.70	0.00	50.71	74.00	-23.29	Peak
2	2483.500	6.43	27.52	5.70	0.00	39.65	54.00	-14.35	Average


Vertical:



Trace: 159
 Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Smart phone
 Model : R55
 Test mode : BT mode BE DH1-H
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	19.90	27.52	5.70	0.00	53.12	74.00	-20.88	Peak
2	2483.500	6.52	27.52	5.70	0.00	39.74	54.00	-14.26	Average


$\pi/4$ -DQPSK mode
Test channel: Lowest
Horizontal:



Trace: 169
Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
EUT : Smart phone
Model : R55
Test mode : BT mode BE 2DH1-L
Power Rating : AC120V/60Hz
Environment : Temp:25.5°C Humi:55%
Test Engineer: A-bomb
REMARK :

	Freq	Read	Antenna	Cable	Preamp	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	dBuV/m	Line	Limit	Remark
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	18.87	27.58	5.67	0.00	52.12	74.00	-21.88	Peak
2	2390.000	6.49	27.58	5.67	0.00	39.74	54.00	-14.26	Average

Vertical:




Trace: 175

Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Smart phone
 Model : R55
 Test mode : BT mode BE 2DH1-L
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

	Freq	Read	Antenna	Cable	Preamp	Limit	Over	
		Level	Factor	Loss	Factor	Level	Line	Limit Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	18.61	27.58	5.67	0.00	51.86	74.00	-22.14 Peak
2	2390.000	6.51	27.58	5.67	0.00	39.76	54.00	-14.24 Average

Test channel: Highest

Horizontal:




Trace: 163

Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : Smart phone
 Model : R55
 Test mode : BT mode BE 2DH1-H
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

		ReadAntenna	Cable Preamp		Limit	Over	
Freq	Level	Factor	Loss Factor	Level	Line	Limit	Remark
-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1 2483.500	20.82	27.52	5.70	0.00	54.04	74.00	-19.96 Peak
2 2483.500	6.44	27.52	5.70	0.00	39.66	54.00	-14.34 Average

Vertical:



Trace: 157


Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120 (1G18) VERTICAL
 EUT : Smart phone
 Model : R55
 Test mode : BT mode BE 2DH1-H
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

	Freq	Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1	2483.500	19.76	27.52	5.70	0.00	52.98	74.00	-21.02	Peak
2	2483.500	6.48	27.52	5.70	0.00	39.70	54.00	-14.30	Average

8DPSK mode

Test channel: Lowest

Horizontal:




Trace: 167

Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : Smart phone
 Model : R55
 Test mode : BT mode BE 3DH1-L
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

	Freq	Read	Antenna	Cable	Preamp	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	18.51	27.58	5.67	0.00	51.76	74.00	-22.24 Peak
2	2390.000	6.51	27.58	5.67	0.00	39.76	54.00	-14.24 Average

Vertical:




Trace: 177

Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Smart phone
 Model : R55
 Test mode : BT mode BE 3DH1-L
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
		Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	17.79	27.58	5.67	0.00	51.04	74.00	-22.96	Peak
2	2390.000	6.55	27.58	5.67	0.00	39.80	54.00	-14.20	Average

Test channel: Highest

Horizontal:




Trace: 165

Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : Smart phone
 Model : R55
 Test mode : BT mode BE 3DH1-H
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

	Freq	ReadAntenna	Cable	Preamp		Limit	Over	
		Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	19.80	27.52	5.70	0.00	53.02	74.00	-20.98 Peak
2	2483.500	6.42	27.52	5.70	0.00	39.64	54.00	-14.36 Average

Vertical:




Trace: 155
 Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Smart phone
 Model : R55
 Test mode : BT mode BE 3DH1-H
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	18.95	27.52	5.70	0.00	52.17	74.00	-21.83 Peak
2	2483.500	6.49	27.52	5.70	0.00	39.71	54.00	-14.29 Average


6.10 Spurious Emission

6.10.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d) RSS 210 section A8.5
Test Method:	ANSI C63.4:2003 and DA00-705 RSS 210 section A8.5
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by two vertical legs. Below the table is a Ground Reference Plane, represented by a thick grey bar.
Test Instruments:	Refer to section 5.6 for details
Test mode:	Non-hopping mode
Test results:	Pass

GFSK


Lowest channel



Date: 31.MAR.2014 15:23:44

30MHz~25GHz


Middle channel



Date: 31.MAR.2014 15:25:51

30MHz~25GHz

Highest channel




Date: 31.MAR.2014 15:28:04

30MHz~25GHz

$\pi/4$ -DQPSK


Lowest channel



Date: 31.MAR.2014 15:30:22

30MHz~25GHz


Middle channel



Date: 31.MAR.2014 15:32:10

30MHz~25GHz

Highest channel




Date: 31.MAR.2014 15:33:40

30MHz~25GHz

8DPSK


Lowest channel



Date: 31.MAR.2014 15:35:27

30MHz~25GHz


Middle channel



Date: 31.MAR.2014 15:36:44

30MHz~25GHz



Highest channel



Date: 31.MAR.2014 15:38:33

30MHz~25GHz

6.10.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 RSS 210 section A8.5				
Test Method:	ANSI C63.4: 2003 RSS Gen section 4.9				
Test Frequency Range:	9 kHz to 25 GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
			74.0		Peak Value
Test setup:	Below 1GHz				
					
	Above 1GHz				
					

Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 5.6 for details
Test mode:	Non-hopping mode
Test results:	Pass


Remark:

1. During the test, pre-scan the GFSK, $\pi/4$ -DQPSK, 8DPSK modulation, and found the GFSK modulation is the worst case.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.
3. 9 kHz to 30 MHz is noise floor, so only shows the data of above 30MHz in this report.

Measurement data:

Below 1GHz


Vertical:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) VERTICAL
 EUT : Smart phone
 Model : R55
 Test mode : BT mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

	Freq	Read	Antenna	Cable	Preamp	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	dBuV/m	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	30.000	49.91	12.33	0.72	26.27	36.69	40.00	-3.31	QP
2	35.499	47.44	12.44	1.07	26.85	34.10	40.00	-5.90	QP
3	57.594	38.77	12.87	1.37	28.99	24.02	40.00	-15.98	QP
4	115.321	45.45	11.31	2.11	29.78	29.09	43.50	-14.41	QP
5	145.351	38.54	8.23	2.46	29.30	19.93	43.50	-23.57	QP
6	178.133	32.53	9.55	2.71	26.96	17.83	43.50	-25.67	QP

Horizontal:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) HORIZONTAL
 EUT : Smart phone
 Model : R55
 Test mode : BT mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

	Freq	Read	Antenna	Cable	Preamp	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	dBuV/m	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	32.864	37.09	12.31	0.91	26.58	23.73	40.00	-16.27	QP
2	57.594	32.47	12.87	1.37	28.99	17.72	40.00	-22.28	QP
3	124.569	42.47	9.80	2.22	29.62	24.87	43.50	-18.63	QP
4	138.387	41.80	8.30	2.38	29.40	23.08	43.50	-20.42	QP
5	249.425	39.83	12.07	2.81	29.60	25.11	46.00	-20.89	QP
6	747.483	33.17	19.43	4.35	30.50	26.45	46.00	-19.55	QP

Above 1GHz:

Test channel:			Lowest		Level:		Peak	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	47.26	31.53	8.90	40.24	47.45	74.00	-26.55	Vertical
7206.00	46.36	36.47	10.59	41.24	52.18	74.00	-21.82	Vertical
4804.00	47.11	31.53	8.90	40.24	47.30	74.00	-26.70	Horizontal
7206.00	45.06	36.47	10.59	41.24	50.88	74.00	-23.12	Horizontal
Test channel:			Lowest		Level:		Average	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	35.85	31.53	8.90	40.24	36.04	54.00	-17.96	Vertical
7206.00	36.23	36.47	10.59	41.24	42.05	54.00	-11.95	Vertical
4804.00	37.28	31.53	8.90	40.24	37.47	54.00	-16.53	Horizontal
7206.00	35.81	36.47	10.59	41.24	41.63	54.00	-12.37	Horizontal



Test channel:			Middle		Level:		Peak	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	46.70	31.58	8.98	40.15	47.11	74.00	-26.89	Vertical
7323.00	45.40	36.47	10.69	41.15	51.41	74.00	-22.59	Vertical
4882.00	47.10	31.58	8.98	40.15	47.51	74.00	-26.49	Horizontal
7323.00	46.11	36.47	10.69	41.15	52.12	74.00	-21.88	Horizontal
Test channel:			Middle		Level:		Average	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	36.72	31.58	8.98	40.15	37.13	54.00	-16.87	Vertical
7323.00	35.81	36.47	10.69	41.15	41.82	54.00	-12.18	Vertical
4882.00	37.49	31.58	8.98	40.15	37.90	54.00	-16.10	Horizontal
7323.00	36.74	36.47	10.69	41.15	42.75	54.00	-11.25	Horizontal

Test channel:			Highest		Level:		Peak	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	46.99	31.69	9.08	40.03	47.73	74.00	-26.27	Vertical
7440.00	48.09	36.60	10.80	41.05	54.44	74.00	-19.56	Vertical
4960.00	47.17	31.69	9.08	40.03	47.91	74.00	-26.09	Horizontal
7440.00	47.13	36.60	10.80	41.05	53.48	74.00	-20.52	Horizontal
Test channel:			Highest		Level:		Average	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	36.58	31.69	9.08	40.03	37.32	54.00	-16.68	Vertical
7440.00	38.52	36.60	10.80	41.05	44.87	54.00	-9.13	Vertical
4960.00	37.26	31.69	9.08	40.03	38.00	54.00	-16.00	Horizontal
7440.00	37.53	36.60	10.80	41.05	43.88	54.00	-10.12	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

6.11 Receiver spurious emissions

Test Requirement:	RSS Gen section 4.10				
Test Method:	RSS Gen section 4.10				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	100kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
			74.0		Peak Value
Test setup:	Below 1GHz				
					
	Above 1GHz				
					

Test Procedure:	7. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 8. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 9. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 10. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 11. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 12. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 5.6 for details
Test mode:	Receiving mode
Test results:	Pass


Remark:

1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.

Measurement data:

Below 1GHz


Horizontal:



Site : 3m chamber
 Condition : ICES-003 CLASS-B 3m VULB9163(30M1G) HORIZONTAL
 EUT : Smart phone
 Model : R55
 Test mode : BT RX mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

	Freq	Read	Antenna	Cable	Preamp	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	32.864	38.09	12.31	0.91	26.58	24.73	40.00	-15.27 QP
2	124.569	44.47	9.80	2.22	29.62	26.87	43.50	-16.63 QP
3	138.387	43.80	8.30	2.38	29.40	25.08	43.50	-18.42 QP
4	249.425	42.83	12.07	2.81	29.60	28.11	46.00	-17.89 QP
5	360.448	36.96	14.43	3.10	29.73	24.76	46.00	-21.24 QP
6	747.483	34.17	19.43	4.35	30.50	27.45	46.00	-18.55 QP

Vertical:



Site : 3m chamber
 Condition : ICES-003 CLASS-B 3m VULB9163 (30M1G) VERTICAL
 EUT : Smart phone
 Model : R55
 Test mode : BT RX mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: A-bomb
 REMARK :

	Freq	ReadAntenna	Cable Preamp		Limit	Over	
	Level	Factor	Loss	Factor	Level	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m
1	30.000	48.91	12.33	0.72	26.27	35.69	40.00
2	35.499	46.44	12.44	1.07	26.85	33.10	40.00
3	57.594	37.77	12.87	1.37	28.99	23.02	40.00
4	115.321	44.45	11.31	2.11	29.78	28.09	43.50
5	145.351	37.54	8.23	2.46	29.30	18.93	43.50
6	747.483	30.98	19.43	4.35	30.50	24.26	46.00

Remark: The emissions above 1GHz only noise floor, so not recorded in report.