EMC TEST REPORT	
TEST REPORT NUMBER	DBN 1614TEL688-A
TEST REPORT DATE	14-Jun-2016
TEST REPORT VERSION	1.0
MANUFACTURER	Cambium Networks
PRODUCT NAME	ePMP2000
PRODUCT MODEL	C050900P031A
CONDITION OF EUT WHEN RECEIVED	Good and in proper working condition
ISSUED TO	Cambium Networks, 3800 Golf Road, Suite 360, Rolling Meadows, IL, USA 60008
ISSUED BY	**TARANG Lab** Wipro Technologies, SJP2, Survey#70,77,78/8A, Dodda Kanelli, Sarjapur road, Bangalore. Karnataka. India - 560 035 Tel: +91-80-30292929 Fax: +91-80-30298200 Email: tarang.planet@wipro.com Web: www.wipro.com

AMENDMENT HISTORY

Amendment Number	Amendment Date	Author of Amendment	Previous Report Version	Previous Report Date
Amendment Details				

TABLE OF CONTENTS

1 TEST REPORT SUMMARY 9

2 GENERAL INFORMATION 10

2.1 ACCREDITATION DETAILS 10
2.2 MEASUREMENT UNCERTAINTY 10

3 INSTRUMENTATION AND CALIBRATION 11

3.1 TEST AND MEASURING EQUIPMENT 11
3.2 EQUIPMENTS USED 11

4 PRODUCT INFORMATION 12

4.1 DESCRIPTION OF THE PRODUCT 12
4.2 SOFTWARE AND FIRMWARE DETAILS 12

5 TEST DETAILS 13

5.1 PRODUCT AND TEST SETUP 13
5.1.1 PRODUCT CONFIGURATION 13
5.1.2 TEST SETUP DETAILS 14
5.1.3 ACCESSORIES 14
5.2 APPLICABLE TESTS 14
5.3 TEST RESULT 15
5.3.1 DUTY CYCLE (X) AND TRANSMISSION DURATION (T) 15
5.3.2 26 dB EMISSION BANDWIDTH 18
5.3.3 99 PERCENT OCCUPIED CHANNEL BANDWIDTH 26
5.3.4 MAXIMUM CONDUCTED OUTPUT POWER 34
5.3.5 POWER SPECTRAL DENSITY 39
5.3.6 TRANSMITTER UNWANTED EMISSIONS (CONDUCTED) 47
5.3.7 BAND EDGE EMISSIONS 105

ANNEXURE I: EUT SOFTWARE SETTINGS 110

ANNEXURE II: ACRONYMS 114

LIST OF FIGURES

Figure 1: Block diagram of the EUT test setup....14
Figure 2: Typical test setup for Conducted RF Test 15
Figure 3: Measured ON time 16
Figure 4: Measured Transmission Period (T) 16
Figure 5: Typical test setup for Conducted RF Test 18
Figure 6: 40 MHz, 17 dBi, Low channel: 26 dB bandwidth measured at Ch.0 – 5495 MHz 19
Figure 7: 40 MHz, 17 dBi, Low channel: 26 dB bandwidth measured at Ch.1– 5495 MHz 19
Figure 8: 40 MHz, 17 dBi, Mid channel: 26 dB bandwidth measured at Ch.0 - 5595 MHz....20
Figure 9: 40 MHz, 17 dBi, Mid channel: 26 dB bandwidth measured at Ch.1 - 5595 MHz....20
Figure 10: 40 MHz, 17 dBi, High channel: 26 dB bandwidth measured at Ch.0 - 5700 MHz 21
Figure 11: 40 MHz, 17 dBi, High channel: 26 dB bandwidth: measured at Ch.1 - 5700 MHz 21
Figure 12: 10 MHz, 17 dBi, Low channel: 26 dB bandwidth measured at Ch.0 - 5485 MHz....22
Figure 13: 10 MHz, 17 dBi, Low channel: 26 dB bandwidth measured at Ch.1 - 5485 MHz....22
Figure 14: 10 MHz, 17 dBi, Mid channel: 26 dB bandwidth measured at Ch.0 - 5595 MHz....23
Figure 15: 10 MHz, 17 dBi, Mid channel: 26 dB bandwidth measured at Ch.1 - 5595 MHz....23
Figure 16: 10 MHz, 17 dBi, High channel: 26 dB bandwidth measured at Ch.0 - 5710 MHz 24
Figure 17: 10 MHz, 17 dBi, High channel: 26 dB bandwidth measured at Ch.1 - 5710 MHz 24
Figure 18 Typical test setup for Conducted RF Test 26
Figure 19: 40 MHz, 17 dBi, Low channel: 99% OBW measured at Ch.0 – 5495 MHz 27
Figure 20: 40 MHz, 17 dBi, Low channel: 99% OBW measured at Ch.1 – 5495 MHz 27
Figure 21: 40 MHz, 17 dBi, Mid channel: 99% OBW measured at Ch.0 – 5595 MHz....28
Figure 22: 40 MHz, 17 dBi, Mid channel: 99% OBW measured at Ch.1 – 5595 MHz....28
Figure 23: 40 MHz, 17 dBi, High channel: 99% OBW measured at Ch.0 – 5700 MHz 29
Figure 24: 40 MHz, 17 dBi, High channel: 99% OBW measured at Ch.1 – 5700 MHz 29
Figure 25: 10 MHz, 17 dBi, Low channel: 99% OBW measured at Ch.0 – 5485 MHz 30
Figure 26: 10 MHz, 17 dBi, Low channel: 99% OBW measured at Ch.1 – 5485 MHz 30
Figure 27: 10 MHz, 17 dBi, Mid channel: 99% OBW measured at Ch.0 – 5595 MHz....31
Figure 28: 10 MHz, 17 dBi, Mid channel: 99% OBW measured at Ch.1 – 5595 MHz....32
Figure 29: 10 MHz, 17 dBi, High channel: 99% OBW measured at Ch.0 – 5710 MHz 32
Figure 30: 10 MHz, 17 dBi, High channel: 99% OBW measured at Ch.1 – 5710 MHz 33
Figure 31: Typical test setup for Conducted RF Test 34
Figure 32: 40 MHz, 17 dBi, Low channel: Maximum conducted output power measured at Ch.0 & Ch.1 – 5495 MHz....35
Figure 33: 40 MHz, 17 dBi, Mid channel: Maximum conducted output power measured at Ch.0 & Ch.1 – 5595 MHz....35
Figure 34: 40 MHz, 17 dBi, High channel: Maximum conducted output power measured at Ch.0 & Ch.1 – 5700 MHz 36
Figure 35: 10 MHz, 17 dBi, Low channel: Maximum conducted output power measured at Ch.0 & Ch.1 – 5485 MHz....36
Figure 36: 10 MHz, 17 dBi, Mid channel: Maximum conducted output power measured at Ch.0 & Ch.1 – 5595 MHz....37
Figure 37: 10 MHz, 17 dBi, High channel: Maximum conducted output power measured at Ch.0 & Ch.1 – 5710 MHz 37
Figure 38: Typical test setup for Conducted Test 39
Figure 39: 40 MHz, 17 dBi, Low channel: Power spectral density measured at Ch. 0 – 5495 MHz....40
Figure 40: 40 MHz, 17 dBi, Low channel: Power spectral density measured at Ch. 1 – 5495 MHz....40
Figure 41: 40 MHz, 17 dBi, Mid channel: Power spectral density measured at Ch. 0 – 5595 MHz 41
Figure 42: 40 MHz, 17 dBi, Mid channel: Power spectral density measured at Ch. 1 – 5595 MHz 41
Figure 43: 40 MHz, 17 dBi, High channel: Power spectral density measured at Ch. 0 – 5700 MHz 42
Figure 44: 40 MHz, 17 dBi, High channel: Power spectral density measured at Ch. 1 – 5700 MHz 42
Figure 45: 10 MHz, 17 dBi, Low channel: Power spectral density measured at Ch. 0 – 5485 MHz....43
Figure 46: 10 MHz, 17 dBi, Low channel: Power spectral density measured at Ch. 1 – 5485 MHz....43
Figure 47: 10 MHz, 17 dBi, Mid channel: Power spectral density measured at Ch. 0– 5595 MHz 44
Figure 48: 10 MHz, 17 dBi, Mid channel: Power spectral density measured at Ch. 1 – 5595 MHz 44
Figure 49: 10 MHz, 17 dBi, High channel: Power spectral density measured at Ch. 0 – 5710 MHz 45
Figure 50: 10 MHz, 17 dBi, High channel: Power spectral density measured at Ch. 1 – 5710 MHz 45
Figure 51: Typical test setup for Conducted Test 48
Figure 52: 40 MHz, 17 dBi, Low channel: Peak emission from 9 kHz to 150 kHz at Ch. 0 – 5495 MHz 49

Figure 53: 40 MHz, 17 dBi, Low channel: Peak emission from 150 kHz to 30 MHz at Ch. 0 –5495 MHz....49
Figure 54: 40 MHz, 17 dBi, Low channel: Peak emission from 30 MHz to 1 GHz at Ch. 0 –5495 MHz....50
Figure 55: 40 MHz, 17 dBi, Low channel: Average emission from 1 GHz to 18 GHz at Ch. 0 –5495 MHz....50
Figure 56: 40 MHz, 17 dBi, Low channel: Average emission from 18 GHz to 26.5 GHz at Ch. 0 –5495 MHz....51
Figure 57: 40 MHz, 17 dBi, Low channel: Average emission from 26.5 GHz to 40 GHz at Ch. 0 –5495 MHz....51
Figure 58: 40 MHz, 17 dBi, Low channel: Peak emission from 1 GHz to 18 GHz at Ch. 0 –5495 MHz....52
Figure 59: 40 MHz, 17 dBi, Low channel: Peak emission from 18 GHz to 26.5 GHz at Ch. 0 –5495 MHz....52
Figure 60: 40 MHz, 17 dBi, Low channel: Peak emission from 26.5 GHz to 40 GHz at Ch. 0 –5495 MHz....53
Figure 61: 40 MHz, 17 dBi, Low channel: Peak emission from 9 kHz to 150 kHz at Ch. 1 –5495 MHz....53
Figure 62: 40 MHz, 17 dBi, Low channel: Peak emission from 150 kHz to 30 MHz at Ch. 1 –5495 MHz....54
Figure 63: 40 MHz, 17 dBi, Low channel: Peak emission from 30 MHz to 1 GHz at Ch. 1 –5495 MHz....54
Figure 64: 40 MHz, 17 dBi, Low channel: Average emission from 1 GHz to 18 GHz at Ch. 1 –5495 MHz....55
Figure 65: 40 MHz, 17 dBi, Low channel: Average emission from 18 GHz to 26.5 GHz at Ch. 1 –5495 MHz....55
Figure 66: 40 MHz, 17 dBi, Low channel: Average emission from 26.5 GHz to 40 GHz at Ch. 1 –5495 MHz....56
Figure 67: 40 MHz, 17 dBi, Low channel: Peak emission from 1 GHz to 18 GHz at Ch. 1 –5495 MHz....56
Figure 68: 40 MHz, 17 dBi, Low channel: Peak emission from 18 GHz to 26.5 GHz at Ch. 1 –5495 MHz....57
Figure 69: 40 MHz, 17 dBi, Low channel: Peak emission from 26.5 GHz to 40 GHz at Ch. 1 –5495 MHz....57
Figure 70: 40 MHz, 17 dBi, Mid channel: Peak emission from 9 kHz to 150 kHz at Ch. 0 –5595 MHz....58
Figure 71: 40 MHz, 17 dBi, Mid channel: Peak emission from 150 kHz to 30 MHz at Ch. 0 –5595MHz....58
Figure 72: 40 MHz, 17 dBi, Mid channel: Peak emission from 30 MHz to 1 GHz at Ch. 0 –5595 MHz....59
Figure 73: 40 MHz, 17 dBi, Mid channel: Average emission from 1 GHz to 18 GHz at Ch. 0 –5595 MHz....59
Figure 74: 40 MHz, 17 dBi, Mid channel: Average emission from 18 GHz to 26.5 GHz at Ch. 0 –5595 MHz....60
Figure 75: 40 MHz, 17 dBi, Mid channel: Average emission from 26.5 GHz to 40 GHz at Ch. 0 –5595 MHz....60
Figure 76: 40 MHz, 17 dBi, Mid channel: Peak emission from 1 GHz to 18 GHz at Ch. 0 –5595 MHz....61
Figure 77: 40 MHz, 17 dBi, Mid channel: Peak emission from 18 GHz to 26.5 GHz at Ch. 0 –5595 MHz....61
Figure 78: 40 MHz, 17 dBi, Mid channel: Peak emission from 26.5 GHz to 40 GHz at Ch. 0 –5595 MHz....62
Figure 79: 40 MHz, 17 dBi, Mid channel: Peak emission from 9 kHz to 150 kHz at Ch. 1 –5595 MHz....62
Figure 80: 40 MHz, 17 dBi, Mid channel: Peak emission from 150 kHz to 30 MHz at Ch. 1 –5595 MHz....63
Figure 81: 40 MHz, 17 dBi, Mid channel: Peak emission from 30 MHz to 1 GHz at Ch. 1–5595 MHz....63
Figure 82: 40 MHz, 17 dBi, Mid channel: Average emission from 1 GHz to 18 GHz at Ch. 1 –5595 MHz....64
Figure 83: 40 MHz, 17 dBi, Mid channel: Average emission from 18 GHz to 26.5 GHz at Ch. 1 –5595 MHz....64
Figure 84: 40 MHz, 17 dBi, Mid channel: Average emission from 26.5 GHz to 40 GHz at Ch. 1 –5595 MHz....65
Figure 85: 40 MHz, 17 dBi, Mid channel: Peak emission from 1 GHz to 18 GHz at Ch. 1 –5595 MHz....65
Figure 86: 40 MHz, 17 dBi, Mid channel: Peak emission from 18 GHz to 26.5 GHz at Ch. 1 –5595 MHz....66
Figure 87: 40 MHz, 17 dBi, Mid channel: Peak emission from 26.5 GHz to 40 GHz at Ch. 1 –5595 MHz....66
Figure 88: 40 MHz, 17 dBi, High channel: Peak emission from 9 kHz to 150 kHz at Ch. 0 –5700 MHz....67
Figure 89: 40 MHz, 17 dBi, High channel: Peak emission from 150 kHz to 30 MHz at Ch. 0 –5700 MHz....67
Figure 90: 40 MHz, 17 dBi, High channel: Peak emission from 30 MHz to 1 GHz at Ch. 0 –5700 MHz....68
Figure 91: 40 MHz, 17 dBi, High channel: Average emission from 1 GHz to 18 GHz at Ch. 0 –5700 MHz....68
Figure 92: 40 MHz, 17 dBi, High channel: Average emission from 18 GHz to 26.5 GHz at Ch. 0 –5700 MHz....69
Figure 93: 40 MHz, 17 dBi, High channel: Average emission from 26.5 GHz to 40 GHz at Ch. 0 –5700 MHz....69
Figure 94: 40 MHz, 17 dBi, High channel: Peak emission from 1 GHz to 18 GHz at Ch. 0 –5700 MHz....70
Figure 95: 40 MHz, 17 dBi, High channel: Peak emission from 18 GHz to 26.5 GHz at Ch. 0 –5700 MHz....70
Figure 96: 40 MHz, 17 dBi, High channel: Peak emission from 26.5 GHz to 40 GHz at Ch. 0 –5700 MHz....71
Figure 97: 40 MHz, 17 dBi, High channel: Peak emission from 9 kHz to 150 kHz at Ch. 1 –5700 MHz....71
Figure 98: 40 MHz, 17 dBi, High channel: Peak emission from 150 kHz to 30 MHz at Ch. 1 –5700 MHz....72
Figure 99: 40 MHz, 17 dBi, High channel: Peak emission from 30 MHz to 1 GHz at Ch. 1 –5700 MHz....72
Figure 100: 40 MHz, 17 dBi, High channel: Average emission from 1 GHz to 18 GHz at Ch. 1 –5700 MHz....73
Figure 101: 40 MHz, 17 dBi, High channel: Average emission from 18 GHz to 26.5 GHz at Ch. 1 –5700 MHz....73
Figure 102: 40 MHz, 17 dBi, High channel: Average emission from 26.5 GHz to 40 GHz at Ch. 1 –5700 MHz....74
Figure 103: 40 MHz, 17 dBi, High channel: Peak emission from 1 GHz to 18 GHz at Ch. 1 –5700 MHz....74
Figure 104: 40 MHz, 17 dBi, High channel: Peak emission from 18 GHz to 26.5 GHz at Ch. 1 –5700 MHz....75
Figure 105: 40 MHz, 17 dBi, High channel: Peak emission from 26.5 GHz to 40 GHz at Ch. 1 –5700 MHz....75

Figure 106: 10 MHz, 17 dBi, Low channel: Peak emission from 9 kHz to 150 kHz at Ch. 0 –5485 MHz 76
Figure 107: 10 MHz, 17 dBi, Low channel: Peak emission from 150 kHz to 30 MHz at Ch. 0 –5485 MHz....76
Figure 108: 10 MHz, 17 dBi, Low channel: Peak emission from 30 MHz to 1 GHz at Ch. 0 –5485 MHz....77
Figure 109: 10 MHz, 17 dBi, Low channel: Average emission from 1 GHz to 18 GHz at Ch. 0 –5485 MHz....77
Figure 110: 10 MHz, 17 dBi, Low channel: Average emission from 18 GHz to 26.5 GHz at Ch. 0 –5485 MHz....78
Figure 111: 10 MHz, 17 dBi, Low channel: Average emission from 26.5 GHz to 40 GHz at Ch. 0 –5485 MHz....78
Figure 112: 10 MHz, 17 dBi, Low channel: Peak emission from 1 GHz to 18 GHz at Ch. 0 –5485 MHz 79
Figure 113: 10 MHz, 17 dBi, Low channel: Peak emission from 18 GHz to 26.5 GHz at Ch. 0 –5485 MHz 79
Figure 114: 10 MHz, 17 dBi, Low channel: Peak emission from 26.5 GHz to 40 GHz at Ch. 0 –5485 MHz 80
Figure 115: 10 MHz, 17 dBi, Low channel: Peak emission from 9 kHz to 150 kHz at Ch. 1 –5485 MHz 80
Figure 116: 10 MHz, 17 dBi, Low channel: Peak emission from 150 kHz to 30 MHz at Ch. 1 –5485 MHz....81
Figure 117: 10 MHz, 17 dBi, Low channel: Peak emission from 30 MHz to 1 GHz at Ch. 1 –5485 MHz....81
Figure 118: 10 MHz, 17 dBi, Low channel: Average emission from 1 GHz to 18 GHz at Ch. 1 –5485 MHz....82
Figure 119: 10 MHz, 17 dBi, Low channel: Average emission from 18 GHz to 26.5 GHz at Ch. 1 –5485 MHz....82
Figure 120: 10 MHz, 17 dBi, Low channel: Average emission from 26.5 GHz to 40 GHz at Ch. 1 –5485 MHz....83
Figure 121: 10 MHz, 17 dBi, Low channel: Peak emission from 1 GHz to 18 GHz at Ch. 1 –5485 MHz 83
Figure 122: 10 MHz, 17 dBi, Low channel: Peak emission from 18 GHz to 26.5 GHz at Ch. 1 –5485 MHz 84
Figure 123: 10 MHz, 17 dBi, Low channel: Peak emission from 26.5 GHz to 40 GHz at Ch. 1 –5485 MHz 84
Figure 124: 10 MHz, 17 dBi, Mid channel: Peak emission from 9 kHz to 150 kHz at Ch. 0 –5595 MHz....85
Figure 125: 10 MHz, 17 dBi, Mid channel: Peak emission from 150 kHz to 30 MHz at Ch. 0 –5595 MHz 85
Figure 126: 10 MHz, 17 dBi, Mid channel: Peak emission from 30 MHz to 1 GHz at Ch. 0 –5595 MHz 86
Figure 127: 10 MHz, 17 dBi, Mid channel: Average emission from 1 GHz to 18 GHz at Ch. 0 –5595 MHz 86
Figure 128: 10 MHz, 17 dBi, Mid channel: Average emission from 18 GHz to 26.5 GHz at Ch. 0 –5595 MHz 87
Figure 129: 10 MHz, 17 dBi, Mid channel: Average emission from 26.5 GHz to 40 GHz at Ch. 0 –5595 MHz 87
Figure 130: 10 MHz, 17 dBi, Mid channel: Peak emission from 1 GHz to 18 GHz at Ch. 0 –5595 MHz 88
Figure 131: 10 MHz, 17 dBi, Mid channel: Peak emission from 18 GHz to 26.5 GHz at Ch. 0 –5595 MHz 88
Figure 132: 10 MHz, 17 dBi, Mid channel: Peak emission from 26.5 GHz to 40 GHz at Ch. 0 –5595 MHz 89
Figure 133: 10 MHz, 17 dBi, Mid channel: Peak emission from 9 kHz to 150 kHz at Ch. 1 –5595 MHz....89
Figure 134: 10 MHz, 17 dBi, Mid channel: Peak emission from 150 kHz to 30 MHz at Ch. 1 –5595 MHz 90
Figure 135: 10 MHz, 17 dBi, Mid channel: Peak emission from 30 MHz to 1 GHz at Ch. 1 –5595 MHz 90
Figure 136: 10 MHz, 17 dBi, Mid channel: Average emission from 1 GHz to 18 GHz at Ch. 1 –5595 MHz 91
Figure 137: 10 MHz, 17 dBi, Mid channel: Average emission from 18 GHz to 26.5 GHz at Ch. 1 –5595 MHz 91
Figure 138: 10 MHz, 17 dBi, Mid channel: Average emission from 26.5 GHz to 40 GHz at Ch. 1 –5595 MHz 92
Figure 139: 10 MHz, 17 dBi, Mid channel: Peak emission from 1 GHz to 18 GHz at Ch. 1 –5595 MHz 92
Figure 140: 10 MHz, 17 dBi, Mid channel: Peak emission from 18 GHz to 26.5 GHz at Ch. 1 –5595 MHz 93
Figure 141: 10 MHz, 17 dBi, Mid channel: Peak emission from 26.5 GHz to 40 GHz at Ch. 1 –5595 MHz 93
Figure 142: 10 MHz, 17 dBi, High channel: Peak emission from 9 kHz to 150 kHz at Ch. 0 –5710 MHz....94
Figure 143: 10 MHz, 17 dBi, High channel: Peak emission from 150 kHz to 30 MHz at Ch. 0 –5710 MHz....94
Figure 144: 10 MHz, 17 dBi, High channel: Peak emission from 30 MHz to 1 GHz at Ch. 0 –5710 MHz....95
Figure 145: 10 MHz, 17 dBi, High channel: Average emission from 1 GHz to 18 GHz at Ch. 0 –5710 MHz....95
Figure 146: 10 MHz, 17 dBi, High channel: Average emission from 18 GHz to 26.5 GHz at Ch. 0 –5710 MHz....96
Figure 147: 10 MHz, 17 dBi, High channel: Average emission from 26.5 GHz to 40 GHz at Ch. 0 –5710 MHz....96
Figure 148: 10 MHz, 17 dBi, High channel: Peak emission from 1 GHz to 18 GHz at Ch. 0 –5710 MHz....97
Figure 149: 10 MHz, 17 dBi, High channel: Peak emission from 18 GHz to 26.5 GHz at Ch. 0 –5710 MHz....97
Figure 150: 10 MHz, 17 dBi, High channel: Peak emission from 26.5 GHz to 40 GHz at Ch. 0 –5710 MHz....98
Figure 151: 10 MHz, 17 dBi, High channel: Peak emission from 9 kHz to 150 kHz at Ch. 1 –5710 MHz....98
Figure 152: 10 MHz, 17 dBi, High channel: Peak emission from 150 kHz to 30 MHz at Ch. 1 –5710 MHz....99
Figure 153: 10 MHz, 17 dBi, High channel: Peak emission from 30 MHz to 1 GHz at Ch. 1 –5710 MHz....99
Figure 154: 10 MHz, 17 dBi, High channel: Average emission from 1 GHz to 18 GHz at Ch. 1 –5710 MHz....100
Figure 155: 10 MHz, 17 dBi, High channel: Average emission from 18 GHz to 26.5 GHz at Ch. 1 –5710 MHz....100
Figure 156: 10 MHz, 17 dBi, High channel: Average emission from 26.5 GHz to 40 GHz at Ch. 1 –5710 MHz....101
Figure 157: 10 MHz, 17 dBi, High channel: Peak emission from 1 GHz to 18 GHz at Ch. 1 –5710 MHz....101
Figure 158: 10 MHz, 17 dBi, High channel: Peak emission from 18 GHz to 26.5 GHz at Ch. 1 –5710 MHz....102

Figure 159: 10 MHz, 17 dBi, High channel: Peak emission from 26.5 GHz to 40 GHz at Ch. 1 –5710 MHz.....102
Figure 160: Typical test setup for Conducted Test 105
Figure 161: 40 MHz, 17 dBi, Low channel: Band edge measured at Ch.0 –5495 MHz.....106
Figure 162: 40 MHz, 17 dBi, Low channel: Band edge measured at Ch.1 –5495 MHz.....106
Figure 163: 40 MHz, 17 dBi, High channel: Band edge measured at Ch.0 –5700 MHz 107
Figure 164: 40 MHz, 17 dBi, High channel: Band edge measured at Ch.1 –5700 MHz 107
Figure 165: 10 MHz, 17 dBi, Low channel: Band edge measured at Ch.0 –5485 MHz.....108
Figure 166: 10 MHz, 17 dBi, Low channel: Band edge measured at Ch.1 –5485 MHz.....108
Figure 167: 10 MHz, 17 dBi, High channel: Band edge measured at Ch.0 –5710 MHz 109
Figure 168: 10 MHz, 17 dBi, High channel: Band edge measured at Ch.1 –5710 MHz 109
Figure 169: tftpd32 application screenshot 110
Figure 170: tftpd32 application initialization root_ screenshot.....110
Figure 171: Tera term application screenshot 111
Figure 172: Tera term application Login screenshot.....111
Figure 173: Initializing EUT screenshot 112
Figure 174: Atheros Radio Test GUI screenshot-1 112
Figure 175: Atheros Radio Test GUI screenshot -2 113

LIST OF TABLES

Table 1: List of equipment used for Conducted RF Test 11
Table 2: EUT details 12
Table 3: List of cables connected to the EUT 12
Table 4: Result for 26 dB bandwidth in both 40 MHz and 10 MHz modulation bandwidth 25
Table 5: Result for 99% Occupied bandwidth in both 40 MHz and 10 MHz modulation bandwidth 33
Table 6: Max RF out power for 17 dBi configuration 38
Table 7: Consolidated values across channels and final power for 17 dBi configuration 38
Table 8: Result of PSD for 17 dBi configuration for both 40 MHz and 10 MHz modulation bandwidth 46
Table 9: Unwanted emission Limit 47
Table 10: General Field strength limit below 30 MHz 47
Table 11: General Field strength limit above 30 MHz 47
Table 12: Result for 17 dBi configuration – 40 MHz modulation bandwidth 103
Table 13: Result for 17 dBi configuration - 10 MHz modulation bandwidth 104

1 TEST REPORT SUMMARY

Applicant	Cambium Networks
Manufacturer	Cambium Networks
Product Name	ePMP2000
Product Model	C050900P031A
Product Serial Number	000456D1846A
Date of Test	08th Feb 2016 & 28th Apr 2016
Venue of Test	Tarang Lab

Applicable Standard	Description	Results
47 CFR Part 15 Feb 2016	Duty cycle and Transmission Duration	NA
	§15.403 (h) (i)- 26 dB Bandwidth measurement	NA
	99 Percent Occupied Bandwidth	NA
	§15.407 (a) (2)- Maximum conducted Output Power	PASS
	§15.407 (a) (2)- Power Spectral Density	PASS
	§15.407 b (3) –Transmission Unwanted emission (Conducted)	PASS
	§15.407 b (3) - Unwanted Emissions levels-Conducted Band edge	PASS

ePMP2000 was tested by Tarang Lab as per the standards that are listed in the table above. Based on the observations during the test and interpretations by Tarang lab, results have been indicated. The test results produced in this report shall apply only to the above sample that has been tested under the specific conditions and modes of testing as described in the report. Other similar equipment may not necessarily reproduce same result due to production tolerances and measurement uncertainties. Any measurement uncertainties listed in this report are for information purpose only.

The results shall stand invalid, in case there are any modifications / additions / removals to the hardware or software or end use atmosphere to the product tested. This report shall not be modified or in any way revised unless it is expressly permitted and endorsed by Tarang lab, through a duly authorized representative. Particulars on Manufacturer / Supplier / Product configuration / performance criteria, given in this report, are based on the information given by the customer, along with test request. Tarang does not assume any responsibility for the correctness of such information for the above mentioned equipment under test.

Customer acknowledges that this is a test report and not a certificate to gain market access for the product. To gain market access, Customer needs appropriate clearance from the Government or authorized agency for the target market. For markets that allow self-declaration, customer needs to follow the procedure defined by the target market.

Prepared by	Reviewed by	Approved by
Suresh G N	Arun Kumar .N.C	Satheesh I
EMI/EMC Test Engineer	**Lead EMI/EMC Test Engineer**	**Technical Manager**

2 GENERAL INFORMATION

2.1 ACCREDITATION DETAILS

Following are the accreditation and listing details for Tarang.

Accreditation / Listing body	Registration / Company / Certificate Number
NABL, India	Certificate No: T-1533, T-1534 http://www.nabl-india.org/
FCC (Federal Communications Commission)	Registration Number: 799247 http://www.fcc.gov/
IC (Industry Canada)	Company Number: 9023A-1 http://www.ic.gc.ca

2.2 MEASUREMENT UNCERTAINTY

NA

3 INSTRUMENTATION AND CALIBRATION

3.1 TEST AND MEASURING EQUIPMENT

The list of following measuring equipment used for this testing conforms to the applicable standards. Performance of all test and measuring equipment including any accessories are checked periodically to ensure accuracy.

3.2 EQUIPMENTS USED

Name of Equipment	Manufacturer	Model No	Serial No	Calibration Due
Spectrum Analyzer	Keysight Technologies	N9020A	MY54420183	05th Jul 2016
X series USB Peak and Average Power sensor	Keysight Technologies	U2021XA	MY55050001	05th Jul 2016
X series USB Peak and Average Power sensor	Keysight Technologies	U2021XA	MY55050002	05th Jul 2016
EMI Test Receiver	R&S	ESIB40	100306	21st Jan 2017 / 04th Jul 2016

Table 1: List of equipment used for Conducted RF Test

4 PRODUCT INFORMATION

4.1 DESCRIPTION OF THE PRODUCT

EUT is a point to point & point to multipoint fixed outdoor Transceiver with the following defined channels.

40 MHz channel for 17 dBi antenna	**10 MHz channel for 17 dBi antenna**
Low – 5495 MHz	Low – 5485 MHz
Mid - 5595 MHz	Mid – 5595 MHz
High - 5700 MHz	High – 5710 MHz

Product	ePMP2000
Model Number	C050900P031A
Serial Number	000456D1846A
Product Category / Type of Equipment	ITE
EUT Operating Voltage	120 V AC
EUT Operating frequency range	60 Hz
Max EUT Operating Current	<1 A

Table 2: EUT details

Cable No.	**Cable Name**	**Cable Length**	**Power / Interconnection cable**	**Shielded / Unshielded**
Cable - 1	Power cable	0.8 meter	Power	Unshielded
Cable - 2	Ethernet Cable	1.5 meter	Interconnection	Unshielded
Cable - 3	Ethernet Cable	3.0 meter	Interconnection	Unshielded

Table 3: List of cables connected to the EUT

4.2 SOFTWARE AND FIRMWARE DETAILS

Atheros Radio Test 2 (ART2-GUI) Version 2.3

5 TEST DETAILS

5.1 PRODUCT AND TEST SETUP

5.1.1 PRODUCT CONFIGURATION

The EUT was powered through AC power supply (120 V AC / 60 Hz). The EUT was connected to Ethernet switch by using RJ45 cable. Figure 1 shows the product configuration during the tests. POE module was used during the test to power ON the EUT.

The 5.4 GHz ePMP Integrated Radio was configured with test software and configured to have the following settings during the course of testing:

- 40 MHz modulation bandwidth for low, mid & high channels
  - Rate - HT40,
  - 54 Mbps OFDM, MCS15 / 270 Mbps
  - Tx Power is 10.5 dBm Tx99 for 17 dBi antenna configuration-Low channel
  - Tx Power is 11.5 dBm Tx99 for 17 dBi antenna configuration-Mid channel
  - Tx Power is 12 dBm Tx99 for 17 dBi antenna configuration-High channel

- 10 MHz modulation bandwidth for low, mid & high channels
  - Rate – Legacy,
  - 54 Mbps OFDM, MCS15 / 130 Mbps
  - Tx Power is 9 dBm Tx99 for 17 dBi antenna configuration-Low channel
  - Tx Power is 9 dBm Tx99 for 17 dBi antenna configuration-Mid channel
  - Tx Power is 9 dBm Tx99 for 17 dBi antenna configuration-High channel

The unit was continuously monitored for transmission using an auxiliary antenna during the radiated tests.

5.1.2 TEST SETUP DETAILS



Figure 1: Block diagram of the EUT test setup

5.1.3 ACCESSORIES

Name of the Equipment	Manufacturer	Model Number	Serial Number
17 dBi Antenna Beam steer- Rx	Cambium Networks	C050900D020A	NA
17 dBi Antenna sector- Tx	Cambium Networks	C050900D021A	NA
Power Supply	Cambium Networks	NET P30 56	031-326-6719
Switching Power Supply Gigabit Compatible	Cambium Networks	NET-P30-56	N000000L034A

5.2 APPLICABLE TESTS

Applicable Standard	Description	Test level / Test Voltage	Applicability
47 CFR Part 15, Feb 2016	Duty Cycle and transmission duration	NA	Antenna port
	26 dB Bandwidth measurement	NA	Antenna port
	99 Percent Occupied Bandwidth	NA	Antenna port
	Maximum Conducted Output Power	≤ 250 mW	Antenna port
	Power Spectral Density	Power spectral density should be ≤ 11 dBm in 1 MHz bandwidth	Antenna port
	Transmitter Unwanted emission (Conducted)	9 kHz to 40 GHz	Antenna port
	Unwanted Emission(Band edge)	EIRP of < -27dBm/MHz	Antenna port

5.3 TEST RESULT

5.3.1 DUTY CYCLE (X) AND TRANSMISSION DURATION (T)

5.3.1.1 TEST SPECIFICATION

Test Standard	47 CFR, Part 15 Feb 2016
Test Procedure	789033 D2 General U-NII Test Procedures New Rule V01r01
Resolution Bandwidth	8 MHz
Video Bandwidth	8 MHz
Sweep Time	Auto
Attenuation	Auto
Test Mode	Conducted
Detector	RMS
Input Voltage	120 V AC
Input Frequency	60 Hz
Temperature	24.0 °C
Humidity	55.0 %
Tested By	Dikshit Raviteja / Suresh.G.N
Test Date	8th Feb 2016

5.3.1.2 LIMITS

NA

5.3.1.3 TEST SETUP

Figure 2: Typical test setup for Conducted RF Test

5.3.1.4 TEST PROCEDURE

The Conducted test was performed using the Spectrum analyzer. Measurements were done as per section II B of **"789033 D2 General U-NII Test Procedures New Rule V01r01".** The RF output of the EUT was connected to the input port of Spectrum analyzer using an attenuator. The graph and data captured from spectrum analyzer and recorded.

5.3.1.5 MEASUREMENT GRAPHS / DATA



Figure 3: Measured ON time



Figure 4: Measured Transmission Period (T)

5.3.1.6 RESULT

The Duty cycle and Transmission duration data were recorded.

Mode	ON time (µsec)	T (µsec)	Duty Cycle X (Linear)	Duty Cycle (%)	50/T Minimum RBW and VBW (kHz)
Tx ON	485.3	589.9	0.822	82.2%	847.6

*Note: Duty cycle = (ON time / Period)*100*

5.3.2 26 DB EMISSION BANDWIDTH

5.3.2.1 TEST SPECIFICATION

Test Standard	47 CFR, Part 15 Feb 2016
Test Procedure	789033 D2 General U-NII Test Procedures New Rule V01r01
Resolution Bandwidth	100 kHz, 300 kHz
Video Bandwidth	300 kHz, 1 MHz
Sweep Time	Auto
Attenuation	Auto
Test Mode	Conducted
Detector	Peak
Input Voltage	120 V AC
Input Frequency	60 Hz
Temperature	24.0 °C
Humidity	55.0 %
Tested By	Dikshit Raviteja / Suresh.G.N
Test Date	08th Feb 2016

5.3.2.2 LIMITS

Standard	Reference section	Frequency range	Limit
47 CFR, Part 15 Feb 2016	§15.403 (h) (i)	5470 MHz to 5725 MHz	NA

5.3.2.3 TEST SETUP

Figure 5: Typical test setup for Conducted RF Test

5.3.2.4 TEST PROCEDURE

The Conducted test was performed using the Spectrum analyzer. Measurements were done as per the **"789033 D2 General U-NII Test Procedures New Rule V01r01".** The RF output of the EUT was connected to the input port of Spectrum analyzer using an attenuator. The graph and data captured from spectrum analyzer and recorded.

5.3.2.5 MEASUREMENT GRAPHS / DATA



Figure 6: 40 MHz, 17 dBi, Low channel: 26 dB bandwidth measured at Ch.0 – 5495 MHz



Figure 7: 40 MHz, 17 dBi, Low channel: 26 dB bandwidth measured at Ch.1– 5495 MHz



Figure 8: 40 MHz, 17 dBi, Mid channel: 26 dB bandwidth measured at Ch.0 - 5595 MHz



Figure 9: 40 MHz, 17 dBi, Mid channel: 26 dB bandwidth measured at Ch.1 - 5595 MHz



Figure 10: 40 MHz, 17 dBi, High channel: 26 dB bandwidth measured at Ch.0 - 5700 MHz



Figure 11: 40 MHz, 17 dBi, High channel: 26 dB bandwidth: measured at Ch.1 - 5700 MHz



Figure 12: 10 MHz, 17 dBi, Low channel: 26 dB bandwidth measured at Ch.0 - 5485 MHz



Figure 13: 10 MHz, 17 dBi, Low channel: 26 dB bandwidth measured at Ch.1 - 5485 MHz



Figure 14: 10 MHz, 17 dBi, Mid channel: 26 dB bandwidth measured at Ch.0 - 5595 MHz



Figure 15: 10 MHz, 17 dBi, Mid channel: 26 dB bandwidth measured at Ch.1 - 5595 MHz



Figure 16: 10 MHz, 17 dBi, High channel: 26 dB bandwidth measured at Ch.0 - 5710 MHz



Figure 17: 10 MHz, 17 dBi, High channel: 26 dB bandwidth measured at Ch.1 - 5710 MHz

5.3.2.6 RESULT

The 26 dB Emission bandwidth is measured for all channels in both 40 MHz & 10 MHz modulation bandwidth. Refer below table for consolidated data.

Configuration	Modulation Bandwidth (MHz)	Antenna path	Channel Frequency (MHz)	Recorded value (MHz)
17 dBi Antenna Condition	40	Ch. 0	5495	43.03
	40	Ch. 0	5595	42.75
	40	Ch. 0	5700	43.01
	40	Ch. 1	5495	44.03
	40	Ch. 1	5595	43.40
	40	Ch. 1	5700	43.10
	10	Ch. 0	5485	10.10
	10	Ch. 0	5595	9.546
	10	Ch. 0	5710	9.447
	10	Ch. 1	5485	9.530
	10	Ch. 1	5595	9.894
	10	Ch. 1	5710	10.16

Table 4: Result for 26 dB bandwidth in both 40 MHz and 10 MHz modulation bandwidth

5.3.3 99 PERCENT OCCUPIED CHANNEL BANDWIDTH

5.3.3.1 TEST SPECIFICATION

Test Standard	47 CFR, Part 15 Feb 2016
Test Procedure	789033 D2 General U-NII Test Procedures New Rule V01r01
Resolution Bandwidth	100 kHz, 300 kHz
Video Bandwidth	300 kHz, 1 MHz
Sweep Time	Auto
Attenuation	Auto
Test Mode	Conducted
Detector	Peak
Input Voltage	120 V AC
Input Frequency	60 Hz
Temperature	24.0 °C
Humidity	55.0 %
Tested By	Dikshit Raviteja
Test Date	8th Feb 2016

5.3.3.2 LIMITS

Standard	Reference section	Frequency range	Limit
47 CFR, Part 15 Feb 2016	NA	5470 MHz to 5725 MHz	NA

5.3.3.3 TEST SETUP



Figure 18 Typical test setup for Conducted RF Test

5.3.3.4 TEST PROCEDURE

The Conducted test was performed using the Spectrum analyzer. Measurements were done as per the **"789033 D2 General U-NII Test Procedures New Rule V01r01".** The RF output of the EUT was connected to the input port of Spectrum analyzer using an attenuator. The graph and data captured from spectrum analyzer and recorded.

5.3.3.5 MEASUREMENT GRAPHS / DATA



Figure 19: 40 MHz, 17 dBi, Low channel: 99% OBW measured at Ch.0 – 5495 MHz



Figure 20: 40 MHz, 17 dBi, Low channel: 99% OBW measured at Ch.1 – 5495 MHz



Figure 21: 40 MHz, 17 dBi, Mid channel: 99% OBW measured at Ch.0 – 5595 MHz



Figure 22: 40 MHz, 17 dBi, Mid channel: 99% OBW measured at Ch.1 – 5595 MHz



Figure 23: 40 MHz, 17 dBi, High channel: 99% OBW measured at Ch.0 – 5700 MHz



Figure 24: 40 MHz, 17 dBi, High channel: 99% OBW measured at Ch.1 – 5700 MHz



Figure 25: 10 MHz, 17 dBi, Low channel: 99% OBW measured at Ch.0 – 5485 MHz



Figure 26: 10 MHz, 17 dBi, Low channel: 99% OBW measured at Ch.1 – 5485 MHz



Figure 27: 10 MHz, 17 dBi, Mid channel: 99% OBW measured at Ch.0 – 5595 MHz



Figure 28: 10 MHz, 17 dBi, Mid channel: 99% OBW measured at Ch.1 – 5595 MHz



Figure 29: 10 MHz, 17 dBi, High channel: 99% OBW measured at Ch.0 – 5710 MHz



Figure 30: 10 MHz, 17 dBi, High channel: 99% OBW measured at Ch.1 – 5710 MHz

5.3.3.6 RESULT

The 99% Occupied Channel Bandwidth for all channels in both 40 MHz & 10 MHz Modulation Bandwidths has been measured and tabulated in below table.

Configuration	Modulation Bandwidth (MHz)	Antenna path	Channel Frequency (MHz)	Recorded value (MHz)
17 dBi Antenna Condition	40	Ch. 0	5495	36.283
	40	Ch. 0	5595	36.260
	40	Ch. 0	5700	36.185
	40	Ch. 1	5495	36.302
	40	Ch. 1	5595	36.296
	40	Ch. 1	5700	36.292
	10	Ch. 0	5485	8.259
	10	Ch. 0	5595	8.238
	10	Ch. 0	5710	8.254
	10	Ch. 1	5485	8.254
	10	Ch. 1	5595	8.266
	10	Ch. 1	5710	8.254

Table 5: Result for 99% Occupied bandwidth in both 40 MHz and 10 MHz modulation bandwidth

5.3.4 MAXIMUM CONDUCTED OUTPUT POWER

5.3.4.1 TEST SPECIFICATION

Test Standard	47 CFR, Part 15 Feb 2016
Test Procedure	789033 D2 General U-NII Test Procedures New Rule V01r01
Test Mode	Conducted
Detector	Average
Input Voltage	120 V AC
Input Frequency	60 Hz
Temperature	24.0 °C
Humidity	55.0 %
Tested By	Dikshit Raviteja / Suresh GN
Test Date	08th Feb 2016

5.3.4.2 LIMITS

Standard	Reference section	Frequency range	Limit
47 CFR, Part 15 Feb 2016	§15.407 a (2)	5470 MHz to 5725 MHz	max conducted Tx power ≤ 23.97 dBm (250 mW) max Limit (for 17 dBi antenna) : ≤ 12.97 dBm

5.3.4.3 TEST SETUP

Figure 31: Typical test setup for Conducted RF Test

5.3.4.4 TEST PROCEDURE

The Conducted test was performed using the power meter. Measurements were done as per Section II E 3.b (Method PM-G) of KDB **"789033 DO2 General UNII Test Procedures New Rules v01r01".** The RF output of the EUT was connected to the input port of Power meter using an attenuator. The graph and data captured from power meter and compared with the limits specified in the standard.

5.3.4.5 MEASUREMENT GRAPHS / DATA

Figure 32: 40 MHz, 17 dBi, Low channel: Maximum conducted output power measured at Ch.0 & Ch.1 – 5495 MHz

Figure 33: 40 MHz, 17 dBi, Mid channel: Maximum conducted output power measured at Ch.0 & Ch.1 – 5595 MHz

Figure 34: 40 MHz, 17 dBi, High channel: Maximum conducted output power measured at Ch.0 & Ch.1 – 5700 MHz

Figure 35: 10 MHz, 17 dBi, Low channel: Maximum conducted output power measured at Ch.0 & Ch.1 – 5485 MHz



Figure 36: 10 MHz, 17 dBi, Mid channel: Maximum conducted output power measured at Ch.0 & Ch.1 – 5595 MHz

Figure 37: 10 MHz, 17 dBi, High channel: Maximum conducted output power measured at Ch.0 & Ch.1 – 5710 MHz

5.3.4.6 RESULT

Maximum Conducted Output Power for all channels in both 40 MHz & 5 MHz modulation bandwidth is within the specified limits. Refer below table for consolidated data.

Modulation Bandwidth (MHz)	Antenna path	Channel Frequency (MHz)	Recorded value (dBm)
40	Ch. 0	5495	8.13
40	Ch. 1	5495	8.93
40	Ch. 0	5595	9.56
40	Ch. 1	5595	9.55
40	Ch. 0	5700	9.17
40	Ch. 1	5700	9.60
10	Ch. 0	5485	9.52
10	Ch. 1	5485	9.54
10	Ch. 0	5595	9.29
10	Ch. 1	5595	9.34
10	Ch. 0	5710	8.91
10	Ch. 1	5710	7.97

Table 6: Max RF out power for 17 dBi configuration

Modulation Bandwidth (MHz)	Antenna path	Channel Frequency (MHz)	Consolidated Power (dBm)	Limit (dBm)	Result
40	Ch. 0 & Ch. 1	5495	11.55	12.97	PASS
40	Ch. 0 & Ch. 1	5595	12.55	12.97	PASS
40	Ch. 0 & Ch. 1	5700	12.38	12.97	PASS
10	Ch. 0 & Ch. 1	5485	12.50	12.97	PASS
10	Ch. 0 & Ch. 1	5595	12.27	12.97	PASS
10	Ch. 0 & Ch. 1	5710	11.39	12.97	PASS

Table 7: Consolidated values across channels and final power for 17 dBi configuration

The recorded power in dBm was converted into Watt, and then added and convert the result back to dBm
*dBm to mW =log(mW)*10*
mW to dBm = 10^(dBm/10)

5.3.5 POWER SPECTRAL DENSITY

5.3.5.1 TEST SPECIFICATION

Test Standard	47 CFR, Part 15 Feb 2016
Test Procedure	789033 D2 General U-NII Test Procedures New Rule V01r01
Frequency Range	5470 MHz to 5725 MHz
Resolution Bandwidth	1 MHz
Video Bandwidth	3 MHz
Sweep Time	1 ms
Attenuation	Auto
Test Mode	Conducted
Detector	RMS
Input Voltage	120 V AC
Input Frequency	60 Hz
Temperature	24.0 °C
Humidity	55.0 %
Tested By	Dikshit Raviteja
Test Date	08th Feb 2016

5.3.5.2 LIMITS

Standard	Reference section	Frequency range	Limit
47 CFR, Part 15 Feb 2016	§15.407 a(2)	5470 MHz to 5725 MHz	≤ 11 dBm in any 1MHz band Limit (for 17 dBi antenna configuration) : ≤ 0 dBm\MHz

5.3.5.3 TEST SETUP

Figure 38: Typical test setup for Conducted Test

5.3.5.4 TEST PROCEDURE

The Conducted test was performed using the Spectrum analyzer. Measurements were done as per Section II F (PSD) of KDB **'789033 D02 General UNII Test Procedures New Rules v01r01".** The RF output of the EUT was connected to the input port of Spectrum analyzer using an attenuator. The graph and data captured from spectrum analyzer and compared with the limits specified in the standard.

5.3.5.5 MEASUREMENT GRAPHS / DATA



Figure 39: 40 MHz, 17 dBi, Low channel: Power spectral density measured at Ch. 0 – 5495 MHz



Figure 40: 40 MHz, 17 dBi, Low channel: Power spectral density measured at Ch. 1 – 5495 MHz



Figure 41: 40 MHz, 17 dBi, Mid channel: Power spectral density measured at Ch. 0 – 5595 MHz



Figure 42: 40 MHz, 17 dBi, Mid channel: Power spectral density measured at Ch. 1 – 5595 MHz



Figure 43: 40 MHz, 17 dBi, High channel: Power spectral density measured at Ch. 0 – 5700 MHz



Figure 44: 40 MHz, 17 dBi, High channel: Power spectral density measured at Ch. 1 – 5700 MHz

Figure 45: 10 MHz, 17 dBi, Low channel: Power spectral density measured at Ch. 0 – 5485 MHz

Figure 46: 10 MHz, 17 dBi, Low channel: Power spectral density measured at Ch. 1 – 5485 MHz

Figure 47: 10 MHz, 17 dBi, Mid channel: Power spectral density measured at Ch. 0– 5595 MHz



Figure 48: 10 MHz, 17 dBi, Mid channel: Power spectral density measured at Ch. 1 – 5595 MHz



Figure 49: 10 MHz, 17 dBi, High channel: Power spectral density measured at Ch. 0 – 5710 MHz

Figure 50: 10 MHz, 17 dBi, High channel: Power spectral density measured at Ch. 1 – 5710 MHz

5.3.5.6 RESULT

Power Spectral Density for all channels in both 40 MHz & 10 MHz Modulation Bandwidths is within the Specified limit. Refer below table for consolidated result.

Modulation Bandwidth (MHz)	Antenna path	Channel Frequency (MHz)	Recorded value (dBm/MHz)	Limit (dBm/MHz)	Result
40	Ch. 0	5495	-33.31	-3	Pass
40	Ch. 0	5595	-20.32	-3	Pass
40	Ch. 0	5700	-20.58	-3	Pass
40	Ch. 1	5495	-20.85	-3	Pass
40	Ch. 1	5595	-20.34	-3	Pass
40	Ch. 1	5700	-22.63	-3	Pass
10	Ch. 0	5485	-3.190	-3	Pass
10	Ch. 0	5595	-3.404	-3	Pass
10	Ch. 0	5710	-3.887	-3	Pass
10	Ch. 1	5485	-3.190	-3	Pass
10	Ch. 1	5595	-4.614	-3	Pass
10	Ch. 1	5710	-3.887	-3	Pass

Table 8: Result of PSD for 17 dBi configuration for both 40 MHz and 10 MHz modulation bandwidth

5.3.6 TRANSMITTER UNWANTED EMISSIONS (CONDUCTED)

5.3.6.1 TEST SPECIFICATION

Test Standard	47 CFR, Part 15 Feb 2016			
Test Procedure	ANSI C63.10-2013			
Frequency Range	9 kHz - 150 kHz	150 kHz -30 MHz	30 MHz-1 GHz	1 GHz – 40 GHz
Resolution Bandwidth	200 Hz	9 kHz	120 kHz	1 MHz
Video Bandwidth	1 kHz	30 kHz	300 kHz	3 MHz
Sweep Time	Auto	Auto	Auto	Auto
Detector	Peak	Peak	Peak	Peak & Average
Attenuation	Auto			
Test Mode	Conducted			
Input Voltage	120 V AC			
Input Frequency	60 Hz			
Temperature	23.0 °C			
Humidity	54.0 %			
Tested By	Suresh G N			
Test Date	28th Apr 2016			

5.3.6.2 LIMITS

Standard	Reference section	Frequency range	Limit EIRP (dBm/MHz)
47 CFR, Part 15 Feb 2016	§15.407 b (3)	Outside 5470-5725 MHz	-27

Table 9: Unwanted emission Limit

Standard	Reference section	Frequency range	Limit (dBµV/m)
47 CFR, Part 15 Feb 2016	§15.209	9 kHz to 490 kHz 490 kHz to 1.705 MHz 1.705 MHz to 30 MHz	128.5194 to 93.8003* 73.8003 to 62.9697* 69.5429

Table 10: General Field strength limit below 30 MHz

*Note: * Decreases with the logarithm of the frequency*

Standard	Reference section	Frequency range	Limit (dBµV/m) as per Section 5.209
47 CFR, Part 15 Feb 2016	§15.209	30 MHz to 88 MHz 88 MHz to 216 MHz 216 MHz to 960 MHz 960 MHz to 40 GHz	40 43.52 46.02 53.98

Table 11: General Field strength limit above 30 MHz

Above table specifies limit with Average detector above 1 GHz. 73.98 dBµV/m is considered as the limit when Peak detector is employed for the measurements above 1 GHz.

5.3.6.3 TEST SETUP

Figure 51: Typical test setup for Conducted Test

5.3.6.4 TEST PROCEDURE

The Conducted test was performed using the Spectrum analyzer/EMI receiver. Measurements were done as per Section II G.0 of KDB **"789033 DO2 General UNII Test Procedure New Rules v01r01".** The RF output of the EUT was connected to the input port of Spectrum analyzer/EMI receiver using an attenuator. The graph and data captured from spectrum analyzer and performed required calculations to attain the Electric Field value and compared with the limits specified in the standard.

In the frequency range 9 kHz to 1 GHz, the measurement was performed with peak detector. In the frequency range 1 GHz to 40 GHz, measurement was performed employing both peak & average detector as specified in the standard. Detectors were selected based on FCC KDB document.

Peak search option was used to capture the frequency with maximum amplitude in the respective bands and final calculations have been performed on these frequencies to show compliance with the limits specified.

5.3.6.5 MEASUREMENT GRAPHS / DATA



Figure 52: 40 MHz, 17 dBi, Low channel: Peak emission from 9 kHz to 150 kHz at Ch. 0 – 5495 MHz



Figure 53: 40 MHz, 17 dBi, Low channel: Peak emission from 150 kHz to 30 MHz at Ch. 0 –5495 MHz



Figure 54: 40 MHz, 17 dBi, Low channel: Peak emission from 30 MHz to 1 GHz at Ch. 0 –5495 MHz



Figure 55: 40 MHz, 17 dBi, Low channel: Average emission from 1 GHz to 18 GHz at Ch. 0 –5495 MHz