

FCC AND IC CERTIFICATION TEST REPORT

FOR

Applicant	:	Edifier International Limited
Address	:	P.O. Box 6264 General Post Office Hong Kong
Equipment under Test	:	Wireless Speaker
Model No.	:	EDF100008
Trade Mark	:	EDIFIER
FCC ID	:	Z9G-EDF112
IC	:	10004A-EDF112
Manufacturer	:	Beijing Edifier Technology Co., Ltd.
Address	:	8th floor, ZuoAn Building, NO.68 BeiSiHuanXiLu, Haidian District, Beijing 100080, CHINA

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

	Test report declares.....	4
1.	Summary of Test Results.....	6
2.	General Test Information	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT.....	7
2.3.	Assistant equipment used for test.....	7
2.4.	Block diagram of EUT configuration for test	8
2.5.	Deviations of test standard.....	8
2.6.	Test environment conditions	8
2.7.	Test laboratory	8
2.8.	Measurement uncertainty.....	9
3.	Equipment Used During Test.....	10
4.	6dB Bandwidth and 99% Bandwidth.....	12
4.1.	Block diagram of test setup.....	12
4.2.	Limits	12
4.3.	Test procedure	12
4.4.	Test result.....	13
4.5.	original test data	13
5.	Conducted peak Output Power.....	20
5.1.	Block diagram of test setup.....	20
5.2.	Limits	20
5.3.	Test procedure	20
5.4.	Test result.....	20
6.	Power Spectral Density.....	21
6.1.	Block diagram of test setup.....	21
6.2.	Limits	21
6.3.	Test procedure	21
6.4.	Test result.....	21
6.5.	original test data	22
7.	Band Edge and Spurious Emissions (Conducted)	26
7.1.	Block diagram of test setup.....	26
7.2.	Limits	26
7.3.	Test procedure	26
7.4.	Test result.....	27
7.5.	original test data	27
8.	Radiated Spurious Emissions	39
8.1.	Block diagram of test setup.....	39

8.2.	Limit	40
8.3.	Test procedure	41
8.4.	Test result	43
9.	Radiated Band Edge Compliance	47
9.1.	Block diagram of test setup	47
9.2.	Limit	47
9.3.	Test procedure	47
9.4.	Test result	47
10.	Power Line Conducted Emission	60
10.1.	Block diagram of test setup	60
10.2.	Power Line Conducted Emission Limits (Class B)	60
10.3.	Test procedure	60
10.4.	Test result	61
11.	Antenna Requirements	64
11.1.	Limit	64
11.2.	Result	64
12.	Test Setup Photograph	65
13.	Photos of the EUT	67

Test Report Declare

Applicant	:	Edifier International Limited
Address	:	P.O. Box 6264 General Post Office Hong Kong
Equipment under Test	:	Wireless Speaker
Model No.	:	EDF100008
Trade Mark	:	EDIFIER
Manufacturer	:	Beijing Edifier Technology Co., Ltd.
Address	:	8th floor, ZuoAn Building, NO.68 BeiSiHuanXiLu, Haidian District, Beijing 100080, CHINA

Test Standard Used: FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 2 February 2017.

Test procedure used: ANSI C63.10:2013, RSS-Gen Issue 5, Apr. 2018, 558074 D01 15.247 Meas Guidance v05r02, 662911 D01 Multiple Transmitter Output v02r01

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC&IC standards.

Report No:	DDT-R21030302-2E3		
Date of Receipt:	Mar. 02, 2021	Date of Test:	Mar. 02, 2021~ Apr. 17, 2021

Prepared By:

Ella Gong

Ella Gong/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Apr. 17, 2021	

1. Summary of Test Results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	Standard	Verdict
6dB Bandwidth and 99% Bandwidth	FCC 15.247 (a) (2) RSS-247 Clause 5.2 (a)	Pass
Conducted Output Power	FCC 15.247 (b) (3) RSS-247 Clause 5.4 (e)	Pass
Power Spectral Density	FCC 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
Band-edge and Spurious Emissions (Conducted)	FCC 15.247 (d) RSS-247 Clause 5.5	Pass
Radiated Spurious Emissions	FCC 15.247 (d) FCC 15.209 FCC 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
Radiated Band Edge Compliance	FCC 15.247 (d) FCC 15.209 FCC 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
Power Line Conducted Emission	FCC 15.207 RSS-GEN Clause 8.8	Pass
Antenna Requirement	FCC 15.203 RSS-GEN Clause 6.8	Pass

2. General Test Information

2.1. Description of EUT

EUT* Name	: Wireless Speaker
Model Number	: EDF100008
EUT Function Description	: Please reference user manual of this device
Power Supply	: 100-240V ~ 50/60Hz 300mA
Radio Technology	: IEEE 802.11b/g/n
FCC Operation Frequency	: IEEE 802.11b: 2412MHz-2462MHz IEEE 802.11g: 2412MHz-2462MHz IEEE 802.11n HT20: 2412MHz-2462MHz
Modulation	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK)
Transmitter Rate	: IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n HT20: 6.5, 13, 19.5, 26, 39, 52, 58.5, 65 Mbps
Antenna Type	: Dedicated FPC antenna, maximum PK gain: 2.77 dBi
Sample Type	: Series production
Serial Number	: 636000243682 for conductive 636000245215 for radiation

Note: EUT is the ab. of equipment under test.

Channel information					
CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Description	Remark
AC Cable	N/A	N/A	N/A	Length: 173mm, unshielded

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
Notebook	Lenovo Beijing Co. Ltd.	ThinkPad	FCC/CE	TP00015A

2.4. Block diagram of EUT configuration for test



Run a special test software “adb.exe” provided by manufacturer to control EUT work in Continuous Tx mode, and select test channel, wireless mode and data rate.

Tested mode, channel, and data rate information				
Mode	Setting Tx Power	data rate (Mbps) (see Note)	Channel	Frequency (MHz)
IEEE 802.11b	64	11	LCH: CH1	2412
	64	11	MCH: CH6	2437
	64	11	HCH: CH11	2462
IEEE 802.11g	64	54	LCH: CH1	2412
	64	54	MCH: CH6	2437
	64	54	HCH: CH11	2462
IEEE 802.11n HT20	64	MCS 7	LCH: CH1	2412
	64	MCS 7	MCH: CH6	2437
	64	MCS 7	HCH: CH11	2462

Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

2.5. Deviations of test standard

No Deviation

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Frequencies Stability	6.7×10^{-8} (Antenna couple method)
	5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.40 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
	1.66 dB ($8 \text{ GHz} \leq f < 22 \text{ GHz}$)
Uncertainty for radio frequency (RBW<20 kHz)	3×10^{-8}
Temperature	0.4℃
Humidity	2%
Uncertainty for Radiation Emission test (30 MHz-1 GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz-40 GHz)	4.10 dB (1-6 GHz)
	4.40 dB (6 GHz-18 GHz)
	3.54 dB (18 GHz-26 GHz)
	4.30 dB (26 GHz-40 GHz)
Uncertainty for Power line conduction emission test	3.32 dB (150 kHz-30 MHz)

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


3. Equipment Used During Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☐ RF Connected Test (Tonscend RF Measurement System 1#)					
Spectrum analyzer	R&S	FSU26	101272	Jul. 01, 2020	1 Year
Spectrum analyzer	Agilent	N9020D	MY49100362	Sep. 28, 2020	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	Jul. 01, 2020	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Sep. 24, 2020	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jul. 01, 2020	1 Year
Power Sensor	Agilent	U2021XA	MY55150010	Jul. 01, 2020	1 Year
Power Sensor	Agilent	U2021XA	MY55150011	Jul. 01, 2020	1 Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Apr. 25, 2020	1 Year
RF Cable	Micable	C10-01-01-1	100309	Sep. 28, 2020	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Jul. 01, 2020	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.7	N/A	N/A
☒ RF Connected Test (Tonscend RF Measurement System 2#)					
Spectrum analyzer	R&S	FSU26	200071	Sep. 25, 2020	1 Year
Spectrum analyzer	Agilent	N9020D	MY49100362	Sep. 28, 2020	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	Jul. 01, 2020	1 Year
Vector Signal Generator	Agilent	N5182A	MY19060405	Jul. 01, 2020	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180912	Jul. 01, 2020	1 Year
RF Control Unit	Tonsend	JS0806-2	DDT-ZC01449	Jul. 01, 2020	1 Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Apr. 25, 2020	1 Year
RF Cable	Micable	C10-01-01-1	100309	Sep. 28, 2020	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Jul. 01, 2020	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.7	N/A	N/A
☐ Radiation 1#chamber					
EMI Test Receiver	R&S	ESU8	100316	Sep. 24, 2020	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jul. 01, 2020	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Nov. 13, 2020	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Nov. 18, 2020	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Nov. 13, 2020	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Apr. 11, 2021	1 Year
Pre-amplifier	A.H.	PAM-0118	360	Sep. 28, 2020	1 Year
RF Cable	HUBSER	CP-X2+ CP-X1	W11.03+ W12.02	Sep. 24, 2020	1 Year

RF Cable	N/A	5m+6m+1m	06270619	Sep. 30, 2020	1 Year
MI Cable	HUBSER	C10-01-01-1M	1091629	Sep. 30, 2020	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
☒ Radiation 2#chamber					
EMI Test Receiver	R&S	ESCI	101364	Sep. 28, 2020	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jul. 01, 2020	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	9163-994	Nov. 13, 2020	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Nov. 18, 2020	1 Year
Double Ridged Horn Antenna	Schwarzbeck	BBHA9120	02108	Jul. 11, 2020	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Apr. 11, 2021	1 Year
Pre-amplifier	TERA-MW	TRLA-0040G35	101303	Sep. 28, 2020	1 Year
RF Cable	N/A	14+1.5m	06270619	Sep. 28, 2020	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
☒ Power Line Conducted Emissions Test 1#					
EMI Test Receiver	R&S	ESU8	100316	Sep. 24, 2020	1 Year
LISN 1	R&S	ENV216	101109	Sep. 28, 2020	1 Year
LISN 2	R&S	ESH2-Z5	100309	Sep. 28, 2020	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Sep. 24, 2020	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Sep. 24, 2020	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
☐ Power Line Conducted Emissions Test 2#					
Test Receiver	R&S	ESPI	101761	Sep. 24, 2020	1 Year
LISN 1	R&S	ENV216	101170	Sep. 28, 2020	1 Year
LISN 2	R&S	ESH2-Z5	100309	Sep. 28, 2020	1 Year
Pulse Limiter	R&S	KH43101	431011801568-12#	Jul. 01, 2020	1 Year
CE Cable 2	HUBSER	N/A	W11.02	Sep. 24, 2020	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A

4. 6dB Bandwidth and 99% Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) 99% Bandwidth set the spectrum analyzer as follows:

RBW:	300 kHz
VBW:	1 MHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) 6dB Bandwidth set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(4) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


4.4. Test result


TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	6.760	2408.760	2415.520	0.5	PASS
		2437	7.480	2433.040	2440.520	0.5	PASS
		2462	7.480	2458.200	2465.680	0.5	PASS
11G	Ant1	2412	15.240	2404.400	2419.640	0.5	PASS
		2437	15.200	2429.400	2444.600	0.5	PASS
		2462	15.200	2454.400	2469.600	0.5	PASS
11N20SISO	Ant1	2412	15.200	2404.400	2419.600	0.5	PASS
		2437	16.160	2429.360	2445.520	0.5	PASS
		2462	15.240	2454.400	2469.640	0.5	PASS

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	10.84	2406.680	2417.520	---	PASS
		2437	11.04	2431.440	2442.480	---	PASS
		2462	11.12	2456.520	2467.640	---	PASS
11G	Ant1	2412	16.4	2403.880	2420.280	---	PASS
		2437	16.52	2428.760	2445.280	---	PASS
		2462	16.48	2453.840	2470.320	---	PASS
11N20SISO	Ant1	2412	17.72	2403.200	2420.920	---	PASS
		2437	17.8	2428.080	2445.880	---	PASS
		2462	17.76	2453.160	2470.920	---	PASS


4.5. original test data

6dB Bandwidth:







11B Ant1 2462



11G Ant1 2412




11G Ant1 2437




Date: 31.MAR.2021 21:43:18

11G Ant1 2462




Date: 31.MAR.2021 21:43:45

11N20SISO Ant1 2412




Date: 30.MAR.2021 11:51:31

11N20SISO Ant1 2437




11N20SISO Ant1 2462




99% Bandwidth


11B Ant1 2412




11B Ant1 2437




11B Ant1 2462




11G Ant1 2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412



11N20SISO Ant1 2437



11N20SISO Ant1 2462



5. Conducted peak Output Power

5.1. Block diagram of test setup

Same as section 4.1

5.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.3. Test procedure

Connect each EUT's antenna output to power sensor by RF cable and attenuator

Measure the PK output power of each antenna port by power meter.

5.4. Test result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	14.97	<=30	PASS
		2437	15.56	<=30	PASS
		2462	14.23	<=30	PASS
11G	Ant1	2412	10.97	<=30	PASS
		2437	11.81	<=30	PASS
		2462	10.25	<=30	PASS
11N20SISO	Ant1	2412	11.43	<=30	PASS
		2437	11.95	<=30	PASS
		2462	10.53	<=30	PASS

6. Power Spectral Density

6.1. Block diagram of test setup

Same as section 4.1

6.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

6.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Set the spectrum analyzer as follows:


Center frequency	DTS Channel center frequency
RBW:	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	RMS
Sweep time:	auto
Trace mode	Max hold


- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
- (4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.4. Test result

TestMode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-9.51	≤ 8	PASS
		2437	-10.71	≤ 8	PASS
		2462	-11.38	≤ 8	PASS
11G	Ant1	2412	-12.03	≤ 8	PASS
		2437	-13.36	≤ 8	PASS
		2462	-14.77	≤ 8	PASS
11N20SISO	Ant1	2412	-14.19	≤ 8	PASS
		2437	-14.18	≤ 8	PASS
		2462	-13.95	≤ 8	PASS


6.5. original test data






Date: 30.MAR.2021 11:40:31

11G_Ant1_2412




Date: 30.MAR.2021 11:43:31

11G_Ant1_2437




Date: 30.MAR.2021 11:46:26

11G_Ant1_2462




Date: 30.MAR.2021 11:48:10

11N20SISO_Ant1_2412




Date: 30.MAR.2021 11:51:57

11N20SISO_Ant1_2437



Date: 30.MAR.2021 11:55:18

11N20SISO_Ant1_2462



7. Band Edge and Spurious Emissions (Conducted)

7.1. Block diagram of test setup

Same as section 4.1

7.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

7.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100 kHz
VBW:	300 kHz
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span/RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band




7.4. Test result


EUT Set Mode	CH or Frequency	Result (dBm)	EUT Set Mode	CH or Frequency	Result Result (dBm)
11b	CH1	Pass	11n HT 20	CH1	Pass
	CH6	Pass		CH6	Pass
	CH11	Pass		CH11	Pass
11g	CH1	Pass	11n HT 40	CH3	Pass
	CH6	Pass		CH6	Pass
	CH11	Pass		CH9	Pass

7.5. original test data


Band Edge









Spurious Emissions






Date: 30.MAR.2021 11:36:59

11B_Ant1_2412_1000~26500




Date: 30.MAR.2021 11:37:36

11B_Ant1_2437_0~Reference




Date: 30.MAR.2021 11:38:56

11B_Ant1_2437_30~1000




Date: 30.MAR.2021 11:39:01

11B_Ant1_2437_1000~26500




Date: 30.MAR.2021 11:39:37

11B_Ant1_2462_0~Reference




Date: 30.MAR.2021 11:41:41

11B_Ant1_2462_30~1000




Date: 30.MAR.2021 11:41:46

11B Ant1 2462 1000~26500




Date: 30.MAR.2021 11:42:22

11G Ant1 2412 0~Reference




Date: 30.MAR.2021 11:44:42

11G Ant1 2412 30~1000




Date: 30.MAR.2021 11:44:47

11G Ant1 2412 1000~26500




Date: 30.MAR.2021 11:45:23

11G Ant1 2437 0~Reference




Date: 30.MAR.2021 11:46:35

11G Ant1 2437 30~1000




Date: 30.MAR.2021 11:46:39

11G Ant1 2437 1000~26500




Date: 30.MAR.2021 11:47:16

11G Ant1 2462 0~Reference




Date: 30.MAR.2021 11:49:20

11G Ant1 2462 30~1000




Date: 30.MAR.2021 11:49:27

11G Ant1 2462 1000~26500




Date: 30.MAR.2021 11:50:04

11N20SISO Ant1 2412 0~Reference




Date: 30.MAR.2021 11:53:10

11N20SISO Ant1 2412 30~1000




Date: 30.MAR.2021 11:53:14

11N20SISO Ant1 2412 1000-26500




Date: 30.MAR.2021 11:53:52

11N20SISO Ant1 2437 0-Reference




Date: 30.MAR.2021 11:55:27

11N20SISO Ant1 2437 30-1000




Date: 30.MAR.2021 11:55:31

11N20SISO Ant1 2437 1000~26500




Date: 30.MAR.2021 11:56:08

11N20SISO Ant1 2462 0~Reference




Date: 30.MAR.2021 11:58:43

11N20SISO Ant1 2462 30~1000




11N20SISO Ant1 2462 1000~26500




8. Radiated Spurious Emissions

8.1. Block diagram of test setup


In 3 m Anechoic Chamber, test setup diagram for 9 kHz - 30 MHz:



In 3 m Anechoic Chamber, test setup diagram for 30 MHz – 1 GHz:



In 3 m Anechoic Chamber, test setup diagram for frequency above 1 GHz:



Note: For harmonic emissions test an appropriate high pass filter was inserted in the input port of AMP.

8.2. Limit

8.2.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6

8.2.2 FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V}/\text{m}) + 40\text{Log}(30\text{m}/3\text{m})$$

8.2.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions or comply with 15.209 limits.

8.3. Test procedure

(1) EUT height should be 0.8 m for below 1 GHz at a semi-anechoic chamber while EUT height should be 1.5 m for above 1 GHz at full chamber or semi-anechoic chamber ground with absorbers.

(2) The antenna used as below table.

Test frequency range	Test antenna used	Measuring distance
9 kHz-30 MHz	Active Loop antenna	3 m
30 MHz-1 GHz	Trilog Broadband Antenna	3 m
1 GHz-18 GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3 m
18 GHz-40 GHz	Horn Antenna(18GHz-40GHz)	1 m

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30 MHz, the Trilog Broadband Antenna or

Horn Antenna was located 3 m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 25GHz, so below final test was performed with frequency range from 9kHz to 18GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9-90 kHz, 110-490 kHz, for emissions from 9 kHz-90 kHz, 110 kHz-490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9 kHz-150 kHz	200 Hz
150 kHz-30 MHz	9 kHz
30 MHz-1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; RMS detector RBW 1 MHz VBW 1/T for Average measure (according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure).

8.4. Test result

Pass. (See below detailed test result)

All the emissions except fundamental emission from 9 kHz to 25 GHz were comply with 15.209 limit.

Note1: According exploratory test no any obvious emission was detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

Note2: For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in 11b, Tx CH11 mode.

Radiated Emission test (below 1GHz)

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50A\RF\FCC
BELOW1G.EM6

Test Date : 2021-03-24

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008


Power Supply : DC 120V60Hz

Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 VULB 9163 2#/3m/VERTICAL

Memo :



Data: 5

Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	37.55	19.47	10.81	3.74	34.02	40.00	-5.98	QP	VERTICAL
2	40.14	18.21	11.45	3.76	33.42	40.00	-6.58	QP	VERTICAL
3	57.80	17.40	11.64	3.94	32.98	40.00	-7.02	QP	VERTICAL
4	162.04	25.02	8.34	4.83	38.19	43.50	-5.31	QP	VERTICAL
5	431.03	14.35	16.01	6.04	36.40	46.00	-9.60	QP	VERTICAL
6	793.40	10.62	20.89	7.33	38.84	46.00	-7.16	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50AIR\FCC
BELOW1G.EM6

Test Date : 2021-03-23

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008


Power Supply : DC 120V60Hz

Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 VULB 9163 2#/3m/HORIZONTAL

Memo :



Data: 6

Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	44.43	10.11	12.94	3.80	26.85	40.00	-13.15	QP	HORIZONTAL
2	159.23	19.89	8.26	4.81	32.96	43.50	-10.54	QP	HORIZONTAL
3	603.54	8.40	19.21	6.73	34.34	46.00	-11.66	QP	HORIZONTAL
4	651.94	11.32	19.32	6.91	37.55	46.00	-8.45	QP	HORIZONTAL
5	774.16	10.02	20.85	7.28	38.15	46.00	-7.85	QP	HORIZONTAL
6	793.40	9.76	20.89	7.33	37.98	46.00	-8.02	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Radiated Emission test (above 1GHz)

Freq (MHz)	Read level (dBμV)	Antenna Factor (dB/m)	PRM Factor(dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector type	Polarization
11b CH1									
5199.00	48.28	32.78	43.26	7.07	44.87	74.00	-29.13	Peak	HORIZONTAL
7494.00	46.65	37.09	42.64	8.83	49.93	74.00	-24.07	Peak	HORIZONTAL
8089.00	47.30	37.92	42.25	8.66	51.63	74.00	-22.37	Peak	HORIZONTAL
11030.00	45.28	39.80	42.85	10.60	52.83	74.00	-21.17	Peak	HORIZONTAL
12866.00	45.41	39.49	42.79	11.41	53.52	74.00	-20.48	Peak	HORIZONTAL
15705.00	43.83	39.35	42.13	12.49	53.54	74.00	-20.46	Peak	HORIZONTAL
4944.00	48.69	32.59	43.24	6.97	45.01	74.00	-28.99	Peak	VERTICAL
7494.00	47.61	37.09	42.64	8.83	50.89	74.00	-23.11	Peak	VERTICAL
8786.00	46.10	38.17	41.90	9.22	51.59	74.00	-22.41	Peak	VERTICAL
10741.00	46.03	39.70	42.73	10.46	53.46	74.00	-20.54	Peak	VERTICAL
12866.00	45.10	39.49	42.79	11.41	53.21	74.00	-20.79	Peak	VERTICAL
15824.00	43.80	39.21	42.20	12.56	53.37	74.00	-20.63	Peak	VERTICAL
11b CH6									
5709.00	44.51	34.97	43.93	6.84	42.39	74.00	-31.61	Peak	HORIZONTAL
7545.00	43.74	36.33	43.35	9.03	45.75	74.00	-28.25	Peak	HORIZONTAL
10010.00	43.94	37.80	44.88	9.23	46.09	74.00	-27.91	Peak	HORIZONTAL
11744.00	43.60	38.30	43.34	9.82	48.38	74.00	-25.62	Peak	HORIZONTAL
12866.00	44.52	38.79	42.99	11.20	51.52	74.00	-22.48	Peak	HORIZONTAL
14311.00	43.88	40.17	42.63	10.71	52.13	74.00	-21.87	Peak	HORIZONTAL
5046.00	48.58	32.72	43.22	7.05	45.13	74.00	-28.87	Peak	VERTICAL
7375.00	47.32	36.90	42.73	8.63	50.12	74.00	-23.88	Peak	VERTICAL
10486.00	45.58	39.58	42.55	10.36	52.97	74.00	-21.03	Peak	VERTICAL
11336.00	44.79	39.80	42.38	10.94	53.15	74.00	-20.85	Peak	VERTICAL
12985.00	45.19	39.68	42.98	11.19	53.08	74.00	-20.92	Peak	VERTICAL
15790.00	43.25	39.25	42.18	12.54	52.86	74.00	-21.14	Peak	VERTICAL
11b CH11									
4944.00	49.14	32.59	43.24	6.97	45.46	74.00	-28.54	Peak	HORIZONTAL
7460.00	45.96	37.04	42.67	8.77	49.10	74.00	-24.90	Peak	HORIZONTAL
9466.00	45.95	38.77	41.99	9.65	52.38	74.00	-21.62	Peak	HORIZONTAL
11625.00	44.04	39.75	41.95	11.11	52.95	74.00	-21.05	Peak	HORIZONTAL
12866.00	45.26	39.49	42.79	11.41	53.37	74.00	-20.63	Peak	HORIZONTAL
15671.00	43.13	39.39	42.11	12.47	52.88	74.00	-21.12	Peak	HORIZONTAL
4961.00	46.23	34.43	44.05	6.51	43.12	74.00	-30.88	Peak	VERTICAL
6950.00	45.17	35.87	43.77	8.65	45.92	74.00	-28.08	Peak	VERTICAL
9619.00	44.38	37.50	44.09	9.00	46.79	74.00	-27.21	Peak	VERTICAL
11744.00	44.25	38.30	43.34	9.82	49.03	74.00	-24.97	Peak	VERTICAL
13920.00	44.21	40.21	42.47	10.62	52.57	74.00	-21.43	Peak	VERTICAL
16215.00	41.61	41.85	43.19	11.52	51.79	74.00	-22.21	Peak	VERTICAL

Note: 1.30MHz~25GHz: (Scan with 11b, 11g, 11n HT20 mode, the worst case is 11b mode)


2. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

4. For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

9. Radiated Band Edge Compliance

9.1. Block diagram of test setup



9.2. Limit

All restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400 MHz to 2483.5 MHz shall be at least 20dB below the fundamental emissions or comply with RSS-Gen Issue 3 clause 7.2.5 (Same as FCC 15.209) limits.

9.3. Test procedure

Same with clause 8.3 except change investigated frequency range from 2310 MHz to 2430 MHz and 2445 MHz to 2500 MHz, 2310 MHz to 2450 MHz and 2425 MHz to 2500MHz.

Remark: All restriction band have been tested, and shown in report.

9.4. Test result

Pass. (See below detailed test result)

Note: All mode was test and record this report.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50AIR\FCC
ABOVE 1G 2.4G.EM6

Test Date : 2021-03-23

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008

Power Supply : AC120V 60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 BBHA9120D/3m/HORIZONTAL

Memo : 11B 2412

Data: 9



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2354.04	52.61	27.85	43.10	4.76	42.12	74.00	-31.88	Peak	HORIZONTAL
2	2390.04	51.03	27.89	43.14	4.80	40.58	74.00	-33.42	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50AIR\FCC
ABOVE 1G 2.4G.EM6

Test Date : 2021-03-23

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008

Power Supply : AC120V 60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 BBHA9120D/3m/VERTICAL

Memo : 11B 2412

Data: 10



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2384.64	52.67	27.88	43.13	4.79	42.21	74.00	-31.79	Peak	VERTICAL
2	2390.04	51.90	27.89	43.14	4.80	41.45	74.00	-32.55	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50AIR\FCC
ABOVE 1G 2.4G.EM6

Test Date : 2021-03-23

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008

Power Supply : AC120V 60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 BBHA9120D/3m/VERTICAL

Memo : 11B 2462

Data: 11



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	51.55	27.98	43.23	4.90	41.20	74.00	-32.80	Peak	VERTICAL
2	2497.60	56.32	28.00	43.25	4.92	45.99	74.00	-28.01	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50ARF\FCC
ABOVE 1G 2.4G.EM6

Test Date : 2021-03-23

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008

Power Supply : AC120V 60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 BBHA9120D/3m/HORIZONTAL

Memo : 11B 2462

Data: 12



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	51.12	27.98	43.23	4.90	40.77	74.00	-33.23	Peak	HORIZONTAL
2	2486.80	52.68	27.99	43.24	4.91	42.34	74.00	-31.66	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50A\RF\FCC
ABOVE 1G 2.4G.EM6

Test Date : 2021-03-23

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008

Power Supply : AC120V 60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 BBHA9120D/3m/HORIZONTAL

Memo : 11G 2412

Data: 13



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2358.96	57.91	27.86	43.11	4.76	47.42	74.00	-26.58	Peak	HORIZONTAL
2	2390.04	54.54	27.89	43.14	4.80	44.09	74.00	-29.91	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50A\RF\FCC
ABOVE 1G 2.4G.EM6

Test Date : 2021-03-23

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008

Power Supply : AC120V 60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 BBHA9120D/3m/VERTICAL

Memo : 11G 2412

Data: 14



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2314.80	53.75	27.81	43.06	4.71	43.21	74.00	-30.79	Peak	VERTICAL
2	2390.04	57.49	27.89	43.14	4.80	47.04	74.00	-26.96	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50A\RF\FCC
ABOVE 1G 2.4G.EM6

Test Date : 2021-03-23

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008

Power Supply : AC120V 60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 BBHA9120D/3m/VERTICAL

Memo : 11G 2462

Data: 15



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	53.20	27.98	43.23	4.90	42.85	74.00	-31.15	Peak	VERTICAL
2	2486.08	54.58	27.99	43.24	4.90	44.23	74.00	-29.77	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50AIR\FCC ABOVE 1G 2.4G.EM6

Test Date : 2021-03-23

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008

Power Supply : AC120V 60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 BBHA9120D/3m/HORIZONTAL

Memo : 11G 2462

Data: 16



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2478.58	56.22	27.98	43.23	4.90	45.87	74.00	-28.13	Peak	HORIZONTAL
2	2483.50	52.18	27.98	43.23	4.90	41.83	74.00	-32.17	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50ARF\FCC
ABOVE 1G 2.4G.EM6

Test Date : 2021-03-23

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008

Power Supply : AC120V 60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 BBHA9120D/3m/HORIZONTAL

Memo : 11N20 2412

Data: 17



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2384.76	58.85	27.88	43.13	4.79	48.39	74.00	-25.61	Peak	HORIZONTAL
2	2390.04	58.64	27.89	43.14	4.80	48.19	74.00	-25.81	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50A\RF\FCC
ABOVE 1G 2.4G.EM6

Test Date : 2021-03-23

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008

Power Supply : AC120V 60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 BBHA9120D/3m/VERTICAL

Memo : 11N20 2412

Data: 18



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2388.36	61.33	27.89	43.14	4.80	50.88	74.00	-23.12	Peak	VERTICAL
2	2390.04	59.23	27.89	43.14	4.80	48.78	74.00	-25.22	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50AIR\FCC ABOVE 1G 2.4G.EM6

Test Date : 2021-03-23

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008

Power Supply : AC120V 60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 BBHA9120D/3m/VERTICAL

Memo : 11N20 2462

Data: 19



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	56.87	27.98	43.23	4.90	46.52	74.00	-27.48	Peak	VERTICAL
2	2485.72	57.74	27.99	43.24	4.90	47.39	74.00	-26.61	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2#

D:\2021 RE2# Report Data\Q21030302-2E MS50A\RF\FCC
ABOVE 1G 2.4G.EM6

Test Date : 2021-03-23

Tested By : Kennys

EUT : Wireless Speaker

Model Number : EDF100008

Power Supply : AC120V 60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2020 BBHA9120D/3m/HORIZONTAL

Memo : 11N20 2462

Data: 20



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	51.79	27.98	43.23	4.90	41.44	74.00	-32.56	Peak	HORIZONTAL
2	2497.12	54.32	28.00	43.25	4.92	43.99	74.00	-30.01	Peak	HORIZONTAL


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

10. Power Line Conducted Emission

10.1. Block diagram of test setup



10.2. Power Line Conducted Emission Limits (Class B)

Frequency	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150 kHz ~ 500 kHz	66 ~ 56*	56 ~ 46*
500 kHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

10.3. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

10.4. Test result

Pass. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: "----" means peak detection; "----" means average detection

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worse case.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 5# Shield Room

D:\2021 report data\Q21030302-1E\RF FCC CE.EM6

Test Date : 2021-03-05

Tested By : Junchang Du

EUT : Wireless Speaker

Model Number : EDF100008


Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55.5%,Press:100.1kPa
a

LISN : 2020 ENV 216 2#/NEUTRAL

Memo :



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.15	39.74	9.38	0.02	10.01	59.15	66.00	-6.85	QP	NEUTRAL
2	0.15	23.30	9.38	0.02	10.01	42.71	56.00	-13.29	Average	NEUTRAL
3	0.20	34.93	9.39	0.02	10.01	54.35	63.76	-9.41	QP	NEUTRAL
4	0.20	20.06	9.39	0.02	10.01	39.48	53.76	-14.28	Average	NEUTRAL
5	0.25	29.40	9.39	0.02	10.01	48.82	61.82	-13.00	QP	NEUTRAL
6	0.25	15.52	9.39	0.02	10.01	34.94	51.82	-16.88	Average	NEUTRAL
7	0.85	17.34	9.41	0.03	10.01	36.79	56.00	-19.21	QP	NEUTRAL
8	0.85	10.23	9.41	0.03	10.01	29.68	46.00	-16.32	Average	NEUTRAL
9	2.53	8.76	9.42	0.06	10.01	28.25	56.00	-27.75	QP	NEUTRAL
10	2.53	3.18	9.42	0.06	10.01	22.67	46.00	-23.33	Average	NEUTRAL
11	21.95	16.29	9.57	0.16	10.02	36.04	60.00	-23.96	QP	NEUTRAL
12	21.95	10.47	9.57	0.16	10.02	30.22	50.00	-19.78	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 5# Shield Room

D:\2021 report data\Q21030302-1E\RF FCC CE.EM6

Test Date : 2021-03-05

Tested By : Junchang Du

EUT : Wireless Speaker

Model Number : EDF100008


Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55.5%,Press:100.1kPa
a

LISN : 2020 ENV 216 2#/LINE

Memo :



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.15	39.44	9.41	0.02	10.01	58.88	66.00	-7.12	QP	LINE
2	0.15	22.56	9.41	0.02	10.01	42.00	56.00	-14.00	Average	LINE
3	0.20	33.80	9.42	0.02	10.01	53.25	63.80	-10.55	QP	LINE
4	0.20	17.70	9.42	0.02	10.01	37.15	53.80	-16.65	Average	LINE
5	0.25	29.07	9.43	0.02	10.01	48.53	61.86	-13.33	QP	LINE
6	0.25	13.52	9.43	0.02	10.01	32.98	51.86	-18.88	Average	LINE
7	0.29	24.36	9.44	0.02	10.01	43.83	60.41	-16.58	QP	LINE
8	0.29	9.47	9.44	0.02	10.01	28.94	50.41	-21.47	Average	LINE
9	0.84	15.57	9.44	0.03	10.01	35.05	56.00	-20.95	QP	LINE
10	0.84	8.00	9.44	0.03	10.01	27.48	46.00	-18.52	Average	LINE
11	7.73	12.68	9.58	0.10	10.01	32.37	60.00	-27.63	QP	LINE
12	7.73	6.25	9.58	0.10	10.01	25.94	50.00	-24.06	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. Result

The antenna used for this product is FPC antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 2.77 dBi.

12. Test Setup Photograph

13. Photos of the EUT

END OF REPORT