



Report No.: HKEM190100000702

Page: 1 of 10

FCC ID: Z9O-92053072

RF Exposure Evaluation Report

Application No.: HKEM1901000007AT
Applicant: Ecolab, Inc
Address of Manufacturer: 650 Lone Oak Drive, Ecolab Schuman Center, Eagan Minnesota 55121
Equipment Under Test (EUT):
Product Name: HHCM915 Bed Beacon
Model No.: 92053072
FCC ID: Z9O-92053072
Standards: 47 CFR Part 1.1307 (2018)
47 CFR Part 1.1310 (2018)
Date of Receipt: 2019-01-03
Date of Test: 2019-03-11 to 2019-03-14
Date of Issue: 2019-03-14

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Ivan Toa
EMC Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Contents

	Page
.....	1
CONTENTS.....	2
2 GENERAL INFORMATION.....	3
2.1 GENERAL DESCRIPTION OF EUT.....	3
2.2 TEST LOCATION.....	4
2.3 TEST FACILITY	4
2.4 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, $K=2$)	4
2.5 DEVIATION FROM STANDARDS	5
2.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
2.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
3 RF EXPOSURE EVALUATION	6
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
3.1.1 <i>Limits</i>	6
3.1.2 <i>Test Procedure</i>	6
3.1.3 <i>EUT RF Exposure Evaluation</i>	7



2 General Information

2.1 General Description of EUT

Operating Frequency	913.75 MHz to 916.30 MHz
Type of Modulation:	FHSS
Number of Channels	50 Channels
Dwell time	Per channel is less than 0.4s.
Antenna Type	Integral
Antenna gain:	-2.5 dBi
Power Supply:	DC 3V ("D" size x 2 pcs)

2.2 Test Location

All tests were performed at:

SGS IECC Limited (Member of the SGS Group (SGS SA))
No. 16-B, Yip Wo Street, On Lok Tsuen, Fanling, N.T., Hong Kong
Tel: +852 2305 2570 Fax: +852 2756 4480
No tests were sub-contracted.

2.3 Test Facility

The test facility is recognized or accredited by the following organizations:

• HOKLAS (Lab Code: 125)

SGS IECC Limited has been accepted by HKAS Executive, on the recommendation of the Accreditation Advisory Board, as a HOKLAS Accredited Laboratory, this laboratory meets the requirements of ISO/IEC 17025:2005 and it has been accredited for performing specific test as listed in the scope of accreditation within the test category of Electrical and Electronic Products.

• FCC Recognized Accredited Test Firm (CAB Registration No.: 446297)

SGS IECC Limited has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: HK0010, Test Firm Registration Number: 446297.

• Industry Canada (Site Registration No.: 5193A; CAB Identifier No.: HK0001)

SGS IECC Limited has been recognized by Department of Innovation, Science and Economic Development (ISED) Canada as a wireless testing laboratory. The acceptance letter from the ISED is maintained in our files. CAB Identifier No: HK0001, Site Registration Number: 5193A.

2.4 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio frequency	$\pm 7.25 \times 10^{-8}$
2	RF power (conducted)	$\pm 0.75\text{dB}$
3	Radiated Spurious emission	$\pm 5.26\text{dB}$ (30MHz-1GHz)
		$\pm 5.11\text{dB}$ (1GHz-25GHz)
4	Temperature test	$\pm 1^\circ\text{C}$
5	Humidity test	$\pm 3\%$
6	DC and low frequency voltages test	$\pm 0.5\%$



2.5 Deviation from Standards

None.

2.6 Abnormalities from Standard Conditions

None.

2.7 Other Information Requested by the Customer

None.

3 RF Exposure Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f= Frequency in MHz

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, f/1500 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest and highest channel individually.



3.1.3 EUT RF Exposure Evaluation

For 900MHz network hub

Antenna 1 Gain: -2.5dBi ,

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 0.56 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Worst case result:

Frequency (MHz)	Conduct power (including Tune-up tolerance) (dBm)	Conduct power (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	MPE Ratios	Result
916.30	6.46	4.43	20	0.610	0.0005	PASS

Note: Refer to test report **HKEM190100000701** for EUT EIRP value. The distancer (5th column) calculated from the Fries transmission formula is far greater than **20 cm** separation requirement.

So the SAR report is not required

- End of the Report -