

TEST REPORT

Applicant: 8devices

Address: FCC: Antakalnio 17 - 6 Vilnius Lithuania
IC: Antakalnio g. 17-6 Vilnius Vilnius County LT-10312 Lithuania

Product Name: Noni56M2-I

FCC ID: Z9W-NON56

IC: 11468A-NON56

HVIN: NON_100M

47 CFR Part 15, Subpart E(15.407)
RSS-247 Issue 3, August 2023
RSS-Gen, Issue 5, February 2021 Amendment 2
Standard(s): ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 +
Errata to C63.10a-2024*
KDB 789033 D02 General U-NII Test Procedures New Rules
v02r01

Report Number: 2402Z106133E-RF-00AA1

Report Date: 2025/10/19

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Pedro Yun

Gavin Xu

Reviewed By: Pedro Yun

Approved By: Gavin Xu

Title: Project Engineer

Title: RF Supervisor

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL▲	6
1.4 EQUIPMENT MODIFICATIONS	6
2. SUMMARY OF TEST RESULTS	7
3. DESCRIPTION OF TEST CONFIGURATION	8
3.1 OPERATION FREQUENCY DETAIL	8
3.2 EUT OPERATION CONDITION	9
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	11
3.4 SUPPORT CABLE LIST AND DETAILS	12
3.5 BLOCK DIAGRAM OF TEST SETUP	12
3.6 TEST FACILITY	14
3.7 MEASUREMENT UNCERTAINTY	14
4. REQUIREMENTS AND TEST PROCEDURES	15
4.1 AC LINE CONDUCTED EMISSIONS	15
4.1.1 Applicable Standard	15
4.1.2 EUT Setup	17
4.1.3 EMI Test Receiver Setup	17
4.1.4 Test Procedure	18
4.1.5 Corrected Amplitude & Margin Calculation	18
4.1.6 Test Result	18
4.2 RADIATION SPURIOUS EMISSIONS	19
4.2.1 Applicable Standard	19
4.2.2 EUT Setup	21
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	23
4.2.4 Test Procedure	23
4.2.5 Corrected Result & Margin Calculation	24
4.2.6 Test Result	24
4.3 MAXIMUM CONDUCTED OUTPUT POWER	25
4.3.1 Applicable Standard	25
4.3.2 EUT Setup	26
4.3.3 Test Procedure	26
4.3.4 Test Result	26
4.4 ANTENNA REQUIREMENT	27
4.4.1 Applicable Standard	27
4.4.2 Judgment	27
4.5 ADDITIONAL REQUIREMENT	28

4.5.1 Applicable Standard	28
4.5.2 Judgment	29
5. Test DATA AND RESULTS	30
5.1 AC LINE CONDUCTED EMISSIONS.....	30
5.2 RADIATION SPURIOUS EMISSIONS.....	35
5.3 SPOT CHECK WITH MAXIMUM CONDUCTED OUTPUT POWER	57
EXHIBIT A - EUT PHOTOGRAPHS.....	60
EXHIBIT B - TEST SETUP PHOTOGRAPHS	61
EXHIBIT C - RF EXPOSURE EVALUATION	62
MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	62
EXEMPTION LIMITS FOR ROUTINE EVALUATION-RF EXPOSURE EVALUATION	64

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2402Z106133E-RF-00A	Original Report	2025/7/2
2.0	2402Z106133E-RF-00AA1	Amended Report	2025/10/19

Note: This is the amended report application which was based on the original report. The differences between them as following:

1. Add the DFS master function, which was switched by software, all other RF parameters remain unchanged.
2. Change the HVIN to **NON_100M**, Change the FVIN to **WBE.1.1**.
3. Test on the host(Model: KIT_100), shielding removed.

The change between the previous equipment and the current equipment is stated and guaranteed by the applicant. The difference between them will affect the test, we will change the test data and test photo.

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Noni56M2-I
EUT Model:	NON_100
Operation Frequency:	5150-5250MHz: 5180-5240 MHz(802.11a/n ht20/ac vht20/ax he20/be eht20) 5190-5230 MHz(802.11n ht40/ac vht40/ax he40/be eht40) 5210 MHz(802.11ac vht80/ax he80/be eht80) 5250-5350MHz: 5260-5320 MHz (802.11a/n ht20/ac vht20/ax he20/be eht20) 5270-5310 MHz(802.11n ht40/ac vht40/ax he40/be eht40) 5290 MHz(802.11ac vht80/ax he80/be eht80) 5150-5250MHz&5250-5350MHz: 5250MHz(802.11ac vht160/ax he160/be eht160) 5470-5725MHz: 5500-5720 MHz (802.11a/n ht20/ac vht20/ax he20/be eht20) 5510-5710 MHz(802.11n ht40/vht40/ax he40/be eht40) 5530-5690MHz(802.11ac vht80/ax he80/be eht80) 5570MHz(802.11ac vht160/ax he160/be eht160) 5725-5850MHz: 5745-5825 MHz (802.11a/n ht20/ac vht20/ax he20/be eht20) 5755-5795 MHz(802.11n ht40/ac vht40/ax he40/be eht40) 5775 MHz(802.11ac vht80/ax he80/be eht80)
Maximum Average Output Power (Conducted) ▲:	18.71dBm in 5150-5250 MHz Band 19.5dBm in 5250-5350 MHz Band 19.88dBm in 5470-5725 MHz Band 21.42dBm in 5725-5850 MHz Band
Maximum Average Output Power (EIRP) ▲:	22.21dBm in 5150-5250 MHz Band 23dBm in 5250-5350 MHz Band 23.38dBm in 5470-5725 MHz Band 24.92dBm in 5725-5850 MHz Band
Modulation Type:	802.11a/n/ac: OFDM-BPSK, QPSK, 16QAM, 64QAM,256QAM 802.11ax: OFDMA-BPSK, QPSK, 16QAM, 64QAM,256QAM,1024QAM 802.11be: OFDMA-BPSK, QPSK, 16QAM, 64QAM,256QAM,1024QAM,4096QAM
Rated Input Voltage:	DC 3.3V
Serial Number:	2UUQ-1(For RF Conducted Test) 2UUQ-2(For Radiated spurious emission and AC line conducted emission tests)
EUT Received Date:	2024/11/21
EUT Received Status:	Good
Note: 5600-5650 MHz was disabled by software in Canada Market.	

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.3 Antenna Information Detail ▲

Antenna	Antenna Manufacturer	Antenna Type	Input impedance (Ohm)	Frequency Range	Antenna Gain
Chain 0 &Chain 1 &Chain 2 &Chain 3	ABRACON	FPC	50	5150-5850MHz	3.5dBi
Note: The system supports maximum 4T4R CDD modes for 802.11n/ac/ax/be modes. Per KDB 662911 D01 Multiple Transmitter Output v02r01: For power measurements: CDD Mode: Array Gain = 3.5 dB (i.e., no array gain) for $N_{ANT} \leq 4$ directional gain=3.5 dBi +0dB =3.5 dBi For power spectral density (PSD) measurements: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB. directional gain=3.5 dBi +6dB =9.5dBi The design of compliance with §15.203: ☐ Unit uses a permanently attached antenna. ☒ Unit uses a unique coupling to the intentional radiator. ☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.					

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result	Note
§15.207(a) RSS-Gen Clause 8.8	AC line conducted emissions	Compliant	/
FCC§15.205& §15.209 &§15.407(b) RSS-247 Clause 6.2	Undesirable Emission& Restricted Bands Below 1G	Compliant	/
FCC§15.205& §15.209 &§15.407(b) RSS-247 Clause 6.2	Undesirable Emission& Restricted Bands Above 1G	Reporting	The test result please refer to report 2402Z106133E-RF-00A page 48-199
RSS-247 Clause 6.2.1.2	26dB attenuated below the channel power	Compliant*	The test result please refer to report 2402Z106133E-RF-00A page 200-210
FCC§15.407(a) (e) RSS-247 Clause 6.2 RSS-Gen Clause 6.7	Emission Bandwidth	Compliant*	The test result please refer to report 2402Z106133E-RF-00A page 211-244
FCC§15.407(a) RSS-247 Clause 6.2	Maximum Conducted Output Power	Reporting	The test result please refer to report 2402Z106133E-RF-00A page 245-256
FCC§15.407 (a) RSS-247 Clause 6.2	Power Spectral Density	Compliant*	The test result please refer to report 2402Z106133E-RF-00A page 257-320
§15.203 RSS-Gen Clause 6.8	Antenna Requirement	Compliant	/
RSS-247 Clause 6.4	Additional requirements	Compliant	/
FCC §1.1310&§2.1091 &§15.407 (f)	Maximum Permissible Exposure (MPE)	Compliant	/
RSS-102 Clause 6.6	Exemption Limits For Routine Evaluation-RF Exposure Evaluation	Compliant	/
Note 1: For AC line conducted emissions, the maximum output power mode and channel was tested. Note 2: For Radiated Spurious Emissions 9kHz~1GHz and 18~40GHz, the maximum output power mode and channel was tested. Compliant*: The change of the EUT does not affect the test result, please refer to the original report: 2402Z106133E-RF-00A.			

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

For 802.11a/n ht20/ac vht20/ax he20/be eht20:

5150-5250MHz Band		5250-5350 MHz Band		5470-5725 MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745
40	5200	56	5280	104	5520	153	5765
44	5220	60	5300	108	5540	157	5785
48	5240	64	5320	112	5560	161	5805
/	/	/	/	116	5580	165	5825
/	/	/	/	120**	5600	/	/
/	/	/	/	124**	5620	/	/
/	/	/	/	128**	5640	/	/
/	/	/	/	132	5660	/	/
/	/	/	/	136	5680	/	/
/	/	/	/	140	5700	/	/
/	/	/	/	144*	5720	/	/

For 802.11n ht40/ac vht40/ax he40/be eht40:

5150-5250MHz		5250-5350 MHz		5470-5725 MHz		5725-5850MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755
46	5230	62	5310	110	5550	159	5795
/	/	/	/	118**	5590	/	/
/	/	/	/	126**	5630	/	/
/	/	/	/	134	5670	/	/
/	/	/	/	142*	5710	/	/

For 802.11ac vht80/ax he80/be eht80:

5150-5250MHz		5250-5350 MHz		5470-5725 MHz		5725-5850MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	58	5290	106	5530	155	5775
/	/	/	/	122**	5610	/	/
/	/	/	/	138*	5690	/	/

For 802.11ac vht160/ax he160/be eht160:

5150-5250MHz&5250-5350 MHz				5470-5725 MHz		5725-5850MHz	
Channel		Frequency (MHz)		Channel	Frequency (MHz)	Channel	Frequency (MHz)
50		5250		114	5570	/	/

Note:

*:Additional channels cross the band 5470-5725MHz and 5725-5850 MHz, Conducted output power/ Power Spectral Density/bandwidth test with the additional channel to compliance with stricter limit of the two bands(5470-5725MHz more stricter).

**: Those channels in 5600-5650 MHz are disabled by software in Canada Market.

3.2 EUT Operation Condition

The system was configured for testing in Engineering Mode, which was provided by the manufacturer. The EUT configuration is below:

EUT Exercise Software:			QRCT4				
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲ :							
5150-5250 MHz Band:							
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting			
				Chain 0	Chain 1	Chain 2	Chain 3
802.11a	Lowest	5180	6Mbps	14	14	13	11
	Middle	5200	6Mbps	14	14	13	11
	Highest	5240	6Mbps	14	14	13	11
802.11n ht20	Lowest	5180	MCS0	11	11	11	11
	Middle	5200	MCS0	11	11	11	11
	Highest	5240	MCS0	11	11	11	11
802.11n ht40	Lowest	5190	MCS0	11	11	11	11
	Highest	5230	MCS0	11	11	11	11
802.11ac vht80	Middle	5210	MCS0	11	11	11	11
802.11be eht20	Lowest	5180	MCS0	10	10	10	10
	Middle	5200	MCS0	10	10	10	10
	Highest	5240	MCS0	10	10	10	10
802.11be eht40	Lowest	5190	MCS0	10	10	10	10
	Highest	5230	MCS0	10	10	10	10
802.11be eht80	Middle	5210	MCS0	11	11	11	11
802.11be eht160	Middle	5250	MCS0	12	12	12	12
5250-5350 MHz Band:							
802.11a	Lowest	5260	6Mbps	16	16	16	11
	Middle	5280	6Mbps	16	16	16	11
	Highest	5320	6Mbps	16	16	16	11
802.11n ht20	Lowest	5260	MCS0	10	10	10	10
	Middle	5280	MCS0	10	10	10	10
	Highest	5320	MCS0	10	10	10	10
802.11n ht40	Lowest	5270	MCS0	12	12	12	12
	Highest	5310	MCS0	10	10	10	10
802.11ac vht80	Middle	5290	MCS0	13	13	13	13
802.11ac vht160	Middle	5250	MCS0	10	10	10	10
802.11be eht20	Lowest	5260	MCS0	10	10	10	10
	Middle	5280	MCS0	10	10	10	10
	Highest	5320	MCS0	10	10	10	10
802.11be eht40	Lowest	5270	MCS0	11	11	11	11
	Highest	5310	MCS0	11	11	11	11
802.11be eht80	Middle	5290	MCS0	11	11	11	11

5470-5725 MHz Band:							
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting			
				Chain 0	Chain 1	Chain 2	Chain 3
802.11a	Lowest	5500	6Mbps	14	14	14	14
	Middle	5580	6Mbps	14	14	13	13
	Highest	5700	6Mbps	13	14	13	13
	Cross	5720	6Mbps	13	14	13	13
802.11n ht20	Lowest	5500	MCS0	8	8	8	8
	Middle	5580	MCS0	7	7	7	7
	Highest	5700	MCS0	7	7	7	7
	Cross	5720	MCS0	7	7	7	7
802.11n ht40	Lowest	5510	MCS0	9	9	9	9
	Middle	5550	MCS0	9	9	9	9
	Highest	5670	MCS0	9	9	9	9
	Cross	5710	MCS0	9	9	9	9
802.11ac vht80	Lowest	5530	MCS0	10	10	10	10
	Highest	5610	MCS0	10	10	10	10
	Cross	5690	MCS0	10	10	10	10
802.11be eht20	Lowest	5500	MCS0	7	7	7	7
	Middle	5580	MCS0	7	7	7	7
	Highest	5700	MCS0	7	7	7	7
	Cross	5720	MCS0	7	7	7	7
802.11be eht40	Lowest	5510	MCS0	7	7	7	7
	Middle	5550	MCS0	7	7	7	7
	Highest	5670	MCS0	7	7	7	7
	Cross	5710	MCS0	7	7	7	7
802.11be eht80	Lowest	5530	MCS0	8	8	8	8
	Highest	5610	MCS0	8	8	8	8
	Cross	5690	MCS0	8	8	8	8
802.11ac vht160	Middle	5570	MCS0	10	10	10	10
802.11be eht160	Middle	5570	MCS0	10	10	10	10

5725-5850 MHz Band:

Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting			
				Chain 0	Chain 1	Chain 2	Chain 3
802.11a	Lowest	5745	6Mbps	12	16	12	12
	Middle	5785	6Mbps	12	16	12	12
	Highest	5825	6Mbps	12	16	12	12
802.11n ht20	Lowest	5745	MCS0	9	9	9	9
	Middle	5785	MCS0	9	9	9	9
	Highest	5825	MCS0	9	9	9	9
802.11n ht40	Lowest	5755	MCS0	9	9	9	9
	Highest	5795	MCS0	9	9	9	9
802.11ac vht80	Middle	5775	MCS0	10	10	10	10
802.11be eht20	Lowest	5745	MCS0	9	9	9	9
	Middle	5785	MCS0	9	9	9	9
	Highest	5825	MCS0	9	9	9	9
802.11be eht40	Lowest	5755	MCS0	8	8	8	8
	Highest	5795	MCS0	8	8	8	8
802.11be eht80	Middle	5775	MCS0	7	7	7	7

Note:

1. The system support 802.11a/n ht20/n ht40/ac vht20/ac vht40/ac vht80/ac vht160/ax he20/ax he40/ax he80/ax he160/be eht20/be eht40/be eht80/be eht160, the ac vht20/ac vht40 were reduced since the identical parameters with 802.11n ht20 and ht40, ax he20/ax he40/ax he80/ax he160 were reduced since the identical parameters with be eht20/be eht40/be eht80/be eht160.
2. The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.
3. The device supports SISO in all modes, and MIMO 4T4R in 802.11n/ac/ax/be modes, per pretest, 4T4R mode was the worst mode and reported for 802.11n/ac/ax/be modes.
4. For 802.11ax/be mode, the device only supports full-RU.
5. The device both support 4*4 MIMO and 2*2 MIMO function, the power setting are the same.

3.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
ZIONCOM	Router	MB-R210-00	EMZBWR21103002
Baol	RJ45 Load	RJ45X1	F-EM-PHRJ45X1001
Lenovo	Laptop	G510	CB30920865
GlobTek	Adapter	GT-46240-2412-T2	SAA-210577-EA
Kingston	U-Disk1	32G	EMZBUD21103001
SANDisk	U-Disk2	16G	BL201026115 B
SANDisk	U-Disk3	16G	BL201026331
SANDisk	U-Disk4	16G	BL201111386N
8devices	Host	KIT_100	2UUQ-4

3.4 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	No	No	1.2	Adapter	Debug Board
RJ45 Cable	Yes	No	10	Router	Debug Board
RJ45 Cable	Yes	No	10	RJ45 Load	Debug Board
RJ45 Cable	Yes	No	10	Laptop	Debug Board


3.5 Block Diagram of Test Setup

AC line conducted emissions:




Spurious Emissions:

Below 1GHz:



Above 1GHz:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz:5.47 dB, 26.5GHz~40GHz:5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1℃
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

RSS-Gen Clause 8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT. For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 4 – AC power-line conducted emissions limits


Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ¹	56 to 46 ¹
0.5 – 5	56	46
5 – 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

- (a) Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.
- (b) Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207, RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions

4.2.1 Applicable Standard

FCC §15.407 (b);

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of – 27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of – 27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of – 27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725-5.850 GHz band:
 - (i) All emissions shall be limited to a level of – 27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
- (8) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (9) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in § 15.207.
- (10) The provisions of § 15.205 apply to intentional radiators operating under this section.
- (11) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.
- (c) The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

Frequency band 5150-5250 MHz:

RSS-247 Clause 6.2.1.2

For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

Frequency band 5250-5350 MHz:

RSS-247 Clause 6.2.2.2

For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

Frequency bands 5470-5600 MHz and 5650-5725 MHz:

RSS-247 Clause 6.2.3.2

Emissions outside the band 5470-5600 MHz and 5650-5725 MHz shall not exceed -27 dBm/MHz e.i.r.p. However, devices with bandwidth overlapping the band edge of 5725 MHz can meet the emission limit of -27 dBm/MHz e.i.r.p. at 5850 MHz instead of 5725 MHz.

Frequency band 5725-5850 MHz

RSS-247 Clause 6.2.4.3


Devices operating in the band 5725-5850 MHz with antenna gain greater than 10 dBi can have unwanted emissions that comply with either the limits in this section or in section 5.5 until six (6) months after the publication date of this standard for certification. Certified devices that do not comply with emission limits in this section shall not be manufactured, imported, distributed, leased, offered for sale or sold after April 1, 2018.

Devices operating in the band 5725-5850 MHz with antenna gain of 10 dBi or less can have unwanted emissions that comply with either the limits in this section or in section 5.5 until April 1, 2018 for certification. Certified devices that do not comply with emission limits in this section shall not be manufactured, imported, distributed, leased, offered for sale or sold after April 1, 2020. Devices operating in the band 5725-5850 MHz shall have e.i.r.p. of unwanted emissions comply with the following:


- a) 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;
- b) 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;
- c) 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and
- d) -27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.

4.2.2 EUT Setup


9kHz~30MHz:




30MHz~1GHz:



1-18GHz:



18-40GHz:



The radiated emission tests were performed in the semi-anechoic chamber, using the setup accordance with the ANSI C63.10-2020. The specification used was FCC 15.209, FCC 15.407, RSS-247, RSS-Gen limits.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	QP/AV	200Hz	1 kHz	200 Hz	QP/AV
150 kHz – 30 MHz	QP/AV	9 kHz	30 kHz	9 kHz	QP/AV
30MHz – 1000 MHz	PK	120 kHz	500 kHz	/	PK
	QP	/	/	120kHz	QP

1GHz- 40GHz:

Pre-scan:

Frequency Range	Measurement	RBW	Video B/W	Detector
Above 1 GHz	Peak	1MHz	3 MHz	PK
	AV	1MHz	5kHz	PK

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	PK	Any	1MHz	3 MHz
Ave.	PK	>98%	1MHz	10 Hz
		<98%	1MHz	≥1/T

Note: T is minimum transmission duration

If the maximized peak measured value is under the QP limit by more than 6dB, then it is unnecessary to perform an QP measurement.

If the maximized peak measured value is under the average limit, then it is unnecessary to perform an QP measurement.

4.2.4 Test Procedure

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz -1 GHz, except 9-90 kHz, 110-490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP[dBm] + 95.2$, for $d = 3$ meters.

For Radiated 18-40GHz test, which was performed at 1.0 m distance, according to C63.10, the test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.0m

Distance extrapolation Factor = $20 \log (\text{specific distance } [3m] / \text{test distance } [1.0m])$ dB = 9.54 dB

4.2.5 Corrected Result & Margin Calculation

$$E_{Log} = 20 \times \log_{10}(E_{Linear})$$

E_{Linear} is the field strength of the emission, in μ V/m

E_{Log} is the field strength of the emission, in dB μ V/m

For 9kHz-30MHz test, test distance is 3m, extrapolation limit shall be calculated using Equation:

$$E_{limit-measure} = E_{limit-Standard} + 40 \times \log_{10} (d_{standard}/d_{measure})$$

The basic equation except 18-40GHz test is as follows:

Factor = Antenna Factor + Cable Loss- Amplifier Gain

For Radiated 18-40GHz test:

Factor = Antenna Factor + Cable Loss- Distance extrapolation Factor

Result = Reading + Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Result}$$

For the spurious emission below 30MHz, the limit was convert from dB μ A/m to dB μ V/m by adding 51.5 dB

4.2.6 Test Result

Please refer to section 5.2.

4.3 Maximum Conducted Output Power

4.3.1 Applicable Standard

FCC §15.407(a) (1)(ii)

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

RSS-247 Clause 6.2.1.1

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less stringent. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

RSS-247 Clause 6.2.2.1

Devices, other than devices installed in vehicles, shall comply with the following:

- a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;
- b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

RSS-247 Clause 6.2.3.1


The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

RSS-247 Clause 6.2.4.2

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

4.3.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The cable loss of this RF cable was offset into the setting of test equipment, which was provided by manufacturer ▲.

4.3.3 Test Procedure

According to ANSI C63.10-2020 Section 12.4.3.2

Method PM-G is measurement using a gated RF average power meter.

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

4.3.4 Test Result

Please refer to section 5.3.

4.4 Antenna Requirement

4.4.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-Gen Clause 6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below). When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

4.4.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

4.5 Additional requirement

4.5.1 Applicable Standard

According to RSS-247 Clause 6.4 Additional requirement

The following requirements shall apply:

- a) The device shall automatically discontinue transmission in cases of absence of information to transmit, or operational failure. A description on how this is done shall accompany the application for equipment certification. Note that this is not intended to prohibit transmission of control or signalling information or the use of repetitive codes where required by the technology.
- b) All LE-LAN devices must contain security features to protect against modification of software by unauthorized parties.

Manufacturers must implement security features in any digitally modulated devices capable of operating in any of the frequency ranges within the 5 GHz band, so that third parties are not able to reprogram the device to operate outside the parameters for which the device was certified. The software must prevent the user from operating the transmitter with operating frequencies, output power, modulation types or other radio frequency parameters outside those that were approved for the device. Manufacturers may use various means, including the use of a private network that allows only authenticated users to download software, electronic signatures in software or coding in hardware that is decoded by software to verify that new software can be legally loaded into a device to meet these requirements and must describe the methods in their application for equipment certification.

Manufacturers must take steps to ensure that DFS functionality cannot be disabled by the operator of the LE-LAN device.

- c) The user manual for LE-LAN devices shall contain instructions related to the restrictions mentioned in the above sections, namely that:
 - i. the device for operation in the band 5150–5250 MHz is only for indoor use to reduce the potential for harmful interference to co-channel mobile satellite systems;⁴
 - ii. for devices with detachable antenna(s), the maximum antenna gain permitted for devices in the bands 5250-5350 MHz and 5470-5725 MHz shall be such that the equipment still complies with the e.i.r.p. limit;
 - iii. for devices with detachable antenna(s), the maximum antenna gain permitted for devices in the band 5725-5850 MHz shall be such that the equipment still complies with the e.i.r.p. limits as appropriate; and
 - iv. where applicable, antenna type(s), antenna models(s), and worst-case tilt angle(s) necessary to remain compliant with the e.i.r.p. elevation mask requirement set forth in section 6.2.2.3 shall be clearly indicated.

4.5.2 Judgment

RSS-247 Clause 6.4 a):

The device shall automatically discontinue transmission in cases of absence of information to transmit, or operational failure. Please refer to the declaration

RSS-247 Clause 6.4 b):

The devices must contain security features to protect against modification of software by unauthorized parties. Please refer to the declaration

RSS-247 Clause 6.4 c):

i). The device is only for indoor use.

ii). The device's the antenna uses a unique coupling to the intentional radiator , and operates on 5250-5350MHz/5470-5725MHz meet the EIRP limit, please refer to the power test result.

iii). The antenna uses a unique coupling to the intentional radiator, and all the EIPR compliance with RSS-247 requirement. Please refer to the conducted output power test result.

iv). The device EIRP less than 200mW(23 dBm) for 5250-5350MHz.

5. Test DATA AND RESULTS

5.1 AC Line Conducted Emissions

Serial Number:	2UUQ-2	Test Date:	2025/04/29~2025/10/17
Test Site:	CE	Test Mode:	Transmitting
Tester:	Yolo Fan, Lane Sun	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.1~27.3	Relative Humidity: (%)	57~63	ATM Pressure: (kPa)	100.8~101.2
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2024/9/5	2025/9/4
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2024/9/5	2025/9/4
R&S	EMI Test Receiver	ESCI	101121	2024/9/5	2025/9/4
R&S	LISN	ENV216	101614	2025/6/25	2026/6/24
Unknown	Coaxial Cable	RG 142	C-0200-05	2025/5/6	2026/5/5
R&S	EMI Test Receiver	ESCI	100224	2025/6/25	2026/6/24
Audix	Test Software	E3	191218 V9	N/A	N/A


* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Note: 802.11ac80 5775MHz was tested.

Project No.: 2402Z106133E-RF-A1
Port: Line
Test Mode: Transmitting
Note: IF B/W 9KHz PK/AV


Serial No.: 2UUQ-2
Tester: Yolo Fan



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.155	41.86	10.76	52.62	65.75	13.13	QP
2	0.155	21.48	10.76	32.24	55.75	23.51	Average
3	0.178	37.32	10.81	48.13	64.58	16.45	QP
4	0.178	18.13	10.81	28.94	54.58	25.64	Average
5	0.209	33.20	10.85	44.05	63.23	19.18	QP
6	0.209	17.22	10.85	28.07	53.23	25.16	Average
7	0.238	28.85	10.84	39.69	62.16	22.47	QP
8	0.238	13.18	10.84	24.02	52.16	28.14	Average
9	0.296	23.29	10.82	34.11	60.35	26.24	QP
10	0.296	11.93	10.82	22.75	50.35	27.60	Average
11	1.323	10.22	10.84	21.06	56.00	34.94	QP
12	1.323	0.67	10.84	11.51	46.00	34.49	Average

Project No.: 2402Z106133E-RF-A1
Port: neutral
Test Mode: Transmitting
Note: IF B/W 9KHz PK/AV

Serial No.: 2UUQ-2
Tester: Yolo Fan




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.153	41.62	10.85	52.47	65.84	13.37	QP
2	0.153	21.31	10.85	32.16	55.84	23.68	Average
3	0.167	38.20	10.85	49.05	65.12	16.07	QP
4	0.167	18.68	10.85	29.53	55.12	25.59	Average
5	0.195	35.00	10.85	45.85	63.84	17.99	QP
6	0.195	17.31	10.85	28.16	53.84	25.68	Average
7	0.213	32.15	10.85	43.00	63.10	20.10	QP
8	0.213	16.37	10.85	27.22	53.10	25.88	Average
9	0.264	25.83	10.81	36.64	61.30	24.66	QP
10	0.264	12.61	10.81	23.42	51.30	27.88	Average
11	0.316	21.60	10.78	32.38	59.80	27.42	QP
12	0.316	9.95	10.78	20.73	49.80	29.07	Average
13	1.333	13.42	10.87	24.29	56.00	31.71	QP
14	1.333	5.69	10.87	16.56	46.00	29.44	Average

5G Wifi is transmitted simultaneously with 6G Wifi:
802.11ac80 5290MHz+802.11be320 6265MHz was tested:

Project No.: 2402Z106133E-RF-A1
Port: Line
Test Mode: Transmitting
IF B/W 9kHz PK/AV


Serial No.: 2UUQ-2
Tester: Lane Sun
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.150	44.00	11.20	55.20	65.98	10.78	QP
2	0.150	20.79	11.20	31.99	55.98	23.99	Average
3	0.155	43.04	11.16	54.20	65.73	11.53	QP
4	0.155	22.76	11.16	33.92	55.73	21.81	Average
5	0.157	42.00	11.14	53.14	65.60	12.46	QP
6	0.157	20.95	11.14	32.09	55.60	23.51	Average
7	0.170	41.00	11.04	52.04	64.94	12.90	QP
8	0.170	18.80	11.04	29.84	54.94	25.10	Average
9	0.195	36.00	10.84	46.84	63.82	16.98	QP
10	0.195	16.46	10.84	27.30	53.82	26.52	Average
11	0.277	29.00	10.75	39.75	60.92	21.17	QP
12	0.277	12.90	10.75	23.65	50.92	27.27	Average

Project No.: 2402Z106133E-RF-A1
Port: neutral
Test Mode: Transmitting
IF B/W 9kHz PK/AV

Serial No.: 2UUQ-2
Tester: Lane Sun
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.153	40.12	10.71	50.83	65.86	15.03	QP
2	0.153	20.19	10.71	30.90	55.86	24.96	Average
3	0.164	38.20	10.76	48.96	65.27	16.31	QP
4	0.164	19.44	10.76	30.20	55.27	25.07	Average
5	0.168	36.84	10.77	47.61	65.08	17.47	QP
6	0.168	18.90	10.77	29.67	55.08	25.41	Average
7	0.178	35.65	10.81	46.46	64.58	18.12	QP
8	0.178	17.67	10.81	28.48	54.58	26.10	Average
9	0.203	31.31	10.90	42.21	63.49	21.28	QP
10	0.203	14.59	10.90	25.49	53.49	28.00	Average
11	0.234	27.67	10.85	38.52	62.30	23.78	QP
12	0.234	12.19	10.85	23.04	52.30	29.26	Average

5.2 Radiation Spurious Emissions

1) 9kHz - 1GHz

Serial Number:	2UUQ-2	Test Date:	2025/4/23~2025/10/16
Test Site:	Chamber 10m	Test Mode:	Transmitting
Tester:	Zoo Zou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.4~25.9	Relative Humidity: (%)	44~50	ATM Pressure: (kPa)	100.5~100.7
----------------------	-----------	---------------------------	-------	---------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Sunol Sciences	Hybrid Antenna	JB3	A060611-1	2023/9/6	2026/9/5
Narda	Coaxial Attenuator	779-6dB	04269	2023/9/6	2026/9/5
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-04	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2024/7/1	2025/6/30
Sonoma	Amplifier	310N	185914	2024/8/26	2025/8/25
R&S	EMI Test Receiver	ESCI	100224	2024/8/26	2025/8/25
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-04	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2025/7/1	2026/6/30
Sonoma	Amplifier	310N	185914	2025/8/25	2026/8/24
R&S	EMI Test Receiver	ESR3	102453	2025/6/25	2026/6/24
Audix	Test Software	E3	191218 V9	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.


Note: 802.11ac80 5775MHz was tested.

9kHz~30MHz

Three antenna orientations (parallel, perpendicular, and ground-parallel) was measured, the worst orientations was below:

Project No.: 2402Z106133E-RF-A1
Polarization: Parallel
Test Mode: Transmitting
Note:
RBW:200Hz VBW:1kHz


Serial No.: 2UUQ-2
Tester: Zoo Zou



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	0.01	9.32	53.02	62.34	128.00	65.66	Peak
2	0.02	5.56	49.05	54.61	120.02	65.41	Peak
3	0.03	20.29	46.67	66.96	116.74	49.78	Peak
4	0.07	4.62	40.41	45.03	110.57	65.54	Peak
5	0.08	4.72	39.62	44.34	110.01	65.67	Peak
6	0.11	1.76	34.65	36.41	106.50	70.09	Peak

Project No.: 2402Z106133E-RF-A1
Polarization: Parallel
Test Mode: Transmitting
Note:
RBW:9kHz VBW:30kHz

Serial No.: 2UUQ-2
Tester: Zoo Zou




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	0.67	15.84	21.78	37.62	71.05	33.43	Peak
2	0.80	15.77	20.56	36.33	69.45	33.12	Peak
3	0.98	19.34	16.99	36.33	67.66	31.33	Peak
4	1.14	18.74	15.96	34.70	66.35	31.65	Peak
5	1.22	17.76	15.57	33.33	65.69	32.36	Peak
6	1.37	19.31	14.90	34.21	64.66	30.45	Peak

5G Wifi is transmitted simultaneously with 6G Wifi:
802.11ac80 5290MHz+802.11be320 6265MHz was tested:

Project No.: 2402Z106133E-RF-A1
Polarization: Parallel
Test Mode: Transmitting
Note:
RBW:200Hz VBW:1kHz


Serial No.: 2UUQ-2
Tester: Zoo Zou



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	0.019	6.40	53.85	60.25	122.09	61.84	Peak
2	0.022	5.91	53.32	59.23	120.94	61.71	Peak
3	0.024	5.31	52.87	58.18	119.97	61.79	Peak
4	0.035	16.94	50.62	67.56	116.63	49.07	Peak
5	0.048	3.80	48.13	51.93	113.92	61.99	Peak
6	0.071	13.64	44.25	57.89	110.59	52.70	Peak

Project No.: 2402Z106133E-RF-A1
Polarization: Parallel
Test Mode: Transmitting
Note:
RBW:9kHz VBW:30kHz

Serial No.: 2UUQ-2
Tester: Zoo Zou




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	0.617	15.78	25.15	40.93	71.75	30.82	Peak
2	0.641	15.93	24.91	40.84	71.42	30.58	Peak
3	0.683	15.93	24.47	40.40	70.86	30.46	Peak
4	0.788	15.76	23.47	39.23	69.59	30.36	Peak
5	0.826	15.35	22.82	38.17	69.17	31.00	Peak
6	0.943	16.40	20.39	36.79	67.99	31.20	Peak

30MHz-1GHz

Project No.: 2402Z106133E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note:
RBW:120kHz VBW:500kHz


Serial No.: 2UUQ-2
Tester: Zoo Zou



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	156.10	47.70	-11.11	36.59	43.50	6.91	QP
2	483.96	44.80	-4.62	40.18	46.00	5.82	QP
3	515.00	44.30	-4.02	40.28	46.00	5.72	QP
4	895.24	37.30	1.36	38.66	46.00	7.34	QP
5	903.00	38.81	1.44	40.25	46.00	5.75	QP
6	912.70	39.90	1.57	41.47	46.00	4.53	QP
7	922.40	39.10	1.69	40.79	46.00	5.21	QP
8	934.04	37.20	1.83	39.03	46.00	6.97	QP

Project No.: 2402Z106133E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note:
RBW:120kHz VBW:500kHz

Serial No.: 2UUQ-2
Tester: Zoo Zou




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	64.92	51.60	-16.50	35.10	40.00	4.90	QP
2	76.56	52.31	-16.25	36.06	40.00	3.94	QP
3	84.32	48.90	-16.62	32.28	40.00	7.72	QP
4	113.42	48.10	-10.87	37.23	43.50	6.27	QP
5	908.82	37.40	1.52	38.92	46.00	7.08	QP
6	914.64	37.59	1.60	39.19	46.00	6.81	QP

5G Wifi is transmitted simultaneously with 6G Wifi:
802.11ac80 5290MHz+802.11be320 6265MHz was tested:

Project No.: 2402Z106133E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note:
RBW:120kHz VBW:500kHz

Serial No.: 2UUQ-2
Tester: Zoo Zou



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	113.42	48.50	-10.87	37.63	43.50	5.87	QP
2	150.28	51.20	-11.06	40.14	43.50	3.36	QP
3	483.96	47.20	-4.62	42.58	46.00	3.42	QP
4	499.48	47.10	-4.29	42.81	46.00	3.19	QP
5	515.00	45.80	-4.02	41.78	46.00	4.22	QP
6	906.88	38.50	1.50	40.00	46.00	6.00	QP
7	920.46	39.40	1.66	41.06	46.00	4.94	QP

Project No.: 2402Z106133E-RF-A1

Serial No.: 2UUQ-2


Polarization: Vertical

Tester: Zoo Zou

Test Mode: Transmitting

Note:

RBW:120kHz VBW:500kHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	64.92	51.70	-16.50	35.20	40.00	4.80	QP
2	76.56	53.11	-16.25	36.86	40.00	3.14	QP
3	113.42	50.10	-10.87	39.23	43.50	4.27	QP
4	150.28	47.70	-11.06	36.64	43.50	6.86	QP
5	483.96	44.22	-4.62	39.60	46.00	6.40	Peak
6	914.64	36.59	1.60	38.19	46.00	7.81	QP

2) 1-40GHz:

Serial Number:	2UUQ-2	Test Date:	2025/04/16~2025/10/18
Test Site:	Chamber B	Test Mode:	Transmitting
Tester:	Colin Yang, Leo Xiao, Alan Xie	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.5~27.7	Relative Humidity: (%)	29~43	ATM Pressure: (kPa)	100.6~100.8
----------------------	-----------	---------------------------	-------	---------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2023/2/22	2026/2/21
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-01 1302	2023/2/22	2026/2/21
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2024/11/17	2025/11/16
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2024/12/9	2025/12/8
AH	Preamplifier	PAM-0118P	469	2025/4/11	2026/4/10
AH	Preamplifier	PAM-1840VH	191	2024/9/5	2025/9/4
AH	Preamplifier	PAM-1840VH	191	2025/7/31	2026/7/30
R&S	Spectrum Analyzer	FSV40	101944	2024/9/6	2025/9/5
R&S	Spectrum Analyzer	FSV40	101944	2025/8/8	2026/8/7
Audix	Test Software	E3	191218 V9	N/A	N/A
Decentest	Multiplex Switch Test Control Set & Filter Switch Unit	DT7220SCU & DT7220FCU	DC79902 & DC79905	2024/8/27	2025/8/26
Decentest	Multiplex Switch Test Control Set & Filter Switch Unit	DT7220SCU & DT7220FCU	DC79902 & DC79905	2025/8/25	2026/8/24

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.


1-18GHz:

5150-5250MHz: Chain 2

802.11a mode, High Channel, Horizontal

Project No.: 2402Z106133E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain2
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2UJQ-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	3816.00	53.62	-5.71	47.91	74.00	26.09	Peak
2	5968.50	51.35	-0.37	50.98	68.20	17.22	Peak

802.11a mode, High Channel, Vertical

Project No.: 2402Z106133E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain2
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 2UJQ-2
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	3999.70	52.79	-5.37	47.42	74.00	26.58	Peak
2	6310.80	51.24	-0.39	50.85	68.20	17.35	Peak

Project No.: 2402Z106133E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain2
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 2UJQ-2
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10480.00	46.01	2.93	48.94	68.20	19.26	Peak
2	15720.00	47.48	3.43	50.91	74.00	23.09	Peak
3	17990.80	47.64	11.45	59.09	74.00	14.91	Peak
4	17990.80	36.14	11.45	47.59	54.00	6.41	Average

Project No.: 2402Z106133E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain2
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 2UJQ-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10480.00	46.60	2.93	49.53	68.20	18.67	Peak
2	15720.00	51.58	3.43	55.01	74.00	18.99	Peak
3	15720.00	43.33	3.43	46.76	54.00	7.24	Average
4	17995.40	48.61	11.49	60.10	74.00	13.90	Peak
5	17995.40	36.34	11.49	47.83	54.00	6.17	Average

5250-5350MHz : MIMO Mode:**802.11 ac vht80 mode, Middle Channel, Horizontal**

Project No.: 2402Z106133E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2A middle channel 5290MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2UQ-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4659.70	51.51	-4.01	47.50	74.00	26.50	Peak
2	6490.10	51.04	-0.11	50.93	68.20	17.27	Peak

802.11 ac vht80 mode, Middle Channel, Vertical

Project No.: 2402Z106133E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2A middle channel 5290MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 2UQ-2
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5006.20	50.43	-2.94	47.49	74.00	26.51	Peak
2	6484.60	50.46	-0.12	50.34	68.20	17.86	Peak

Project No.: 2402Z106133E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2A middle channel 5290MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 2UQ-2
Tester: Colin Yang







No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10580.00	48.48	2.89	51.37	68.20	16.83	Peak
2	15870.00	47.54	3.41	50.95	74.00	23.05	Peak
3	17970.10	48.76	11.29	60.05	74.00	13.95	Peak
4	17970.10	36.14	11.29	47.43	54.00	6.57	Average

Project No.: 2402Z106133E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2A middle channel 5290MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 2UQ-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10580.00	49.45	2.89	52.34	68.20	15.86	Peak
2	15870.00	52.30	3.41	55.71	74.00	18.29	Peak
3	15870.00	43.55	3.41	46.96	54.00	7.04	Average
4	17995.40	47.74	11.49	59.23	74.00	14.77	Peak
5	17995.40	36.40	11.49	47.89	54.00	6.11	Average

5470-5725MHz: MIMO Mode:**802.11 ac vht80 mode, Low Channel, Horizontal****802.11 ac vht80 mode, Low Channel, Vertical**

5725-5850MHz: MIMO Mode:**802.11 ac vht80 mode, Middle Channel, Horizontal**

Project No.: 2402Z106133E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac80_U-NII-3 middle channel 5775MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2UJQ-2
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5378.00	49.85	-1.39	48.46	74.00	25.54	Peak

802.11 ac vht80 mode, Middle Channel, Vertical

Project No.: 2402Z106133E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac80_U-NII-3 middle channel 5775MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 2UJQ-2
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5417.60	50.41	-1.33	49.08	74.00	24.92	Peak

Project No.: 2402Z106133E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac80_U-NII-3 middle channel 5775MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 2UJQ-2
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11550.00	46.53	4.08	50.61	74.00	23.39	Peak
2	17325.00	47.20	7.26	54.46	68.20	13.74	Peak
3	17983.90	47.83	11.40	59.23	74.00	14.77	Peak
4	17983.90	36.29	11.40	47.69	54.00	6.31	Average

Project No.: 2402Z106133E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac80_U-NII-3 middle channel 5775MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz





Serial No.: 2UJQ-2
Tester: Leo Xiao







No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11550.00	48.89	4.08	52.97	74.00	21.03	Peak
2	17320.00	48.31	7.25	55.56	68.20	12.64	Peak
3	17917.20	48.10	10.91	59.01	74.00	14.99	Peak
4	17917.20	36.47	10.91	47.38	54.00	6.62	Average

18-40GHz:


No Emission was detected in the range 18-40GHz, test was performed on the mode and channel which with the maximum power.

802.11 ac vht80 mode, Middle Channel, Horizontal**802.11 ac vht80 mode, Middle Channel, Vertical**

**Bandedge:
5150-5250MHz:****802.11 a mode 5180MHz Chain 2, Horizontal****802.11 a mode 5180MHz Chain 2, Vertical****802.11 a mode 5240MHz Chain 2, Horizontal****802.11 a mode 5240MHz Chain 2, Vertical**

5250-5350MHz:**802.11 ac80 mode 5290MHz, Horizontal**


Project No.: 2402Z106133E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Serial No.: 20UQ-2
Tester: Alan Xie
Note: 802.11ac80_U-NII-2A middle channel 5290MHz
Peak: RBW:10Hz, VBW:30Hz Ave:RBW:10Hz, VBW:5kHz







No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5143.14	49.78	7.43	57.21	74.00	16.79	Peak
2	5143.14	36.86	7.43	44.29	54.00	9.71	Average
3	5150.00	48.14	7.47	55.61	74.00	18.39	Peak
4	5150.00	36.68	7.47	44.15	54.00	9.85	Average
5	5350.00	47.82	8.01	55.83	74.00	18.17	Peak
6	5350.00	36.99	8.01	45.00	54.00	9.00	Average
7	5384.64	50.41	7.98	58.39	74.00	15.61	Peak
8	5384.64	37.02	7.98	45.00	54.00	9.00	Average

802.11 ac80 mode 5290MHz, Vertical

Project No.: 2402Z106133E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Serial No.: 20UQ-2
Tester: Alan Xie
Note: 802.11ac80_U-NII-2A middle channel 5290MHz
Peak: RBW:10Hz, VBW:30Hz Ave:RBW:10Hz, VBW:5kHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5137.56	49.86	7.38	57.24	74.00	16.76	Peak
2	5137.56	37.14	7.38	44.52	54.00	9.48	Average
3	5150.00	47.91	7.47	55.38	74.00	18.62	Peak
4	5150.00	37.26	7.47	44.73	54.00	9.27	Average
5	5350.00	50.07	8.01	58.08	74.00	15.92	Peak
6	5350.00	39.40	8.01	47.41	54.00	6.59	Average
7	5350.56	52.34	8.00	60.34	74.00	13.66	Peak
8	5350.56	40.60	8.00	48.60	54.00	5.40	Average

5470-5725MHz:**802.11 ac80 mode 5530MHz, Horizontal****802.11 ac80 mode 5530MHz, Vertical****802.11 ac80 mode 5610MHz, Horizontal****802.11 ac80 mode 5610MHz, Vertical**

5725-5850MHz:**802.11 ac80 mode 5775MHz, Horizontal**

Project No.: 2402Z106133E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac80_U-NII-3 middle channel 5775MHz
Peak:RBW:10Hz,VBW:30Hz

Serial No.: 2U0Q-2
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5650.00	48.49	8.82	57.31	68.20	10.89	Peak
2	5700.00	50.45	8.85	59.30	105.20	45.90	Peak
3	5720.00	55.08	8.91	63.99	110.00	46.01	Peak
4	5725.00	55.28	8.93	64.21	122.20	57.99	Peak
5	5850.00	48.60	9.10	57.70	122.20	64.50	Peak
6	5855.00	48.08	9.12	57.20	110.80	53.60	Peak
7	5875.00	47.57	9.16	56.73	105.20	48.47	Peak
8	5925.00	47.05	9.24	56.29	68.20	11.91	Peak


802.11 ac80 mode 5775MHz, Vertical

Project No.: 2402Z106133E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac80_U-NII-3 middle channel 5775MHz
Peak:RBW:10Hz,VBW:30Hz

Serial No.: 2U0Q-2
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5650.00	49.34	8.82	58.16	68.20	10.04	Peak
2	5700.00	55.94	8.85	64.79	105.20	40.41	Peak
3	5720.00	61.19	8.91	70.10	110.00	40.70	Peak
4	5725.00	63.24	8.93	72.17	122.20	50.03	Peak
5	5850.00	52.60	9.10	61.70	122.20	60.50	Peak
6	5855.00	50.57	9.12	59.69	110.80	51.11	Peak
7	5875.00	48.89	9.16	58.05	105.20	47.15	Peak
8	5925.00	47.88	9.24	57.12	68.20	11.08	Peak

**5G Wifi is transmitted simultaneously with 6G Wifi:
1-18GHz:**

Horizontal


Project No.: 2402Z106133E-RF-A1 Serial No.: 2UJQ-2
Polarization: Horizontal Tester: Alan Xie
Test Mode: Transmitting
Note: 802.11ac@0_U-NII-2A middle channel 5290MHz; 802.11be320_U-NII 5 middle Channel 6265MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	12530.00	45.74	3.95	49.69	74.00	24.31	Peak
2	17980.00	46.77	11.00	57.77	74.00	16.23	Peak
3	17980.00	35.35	11.00	46.35	54.00	7.65	Average

Vertical

Project No.: 2402Z106133E-RF-A1 Serial No.: 2UJQ-2
Polarization: Vertical Tester: Alan Xie
Test Mode: Transmitting
Note: 802.11ac@0_U-NII-2A middle channel 5290MHz; 802.11be320_U-NII 5 middle Channel 6265MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	12530.00	45.83	3.95	49.78	74.00	24.22	Peak
2	17980.00	47.53	10.92	58.45	74.00	15.55	Peak
3	17980.00	35.62	10.92	46.54	54.00	7.46	Average

18-40GHz:

Horizontal

Project No.: 2402Z106133E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2A middle channel 5290MHz; 802.11be320_U-NII 5 middle Channel 6265MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2UUQ-2
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	19363.40	46.49	0.20	46.69	74.00	27.31	Peak

Vertical

Project No.: 2402Z106133E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2A middle channel 5290MHz; 802.11be320_U-NII 5 middle Channel 6265MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 2UUQ-2
Tester: Alan Xie



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	19820.70	47.49	0.21	47.70	74.00	26.30	Peak

Project No.: 2402Z106133E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2A middle channel 5290MHz; 802.11be320_U-NII 5 middle Channel 6265MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 2UUQ-2
Tester: Alan Xie



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	35812.30	46.75	7.57	54.32	88.20	33.88	Peak
2	38990.20	43.72	9.23	52.95	74.00	21.05	Peak

Project No.: 2402Z106133E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2A middle channel 5290MHz; 802.11be320_U-NII 5 middle Channel 6265MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2UUQ-2
Tester: Alan Xie



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	37111.00	47.43	7.62	55.05	88.20	33.15	Peak
2	38701.30	43.76	8.88	52.64	74.00	21.36	Peak

5.3 Spot Check With Maximum Conducted Output Power

Serial No.:	2UUQ-1	Test Date:	2025/5/24
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cooper Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	25	Relative Humidity: (%)	57	ATM Pressure: (kPa)	100.9
-----------------------	----	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM503	2024/06/07	2025/06/06
Anritsu	Microwave Peak Power Sensor	MA24418A	12618	2024/08/27	2025/08/26

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

5150-5250MHz

Mode	Antenna	Test Frequency (MHz)	Average Output Power (dBm)	FCC Limit (dBm)	EIRP (dBm)	RSS 247 EIRP Limit (dBm)
802.11a	Chain 0	5180	14.37	30	17.87	22.27
		5200	14.34	30	17.84	22.29
		5240	13.98	30	17.48	22.29
	Chain 1	5180	15.33	30	18.83	22.27
		5200	14.87	30	18.37	22.29
		5240	14.70	30	18.20	22.29
	Chain 2	5180	14.82	30	18.32	22.27
		5200	15.23	30	18.73	22.29
		5240	15.34	30	18.84	22.29
	Chain 3	5180	14.58	30	18.08	22.27
		5200	14.28	30	17.78	22.29
		5240	14.93	30	18.43	22.29

Note:

The device is a Indoor AP.

5250-5350MHz

Mode	Antenna	Test Frequency (MHz)	Average Output Power (dBm)	FCC Limit (dBm)	RSS 247 Limit (dBm)	EIRP (dBm)	RSS 247 EIRP Limit (dBm)
802.11ac80	Chain 0	5290	12.49	24	24	15.99	30
	Chain 1	5290	13.68	24	24	17.18	30
	Chain 2	5290	14.27	24	24	17.77	30
	Chain 3	5290	12.56	24	24	16.06	30
	Chain 0+ Chain 1+ Chain 2+ Chain 3	5290	19.34	24	24	22.84	30

5150-5250MHz&5250-5350MHz

Mode	Antenna	Test Frequency (MHz)	Average Output Power (dBm)	FCC Limit (dBm)	RSS 247 Limit (dBm)	EIRP (dBm)	RSS 247 EIRP Limit (dBm)
802.11be160	Chain 0	5250	12.31	24	24	15.81	23
	Chain 1	5250	12.02	24	24	15.52	23
	Chain 2	5250	13.18	24	24	16.68	23
	Chain 3	5250	13.36	24	24	16.86	23
	Chain 0 +Chain 1 +Chain 2 +Chain 3	5250	18.77	24	24	22.27	23

5470-5725MHz

Mode	Antenna	Test Frequency (MHz)	Average Output Power (dBm)	FCC Limit (dBm)	RSS 247 Limit (dBm)	EIRP (dBm)	RSS 247 EIRP Limit (dBm)
802.11ac80	Chain 0	5530	13.14	24	24	16.64	30
		5610	13.42	24	24	16.92	30
		5690	13.00	24	24	16.50	30
	Chain 1	5530	13.64	24	24	17.14	30
		5610	12.84	24	24	16.34	30
		5690	12.69	24	24	16.19	30
	Chain 2	5530	14.46	24	24	17.96	30
		5610	13.94	24	24	17.44	30
		5690	13.38	24	24	16.88	30
	Chain 3	5530	13.96	24	24	17.46	30
		5610	14.73	24	24	18.23	30
		5690	13.73	24	24	17.23	30
	Chain 0 +Chain 1 +Chain 2 +Chain 3	5530	19.85	24	24	23.35	30
		5610	19.81	24	24	23.31	30
		5690	19.24	24	24	22.74	30

5725-5850MHz

Mode	Antenna	Test Frequency (MHz)	Average Output Power (dBm)	FCC&RSS 247 Limit (dBm)	Verdict
802.11ac80	Chain 0	5775	14.88	30	Pass
	Chain 1	5775	15.67	30	Pass
	Chain 2	5775	14.92	30	Pass
	Chain 3	5775	16.14	30	Pass
	Chain 0+Chain 1 +Chain 2+Chain 3	5775	21.46	30	Pass

Note: The Spot Check data were similar to the original data.

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2402Z106133E-RF-A1-EXP EUT EXTERNAL PHOTOGRAPHS and 2402Z106133E-RF-A1-INP EUT INTERNAL PHOTOGRAPHS.

EXHIBIT B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2402Z106133E-RF-00AA1-TSP TEST SETUP PHOTOGRAPHS.

EXHIBIT C - RF EXPOSURE EVALUATION

Maximum Permissible Exposure (MPE)

Applicable Standard

According to subpart §1.1310, and 15.407(f) systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency (MHz)	EIRP including Tune-up Tolerance [▲]		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBm)	(mW)			
5150-5250	22.5	177.83	20.00	0.035	1.0
5250-5350	23	199.53	20.00	0.040	1.0
5470-5725	23.5	223.87	20.00	0.045	1.0
5725-5850	25.0	316.23	20.00	0.063	1.0
5925-6425	13.5	22.39	20.00	0.004	1.0
6425-6525	15.0	31.62	20.00	0.006	1.0
6525-6875	16.0	39.81	20.00	0.008	1.0
6875-7125	15.5	35.48	20.00	0.007	1.0

Note: The EIRP including Tune-up Tolerance was provided by manufacturer.

For Simultaneous transmission:

5G Wifi and 6G Wifi can transmit simultaneously:

$$\text{EIRP}_{5\text{G Wifi}}/\text{Limit}_{5\text{G Wifi}} + \text{EIRP}_{6\text{G Wifi}}/\text{Limit}_{6\text{G Wifi}}$$

$$=0.063/1.0+0.008/1.0$$

$$=0.071$$

$$<1.0$$

Result: The device meet FCC MPE at 20 cm distance

Exemption Limits For Routine Evaluation-RF Exposure Evaluation

Applicable Standard

RSS-102, Issue 6, Clause 6.6:

Field reference level (FRL) exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm (i.e. mobile devices), except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Calculated Data:

Frequency (MHz)	EIRP including Tune-up Tolerance [▲]		Exemption limits (mW)
	(dBm)	(mW)	
5150-5250	22.5	177.83	4507
5250-5350	23	199.53	4567
5470-5725	23.5	223.87	4697
5725-5850	25.0	316.23	4845
5925-6425	13.5	22.39	4961
6425-6525	15.0	31.62	5000
6525-6875	16.0	39.81	5000
6875-7125	15.5	35.48	5000

Note: The EIRP including Tune-up Tolerance was provided by manufacturer.

For Simultaneous transmission:

5G Wifi and 6G Wifi can transmit simultaneously:

$$\text{EIRP}_{5\text{G Wifi}}/\text{Limit}_{5\text{G Wifi}} + \text{EIRP}_{6\text{G Wifi}}/\text{Limit}_{6\text{G Wifi}}$$

$$=316.23/4845+39.81/5000$$

$$=0.073$$

$$<1.0$$

Result: So the device is compliance with the exemption from Routine Evaluation Limits –RF exposure Evaluation.

******* END OF REPORT *******