

RF Exposure Analysis

FCC ID: ZB9-10603

Analysis for FCC portable use

Standalone SAR test exclusion considerations are defined in KDB 447498D01 (v06) Chapter 4.3.1 where the 1-g head or body and 10-g extremity SAR exclusion threshold is defined by the following formula:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

For the Tom and Floor the maximum conducted output power is 5.0 dBm (3.16mW).

Applying the above data using the given KDB 447498 D01 formula, and minimum separation distance of 5mm, the following results:

$(3.16\text{mW} / 5 \text{ mm}) \times \sqrt{2.45 \text{ GHz}} = 1.0$ (i.e.: ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR)

Conclusion

This demonstrates the Tom and Floor meets the criteria for 1-g head/ body and 10-g extremity SAR test exemption.

Signature:  Date: 28 November 2019