

SHENZHEN DNS INDUSTRIES CO., LTD.

TEST REPORT

SCOPE OF WORK

FCC TESTING – SH-207AG, ASPBSTC-0526, NFC3-207A1,
NFC3-207A2, NFC3-207G1, NFC3-207G2, NFC3-207AG

REPORT NUMBER

251223010SZN-001

ISSUE DATE

02 March 2026

[REVISED DATE]

[-----]

PAGES

34

DOCUMENT CONTROL NUMBER

FCC ID 247_b

© 2017 INTERTEK




Intertek Report No.: 251223010SZN-001

SHENZHEN DNS INDUSTRIES CO., LTD.Application
For
Certification**FCC ID: ZBC-SH207AG****Smart Tag / Smart Tag Card****Model:****SH-207AG, ASPBSTC-0526, NFC3-207A1, NFC3-207A2, NFC3-207G1, NFC3-207G2,
NFC3-207AG****Brand Name: DNS, BAUHN, NOVOO****2.4GHz Transceiver**

Report No.: 251223010SZN-001

We hereby certify that the sample of the above item is considered to comply with the
requirements of FCC Part 15, Subpart C for Intentional Radiator,
mention 47 CFR [10-1-24]

Prepared and Checked by:**Molly Wu
Engineer****Approved by:**

**Johnny Wang
Project Engineer
Date: 02 March 2026**

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Service Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen.

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

MEASUREMENT/TECHNICAL REPORT

This report concerns (check one:) Original Grant ☒ Change ID _____

Equipment Type: DTS - Part 15 Digital Transmission System

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes _____ No ☒

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes _____ No ☒

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [10-1-24 Edition] provision.

Report prepared by:

Molly Wu
Intertek Testing Services Shenzhen Ltd. Longhua Branch
101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing
Community, GuanHu Subdistrict, LongHua District, Shenzhen.
Tel: (86 755) 8614 0669 Fax: (86 755) 8601 6661

Table of Contents

1.0	<u>Summary of Test Results</u>	4
2.0	<u>General Description</u>	5
2.1	Product Description	5
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology	5
2.4	Test Facility	6
3.0	<u>System Test Configuration</u>	7
3.1	Justification	7
3.2	EUT Exercising Software	7
3.3	Special Accessories	7
3.4	Measurement Uncertainty	8
3.5	Equipment Modification	8
3.6	Support Equipment List and Description	8
4.0	<u>Test Results</u>	9
4.1	Radiated Test Result	9
4.1.1	Field Strength Calculation	9
4.1.2	Radiated Emission Configuration Photograph	10
4.1.3	Radiated Emission	10
4.1.4	Transmitter Spurious Emissions (Radiated)	13
4.2	Maximum Conducted Output Power at Antenna Terminals	17
4.3	Minimum 6 dB RF Bandwidth	18
4.4	Maximum Power Density Reading	22
4.5	Out of Band Conducted Emissions	26
5.0	<u>Equipment Photographs</u>	30
6.0	<u>Product Labelling</u>	30
7.0	<u>Technical Specifications</u>	30
8.0	<u>Instruction Manual</u>	30
9.0	<u>Miscellaneous Information</u>	31
9.1	Discussion of Pulse Desensitization	31
9.2	Calculation of Average Factor	31
9.3	Emissions Test Procedures	32
10.0	<u>Test Equipment List</u>	34

1.0 Summary of Test Results

Applicant: SHENZHEN DNS INDUSTRIES CO., LTD.

Applicant Address: 23/F Building A, Shenzhen International Innovation Center, No.1006
Shennan Road, Futian, Shenzhen, China

Models: SH-207AG, ASPBSTC-0526, NFC3-207A1, NFC3-207A2, NFC3-207G1, NFC3-207G2,
NFC3-207AG

FCC ID: ZBC-SH207AG

TEST ITEM	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Transmitter Radiated Emissions in Restricted Bands	15.247(d), 15.209, FCC 15.205	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

2.0 General Description

2.1 Product Description

The equipment under test (EUT) is a Smart Tag / Smart Tag Card with Bluetooth 5.3 function operating in 2402-2480MHz. The EUT is powered by DC 3.7V from inner battery which can be charged by Wireless Input: 0.8W max, the EUT only has the function of wireless charging reception. For more detail information pls. refer to the user manual.

Type of Modulation: GFSK (BLE)

Antenna Type: Internal Antenna

Antenna Gain: 2.089dBi (This information is provided by manufacturer, and the manufacturer is responsible for the authenticity of the provided information.)

Bluetooth Version: 5.3

The model: ASPBSTC-0526, NFC3-207A1, NFC3-207A2, NFC3-207G1, NFC3-207G2, NFC3-207AG are the same as the model: SH-207AG in hardware aspect. The difference in model number, trade name and support devices serves as marketing strategy.

Production name	Trade name	Model no.	Description
Smart Tag / Smart Tag Card	DNS	SH-207AG	Support iOS & Google devices
	BAUHN	ASPBSTC-0526	Support iOS & Google devices
	NOVOO	NFC3-207A1 NFC3-207A2	Support iOS devices
		NFC3-207G1 NFC3-207G2	Support Google devices
		NFC3-207AG	Support iOS & Google devices

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

2.2 Related Submittal(s) Grants

This is an application for certification of transceiver for the Smart Tag / Smart Tag Card which has Bluetooth function.

2.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.10 (2020). Radiated emission measurement was performed in semi-anechoic chamber. For radiated emission measurement, preliminary scans were performed in the semi-anechoic

chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

2.4 Test Facility

The Semi-anechoic chamber used to collect the radiated data is **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308

Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen.
This test facility and site measurement data have been fully placed on file with File Number: CN1188

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by DC 3.7V from inner battery which can be charged by Wireless Input: 0.8W max during the test.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 12mm up to 1GHz and 12 mm above 1GHz. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

The rear of unit shall be flushed with the rear of the table.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst-case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

Test software: EMI_Test_Tool

3.3 Special Accessories

N/A.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

3.5 Equipment Modification

Any modifications installed previous to testing by SHENZHEN DNS INDUSTRIES CO., LTD. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

3.6 Support Equipment List and Description

Description	Remark
mobile phone	iPhone 14 Pro (provided by Intertek)

4.0 Test Results

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

4.1 Radiated Test Results

A sample calculation, configuration photographs and data tables of the emissions are included.

4.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB/m
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB
- AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB/m and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB/m}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

4.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

4.1.3 Radiated Emissions- FCC section 15.209

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission

at 941.476667 MHz

Judgement: Passed by 13.9 dB

TEST PERSONNEL:

Sign on file

Molly Wu, Engineer
Typed/Printed Name

20 January 2026
Date

TEST REPORT

Intertek Report No.: 251223010SZN-001

Applicant: SHENZHEN DNS INDUSTRIES CO., LTD.

Date of Test: 20 January 2026

Model: SH-207AG

Worst Case Operating Mode:


BT link

Modulation type:

GFSK

ANT Polarity: Horizontal

FCC Part 15



Frequency (MHz)	Quasi Peak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
560.396000	28.7	1000.0	120.000	100.0	H	29.1	17.3	46.0
712.977000	31.4	1000.0	120.000	100.0	H	31.1	14.6	46.0
941.476667	32.1	1000.0	120.000	100.0	H	33.4	13.9	46.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

TEST REPORT

Intertek Report No.: 251223010SZN-001

Applicant: SHENZHEN DNS INDUSTRIES CO., LTD.

Date of Test: 20 January 2026

Model: SH-207AG

Worst Case Operating Mode:


BT link

Modulation type:

GFSK

ANT Polarity: Vertical

FCC Part 15



Frequency (MHz)	Quasi Peak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
575.237000	28.7	1000.0	120.000	100.0	V	29.0	17.3	46.0
751.874000	29.7	1000.0	120.000	100.0	V	31.0	16.3	46.0
977.819333	31.9	1000.0	120.000	100.0	V	33.7	22.1	54.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

4.1.4 Transmitter Spurious Emissions (Radiated) - FCC section 15.209

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission

at 2483.500 MHz

Judgement: Passed by 7.1 dB

TEST PERSONNEL:

Sign on file

Molly Wu, Engineer
Typed/Printed Name

20 January 2026
Date

TEST REPORT

Intertek Report No.: 251223010SZN-001

Applicant: SHENZHEN DNS INDUSTRIES CO., LTD.

Date of Test: 20 January 2026

Model: SH-207AG

Worst Case Operating Mode:

Transmitting(2402MHz)

Modulation type:

GFSK-BW 1MHz

Table 1

Radiated Emissions

(2402MHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	**2390.000	63.5	33.1	27.4	57.8	74.0	-16.2
Horizontal	*4804.000	44.0	30.6	32.8	46.2	74.0	-27.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	**2390.000	52.1	33.1	27.4	46.4	54.0	-7.6
Horizontal	*4804.000	28.8	30.6	32.8	31.0	54.0	-23.0

Notes: 1. Peak detector is used for the emission measurement (RBW=1MHz / VBW=3MHz for Peak value, and RBW=1MHz / VBW=10Hz for Average value; RBW=3MHz is used for fundamental emission measurement).

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

TEST REPORT

Intertek Report No.: 251223010SZN-001

Applicant: SHENZHEN DNS INDUSTRIES CO., LTD.

Date of Test: 20 January 2026

Model: SH-207AG

Worst Case Operating Mode:

Transmitting(2440MHz)

Modulation type:

GFSK-BW 1MHz

Table 2

Radiated Emissions

(2440MHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4880.000	50.1	36.9	28.1	41.3	74.0	-32.7
Horizontal	*7320.000	43.1	37.0	37.2	43.3	74.0	-30.7

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4880.000	38.9	36.9	28.1	30.1	54.0	-23.9
Horizontal	*7320.000	34.9	37.0	37.2	35.1	54.0	-18.9

Notes: 1. Peak detector is used for the emission measurement (RBW=1MHz / VBW=3MHz for Peak value, and RBW=1MHz / VBW=10Hz for Average value; RBW=3MHz is used for fundamental emission measurement).

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

TEST REPORT

Intertek Report No.: 251223010SZN-001

Applicant: SHENZHEN DNS INDUSTRIES CO., LTD.

Date of Test: 20 January 2026

Model: SH-207AG

Worst Case Operating Mode:

Transmitting(2480MHz)

Modulation type:

GFSK-BW 1MHz

Table 3

Radiated Emissions

(2480MHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	**2483.500	67.4	37.6	27.8	57.6	74.0	-16.4
Horizontal	*4959.750	47.4	36.9	32.9	43.4	74.0	-30.6
Horizontal	*7440.000	42.4	37.0	37.2	42.6	74.0	-31.4

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	**2483.500	56.7	37.6	27.8	46.9	54.0	-7.1
Horizontal	*4959.750	37.9	36.9	32.9	33.9	54.0	-20.1
Horizontal	*7440.000	40.7	37.0	37.2	40.9	54.0	-13.1

Notes: 1. Peak detector is used for the emission measurement (RBW=1MHz / VBW=3MHz for Peak value, and RBW=1MHz / VBW=10Hz for Average value; RBW=3MHz is used for fundamental emission measurement).

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

TEST REPORT

Intertek Report No.: 251223010SZN-001

Applicant: SHENZHEN DNS INDUSTRIES CO., LTD.

Date of Test: 20 January 2026


Model: SH-207AG

4.2 Maximum Conducted Output Power at Antenna Terminals

FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter has a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

Block Diagram:



Power meter

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

BW-1MHz

Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2402	6.06	4.04
Middle Channel: 2440	6.69	4.67
High Channel: 2480	7.29	5.36

Cable loss: 0.5 dB External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. E.I.R.P = 9.379 dBm = 8.67mW

For RF Exposure, the information is saved with filename: RF exposure.pdf.

Applicant: SHENZHEN DNS INDUSTRIES CO., LTD.


Date of Test: 09 January 2026

Model: SH-207AG

4.3 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a) (2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v05r02. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Block Diagram:



Spectrum Analyzer



Limit: The 6 dB Bandwidth is at least 500 kHz.


BW-1MHz

Frequency (MHz)	6 dB Bandwidth (MHz)
2402	1.424
2440	1.332
2480	1.404

The test plots are attached as below.

BW-1MHz





TEST REPORT

Intertek Report No.: 251223010SZN-001

Applicant: SHENZHEN DNS INDUSTRIES CO., LTD.

Date of Test: 09 January 2026


Model: SH-207AG

4.4 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v05r02.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Block Diagram:



Spectrum Analyzer



Limit: The Power Density does not exceed 8dBm/3 kHz.


BW-1MHz

Frequency (MHz)	Power Density with RBW 3KHz
2402	-8.53
2440	-8.08
2480	-7.84

The test plots are attached as below.

BW-1MHz





TEST REPORT

Intertek Report No.: 251223010SZN-001

Applicant: SHENZHEN DNS INDUSTRIES CO., LTD.

Date of Test: 09 January 2026

Model: SH-207AG

4.5 Out of Band Conducted Emissions, FCC Rule 15.247(d):


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v05r02.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps & 2Mbps for BLE.

The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

Block Diagram:





Spectrum Analyzer

The test plots are attached as below.

BW-1MHz



Channel 0 (2402MHz) Reference Level: 2.16dBm








Channel 19 (2440MHz) Reference Level: 2.48dBm





Channel 39 (2480MHz) Reference Level: 3.13dBm





5.0 Equipment Photographs

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

6.0 Product Labelling

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

7.0 Technical Specifications

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

9.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandedge, the test procedure and calculation of factor such as pulse desensitization.

9.1 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (T_{eff}) is approximately 625 μ s for Bluetooth. With a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

9.2 Calculation of Average Factor

Based on the Bluetooth Specification Version 5.0 (EDR mode) and worst case AFH mode, transmitter ON time is independent of packet type (DH1, DH3 and DH5) and packet length, the AFH mode Duty cycle connection factor as below:

Channel hop rate = 800 hops/second (AFH Mode)

Adjusted channel hop rate for DH5 mode = 133.33 hops/second

Time per channel hop = $1 / 133.33 \text{ hops/second} = 7.5 \text{ ms}$

Time to cycle through all channels = $7.5 \times 20 \text{ channels} = 150 \text{ ms}$

Number of times transmitter hits on one channel = $100 \text{ ms} / 150 \text{ ms} = 1 \text{ time(s)}$

Worst case dwell time = 7.5 ms

Duty cycle connection factor = $20\log_{10} (7.5\text{ms} / 100\text{ms}) = -22.5 \text{ dB}$

9.3 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.10: 2020.

The transmitting equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter, up to 1GHz 0.8m and above 1GHz 1.5m in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjust through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in section 9.2.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz with RBW 9KHz used.

9.3 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.10: 2020.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz is used (RBW 3MHz used for fundamental emission).

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

10 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	2025-04-21	2026-04-21
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	2025-04-21	2026-04-21
SZ061-13	BiConiLog Antenna	ETS	3142E	00217919	2025-05-29	2028-05-29
SZ185-03	EMI Receiver	R&S	ESCI	101975	2025-04-13	2026-04-13
SZ061-08	Double - Ridged Waveguide Horn Antenna	ETS	3115	00092346	2024-09-13	2027-09-13
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	2024-05-05	2027-05-05
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	2025-04-21	2026-04-21
SZ056-08	Signal Analyzer	R&S	FSV 40	101430	2025-04-21	2026-04-21
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	2025-04-21	2026-04-21
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	2021-12-12	2026-12-12
SZ062-24	RF Cable	RADIAL	RG 213U	--	2025-09-15	2026-09-15
SZ062-25	RF Cable	RADIAL	0.04-26.5GHz	--	2025-09-15	2026-09-15
SZ062-38	RF Cable	RADIAL	0.04-26.5GHz	--	2025-09-15	2026-09-15
SZ067-04	Notch Filter	Micro-Tronics	BRM50702-02	--	2025-04-21	2026-04-21
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	2025-06-30	2026-06-30
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	2025-04-25	2026-04-25
SZ188-03	Shielding Room	ETS	RFD-100	4100	2022-12-20	2027-12-20

***** End of Report*****