Test Lab
Cert 2951.01

FCC TEST REPORT

(PART 24)

Product:	ILIUM PAD L8
Model Name:	ILIUM PAD L8
FCC ID:	ZC4L8
Applicant:	CORPORATIVO LANIX, S.A. DE C.V.
Address:	CARRETERA INTERNACIONAL A NOGALES KM.8.5, SAN LUIS. HERMOSILLO, SONORA, MÉXICO. CP. 83160
Manufacturer:	Foxda Technology Industrial(Shenzhen) Co., Ltd
Address:	1F of 1st Building&1F-3F of 2nd Building, Foxda Industrial Zone,North of Lanzhu Road,Pingshan New District,Shenzhen City,Guangdong Province,P.R. China
Prepared by:	Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch
Lab Location:	No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China
TEL:	+86 769 8593 5656
FAX:	+86 769 8593 1080
E-MAIL:	customerservice.dg@cn.bureauveritas.com
Report No.:	RF150512N006-4
Received Date:	May 12, 2015
Test Date:	May 12, 2015 ~ Jun. 04, 2015
Issued Date:	Jun. 05, 2015

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

TABLE OF CONTENTS

RELEASE CONTROL RECORD 4

1 CERTIFICATION 5

2 SUMMARY OF TEST RESULTS 6

2.1 MEASUREMENT UNCERTAINTY 6
2.2 TEST SITE AND INSTRUMENTS 7

3 GENERAL INFORMATION 8

3.1 GENERAL DESCRIPTION OF EUT 8
3.2 CONFIGURATION OF SYSTEM UNDER TEST 10
3.3 DESCRIPTION OF SUPPORT UNITS 11
3.4 TEST ITEM AND TEST CONFIGURATION 11
3.5 EUT OPERATING CONDITIONS 14
3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS 14

4 TEST TYPES AND RESULTS 15

4.1 OUTPUT POWER MEASUREMENT 15
4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT 15
4.1.2 TEST PROCEDURES 15
4.1.3 TEST SETUP 16
4.1.4 TEST RESULTS 17

4.2 FREQUENCY STABILITY MEASUREMENT 27
4.2.1 LIMITS OF FREQUENCY STABILIITY MEASUREMENT 27
4.2.2 TEST PROCEDURE 27
4.2.3 TEST SETUP 27
4.2.4 TEST RESULTS 28

4.3 OCCUPIED BANDWIDTH MEASUREMENT 30
4.3.1 TEST PROCEDURES 30
4.3.2 TEST SETUP 30
4.3.3 TEST RESULTS 31

4.4 BAND EDGE MEASUREMENT 39
4.4.1 LIMITS OF BAND EDGE MEASUREMENT 39
4.4.2 TEST SETUP 39
4.4.3 TEST PROCEDURES 39
4.4.4. TEST RESULTS 41

4.5 CONDUCTED SPURIOUS EMISSIONS 48
4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT 48
4.5.2 TEST PROCEDURE 48
4.5.3 TEST SETUP 48
4.5.4 TEST RESULTS 49

4.6 RADIATED EMISSION MEASUREMENT 54
4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT 54
4.6.2 TEST PROCEDURES 54
4.6.3 DEVIATION FROM TEST STANDARD 54
4.6.4 TEST SETUP 55
4.6.5 TEST RESULTS 56

4.7 PEAK TO AVERAGE RATIO 66
4.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT 76
4.7.2 TEST SETUP 76
4.7.3 TEST PROCEDURES 76
4.7.4 TEST RESULTS 77

5 INFORMATION ON THE TESTING LABORATORIES 83

6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 84

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF150512N006-4	Original release	Jun. 05, 2015

1 CERTIFICATION

PRODUCT:	ILIUM PAD L8
BRAND NAME:	LANIX
MODEL NAME:	ILIUM PAD L8
APPLICANT:	CORPORATIVO LANIX, S.A. DE C.V.
TESTED:	May 12, 2015 ~ Jun. 04, 2015
TEST SAMPLE:	Production unit
STANDARDS:	**FCC Part 24, Subpart E**

The above equipment has been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

TESTED BY : _____, **DATE :** Jun. 05, 2015

Glyn He/ Project Engineer

APPROVED BY : _____, **DATE :** Jun. 05, 2015

Sam Tung / Technical Manager

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 24 & Part 2			
STANDARD SECTION	**TEST TYPE**	**RESULT**	**REMARK**
2.1046 24.232	Equivalent Isotropic Radiated Power	PASS	Meet the requirement of limit.
2.1055 24.235	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 24.238(b)	Occupied Bandwidth	PASS	Meet the requirement of limit.
24.232(d)	Peak to average ratio	PASS	Meet the requirement of limit.
24.238(b)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 24.238	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 24.238	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -40.95dB at 5653.62MHz.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
Radiated emissions	9KHz ~ 30MHz	2.74dB
	30MHz ~ 1GHz	3.55dB
	1GHz ~ 18GHz	4.84dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU 26	100005	May 11,15	May 10,16
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 14	Aug. 07, 15
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 25, 14	Jul. 24, 15
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 30, 14	May 29, 16
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Mar. 04,15	Mar. 03, 16
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 20,14	Nov. 19,15
Pre-Amplifier (100MHz-26.5GHz)	Agilent	8449B	3008A00409	May 11,15	May 10,16
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 14	Aug. 07, 15
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Apr. 19,14	Apr. 18,16
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
Spectrum Analyzer (10Hz–40GHz)	Rohde&Schwarz	FSV40	101003	Apr. 07,15	Apr. 06,16
Power Meter	Anritsu	ML2495A	1139001	Feb. 20,15	Feb. 19,16
Power Sensor	Anritsu	MA2411B	1126068	Feb. 20,15	Feb. 19,16
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 27,14	Oct. 26,15
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.04,14	Sep. 03,15
Oscilloscope	Agilent	DSO9254A	MY51260160	Oct. 17, 14	Oct. 16, 15
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 05,14	Nov. 04,15
Signal Generator	Agilent	N5183A	MY50140980	Nov. 05,14	Nov. 04,15
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Mar.13, 15	Mar.12, 16
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Sep. 04,14	Sep. 03,15

NOTE: 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in Dongguan 966 Chamber.

3. The horn antenna are used only for the measurement of emission frequency above 1GHz if tested.

4. The FCC Site Registration No. is 502831.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	ILIUM PAD L8	
MODEL NAME	ILIUM PAD L8	
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.7Vdc (battery)	
MODULATION TYPE	**GSM, GPRS:** GMSK **EDGE:** GMSK, 8PSK **WCDMA :** BPSK **LTE Band 2:** QPSK, 16QAM	
FREQUENCY RANGE	**GSM, GPRS, EDGE:** 1850.2MHz ~ 1909.8MHz	
	WCDMA: 1852.4MHz ~ 1907.6MHz	
	LTE Band 2 **Channel Bandwidth: 1.4MHz**	1850.7MHz ~ 1909.3MHz
	LTE Band 2 **Channel Bandwidth: 3MHz**	1851.5MHz ~ 1908.5MHz
	LTE Band 2 **Channel Bandwidth: 5MHz**	1852.5MHz ~ 1907.5MHz
	LTE Band 2 **Channel Bandwidth: 10MHz**	1855.0MHz ~ 1905.0MHz
	LTE Band 2 **Channel Bandwidth: 15MHz**	1857.5MHz ~ 1902.5MHz
	LTE Band 2 **Channel Bandwidth: 20MHz**	1860.0MHz ~ 1900.0MHz
MAX. EIRP POWER	**GSM:** 444mW	
	EDGE: 411mW	
	WCDMA: 254mW	
	LTE Band 2 **Channel Bandwidth: 1.4MHz**	127mW
	LTE Band 2 **Channel Bandwidth: 3MHz**	114mW
	LTE Band 2 **Channel Bandwidth: 5MHz**	121mW
	LTE Band 2 **Channel Bandwidth: 10MHz**	134mW
	LTE Band 2 **Channel Bandwidth: 15MHz**	160mW
	LTE Band 2 **Channel Bandwidth: 20MHz**	159mW
EMISSION DESIGNATOR	**GSM**	243KGXW
	EDGE	255KG7W

	WCDMA	4M17F9W
	LTE Band 2 Channel Bandwidth: 1.4MHz	1M09G7D
	LTE Band 2 Channel Bandwidth: 3MHz	2M69W7D
	LTE Band 2 Channel Bandwidth: 5MHz	4M49G7D
	LTE Band 2 Channel Bandwidth: 10MHz	8M97W7D
	LTE Band 2 Channel Bandwidth: 15MHz	13M5G7D
	LTE Band 2 Channel Bandwidth: 20MHz	17M9G7D
ANTENNA TYPE	Fixed Internal antenna with 2dBi gain	
HW VERSION	V03	
SW VERSION	Android version 4.4.4; ILIUM PAD L8_TELCEL_SW_01	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	USB cable: Unshielded, detachable, 0.8m	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT was powered by the following adapter:

ADAPTER	
BRAND:	HJ
MODEL:	HJ-0501500-ZT
INPUT:	AC 100-240V, 250mA
OUTPUT:	DC 5V, 1500mA

3. The EUT matched the following USB cable:

USB CABLE	
BRAND:	ACH
MODEL:	USB 2.0 AM TO Micro B 5P
SIGNAL LINE:	0.8 METER

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



FOR E.I.R.P. TEST



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m

NOTE:

1. All power cords of the above support units are non shielded (1.8m).

3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports The worst case in EIRP and radiated emission was found when positioned on X-plane for GSM/EDGE/WCDMA and Z-plane for LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	**EUT + Adapter + USB Cable with GSM ,WCDMA or LTE link**
B	EUT + Battery+ USB Cable with **GSM ,WCDMA or LTE link**

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
B	EIRP	512 to 810	512, 661, 810	GSM, EDGE
B	FREQUENCY STABILITY	512 to 810	661	GSM, EDGE
B	OCCUPIED BANDWIDTH	512 to 810	512, 661, 810	GSM, EDGE
B	PEAK TO AVERAGE RATIO	512 to 810	661	GSM, EDGE
B	BAND EDGE	512 to 810	512, 810	GSM, EDGE
B	CONDCUDETED EMISSION	512 to 810	661	GSM, EDGE
A	RADIATED EMISSION	512 to 810	661	GSM, EDGE

WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
B	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
B	FREQUENCY STABILITY	9262 to 9538	9400	WCDMA
B	OCCUPIED BANDWIDTH	9262 to 9538	9262, 9400, 9538	WCDMA
B	PEAK TO AVERAGE RATIO	9262 to 9538	9400	WCDMA
B	BAND EDGE	9262 to 9538	9262, 9538	WCDMA
B	CONDCUDETED EMISSION	9262 to 9538	9400	WCDMA
A	RADIATED EMISSION	9262 to 9538	9400	WCDMA

LTE BAND 2

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	EIRP	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	18607 to 19193	18900	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18900	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18900	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18900	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18900	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18900	20MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK, 16QAM	100 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset

B	BAND EDGE	18607 to 19193	18607	1.4MHz	QPSK	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			19193	1.4MHz	QPSK	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		18615 to 19185	18615	3MHz	QPSK	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			19185	3MHz	QPSK	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		18625 to 19175	18625	5MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			19175	5MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		18650 to 19150	18650	10MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			19150	10MHz	QPSK	1 RB / 49 RB Offset
						50 RB / 0 RB Offset
		18675 to 19125	18675	15MHz	QPSK	1 RB / 0 RB Offset
						75 RB / 0 RB Offset
			19125	15MHz	QPSK	1 RB / 74 RB Offset
						75 RB / 0 RB Offset
		18700 to 19100	18700	20MHz	QPSK	1 RB / 0 RB Offset
						100 RB / 0 RB Offset
			19100	20MHz	QPSK	1 RB / 99 RB Offset
						100 RB / 0 RB Offset
B	CONDCUDETED EMISSION	18607 to 19193	18900	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18900	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18900	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18900	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18900	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18900	20MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	18607 to 19193	18900	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18900	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18900	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18900	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18900	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18900	20MHz	QPSK	1 RB / 0 RB Offset

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP	25deg. C, 57%RH	5Vdc from adapter	Blue Zheng
FREQUENCY STABILITY	23deg. C, 61%RH	3.7Vdc from Battery	Yuqiang Yin
OCCUPIED BANDWIDTH	23deg. C, 61%RH	3.7Vdc from Battery	Yuqiang Yin
PEAK TO AVERAGE RATIO	23deg. C, 61%RH	3.7Vdc from Battery	Yuqiang Yin
BAND EDGE	23deg. C, 61%RH	3.7Vdc from Battery	Yuqiang Yin
CONDCUDETED EMISSION	23deg. C, 61%RH	3.7Vdc from Battery	Yuqiang Yin
RADIATED EMISSION	25deg. C, 57%RH	5Vdc from adapter	Blue Zheng

3.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.

4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile and portable stations are limited to 2 watts EIRP

4.1.2 TEST PROCEDURES

EIRP MEASUREMENT:

a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz for GSM, GPRS & EDGE and 5MHz for WCDMA mode.

b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.

c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step b. Record the power level of S.G

d. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.

CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with GSM, GPRS, EDGE & WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 TEST SETUP

EIRP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	GSM1900		
Channel	512	661	810
Frequency (MHz)	1850.2	1880.0	1909.8
GSM	30.42	30.41	30.60
GPRS 8	30.42	30.41	30.55
GPRS 10	30.40	30.39	30.54
EDGE 8 (MCS1)	30.41	30.40	30.51
EDGE 10 (MCS1)	30.38	30.35	30.50
EDGE 8 (MCS9)	26.76	26.63	26.77
EDGE 10 (MCS9)	26.73	26.64	26.75

Band	WCDMA II		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880.0	1907.6
RMC 12.2K	23.12	23.20	23.24
HSPA			
HSDPA Subtest-1	22.33	22.37	22.60
HSDPA Subtest-2	22.47	22.36	22.53
HSDPA Subtest-3	21.91	21.88	22.09
HSDPA Subtest-4	21.93	21.85	22.04
HSUPA Subtest-1	22.07	22.04	22.31
HSUPA Subtest-2	20.33	19.93	20.53
HSUPA Subtest-3	21.00	21.19	21.26
HSUPA Subtest-4	20.19	20.15	20.13
HSUPA Subtest-5	22.30	22.31	22.47

LTE Band 2							
BW	Modulation	RB Size	RB Offset	Low CH 18607	Mid CH 18900	High CH 19193	3GPP MPR (dB)
				Frequency 1850.7 MHz	Frequency 1880 MHz	Frequency 1909.3 MHz	
1.4MHz	QPSK	1	0	23.11	23.12	**23.26**	0
		1	2	23.1	22.79	23.25	0
		1	5	22.7	22.65	23	0
		3	0	22.55	22.73	23.1	0
		3	1	22.91	22.75	23.08	0
		3	3	22.99	22.79	**23.25**	0
		6	0	21.76	21.66	**22.24**	1
	16QAM	1	0	22.06	21.83	22.23	1
		1	2	22	21.82	**22.35**	1
		1	5	22.05	21.66	22.22	1
		3	0	21.91	21.69	22.22	1
		3	1	21.72	21.7	22.08	1
		3	3	21.5	21.71	**22.26**	1
		6	0	20.8	20.63	**21.22**	2

LTE Band 2							
BW	Modulation	RB Size	RB Offset	Low CH 18615 Frequency 1851.5 MHz	Mid CH 18900 Frequency 1880 MHz	High CH 19185 Frequency 1908.5 MHz	3GPP MPR (dB)
3 MHz	QPSK	1	0	23.15	23.16	**23.3**	0
		1	7	23.14	22.83	23.29	0
		1	14	22.74	22.69	23.04	0
		8	0	21.59	21.77	22.14	1
		8	3	21.95	21.79	22.12	1
		8	7	22.03	21.83	**22.3**	1
		15	0	21.8	21.7	**22.28**	1
	16QAM	1	0	22.1	21.87	22.27	1
		1	7	22.04	21.86	**22.39**	1
		1	14	22.09	21.7	22.26	1
		8	0	20.95	20.73	21.26	2
		8	3	20.76	20.74	21.12	2
		8	7	20.54	20.75	**21.3**	2
		15	0	20.84	20.67	**21.26**	2
BW	Modulation	RB Size	RB Offset	Low CH 18625 Frequency 1852.5 MHz	Mid CH 18900 Frequency 1880 MHz	High CH 19175 Frequency 1907.5 MHz	3GPP MPR (dB)
5 MHz	QPSK	1	0	23.21	23.22	**23.36**	0
		1	12	23.2	22.89	23.35	0
		1	24	22.8	22.75	23.1	0
		12	0	21.65	21.83	22.2	1
		12	6	22.01	21.85	22.18	1
		12	13	22.09	21.89	**22.36**	1
		25	0	21.86	21.76	**22.34**	1
	16QAM	1	0	22.16	21.93	22.33	1
		1	12	22.1	21.92	**22.45**	1
		1	24	22.15	21.76	22.32	1
		12	0	21.01	20.79	21.32	2
		12	6	20.82	20.8	21.18	2
		12	13	20.6	20.81	**21.36**	2
		25	0	20.9	20.73	**21.32**	2

LTE Band 2							
BW	Modulation	RB Size	RB Offset	Low CH 18650 Frequency 1855 MHz	Mid CH 18900 Frequency 1880 MHz	High CH 19150 Frequency 1905 MHz	3GPP MPR (dB)
10 MHz	QPSK	1	0	23.26	23.27	**23.41**	0
		1	24	23.25	22.94	23.4	0
		1	49	22.85	22.8	23.15	0
		25	0	21.7	21.88	22.25	1
		25	12	22.06	21.9	22.23	1
		25	25	22.14	21.94	**22.41**	1
		50	0	21.91	21.81	**22.39**	1
	16QAM	1	0	22.21	21.98	22.38	1
		1	24	22.15	21.97	**22.5**	1
		1	49	22.2	21.81	22.37	1
		25	0	21.06	20.84	21.37	2
		25	12	20.87	20.85	21.23	2
		25	25	20.65	20.86	**21.41**	2
		50	0	20.95	20.78	**21.37**	2
BW	Modulation	RB Size	RB Offset	Low CH 18675 Frequency 1857.5 MHz	Mid CH 18900 Frequency 1880 MHz	High CH 19125 Frequency 1902.5 MHz	3GPP MPR (dB)
15 MHz	QPSK	1	0	23.32	23.33	**23.47**	0
		1	37	23.31	23	23.46	0
		1	74	22.91	22.86	23.21	0
		36	0	21.76	21.94	22.31	1
		36	19	22.12	21.96	22.29	1
		36	39	22.2	22	**22.47**	1
		75	0	21.97	21.87	**22.45**	1
	16QAM	1	0	22.27	22.04	22.44	1
		1	37	22.21	22.03	**22.56**	1
		1	74	22.26	21.87	22.43	1
		36	0	21.12	20.9	21.43	2
		36	19	20.93	20.91	21.29	2
		36	39	20.71	20.92	**21.47**	2
		75	0	21.01	20.84	**21.43**	2

LTE Band 2							
BW	Modulation	RB Size	RB Offset	Low CH 18700 Frequency 1860 MHz	Mid CH 18900 Frequency 1880 MHz	High CH 19100 Frequency 1900 MHz	3GPP MPR (dB)
20MHz	QPSK	1	0	23.36	23.37	**23.51**	0
		1	50	23.35	23.04	23.5	0
		1	99	22.95	22.9	23.25	0
		50	0	21.8	21.98	22.35	1
		50	25	22.16	22	22.33	1
		50	50	22.24	22.04	**22.51**	1
		100	0	22.01	21.91	**22.49**	1
	16QAM	1	0	22.31	22.08	22.48	1
		1	50	22.25	22.07	**22.6**	1
		1	99	22.3	21.91	22.47	1
		50	0	21.16	20.94	21.47	2
		50	25	20.97	20.95	21.33	2
		50	50	20.75	20.96	**21.51**	2
		100	0	21.05	20.88	**21.47**	2

EIRP POWER (dBm)

GSM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
512	1850.2	-16.22	41.66	25.44	349.95	H
661	1880.0	-15.87	42.34	26.47	**443.61**	H
810	1909.8	-16.34	42.49	26.15	412.10	H
512	1850.2	-20.18	44.28	24.10	257.04	V
661	1880.0	-20.01	44.10	24.09	256.45	V
810	1909.8	-20.54	44.42	23.88	244.34	V

EDGE

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
512	1850.2	-16.49	41.66	25.17	328.85	H
661	1880.0	-16.20	42.34	26.14	**411.15**	H
810	1909.8	-16.38	42.49	26.11	408.32	H
512	1850.2	-27.46	44.24	16.78	47.64	V
661	1880.0	-27.27	44.01	16.74	47.21	V
810	1909.8	-27.19	44.79	17.60	57.54	V

WCDMA

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
9262	1852.4	-18.13	41.69	23.56	226.99	H
9400	1880.0	-18.91	42.34	23.43	220.29	H
9538	1907.6	-18.72	42.77	24.05	**254.10**	H
9262	1852.4	-22.66	44.24	21.58	143.88	V
9400	1880.0	-22.49	44.01	21.52	141.91	V
9538	1907.6	-22.78	44.79	22.01	158.85	V

REMARKS: 1. EIRP Output Power (dBm) = LVL (dBm) + Correction Factor (dB).
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

LTE BAND 2

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18607	1850.7	-21.42	41.15	19.73	93.97	H	1
18900	1880.0	-21.32	41.89	20.57	114.02	H	1
19193	1909.3	-21.08	42.11	21.03	**126.77**	H	1
18607	1850.7	-26.25	43.87	17.62	57.81	V	1
18900	1880.0	-26.64	43.56	16.92	49.20	V	1
19193	1909.3	-26.78	44.35	17.57	57.15	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18607	1850.7	-20.44	41.15	20.71	117.76	H	1
18900	1880.0	-21.80	41.89	20.09	102.09	H	1
19193	1909.3	-22.05	42.11	20.06	101.39	H	1
18607	1850.7	-26.67	43.87	17.20	52.48	V	1
18900	1880.0	-26.51	43.56	17.05	50.70	V	1
19193	1909.3	-26.40	44.35	17.95	62.37	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18615	1851.5	-20.62	41.18	20.56	**113.76**	H	1
18900	1880.0	-21.82	41.89	20.07	101.62	H	1
19185	1908.5	-22.03	42.14	20.11	102.57	H	1
18615	1851.5	-26.85	43.77	16.92	49.20	V	1
18900	1880.0	-26.53	43.56	17.03	50.47	V	1
19185	1908.5	-26.38	44.31	17.93	62.09	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18615	1851.5	-21.21	41.18	19.97	99.31	H	1
18900	1880.0	-21.53	41.89	20.36	108.64	H	1
19185	1908.5	-21.96	42.14	20.18	104.23	H	1
18615	1851.5	-27.32	43.77	16.45	44.16	V	1
18900	1880.0	-27.14	43.56	16.42	43.85	V	1
19185	1908.5	-26.85	44.31	17.46	55.72	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18625	1852.5	-20.44	41.27	20.83	**121.06**	H	1
18900	1880.0	-21.90	41.89	19.99	99.77	H	1
19175	1907.5	-22.09	42.29	20.20	104.71	H	1
18625	1852.5	-26.67	43.68	17.01	50.23	V	1
18900	1880.0	-26.61	43.56	16.95	49.55	V	1
19175	1907.5	-26.44	44.29	17.85	60.95	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18625	1852.5	-21.24	41.27	20.03	100.69	H	1
18900	1880.0	-21.41	41.89	20.48	111.69	H	1
19175	1907.5	-21.63	42.29	20.66	116.41	H	1
18625	1852.5	-26.75	43.68	16.93	49.32	V	1
18900	1880.0	-26.54	43.56	17.02	50.35	V	1
19175	1907.5	-26.35	44.29	17.94	62.23	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18650	1855.0	-20.57	41.84	21.27	**133.97**	H	1
18900	1880.0	-21.92	41.89	19.97	99.31	H	1
19150	1905.0	-22.02	42.79	20.77	119.40	H	1
18650	1855.0	-26.80	43.61	16.81	47.97	V	1
18900	1880.0	-26.63	43.56	16.93	49.32	V	1
19150	1905.0	-26.37	44.21	17.84	60.81	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18650	1855.0	-21.21	41.84	20.63	115.61	H	1
18900	1880.0	-21.54	41.89	20.35	108.39	H	1
19150	1905.0	-21.63	42.79	21.16	130.62	H	1
18650	1855.0	-26.58	43.61	17.03	50.47	V	1
18900	1880.0	-26.71	43.56	16.85	48.42	V	1
19150	1905.0	-26.82	44.21	17.39	54.83	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18675	1857.5	-20.95	42.23	21.28	134.28	H	1
18900	1880.0	-20.84	41.89	21.05	127.35	H	1
19125	1902.5	-20.64	42.67	22.03	**159.59**	H	1
18675	1857.5	-27.02	43.61	16.59	45.60	V	1
18900	1880.0	-27.08	43.56	16.48	44.46	V	1
19125	1902.5	-27.17	44.34	17.17	52.12	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18675	1857.5	-20.29	42.23	21.94	156.31	H	1
18900	1880.0	-21.76	41.89	20.13	103.04	H	1
19125	1902.5	-21.78	42.67	20.89	122.74	H	1
18675	1857.5	-26.52	43.61	17.09	51.17	V	1
18900	1880.0	-26.47	43.56	17.09	51.17	V	1
19125	1902.5	-26.13	44.34	18.21	66.22	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18700	1860.0	-20.01	42.02	22.01	**158.85**	H	1
18900	1880.0	-21.34	41.89	20.55	113.50	H	1
19100	1900.0	-21.51	42.37	20.86	121.90	H	1
18700	1860.0	-26.24	43.83	17.59	57.41	V	1
18900	1880.0	-26.05	43.56	17.51	56.36	V	1
19100	1900.0	-25.86	44.74	18.88	77.27	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18700	1860.0	-20.94	42.02	21.08	128.23	H	1
18900	1880.0	-22.41	41.89	19.48	88.72	H	1
19100	1900.0	-22.34	42.37	20.03	100.69	H	1
18700	1860.0	-27.17	43.83	16.66	46.34	V	1
18900	1880.0	-27.12	43.56	16.44	44.06	V	1
19100	1900.0	-26.69	44.74	18.05	63.83	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILIITY MEASUREMENT

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

4.2.2 TEST PROCEDURE

a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.

b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.

c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ±0.5℃ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 TEST SETUP



4.2.4 TEST RESULTS

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)			LIMIT (ppm)
	GSM	EDGE	WCDMA	
3.7	-0.010	-0.011	-0.008	2.5
3.6	-0.009	-0.010	-0.007	2.5
4.2	-0.008	-0.009	-0.006	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.6Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	FREQUENCY ERROR (PPM)			LIMIT (PPM)
	GSM	EDGE	WCDMA	
-30	-0.013	-0.013	-0.012	2.5
-20	-0.011	-0.012	-0.009	2.5
-10	-0.012	-0.011	-0.007	2.5
0	-0.010	-0.010	-0.003	2.5
10	-0.009	-0.010	-0.004	2.5
20	-0.009	-0.009	-0.009	2.5
30	-0.008	-0.008	-0.009	2.5
40	-0.007	-0.008	-0.011	2.5
50	0.002	0.002	-0.012	2.5
60	0.006	0.006	-0.013	2.5

LTE BAND 2

AFC FREQUENCY ERROR vs. VOLTAGE							
VOLTAGE (Volts)	FREQUENCY ERROR (ppm)						LIMIT (ppm)
	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	
3.7	-0.012	-0.006	-0.010	-0.015	-0.007	-0.007	2.5
3.6	-0.002	0.004	-0.006	0.007	0.003	0.004	2.5
4.2	0.007	-0.009	0.004	-0.007	0.011	0.006	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.6Vdc to 4.2Vdc.

AFC FREQUENCY ERROR vs. TEMPERATURE							
TEMP. (℃)	FREQUENCY ERROR (ppm)						LIMIT (ppm)
	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	
-30	-0.008	-0.008	-0.009	-0.007	-0.008	-0.006	2.5
-20	-0.007	-0.007	-0.008	-0.005	-0.007	-0.005	2.5
-10	-0.006	-0.005	-0.007	-0.004	-0.006	-0.004	2.5
0	-0.005	-0.003	-0.006	-0.002	-0.005	-0.002	2.5
10	-0.004	-0.003	-0.004	0.002	-0.004	-0.001	2.5
20	-0.002	0.002	-0.002	0.003	0.002	-0.004	2.5
30	-0.001	0.003	0.003	0.004	0.003	0.005	2.5
40	-0.002	0.003	0.004	0.004	0.004	0.005	2.5
50	-0.003	0.004	0.005	0.005	0.005	0.006	2.5
60	-0.004	0.004	0.004	0.005	0.005	0.005	2.5

4.3 OCCUPIED BANDWIDTH MEASUREMENT

4.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.2 TEST SETUP



4.3.3 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (kHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)
		GSM	EDGE			WCDMA
512	1850.2	243.48	255.07	9262	1852.4	4.17
661	1880.0	243.48	252.17	9400	1880.0	4.17
810	1909.8	243.48	252.17	9538	1907.6	4.16

SPECTRUM PLOT OF WORST VALUE

GSM



EDGE



WCDMA



CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (kHz)		CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)
		GSM	EDGE			WCDMA
512	1850.2	312.03	326.42	9262	1852.4	4.78
661	1880.0	313.25	328.54	9400	1880.0	4.72
810	1909.8	317.24	316.93	9538	1907.6	4.72

SPECTRUM PLOT OF WORST VALUE

GSM



EDGE



WCDMA



LTE band 2							
Channel Bandwidth : 1.4MHz							
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		Channel	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18607	1850.7	1.079	1.085	18607	1850.7	1.247	1.288
18900	1880	1.088	1.082	18900	1880	1.264	1.282
19193	1909.3	1.088	1.082	19193	1909.3	1.268	1.267

SPECTRUM PLOT OF WORST VALUE of 99% Occupied Bandwidth

1.4MHz/QPSK



1.4MHz/16QAM



SPECTRUM PLOT OF WORST VALUE of 26dB Bandwidth

1.4MHz/QPSK



1.4MHz/16QAM



LTE band 2							
Channel Bandwidth : 3MHz							
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		Channel	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18615	1851.5	2.685	2.685	18615	1851.5	2.937	2.945
18900	1880	2.684	2.684	18900	1880	2.945	2.937
19185	1908.5	2.684	2.677	19185	1908.5	2.967	2.930

SPECTRUM PLOT OF WORST VALUE of 99% Occupied Bandwidth

3MHz/QPSK



3MHz/16QAM



SPECTRUM PLOT OF WORST VALUE of 26dB Occupied Bandwidth

3MHz/QPSK



3MHz/16QAM



LTE band 2							
Channel Bandwidth : 5 MHz							
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		Channel	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18625	1852.5	4.486	4.472	18625	1852.5	4.935	4.863
18900	1880	4.486	4.471	18900	1880	4.935	4.877
19175	1907.5	4.471	4.471	19175	1907.5	4.096	4.877

SPECTRUM PLOT OF WORST VALUE of 99% Occupied Bandwidth

5MHz/QPSK



5MHz/16QAM



SPECTRUM PLOT OF WORST VALUE of 26dB Occupied Bandwidth

5MHz/QPSK



5MHz/16QAM



LTE band 2							
Channel Bandwidth : 10 MHz							
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		Channel	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18650	1855	8.943	8.914	18650	1855	9.783	9.725
18900	1880	8.943	8.972	18900	1880	9.812	9.783
19150	1905	8.944	8.973	19150	1905	9.725	9.783

SPECTRUM PLOT OF WORST VALUE of 99% Occupied Bandwidth

10MHz/QPSK



10MHz/16QAM



SPECTRUM PLOT OF WORST VALUE of 26dB Occupied Bandwidth

10MHz/QPSK



10MHz/16QAM



LTE band 2							
Channel Bandwidth : 15 MHz							
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		Channel	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18675	1857.5	13.459	13.415	18675	1857.5	14.588	14.588
18900	1880	13.415	13.371	18900	1880	14.501	14.631
19125	1902.5	13.415	13.415	19125	1902.5	14.631	14.544

SPECTRUM PLOT OF WORST VALUE of 99% Occupied Bandwidth

15MHz/QPSK



15MHz/16QAM



SPECTRUM PLOT OF WORST VALUE of 26dB Occupied Bandwidth

15MHz/QPSK



15MHz/16QAM



LTE band 2							
Channel Bandwidth : 20 MHz							
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		Channel	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18700	1860	17.887	17.829	18700	1860	19.161	19.219
18900	1880	17.887	17.829	18900	1880	19.103	19.103
19100	1900	17.887	17.829	19100	1900	19.219	19.045

SPECTRUM PLOT OF WORST VALUE of 99% Occupied Bandwidth

20MHz/QPSK



20MHz/16QAM



SPECTRUM PLOT OF WORST VALUE of 26dB Occupied Bandwidth

20MHz/QPSK



20MHz/16QAM



4.4 BAND EDGE MEASUREMENT

4.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.4.2 TEST SETUP



4.4.3 TEST PROCEDURES

a. All measurements were done at low and high operational frequency range.

b. The center frequency of spectrum is the band edge frequency and span is 1.5 MHz. RBW of the spectrum is 10kHz and VBW of the spectrum is 30kHz (GSM/GPRS/ EDGE).

c. The center frequency of spectrum is the band edge frequency and span is 10MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA).

d. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 20kHz and VB of the spectrum is 100 kHz. (LTE bandwidth 1.4MHz)

e. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 30kHz and VB of the spectrum is 100kHz. (LTE bandwidth 3MHz)

f. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz.

RB of the spectrum is 50kHz and VB of the spectrum is 200kHz. (LTE bandwidth 5MHz)

g. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz. (LTE bandwidth 10MHz)

h. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 200kHz and VB of the spectrum is 1MHz. (LTE bandwidth 15MHz)

i. he center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 200kHz and VB of the spectrum is 1MHz. (LTE bandwidth 20MHz)

j. Record the max trace plot into the test report.

4.4.4. TEST RESULTS

GSM			
CHANNEL	512	CHANNEL	810
GSM			
			
EDGE			
CHANNEL	512	CHANNEL	810
			
WCDMA			
CHANNEL	9262	CHANNEL	9538
			

LTE BAND 2

Channel Bandwidth: 1.4MHz

CHANNEL	18607	1 RB



CHANNEL	19193	1 RB



CHANNEL	18607	Full RB



CHANNEL	19193	Full RB



LTE BAND 2

Channel Bandwidth: 3MHz

CHANNEL	18615	1 RB	CHANNEL	19185	1 RB





CHANNEL	18615	Full RB	CHANNEL	19185	Full RB





LTE BAND 2

Channel Bandwidth: 5MHz

CHANNEL	18625	1 RB	CHANNEL	19175	1 RB





CHANNEL	18625	Full RB	CHANNEL	19175	Full RB





LTE BAND 2

Channel Bandwidth: 10MHz

CHANNEL	18650	1 RB	CHANNEL	19150	1 RB





CHANNEL	18650	Full RB	CHANNEL	19150	Full RB





LTE BAND 2

Channel Bandwidth: 15MHz

CHANNEL	18675	1 RB	CHANNEL	19125	1 RB





CHANNEL	18675	Full RB	CHANNEL	19125	Full RB





LTE BAND 2

Channel Bandwidth: 20MHz

CHANNEL	18700	1 RB	CHANNEL	19100	1 RB





CHANNEL	18700	Full RB	CHANNEL	19100	Full RB





4.5 CONDUCTED SPURIOUS EMISSIONS

4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The emission limit equal to –13dBm.

4.5.2 TEST PROCEDURE

a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.

b. Measuring frequency range is from 9 kHz to 19.1GHz. 20dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

4.5.3 TEST SETUP



4.5.4 TEST RESULTS

GSM

CHANNEL 661

FREQUENCY RANGE : 30MHz~1GHz



FREQUENCY RANGE : 1GHz~3GHz



FREQUENCY RANGE : 3GHz~7GHz



FREQUENCY RANGE : 7GHz~13GHz



FREQUENCY RANGE : 13GHz~19.1GHz



EDGE

CHANNEL 512

FREQUENCY RANGE : 30MHz~1GHz



FREQUENCY RANGE : 1GHz~3GHz



FREQUENCY RANGE : 3GHz~7GHz



FREQUENCY RANGE : 7GHz~13GHz



FREQUENCY RANGE : 13GHz~19.1GHz



WCDMA

CHANNEL 9400

FREQUENCY RANGE : 30MHz~1GHz



FREQUENCY RANGE : 1GHz~3GHz



FREQUENCY RANGE : 3GHz~7GHz



FREQUENCY RANGE : 7GHz~13GHz



FREQUENCY RANGE : 13GHz~19.1GHz



LTE BAND 2

CHANNEL 18900	CHANNEL 18900
1.4MHz / QPSK	3MHz / QPSK
FREQUENCY RANGE : 30MHz~19.1GHz	FREQUENCY RANGE : 30MHz~19.1GHz
	

CHANNEL 18900	CHANNEL 18900
5MHz / QPSK	10MHz / QPSK
FREQUENCY RANGE : 30MHz~19.1GHz	FREQUENCY RANGE : 30MHz~19.1GHz
	

CHANNEL 18900	CHANNEL 18900
15MHz / QPSK	20MHz / QPSK
FREQUENCY RANGE : 30MHz~19.1GHz	FREQUENCY RANGE : 30MHz~19.1GHz
	

4.6 RADIATED EMISSION MEASUREMENT

4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The emission limit equal to –13dBm.

4.6.2 TEST PROCEDURES

a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.

b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G

c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.6.3 DEVIATION FROM TEST STANDARD

No deviation

4.6.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.6.5 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

LTE Band 2:

MODE	TX channel 512	**FREQUENCY RANGE**	Below 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	**INPUT POWER**	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	30.00	-12.55	-77.47	-90.02	-13.00	-77.02	100	0
	2	79.20	-23.85	-73.14	-96.99	-13.00	-83.99	100	0
	3	188.86	-20.84	-73.58	-94.42	-13.00	-81.42	100	0
	4	259.14	-15.67	-74.22	-89.89	-13.00	-76.89	100	0
	5	380.04	-12.70	-76.35	-89.05	-13.00	-76.05	100	0
*	6	419.41	-10.87	-75.03	-85.90	-13.00	-72.90	100	0

MODE	TX channel 512	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	30.00	-12.55	-60.48	-73.03	-13.00	-60.03	100	0
	2	41.25	-18.01	-68.04	-86.05	-13.00	-73.05	100	0
	3	114.35	-19.01	-74.65	-93.66	-13.00	-80.66	100	0
	4	176.20	-20.09	-72.15	-92.24	-13.00	-79.24	100	0
	5	257.74	-15.85	-73.19	-89.04	-13.00	-76.04	100	0
	6	419.41	-10.87	-74.86	-85.73	-13.00	-72.73	100	0

ABOVE 1GHz DATA

PCS 1900:

MODE	TX channel 512	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	**INPUT POWER**	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3753.62 (PK)	6.34	-65.63	-59.29	-13.00	-46.29	100	0
*	2	5653.62 (PK)	10.11	-64.70	-54.59	-13.00	-41.59	100	0

MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3753.62 (PK)	6.34	-66.77	-60.43	-13.00	-47.43	100	0
*	2	5681.16 (PK)	10.17	-65.06	-54.89	-13.00	-41.89	100	0

EDGE 1900:

MODE	TX channel 512	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	**INPUT POWER**	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3726.09 (PK)	6.30	-67.19	-60.89	-13.00	-47.89	100	0
*	2	5626.09 (PK)	10.04	-66.06	-56.02	-13.00	-43.02	100	0

MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3726.09 (PK)	6.30	-66.95	-60.65	-13.00	-47.65	100	0
*	2	5626.09 (PK)	10.04	-65.75	-55.71	-13.00	-42.71	100	0

WCDMA Band II:

MODE	TX channel 9262	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	**INPUT POWER**	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3781.16 (PK)	6.39	-66.03	-59.64	-13.00	-46.64	100	0
*	2	5626.09 (PK)	10.04	-66.41	-56.37	-13.00	-43.37	100	0

MODE	TX channel 9262	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3781.16 (PK)	6.39	-66.58	-60.19	-13.00	-47.19	100	0
*	2	5653.62 (PK)	10.11	-64.93	-54.82	-13.00	-41.82	100	0

LTE Band 2

CHANNEL BANDWIDTH: 1.4MHz / QPSK

MODE	TX channel 18900	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	**INPUT POWER**	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3726.09 (PK)	6.30	-66.74	-60.44	-13.00	-47.44	100	0
*	2	5653.62 (PK)	10.11	-65.07	-54.96	-13.00	-41.96	100	0

MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3726.09 (PK)	6.30	-65.35	-59.05	-13.00	-46.05	100	0
*	2	5626.09 (PK)	10.04	-65.33	-55.29	-13.00	-42.29	100	0

CHANNEL BANDWIDTH: 3MHz / QPSK

MODE	TX channel 18900	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	**INPUT POWER**	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3726.09 (PK)	6.30	-66.31	-60.01	-13.00	-47.01	100	0
*	2	5653.62 (PK)	10.11	-65.82	-55.71	-13.00	-42.71	100	0

MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3726.09 (PK)	6.30	-66.24	-59.94	-13.00	-46.94	100	0
*	2	5626.09 (PK)	10.04	-66.00	-55.96	-13.00	-42.96	100	0

CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 18900	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	**INPUT POWER**	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3726.09 (PK)	6.30	-67.00	-60.70	-13.00	-47.70	100	0
*	2	5653.62 (PK)	10.11	-65.53	-55.42	-13.00	-42.42	100	0

MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3726.09 (PK)	6.30	-67.10	-60.80	-13.00	-47.80	100	0
*	2	5626.09 (PK)	10.04	-66.09	-56.05	-13.00	-43.05	100	0

CHANNEL BANDWIDTH: 10MHz / QPSK

MODE	TX channel 18900	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	**INPUT POWER**	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3726.09 (PK)	6.30	-65.86	-59.56	-13.00	-46.56	100	0
*	2	5653.62 (PK)	10.11	-64.70	-54.59	-13.00	-41.59	100	0

MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3726.09 (PK)	6.30	-65.71	-59.41	-13.00	-46.41	100	0
*	2	5653.62 (PK)	10.11	-64.06	-53.95	-13.00	-40.95	100	0

CHANNEL BANDWIDTH: 15MHz / QPSK

MODE	TX channel 18900	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	**INPUT POWER**	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3726.09 (PK)	6.30	-65.20	-58.90	-13.00	-45.90	100	0
*	2	5653.62 (PK)	10.11	-65.58	-55.47	-13.00	-42.47	100	0

MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3726.09 (PK)	6.30	-66.65	-60.35	-13.00	-47.35	100	0
*	2	5626.09 (PK)	10.04	-65.05	-55.01	-13.00	-42.01	100	0

CHANNEL BANDWIDTH: 20MHz / QPSK

MODE	TX channel 18900	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	**INPUT POWER**	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3753.62 (PK)	6.34	-66.17	-59.83	-13.00	-46.83	100	0
*	2	5653.62 (PK)	10.11	-65.16	-55.05	-13.00	-42.05	100	0

MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Bob Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	3753.62 (PK)	6.34	-65.79	-59.45	-13.00	-46.45	100	0
*	2	5626.09 (PK)	10.04	-65.13	-55.09	-13.00	-42.09	100	0

4.7 PEAK TO AVERAGE RATIO

4.7.1 LIMITS OF peak to average ratio MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

4.7.2 TEST SETUP



4.7.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

4.7.4 TEST RESULTS

GSM

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
661	1880	7.77

SPECTRUM PLOT OF WORST VALUE



EDGE

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
661	1880	9.88

SPECTRUM PLOT OF WORST VALUE



WCDMA

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
9400	1880	2.78

SPECTRUM PLOT OF WORST VALUE



LTE BAND 2

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
18607	1850.7	5.65	6.67	18615	1851.5	5.80	6.41
18900	1880	5.45	6.61	18900	1880	5.71	6.72
19193	1909.3	4.20	5.36	19185	1908.5	4.64	5.42

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



3MHz / QPSK



3MHz / 16QAM



CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
18625	1852.5	5.54	6.49	18650	1855	5.86	6.67
18900	1880	5.48	6.32	18900	1880	5.74	6.58
19175	1907.5	4.75	5.77	19150	1905	5.19	6.09

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM



CHANNEL BANDWIDTH: 15MHz				CHANNEL BANDWIDTH: 20MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
18675	1857.5	5.62	6.58	18700	1860	5.48	6.49
18900	1880	5.65	6.46	18900	1880	5.36	6.38
19125	1902.5	5.33	6.23	19100	1900	5.30	5.32

SPECTRUM PLOT OF WORST VALUE

15MHz / QPSK



15MHz / 16QAM



20MHz / QPSK



20MHz / 16QAM



5 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch, were founded in 2002 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Dongguan EMC/RF Lab:
Tel: +86-769-85935656
Fax: +86-769-85931080

Email: customerservice.dg@cn.bureauveritas.com
Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---