

FCC TEST REPORT

(Part 15, Subpart C)

Product: smartphone

Model Name: Ilium LT520

FCC ID: ZC4LT520

Applicant: Corporativo Lanix S.A. de C.V.

Address: Carretera Internacional Hermosillo-Nogales Km 8.5, Hermosillo
Sonora, Mexico

Manufacturer: Shenzhen Tinnio Mobile Technology Corp.

Address: 4/F., H-3 Building, OCT Eastern Industrial Park. NO.1 XiangShan
East Road., Nan Shan District, Shenzhen, P.R.China.

Prepared by: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

Lab Location: No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan
City, Guangdong 523942, China

TEL: +86 769 8593 5656

FAX: +86 769 8593 1080

E-MAIL: customerservice.dg@cn.bureauveritas.com

Report No.: RF170118W004-2

Received Date: Jan. 18, 2017

Test Date: Jan. 19, 2017 ~ Feb. 18, 2017

Issued Date: Feb. 20, 2017

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 CERTIFICATION	5
2 SUMMARY OF TEST RESULTS.....	6
2.1 MEASUREMENT UNCERTAINTY	6
3 GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	9
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST	10
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	10
3.3 DUTY CYCLE OF TEST SIGNAL	13
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS	14
3.5 DESCRIPTION OF SUPPORT UNITS	14
4 TEST TYPES AND RESULTS.....	15
4.1 CONDUCTED EMISSION MEASUREMENT	15
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	15
4.1.2 TEST INSTRUMENTS.....	15
4.1.3 TEST PROCEDURES	16
4.1.4 DEVIATION FROM TEST STANDARD	16
4.1.5 TEST SETUP.....	17
4.1.6 EUT OPERATING CONDITIONS	17
4.1.7 TEST RESULTS	18
4.2 RADIATED EMISSION MEASUREMENT	20
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	20
4.2.2 TEST INSTRUMENTS.....	21
4.2.3 TEST PROCEDURES	22
4.2.4 DEVIATION FROM TEST STANDARD	22
4.2.5 TEST SETUP.....	23
4.2.6 EUT OPERATING CONDITIONS	24
4.2.7 TEST RESULTS	25
4.3 6 DB BANDWIDTH MEASUREMENT	44
4.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT	44
4.3.2 TEST INSTRUMENTS.....	44
4.3.3 TEST PROCEDURE.....	44
4.3.4 DEVIATION FROM TEST STANDARD	45
4.3.5 TEST SETUP.....	45



Test Report No.: RF170118W004-2

4.3.6	EUT OPERATING CONDITIONS	45
4.3.7	TEST RESULTS	46
4.4	CONDUCTED OUTPUT POWER.....	51
4.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	51
4.4.2	TEST SETUP.....	51
4.4.3	TEST INSTRUMENTS.....	51
4.4.4	TEST PROCEDURES	51
4.4.5	DEVIATION FROM TEST STANDARD	51
4.4.6	EUT OPERATING CONDITIONS	51
4.4.7	TEST RESULTS	52
4.4.7.1	MAXIMUM PEAK OUTPUT POWER	52
4.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	54
4.5	POWER SPECTRAL DENSITY MEASUREMENT	56
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	56
4.5.2	TEST SETUP.....	56
4.5.3	TEST INSTRUMENTS.....	56
4.5.4	TEST PROCEDURE.....	56
4.5.5	DEVIATION FROM TEST STANDARD	56
4.5.6	EUT OPERATING CONDITION	56
4.5.7	TEST RESULTS	57
4.6	OUT OF BAND EMISSION MEASUREMENT	62
4.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	62
4.6.2	TEST SETUP.....	62
4.6.3	TEST INSTRUMENTS.....	62
4.6.4	TEST PROCEDURE.....	62
4.6.5	DEVIATION FROM TEST STANDARD	63
4.6.6	EUT OPERATING CONDITION	63
4.6.7	TEST RESULTS	63
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	74
6	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	75



Test Report No.: RF170118W004-2

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF170118W004-2	Original release	Feb. 20, 2017



Test Report No.: RF170118W004-2

1 CERTIFICATION

PRODUCT: smartphone
BRAND NAME: LANIX
MODEL NAME: Ilium LT520
APPLICANT: Corporativo Lanix S.A. de C.V.
TESTED: Jan. 19, 2017 ~ Feb. 18, 2017
TEST SAMPLE: Identical Prototype
STANDARDS: FCC Part 15, Subpart C. Section 15.247
ANSI C63.10-2013

The above equipment has been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : _____, **DATE:** Feb. 20, 2017
(Harry Li/ Engineer)

APPROVED BY : _____, **DATE:** Feb. 20, 2017
(Sam Tung / Manager)



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -6.74dB at 0.616000MHz.
15.205 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -1.61dB at 2390MHz.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.70dB
Radiated emissions	9KHz ~ 30MHz	2.90dB
	30MHz ~ 1GMHz	4.06dB
	1GHz ~ 18GHz	4.58dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	smartphone
BRAND NAME	LANIX
MODEL NAME	Ilium LT520
NOMINAL VOLTAGE	5.0Vdc (adapter or host equipment) 3.8Vdc (Li-ion, battery)
MODULATION TECHNOLOGY	DSSS, OFDM, DTS
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM BT-LE(GFSK) for DTS
TRANSMISSION RATE	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n: up to 135 Mbps BT_LE: 1 Mbps
OPERATING FREQUENCY	2412-2462MHz for 11b/g/n(HT20) 2422-2452MHz for 11n(HT40) 2402-2480MHz for BT-LE(GFSK)
MAX. OUTPUT POWER	WLAN: 49.091mW (Maximum) BT-LE: 0.813mW (Maximum)
ANTENNA TYPE	PIFA Antenna with 1.2dBi gain
HW VERSION	V1
SW VERSION	Ilium LT520_TELCEL_SW_01
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB cable: non-shielded, detachable, 1.0m Earphone cable: non-shielded, detachable, 1.0m

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
802.11b	1TX /1RX
802.11g	1TX /1RX
802.11n (20MHz)	1TX /1RX
802.11n (40MHz)	1TX /1RX



3. The EUT was powered by the following adapter:

ADAPTER	
BRAND:	Lanix
MODEL:	Ilium LT520
INPUT:	AC 100-240V, 120mA
OUTPUT:	DC 5V, 1000mA

4. The EUT matched the following USB cable and Earphone:

USB CABLE	
BRAND:	LANIX
MODEL:	Ilium LT520
SIGNAL LINE:	1.0 METER

EARPHONE	
BRAND:	LANIX
MODEL:	Ilium LT520
SIGNAL LINE:	1.0 METER

5. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	1	OFDM	BPSK	6.0
BT-LE	0 to 39	39	DTS	GFSK	1

**RADIATED EMISSION TEST (ABOVE 1GHz):**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	13.5
BT-LE	0 to 39	0,19, 39	DTS	GFSK	1

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	1	OFDM	BPSK	6.0

BANDEDGE MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3, 9	OFDM	BPSK	13.5
BT-LE	0 to 39	0, 39	DTS	GFSK	1

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	13.5
BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	22deg. C, 54%RH	DC 5V from adaptor	Tony Zou
RE≥1G	22deg. C, 54%RH	DC 5V from adaptor	Tony Zou
PLC	25deg. C, 60%RH	DC 5V from adaptor	Alex Chen
APCM	25deg. C, 60%RH	3.8Vdc from battery	Wenliang Wu



Test Report No.: RF170118W004-2

3.3 DUTY CYCLE OF TEST SIGNAL


WIFI 2.4GHz

802.11b: Duty cycle = $0.733/0.740 = 0.991 > 98\%$, Duty factor is not required.

802.11g: Duty cycle = $0.088/0.097 = 0.907 < 98\%$, Duty factor = $10 * \log(1/0.907) = 0.423$

802.11n (HT20): Duty cycle = $0.010/0.018 = 0.556 < 98\%$, Duty factor = $10 * \log(1/0.556) = 2.553$

802.11n (HT40): Duty cycle = $0.195/0.198 = 0.985 > 98\%$, Duty factor is not required.





3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v03r05

ANSI C63.10-2013

Note:

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,16	Apr. 04,17
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Mar. 04,16	Mar. 03,17
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Apr. 05,16	Apr. 04,17
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Nov. 25,16	Nov. 24,17
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

NOTE:

1. The test was performed in shielded room 553.
2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.



4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80
from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- Turned on the power and connected of all equipment.
- EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



4.1.7 TEST RESULTS


CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Alex Chen	TEST DATE	2017/02/09

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.700000	---	23.45	46.00	-22.55	L	ON	9.6
0.700000	33.90	---	56.00	-22.10	L	ON	9.6
1.200000	---	30.69	46.00	-15.31	L	ON	9.7
1.200000	41.94	---	56.00	-14.06	L	ON	9.7
1.832000	---	33.39	46.00	-12.61	L	ON	9.7
1.832000	43.96	---	56.00	-12.04	L	ON	9.7
2.308000	---	31.13	46.00	-14.87	L	ON	9.7
2.308000	41.16	---	56.00	-14.84	L	ON	9.7
4.122000	---	29.30	46.00	-16.70	L	ON	9.7
4.122000	38.44	---	56.00	-17.56	L	ON	9.7
22.168000	---	26.82	50.00	-23.18	L	ON	9.9
22.168000	35.64	---	60.00	-24.36	L	ON	9.9

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.

Full Spectrum






Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Alex Chen	TEST DATE	2017/02/09

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.616000	---	37.73	46.00	-8.27	N	ON	10.1
0.616000	49.26	---	56.00	-6.74	N	ON	10.1
1.220000	---	32.89	46.00	-13.11	N	ON	9.9
1.220000	44.61	---	56.00	-11.39	N	ON	9.9
1.784000	---	37.89	46.00	-8.11	N	ON	9.8
1.784000	48.69	---	56.00	-7.31	N	ON	9.8
2.344000	---	37.67	46.00	-8.33	N	ON	9.8
2.344000	47.94	---	56.00	-8.06	N	ON	9.8
3.804000	---	35.80	46.00	-10.20	N	ON	9.8
3.804000	43.11	---	56.00	-12.89	N	ON	9.8
22.652000	---	32.82	50.00	-17.18	N	ON	10.1
22.652000	45.24	---	60.00	-14.76	N	ON	10.1

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



Test Report No.: RF170118W004-2

4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,16	Apr. 04,17
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Nov. 04,16	Nov. 03,17
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 14, 16	Jul. 13, 17
Loop antenna	Daze	ZN30900A	0708	Nov. 28, 16	Nov. 27, 17
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 18,16	May 17,17
10m Semi-anechoic Chamber	CHANGLING	21.4m*12.1m*8.8m	NSEMC006	Mar. 12,16	Mar. 11,18
Test Software	E3	V 9.160323	N/A	N/A	N/A
Horn Antenna (15GHz-40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170242	Mar. 12,16	Mar. 11,17
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Mar. 04,16	Mar. 03, 17
Pre-Amplifier(1-18G)	HP	8449B	3008A00409	Apr. 25,16	Apr. 24,17
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 04,16	Nov. 03,17
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug. 08,16	Aug. 07,17

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 10m Chamber.
3. The FCC Site Registration No. is 502831.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 10 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be performed using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor (10 log(1/duty cycle)).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


4.2.4 DEVIATION FROM TEST STANDARD

No deviation




4.2.5 TEST SETUP

< Frequency Range below 30MHz >




< Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

9 KHz – 30 KHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:


802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
43.58	26.71	54.29	40.00	-13.29	8.88	0.99	37.45	200	24	QP
107.60	36.58	64.23	43.50	-6.92	7.73	1.59	36.97	200	63	QP
171.62	32.01	56.68	43.50	-11.49	10.03	2.01	36.71	200	105	QP
265.71	19.96	41.35	46.00	-26.04	12.59	2.53	36.51	200	280	QP
320.03	30.48	50.37	46.00	-15.52	13.84	2.81	36.54	200	96	QP
422.85	25.20	41.28	46.00	-20.80	17.47	3.22	36.77	200	179	QP

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.





**BUREAU
VERITAS**


Test Report No.: RF170118W004-2

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
31.94	35.23	56.19	40.00	-4.77	15.76	0.82	37.54	100	34	QP
83.35	34.65	63.65	40.00	-5.35	6.70	1.41	37.11	100	94	QP
101.78	37.78	65.28	43.50	-5.72	7.94	1.55	36.99	100	69	QP
183.26	27.74	52.40	43.50	-15.76	9.93	2.08	36.67	100	95	QP
319.06	24.22	44.16	46.00	-21.78	13.80	2.80	36.54	100	157	QP
422.85	24.13	40.21	46.00	-21.87	17.47	3.22	36.77	100	236	QP

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.





ABOVE 1GHz WORST-CASE DATA:

Note: For higher frequency, the emission is too low to be detected.

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	36.04	43.91	54.00	-17.96	32.29	8.15	48.31	160	232	Average
2390	47.64	55.51	74.00	-26.36	32.29	8.15	48.31	160	232	Peak
2412	100.07	107.88			32.31	8.19	48.31	160	232	Average
2412	102.44	110.25			32.31	8.19	48.31	160	232	Peak
2483.5	34.10	41.70	54.00	-19.90	32.38	8.32	48.30	160	232	Average
2483.5	45.82	53.42	74.00	-28.18	32.38	8.32	48.30	160	232	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2387	40.25	48.12	54.00	-13.75	32.29	8.15	48.31	100	280	Average
2387	48.72	56.59	74.00	-25.28	32.29	8.15	48.31	100	280	Peak
2412	102.84	110.65			32.31	8.19	48.31	100	280	Average
2412	105.29	113.10			32.31	8.19	48.31	100	280	Peak
2483.5	35.05	42.65	54.00	-18.95	32.38	8.32	48.30	100	280	Average
2483.5	47.27	54.87	74.00	-26.73	32.38	8.32	48.30	100	280	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.92	42.79	54.00	-19.08	32.29	8.15	48.31	156	235	Average
2390	45.70	53.57	74.00	-28.30	32.29	8.15	48.31	156	235	Peak
2437	99.66	107.39			32.34	8.24	48.31	156	235	Average
2437	101.71	109.44			32.34	8.24	48.31	156	235	Peak
2483.5	36.03	43.63	54.00	-17.97	32.38	8.32	48.30	156	235	Average
2483.5	46.83	54.43	74.00	-27.17	32.38	8.32	48.30	156	235	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	36.14	44.01	54.00	-17.86	32.29	8.15	48.31	100	280	Average
2390	46.07	53.94	74.00	-27.93	32.29	8.15	48.31	100	280	Peak
2437	102.23	109.96			32.34	8.24	48.31	100	280	Average
2437	104.24	111.97			32.34	8.24	48.31	100	280	Peak
2483.5	38.38	45.98	54.00	-15.62	32.38	8.32	48.30	100	280	Average
2483.5	49.15	56.75	74.00	-24.85	32.38	8.32	48.30	100	280	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: RF170118W004-2

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.91	41.78	54.00	-20.09	32.29	8.15	48.31	156	238	Average
2390	45.26	53.13	74.00	-28.74	32.29	8.15	48.31	156	238	Peak
2462	99.40	107.06			32.36	8.28	48.30	156	238	Average
2462	101.63	109.29			32.36	8.28	48.30	156	238	Peak
2483.5	37.03	44.63	54.00	-16.97	32.38	8.32	48.30	156	238	Average
2483.5	48.41	56.01	74.00	-25.59	32.38	8.32	48.30	156	238	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.68	42.55	54.00	-19.32	32.29	8.15	48.31	100	285	Average
2390	45.28	53.15	74.00	-28.72	32.29	8.15	48.31	100	285	Peak
2462	102.04	109.70			32.36	8.28	48.30	100	285	Average
2462	104.31	111.97			32.36	8.28	48.30	100	285	Peak
2483.5	43.63	51.23	54.00	-10.37	32.38	8.32	48.30	100	285	Average
2483.5	51.78	59.38	74.00	-22.22	32.38	8.32	48.30	100	285	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



Test Report No.: RF170118W004-2

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.72	51.59	54.00	-10.28	32.29	8.15	48.31	107	235	Average
2390	58.96	66.83	74.00	-15.04	32.29	8.15	48.31	107	235	Peak
2412	95.63	103.44			32.31	8.19	48.31	107	235	Average
2412	103.29	111.10			32.31	8.19	48.31	107	235	Peak
2483.5	36.37	43.97	54.00	-17.63	32.38	8.32	48.30	107	235	Average
2483.5	47.74	55.34	74.00	-26.26	32.38	8.32	48.30	107	235	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	52.39	60.26	54.00	-1.61	32.29	8.15	48.31	100	290	Average
2390	68.25	76.12	74.00	-5.75	32.29	8.15	48.31	100	290	Peak
2412	98.51	106.32			32.31	8.19	48.31	100	290	Average
2412	106.07	113.88			32.31	8.19	48.31	100	290	Peak
2483.5	38.57	46.17	54.00	-15.43	32.38	8.32	48.30	100	290	Average
2483.5	50.07	57.67	74.00	-23.93	32.38	8.32	48.30	100	290	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	38.67	46.54	54.00	-15.33	32.29	8.15	48.31	106	255	Average
2390	49.27	57.14	74.00	-24.73	32.29	8.15	48.31	106	255	Peak
2437	94.37	102.10			32.34	8.24	48.31	106	255	Average
2437	102.40	110.13			32.34	8.24	48.31	106	255	Peak
2483.5	39.32	46.92	54.00	-14.68	32.38	8.32	48.30	106	255	Average
2483.5	50.77	58.37	74.00	-23.23	32.38	8.32	48.30	106	255	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	41.33	49.20	54.00	-12.67	32.29	8.15	48.31	100	290	Average
2390	51.24	59.11	74.00	-22.76	32.29	8.15	48.31	100	290	Peak
2437	98.51	106.24			32.34	8.24	48.31	100	290	Average
2437	106.09	113.82			32.34	8.24	48.31	100	290	Peak
2483.5	44.11	51.71	54.00	-9.89	32.38	8.32	48.30	100	290	Average
2483.5	55.24	62.84	74.00	-18.76	32.38	8.32	48.30	100	290	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	35.55	43.42	54.00	-18.45	32.29	8.15	48.31	156	238	Average
2390	46.11	53.98	74.00	-27.89	32.29	8.15	48.31	156	238	Peak
2462	94.04	101.70			32.36	8.28	48.30	156	238	Average
2462	101.69	109.35			32.36	8.28	48.30	156	238	Peak
2483.5	47.15	54.75	54.00	-6.85	32.38	8.32	48.30	156	238	Average
2483.5	63.22	70.82	74.00	-10.78	32.38	8.32	48.30	156	238	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	36.97	44.84	54.00	-17.03	32.29	8.15	48.31	100	280	Average
2390	48.18	56.05	74.00	-25.82	32.29	8.15	48.31	100	280	Peak
2462	96.68	104.34			32.36	8.28	48.30	100	280	Average
2462	104.26	111.92			32.36	8.28	48.30	100	280	Peak
2483.5	52.25	59.85	54.00	-1.75	32.38	8.32	48.30	100	280	Average
2483.5	68.05	75.65	74.00	-5.95	32.38	8.32	48.30	100	280	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	41.01	48.88	54.00	-12.99	32.29	8.15	48.31	156	232	Average
2390	55.48	63.35	74.00	-18.52	32.29	8.15	48.31	156	232	Peak
2412	93.13	100.94			32.31	8.19	48.31	156	232	Average
2412	100.23	108.04			32.31	8.19	48.31	156	232	Peak
2483.5	36.20	43.80	54.00	-17.80	32.38	8.32	48.30	156	232	Average
2483.5	47.55	55.15	74.00	-26.45	32.38	8.32	48.30	156	232	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.98	58.85	54.00	-3.02	32.29	8.15	48.31	100	290	Average
2390	66.94	74.81	74.00	-7.06	32.29	8.15	48.31	100	290	Peak
2412	96.45	104.26			32.31	8.19	48.31	100	290	Average
2412	103.61	111.42			32.31	8.19	48.31	100	290	Peak
2483.5	38.30	45.90	54.00	-15.70	32.38	8.32	48.30	100	290	Average
2483.5	49.31	56.91	74.00	-24.69	32.38	8.32	48.30	100	290	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	38.37	46.24	54.00	-15.63	32.29	8.15	48.31	107	250	Average
2390	49.16	57.03	74.00	-24.84	32.29	8.15	48.31	107	250	Peak
2437	94.19	101.92			32.34	8.24	48.31	107	250	Average
2437	101.73	109.46			32.34	8.24	48.31	107	250	Peak
2483.5	38.55	46.15	54.00	-15.45	32.38	8.32	48.30	107	250	Average
2483.5	49.98	57.58	74.00	-24.02	32.38	8.32	48.30	107	250	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	41.03	48.90	54.00	-12.97	32.29	8.15	48.31	100	290	Average
2390	52.44	60.31	74.00	-21.56	32.29	8.15	48.31	100	290	Peak
2437	97.62	105.35			32.34	8.24	48.31	100	290	Average
2437	104.92	112.65			32.34	8.24	48.31	100	290	Peak
2483.5	43.61	51.21	54.00	-10.39	32.38	8.32	48.30	100	290	Average
2483.5	55.43	63.03	74.00	-18.57	32.38	8.32	48.30	100	290	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	35.10	42.97	54.00	-18.90	32.29	8.15	48.31	156	238	Average
2390	46.07	53.94	74.00	-27.93	32.29	8.15	48.31	156	238	Peak
2462	91.60	99.26			32.36	8.28	48.30	156	238	Average
2462	100.03	107.69			32.36	8.28	48.30	156	238	Peak
2483.5	45.77	53.37	54.00	-8.23	32.38	8.32	48.30	156	238	Average
2483.5	61.01	68.61	74.00	-12.99	32.38	8.32	48.30	156	238	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	36.46	44.33	54.00	-17.54	32.29	8.15	48.31	100	290	Average
2390	47.42	55.29	74.00	-26.58	32.29	8.15	48.31	100	290	Peak
2462	95.21	102.87			32.36	8.28	48.30	100	290	Average
2462	103.05	110.71			32.36	8.28	48.30	100	290	Peak
2483.5	52.31	59.91	54.00	-1.69	32.38	8.32	48.30	100	290	Average
2483.5	67.07	74.67	74.00	-6.93	32.38	8.32	48.30	100	290	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



802.11n (40MHz)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	39.41	47.28	54.00	-14.59	32.29	8.15	48.31	195	235	Average
2390	51.88	59.75	74.00	-22.12	32.29	8.15	48.31	195	235	Peak
2422	88.45	96.23			32.32	8.21	48.31	195	235	Average
2422	96.88	104.66			32.32	8.21	48.31	195	235	Peak
2483.5	35.54	43.14	54.00	-18.46	32.38	8.32	48.30	195	235	Average
2483.5	47.82	55.42	74.00	-26.18	32.38	8.32	48.30	195	235	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	49.81	57.68	54.00	-4.19	32.29	8.15	48.31	100	290	Average
2390	63.54	71.41	74.00	-10.46	32.29	8.15	48.31	100	290	Peak
2422	91.97	99.75			32.32	8.21	48.31	100	290	Average
2422	100.33	108.11			32.32	8.21	48.31	100	290	Peak
2483.5	37.68	45.28	54.00	-16.32	32.38	8.32	48.30	100	290	Average
2483.5	50.02	57.62	74.00	-23.98	32.38	8.32	48.30	100	290	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2422MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: RF170118W004-2

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	41.21	49.08	54.00	-12.79	32.29	8.15	48.31	106	250	Average
2390	55.54	63.41	74.00	-18.46	32.29	8.15	48.31	106	250	Peak
2437	88.51	96.24			32.34	8.24	48.31	106	250	Average
2437	96.27	104.00			32.34	8.24	48.31	106	250	Peak
2483.5	41.57	49.17	54.00	-12.43	32.38	8.32	48.30	106	250	Average
2483.5	55.02	62.62	74.00	-18.98	32.38	8.32	48.30	106	250	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.56	58.43	54.00	-3.44	32.29	8.15	48.31	100	290	Average
2390	65.14	73.01	74.00	-8.86	32.29	8.15	48.31	100	290	Peak
2437	91.72	99.45			32.34	8.24	48.31	100	290	Average
2437	99.59	107.32			32.34	8.24	48.31	100	290	Peak
2483.5	52.15	59.75	54.00	-1.85	32.38	8.32	48.30	100	290	Average
2483.5	66.16	73.76	74.00	-7.84	32.38	8.32	48.30	100	290	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.80	42.67	54.00	-19.20	32.29	8.15	48.31	136	252	Average
2390	45.83	53.70	74.00	-28.17	32.29	8.15	48.31	136	252	Peak
2452	88.13	95.82			32.35	8.26	48.30	136	252	Average
2452	95.74	103.43			32.35	8.26	48.30	136	252	Peak
2483.5	40.52	48.12	54.00	-13.48	32.38	8.32	48.30	136	252	Average
2483.5	52.21	59.81	74.00	-21.79	32.38	8.32	48.30	136	252	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	36.18	44.05	54.00	-17.82	32.29	8.15	48.31	100	290	Average
2390	46.61	54.48	74.00	-27.39	32.29	8.15	48.31	100	290	Peak
2452	91.34	99.03			32.35	8.26	48.30	100	290	Average
2452	98.77	106.46			32.35	8.26	48.30	100	290	Peak
2483.5	51.43	59.03	54.00	-2.57	32.38	8.32	48.30	100	290	Average
2483.5	62.76	70.36	74.00	-11.24	32.38	8.32	48.30	100	290	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2452MHz: Fundamental frequency.



BELOW 1GHz WORST-CASE DATA:

9 KHz – 30 KHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:


BT-LE (GFSK)

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
43.58	27.07	54.65	40.00	-12.93	8.88	0.99	37.45	200	42	QP
108.57	37.35	65.02	43.50	-6.15	7.70	1.60	36.97	200	63	QP
171.62	31.90	56.57	43.50	-11.60	10.03	2.01	36.71	200	145	QP
266.68	21.41	42.78	46.00	-24.59	12.60	2.54	36.51	200	188	QP
319.06	29.84	49.78	46.00	-16.16	13.80	2.80	36.54	200	280	QP
422.85	25.86	41.94	46.00	-20.14	17.47	3.22	36.77	200	95	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value






CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
38.73	36.24	61.73	40.00	-3.76	11.08	0.92	37.49	100	25	QP
102.75	38.69	66.21	43.50	-4.81	7.90	1.56	36.98	100	36	QP
187.14	29.26	53.83	43.50	-14.24	9.97	2.10	36.64	100	120	QP
319.06	24.21	44.15	46.00	-21.79	13.80	2.80	36.54	100	185	QP
422.85	23.99	40.07	46.00	-22.01	17.47	3.22	36.77	100	256	QP
598.42	29.20	42.18	46.00	-16.80	20.27	4.00	37.25	100	72	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value





Test Report No.: RF170118W004-2

ABOVE 1GHz TEST DATA:

Note: For higher frequency, the emission is too low to be detected.

BT-LE (GFSK)

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	32.71	40.58	54.00	-21.29	32.29	8.15	48.31	180	325	Average
2390	45.21	53.08	74.00	-28.79	32.29	8.15	48.31	180	325	Peak
2402	88.31	96.15			32.30	8.17	48.31	180	325	Average
2402	93.69	101.53			32.30	8.17	48.31	180	325	Peak
2483.5	32.84	40.44	54.00	-21.16	32.38	8.32	48.30	180	325	Average
2483.5	45.51	53.11	74.00	-28.49	32.38	8.32	48.30	180	325	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	32.72	40.59	54.00	-21.28	32.29	8.15	48.31	102	290	Average
2390	44.80	52.67	74.00	-29.20	32.29	8.15	48.31	102	290	Peak
2402	93.74	101.58			32.30	8.17	48.31	102	290	Average
2402	99.06	106.90			32.30	8.17	48.31	102	290	Peak
2483.5	32.85	40.45	54.00	-21.15	32.38	8.32	48.30	102	290	Average
2483.5	45.20	52.80	74.00	-28.80	32.38	8.32	48.30	102	290	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2402MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: RF170118W004-2

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	32.74	40.61	54.00	-21.26	32.29	8.15	48.31	175	318	Average
2390	44.85	52.72	74.00	-29.15	32.29	8.15	48.31	175	318	Peak
2440	89.59	97.32			32.34	8.24	48.31	175	318	Average
2440	94.77	102.50			32.34	8.24	48.31	175	318	Peak
2483.5	32.86	40.46	54.00	-21.14	32.38	8.32	48.30	175	318	Average
2483.5	45.45	53.05	74.00	-28.55	32.38	8.32	48.30	175	318	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	32.70	40.57	54.00	-21.30	32.29	8.15	48.31	100	288	Average
2390	44.29	52.16	74.00	-29.71	32.29	8.15	48.31	100	288	Peak
2440	95.14	102.87			32.34	8.24	48.31	100	288	Average
2440	100.32	108.05			32.34	8.24	48.31	100	288	Peak
2483.5	32.81	40.41	54.00	-21.19	32.38	8.32	48.30	100	288	Average
2483.5	45.88	53.48	74.00	-28.12	32.38	8.32	48.30	100	288	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2440MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: RF170118W004-2

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	32.59	40.46	54.00	-21.41	32.29	8.15	48.31	156	340	Average
2390	44.37	52.24	74.00	-29.63	32.29	8.15	48.31	156	340	Peak
2480	87.19	94.80			32.38	8.31	48.30	156	340	Average
2480	92.56	100.17			32.38	8.31	48.30	156	340	Peak
2483.5	33.08	40.68	54.00	-20.92	32.38	8.32	48.30	156	340	Average
2483.5	45.08	52.68	74.00	-28.92	32.38	8.32	48.30	156	340	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	32.55	40.42	54.00	-21.45	32.29	8.15	48.31	112	290	Average
2390	44.37	52.24	74.00	-29.63	32.29	8.15	48.31	112	290	Peak
2480	94.18	101.79			32.38	8.31	48.30	112	290	Average
2480	99.49	107.10			32.38	8.31	48.30	112	290	Peak
2483.5	33.68	41.28	54.00	-20.32	32.38	8.32	48.30	112	290	Average
2483.5	46.08	53.68	74.00	-27.92	32.38	8.32	48.30	112	290	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.



4.3 6 dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	May 04,16	May 03,17
Power Sensor	Keysight	U2021XA	MY55060018	May 04,16	May 03,17
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jul. 27, 16	Jul. 26, 17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 13, 16	Oct.12, 17
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.05,16	Sep. 04,17
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 04,16	Nov. 03,17
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 04,16	Nov. 03,17
Signal Generator	Agilent	N5183A	MY50140980	Nov. 04,16	Nov. 03,17
Agile Signal Generator	Agilent	8645A	Agilent	Aug.08, 16	Aug.07, 17
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Apr. 22, 16	Apr. 21, 17
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug.08, 16	Aug. 07, 17

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

4.3.3 TEST PROCEDURE


1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.3.7 TEST RESULTS

802.11b


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	9.14	0.5	PASS
6	2437	9.14	0.5	PASS
11	2462	9.14	0.5	PASS





802.11g


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.60	0.5	PASS
6	2437	16.62	0.5	PASS
11	2462	16.60	0.5	PASS





802.11n (20MHz)


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.83	0.5	PASS
6	2437	17.82	0.5	PASS
11	2462	17.81	0.5	PASS





802.11n (40MHz)


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
3	2422	36.42	0.5	PASS
6	2437	36.55	0.5	PASS
9	2452	36.51	0.5	PASS





BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.71	0.5	PASS
19	2440	0.71	0.5	PASS
39	2480	0.71	0.5	PASS






4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

**4.4.7 TEST RESULTS****4.4.7.1 MAXIMUM PEAK OUTPUT POWER****802.11b**

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	16.18	41.495	1	PASS
6	2437	16.59	45.604	1	PASS
11	2462	16.21	41.783	1	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	16.91	49.091	1	PASS
6	2437	16.80	47.863	1	PASS
11	2462	16.42	43.853	1	PASS

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	14.71	29.580	1	PASS
6	2437	14.62	28.973	1	PASS
11	2462	14.32	27.040	1	PASS

802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
3	2422	12.74	18.793	1	PASS
6	2437	12.83	19.187	1	PASS
9	2452	12.76	18.880	1	PASS



Test Report No.: RF170118W004-2

BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
0	2402	-1.36	0.731	1	PASS
19	2440	-0.90	0.813	1	PASS
39	2480	-2.11	0.615	1	PASS

**4.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)**

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	13.10	N/A
6	2437	13.65	N/A
11	2462	13.24	N/A

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	10.37	N/A
6	2437	10.04	N/A
11	2462	9.86	N/A

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	8.45	N/A
6	2437	8.31	N/A
11	2462	7.87	N/A

802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
3	2422	5.54	N/A
6	2437	6.03	N/A
9	2452	5.55	N/A



Test Report No.: RF170118W004-2

BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	-1.62	N/A
19	2440	-1.12	N/A
39	2480	-2.39	N/A




4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 3 kHz, VBW $\geq 3 \times$ RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.5.7 TEST RESULTS

802.11b


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-15.47	8	PASS
6	2437	-14.64	8	PASS
11	2462	-15.07	8	PASS





802.11g


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-17.84	8	PASS
6	2437	-17.60	8	PASS
11	2462	-18.43	8	PASS





802.11n (20MHz)


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-19.95	8	PASS
6	2437	-18.93	8	PASS
11	2462	-19.56	8	PASS





802.11n (40MHz)


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
3	2422	-23.21	8	PASS
6	2437	-24.19	8	PASS
9	2452	-23.61	8	PASS





BT-LE (GFSK)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	-14.94	8	PASS
19	2440	-14.30	8	PASS
39	2480	-15.65	8	PASS






4.6 OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.




BUREAU
VERITAS


Test Report No.: RF170118W004-2

802.11b


CH 1



CH 6



CH 11







BUREAU
VERITAS

Test Report No.: RF170118W004-2

CH 1 Band Edge



CH 11 Band Edge







BUREAU
VERITAS



Test Report No.: RF170118W004-2

802.11g



CH 1



CH 6



CH 11







BUREAU
VERITAS

Test Report No.: RF170118W004-2

CH 1 Band Edge



CH 11 Band Edge






BUREAU
VERITAS

Test Report No.: RF170118W004-2


802.11n (20MHz)





BUREAU
VERITAS

Test Report No.: RF170118W004-2






BUREAU
VERITAS

Test Report No.: RF170118W004-2

802.11n (40MHz)



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch


No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City, Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



BUREAU
VERITAS

Test Report No.: RF170118W004-2



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City, Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com




BUREAU
VERITAS


Test Report No.: RF170118W004-2

BT-LE (GFSK)


CH 0



CH 19




CH 39





BUREAU
VERITAS

Test Report No.: RF170118W004-2



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City, Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



Test Report No.: RF170118W004-2

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF170118W004-2

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---