

FCC TEST REPORT

(Part 15, Subpart C)

Applicant:	Corporativo Lanix S.A. de C.V.
Address:	Carretera Internacional Hermosillo-Nogales Km 8.5, Hermosillo Sonora, Mexico

Manufacturer or Supplier:	Corporativo Lanix S.A. de C.V.
Address:	Carretera Internacional Hermosillo-Nogales Km 8.5, Hermosillo Sonora, Mexico
Product:	Smartphone
Brand Name:	LANIX
Model Name:	Ilium M7
FCC ID:	ZC4M7
Date of tests:	Feb. 26, 2018 ~ Mar. 12, 2018

The tests have been carried out according to the requirements of the following standard:

- ☒ FCC Part 15, Subpart C, Section 15.247
- ☒ ANSI C63.10-2013

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Yuqiang Yin Engineer / Mobile Department	Approved by Bill Yao Manager / Mobile Department
 Date: Mar. 13, 2018	 Date: Mar. 13, 2018

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD	5
1 SUMMARY OF TEST RESULTS.....	6
1.1 MEASUREMENT UNCERTAINTY.....	6
2 GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	8
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST	9
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	9
2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	11
2.4 DESCRIPTION OF SUPPORT UNITS.....	11
3 TEST TYPES AND RESULTS.....	12
3.1 CONDUCTED EMISSION MEASUREMENT.....	12
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	12
3.1.2 TEST INSTRUMENTS.....	12
3.1.3 TEST PROCEDURES	12
3.1.4 DEVIATION FROM TEST STANDARD	13
3.1.5 TEST SETUP	13
3.1.6 EUT OPERATING CONDITIONS	13
3.1.7 TEST RESULTS.....	14
3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT	16
3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	16
3.2.2 TEST INSTRUMENTS.....	17
3.2.3 TEST PROCEDURES	18
3.2.4 DEVIATION FROM TEST STANDARD	18
3.2.5 TEST SETUP	19
3.2.6 EUT OPERATING CONDITIONS	20
3.2.7 TEST RESULTS.....	21
3.3 NUMBER OF HOPPING FREQUENCY USED	29
3.3.1 LIMIT OF HOPPING FREQUENCY USED	29
3.3.2 TEST SETUP	29
3.3.3 TEST INSTRUMENTS.....	29
3.3.4 TEST PROCEDURES	30
3.3.5 DEVIATION FROM TEST STANDARD	30
3.3.6 TEST RESULTS.....	30
3.4 DWELL TIME ON EACH CHANNEL	33

3.4.1	LIMIT OF DWELL TIME USED	33
3.4.2	TEST SETUP	33
3.4.3	TEST INSTRUMENTS.....	33
3.4.4	TEST PROCEDURES	33
3.4.5	DEVIATION FROM TEST STANDARD	34
3.4.6	TEST RESULTS.....	34
3.5	CHANNEL BANDWIDTH	38
3.5.1	LIMITS OF CHANNEL BANDWIDTH	38
3.5.2	TEST SETUP	38
3.5.3	TEST INSTRUMENTS.....	38
3.5.4	TEST PROCEDURE	38
3.5.5	DEVIATION FROM TEST STANDARD	38
3.5.6	EUT OPERATING CONDITION.....	39
3.5.7	TEST RESULTS.....	39
3.6	HOPPING CHANNEL SEPARATION	45
3.6.1	LIMIT OF HOPPING CHANNEL SEPARATION	45
3.6.2	TEST SETUP	45
3.6.3	TEST INSTRUMENTS.....	45
3.6.4	TEST PROCEDURES	45
3.6.5	DEVIATION FROM TEST STANDARD	45
3.6.6	TEST RESULTS.....	46
3.7	MAXIMUM OUTPUT POWER.....	50
3.7.1	LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT	50
3.7.2	TEST SETUP	50
3.7.3	TEST INSTRUMENTS.....	50
3.7.4	TEST PROCEDURES	50
3.7.5	DEVIATION FROM TEST STANDARD	50
3.7.6	EUT OPERATING CONDITION.....	50
3.7.7	TEST RESULTS.....	51
3.7.8	AVERAGE OUTPUT POWER (FOR REFERENCE)	52
3.8	OUT OF BAND MEASUREMENT	53
3.8.1	LIMITS OF OUT OF BAND MEASUREMENT.....	53
3.8.2	TEST INSTRUMENTS.....	53
3.8.3	TEST PROCEDURE	53
3.8.4	DEVIATION FROM TEST STANDARD	53
3.8.5	EUT OPERATING CONDITION.....	53



Test Report No.: RF180224W001-1

3.8.6	TEST RESULTS.....	53
4	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	58
5	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	59



Test Report No.: RF180224W001-1

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF180224W001-1	Original release	Mar. 13, 2018

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -10.60dB at 12.916000MHz.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)&15.209	Transmitter Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -6.56dB at 2390MHz.
15.247(d)	Out of band Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

NOTE: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in ETSI TR 100 028-2001:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
Radiated emissions	9KHz ~ 30MHz	2.68dB
	30MHz ~ 1GMHz	3.26dB
	1GHz ~ 18GHz	4.48dB
	18GHz ~ 40GHz	4.12dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Smartphone
MODEL NAME	Ilium M7
POWER SUPPLY	5Vdc (adapter or host equipment) 3.8Vdc (Li-ion, battery)
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, 8DPSK, $\pi/4$ DQPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
MAX. OUTPUT POWER	3.04mW (Max. Measured)
ANTENNA TYPE	PIFA Antenna with 1.5dBi gain
HW VERSION	V1.0
SW VERSION	Ilium M7_SW_01
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB cable: non-shielded, detachable, 1.0meter Earphone cable: non-shielded, detachable, 1.2meter

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT was powered by the following adapter:

ADAPTER	
BRAND:	LANIX
MODEL:	Ilium M7-C
INPUT:	AC 100-240V, 150mA
OUTPUT:	DC 5V, 1000mA

- The EUT matched the following USB cable and earphone:

USB CABLE	
BRAND:	LANIX
MODEL:	Ilium M7
SIGNAL LINE:	1.0 METER

EARPHONE	
BRAND:	LANIX
MODEL:	Ilium M7
SIGNAL LINE:	1.2 METER

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

2.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on X axis for radiated emission.

Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0	FHSS	8DPSK	DH5

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	DH5

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0	FHSS	8DPSK	DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	$\pi/4$ DQPSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	22deg. C, 54%RH	DC 5V from adaptor	Star Le
RE≥1G	22deg. C, 54%RH	DC 5V from adaptor	Star Le
PLC	24deg. C, 55%RH	DC 5V from adaptor	Jocan Guo
APCM	25deg. C, 60%RH	DC 3.8V from battery	Wenliang Wu

2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. Section 15.247

ANSI C63.10-2013

FCC Public Notice DA 00-705

NOTE:

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m

3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:** 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Jun. 28,17	Jun. 27,18
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Sep. 18,17	Sep. 17,18

- NOTE:** 1. The test was performed in CE shielded room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

3.1.3 TEST PROCEDURES


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.

3.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

3.1.7 TEST RESULTS


CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Jocan Guo	TEST DATE	2018/02/26

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	31.56	56.00	-24.44	L1	ON	9.6
0.150000	41.04	---	66.00	-24.96	L1	ON	9.6
3.568000	---	29.92	46.00	-16.08	L1	ON	9.7
3.568000	35.82	---	56.00	-20.18	L1	ON	9.7
4.216000	---	28.74	46.00	-17.26	L1	ON	9.7
4.216000	35.57	---	56.00	-20.43	L1	ON	9.7
10.308000	---	34.77	50.00	-15.23	L1	ON	9.9
10.308000	40.74	---	60.00	-19.26	L1	ON	9.9
13.364000	---	34.50	50.00	-15.50	L1	ON	9.9
13.364000	40.93	---	60.00	-19.07	L1	ON	9.9
19.084000	---	24.72	50.00	-25.28	L1	ON	9.9
19.084000	34.96	---	60.00	-25.04	L1	ON	9.9

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum




Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Jocan Guo	TEST DATE	2018/02/26

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.472000	---	32.33	46.48	-14.15	N	ON	10.1
0.472000	40.93	---	56.48	-15.55	N	ON	10.1
2.960000	---	28.75	46.00	-17.25	N	ON	9.8
2.960000	39.41	---	56.00	-16.59	N	ON	9.8
4.396000	---	33.89	46.00	-12.11	N	ON	9.8
4.396000	43.43	---	56.00	-12.57	N	ON	9.8
9.960000	---	38.45	50.00	-11.55	N	ON	9.9
9.960000	47.86	---	60.00	-12.14	N	ON	9.9
12.916000	---	39.39	50.00	-10.61	N	ON	9.9
12.916000	49.40	---	60.00	-10.60	N	ON	9.9
18.748000	---	32.00	50.00	-18.00	N	ON	10.0
18.748000	44.16	---	60.00	-15.84	N	ON	10.0

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum



3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May 06,17	May 05,18
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Nov. 26,16	Nov. 25,18
Horn Antenna	ETS-LINDGREN	3117	00168728	Nov. 26,16	Nov. 25,18
Loop antenna	Daze	ZN30900A	0708	Nov. 20,17	Nov. 19,18
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Dec. 16,16	Dec. 15,18
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jul. 24,17	Jul. 23,18
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 10,18	Mar. 09,19
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jul. 24,17	Jul. 23,18

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Chamber.
 3. The FCC Site Registration No. is 525120.

3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit.
5. All modes of operation were investigated and the worst-case emissions are reported.

3.2.4 DEVIATION FROM TEST STANDARD


No deviation.

3.2.5 TEST SETUP


< Frequency Range below 30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

3.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

9 KHz – 30 KHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:


BT_8DPSK

CHANNEL	Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
48.43	15.56	44.83	-24.44	7.08	1.05	37.4	40	200	124	QP
113.42	30.56	58.36	-12.94	7.53	1.63	36.96	43.5	200	63	QP
144.46	33.72	60.15	-9.78	8.54	1.85	36.82	43.5	200	80	QP
170.65	23.66	48.33	-19.84	10.04	2	36.71	43.5	200	156	QP
229.82	32.32	55.04	-13.68	11.47	2.34	36.53	46	200	210	QP
260.86	23.91	45.39	-22.09	12.53	2.51	36.52	46	200	172	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




CHANNEL	Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
38.73	27.06	52.55	-12.94	11.08	0.92	37.49	40	100	24	QP
94.02	25	53.19	-18.5	7.34	1.49	37.02	43.5	100	72	QP
144.46	33.79	60.22	-9.71	8.54	1.85	36.82	43.5	100	163	QP
227.88	30.68	53.5	-15.32	11.38	2.33	36.53	46	100	210	QP
288.02	22.14	43.12	-23.86	12.86	2.66	36.5	46	100	180	QP
385.02	26.22	43.25	-19.78	16.57	3.09	36.69	46	100	236	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



ABOVE 1GHz WORST-CASE DATA:

Note: For higher frequency, the emission is too low to be detected.

GFSK DH5

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.54	54.41	-7.46	32.29	8.15	48.31	54	100	20	Average
2390	56.93	64.8	-17.07	32.29	8.15	48.31	74	100	20	Peak
2402	97.06	104.9		32.3	8.17	48.31		100	20	Average
2402	101.92	109.76		32.3	8.17	48.31		100	20	Peak
2483.5	41.46	49.06	-12.54	32.38	8.32	48.3	54	100	20	Average
2483.5	52.29	59.89	-21.71	32.38	8.32	48.3	74	100	20	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	45.43	53.3	-8.57	32.29	8.15	48.31	54	104	295	Average
2390	56.17	64.04	-17.83	32.29	8.15	48.31	74	104	295	Peak
2402	93.56	101.4		32.3	8.17	48.31		104	295	Average
2402	97.47	105.31		32.3	8.17	48.31		104	295	Peak
2483.5	42.51	50.11	-11.49	32.38	8.32	48.3	54	104	295	Average
2483.5	52.2	59.8	-21.8	32.38	8.32	48.3	74	104	295	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2402MHz: Fundamental frequency.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	45.29	53.16	-8.71	32.29	8.15	48.31	54	100	21	Average
2390	59.06	66.93	-14.94	32.29	8.15	48.31	74	100	21	Peak
2441	95.6	103.33		32.34	8.24	48.31		100	21	Average
2441	101.87	109.6		32.34	8.24	48.31		100	21	Peak
2483.5	41.45	49.05	-12.55	32.38	8.32	48.3	54	100	21	Average
2483.5	52.65	60.25	-21.35	32.38	8.32	48.3	74	100	21	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	45.45	53.32	-8.55	32.29	8.15	48.31	54	130	295	Average
2390	56.23	64.1	-17.77	32.29	8.15	48.31	74	130	295	Peak
2441	93.7	101.43		32.34	8.24	48.31		130	295	Average
2441	98.21	105.94		32.34	8.24	48.31		130	295	Peak
2483.5	41.52	49.12	-12.48	32.38	8.32	48.3	54	130	295	Average
2483.5	52.66	60.26	-21.34	32.38	8.32	48.3	74	130	295	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor

Margin value = Emission level – Limit value.

2. 2441MHz: Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	47.39	55.26	-6.61	32.29	8.15	48.31	54	110	30	Average
2390	57.65	65.52	-16.35	32.29	8.15	48.31	74	110	30	Peak
2480	94.53	102.14		32.38	8.31	48.3		110	30	Average
2480	100.01	107.62		32.38	8.31	48.3		110	30	Peak
2483.5	41.9	49.5	-12.1	32.38	8.32	48.3	54	110	30	Average
2483.5	53.88	61.48	-20.12	32.38	8.32	48.3	74	110	30	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.38	54.25	-7.62	32.29	8.15	48.31	54	115	296	Average
2390	58.12	65.99	-15.88	32.29	8.15	48.31	74	115	296	Peak
2480	93.4	101.01		32.38	8.31	48.3		115	296	Average
2480	98.17	105.78		32.38	8.31	48.3		115	296	Peak
2483.5	42	49.6	-12	32.38	8.32	48.3	54	115	296	Average
2483.5	53.23	60.83	-20.77	32.38	8.32	48.3	74	115	296	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.

BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.46	54.33	-7.54	32.29	8.15	48.31	54	100	20	Average
2390	57.46	65.33	-16.54	32.29	8.15	48.31	74	100	20	Peak
2402	95.87	103.71		32.3	8.17	48.31		100	20	Average
2402	101.27	109.11		32.3	8.17	48.31		100	20	Peak
2483.5	41.57	49.17	-12.43	32.38	8.32	48.3	54	100	20	Average
2483.5	53.82	61.42	-20.18	32.38	8.32	48.3	74	100	20	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	47.44	55.31	-6.56	32.29	8.15	48.31	54	135	298	Average
2390	58.19	66.06	-15.81	32.29	8.15	48.31	74	135	298	Peak
2402	93.66	101.5		32.3	8.17	48.31		135	298	Average
2402	98.9	106.74		32.3	8.17	48.31		135	298	Peak
2483.5	42.59	50.19	-11.41	32.38	8.32	48.3	54	135	298	Average
2483.5	52.66	60.26	-21.34	32.38	8.32	48.3	74	135	298	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2402MHz: Fundamental frequency.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.48	54.35	-7.52	32.29	8.15	48.31	54	100	25	Average
2390	59.02	66.89	-14.98	32.29	8.15	48.31	74	100	25	Peak
2441	96.24	103.97		32.34	8.24	48.31		100	25	Average
2441	101.85	109.58		32.34	8.24	48.31		100	25	Peak
2483.5	41.52	49.12	-12.48	32.38	8.32	48.3	54	100	25	Average
2483.5	53.9	61.5	-20.1	32.38	8.32	48.3	74	100	25	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.34	54.21	-7.66	32.29	8.15	48.31	54	145	295	Average
2390	56.68	64.55	-17.32	32.29	8.15	48.31	74	145	295	Peak
2441	94.44	102.17		32.34	8.24	48.31		145	295	Average
2441	97.81	105.54		32.34	8.24	48.31		145	295	Peak
2483.5	42.53	50.13	-11.47	32.38	8.32	48.3	54	145	295	Average
2483.5	51.59	59.19	-22.41	32.38	8.32	48.3	74	145	295	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2441MHz: Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.36	54.23	-7.64	32.29	8.15	48.31	54	110	30	Average
2390	59.48	67.35	-14.52	32.29	8.15	48.31	74	110	30	Peak
2480	96.29	103.9		32.38	8.31	48.3		110	30	Average
2480	101.76	109.37		32.38	8.31	48.3		110	30	Peak
2483.5	43.27	50.87	-10.73	32.38	8.32	48.3	54	110	30	Average
2483.5	52.52	60.12	-21.48	32.38	8.32	48.3	74	110	30	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	MARGIN (dB)	ANTENN A FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	LIMIT (dBuV/m)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.36	54.23	-7.64	32.29	8.15	48.31	54	100	296	Average
2390	58.7	66.57	-15.3	32.29	8.15	48.31	74	100	296	Peak
2480	91.4	99.01		32.38	8.31	48.3		100	296	Average
2480	97.68	105.29		32.38	8.31	48.3		100	296	Peak
2483.5	43.23	50.83	-10.77	32.38	8.32	48.3	54	100	296	Average
2483.5	53.85	61.45	-20.15	32.38	8.32	48.3	74	100	296	Peak

REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.

3.3 NUMBER OF HOPPING FREQUENCY USED

3.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

3.3.2 TEST SETUP



3.3.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Meter	ANRITSU	ML2495A	1506002	Mar. 01,18	Feb. 28,19
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510523	Mar. 01,18	Feb. 28,19
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510332	Mar. 01,18	Feb. 28,19
Power Sensor	ANRITSU	MA2411B	1339352	Mar. 01,18	Feb. 28,19
CBT32 BLUETOOTH TESTER 4HU	Rohde&Schwarz	CBT32	101176	Jun. 26,17	Jun. 25,18

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GREGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

3.3.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were completed.



3.3.5 DEVIATION FROM TEST STANDARD

No deviation.



3.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK



8DPSK




3.4 DWELL TIME ON EACH CHANNEL

3.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.4.2 TEST SETUP



3.4.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.4.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

3.4.5 DEVIATION FROM TEST STANDARD

No deviation.


3.4.6 TEST RESULTS

GFSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	51	322.32	0.414	133.44	400	PASS
DH3	79	31.6	5	26	164.32	1.69	277.7	400	PASS
DH5	79	31.6	5	18	113.76	2.93	333.32	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next page.

GFSK




8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	50	316	0.432	136.51	400	PASS
DH3	79	31.6	5	25	158	1.705	269.39	400	PASS
DH5	79	31.6	5	17	107.44	2.93	314.8	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next page.

8DPSK




3.5 CHANNEL BANDWIDTH

3.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

3.5.2 TEST SETUP



3.5.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.5.4 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

3.5.5 DEVIATION FROM TEST STANDARD

No deviation.

3.5.6 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.5.7 TEST RESULTS


GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.95
39	2441	1.02
78	2480	1.03


CH 0



CH 39




CH 78




$\pi/4$ DQPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.29
39	2441	1.28
78	2480	1.28


CH 0



CH 39




CH 78




8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.29
39	2441	1.30
78	2480	1.29


CH 0



CH 39



CH 78




3.6 HOPPING CHANNEL SEPARATION

3.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

3.6.2 TEST SETUP



3.6.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.6.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

3.6.5 DEVIATION FROM TEST STANDARD

No deviation.




GFSK


CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.01	0.95	0.64	PASS
39	2441	1.00	1.02	0.64	PASS
78	2480	1.00	1.03	0.64	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.


CH 0



CH 39



CH 78




8DPSK


CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.01	1.29	0.90	PASS
39	2441	1.00	1.30	0.90	PASS
78	2480	1.00	1.29	0.90	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.


CH 0



CH 39



CH 78




3.7 MAXIMUM OUTPUT POWER

3.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

3.7.2 TEST SETUP



3.7.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.7.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

3.7.5 DEVIATION FROM TEST STANDARD

No deviation.

3.7.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.7.7 TEST RESULTS

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (dBm)	POWER OUTPUT (mW)	POWER LIMIT (mW)	PASS/FAIL
0	2402	4.83	3.04	125	PASS
39	2441	4.52	2.83	125	PASS
78	2480	4.56	2.86	125	PASS

$\pi/4$ DQPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (dBm)	POWER OUTPUT (mW)	POWER LIMIT (mW)	PASS/FAIL
0	2402	4.66	2.92	125	PASS
39	2441	4.22	2.64	125	PASS
78	2480	4.13	2.59	125	PASS

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (dBm)	POWER OUTPUT (mW)	POWER LIMIT (mW)	PASS/FAIL
0	2402	4.58	2.87	125	PASS
39	2441	4.46	2.79	125	PASS
78	2480	4.36	2.73	125	PASS

3.7.8 AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	4.64	N/A
39	2441	4.35	N/A
78	2480	4.35	N/A

$\pi/4$ DQPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	2.60	N/A
39	2441	2.08	N/A
78	2480	1.99	N/A

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	2.50	N/A
39	2441	2.18	N/A
78	2480	2.11	N/A

3.8 OUT OF BAND MEASUREMENT

3.8.1 LIMITS OF OUT OF BAND MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz RBW).

3.8.2 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

3.8.4 DEVIATION FROM TEST STANDARD

No deviation.


3.8.5 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.8.6 TEST RESULTS


The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

GFSK







8DPSK



Hopping enabled_Low Channel



Hopping enabled_High Channel



4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---