ACCREDITED
Certificate # 3939.01

FCC TEST REPORT

(PART 27)

Applicant:	Corporativo Lanix S.A. de C.V.
Address:	Carretera Internacional Hermosillo-Nogales Km 8.5, Hermosillo Sonora, Mexico

Manufacturer or Supplier:	Corporativo Lanix S.A. de C.V.
Address:	Carretera Internacional Hermosillo-Nogales Km 8.5, Hermosillo Sonora, Mexico
Product:	smartphone
Brand Name:	LANIX
Model Name:	Ilium M9s
FCC ID:	ZC4M9S
Date of tests:	Apr. 19, 2019 ~ May. 28, 2019

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 27, Subpart C, L** ☒ **ANSI/TIA/EIA-603- D**
☒ **FCC Part 2** ☒ **ANSI/TIA/EIA-603-E** ☒ **ANSI C63.26-2015**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Alex Chen Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
Alex	Luke Lu
Date: May. 29, 2019	Date: May. 29, 2019

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD 4

1 SUMMARY OF TEST RESULTS 5

1.1 MEASUREMENT UNCERTAINTY 5
1.2 TEST SITE AND INSTRUMENTS 6

2 GENERAL INFORMATION 7

2.1 GENERAL DESCRIPTION OF EUT 7
2.2 CONFIGURATION OF SYSTEM UNDER TEST 10
2.3 DESCRIPTION OF SUPPORT UNITS 11
2.4 DESCRIPTION OF TEST MODES 11
2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS 16

3 TEST TYPES AND RESULTS 17

3.1 OUTPUT POWER MEASUREMENT 17
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT 17
3.1.2 TEST PROCEDURES 17
3.1.3 TEST SETUP 18
3.1.4 TEST RESULTS 19
3.2 FREQUENCY STABILITY MEASUREMENT 32
3.2.1 LIMITS OF FREQUENCY STABILIITY MEASUREMENT 32
3.2.2 TEST PROCEDURE 32
3.2.3 TEST SETUP 32
3.2.4 TEST RESULTS 33
3.3 OCCUPIED BANDWIDTH MEASUREMENT 44
3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT 44
3.3.2 TEST SETUP 44
3.3.3 TEST PROCEDURES 44
3.3.4 TEST RESULTS 45
3.4 PEAK TO AVERAGE RATIO 51
3.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT 51
3.4.2 TEST SETUP 51
3.4.3 TEST PROCEDURES 51
3.4.4 TEST RESULTS 52
3.5 BAND EDGE MEASUREMENT 60
3.5.1 LIMITS OF BAND EDGE MEASUREMENT 60
3.5.2 TEST SETUP 60
3.5.3 TEST PROCEDURES 61
3.5.4 TEST RESULTS 62
3.6 CONDUCTED SPURIOUS EMISSIONS 83
3.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT 83
3.6.2 TEST PROCEDURE 83
3.6.3 TEST SETUP 83
3.6.4 TEST RESULTS 84
3.7 RADIATED EMISSION MEASUREMENT 95
3.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT 95
3.7.2 TEST PROCEDURES 95
3.7.3 DEVIATION FROM TEST STANDARD 95
3.7.4 TEST SETUP 96
3.7.5 TEST RESULTS 98

4 INFORMATION ON THE TESTING LABORATORIES 134

5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 135

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF190418W001-5	Original release	May. 29, 2019

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 27 & Part 2			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
2.1046 27.50(d)(4)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 27.53(h)	Occupied Bandwidth	PASS	Meet the requirement of limit.
27.50(d)(5)	Peak to average ratio	PASS	Meet the requirement of limit.
27.53(h)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 27.53(h)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 27.53(h)	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -7.01dB at 34.850MHz.

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Maximum Peak Output Power	±1dB
Frequency Stability	±39.27Hz
Radiated emissions	±4.48dB
Conducted emissions	±2 dB
Occupied Channel Bandwidth	±21.7KHz
Band Edge Measurements	±4.48dB
Peak to average ratio	±0.76dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 26,19	Feb. 25,20
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510322	Feb. 26,19	Feb. 25,20
Bilog Antenna 1	ETS-LINDGREN	3143B	00161964	Feb. 26,19	Feb. 25,20
Bilog Antenna 2	ETS-LINDGREN	3143B	00161965	Feb. 26,19	Feb. 25,20
Horn Antenna 1	ETS-LINDGREN	3117	00168728	Feb. 26,19	Feb. 25,20
Horn Antenna 2	ETS-LINDGREN	3117	00168692	Nov. 30, 18	Nov. 29, 19
Loop antenna	Daze	ZN30900A	0708	Oct. 23,18	Oct. 22, 19
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Nov. 21, 18	Nov. 20, 19
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 26,19	Feb. 25,20
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 09,18	Jul. 08,19
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 09,18	Jul. 08,19
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jul. 09,18	Jul. 08,19
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Feb. 26,19	Feb. 25,20
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jul. 09,18	Jul. 08,19
Power Meter	Anritsu	ML2495A	1506002	Feb. 26,19	Feb. 25,20
Power Sensor	Anritsu	MA2411B	1339352	Feb. 26,19	Feb. 25,20
Humid & Temp Programmable Tester	Juyi	ITH-120-45-CP-AR	IAA1504-001	Jul. 09,18	Jul. 08,19
MXG Analog Microvave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 26,19	Feb. 25,20

NOTE: 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.

3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.

4. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	smartphone	
BRAND NAME	LANIX	
MODEL NAME	Ilium M9s	
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.85Vdc (Li-ion, battery)	
MODULATION TECHNOLOGY	**WCDMA IV**	BPSK, QPSK
	LTE	QPSK, 16QAM
FREQUENCY RANGE	**WCDMA IV**	1712.4MHz ~ 1752.6MHz
	LTE Band 4 Channel Bandwidth: 1.4MHz	1710.7MHz ~ 1754.3MHz
	LTE Band 4 Channel Bandwidth: 3MHz	1711.5MHz ~ 1753.5MHz
	LTE Band 4 Channel Bandwidth: 5MHz	1712.5MHz ~ 1752.5MHz
	LTE Band 4 Channel Bandwidth: 10MHz	1715.0MHz ~ 1750.0MHz
	LTE Band 4 Channel Bandwidth: 15MHz	1717.5MHz ~ 1747.5MHz
	LTE Band 4 Channel Bandwidth: 20MHz	1720.0MHz ~ 1745.0MHz
	LTE Band 12 Channel Bandwidth: 1.4MHz	699.7MHz ~ 715.3MHz
	LTE Band 12 Channel Bandwidth: 3MHz	700.5MHz ~ 714.5MHz
	LTE Band 12 Channel Bandwidth: 5MHz	701.5MHz ~ 713.5MHz
	LTE Band 12 Channel Bandwidth: 10MHz	704.0MHz ~ 711.0MHz
EMISSION DESIGNATOR	**WCDMA IV**	4M16F9W
	LTE Band 4 Channel Bandwidth: 1.4MHz	QPSK: 1M09G7D
		16QAM: 1M09W7D
	LTE Band 4 Channel Bandwidth: 3MHz	QPSK: 2M69G7D
		16QAM: 2M69W7D
	LTE Band 4 Channel Bandwidth: 5MHz	QPSK: 4M47G7D
		16QAM: 4M47W7D
	LTE Band 4 Channel Bandwidth: 10MHz	QPSK: 8M95G7D
		16QAM: 8M94W7D
	LTE Band 4 Channel Bandwidth: 15MHz	QPSK: 13M4G7D
		16QAM: 13M4W7D

EMISSION DESIGNATOR	**LTE Band 4 Channel Bandwidth: 20MHz**	QPSK: 17M9G7D
		16QAM: 17M9W7D
	LTE Band 12 Channel Bandwidth: 1.4MHz	QPSK: 1M09G7D
		16QAM: 1M09W7D
	LTE Band 12 Channel Bandwidth: 3MHz	QPSK: 2M69G7D
		16QAM: 2M69W7D
	LTE Band 12 Channel Bandwidth: 5MHz	QPSK: 4M48G7D
		16QAM: 4M48W7D
	LTE Band 12 Channel Bandwidth: 10MHz	QPSK: 8M98G7D
		16QAM: 8M96W7D
MAX. ERP/EIRP POWER	**WCDMA IV**	64mW
	LTE Band 4 Channel Bandwidth: 1.4MHz	68mW
	LTE Band 4 Channel Bandwidth: 3MHz	69mW
	LTE Band 4 Channel Bandwidth: 5MHz	69mW
	LTE Band 4 Channel Bandwidth: 10MHz	75mW
	LTE Band 4 Channel Bandwidth: 15MHz	68mW
	LTE Band 4 Channel Bandwidth: 20MHz	60mW
	LTE Band 12 Channel Bandwidth: 1.4MHz	55mW
	LTE Band 12 Channel Bandwidth: 3MHz	57mW
	LTE Band 12 Channel Bandwidth: 5MHz	58mW
	LTE Band 12 Channel Bandwidth: 10MHz	51mW
ANTENNA TYPE	Fixed Internal Antenna	
ANTENNA GAIN	0.4dBi for WCDMA IV / LTE Band 4 -1.5dBi for LTE Band 12	
HW VERSION	V0.10	
SW VERSION	Ilium M9s_SW_01_V01	
ACCESSORY DEVICE	Refer to note as below	
DATA CABLE	USB cable: non-shielded, detachable, 1.0m Earphone cable: non-shielded, detachable, 1.2m	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. The EUT was powered by the following adapter:

ADAPTER	
BRAND:	lanix
MODEL:	Ilium M9s-C
NPUT:	AC 100-240V, 250mA
OUTPUT:	DC 5V, 1550mA

3. The EUT matched the following USB cable and Earphone:

USB CABLE	
BRAND:	lanix
MODEL:	M9s
IGNAL LINE:	1.0 meter

EARPHONE	
BRAND:	lanix
MODEL:	M9s
SIGNAL LINE:	1.2 meter

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

2.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



FOR CONDUCTED & E.R.P./E.I.R.P TEST



2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m

NOTE:

1. All power cords of the above support units are non shielded (1.8m).

2.4 DESCRIPTION OF TEST MODES

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports The worst case in ERP/EIRP and radiated emission was found when positioned on X-plane for WCDMA/LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	**EUT + Adapter + USB Cable + Earphone with WCDMA or LTE link**
B	EUT + Battery with **WCDMA or LTE link**

WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
B	EIRP	1312 to 1513	1312, 1413, 1513	WCDMA
B	FREQUENCY STABILITY	1312 to 1513	1312, 1513	WCDMA
B	OCCUPIED BANDWIDTH	1312 to 1513	1312, 1413, 1513	WCDMA
B	BAND EDGE	1312 to 1513	1312, 1513	WCDMA
B	PEAK TO AVERAGE RATIO	1312 to 1513	1312, 1413, 1513	WCDMA
B	CONDCUDETED EMISSION	1312 to 1513	1312, 1413, 1513	WCDMA
A	RADIATED EMISSION	1312 to 1513	1312, 1413, 1513	WCDMA

LTE BAND 4

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	EIRP	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	19957 to 20393	19957, 20393	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	19965, 20385	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	19975, 20375	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20000, 20350	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20025, 20325	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20050, 20300	20MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	100 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	BAND EDGE	19957 to 20393	19957	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			20393	1.4MHz	QPSK, 16QAM	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		19965 to 20385	19965	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			20385	3MHz	QPSK, 16QAM	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		19975 to 20375	19975	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			20375	5MHz	QPSK, 16QAM	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		20000 to 20350	20000	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			20350	10MHz	QPSK, 16QAM	1 RB / 49 RB Offset
						50 RB / 0 RB Offset

B	BAND EDGE	20025 to 20325	20025	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
						75 RB / 0 RB Offset
			20325	15MHz	QPSK, 16QAM	1 RB / 74 RB Offset
						75 RB / 0 RB Offset
		20050 to 20300	20050	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
						100 RB / 0 RB Offset
			20300	20MHz	QPSK, 16QAM	1 RB / 99 RB Offset
						100 RB / 0 RB Offset
B	CONDCUDETED EMISSION	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20175	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

LTE BAND 12

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	ERP	23017 to 23173	23017, 23095 , 23173	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK,16QAM	1 RB / 0 RB Offset
		23035 to 23155	23035, 23095 ,23155	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
		23060 to 23130	23060, 23095 ,23130	10MHz	QPSK,16QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	23017 to 23173	23017, 23173	1.4MHz	QPSK	1 RB / 0 RB Offset
		23025 to 23165	23025, 23165	3MHz	QPSK	1 RB / 0 RB Offset
		23035 to 23155	23035, 23155	5MHz	QPSK	1 RB / 0 RB Offset
		23060 to 23130	23060, 23130	10MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	23017 to 23173	23017, 23095 , 23173	1.4MHz	QPSK,16QAM	6 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK,16QAM	15 RB / 0 RB Offset
		23035 to 23155	23035, 23095 ,23155	5MHz	QPSK,16QAM	25 RB / 0 RB Offset
		23060 to 23130	23060, 23095 ,23130	10MHz	QPSK,16QAM	50 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	23017 to 23173	23017, 23095 , 23173	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23035 to 23155	23035, 23095 ,23155	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23060 to 23130	23060, 23095 ,23130	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	BAND EDGE	23017 to 23173	23017	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			23173	1.4MHz	QPSK, 16QAM	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		23025 to 23165	23025	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			23165	3MHz	QPSK, 16QAM	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		23035 to 23155	23035	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			23155	5MHz	QPSK, 16QAM	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		23060 to 23130	23060	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			23130	10MHz	QPSK, 16QAM	1 RB / 49 RB Offset
						50 RB / 0 RB Offset
B	CONDCUDETED EMISSION	23017 to 23173	23017, 23095 , 23173	1.4MHz	QPSK	1 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK	1 RB / 0 RB Offset
		23035 to 23155	23035, 23095 ,23155	5MHz	QPSK	1 RB / 0 RB Offset
		23060 to 23130	23060, 23095 ,23130	10MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	23017 to 23173	23095	1.4MHz	QPSK	1 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK	1 RB / 0 RB Offset
		23035 to 23155	23095	5MHz	QPSK	1 RB / 0 RB Offset
		23060 to 23130	23095	10MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP(ERP)	24deg. C, 60%RH	3.85Vdc from Battery	Star Le
FREQUENCY STABILITY	24deg. C, 61%RH	DC 3.5V/3.8V/4.2V	Rain Wang
OCCUPIED BANDWIDTH	24deg. C, 61%RH	3.85Vdc from Battery	Rain Wang
PEAK TO AVERAGE RATIO	24deg. C, 61%RH	3.85Vdc from Battery	Rain Wang
BAND EDGE	24deg. C, 61%RH	3.85Vdc from Battery	Rain Wang
CONDCUDETED EMISSION	24deg. C, 61%RH	3.85Vdc from Battery	Rain Wang
RADIATED EMISSION	24deg. C, 60%RH	5Vdc from adapter	Star Le

2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

Portable stations (hand-held devices) operating in the 699-716 MHz bands are limited to 3 watts ERP.

3.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:

a. The EUT was set up for the maximum power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels (low, middle and high operational frequency range). RBW and VBW is 10MHz for LTE.

b. E.I.R.P power measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.

c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G

d. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn

e. E.R.P = E.I.R.P- 2.15 dB

CONDUCTED POWER MEASUREMENT:

a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.

b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

3.1.3 TEST SETUP

EIRP / ERP Measurement:
<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



3.1.4 TEST RESULTS

AVERAGE CONDUCTED OUTPUT POWER (dBm)

Band	WCDMA IV		
Channel	1312	1413	1513
Frequency (MHz)	1712.4	1732.6	1752.6
RMC 12.2K	22.76	**22.77**	22.72
HSPA			
HSDPA Subtest-1	21.88	21.89	21.84
HSDPA Subtest-2	21.81	21.82	21.77
HSDPA Subtest-3	21.27	21.28	21.23
HSDPA Subtest-4	21.23	21.24	21.19
DC-HSDPA Subtest-1	21.84	21.85	21.80
DC-HSDPA Subtest-2	21.78	21.79	21.74
DC-HSDPA Subtest-3	21.23	21.24	21.19
DC-HSDPA Subtest-4	21.20	21.21	21.16
HSUPA Subtest-1	21.83	21.84	21.79
HSUPA Subtest-2	19.91	19.92	19.87
HSUPA Subtest-3	20.78	20.79	20.74
HSUPA Subtest-4	19.86	19.87	19.82
HSUPA Subtest-5	21.77	21.78	21.73
HSPA+ Subtest-1	21.45	21.46	21.41

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 19957	Mid CH 20175	High CH 20393	MPR
				Frequency 1710.7 MHz	Frequency 1732.5 MHz	Frequency 1754.3 MHz	
1.4MHz	QPSK	1	0	22.01	22.02	22.09	0
		1	2	21.92	21.93	22.00	0
		1	5	21.82	21.83	21.90	0
		3	0	21.99	22.00	22.07	0
		3	1	21.90	21.91	21.98	0
		3	3	21.80	21.81	21.88	0
		6	0	20.99	21.00	21.07	1
	16QAM	1	0	21.40	21.41	21.48	1
		1	2	21.37	21.38	21.45	1
		1	5	21.23	21.24	21.31	1
		3	0	21.39	21.40	21.47	1
		3	1	21.36	21.37	21.44	1
		3	3	21.22	21.23	21.30	1
		6	0	20.21	20.22	20.29	2
BW	Modulation	RB Size	RB Offset	Low CH 19965	Mid CH 20175	High CH 20385	MPR
				Frequency 1711.5 MHz	Frequency 1732.5 MHz	Frequency 1753.5 MHz	
3 MHz	QPSK	1	0	22.02	22.03	22.10	0
		1	7	21.93	21.94	22.01	0
		1	14	21.83	21.84	21.91	0
		8	0	21.17	21.18	21.25	1
		8	3	21.04	21.05	21.12	1
		8	7	21.08	21.09	21.16	1
		15	0	21.00	21.01	21.08	1
	16QAM	1	0	21.41	21.42	21.49	1
		1	7	21.38	21.39	21.46	1
		1	14	21.24	21.25	21.32	1
		8	0	20.19	20.20	20.27	2
		8	3	20.14	20.15	20.22	2
		8	7	20.17	20.18	20.25	2
		15	0	20.22	20.23	20.30	2

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 19975	Mid CH 20175	High CH 20375	MPR
				Frequency 1712.5 MHz	Frequency 1732.5 MHz	Frequency 1752.5 MHz	
5 MHz	QPSK	1	0	22.05	22.06	22.13	0
		1	12	21.96	21.97	22.04	0
		1	24	21.86	21.87	21.94	0
		12	0	21.20	21.21	21.28	1
		12	6	21.07	21.08	21.15	1
		12	13	21.11	21.12	21.19	1
		25	0	21.03	21.04	21.11	1
	16QAM	1	0	21.44	21.45	21.52	1
		1	12	21.41	21.42	21.49	1
		1	24	21.27	21.28	21.35	1
		12	0	20.22	20.23	20.30	2
		12	6	20.17	20.18	20.25	2
		12	13	20.20	20.21	20.28	2
		25	0	20.25	20.26	20.33	2
BW	Modulation	RB Size	RB Offset	Low CH 20000	Mid CH 20175	High CH 20350	MPR
				Frequency 1715 MHz	Frequency 1732.5 MHz	Frequency 1750 MHz	
10 MHz	QPSK	1	0	22.09	22.10	22.17	0
		1	24	22.00	22.01	22.08	0
		1	49	21.90	21.91	21.98	0
		25	0	21.24	21.25	21.32	1
		25	12	21.11	21.12	21.19	1
		25	25	21.15	21.16	21.23	1
		50	0	21.07	21.08	21.15	1
	16QAM	1	0	21.48	21.49	21.56	1
		1	24	21.45	21.46	21.53	1
		1	49	21.31	21.32	21.39	1
		25	0	20.26	20.27	20.34	2
		25	12	20.21	20.22	20.29	2
		25	25	20.24	20.25	20.32	2
		50	0	20.29	20.30	20.37	2

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 20025	Mid CH 20175	High CH 20325	MPR
				Frequency 1717.5 MHz	Frequency 1732.5 MHz	Frequency 1747.5 MHz	
15 MHz	QPSK	1	0	22.15	22.16	22.23	0
		1	37	22.06	22.07	22.14	0
		1	74	21.96	21.97	22.04	0
		36	0	21.30	21.31	21.38	1
		36	19	21.17	21.18	21.25	1
		36	39	21.21	21.22	21.29	1
		75	0	21.13	21.14	21.21	1
	16QAM	1	0	21.54	21.55	21.62	1
		1	37	21.51	21.52	21.59	1
		1	74	21.37	21.38	21.45	1
		36	0	20.32	20.33	20.40	2
		36	19	20.27	20.28	20.35	2
		36	39	20.30	20.31	20.38	2
		75	0	20.35	20.36	20.43	2
BW	Modulation	RB Size	RB Offset	Low CH 20050	Mid CH 20175	High CH 20300	MPR
				Frequency 1720 MHz	Frequency 1732.5 MHz	Frequency 1745 MHz	
20MHz	QPSK	1	0	22.18	22.19	**22.26**	0
		1	50	22.09	22.10	22.17	0
		1	99	21.99	22.00	22.07	0
		50	0	21.33	21.34	21.41	1
		50	25	21.20	21.21	21.28	1
		50	50	21.24	21.25	21.32	1
		100	0	21.16	21.17	21.24	1
	16QAM	1	0	21.57	21.58	21.65	1
		1	50	21.54	21.55	21.62	1
		1	99	21.40	21.41	21.48	1
		50	0	20.35	20.36	20.43	2
		50	25	20.30	20.31	20.38	2
		50	50	20.33	20.34	20.41	2
		100	0	20.38	20.39	20.46	2

LTE Band 12							
BW	Modulation	RB Size	RB Offset	Low CH 23017 Frequency 699.7 MHz	Mid CH 23095 Frequency 707.5 MHz	High CH 23173 Frequency 715.3 MHz	MPR
1.4 MHz	QPSK	1	0	21.93	21.96	21.91	0
		1	2	21.91	21.94	21.89	0
		1	5	21.87	21.90	21.85	0
		3	0	21.91	21.94	21.89	0
		3	1	21.89	21.92	21.87	0
		3	3	21.85	21.88	21.83	0
		6	0	21.10	21.13	21.08	1
	16QAM	1	0	21.12	21.15	21.10	1
		1	2	21.09	21.12	21.07	1
		1	5	21.07	21.10	21.05	1
		3	0	21.11	21.14	21.09	1
		3	1	21.08	21.11	21.06	1
		3	3	21.06	21.09	21.04	1
		6	0	20.18	20.21	20.16	2

LTE Band 12							
BW	Modulation	RB Size	RB Offset	Low CH 23025 Frequency 700.5 MHz	Mid CH 23095 Frequency 707.5 MHz	High CH 23165 Frequency 714.5 MHz	MPR
3 MHz	QPSK	1	0	21.97	22.00	21.95	0
		1	7	21.95	21.98	21.93	0
		1	14	21.91	21.94	21.89	0
		8	0	21.24	21.27	21.22	1
		8	3	21.20	21.23	21.18	1
		8	7	21.17	21.20	21.15	1
		15	0	21.14	21.17	21.12	1
	16QAM	1	0	21.16	21.19	21.14	1
		1	7	21.13	21.16	21.11	1
		1	14	21.11	21.14	21.09	1
		8	0	20.43	20.46	20.41	2
		8	3	20.40	20.43	20.38	2
		8	7	20.31	20.34	20.29	2
		15	0	20.22	20.25	20.20	2

LTE Band 12							
BW	Modulation	RB Size	RB Offset	Low CH 23035 Frequency 701.5 MHz	Mid CH 23095 Frequency 707.5 MHz	High CH 23155 Frequency 713.5 MHz	MPR
5 MHz	QPSK	1	0	22.03	22.06	22.01	0
		1	12	22.01	22.04	21.99	0
		1	24	21.97	22.00	21.95	0
		12	0	21.30	21.33	21.28	1
		12	6	21.26	21.29	21.24	1
		12	13	21.23	21.26	21.21	1
		25	0	21.20	21.23	21.18	1
	16QAM	1	0	21.22	21.25	21.20	1
		1	12	21.19	21.22	21.17	1
		1	24	21.17	21.20	21.15	1
		12	0	20.49	20.52	20.47	2
		12	6	20.46	20.49	20.44	2
		12	13	20.37	20.40	20.35	2
		25	0	20.28	20.31	20.26	2

LTE Band 12							
BW	Modulation	RB Size	RB Offset	Low CH 23060 Frequency 704 MHz	Mid CH 23095 Frequency 707.5 MHz	High CH 23130 Frequency 711 MHz	MPR
10 MHz	QPSK	1	0	22.06	**22.09**	22.04	0
		1	24	22.04	22.07	22.02	0
		1	49	22.00	22.03	21.98	0
		25	0	21.33	21.36	21.31	1
		25	12	21.29	21.32	21.27	1
		25	25	21.26	21.29	21.24	1
		50	0	21.23	21.26	21.21	1
	16QAM	1	0	21.25	21.28	21.23	1
		1	24	21.22	21.25	21.20	1
		1	49	21.20	21.23	21.18	1
		25	0	20.52	20.55	20.50	2
		25	12	20.49	20.52	20.47	2
		25	25	20.40	20.43	20.38	2
		50	0	20.31	20.34	20.29	2

EIRP / ERP

WCDMA IV

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
1312	1712.40	-29.26	41.39	12.13	16.33	H
1413	1732.60	-28.58	41.36	12.78	18.97	H
1513	1752.60	-28.87	42.63	13.76	23.76	H
1312	1712.40	-26.35	44.17	17.82	60.48	V
1413	1732.60	-26.12	44.20	18.08	**64.27**	V
1513	1752.60	-27.24	44.35	17.11	61.45	V

REMARKS: 1. EIRP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB).
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19957	1710.7	-28.83	41.29	12.46	17.64	H	1
20175	1732.5	-30.03	41.36	11.33	13.58	H	1
20393	1754.3	-28.90	42.74	13.84	24.20	H	1
19957	1710.7	-25.90	44.25	18.35	**68.31**	V	1
20175	1732.5	-25.96	44.20	18.24	66.68	V	1
20393	1754.3	-26.07	44.09	18.02	63.31	V	1

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19957	1710.7	-29.70	41.29	11.59	14.43	H	1
20175	1732.5	-30.96	41.36	10.40	10.96	H	1
20393	1754.3	-29.86	42.74	12.88	19.40	H	1
19957	1710.7	-26.77	44.25	17.48	55.91	V	1
20175	1732.5	-26.89	44.20	17.31	53.83	V	1
20393	1754.3	-27.03	44.09	17.06	50.76	V	1

LTE BAND 4

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19965	1711.5	-28.81	41.27	12.46	17.61	H	1
20175	1732.5	-30.09	41.36	11.27	13.40	H	1
20385	1753.5	-28.85	42.76	13.91	24.59	H	1
19965	1711.5	-25.88	44.26	18.38	**68.90**	V	1
20175	1732.5	-26.02	44.20	18.18	65.77	V	1
20385	1753.5	-26.02	44.23	18.21	66.25	V	1

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19965	1711.5	-29.88	41.27	11.39	13.76	H	1
20175	1732.5	-30.98	41.36	10.38	10.91	H	1
20385	1753.5	-29.84	42.76	12.92	19.57	H	1
19965	1711.5	-26.95	44.26	17.31	53.85	V	1
20175	1732.5	-26.91	44.20	17.29	53.58	V	1
20385	1753.5	-27.01	44.23	17.22	52.75	V	1

LTE BAND 4

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19975	1712.5	-28.87	41.39	12.52	17.86	H	1
20175	1732.5	-30.04	41.36	11.32	13.55	H	1
20375	1752.5	-28.80	42.63	13.83	24.15	H	1
19975	1712.5	-25.94	44.17	18.23	66.47	V	1
20175	1732.5	-25.97	44.20	18.23	66.53	V	1
20375	1752.5	-25.97	44.35	18.38	**68.79**	V	1

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19975	1712.5	-29.70	41.39	11.69	14.75	H	1
20175	1732.5	-31.06	41.36	10.30	10.72	H	1
20375	1752.5	-29.90	42.63	12.73	18.75	H	1
19975	1712.5	-26.77	44.17	17.40	54.90	V	1
20175	1732.5	-26.99	44.20	17.21	52.60	V	1
20375	1752.5	-27.07	44.35	17.28	53.39	V	1

LTE BAND 4

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20000	1715.0	-28.68	41.49	12.81	19.08	H	1
20175	1732.5	-28.75	41.36	12.61	18.24	H	1
20350	1750.0	-28.62	42.28	13.66	23.24	H	1
20000	1715.0	-25.75	44.06	18.31	67.81	V	1
20175	1732.5	-25.82	44.20	18.38	68.87	V	1
20350	1750.0	-25.69	44.43	18.74	**74.82**	V	1

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20000	1715.0	-29.83	41.49	11.66	14.64	H	1
20175	1732.5	-31.08	41.36	10.28	10.67	H	1
20350	1750.0	-29.83	42.28	12.45	17.59	H	1
20000	1715.0	-26.90	44.06	17.16	52.04	V	1
20175	1732.5	-27.01	44.20	17.19	52.36	V	1
20350	1750.0	-27.00	44.43	17.43	55.34	V	1

LTE BAND 4

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20025	1717.5	-28.69	41.34	12.65	18.40	H	1
20175	1732.5	-30.05	41.36	11.31	13.52	H	1
20325	1747.5	-28.74	42.09	13.35	21.61	H	1
20025	1717.5	-25.76	44.04	18.28	67.36	V	1
20175	1732.5	-25.98	44.20	18.22	66.37	V	1
20325	1747.5	-25.91	44.22	18.31	**67.69**	V	1

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20025	1717.5	-29.55	41.34	11.79	15.09	H	1
20175	1732.5	-30.92	41.36	10.44	11.07	H	1
20325	1747.5	-29.59	42.09	12.50	17.77	H	1
20025	1717.5	-26.62	44.04	17.42	55.26	V	1
20175	1732.5	-26.85	44.20	17.35	54.33	V	1
20325	1747.5	-26.76	44.22	17.46	55.65	V	1

LTE BAND 4

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20050	1720.0	-29.27	41.28	12.01	15.89	H	1
20175	1732.5	-30.50	41.36	10.86	12.19	H	1
20300	1745.0	-29.32	41.96	12.64	18.35	H	1
20050	1720.0	-26.34	44.14	17.80	**60.19**	V	1
20175	1732.5	-26.43	44.20	17.77	59.79	V	1
20300	1745.0	-26.49	43.88	17.39	54.85	V	1

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20050	1720.0	-30.20	41.28	11.08	12.83	H	1
20175	1732.5	-31.57	41.36	9.79	9.53	H	1
20300	1745.0	-30.15	41.96	11.81	15.16	H	1
20050	1720.0	-27.27	44.14	16.87	48.58	V	1
20175	1732.5	-27.50	44.20	16.70	46.73	V	1
20300	1745.0	-27.32	43.88	16.56	45.31	V	1

REMARKS: 1. EIRP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB).
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23017	699.7	-14.03	32.77	16.59	45.60	H	3
23095	707.5	-14.18	33.23	16.90	48.98	H	3
23173	715.3	-13.60	33.14	17.39	**54.80**	H	3
23017	699.7	-18.38	32.42	11.89	15.44	V	3
23095	707.5	-18.80	32.60	11.65	14.62	V	3
23173	715.3	-19.11	32.19	10.93	12.38	V	3

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23017	699.7	-14.86	32.77	15.76	37.67	H	3
23095	707.5	-15.20	33.23	15.88	38.73	H	3
23173	715.3	-14.70	33.14	16.29	42.54	H	3
23017	699.7	-19.21	32.42	11.06	12.75	V	3
23095	707.5	-19.82	32.60	10.63	11.56	V	3
23173	715.3	-20.21	32.19	9.83	9.61	V	3

LTE BAND 12

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23025	700.5	-13.84	32.63	16.64	46.14	H	3
23095	707.5	-14.12	33.23	16.96	49.66	H	3
23165	714.5	-13.47	33.21	17.59	**57.35**	H	3
23025	700.5	-18.19	32.33	11.99	15.80	V	3
23095	707.5	-18.74	32.60	11.71	14.83	V	3
23165	714.5	-18.98	32.30	11.17	13.09	V	3

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23025	700.5	-14.99	32.63	15.49	35.41	H	3
23095	707.5	-15.22	33.23	15.86	38.55	H	3
23165	714.5	-14.63	33.21	16.43	43.90	H	3
23025	700.5	-19.34	32.33	10.84	12.13	V	3
23095	707.5	-19.84	32.60	10.61	11.51	V	3
23165	714.5	-20.14	32.30	10.01	10.03	V	3

LTE BAND 12

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23035	701.5	-13.85	32.53	16.53	44.93	H	3
23095	707.5	-14.19	33.23	16.89	48.84	H	3
23155	713.5	-13.54	33.29	17.60	**57.50**	H	3
23035	701.5	-18.20	32.25	11.90	15.50	V	3
23095	707.5	-18.81	32.60	11.64	14.59	V	3
23155	713.5	-19.05	32.39	11.19	13.14	V	3

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23035	701.5	-14.71	32.53	15.67	36.86	H	3
23095	707.5	-15.06	33.23	16.02	39.98	H	3
23155	713.5	-14.39	33.29	16.75	47.28	H	3
23035	701.5	-19.06	32.25	11.04	12.72	V	3
23095	707.5	-19.68	32.60	10.77	11.94	V	3
23155	713.5	-19.90	32.39	10.34	10.80	V	3

LTE BAND 12

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23060	704.0	-14.43	32.68	16.10	40.77	H	3
23095	707.5	-14.64	33.23	16.44	44.06	H	3
23130	711.0	-14.12	33.39	17.12	**51.49**	H	3
23060	704.0	-18.78	32.37	11.44	13.93	V	3
23095	707.5	-19.26	32.60	11.19	13.15	V	3
23130	711.0	-19.63	32.56	10.78	11.95	V	3

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23060	704.0	-15.36	32.68	15.17	32.91	H	3
23095	707.5	-15.71	33.23	15.37	34.43	H	3
23130	711.0	-14.95	33.39	16.29	42.53	H	3
23060	704.0	-19.71	32.37	10.51	11.24	V	3
23095	707.5	-20.33	32.60	10.12	10.28	V	3
23130	711.0	-20.46	32.56	9.95	9.87	V	3

REMARKS: 1. ERP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB) -2.15(dB).

2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILIITY MEASUREMENT

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

3.2.2 TEST PROCEDURE

a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.

b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.

c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ±0.5℃ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP



3.2.4 TEST RESULTS

WCDMA BAND IV

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
3.8	0.0018	0.0019	2.5
3.5	-0.0023	-0.0023	2.5
4.2	0.0019	0.0021	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
-30	-0.0126	-0.0121	2.5
-20	-0.0113	-0.0108	2.5
-10	-0.0106	-0.0101	2.5
0	-0.0088	-0.0085	2.5
10	-0.0064	-0.0061	2.5
20	-0.0052	-0.0050	2.5
30	-0.0039	-0.0037	2.5
40	-0.0035	-0.0033	2.5
50	-0.0029	-0.0028	2.5

LTE BAND 4

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.8	0.0011	0.0011	2.5
3.5	-0.0016	-0.0016	2.5
4.2	0.0009	0.0010	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0062	-0.0054	2.5
-20	-0.0055	-0.0049	2.5
-10	-0.0045	-0.0043	2.5
0	-0.0040	-0.0035	2.5
10	-0.0029	-0.0031	2.5
20	-0.0025	-0.0025	2.5
30	-0.0020	-0.0014	2.5
40	-0.0010	-0.0009	2.5
50	-0.0004	-0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.8	0.0008	0.0010	2.5
3.5	-0.0008	-0.0011	2.5
4.2	0.0009	0.0010	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0054	-0.0055	2.5
-20	-0.0050	-0.0049	2.5
-10	-0.0044	-0.0041	2.5
0	-0.0037	-0.0036	2.5
10	-0.0028	-0.0027	2.5
20	-0.0019	-0.0022	2.5
30	-0.0016	-0.0018	2.5
40	-0.0008	-0.0010	2.5
50	-0.0002	-0.0004	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.8	0.0011	0.0010	2.5
3.5	-0.0010	-0.0013	2.5
4.2	0.0010	0.0010	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0060	-0.0050	2.5
-20	-0.0056	-0.0043	2.5
-10	-0.0049	-0.0041	2.5
0	-0.0039	-0.0033	2.5
10	-0.0035	-0.0026	2.5
20	-0.0027	-0.0023	2.5
30	-0.0017	-0.0014	2.5
40	-0.0010	-0.0008	2.5
50	-0.0003	-0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.8	0.0009	0.0013	2.5
3.5	-0.0013	-0.0014	2.5
4.2	0.0010	0.0009	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0054	-0.0055	2.5
-20	-0.0049	-0.0045	2.5
-10	-0.0042	-0.0039	2.5
0	-0.0033	-0.0031	2.5
10	-0.0026	-0.0024	2.5
20	-0.0019	-0.0019	2.5
30	-0.0013	-0.0014	2.5
40	-0.0009	-0.0008	2.5
50	-0.0002	-0.0003	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	15MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.8	0.0009	0.0010	2.5
3.5	-0.0014	-0.0013	2.5
4.2	0.0009	0.0010	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	15MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0055	-0.0051	2.5
-20	-0.0049	-0.0045	2.5
-10	-0.0044	-0.0039	2.5
0	-0.0033	-0.0031	2.5
10	-0.0027	-0.0025	2.5
20	-0.0021	-0.0020	2.5
30	-0.0014	-0.0013	2.5
40	-0.0008	-0.0009	2.5
50	-0.0002	-0.0003	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	20MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.8	0.0010	0.0014	2.5
3.5	-0.0016	-0.0015	2.5
4.2	0.0008	0.0013	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	20MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0047	-0.0044	2.5
-20	-0.0042	-0.0042	2.5
-10	-0.0040	-0.0034	2.5
0	-0.0033	-0.0027	2.5
10	-0.0025	-0.0022	2.5
20	-0.0019	-0.0018	2.5
30	-0.0011	-0.0008	2.5
40	-0.0005	-0.0003	2.5
50	-0.0002	0.0004	2.5

LTE BAND 12

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.8	0.0018	0.0028	2.5
3.5	-0.0021	-0.0023	2.5
4.2	0.0019	0.0021	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0146	-0.0141	2.5
-20	-0.0133	-0.0124	2.5
-10	-0.0117	-0.0106	2.5
0	-0.0097	-0.0091	2.5
10	-0.0077	-0.0079	2.5
20	-0.0060	-0.0071	2.5
30	-0.0047	-0.0048	2.5
40	-0.0027	-0.0028	2.5
50	-0.0010	-0.0015	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.8	0.0020	0.0020	2.5
3.5	-0.0027	-0.0021	2.5
4.2	0.0020	0.0018	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0149	-0.0145	2.5
-20	-0.0139	-0.0130	2.5
-10	-0.0103	-0.0103	2.5
0	-0.0083	-0.0080	2.5
10	-0.0063	-0.0061	2.5
20	-0.0052	-0.0048	2.5
30	-0.0019	-0.0021	2.5
40	-0.0008	-0.0010	2.5
50	0.0007	0.0006	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.8	0.0023	0.0024	2.5
3.5	-0.0022	-0.0025	2.5
4.2	0.0023	0.0020	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0137	-0.0143	2.5
-20	-0.0116	-0.0124	2.5
-10	-0.0106	-0.0110	2.5
0	-0.0091	-0.0093	2.5
10	-0.0075	-0.0073	2.5
20	-0.0062	-0.0060	2.5
30	-0.0045	-0.0048	2.5
40	-0.0025	-0.0026	2.5
50	-0.0006	-0.0007	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.8	0.0021	0.0022	2.5
3.5	-0.0024	-0.0023	2.5
4.2	0.0019	0.0018	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0150	-0.0138	2.5
-20	-0.0139	-0.0119	2.5
-10	-0.0120	-0.0089	2.5
0	-0.0108	-0.0075	2.5
10	-0.0077	-0.0065	2.5
20	-0.0058	-0.0049	2.5
30	-0.0048	-0.0033	2.5
40	-0.0033	-0.0023	2.5
50	-0.0013	-0.0014	2.5

3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

3.3.2 TEST SETUP



3.3.3 TEST PROCEDURES

a. The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

b. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

3.3.4 TEST RESULTS

WCDMA BAND IV

Channel	FREQ. (MHz)	99% Occupied Bandwidth (MHz)	Channel	FREQ. (MHz)	26dB Bandwidth (MHz)
		WCDMA			WCDMA
1312	1712.40	4.15	1312	1712.40	4.70
1413	1732.60	4.14	1413	1732.60	4.87
1513	1752.60	4.16	1513	1752.60	4.70

SPECTRUM PLOT OF WORST VALUE	
99% Occupied Bandwidth	26dB Bandwidth
	

LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	1.09	1.09	19965	1711.5	2.69	2.69
20175	1732.5	1.09	1.09	20175	1732.5	2.68	2.69
20393	1754.3	1.09	1.08	20385	1753.5	2.68	2.69

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



3MHz / QPSK



3MHz / 16QAM



LTE BAND 4

CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	4.47	4.47	20000	1715	8.94	8.92
20175	1732.5	4.47	4.47	20175	1732.5	8.95	8.94
20375	1752.5	4.47	4.47	20350	1750	8.94	8.93

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM



LTE BAND 4

CHANNEL BANDWIDTH: 15MHz				CHANNEL BANDWIDTH: 20MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	13.44	13.40	20050	1720	17.91	17.87
20175	1732.5	13.39	13.40	20175	1732.5	17.84	17.91
20325	1747.5	13.44	13.41	20300	1745	17.91	17.91

SPECTRUM PLOT OF WORST VALUE

15MHz / QPSK



15MHz / 16QAM



20MHz / QPSK



20MHz / 16QAM



LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
23017	699.7	1.09	1.09	23025	700.5	2.68	2.69
23095	707.5	1.09	1.09	23095	707.5	2.69	2.69
23173	715.3	1.09	1.09	23165	714.5	2.69	2.69

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



3MHz / QPSK



3MHz / 16QAM



LTE BAND 12

CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23035	701.5	4.47	4.47	23060	704	8.96	8.93
23095	707.5	4.48	4.48	23095	707.5	8.98	8.96
23155	713.5	4.47	4.47	23130	711	8.94	8.91

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM



10MHz / QPSK

10MHz / 16QAM



3.4 PEAK TO AVERAGE RATIO

3.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

3.4.2 TEST SETUP



3.4.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

3.4.4 TEST RESULTS

WCDMA Band IV

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
1312	1712.4	2.71

SPECTRUM PLOT OF WORST VALUE



CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
1413	1732.6	2.87

SPECTRUM PLOT OF WORST VALUE



CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
1513	1752.6	2.60

SPECTRUM PLOT OF WORST VALUE



LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	4.99	6.00	19965	1711.5	5.11	5.88
20175	1732.5	5.29	6.17	20175	1732.5	5.34	6.16
20393	1754.3	5.24	5.81	20385	1753.5	4.79	5.61

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



3MHz / QPSK

3MHz / 16QAM

CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	5.31	5.99	20000	1715	5.11	5.84
20175	1732.5	5.46	6.18	20175	1732.5	5.30	6.05
20375	1752.5	5.07	5.83	20350	1750	4.66	5.47

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK

5MHz / 16QAM

10MHz / QPSK



10MHz / 16QAM

CHANNEL BANDWIDTH: 15MHz				CHANNEL BANDWIDTH: 20MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	5.25	5.99	20050	1720	5.42	6.13
20175	1732.5	5.36	6.13	20175	1732.5	5.42	6.14
20325	1747.5	5.02	5.69	20300	1745	5.21	5.90

SPECTRUM PLOT OF WORST VALUE

15MHz / QPSK



15MHz / 16QAM

20MHz / QPSK

20MHz / 16QAM



LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
23017	699.7	5.61	6.42	23025	700.5	5.56	6.22
23095	707.5	6.16	6.40	23095	707.5	5.46	5.95
23173	715.3	4.58	5.63	23165	714.5	5.03	5.84

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM

3MHz / QPSK



3MHz / 16QAM



CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
23035	701.5	5.43	6.14	23060	704	5.59	6.28
23095	707.5	5.54	6.21	23095	707.5	5.56	6.32
23155	713.5	5.35	6.10	23130	711	5.36	6.20

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM



3.5 BAND EDGE MEASUREMENT

3.5.1 LIMITS OF BAND EDGE MEASUREMENT

The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least 43 + 10 log (P) dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.
However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

3.5.2 TEST SETUP



3.5.3 TEST PROCEDURES

a. The EUT was set up for the maximum peak power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels (low and high operational frequency range.).

b. The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

c. The center frequency of spectrum is the band edge frequency and span is 10MHz. RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz (WCDMA).

d. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 20kHz and VBW of the spectrum is 100 kHz. (LTE bandwidth 1.4MHz)

e. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 30kHz and VBW of the spectrum is 100kHz. (LTE bandwidth 3MHz)

f. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 50kHz and VBW of the spectrum is 200kHz. (LTE bandwidth 5MHz)

g. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz. (LTE bandwidth 10MHz)

h. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 200kHz and VBW of the spectrum is 1MHz. (LTE bandwidth 15MHz)

i. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 200kHz and VBW of the spectrum is 1MHz. (LTE bandwidth 20MHz)

j. Record the max trace plot into the test report.

3.5.4 TEST RESULTS

WCDMA BAND 4

WCDMA			
CHANNEL	1312	CHANNEL	1513
			

LTE BAND 4

Channel Bandwidth: 1.4MHz QPSK					
CHANNEL	19957	1 RB	CHANNEL	20393	1 RB
CHANNEL	19957	Full RB	CHANNEL	20393	Full RB

Channel Bandwidth: 1.4MHz 16QAM

CHANNEL	19957	1 RB	CHANNEL	20393	1 RB

CHANNEL	19957	Full RB	CHANNEL	20393	Full RB

LTE BAND 4

Channel Bandwidth: 3MHz QPSK					
CHANNEL	19965	1 RB	CHANNEL	20385	1 RB
CHANNEL	19965	Full RB	CHANNEL	20385	Full RB
					

Channel Bandwidth: 3MHz 16QAM

CHANNEL	19965	1 RB	CHANNEL	20385	1 RB

CHANNEL	19965	Full RB	CHANNEL	20385	Full RB

LTE BAND 4

Channel Bandwidth: 5MHz QPSK					
CHANNEL	19975	1 RB	CHANNEL	20375	1 RB
CHANNEL	19975	Full RB	CHANNEL	20375	Full RB

Channel Bandwidth: 5MHz 16QAM

CHANNEL	19975	1 RB	CHANNEL	20375	1 RB
CHANNEL	19975	Full RB	CHANNEL	20375	Full RB

LTE BAND 4

Channel Bandwidth: 10MHz QPSK					
CHANNEL	20000	1 RB	CHANNEL	20350	1 RB
					
CHANNEL	20000	Full RB	CHANNEL	20350	Full RB

Channel Bandwidth: 10MHz 16QAM

CHANNEL	20000	1 RB	CHANNEL	20350	1 RB

CHANNEL	20000	Full RB	CHANNEL	20350	Full RB

LTE BAND 4

Channel Bandwidth: 15MHz QPSK					
CHANNEL	20025	1 RB	CHANNEL	20325	1 RB
					
CHANNEL	20025	Full RB	CHANNEL	20325	Full RB
					

Channel Bandwidth: 15MHz 16QAM

CHANNEL	20025	1 RB	CHANNEL	20325	1 RB
					
CHANNEL	20025	Full RB	CHANNEL	20325	Full RB
					

LTE BAND 4

Channel Bandwidth: 20MHz QPSK					
CHANNEL	20050	1 RB	CHANNEL	20300	1 RB
					
CHANNEL	20050	Full RB	CHANNEL	20300	Full RB
					

Channel Bandwidth: 20MHz 16QAM

CHANNEL	20050	1 RB	CHANNEL	20300	1 RB

CHANNEL	20050	Full RB	CHANNEL	20300	Full RB

LTE BAND 12

Channel Bandwidth: 1.4MHz QPSK					
CHANNEL	23017	1 RB	CHANNEL	23173	1 RB
					
CHANNEL	23017	Full RB	CHANNEL	23173	Full RB

Channel Bandwidth: 1.4MHz 16QAM

CHANNEL	23017	1 RB	CHANNEL	23173	1 RB
CHANNEL	23017	Full RB	CHANNEL	23173	Full RB

LTE BAND 12

Channel Bandwidth: 3MHz QPSK					
CHANNEL	23025	1 RB	CHANNEL	23165	1 RB
CHANNEL	23025	Full RB	CHANNEL	23165	Full RB
					

Channel Bandwidth: 3MHz 16QAM

CHANNEL	23025	1 RB	CHANNEL	23165	1 RB

CHANNEL	23025	Full RB	CHANNEL	23165	Full RB

LTE BAND 12

Channel Bandwidth: 5MHz QPSK					
CHANNEL	23035	1 RB	CHANNEL	23155	1 RB
CHANNEL	23035	Full RB	CHANNEL	23155	Full RB

Channel Bandwidth: 5MHz 16QAM

CHANNEL	23035	1 RB	CHANNEL	23155	1 RB
CHANNEL	23035	Full RB	CHANNEL	23155	Full RB

LTE BAND 12

Channel Bandwidth: 10MHz QPSK					
CHANNEL	23060	1 RB	CHANNEL	23130	1 RB
					
CHANNEL	23060	Full RB	CHANNEL	23130	Full RB

Channel Bandwidth: 10MHz 16QAM

CHANNEL	23060	1 RB	CHANNEL	23130	1 RB

CHANNEL	23060	Full RB	CHANNEL	23130	Full RB

3.6 CONDUCTED SPURIOUS EMISSIONS

3.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least 43 +10 log10(P) dB. The limit of emission equal to –13dBm

3.6.2 TEST PROCEDURE

a. The EUT makes a phone call to the communication simulator. All measurements were done at middle operational frequency range.

b. Measuring frequency range is from 30 MHz to 19.1GHz for WCDMA Band 4 & LTE Band 4 and 30 MHz to 9GHz for LTE Band 12. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.

3.6.3 TEST SETUP



3.6.4 TEST RESULTS

WCDMA	
CHANNEL 1312	CHANNEL 1413
FREQUENCY RANGE : 30MHz~17.5GHz	FREQUENCY RANGE : 30MHz~17.5GHz
	
CHANNEL 1513	
FREQUENCY RANGE : 30MHz~17.5GHz	
	

LTE BAND 4

1.4MHz / QPSK	
CHANNEL 19957	CHANNEL 20175
FREQUENCY RANGE : 30MHz~17.55GHz	FREQUENCY RANGE : 30MHz~17.55GHz
	
CHANNEL 20393	
FREQUENCY RANGE : 30MHz~17.55GHz	
	

3MHz / QPSK	
CHANNEL 19965	CHANNEL 20175
FREQUENCY RANGE : 30MHz~17.55GHz	FREQUENCY RANGE : 30MHz~17.55GHz
CHANNEL 20385	
FREQUENCY RANGE : 30MHz~17.55GHz	

5MHz / QPSK

CHANNEL 19975	CHANNEL 20175
FREQUENCY RANGE : 30MHz~17.55GHz	FREQUENCY RANGE : 30MHz~17.55GHz
CHANNEL 20375	
FREQUENCY RANGE : 30MHz~17.55GHz	

10MHz / QPSK

CHANNEL 20000

FREQUENCY RANGE : 30MHz~17.55GHz

CHANNEL 20175

FREQUENCY RANGE : 30MHz~17.55GHz



CHANNEL 20350

FREQUENCY RANGE : 30MHz~17.55GHz



15MHz / QPSK	
CHANNEL 20025	CHANNEL 20175
FREQUENCY RANGE : 30MHz~17.55GHz	FREQUENCY RANGE : 30MHz~17.55GHz
CHANNEL 20325	
FREQUENCY RANGE : 30MHz~17.55GHz	

20MHz / QPSK

CHANNEL 20050

FREQUENCY RANGE : 30MHz~17.55GHz

CHANNEL 20175

FREQUENCY RANGE : 30MHz~17.55GHz

CHANNEL 20300

FREQUENCY RANGE : 30MHz~17.55GHz

LTE BAND 12

1.4MHz / QPSK	
CHANNEL 23017	CHANNEL 23095
FREQUENCY RANGE : 30MHz~7.16GHz	FREQUENCY RANGE : 30MHz~7.16GHz
CHANNEL 23173	
FREQUENCY RANGE : 30MHz~7.16GHz	
	

3MHz / QPSK	
CHANNEL 23025	CHANNEL 23095
FREQUENCY RANGE : 30MHz~7.16GHz	FREQUENCY RANGE : 30MHz~7.16GHz
	
CHANNEL 23165	
FREQUENCY RANGE : 30MHz~7.16GHz	

5MHz / QPSK

CHANNEL 23035

FREQUENCY RANGE : 30MHz~7.16GHz

CHANNEL 23095

FREQUENCY RANGE : 30MHz~7.16GHz

CHANNEL 23155

FREQUENCY RANGE : 30MHz~7.16GHz

10MHz / QPSK	
CHANNEL 23060	CHANNEL 23095
FREQUENCY RANGE : 30MHz~7.16GHz	FREQUENCY RANGE : 30MHz~7.16GHz
CHANNEL 23130	
FREQUENCY RANGE : 30MHz~7.16GHz	
	

3.7 RADIATED EMISSION MEASUREMENT

3.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least 43 +10 log10(P) dB. The limit of emission equal to –13dBm

3.7.2 TEST PROCEDURES

a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.

b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G

c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.

d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15dBi.

NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

3.7.3 DEVIATION FROM TEST STANDARD

No deviation

3.7.4 TEST SETUP

<Below 30MHz>



< Frequency Range 30MHz~1GHz >



< Frequency Range above 1GHz >



For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.7.5 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

9 KHz – 30 MHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:

LTE BAND 4:

CHANNEL BANDWIDTH: 3MHz / QPSK

MODE	TX channel 20175	**FREQUENCY RANGE**	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	34.850	-31.52	-45.91	-13.00	-18.52	14.39	Peak	Horizontal
2	87.230	-39.83	-48.22	-13.00	-26.83	8.39	Peak	Horizontal
3	99.840	-39.64	-49.32	-13.00	-26.64	9.68	Peak	Horizontal
4	195.870	-38.02	-48.72	-13.00	-25.02	10.70	Peak	Horizontal
5	227.880	-39.35	-51.38	-13.00	-26.35	12.03	Peak	Horizontal
6	297.720	-43.93	-57.98	-13.00	-30.93	14.05	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	34.850	-20.01	-34.12	-13.00	-7.01	14.11	Peak	Vertical
2	85.290	-28.03	-36.49	-13.00	-15.03	8.46	Peak	Vertical
3	95.960	-29.46	-38.78	-13.00	-16.46	9.32	Peak	Vertical
4	193.930	-42.92	-53.60	-13.00	-29.92	10.68	Peak	Vertical
5	416.060	-44.03	-61.55	-13.00	-31.03	17.52	Peak	Vertical
6	705.120	-42.82	-65.84	-13.00	-29.82	23.02	Peak	Vertical



ABOVE 1GHz

Note: For higher frequency, the emission is too low to be detected.

WCDMA Band IV:

CH 1312

MODE	TX channel 1312	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3418.000	-58.40	-60.25	-13.00	-45.40	1.85	Peak	Horizontal
2 PP	5137.000	-55.78	-64.32	-13.00	-42.78	8.54	Peak	Horizontal



MODE	TX channel 1312	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3418.000	-56.48	-58.95	-13.00	-43.48	2.47	Peak	Vertical
2	PP	5137.000	-54.43	-62.42	-13.00	-41.43	7.99	Peak	Vertical



CH 1413

MODE	TX channel 1413	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3470.000	-60.10	-62.15	-13.00	-47.10	2.05	Peak	Horizontal
2 PP	5197.000	-56.34	-64.95	-13.00	-43.34	8.61	Peak	Horizontal



MODE	TX channel 1413	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-55.69	-58.22	-13.00	-42.69	2.53	Peak	Vertical
2	PP	5197.000	-54.18	-62.16	-13.00	-41.18	7.98	Peak	Vertical



CH 1513

MODE	TX channel 1513	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3505.000	-57.29	-59.48	-13.00	-44.29	2.19	Peak	Horizontal
2 PP	5257.000	-54.86	-63.54	-13.00	-41.86	8.68	Peak	Horizontal



MODE	TX channel 1513	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3505.000	-55.61	-58.21	-13.00	-42.61	2.60	Peak	Vertical
2	PP	5257.000	-53.38	-61.36	-13.00	-40.38	7.98	Peak	Vertical



LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-58.19	-60.24	-13.00	-45.19	2.05	Peak	Horizontal
2	PP	5197.000	-54.97	-63.58	-13.00	-41.97	8.61	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3470.000	-54.22	-56.75	-13.00	-41.22	2.53	Peak	Vertical
2		5197.000	-54.47	-62.45	-13.00	-41.47	7.98	Peak	Vertical



CHANNEL BANDWIDTH: 3MHz / QPSK

CH 19965

MODE	TX channel 19965	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3418.000	-58.86	-60.71	-13.00	-45.86	1.85	Peak	Horizontal
2	PP	5132.000	-53.86	-62.39	-13.00	-40.86	8.53	Peak	Horizontal



MODE	TX channel 19965	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3418.000	-54.17	-56.64	-13.00	-41.17	2.47	Peak	Vertical
2	PP	5132.000	-53.06	-61.05	-13.00	-40.06	7.99	Peak	Vertical



CH 20175

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-56.74	-58.79	-13.00	-43.74	2.05	Peak	Horizontal
2	PP	5197.000	-53.87	-62.48	-13.00	-40.87	8.61	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-53.89	-56.42	-13.00	-40.89	2.53	Peak	Vertical
2	PP	5197.000	-51.17	-59.15	-13.00	-38.17	7.98	Peak	Vertical



CH 20385

MODE	TX channel 20385	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3502.000	-58.14	-60.31	-13.00	-45.14	2.17	Peak	Horizontal
2	PP	5266.000	-54.90	-63.59	-13.00	-41.90	8.69	Peak	Horizontal



MODE	TX channel 20385	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3502.000	-53.90	-56.48	-13.00	-40.90	2.58	Peak	Vertical
2 PP	5266.000	-52.36	-60.34	-13.00	-39.36	7.98	Peak	Vertical



CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-58.23	-60.28	-13.00	-45.23	2.05	Peak	Horizontal
2	PP	5197.000	-54.81	-63.42	-13.00	-41.81	8.61	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-54.33	-56.86	-13.00	-41.33	2.53	Peak	Vertical
2	PP	5197.000	-53.61	-61.59	-13.00	-40.61	7.98	Peak	Vertical



CHANNEL BANDWIDTH: 10MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3470.000	-54.05	-56.10	-13.00	-41.05	2.05	Peak	Horizontal
2 PP	5197.000	-51.60	-60.21	-13.00	-38.60	8.61	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3470.000	-53.11	-55.64	-13.00	-40.11	2.53	Peak	Vertical
2	5197.000	-54.37	-62.35	-13.00	-41.37	7.98	Peak	Vertical



CHANNEL BANDWIDTH: 15MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-58.27	-60.32	-13.00	-45.27	2.05	Peak	Horizontal
2	PP	5197.000	-54.55	-63.16	-13.00	-41.55	8.61	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-54.22	-56.75	-13.00	-41.22	2.53	Peak	Vertical
2	PP	5197.000	-53.97	-61.95	-13.00	-40.97	7.98	Peak	Vertical



CHANNEL BANDWIDTH: 20MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3470.000	-57.84	-59.89	-13.00	-44.84	2.05	Peak	Horizontal
2 PP	5197.000	-54.50	-63.11	-13.00	-41.50	8.61	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-54.88	-57.41	-13.00	-41.88	2.53	Peak	Vertical
2	PP	5197.000	-52.27	-60.25	-13.00	-39.27	7.98	Peak	Vertical



LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz / QPSK

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Tony		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1416.000	-67.48	-60.76	-13.00	-54.48	-6.72	Peak	Horizontal
2		2122.500	-67.94	-66.01	-13.00	-54.94	-1.93	Peak	Horizontal



MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Tony		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-67.11	-61.67	-13.00	-54.11	-5.44	Peak	Vertical
2	PP	2122.500	-65.90	-65.66	-13.00	-52.90	-0.24	Peak	Vertical



CHANNEL BANDWIDTH: 3MHz / QPSK

CH 23025

MODE	TX channel 23025	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Tony		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1390.000	-64.85	-57.97	-13.00	-51.85	-6.88	Peak	Horizontal
2	2101.500	-66.60	-64.65	-13.00	-53.60	-1.95	Peak	Horizontal



MODE	TX channel 23025	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Tony		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1390.000	-66.11	-60.51	-13.00	-53.11	-5.60	Peak	Vertical
2	PP	2101.500	-65.24	-64.99	-13.00	-52.24	-0.25	Peak	Vertical



CH 23095

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Tony		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1416.000	-57.25	-50.53	-13.00	-44.25	-6.72	Peak	Horizontal
2	2122.500	-67.13	-65.20	-13.00	-54.13	-1.93	Peak	Horizontal



MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Tony		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-69.45	-64.01	-13.00	-56.45	-5.44	Peak	Vertical
2	PP	2122.500	-64.80	-64.56	-13.00	-51.80	-0.24	Peak	Vertical



CH 23165

MODE	TX channel 23165	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Tony		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1416.000	-61.37	-54.65	-13.00	-48.37	-6.72	Peak	Horizontal
2		2143.500	-66.63	-64.71	-13.00	-53.63	-1.92	Peak	Horizontal



MODE	TX channel 23165	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Tony		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-68.56	-63.12	-13.00	-55.56	-5.44	Peak	Vertical
2	PP	2143.500	-65.31	-65.07	-13.00	-52.31	-0.24	Peak	Vertical



CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Tony		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1416.000	-59.00	-52.28	-13.00	-46.00	-6.72	Peak	Horizontal
2		2122.500	-67.39	-65.46	-13.00	-54.39	-1.93	Peak	Horizontal



MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Tony		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-68.47	-63.03	-13.00	-55.47	-5.44	Peak	Vertical
2	PP	2122.500	-65.74	-65.50	-13.00	-52.74	-0.24	Peak	Vertical



CHANNEL BANDWIDTH: 10MHz / QPSK

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Tony		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1416.000	-66.23	-59.51	-13.00	-53.23	-6.72	Peak	Horizontal
2	2122.500	-67.19	-65.26	-13.00	-54.19	-1.93	Peak	Horizontal



MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Tony		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-64.40	-58.96	-13.00	-51.40	-5.44	Peak	Vertical
2	PP	2122.500	-63.09	-62.85	-13.00	-50.09	-0.24	Peak	Vertical



4 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Shenzhen EMC/RF Lab:
Tel: +86-755-88696566
Fax: +86-755-88696577

Email: customerservice.dg@cn.bureauveritas.com
Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---