FCC PART 15C
TEST REPORT
No.I19Z70269-IOT05

for

Samsung Electronics. Co., Ltd.

Mobile phone

SM-A015F/DS, SM-A015F

With

FCC ID: ZCASMA015F

Hardware Version: REV1.0

Software Version: A015F.001(A015FXXE0ASI1)

Issued Date: 2019-10-28

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: cttl_terminals@caict.ac.cn, website: www.caict.ac.cn

©Copyright. All rights reserved by CTTL.

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I19Z70269-IOT05	Rev.0	1st edition	2019-10-28

©Copyright. All rights reserved by CTTL.

CONTENTS

1. TEST LABORATORY 5

1.1. INTRODUCTION & ACCREDITATION 5
1.2. TESTING LOCATION 5
1.3. TESTING ENVIRONMENT 5
1.4. PROJECT DATA 5
1.5. SIGNATURE 5

2. CLIENT INFORMATION 6

2.1. APPLICANT INFORMATION 6
2.2. MANUFACTURER INFORMATION 6

3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) 7

3.1. ABOUT EUT 7
3.2. INTERNAL IDENTIFICATION OF EUT 7
3.3. INTERNAL IDENTIFICATION OF AE 7
3.4. GENERAL DESCRIPTION 8
3.5. INTERPRETATION OF THE TEST ENVIRONMENT 8

4. REFERENCE DOCUMENTS 9

4.1. DOCUMENTS SUPPLIED BY APPLICANT 9
4.2. REFERENCE DOCUMENTS FOR TESTING 9

5. TEST RESULTS 10

5.1. SUMMARY OF TEST RESULTS 10
5.2. STATEMENTS 10
5.3. TEST CONDITIONS 10

6. TEST FACILITIES UTILIZED 11

7. MEASUREMENT UNCERTAINTY 12

7.1. MAXIMUM OUTPUT POWER 12
7.2. PEAK POWER SPECTRAL DENSITY 12
7.3. DTS 6-DB SIGNAL BANDWIDTH 12
7.4. BAND EDGES COMPLIANCE 12
7.5. TRANSMITTER SPURIOUS EMISSION 12
7.6. AC POWER-LINE CONDUCTED EMISSION 12

ANNEX A: DETAILED TEST RESULTS 13

A.1. MEASUREMENT METHOD 13

A.2. MAXIMUM OUTPUT POWER 14

A.2.1. PEAK OUTPUT POWER-CONDUCTED 14
A.2.2. AVERAGE OUTPUT POWER-CONDUCTED 15

©Copyright. All rights reserved by CTTL.

A.3. PEAK POWER SPECTRAL DENSITY 17

A.4. DTS 6-DB SIGNAL BANDWIDTH 24

A.5. BAND EDGES COMPLIANCE 31

A.6. TRANSMITTER SPURIOUS EMISSION 36

A.6.1 TRANSMITTER SPURIOUS EMISSION – CONDUCTED 36

A.6.2 TRANSMITTER SPURIOUS EMISSION - RADIATED 89

A.7. AC POWER-LINE CONDUCTED EMISSION 103

ANNEX B: ACCREDITATION CERTIFICATE 108

©Copyright. All rights reserved by CTTL.

1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Location 1:CTTL(Huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China100191

1.3. Testing Environment

Normal Temperature: 15-35℃

Relative Humidity: 20-75%

1.4. Project data

Testing Start Date: 2019-09-16

Testing End Date: 2019-10-28

1.5. Signature

Xie Xiuzhen

(Prepared this test report)

Zheng Wei

(Reviewed this test report)

Hu Xiaoyu

(Approved this test report)

©Copyright. All rights reserved by CTTL.

2. Client Information

2.1. Applicant Information

Company Name:	Samsung Electronics. Co., Ltd.
Address:	R5, A Tower 22 Floor A-1,(Maetan dong) 129,Samsung-ro,Yeongtong-gu, Suwon-Si, Gyeonggi-do 16677, Korea
City:	/
Postal Code:	/
Country:	Korea
Telephone:	+82-10-4376-0326
Fax:	/

2.2. Manufacturer Information

Company Name:	HUAQIN TELECOM HONG KONG LIMITED
Address:	FLAT/RM 510 5/F LINCOLN CENTER,20 YIP FUNG STREET FANLING NT,HONG KONG
City:	HONG KONG
Postal Code:	/
Country:	China
Telephone:	+86 13632958367
Fax:	/

©Copyright. All rights reserved by CTTL.

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Mobile phone
Model name	SM-A015F/DS, SM-A015F
FCC ID	ZCASMA015F
With WLAN Function	Yes
Frequency Range	ISM 2400MHz~2483.5MHz
Type of Modulation	DSSS/CCK/OFDM
Number of Channels	11
Antenna	Integral Antenna
MAX Conducted Power	25.40dBm
Power Supply	3.85V

3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	359471100095843/ 359472100095841	REV1.0	A015F.001(A015FXXE0ASI1)
EUT2	359471100062801/ 359472100062809	REV1.0	A015F.001(A015FXXE0ASI1)
EUT3	359471100095082/ 359472100095080	REV1.0	A015F.001(A015FXXE0ASI1)

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

AE ID*	Description	SN	Remarks
AE1	Battery	/	/
AE2	Battery	/	/
AE3	Charger	/	/
AE4	Charger	/	/
AE5	USB Cable	/	/

AE1

Model	QL1695
Manufacturer	Ningde Amperex Technology Limited
Capacitance	2920mAh/3000mAh
Nominal voltage	3.85 V

AE2

Model	QL1695
Manufacturer	SCUD(Fujian) Electronics Co., Ltd.
Capacitance	2920mAh/3000mAh
Nominal voltage	3.85 V

©Copyright. All rights reserved by CTTL.

AE3

Model	ETA0U83JWS
Manufacturer	Samsung Electronics Co., Ltd
Length of cable	/

AE4

Model	ETA0U83EWE
Manufacturer	Samsung Electronics Co., Ltd
Length of cable	/

AE5

Model	ECB-DU68WE
Manufacturer	SHENGHUA
Length of cable	/

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment under Test (EUT) is a model of Mobile phone with integrated antenna and inbuilt battery.

It has Bluetooth (EDR) function.

It consists of normal options: travel charger, USB cable.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

3.5. Interpretation of the Test Environment

For the test methods, the test environment uncertainty figures correspond to an expansion factor k=2.

Measurement Uncertainty

Parameter	Uncertainty
temperature	0.48°C
humidity	2 %
DC voltages	0.003V

©Copyright. All rights reserved by CTTL.

4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902-928MHz, 2400-2483.5 MHz, and 5725-5850 MHz.	2018
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	2013

©Copyright. All rights reserved by CTTL.

5. Test Results

5.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15C	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.247 (b)	/	P
Peak Power Spectral Density	15.247 (e)	/	P
Occupied 6dB Bandwidth	15.247 (a)	/	P
Band Edges Compliance	15.247 (d)	/	P
Transmitter Spurious Emission - Conducted	15.247 (d)	/	P
Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	/	P
AC Powerline Conducted Emission	15.107, 15.207	/	P

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NP	Not Perform, The test was not performed by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

5.2. Statements

The test cases as listed in section 5.1 of this report for the EUT specified in section 3 was performed by CTTL and according to the standards or reference documents listed in section 4.2

The EUT met all requirements of the standards or reference documents, and only the WLAN function was tested in this report.

The model of SM-A015F/DS is double card, and the model of SM-A015F is single card.

5.3. Test Conditions

T nom	Normal Temperature
T min	Low Temperature
T max	High Temperature
V nom	Normal Voltage

For this report, if the test cases listed above are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	T nom	26℃
Voltage	V nom	3.85V(By battery)
Humidity	H nom	20-75%

©Copyright. All rights reserved by CTTL.

6. Test Facilities Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	1 year	2020-05-15
2	LISN	ENV216	101200	R&S	1 year	2020-03-04
3	Test Receiver	ESCI3	100344	R&S	1 year	2020-02-14
4	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100235	Rohde & Schwarz	1 year	2020-03-01
2	BiLog Antenna	VULB9163	9163-1222	Schwarzbeck	1 year	2020-03-04
3	Dual-Ridge Waveguide Horn Antenna	3115	6914	ETS-Lindgren	1 year	2020-01-03
4	Dual-Ridge Waveguide Horn Antenna	3116	2663	ETS-Lindgren	1 year	2020-05-31

©Copyright. All rights reserved by CTTL.

7. Measurement Uncertainty

7.1. Maximum Output Power

Measurement Uncertainty: 0.387dB,k=1.96

7.2. Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

7.3. DTS 6-dB Signal Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

7.4. Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

7.5. Transmitter Spurious Emission

Conducted (k=1.96)

Frequency Range	Uncertainty(dB)
30MHz ≤ f ≤ 2GHz	1.22
2GHz ≤ f ≤3.6GHz	1.22
3.6GHz ≤ f ≤8GHz	1.22
8GHz ≤ f ≤12.75GHz	1.51
12.75GHz ≤ f ≤26GHz	1.51
26GHz ≤ f ≤40GHz	1.59

Radiated (k=2)

Frequency Range	Uncertainty(dB)
9kHz-30MHz	/
30MHz ≤ f ≤ 1GHz	5.16
1GHz ≤ f ≤18GHz	5.44
18GHz ≤ f ≤40GHz	5.28

7.6. AC Power-line Conducted Emission

Measurement Uncertainty : 3.08dB,k=2

©Copyright. All rights reserved by CTTL.

ANNEX A: Detailed Test Results

A.1. Measurement Method

A.1.1. Conducted Measurements

Connect the EUT to the test system as Fig.A.1.1.1 shows.
Set the EUT to the required work mode.
Set the EUT to the required channel.
Set the Vector Signal Analyzer and start measurement.
Record the values. Vector Signal Analyzer



Fig.A.1.1.1: Test Setup Diagram for Conducted Measurements

A.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,
Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;
Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



Fig.A.1.2.1: Test Setup Diagram for Radiated Measurements

©Copyright. All rights reserved by CTTL.

A.2. Maximum Output Power

Method of Measurement: See ANSI C63.10-2013-clause 11.9.1.2

a) Set the RBW = 1 MHz.
b) Set the VBW = 3 MHz.
c) Set the span ⩾ [1.5 × DTS bandwidth].
d) Detector = peak.
e) Sweep time = auto couple.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector).

Measurement Limit:

Standard	Limit (dBm)
FCC CRF Part 15.247(b)	< 30

EUT ID: EUT2

A.2.1. Peak Output Power-conducted

Measurement Results:

802.11b/g mode

Mode	Data Rate (Mbps)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11b	1	21.48	/	/
	2	21.62	/	/
	5.5	23.03	/	/
	11	24.58	25.07	24.46
802.11g	6	24.89	25.40	24.85
	9	24.48	/	/
	12	24.26	/	/
	18	24.22	/	/
	24	24.71	/	/
	36	23.80	/	/
	48	22.99	/	/
	54	22.59	/	/

The data rate 11Mbps and 6Mbps are selected as worse condition, and the following cases are performed with this condition.

©Copyright. All rights reserved by CTTL.

802.11n-HT20 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11n (20MHz)	MCS0	24.08	24.78	24.83
	MCS1	23.69	/	/
	MCS2	23.60	/	/
	MCS3	24.04	/	/
	MCS4	24.03	/	/
	MCS5	22.68	/	/
	MCS6	21.76	/	/
	MCS7	21.29	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT40 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		2422MHz (Ch3)	2437MHz (Ch6)	2452 MHz (Ch9)
802.11n (40MHz)	MCS0	24.33	/	/
	MCS1	24.42	/	/
	MCS2	24.35	/	/
	MCS3	24.75	/	/
	MCS4	24.77	24.50	24.89
	MCS5	23.47	/	/
	MCS6	22.50	/	/
	MCS7	22.02	/	/

The data rate MCS4 is selected as worse condition, and the following cases are performed with this condition.

Conclusion: Pass

A.2.2. Average Output Power-conducted

Method of Measurement: See ANSI C63.10-2013-clause 11.9.2.2.2

The procedure for this method is as follows:

a) Set span = 1.5OBW.

b) Set RBW = 1MHz.

c) Set VBW = 3MHz

d) Number of points in sweep = 625

e) Sweep time = auto.

f) Detector = RMS.

g) If transmit duty cycle < 98%, use a sweep trigger with the level set to enable triggering only on

©Copyright. All rights reserved by CTTL.

full power pulses. The transmitter shall operate at the maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no OFFintervals) or at duty cycle ⩾98%, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run.”

h) Trace average 100 traces in power averaging (rms) mode.

i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

802.11b/g mode

Mode	Test Result (dBm)		
	2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11b	17.74	18.10	18.25
802.11g	16.29	17.10	16.65

802.11n-HT20 mode

Mode	Test Result (dBm)		
	2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11n (20MHz)	16.72	15.45	16.86

802.11n-HT40 mode

Mode	Test Result (dBm)		
	2422MHz (Ch3)	2437MHz (Ch6)	2452 MHz (Ch9)
802.11n(40MHz)	16.18	15.08	16.45

Conclusion: Pass

©Copyright. All rights reserved by CTTL.

A.3. Peak Power Spectral Density

Method of Measurement: See ANSI C63.10-2013-clause 11.10.2

a) Set analyzer center frequency to DTS channel center frequency.
b) Set the span to 1.5 times the DTS bandwidth.
c) Set the RBW to RBW = 3 kHz.
d) Set the VBW = 10 kHz.
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum amplitude level within the RBW.

Measurement Limit:

Standard	Limit
FCC CRF Part 15.247(e)	< 8 dBm/3 kHz

Measurement Results:

802.11b/g mode

Mode	Channel	Power Spectral Density (dBm/3 kHz)		Conclusion
802.11b	1	Fig.A.3.1	-3.25	**P**
	6	Fig.A.3.2	-5.43	**P**
	11	Fig.A.3.3	-3.26	**P**
802.11g	1	Fig.A.3.4	-7.93	**P**
	6	Fig.A.3.5	-8.29	**P**
	11	Fig.A.3.6	-7.34	**P**

802.11n-HT20 mode

Mode	Channel	Power Spectral Density (dBm/3 kHz)		Conclusion
802.11n (HT20)	1	Fig.A.3.7	-8.23	**P**
	6	Fig.A.3.8	-8.97	**P**
	11	Fig.A.3.9	-7.42	**P**

802.11n-HT40 mode

Mode	Channel	Power Spectral Density (dBm/3 kHz)		Conclusion
802.11n (HT40)	3	Fig.A.3.10	-11.55	**P**
	6	Fig.A.3.11	-12.03	**P**
	9	Fig.A.3.12	-10.57	**P**

Conclusion: Pass

©Copyright. All rights reserved by CTTL.

Test graphs as below:



Fig.A.3.1 Power Spectral Density(802.11b,Ch1)



Fig.A.3.2 Power Spectral Density (802.11b, Ch 6)

©Copyright. All rights reserved by CTTL.



Fig.A.3.3 Power Spectral Density (802.11b, Ch 11)



Fig.A.3.4 Power Spectral Density (802.11g, Ch 1)

©Copyright. All rights reserved by CTTL.



Fig.A.3.5 Power Spectral Density (802.11g, Ch 6)



Fig.A.3.6 Power Spectral Density (802.11g, Ch 11)

©Copyright. All rights reserved by CTTL.



Fig.A.3.7 Power Spectral Density (802.11n-HT20, Ch 1)



Fig.A.3.8 Power Spectral Density (802.11n-HT20, Ch 6)

©Copyright. All rights reserved by CTTL.



Fig.A.3.9 Power Spectral Density (802.11n-HT20, Ch 11)



Fig.A.3.10 Power Spectral Density (802.11n-HT40, Ch 3)

©Copyright. All rights reserved by CTTL.



Fig.A.3.11 Power Spectral Density (802.11n-HT40, Ch 6)



Fig.A.3.12 Power Spectral Density (802.11n-HT40, Ch 9)

©Copyright. All rights reserved by CTTL.

A.4. DTS 6-dB Signal Bandwidth

Method of Measurement: See ANSI C63.10-2013 section 11.8.1.

a) Set RBW = 100 kHz.
b) Set the video bandwidth (VBW) = 300 kHz.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.247 (a)	≥ 500

EUT ID: EUT2

Measurement Result:

802.11b/g mode

Mode	Channel	Occupied 6dB Bandwidth (kHz)		conclusion
802.11b	1	Fig.A.4.1	7400	**P**
	6	Fig.A.4.2	8300	**P**
	11	Fig.A.4.3	7900	**P**
802.11g	1	Fig.A.4.4	16000	**P**
	6	Fig.A.4.5	16050	**P**
	11	Fig.A.4.6	16050	**P**

802.11n-HT20 mode

Mode	Channel	Occupied 6dB Bandwidth (kHz)		conclusion
802.11n (HT20)	1	Fig.A.4.7	16050	**P**
	6	Fig.A.4.8	16300	**P**
	11	Fig.A.4.9	16350	**P**

802.11n-HT40 mode

Mode	Channel	Occupied 6dB Bandwidth (kHz)		conclusion
802.11n (HT40)	3	Fig.A.4.10	35200	**P**
	6	Fig.A.4.11	35120	**P**
	9	Fig.A.4.12	35440	**P**

©Copyright. All rights reserved by CTTL.

Conclusion: Pass

Test graphs as below:



Fig.A.4.1 Occupied 6dB Bandwidth(802.11b,Ch 1)



Fig.A.4.2 Occupied 6dB Bandwidth (802.11b, Ch 6)

©Copyright. All rights reserved by CTTL.



Fig.A.4.3 Occupied 6dB Bandwidth (802.11b, Ch 11)



Fig.A.4.4 Occupied 6dB Bandwidth (802.11g, Ch 1)

©Copyright. All rights reserved by CTTL.



Fig.A.4.5 Occupied 6dB Bandwidth (802.11g, Ch 6)



Fig.A.4.6 Occupied 6dB Bandwidth (802.11g, Ch 11)

©Copyright. All rights reserved by CTTL.



Fig.A.4.7 Occupied 6dB Bandwidth (802.11n-20MHz, Ch 1)



Fig.A.4.8 Occupied 6dB Bandwidth (802.11n-HT20, Ch 6)

©Copyright. All rights reserved by CTTL.



Fig.A.4.9 Occupied 6dB Bandwidth (802.11n-HT20, Ch 11)



Fig.A.4.10 Occupied 6dB Bandwidth (802.11n-40MHz, Ch 3)

©Copyright. All rights reserved by CTTL.



Fig.A.4.11 Occupied 6dB Bandwidth (802.11n-HT40, Ch 6)



Fig.A.4.12 Occupied 6dB Bandwidth (802.11n-HT40, Ch 9)

©Copyright. All rights reserved by CTTL.

A.5. Band Edges Compliance

Method of Measurement: See ANSI C63.10-2013-clause 6.10.4

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below.

a) Set Span = 100MHz
b) Sweep Time: coupled
c) Set the RBW= 100 kHz
c) Set the VBW= 300 kHz
d) Detector: Peak
e) Trace: Max hold

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	> 20

EUT ID: EUT2

Measurement Result:

802.11b/g mode

Mode	Channel	Test Results	Conclusion
802.11b	1	Fig.A.5.1	**P**
	11	Fig.A.5.2	**P**
802.11g	1	Fig.A.5.3	**P**
	11	Fig.A.5.4	**P**

802.11n-HT20 mode

Mode	Channel	Test Results	Conclusion
802.11n (HT20)	1	Fig.A.5.5	**P**
	11	Fig.A.5.6	**P**

802.11n-HT40 mode

Mode	Channel	Test Results	Conclusion
802.11n (HT40)	3	Fig.A.5.7	**P**
	9	Fig.A.5.8	**P**

Conclusion: Pass

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.A.5.1 Band Edges (802.11b, Ch 1)



Fig.A.5.2 Band Edges (802.11b, Ch 11)

©Copyright. All rights reserved by CTTL.



Fig.A.5.3 Band Edges (802.11g, Ch 1)



Fig.A.5.4 Band Edges (802.11g, Ch 11)

©Copyright. All rights reserved by CTTL.



Fig.A.5.5 Band Edges (802.11n-HT20, Ch 1)



Fig.A.5.6 Band Edges (802.11n-HT20, Ch 11)

©Copyright. All rights reserved by CTTL.



Fig.A.5.7 Band Edges (802.11n-HT40, Ch 3)



Fig.A.5.8 Band Edges (802.11n-HT40, Ch 9)

©Copyright. All rights reserved by CTTL.

A.6. Transmitter Spurious Emission

A.6.1 Transmitter Spurious Emission – Conducted

Method of Measurement: See ANSI C63.10-2013-clause 11.11.2

Establish a reference level by using the following procedure:

a) Set instrument center frequency to DTS channel center frequency
b) Set the span to ≥ 1.5 times the DTS bandwidth
c) Set the RBW= 100 kHz
d) Set the VBW= 300 kHz
e) Detector = Peak
f) Sweep time = auto couple
g) Trace mode = max hold
h) Allow trace to fully stabilize
i) Use the peak marker function to determine the maximum PSD level

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

Establish an emission level by using the following procedure:

a) Set the center frequency and span to encompass frequency range to be measured.
b) Set the RBW = 100 kHz.
c) Set the VBW = 300 kHz.
d) Detector = peak.
e) Sweep time = auto couple.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

EUT ID: EUT2

Measurement Results:

©Copyright. All rights reserved by CTTL.

802.11b mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11b	1	2.412 GHz	Fig.A.6.1.1	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.2	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.3	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.4	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.5	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.6	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.7	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.8	**P**
	6	2.437 GHz	Fig.A.6.1.9	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.10	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.11	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.12	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.13	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.14	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.15	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.16	**P**
	11	2.462 GHz	Fig.A.6.1.17	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.18	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.19	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.20	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.21	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.22	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.23	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.24	**P**

©Copyright. All rights reserved by CTTL.

802.11g mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11g	1	2.412 GHz	Fig.A.6.1.25	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.26	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.27	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.28	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.29	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.30	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.31	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.32	**P**
	6	2.437 GHz	Fig.A.6.1.33	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.34	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.35	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.36	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.37	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.38	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.39	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.40	**P**
	11	2.462 GHz	Fig.A.6.1.41	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.42	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.43	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.44	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.45	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.46	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.47	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.48	**P**

©Copyright. All rights reserved by CTTL.

802.11n-HT20 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT20)	1	2.412 GHz	Fig.A.6.1.49	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.50	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.51	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.52	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.53	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.54	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.55	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.56	**P**
	6	2.437 GHz	Fig.A.6.1.57	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.58	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.59	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.60	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.61	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.62	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.63	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.64	**P**
	11	2.462 GHz	Fig.A.6.1.65	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.66	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.67	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.68	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.69	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.70	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.71	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.72	**P**

©Copyright. All rights reserved by CTTL.

802.11n-HT40 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT40)	3	2.422 GHz	Fig.A.6.1.73	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.74	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.75	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.76	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.77	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.78	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.79	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.80	**P**
	6	2.437 GHz	Fig.A.6.1.81	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.82	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.83	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.84	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.85	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.86	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.87	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.88	**P**
	9	2.452 GHz	Fig.A.6.1.89	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.90	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.91	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.92	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.93	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.94	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.95	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.96	**P**

Conclusion: Pass

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.1 Transmitter Spurious Emission - Conducted (802.11b, Ch1, Center Frequency)



Fig.A.6.1.2 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 30 MHz-1 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.3 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 1 GHz-2.5 GHz)



Fig.A.6.1.4 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 2.5 GHz-7.5 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.5 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 7.5 GHz-10 GHz)



Fig.A.6.1.6 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 10 GHz-15 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.7 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 15 GHz-20 GHz)



Fig.A.6.1.8 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 20 GHz-26 GHz)

©Copyright. All rights reserved by CTTL.