FCC PART 15C
TEST REPORT
No.I20Z70323-IOT04

for

Samsung Electronics Co., Ltd.

Smart Phone

SM-A025G/DSN

With

FCC ID: ZCASMA025G

Hardware Version: REV1.0

Software Version: A025G.001

Issued Date: 2020-11-27

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: cttl_terminals@caict.ac.cn, website: www.caict.ac.cn

©Copyright. All rights reserved by CTTL.

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I20Z60323-IOT04	Rev.0	1st edition	2020-11-27

©Copyright. All rights reserved by CTTL.

CONTENTS

1. TEST LABORATORY 5

1.1. INTRODUCTION & ACCREDITATION 5
1.2. TESTING LOCATION 5
1.3. TESTING ENVIRONMENT 6
1.4. PROJECT DATE 6
1.5. SIGNATURE 6

2. CLIENT INFORMATION 7

2.1. APPLICANT INFORMATION 7
2.2. MANUFACTURER INFORMATION 7

3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) 8

3.1. ABOUT EUT 8
3.2. INTERNAL IDENTIFICATION OF EUT 8
3.3. INTERNAL IDENTIFICATION OF AE 8
3.4. GENERAL DESCRIPTION 10
3.5. INTERPRETATION OF THE TEST ENVIRONMENT 10

4. REFERENCE DOCUMENTS 10

4.1. DOCUMENTS SUPPLIED BY APPLICANT 10
4.2. REFERENCE DOCUMENTS FOR TESTING 10

5. TEST RESULTS 11

5.1. SUMMARY OF TEST RESULTS 11
5.2. STATEMENTS 11
5.3. TEST CONDITIONS 11

6. TEST FACILITIES UTILIZED 12

7. MEASUREMENT UNCERTAINTY 13

7.1. MAXIMUM OUTPUT POWER 13
7.2. PEAK POWER SPECTRAL DENSITY 13
7.3. DTS 6-DB SIGNAL BANDWIDTH 13
7.4. BAND EDGES COMPLIANCE 13
7.5. TRANSMITTER SPURIOUS EMISSION 13
7.6. AC POWER-LINE CONDUCTED EMISSION 13

ANNEX A: DETAILED TEST RESULTS 14

A.1. MEASUREMENT METHOD 14

A.2. MAXIMUM OUTPUT POWER 15

A.2.1. PEAK OUTPUT POWER-CONDUCTED 15

©Copyright. All rights reserved by CTTL.

A.3. PEAK POWER SPECTRAL DENSITY 17

A.4. DTS 6-DB SIGNAL BANDWIDTH 24

A.5. BAND EDGES COMPLIANCE 31

A.6. TRANSMITTER SPURIOUS EMISSION 36

A.6.1 TRANSMITTER SPURIOUS EMISSION – CONDUCTED 36

A.6.2 TRANSMITTER SPURIOUS EMISSION - RADIATED 89

A.7. AC POWER-LINE CONDUCTED EMISSION 103

ANNEX B: ACCREDITATION CERTIFICATE 107

©Copyright. All rights reserved by CTTL.

1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Location 1:CTTL(Gaolizhang Road)

Address:	Cuihu Cloud Center, No.1, Gaolizhang Road, Wenquan, Haidian District, Beijing, China

Location 2:CTTL(BDA)

Address:	No.18A, Kangding Street, Beijing Economic-Technology Development Area, Beijing, P. R. China 100176

©Copyright. All rights reserved by CTTL.

1.3. Testing Environment

Normal Temperature: 15-35℃

Relative Humidity: 20-75%

1.4. Project date

Testing Start Date: 2020-10-28

Testing End Date: 2020-11-27

1.5. Signature

Xie Xiuzhen

(Prepared this test report)

Zheng Wei

(Reviewed this test report)

Hu Xiaoyu

(Approved this test report)

©Copyright. All rights reserved by CTTL.

2. Client Information

2.1. Applicant Information

Company Name:	Samsung Electronics Co., Ltd.
Address:	19 Chapin Rd.,Building D Pine Brook, NJ 07058
Contact:	Jenni Chun
Email	j1.chun@samsung.com
Telephone:	+1-201-937-4203
Fax:	/

2.2. Manufacturer Information

Company Name:	Samsung Electronics Co., Ltd.
Address:	Samsung R5, Maetan dong 129, Samsung ro Youngtong gu, Suwon city 443 742, Korea
Contact:	Sunghoon Cho
Email	ggobi.cho@samsung.com
Telephone:	+82-10-2722-4159
Fax:	/

©Copyright. All rights reserved by CTTL.

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Smart Phone
Model name	SM-A025G/DSN
FCC ID	ZCASMA025G
With WLAN Function	Yes
Frequency Band	ISM 2400MHz~2483.5MHz
Type of Modulation	DSSS/CCK/OFDM
Number of Channels	11
Antenna	Integral Antenna
MAX Conducted Power	23.97dBm
Power Supply	3.85V

3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	2070323UT02a	REV1.0	A025G.001
EUT2	2070323UT01a	REV1.0	A025G.001

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

AE ID*	Description	SN	Remarks
AE1	Charger1	/	
AE2	Charger2	/	
AE3	Charger3	/	/
AE4	Charger4		
AE5	Charger5		
AE6	USB cable		
AE7	Headset1	/	/
AE8	Headset2	/	/
AE9	battery	/	/

AE1

Model	EP-TA50JWE
Manufacturer	HAEM Co.,Ltd
Length of cable	/

AE2

Model	EP-TA50JWE
Manufacturer	RFTech Electronics(HuiZhou)Co.,LTD
Length of cable	/

AE3

©Copyright. All rights reserved by CTTL.

Model	EP-TA200
Manufacturer	HAEM Co.,Ltd
Length of cable	/

AE4

Model	EP-TA200
Manufacturer	RFTech Electronics(HuiZhou)Co.,LTD
Length of cable	/

AE5

Model	EP-TA200
Manufacturer	SoluM Co.,Ltd
Length of cable	/

AE6

Model	EP-DR140AWE
Manufacturer	Samsung Electronics Co., Ltd.
Length of cable	/

AE7

Model	EHS61ASFWE
Manufacturer	DONGGUAN YOUNGBO ELECTRONICS CO.,LTD
Length of cable	/

AE8

Model	EHS61ASFWE
Manufacturer	WATA ELECTRONICS CO.,LTD
Length of cable	/

AE9

Type	HQ-50S
Manufacturer	SUCD(FUJIAN) Electronics Co.,Ltd
Length of cable	/

*AE ID: is used to identify the test sample in the lab internally.

©Copyright. All rights reserved by CTTL.

3.4. General Description

The Equipment under Test (EUT) is a model of Smart Phone with integrated antenna and inbuilt battery.

It has Bluetooth (EDR) function.

It consists of normal options: travel charger, USB cable.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

3.5. Interpretation of the Test Environment

For the test methods, the test environment uncertainty figures correspond to an expansion factor k=2.

Measurement Uncertainty

Parameter	Uncertainty
temperature	0.48°C
humidity	2 %
DC voltages	0.003V

4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902-928MHz, 2400-2483.5 MHz, and 5725-5850 MHz.	2018
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	2013
KDB 558074 D01	Federal Communications Commission Office of Engineering and Technology Laboratory Division GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES	2019

©Copyright. All rights reserved by CTTL.

5. Test Results

5.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15C	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.247 (b)	/	P
Peak Power Spectral Density	15.247 (e)	/	P
Occupied 6dB Bandwidth	15.247 (a)	/	P
Band Edges Compliance	15.247 (d)	/	P
Transmitter Spurious Emission - Conducted	15.247 (d)	/	P
Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	/	P
AC Powerline Conducted Emission	15.107, 15.207	/	P

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NP	Not Perform, The test was not performed by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

5.2. Statements

The test cases as listed in section 5.1 of this report for the EUT specified in section 3 was performed by CTTL and according to the standards or reference documents listed in section 4.2

The EUT met all requirements of the standards or reference documents, and only the WLAN function was tested in this report.

5.3. Test Conditions

T nom	Normal Temperature
T min	Low Temperature
T max	High Temperature
V nom	Normal Voltage

For this report, if the test cases listed above are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	T nom	26℃
Voltage	V nom	3.85V
Humidity	H nom	20-75%

©Copyright. All rights reserved by CTTL.

6. Test Facilities Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	1 year	2021-05-06
2	LISN	ENV216	101459	R&S	1 year	2021-03-17
3	Test Receiver	ESCI	100766	R&S	1 year	2021-03-10
4	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100376	Rohde & Schwarz	1 year	2021-09-04
2	BiLog Antenna	VULB9163	9163-514	Schwarzbeck	1 year	2021-02-24
3	Dual-Ridge Waveguide Horn Antenna	3117	00139065	ETS-Lindgren	1 year	2021-10-11
4	Dual-Ridge Waveguide Horn Antenna	3116	2663	ETS-Lindgren	1 year	2021-08-05

©Copyright. All rights reserved by CTTL.

7. Measurement Uncertainty

7.1. Maximum Output Power

Measurement Uncertainty: 0.387dB,k=1.96

7.2. Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

7.3. DTS 6-dB Signal Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

7.4. Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

7.5. Transmitter Spurious Emission

Conducted (k=1.96)

Frequency Range	Uncertainty(dB)
30MHz ≤ f ≤ 2GHz	1.22
2GHz ≤ f ≤3.6GHz	1.22
3.6GHz ≤ f ≤8GHz	1.22
8GHz ≤ f ≤12.75GHz	1.51
12.75GHz ≤ f ≤26GHz	1.51
26GHz ≤ f ≤40GHz	1.59

Radiated (k=2)

Frequency Range	Uncertainty(dB)
9kHz-30MHz	/
30MHz ≤ f ≤ 1GHz	5.40
1GHz ≤ f ≤18GHz	4.32
18GHz ≤ f ≤40GHz	5.26

7.6. AC Power-line Conducted Emission

Measurement Uncertainty : 3.10dB,k=2

©Copyright. All rights reserved by CTTL.

ANNEX A: Detailed Test Results

A.1. Measurement Method

A.1.1. Conducted Measurements

Connect the EUT to the test system as Fig.A.1.1.1 shows.
Set the EUT to the required work mode.
Set the EUT to the required channel.
Set the Vector Signal Analyzer and start measurement.
Record the values. Vector Signal Analyzer



Fig.A.1.1.1: Test Setup Diagram for Conducted Measurements

A.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,
Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;
Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



Fig.A.1.2.1: Test Setup Diagram for Radiated Measurements

©Copyright. All rights reserved by CTTL.

A.2. Maximum Output Power

Method of Measurement: See ANSI C63.10-2013-clause 11.9.1.2

a) Set the RBW = 1 MHz.
b) Set the VBW = 3 MHz.
c) Set the span ⩾ [1.5 × DTS bandwidth].
d) Detector = peak.
e) Sweep time = auto couple.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector).

Measurement Limit:

Standard	Limit (dBm)
FCC CRF Part 15.247(b)	< 30

EUT ID: EUT2

A.2.1. Peak Output Power-conducted

Measurement Results:

802.11b/g mode

Mode	Data Rate (Mbps)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11b	1	20.48	19.66	19.29
	2	20.37	/	/
	5.5	20.32	/	/
	11	20.45	/	/
802.11g	6	23.66	/	/
	9	23.61	/	/
	12	23.52	/	/
	18	23.49	/	/
	24	23.97	23.33	23.01
	36	23.43	/	/
	48	23.08	/	/
	54	22.58	/	/

The data rate 1Mbps and 24Mbps are selected as worse condition, and the following cases are performed with this condition.

©Copyright. All rights reserved by CTTL.

802.11n-HT20 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11n (20MHz)	MCS0	23.63	/	/
	MCS1	23.66	/	/
	MCS2	23.54	/	/
	MCS3	23.94	/	/
	MCS4	23.95	23.35	23.08
	MCS5	23.11	/	/
	MCS6	23.67	/	/
	MCS7	22.66	/	/

The data rate MCS4 is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT40 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		2422MHz (Ch3)	2437MHz (Ch6)	2452 MHz (Ch9)
802.11n (40MHz)	MCS0	21.32	/	/
	MCS1	21.23	/	/
	MCS2	21.15	/	/
	MCS3	21.57	21.49	21.62
	MCS4	21.56	/	/
	MCS5	20.67	/	/
	MCS6	20.11	/	/
	MCS7	20.13	/	/

The data rate MCS3 is selected as worse condition, and the following cases are performed with this condition.

Conclusion: Pass

©Copyright. All rights reserved by CTTL.

A.3. Peak Power Spectral Density

Method of Measurement: See ANSI C63.10-2013-clause 11.10.2

a) Set analyzer center frequency to DTS channel center frequency.
b) Set the span to 1.5 times the DTS bandwidth.
c) Set the RBW to RBW = 3 kHz.
d) Set the VBW = 10 kHz.
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum amplitude level within the RBW.

Measurement Limit:

Standard	Limit
FCC CRF Part 15.247(e)	< 8 dBm/3 kHz

Measurement Results:

802.11b/g mode

Mode	Channel	Power Spectral Density (dBm/3 kHz)		Conclusion
802.11b	1	Fig.A.3.1	-5.77	**P**
	6	Fig.A.3.2	-5.93	**P**
	11	Fig.A.3.3	-6.45	**P**
802.11g	1	Fig.A.3.4	-10.29	**P**
	6	Fig.A.3.5	-8.51	**P**
	11	Fig.A.3.6	-10.19	**P**

802.11n-HT20 mode

Mode	Channel	Power Spectral Density (dBm/3 kHz)		Conclusion
802.11n (HT20)	1	Fig.A.3.7	-10.00	**P**
	6	Fig.A.3.8	-8.21	**P**
	11	Fig.A.3.9	-10.62	**P**

802.11n-HT40 mode

Mode	Channel	Power Spectral Density (dBm/3 kHz)		Conclusion
802.11n (HT40)	3	Fig.A.3.10	-14.84	**P**
	6	Fig.A.3.11	-15.04	**P**
	9	Fig.A.3.12	-14.10	**P**

Conclusion: Pass

©Copyright. All rights reserved by CTTL.

Test graphs as below:



Fig.A.3.1 Power Spectral Density(802.11b,Ch1)



Fig.A.3.2 Power Spectral Density (802.11b, Ch 6)

©Copyright. All rights reserved by CTTL.



Fig.A.3.3 Power Spectral Density (802.11b, Ch 11)



Fig.A.3.4 Power Spectral Density (802.11g, Ch 1)

©Copyright. All rights reserved by CTTL.



Fig.A.3.5 Power Spectral Density (802.11g, Ch 6)



Fig.A.3.6 Power Spectral Density (802.11g, Ch 11)

©Copyright. All rights reserved by CTTL.



Fig.A.3.7 Power Spectral Density (802.11n-HT20, Ch 1)



Fig.A.3.8 Power Spectral Density (802.11n-HT20, Ch 6)

©Copyright. All rights reserved by CTTL.



Fig.A.3.9 Power Spectral Density (802.11n-HT20, Ch 11)



Fig.A.3.10 Power Spectral Density (802.11n-HT40, Ch 3)

©Copyright. All rights reserved by CTTL.



Fig.A.3.11 Power Spectral Density (802.11n-HT40, Ch 6)



Fig.A.3.12 Power Spectral Density (802.11n-HT40, Ch 9)

©Copyright. All rights reserved by CTTL.

A.4. DTS 6-dB Signal Bandwidth

Method of Measurement: See ANSI C63.10-2013 section 11.8.1.

a) Set RBW = 100 kHz.
b) Set the video bandwidth (VBW) = 300 kHz.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.247 (a)	≥ 500

EUT ID: EUT2

Measurement Result:

802.11b/g mode

Mode	Channel	Occupied 6dB Bandwidth (MHz)		conclusion
802.11b	1	Fig.A.4.1	8.05	**P**
	6	Fig.A.4.2	8.65	**P**
	11	Fig.A.4.3	8.70	**P**
802.11g	1	Fig.A.4.4	16.50	**P**
	6	Fig.A.4.5	16.45	**P**
	11	Fig.A.4.6	16.45	**P**

802.11n-HT20 mode

Mode	Channel	Occupied 6dB Bandwidth (MHz)		conclusion
802.11n (HT20)	1	Fig.A.4.7	17.70	**P**
	6	Fig.A.4.8	17.65	**P**
	11	Fig.A.4.9	17.70	**P**

802.11n-HT40 mode

Mode	Channel	Occupied 6dB Bandwidth (MHz)		conclusion
802.11n (HT40)	3	Fig.A.4.10	35.84	**P**
	6	Fig.A.4.11	35.36	**P**
	9	Fig.A.4.12	35.12	**P**

©Copyright. All rights reserved by CTTL.

Conclusion: Pass

Test graphs as below:

Fig.A.4.1 Occupied 6dB Bandwidth(802.11b,Ch 1)



Fig.A.4.2 Occupied 6dB Bandwidth (802.11b, Ch 6)

©Copyright. All rights reserved by CTTL.



Fig.A.4.3 Occupied 6dB Bandwidth (802.11b, Ch 11)



Fig.A.4.4 Occupied 6dB Bandwidth (802.11g, Ch 1)

©Copyright. All rights reserved by CTTL.



Fig.A.4.5 Occupied 6dB Bandwidth (802.11g, Ch 6)



Fig.A.4.6 Occupied 6dB Bandwidth (802.11g, Ch 11)

©Copyright. All rights reserved by CTTL.



Fig.A.4.7 Occupied 6dB Bandwidth (802.11n-20MHz, Ch 1)



Fig.A.4.8 Occupied 6dB Bandwidth (802.11n-HT20, Ch 6)

©Copyright. All rights reserved by CTTL.



Fig.A.4.9 Occupied 6dB Bandwidth (802.11n-HT20, Ch 11)



Fig.A.4.10 Occupied 6dB Bandwidth (802.11n-40MHz, Ch 3)

©Copyright. All rights reserved by CTTL.



Fig.A.4.11 Occupied 6dB Bandwidth (802.11n-HT40, Ch 6)



Fig.A.4.12 Occupied 6dB Bandwidth (802.11n-HT40, Ch 9)

©Copyright. All rights reserved by CTTL.

A.5. Band Edges Compliance

Method of Measurement: See ANSI C63.10-2013-clause 6.10.4

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below.

a) Set Span = 100MHz
b) Sweep Time: coupled
c) Set the RBW= 100 kHz
c) Set the VBW= 300 kHz
d) Detector: Peak
e) Trace: Max hold

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	> 20

EUT ID: EUT2

Measurement Result:

802.11b/g mode

Mode	Channel	Test Results	Conclusion
802.11b	1	Fig.A.5.1	**P**
	11	Fig.A.5.2	**P**
802.11g	1	Fig.A.5.3	**P**
	11	Fig.A.5.4	**P**

802.11n-HT20 mode

Mode	Channel	Test Results	Conclusion
802.11n (HT20)	1	Fig.A.5.5	**P**
	11	Fig.A.5.6	**P**

802.11n-HT40 mode

Mode	Channel	Test Results	Conclusion
802.11n (HT40)	3	Fig.A.5.7	**P**
	9	Fig.A.5.8	**P**

Conclusion: Pass

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.A.5.1 Band Edges (802.11b, Ch 1)

Fig.A.5.2 Band Edges (802.11b, Ch 11)

©Copyright. All rights reserved by CTTL.

Fig.A.5.3 Band Edges (802.11g, Ch 1)

Fig.A.5.4 Band Edges (802.11g, Ch 11)

©Copyright. All rights reserved by CTTL.



Fig.A.5.5 Band Edges (802.11n-HT20, Ch 1)



Fig.A.5.6 Band Edges (802.11n-HT20, Ch 11)

©Copyright. All rights reserved by CTTL.



Fig.A.5.7 Band Edges (802.11n-HT40, Ch 3)



Fig.A.5.8 Band Edges (802.11n-HT40, Ch 9)

©Copyright. All rights reserved by CTTL.

A.6. Transmitter Spurious Emission

A.6.1 Transmitter Spurious Emission – Conducted

Method of Measurement: See ANSI C63.10-2013-clause 11.11

Establish a reference level by using the following procedure:

a) Set instrument center frequency to DTS channel center frequency
b) Set the span to ≥ 1.5 times the DTS bandwidth
c) Set the RBW= 100 kHz
d) Set the VBW= 300 kHz
e) Detector = Peak
f) Sweep time = auto couple
g) Trace mode = max hold
h) Allow trace to fully stabilize
i) Use the peak marker function to determine the maximum PSD level

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

Establish an emission level by using the following procedure:

a) Set the center frequency and span to encompass frequency range to be measured.
b) Set the RBW = 100 kHz.
c) Set the VBW = 300 kHz.
d) Detector = peak.
e) Sweep time = auto couple.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

EUT ID: EUT2

Measurement Results:

©Copyright. All rights reserved by CTTL.

802.11b mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11b	1	2.412 GHz	Fig.A.6.1.1	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.2	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.3	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.4	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.5	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.6	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.7	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.8	**P**
	6	2.437 GHz	Fig.A.6.1.9	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.10	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.11	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.12	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.13	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.14	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.15	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.16	**P**
	11	2.462 GHz	Fig.A.6.1.17	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.18	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.19	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.20	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.21	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.22	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.23	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.24	**P**

©Copyright. All rights reserved by CTTL.

802.11g mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11g	1	2.412 GHz	Fig.A.6.1.25	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.26	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.27	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.28	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.29	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.30	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.31	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.32	**P**
	6	2.437 GHz	Fig.A.6.1.33	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.34	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.35	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.36	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.37	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.38	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.39	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.40	**P**
	11	2.462 GHz	Fig.A.6.1.41	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.42	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.43	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.44	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.45	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.46	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.47	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.48	**P**

©Copyright. All rights reserved by CTTL.

802.11n-HT20 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT20)	1	2.412 GHz	Fig.A.6.1.49	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.50	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.51	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.52	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.53	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.54	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.55	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.56	**P**
	6	2.437 GHz	Fig.A.6.1.57	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.58	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.59	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.60	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.61	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.62	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.63	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.64	**P**
	11	2.462 GHz	Fig.A.6.1.65	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.66	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.67	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.68	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.69	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.70	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.71	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.72	**P**

©Copyright. All rights reserved by CTTL.

802.11n-HT40 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT40)	3	2.422 GHz	Fig.A.6.1.73	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.74	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.75	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.76	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.77	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.78	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.79	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.80	**P**
	6	2.437 GHz	Fig.A.6.1.81	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.82	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.83	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.84	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.85	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.86	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.87	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.88	**P**
	9	2.452 GHz	Fig.A.6.1.89	**P**
		30 MHz ~ 1 GHz	Fig.A.6.1.90	**P**
		1 GHz ~ 2.5 GHz	Fig.A.6.1.91	**P**
		2.5 GHz ~ 7.5 GHz	Fig.A.6.1.92	**P**
		7.5 GHz ~ 10 GHz	Fig.A.6.1.93	**P**
		10 GHz ~ 15 GHz	Fig.A.6.1.94	**P**
		15 GHz ~ 20 GHz	Fig.A.6.1.95	**P**
		20 GHz ~ 26 GHz	Fig.A.6.1.96	**P**

Conclusion: Pass

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.1 Transmitter Spurious Emission - Conducted (802.11b, Ch1, Center Frequency)



Fig.A.6.1.2 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 30 MHz-1 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.3 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 1 GHz-2.5 GHz)



Fig.A.6.1.4 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 2.5 GHz-7.5 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.5 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 7.5 GHz-10 GHz)



Fig.A.6.1.6 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 10 GHz-15 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.7 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 15 GHz-20 GHz)



Fig.A.6.1.8 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 20 GHz-26 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.9 Transmitter Spurious Emission - Conducted (802.11b, Ch6, Center Frequency)



Fig.A.6.1.10 Transmitter Spurious Emission - Conducted (802.11b, Ch6, 30 MHz-1 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.11 Transmitter Spurious Emission - Conducted (802.11b, Ch6, 1 GHz-2.5 GHz)



Fig.A.6.1.12 Transmitter Spurious Emission - Conducted (802.11b, Ch6, 2.5 GHz-7.5 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.13 Transmitter Spurious Emission - Conducted (802.11b, Ch6, 7.5 GHz-10 GHz)



Fig.A.6.1.14 Transmitter Spurious Emission - Conducted (802.11b, Ch6, 10 GHz-15 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.15 Transmitter Spurious Emission - Conducted (802.11b, Ch6, 15 GHz-20 GHz)



Fig.A.6.1.16 Transmitter Spurious Emission - Conducted (802.11b, Ch6, 20 GHz-26 GHz)

©Copyright. All rights reserved by CTTL.