

Fig.56. Conducted spurious emission: 8DPSK, Channel 39, 1GHz - 3GHz



Fig.57. Conducted spurious emission: 8DPSK, Channel 39, 3GHz - 10GHz

©Copyright. All rights reserved by CTTL.



Fig.58. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz



Fig.59. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz

©Copyright. All rights reserved by CTTL.



Fig.60. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz



Fig.61. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL.



Fig.62. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz



Fig.63. Conducted spurious emission: 8DPSK, Channel 78, 10GHz - 26GHz

©Copyright. All rights reserved by CTTL.

B.6. Transmitter Spurious Emission - Radiated

Method of Measurement: See ANSI C63.10-2013-clause 6.4 &6.5 & 6.6

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency (MHz)	Field strength(μV/m)	Measurement distance(m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength (uV/m)	Field strength (dBuV/m)	Measurement distance (m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Set up:

Tabletop devices shall be placed on a nonconducting platform with nominal top surface dimensions 1 m by 1.5 m. For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. The EUT and transmitting antenna shall be centered on the turntable.

Note:

1. A "reference path loss" is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.
P_{Mea} is the field strength recorded from the instrument.
The measurement results are obtained as described below:
Result=P_{Mea}+$A_{Rpl=}$ P_{Mea}+Cable Loss+Antenna Factor

2. The range of evaluated frequency is from 9 kHz to 26GHz. Measurement value showed here only up to 6 maximum emissions noted.

©Copyright. All rights reserved by CTTL.

Peak Measurement results

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2383.054	61.74	4.60	27.43	29.71	74.00	12.26	H
2387.674	60.68	4.61	27.42	28.65	74.00	13.32	V
4803.500	44.43	-36.04	32.41	48.06	74.00	29.57	H
7205.500	43.61	-34.58	37.21	40.98	74.00	30.39	H
9608.000	44.62	-33.50	37.90	40.22	74.00	29.38	V
12010.000	47.25	-31.69	38.62	40.32	74.00	26.75	V

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2368.000	45.98	-36.81	32.16	50.63	74.00	28.02	V
2510.600	46.62	-36.71	32.41	50.92	74.00	27.38	H
4882.000	45.10	-35.77	32.56	48.31	74.00	28.90	V
7323.000	44.02	-34.21	37.50	40.73	74.00	29.98	H
9764.000	46.32	-33.57	38.00	41.89	74.00	27.68	V
12205.000	46.58	-31.58	38.49	39.66	74.00	27.42	V

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2484.291	62.81	4.65	27.88	30.28	74.00	11.19	H
2486.206	62.06	4.65	27.89	29.53	74.00	11.94	V
4960.000	45.63	-35.60	32.90	48.34	74.00	28.37	H
7440.000	43.55	-34.17	37.50	40.22	74.00	30.45	H
9920.000	45.65	-33.25	38.14	40.76	74.00	28.35	V
12400.000	46.75	-31.25	38.60	39.40	74.00	27.25	H

©Copyright. All rights reserved by CTTL.

π/4 DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2383.736	60.42	4.60	27.43	28.39	74.00	13.58	V
2389.153	60.67	4.61	27.42	28.64	74.00	13.33	V
4804.000	43.02	-36.04	32.41	46.65	74.00	30.98	V
7206.000	43.26	-34.58	37.21	40.63	74.00	30.74	V
9608.000	45.32	-33.50	37.90	40.92	74.00	28.68	H
12010.000	47.21	-31.69	38.62	40.29	74.00	26.79	V

π/4 DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2359.000	45.63	-37.02	32.14	50.51	74.00	28.37	H
2511.400	46.23	-36.72	32.41	50.54	74.00	27.77	V
4882.000	43.95	-35.77	32.56	47.16	74.00	30.05	H
7323.000	43.69	-34.21	37.50	40.40	74.00	30.31	H
9764.000	44.76	-33.57	38.00	40.32	74.00	29.24	V
12205.000	46.49	-31.58	38.49	39.57	74.00	27.51	V

π/4 DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2484.809	62.24	4.65	27.88	29.71	74.00	11.76	H
2486.463	62.70	4.64	27.89	30.16	74.00	11.30	V
4960.000	44.06	-35.60	32.90	46.76	74.00	29.94	H
7440.000	44.52	-34.17	37.50	41.19	74.00	29.48	H
9920.000	45.34	-33.25	38.14	40.45	74.00	28.66	V
12400.000	47.29	-31.25	38.60	39.94	74.00	26.71	H

©Copyright. All rights reserved by CTTL.

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2387.009	60.31	4.61	27.43	28.28	74.00	13.69	H
2388.102	60.34	4.61	27.42	28.31	74.00	13.66	V
4804.000	43.47	-36.04	32.41	47.09	74.00	30.53	H
7206.000	43.91	-34.58	37.21	41.28	74.00	30.09	V
9608.000	44.54	-33.50	37.90	40.14	74.00	29.46	H
12010.000	47.49	-31.69	38.62	40.56	74.00	26.51	H

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2368.600	45.78	-36.80	32.16	50.42	74.00	28.22	V
2502.000	47.01	-36.54	32.40	51.14	74.00	26.99	H
4882.000	44.03	-35.77	32.56	47.24	74.00	29.97	V
7323.000	44.51	-34.21	37.50	41.22	74.00	29.49	V
9764.000	44.75	-33.57	38.00	40.32	74.00	29.25	V
12205.000	46.63	-31.58	38.49	39.72	74.00	27.37	V

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2485.062	62.04	4.65	27.88	29.51	74.00	11.96	H
2488.084	62.03	4.64	27.91	29.49	74.00	11.97	H
4960.000	44.48	-35.60	32.90	47.18	74.00	29.52	V
7440.000	44.62	-34.17	37.50	41.29	74.00	29.38	H
9920.000	45.84	-33.25	38.14	40.95	74.00	28.16	H
12400.000	47.31	-31.25	38.60	39.96	74.00	26.69	V

©Copyright. All rights reserved by CTTL.

Average Measurement results

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2386.275	46.09	4.61	27.43	14.06	54.00	7.91	V
2389.375	46.07	4.61	27.42	14.04	54.00	7.93	H
4804.000	35.63	-36.04	32.41	39.26	54.00	18.37	V
7383.500	31.42	-34.09	37.50	28.01	54.00	22.58	V
9435.500	31.57	-33.36	38.00	26.93	54.00	22.43	V
12010.000	34.21	-31.69	38.62	27.28	54.00	19.79	V

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2436.600	46.92	4.66	27.55	14.71	54.00	7.08	H
2444.137	46.85	4.67	27.58	14.61	54.00	7.15	H
4881.500	32.82	-35.77	32.56	36.03	54.00	21.18	V
7323.000	32.32	-34.21	37.50	29.03	54.00	21.68	V
9764.000	33.17	-33.57	38.00	28.74	54.00	20.83	H
12205.000	35.21	-31.58	38.49	28.30	54.00	18.79	H

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2483.700	47.23	4.65	27.87	14.71	54.00	6.77	H
2483.925	47.20	4.65	27.87	14.68	54.00	6.80	H
4960.000	39.87	-35.60	32.90	42.57	54.00	14.13	V
7440.000	31.67	-34.17	37.50	28.34	54.00	22.33	H
9920.000	33.44	-33.25	38.14	28.55	54.00	20.56	V
12400.000	35.65	-31.25	38.60	28.30	54.00	18.35	V

©Copyright. All rights reserved by CTTL.

π/4 DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2385.262	46.03	4.60	27.43	14.00	54.00	7.97	H
2389.650	45.94	4.61	27.42	13.90	54.00	8.06	H
4804.000	31.59	-36.04	32.41	35.21	54.00	22.41	V
7206.000	31.84	-34.58	37.21	29.21	54.00	22.16	V
9608.000	33.01	-33.50	37.90	28.61	54.00	20.99	V
12010.000	35.10	-31.69	38.62	28.18	54.00	18.90	H

π/4 DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2436.600	46.85	4.66	27.55	14.64	54.00	7.15	V
2444.550	46.67	4.67	27.58	14.42	54.00	7.33	H
4882.000	33.70	-35.77	32.56	36.90	54.00	20.30	V
7323.000	32.32	-34.21	37.50	29.04	54.00	21.68	V
9764.000	33.25	-33.57	38.00	28.81	54.00	20.75	V
12205.000	34.78	-31.58	38.49	27.87	54.00	19.22	H

π/4 DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2483.550	47.13	4.65	27.87	14.60	54.00	6.87	V
2483.812	47.08	4.65	27.87	14.56	54.00	6.92	H
4960.000	37.66	-35.60	32.90	40.37	54.00	16.34	V
7440.000	31.52	-34.17	37.50	28.19	54.00	22.48	H
9920.000	33.33	-33.25	38.14	28.43	54.00	20.67	H
12400.000	35.49	-31.25	38.60	28.14	54.00	18.51	V

©Copyright. All rights reserved by CTTL.

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2389.275	46.00	4.61	27.42	13.97	54.00	8.00	H
2389.688	46.06	4.61	27.42	14.03	54.00	7.94	V
4804.000	32.93	-36.04	32.41	36.56	54.00	21.07	H
7206.000	32.12	-34.58	37.21	29.49	54.00	21.88	H
9608.000	32.67	-33.50	37.90	28.27	54.00	21.33	V
12010.000	35.42	-31.69	38.62	28.49	54.00	18.58	H

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2436.600	46.72	4.66	27.55	14.51	54.00	7.28	V
2444.550	46.64	4.67	27.58	14.40	54.00	7.36	H
4882.000	34.43	-35.77	32.56	37.63	54.00	19.57	H
7323.000	32.18	-34.21	37.50	28.90	54.00	21.82	H
9764.000	33.09	-33.57	38.00	28.65	54.00	20.91	V
12205.000	34.97	-31.58	38.49	28.06	54.00	19.03	H

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2483.812	47.09	4.65	27.87	14.57	54.00	6.91	H
2484.412	47.10	4.65	27.88	14.57	54.00	6.90	H
4960.000	35.86	-35.60	32.90	38.57	54.00	18.14	V
7440.000	31.95	-34.17	37.50	28.62	54.00	22.05	V
9920.000	33.74	-33.25	38.14	28.85	54.00	20.26	H
12400.000	35.51	-31.25	38.60	28.16	54.00	18.49	V

Conclusion: Pass

©Copyright. All rights reserved by CTTL.

B.7. Time of Occupancy (Dwell Time)

Method of Measurement: See ANSI C63.10-clause 7.8.4

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = zero span, centered on a hopping channel
- RBW = 1 MHz
- VBW ≥ RBW
- Sweep = as necessary to capture the entire dwell time per hopping channel
- Detector function = peak
- Trace = max hold

Measure a pulse time in time domain at middle frequency and then count the hopping number in 31.6s(which equals with 0.4 multiply 79) of middle frequency ,then multiply the pulse time and hopping number and record them.

Measurement Limit:

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a) (1)(iii)	< 400

Measurement Result:

For GFSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	DH1	Fig.64	0.38	Fig.65	318	120.84	P
	DH3	Fig.66	1.63	Fig.67	107	174.41	P
	DH5	Fig.68	2.88	Fig.69	56	161.28	P

For π/4 DQPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	2DH1	Fig.70	0.38	Fig.71	319	121.22	P
	2DH3	Fig.72	1.64	Fig.73	112	183.68	P
	2DH5	Fig.74	2.89	Fig.75	50	144.5	P

©Copyright. All rights reserved by CTTL.

For 8DPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	3DH1	Fig.76	0.38	Fig.77	319	121.22	P
	3DH3	Fig.78	1.63	Fig.79	115	187.45	P
	3DH5	Fig.80	2.89	Fig.81	70	202.3	P

Conclusion: PASS

Test graphs as below:



Fig.64. Time of occupancy (Dwell Time): Channel 39, Packet DH1

©Copyright. All rights reserved by CTTL.



Fig.65. Number of Transmissions Measurement: Channel 39,Packet DH1



Fig.66. Time of occupancy (Dwell Time): Channel 39, Packet DH3

©Copyright. All rights reserved by CTTL.



Fig.67. Number of Transmissions Measurement: Channel 39,Packet DH3



Fig.68. Time of occupancy (Dwell Time): Channel 39, Packet DH5

©Copyright. All rights reserved by CTTL.



Fig.69. Number of Transmissions Measurement: Channel 39,Packet DH5



Fig.70. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1

©Copyright. All rights reserved by CTTL.



Fig.71. Number of Transmissions Measurement: Channel 39,Packet 2-DH1



Fig.72. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3

©Copyright. All rights reserved by CTTL.



Fig.73. Number of Transmissions Measurement: Channel 39,Packet 2-DH3



Fig.74. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5

©Copyright. All rights reserved by CTTL.



Fig.75. Number of Transmissions Measurement: Channel 39,Packet 2-DH5



Fig.76. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1

©Copyright. All rights reserved by CTTL.



Fig.77. Number of Transmissions Measurement: Channel 39,Packet 3-DH1



Fig.78. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3

©Copyright. All rights reserved by CTTL.



Fig.79. Number of Transmissions Measurement: Channel 39,Packet 3-DH3



Fig.80. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5

©Copyright. All rights reserved by CTTL.



Fig.81. Number of Transmissions Measurement: Channel 39,Packet 3-DH5

©Copyright. All rights reserved by CTTL.

B.8. 20dB Bandwidth

Method of Measurement: See ANSI C63.10-clause 6.9.2

Measurement Procedure - Unwanted Emissions

1. Set RBW = 30kHz.

2. Set VBW = 100 kHz.

3. Set span to 3MHz

4. Detector = peak.

5. Trace Mode = max hold.

6. Sweep = auto couple.

7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(1)	NA *

Use NdB Down function of the SA to measure the 20dB Bandwidth

* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for “carrier frequency separation” test case, in Annex A.8.

Measurement Results:

For GFSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.82	950.25	NA
39	Fig.83	939.75	NA
78	Fig.84	941.25	NA

For π/4 DQPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.85	1256.25	NA
39	Fig.86	1230.00	NA
78	Fig.87	1262.25	NA

For 8DPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.88	1203.00	NA
39	Fig.89	1204.50	NA
78	Fig.90	1254.00	NA

Conclusion: NA

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.82. 20dB Bandwidth: GFSK, Channel 0



Fig.83. 20dB Bandwidth: GFSK, Channel 39

©Copyright. All rights reserved by CTTL.



Fig.84. 20dB Bandwidth: GFSK, Channel 78



Fig.85. 20dB Bandwidth: π/4 DQPSK, Channel 0

©Copyright. All rights reserved by CTTL.



Fig.86. 20dB Bandwidth: π/4 DQPSK, Channel 39



Fig.87. 20dB Bandwidth: π/4 DQPSK, Channel 78

©Copyright. All rights reserved by CTTL.



Fig.88. 20dB Bandwidth: 8DPSK, Channel 0



Fig.89. 20dB Bandwidth: 8DPSK, Channel 39

©Copyright. All rights reserved by CTTL.



Fig.90. 20dB Bandwidth: 8DPSK, Channel 78

©Copyright. All rights reserved by CTTL.

B.9. Carrier Frequency Separation

Method of Measurement: See ANSI C63.10-clause 7.8.2

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = 3MHz
- RBW=300kHz
- VBW=300kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

Search the peak marks of the middle frequency and adjacent channel, then record the separation between them.

＊Comment: This limit should be over 25 kHz or (2/3) * 20dB bandwidth, whichever is greater.

Measurement Limit:

Standard	Limit(kHz)
FCC 47 CFR Part 15.247(a)(1)	over 25 kHz or (2/3) * 20dB bandwidth

Measurement Result:

For GFSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.91	1145.25	P

For π/4 DQPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.92	1032.75	P

For 8DPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.93	1117.50	P

Conclusion: PASS

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.91. Carrier frequency separation measurement: GFSK, Channel 39



Fig.92. Carrier frequency separation measurement: π/4 DQPSK, Channel 39

©Copyright. All rights reserved by CTTL.



Fig.93. Carrier frequency separation measurement: 8DPSK, Channel 39

©Copyright. All rights reserved by CTTL.

B.10. Number of Hopping Channels

Method of Measurement: See ANSI C63.10-clause 7.8.3

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = the frequency band of operation
- RBW = 500kHz
- VBW = 500kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a) (1)(iii)	At least 15 non-overlapping channels

Measurement Result:

For GFSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.94	79	P
40~78	Fig.95		

Forπ/4 DQPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.96	79	P
40~78	Fig.97		

For 8DPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.98	79	P
40~78	Fig.99		

Conclusion: PASS

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.94. Number of hopping frequencies: GFSK, Channel 0 - 39



Fig.95. Number of hopping frequencies: GFSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL.



Fig.96. Number of hopping frequencies: π/4 DQPSK, Channel 0 - 39



Fig.97. Number of hopping frequencies: π/4 DQPSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL.



Fig.98. Number of hopping frequencies: 8DPSK, Channel 0 - 39



Fig.99. Number of hopping frequencies: 8DPSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL.

B.11. AC Powerline Conducted Emission

Method of Measurement:

See Clause 6.2 of ANSI C63.10-2013 specifically.

See Clause 4 and Clause 5 of ANSI C63.10-2013 generally.

The conducted emissions from the AC port of the EUT are measured in a shielding room. The EUT is connected to a Line Impedance Stabilization Network (LISN). An overview sweep with peak detection was performed. The measurements were performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver: Quasi-Peak / Average Detector.

The measurement bandwidth is:

Frequency of Emission (MHz)	RBW/IF bandwidth
0.15-30	9kHz

Test Condition:

Voltage（V）	Frequency（Hz）
120	60

Measurement Setup



©Copyright. All rights reserved by CTTL.

Measurement Result and limit:

EUT ID: UT17a

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	66 to 56	Fig.B.11.1	Fig.B.11.2	**P**
0.5 to 5	56			
5 to 30	60			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

Bluetooth (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	56 to 46	Fig.B.11.1	Fig.B.11.2	**P**
0.5 to 5	46			
5 to 30	50			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

Conclusion: Pass

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.B.11.1 AC Powerline Conducted Emission- bluetooth

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.159000	45.2	5000.0	9.000	On	L1	19.5	20.3	65.5
0.226500	41.6	5000.0	9.000	On	N	19.8	21.0	62.6
0.267000	39.2	5000.0	9.000	On	N	19.8	22.0	61.2
0.303000	41.2	5000.0	9.000	On	N	19.8	19.0	60.2
0.343500	38.7	5000.0	9.000	On	L1	19.5	20.4	59.1
0.384000	37.1	5000.0	9.000	On	N	19.8	21.1	58.2

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.159000	27.4	5000.0	9.000	On	L1	19.5	28.1	55.5
0.199500	28.2	5000.0	9.000	On	N	19.7	25.5	53.6
0.226500	24.2	5000.0	9.000	On	N	19.8	28.4	52.6
0.343500	22.1	5000.0	9.000	On	N	19.8	27.0	49.1
0.528000	17.9	5000.0	9.000	On	N	19.8	28.1	46.0
12.349500	26.5	5000.0	9.000	On	L1	19.8	23.5	50.0

©Copyright. All rights reserved by CTTL.



Fig.B.11.2 AC Powerline Conducted Emission-Idle

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.163500	47.3	5000.0	9.000	On	L1	19.5	18.0	65.3
0.181500	45.8	5000.0	9.000	On	L1	19.5	18.6	64.4
0.204000	45.5	5000.0	9.000	On	N	19.7	17.9	63.4
0.222000	44.4	5000.0	9.000	On	N	19.8	18.3	62.7
0.262500	42.1	5000.0	9.000	On	N	19.8	19.3	61.4
0.285000	40.7	5000.0	9.000	On	N	19.7	19.9	60.7

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.163500	29.4	5000.0	9.000	On	L1	19.5	25.9	55.3
0.181500	28.4	5000.0	9.000	On	N	19.8	26.0	54.4
0.222000	26.0	5000.0	9.000	On	N	19.8	26.8	52.7
0.262500	23.8	5000.0	9.000	On	N	19.8	27.6	51.4
0.366000	20.2	5000.0	9.000	On	N	19.8	28.4	48.6
12.093000	22.4	5000.0	9.000	On	N	19.8	27.6	50.0

Note: The measurement results showed here are worst cases of the combination of different adaptor.

©Copyright. All rights reserved by CTTL.

ANNEX C: Accreditation Certificate

United States Department of Commerce
National Institute of Standards and Technology

Certificate of Accreditation to ISO/IEC 17025:2017

NVLAP LAB CODE: 600118-0

Telecommunication Technology Labs, CAICT
Beijing
China

is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:

Electromagnetic Compatibility & Telecommunications

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).

2021-09-29 through 2022-09-30
Effective Dates

For the National Voluntary Laboratory Accreditation Program

*****END OF REPORT*****

©Copyright. All rights reserved by CTTL.