

Fig.56. Conducted spurious emission: 8DPSK, Channel 39, 1GHz - 3GHz



Fig.57. Conducted spurious emission: 8DPSK, Channel 39, 3GHz - 10GHz

©Copyright. All rights reserved by CTTL.



Fig.58. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz



Fig.59. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz

©Copyright. All rights reserved by CTTL.



Fig.60. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz



Fig.61. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL.



Fig.62. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz



Fig.63. Conducted spurious emission: 8DPSK, Channel 78, 10GHz - 26GHz

©Copyright. All rights reserved by CTTL.

A.6. Transmitter Spurious Emission - Radiated

Method of Measurement: See ANSI C63.10-2013-clause 6.4 &6.5 & 6.6

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency (MHz)	Field strength(μV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Set up:

Tabletop devices shall be placed on a non-conducting platform with nominal top surface dimensions 1 m by 1.5 m. For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m

The EUT and transmitting antenna shall be centered on the turntable.

©Copyright. All rights reserved by CTTL.





Test Condition

The EUT shall be tested 1 near top, 1 near middle, and 1 near bottom. Set the unlicensed wireless device to operate in continuous transmit mode. For unlicensed wireless devices unable to be configured for 100% duty cycle even in test mode, configure the system for the maximum duty cycle supported.

When required for unlicensed wireless devices, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the

©Copyright. All rights reserved by CTTL.

nominal rated supply voltage.

Exploratory radiated emissions measurements

Exploratory radiated measurements shall be performed at the measurement distance or at a closer distance than that specified for compliance to determine the emission characteristics of the EUT and, if applicable, the EUT configuration that produces the maximum level of emissions. The frequencies of maximum emission may be determined by manually positioning the antenna close to the EUT, and then moving the antenna over all sides of the EUT while observing a spectral display. It is advantageous to have prior knowledge of the frequencies of emissions, although this may be determined from such a near-field scan. The near-field scan shall only be used to determine the frequency but not the amplitude of the emissions. Where exploratory measurements are not adequate to determine the worst-case operating modes and are used only to identify the frequencies of the highest emissions, additional preliminary tests can be required.

For emissions from the EUT, the maximum level shall be determined by rotating the EUT and its antenna through 0° to 360°. For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored.

Broadband antennas and a spectrum analyzer or a radio-noise meter with a panoramic display are often useful in this type of test. If either antenna height or EUT azimuth are not fully measured during exploratory testing, then complete testing can be required at the OATS or semi-anechoic chamber when the final full spectrum testing is performed.

Final radiated emissions measurements

The final measurements are using the orientation and equipment arrangement of the EUT based on the measurement results found during the preliminary (exploratory) measurements, the EUT arrangement, appropriate modulation, and modes of operation that produce the emissions that have the highest amplitude relative to the limit shall be selected for the final measurement.

For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.

For each mode selected, record the frequency and amplitude of the highest fundamental emission (if applicable), as well as the frequency and amplitude of the six highest spurious emissions relative to the limit. Emissions more than 20 dB below the limit do not need to be reported.

This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

The receiver references:

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

©Copyright. All rights reserved by CTTL.

P_{Mea} is the field strength recorded from the instrument.
The measurement results are obtained as described below:
Result= P_{Mea} + Cable Loss + Antenna Factor
Where:

P_{Mea} field strength recorded from the instrument

Peak Measurement results

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2379.230	60.19	2.9	32.0	25.33	74.0	13.8	H	44
2382.744	60.36	2.9	32.0	25.50	74.0	13.6	H	66
4804.000	44.97	-32.8	34.1	43.62	74.0	29.0	V	110
7206.000	42.74	-30.1	35.7	37.09	74.0	31.3	V	0
9608.000	45.45	-29.8	36.7	38.52	74.0	28.5	H	132
12010.000	46.19	-28.9	38.9	36.23	74.0	27.8	H	88

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2378.600	48.59	-26.4	32.0	42.99	74.0	25.4	H	220
2509.000	48.32	-26.5	32.2	42.58	74.0	25.7	V	88
4882.000	44.10	-32.6	34.2	42.58	74.0	29.9	H	66
7323.000	44.25	-29.6	35.8	38.11	74.0	29.7	H	0
9764.000	46.78	-29.5	36.9	39.39	74.0	27.2	H	44
12205.000	47.21	-28.3	38.9	36.59	74.0	26.8	V	242

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2492.990	60.47	2.9	32.2	25.34	74.0	13.5	H	0
2495.350	61.54	2.9	32.2	26.40	74.0	12.5	V	0
4960.000	43.11	-32.5	34.2	41.46	74.0	30.9	V	22
7440.000	44.85	-30.2	35.8	39.22	74.0	29.2	V	66
9920.000	46.39	-29.5	37.1	38.81	74.0	27.6	V	132
12400.000	47.30	-27.8	39.0	36.12	74.0	26.7	V	274

©Copyright. All rights reserved by CTTL.

π/4 DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2384.522	59.84	2.9	32.0	24.97	74.0	14.2	H	22
2389.478	59.94	2.9	32.0	25.06	74.0	14.1	V	44
4804.000	43.45	-32.8	34.1	42.10	74.0	30.6	H	0
7206.000	43.28	-30.1	35.7	37.63	74.0	30.7	H	0
9608.000	44.09	-29.8	36.7	37.15	74.0	29.9	H	22
12010.000	46.61	-28.9	38.9	36.66	74.0	27.4	H	176

π/4 DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2367.000	48.81	-27.2	32.0	44.00	74.0	25.2	H	132
2496.200	48.60	-25.0	32.2	41.36	74.0	25.4	H	154
4882.000	43.65	-32.6	34.2	42.12	74.0	30.4	V	88
7323.000	43.70	-29.6	35.8	37.56	74.0	30.3	H	110
9764.000	45.60	-29.5	36.9	38.21	74.0	28.4	V	110
12205.000	47.40	-28.3	38.9	36.78	74.0	26.6	V	88

π/4 DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2487.885	60.31	2.9	32.2	25.20	74.0	13.7	H	176
2490.220	60.46	2.9	32.2	25.34	74.0	13.5	H	154
4960.000	43.54	-32.5	34.2	41.90	74.0	30.5	V	22
7440.000	44.06	-30.2	35.8	38.42	74.0	29.9	V	176
9920.000	45.62	-29.5	37.1	38.04	74.0	28.4	H	198
12400.000	50.32	-27.8	39.0	39.14	74.0	23.7	H	0

©Copyright. All rights reserved by CTTL.

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2341.850	59.97	2.8	31.9	25.20	74.0	14.0	H	0
2385.348	60.24	2.9	32.0	25.37	74.0	13.8	H	22
4804.000	42.56	-32.8	34.1	41.21	74.0	31.4	H	352
7206.000	43.88	-30.1	35.7	38.23	74.0	30.1	V	352
9608.000	45.39	-29.8	36.7	38.46	74.0	28.6	V	176
12010.000	47.82	-28.9	38.9	37.86	74.0	26.2	V	176

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2369.600	47.82	-27.0	32.0	42.86	74.0	26.2	H	264
2496.400	48.71	-25.1	32.2	41.60	74.0	25.3	H	286
4882.000	43.87	-32.6	34.2	42.35	74.0	30.1	V	308
7323.000	44.21	-29.6	35.8	38.07	74.0	29.8	H	44
9764.000	45.39	-29.5	36.9	38.00	74.0	28.6	H	66
12205.000	47.32	-28.3	38.9	36.70	74.0	26.7	V	88

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2485.190	60.41	2.9	32.2	25.30	74.0	13.6	H	176
2488.985	60.84	2.9	32.2	25.72	74.0	13.2	H	154
4960.000	43.08	-32.5	34.2	41.44	74.0	30.9	V	22
7440.000	43.90	-30.2	35.8	38.27	74.0	30.1	V	176
9920.000	44.70	-29.5	37.1	37.12	74.0	29.3	H	198
12400.000	48.54	-27.8	39.0	37.37	74.0	25.5	H	0

©Copyright. All rights reserved by CTTL.

Average Measurement results

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2383.400	46.42	2.9	32.0	11.55	54.0	7.6	H	46
2386.200	46.45	2.9	32.0	11.58	54.0	7.5	H	60
4804.000	37.48	-32.8	34.1	36.14	54.0	16.5	H	116
7206.000	33.74	-30.1	35.7	28.10	54.0	20.3	H	8
9608.000	35.69	-29.8	36.7	28.75	54.0	18.3	H	128
12010.000	37.15	-28.9	38.9	27.20	54.0	16.8	H	94

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2389.200	46.40	2.9	32.0	11.51	54.0	7.6	H	226
2494.500	46.67	2.9	32.2	11.54	54.0	7.3	H	92
4881.000	35.99	-32.6	34.2	34.47	54.0	18.0	H	70
7232.000	34.08	-29.8	35.7	28.16	54.0	19.9	H	8
9764.000	35.51	-29.5	36.9	28.12	54.0	18.5	H	48
12205.000	37.44	-28.3	38.9	26.82	54.0	16.6	H	246

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2483.500	49.17	2.9	32.2	14.06	54.0	4.8	H	8
2483.600	48.37	2.9	32.2	13.26	54.0	5.6	H	6
4959.000	33.83	-32.5	34.2	32.18	54.0	20.2	H	25
7440.000	33.51	-30.2	35.8	27.88	54.0	20.5	H	70
9608.000	36.24	-29.8	36.7	29.30	54.0	17.8	H	135
12400.000	38.09	-27.8	39.0	26.91	54.0	15.9	H	270

©Copyright. All rights reserved by CTTL.

π/4 DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2386.600	46.39	2.9	32.0	11.51	54.0	7.6	H	25
2389.800	46.41	2.9	32.0	11.53	54.0	7.6	H	49
4804.000	33.06	-32.8	34.1	31.72	54.0	20.9	H	4
7206.000	33.53	-30.1	35.7	27.88	54.0	20.5	H	6
9608.000	35.44	-29.8	36.7	28.50	54.0	18.6	H	25
12010.000	37.12	-28.9	38.9	27.17	54.0	16.9	H	186

π/4 DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2388.900	46.44	2.9	32.0	11.56	54.0	7.6	H	135
2474.000	46.61	2.9	32.2	11.53	54.0	7.4	H	160
4881.000	32.57	-32.6	34.2	31.05	54.0	21.4	H	92
7323.000	33.97	-29.6	35.8	27.83	54.0	20.0	H	115
9764.000	35.34	-29.5	36.9	27.95	54.0	18.7	H	112
12205.000	37.57	-28.3	38.9	26.95	54.0	16.4	H	85

π/4 DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2483.500	48.17	2.9	32.2	13.07	54.0	5.8	H	170
2484.500	46.79	2.9	32.2	11.68	54.0	7.2	H	150
4959.000	31.82	-32.5	34.2	30.17	54.0	22.2	H	20
7440.000	33.53	-30.2	35.8	27.89	54.0	20.5	H	180
9920.000	35.04	-29.5	37.1	27.46	54.0	19.0	H	202
12400.000	38.04	-27.8	39.0	26.86	54.0	16.0	H	8

©Copyright. All rights reserved by CTTL.

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2381.700	46.38	2.9	32.0	11.52	54.0	7.6	H	5
2388.500	46.44	2.9	32.0	11.56	54.0	7.6	H	25
4804.000	33.02	-32.8	34.1	31.67	54.0	21.0	H	356
7206.000	33.68	-30.1	35.7	28.04	54.0	20.3	H	350
9608.000	35.87	-29.8	36.7	28.94	54.0	18.1	H	185
12010.000	37.28	-28.9	38.9	27.32	54.0	16.7	H	187

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2385.900	46.37	2.9	32.0	11.50	54.0	7.6	H	268
2488.900	46.60	2.9	32.2	11.48	54.0	7.4	H	290
4881.000	32.51	-32.6	34.2	30.98	54.0	21.5	H	312
7323.000	34.11	-29.6	35.8	27.96	54.0	19.9	H	46
9764.000	35.64	-29.5	36.9	28.25	54.0	18.4	H	70
12205.000	37.69	-28.3	38.9	27.07	54.0	16.3	H	92

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Turntable angle (deg)
2483.500	47.52	2.9	32.2	12.42	54.0	6.5	H	170
2484.100	46.64	2.9	32.2	11.53	54.0	7.4	H	150
4960.000	31.70	-32.5	34.2	30.06	54.0	22.3	H	20
7440.000	33.61	-30.2	35.8	27.97	54.0	20.4	H	180
9608.000	36.65	-29.8	36.7	29.72	54.0	17.3	H	202
12400.000	38.06	-27.8	39.0	26.89	54.0	15.9	H	8

Conclusion: Pass

©Copyright. All rights reserved by CTTL.

A.7. Time of Occupancy (Dwell Time)

Method of Measurement: See ANSI C63.10-clause 7.8.4

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = zero span, centered on a hopping channel
- RBW = 1 MHz
- VBW ≥ RBW
- Sweep = as necessary to capture the entire dwell time per hopping channel
- Detector function = peak
- Trace = max hold

Measure a pulse time in time domain at middle frequency and then count the hopping number in 31.6s(which equals with 0.4 multiply 79) of middle frequency ,then multiply the pulse time and hopping number and record them.

Measurement Limit:

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a) (1)(iii)	< 400

Measurement Result:

For GFSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	DH1	Fig.64	0.38	Fig.65	319	121.64	P
	DH3	Fig.66	1.64	Fig.67	114	186.65	P
	DH5	Fig.68	2.88	Fig.69	72	207.75	P

For π/4 DQPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	2DH1	Fig.70	0.39	Fig.71	319	123.48	P
	2DH3	Fig.72	1.63	Fig.73	102	167.19	P
	2DH5	Fig.74	2.88	Fig.75	75	216.54	P

©Copyright. All rights reserved by CTTL.

For 8DPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	3DH1	Fig.76	0.38	Fig.77	320	123.87	P
	3DH3	Fig.78	1.64	Fig.79	104	170.38	P
	3DH5	Fig.80	2.89	Fig.81	55	158.91	P

Conclusion: PASS

Test graphs as below:



Fig.64. Time of occupancy (Dwell Time): Channel 39, Packet DH1

©Copyright. All rights reserved by CTTL.



Fig.65. Number of Transmissions Measurement: Channel 39,Packet DH1



Fig.66. Time of occupancy (Dwell Time): Channel 39, Packet DH3

©Copyright. All rights reserved by CTTL.



Fig.67. Number of Transmissions Measurement: Channel 39,Packet DH3



Fig.68. Time of occupancy (Dwell Time): Channel 39, Packet DH5

©Copyright. All rights reserved by CTTL.



Fig.69. Number of Transmissions Measurement: Channel 39,Packet DH5



Fig.70. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1

©Copyright. All rights reserved by CTTL.



Fig.71. Number of Transmissions Measurement: Channel 39,Packet 2-DH1



Fig.72. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3

©Copyright. All rights reserved by CTTL.



Fig.73. Number of Transmissions Measurement: Channel 39,Packet 2-DH3



Fig.74. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5

©Copyright. All rights reserved by CTTL.



Fig.75. Number of Transmissions Measurement: Channel 39,Packet 2-DH5



Fig.76. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1

©Copyright. All rights reserved by CTTL.



Fig.77. Number of Transmissions Measurement: Channel 39,Packet 3-DH1



Fig.78. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3

©Copyright. All rights reserved by CTTL.



Fig.79. Number of Transmissions Measurement: Channel 39,Packet 3-DH3



Fig.80. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5

©Copyright. All rights reserved by CTTL.



Fig.81. Number of Transmissions Measurement: Channel 39,Packet 3-DH5

©Copyright. All rights reserved by CTTL.

A.8. 20dB Bandwidth

Method of Measurement: See ANSI C63.10-clause 6.9.2

Measurement Procedure - Unwanted Emissions

1. Set RBW = 30kHz.

2. Set VBW = 100 kHz.

3. Set span to 3MHz

4. Detector = peak.

5. Trace Mode = max hold.

6. Sweep = auto couple.

7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(1)	NA *

Use NdB Down function of the SA to measure the 20dB Bandwidth

* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for “carrier frequency separation” test case, in Annex A.8.

Measurement Results:

For GFSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.82	940.50	NA
39	Fig.83	940.50	NA
78	Fig.84	937.50	NA

For π/4 DQPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.85	1291.50	NA
39	Fig.86	1282.50	NA
78	Fig.87	1292.25	NA

For 8DPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.88	1280.25	NA
39	Fig.89	1297.50	NA
78	Fig.90	1280.25	NA

Conclusion: NA

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.82. 20dB Bandwidth: GFSK, Channel 0



Fig.83. 20dB Bandwidth: GFSK, Channel 39

©Copyright. All rights reserved by CTTL.



Fig.84. 20dB Bandwidth: GFSK, Channel 78



Fig.85. 20dB Bandwidth: π/4 DQPSK, Channel 0

©Copyright. All rights reserved by CTTL.



Fig.86. 20dB Bandwidth: π/4 DQPSK, Channel 39



Fig.87. 20dB Bandwidth: π/4 DQPSK, Channel 78

©Copyright. All rights reserved by CTTL.



Fig.88. 20dB Bandwidth: 8DPSK, Channel 0



Fig.89. 20dB Bandwidth: 8DPSK, Channel 39

©Copyright. All rights reserved by CTTL.



Fig.90. 20dB Bandwidth: 8DPSK, Channel 78

©Copyright. All rights reserved by CTTL.

A.9. Carrier Frequency Separation

Method of Measurement: See ANSI C63.10-clause 7.8.2

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = 3MHz
- RBW=300kHz
- VBW=300kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

Search the peak marks of the middle frequency and adjacent channel, then record the separation between them.

＊Comment: This limit should be over 25 kHz or (2/3) * 20dB bandwidth, whichever is greater.

Measurement Limit:

Standard	Limit(kHz)
FCC 47 CFR Part 15.247(a)(1)	over 25 kHz or (2/3) * 20dB bandwidth

Measurement Result:

For GFSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.91	1134.00	P

For π/4 DQPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.92	1051.50	P

For 8DPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.93	1142.25	P

Conclusion: PASS

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.91. Carrier frequency separation measurement: GFSK, Channel 39



Fig.92. Carrier frequency separation measurement: π/4 DQPSK, Channel 39

©Copyright. All rights reserved by CTTL.



Fig.93. Carrier frequency separation measurement: 8DPSK, Channel 39

©Copyright. All rights reserved by CTTL.

A.10. Number of Hopping Channels

Method of Measurement: See ANSI C63.10-clause 7.8.3

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = the frequency band of operation
- RBW = 500kHz
- VBW = 500kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a) (1)(iii)	At least 15 non-overlapping channels

Measurement Result:

For GFSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.94	79	P
40~78	Fig.95		

Forπ/4 DQPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.96	79	P
40~78	Fig.97		

For 8DPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.98	79	P
40~78	Fig.99		

Conclusion: PASS

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.94. Number of hopping frequencies: GFSK, Channel 0 - 39



Fig.95. Number of hopping frequencies: GFSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL.

Fig.96. Number of hopping frequencies: π/4 DQPSK, Channel 0 - 39



Fig.97. Number of hopping frequencies: π/4 DQPSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL.

Fig.98. Number of hopping frequencies: 8DPSK, Channel 0 - 39



Fig.99. Number of hopping frequencies: 8DPSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL.

A.11. AC Powerline Conducted Emission

Method of Measurement: See ANSI C63.10-clause 6.2

Setup:

A stand-alone EUT shall be placed in the center along the back edge of the tabletop. For multiunit tabletop systems, the EUT shall be centered laterally (left to right facing the tabletop) on the tabletop and its rear shall be flush with the rear of the table.

Accessories that are part of an EUT system tested on a tabletop shall be placed in a test arrangement on one or both sides of the host with a 10 cm separation between the nearest points of the cabinets. The rear of the host and accessories shall be flush with the back of the supporting tabletop unless that would not be typical of normal use. If more than two accessories are present, then an equipment test arrangement shall be chosen that maintains 10 cm spacing between cabinets unless the equipment is normally located closer together.



Exploratory ac power-line conducted emission measurements

Exploratory measurements shall be used to identify the frequency of the emission that has the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable positions, and with a typical system equipment configuration and arrangement. For each mode of operation and for each ac power current-carrying conductor, cable manipulation shall be performed within the range of likely configurations. For this measurement or series of measurements, the frequency spectrum of interest shall be monitored looking for the emission that has the highest amplitude relative to the limit. Once that emission is found for each current-carrying conductor of each power cord associated with the EUT (but not the cords associated with non-EUT equipment in the overall system), the one configuration and arrangement and mode of operation that produces the emission closest to the limit over all of the

©Copyright. All rights reserved by CTTL.

measured conductors shall be recorded.

Final ac power-line conducted emission measurements

Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT. If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation. If the EUT is composed of equipment units that have their own separate ac power connections (e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network), then each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be measured separately. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.

Test Condition:

Voltage（V）	**Frequency（Hz）**
120	60

Measurement Result and limit:

EUT ID: EUT1

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Conclusion
0.15 to 0.5	66 to 56	P
0.5 to 5	56	
5 to 30	60	
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.		

Bluetooth (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Conclusion
0.15 to 0.5	56 to 46	P
0.5 to 5	46	
5 to 30	50	
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.		

The measurement is made according to ANSI C63.10

©Copyright. All rights reserved by CTTL.

Conclusion: Pass
Test graphs as below:
raffic (With AE3):



Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.159000	53.1	2000.0	9.000	On	L1	28.7	12.5	65.5
0.303000	43.2	2000.0	9.000	On	L1	19.8	17.0	60.2
2.067000	44.7	2000.0	9.000	On	L1	19.6	11.3	56.0
2.139000	44.7	2000.0	9.000	On	L1	19.6	11.3	56.0
17.524500	41.3	2000.0	9.000	On	L1	19.8	18.7	60.0
17.992500	40.2	2000.0	9.000	On	L1	19.8	19.8	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.181500	40.5	2000.0	9.000	On	L1	23.8	14.0	54.4
0.415500	34.8	2000.0	9.000	On	L1	19.8	12.7	47.5
0.613500	31.2	2000.0	9.000	On	L1	19.8	14.8	46.0
0.915000	29.1	2000.0	9.000	On	L1	19.7	16.9	46.0
2.067000	36.5	2000.0	9.000	On	L1	19.6	9.5	46.0
2.125500	36.2	2000.0	9.000	On	L1	19.6	9.8	46.0

©Copyright. All rights reserved by CTTL.

Idle (With AE3):



Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	48.7	2000.0	9.000	On	N	30.6	17.3	66.0
0.406500	41.0	2000.0	9.000	On	L1	19.8	16.8	57.7
0.582000	34.5	2000.0	9.000	On	L1	19.8	21.5	56.0
2.031000	37.9	2000.0	9.000	On	L1	19.6	18.1	56.0
2.125500	37.7	2000.0	9.000	On	L1	19.6	18.3	56.0
4.596000	35.2	2000.0	9.000	On	L1	19.6	20.8	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.181500	32.9	2000.0	9.000	On	L1	23.8	21.5	54.4
0.406500	34.8	2000.0	9.000	On	L1	19.8	13.0	47.7
0.586500	28.4	2000.0	9.000	On	L1	19.8	17.6	46.0
1.194000	28.7	2000.0	9.000	On	L1	19.7	17.3	46.0
2.031000	26.6	2000.0	9.000	On	L1	19.6	19.4	46.0
2.125500	27.2	2000.0	9.000	On	L1	19.6	18.8	46.0

©Copyright. All rights reserved by CTTL.

Traffic (With AE4):



Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	56.8	2000.0	9.000	On	L1	30.7	9.2	66.0
0.267000	39.5	2000.0	9.000	On	L1	19.8	21.7	61.2
0.451500	45.8	2000.0	9.000	On	L1	19.8	11.1	56.8
2.067000	34.6	2000.0	9.000	On	L1	19.6	21.4	56.0
4.483500	35.9	2000.0	9.000	On	L1	19.6	20.1	56.0
17.542500	38.1	2000.0	9.000	On	L1	19.8	21.9	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.163500	40.4	2000.0	9.000	On	L1	27.7	14.9	55.3
0.424500	32.6	2000.0	9.000	On	L1	19.8	14.8	47.4
0.451500	38.1	2000.0	9.000	On	L1	19.8	8.8	46.8
1.194000	27.6	2000.0	9.000	On	L1	19.7	18.4	46.0
2.067000	26.7	2000.0	9.000	On	L1	19.6	19.3	46.0
4.425000	27.7	2000.0	9.000	On	L1	19.6	18.3	46.0

©Copyright. All rights reserved by CTTL.

ANNEX B: Accreditation Certificate

United States Department of Commerce
National Institute of Standards and Technology

NVLAP®

Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 600118-0

Telecommunication Technology Labs, CAICT
Beijing
China

is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:

Electromagnetic Compatibility & Telecommunications

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).

2019-09-26 through 2020-09-30
Effective Dates

For the National Voluntary Laboratory Accreditation Program

*****END OF REPORT*****

©Copyright. All rights reserved by CTTL.