

Fig.52. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz



Fig.53. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz

©Copyright. All rights reserved by CTTL.



Fig.54. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz



Fig.55. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL.



Fig.56. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz



Fig.57. Conducted spurious emission: 8DPSK, Channel 78, 10GHz - 26GHz

©Copyright. All rights reserved by CTTL.

B.5. Radiated Unwanted Emission

Limits

Measurement Limit

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band

Frequency (MHz)	Field strength(μV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength (uV/m)	Field strength (dBuV/m)	Measurement distance (m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Note: When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor.

Test setup



Figure B.5.1. Test Site Diagram (9kHz-30MHz)

©Copyright. All rights reserved by CTTL.



Figure B.5.2. Test Site Diagram (30MHz-1GHz)



Figure B.5.3. Test Site Diagram (1GHz-40GHz)

Test Procedures

Radiated unwanted emissions from the EUT were measured according to ANSI C63.10.

Test setting

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100kHz/300kHz	5
1000-3000	1MHz/3MHz	15
3000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

Sample Calculation

A "reference path loss" is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result=P_{Mea}+$A_{Rpl=}$ P_{Mea}+Cable Loss+Antenna Factor

©Copyright. All rights reserved by CTTL.

Test note

1. Investigation has been done on all modes and modulations/data rates. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.
2. Spurious emissions for all channels were investigated and almost the same below 1GHz. According to FCC 47 CFR §15.31, emission levels are not report much lower than the limit by over 20dB
3. Measurement frequencies were performed from 9 kHz to the 10th harmonic of highest fundamental frequency or 40GHz, whichever is lower.
4. The measurements were performed separately in chain1, chain2 and only the worst cases are shown in this section.

Test Result

©Copyright. All rights reserved by CTTL.

Peak Measurement results

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2388.216	60.29	4.61	27.48	28.21	74.00	13.71	H
2389.021	60.48	4.61	27.48	28.39	74.00	13.52	V
4804.000	41.13	-35.05	33.98	42.20	74.00	32.87	H
7205.500	42.75	-33.04	35.52	40.27	74.00	31.25	V
9608.000	43.98	-32.21	36.32	39.87	74.00	30.03	V
12009.000	46.39	-30.19	38.80	37.78	74.00	27.61	V

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2356.000	45.25	-35.86	31.27	49.83	74.00	28.75	H
2510.200	46.18	-35.79	32.44	49.52	74.00	27.83	V
4881.500	40.57	-34.38	33.83	41.12	74.00	33.44	V
7324.000	41.79	-33.02	35.40	39.41	74.00	32.21	H
9764.000	43.02	-31.87	36.57	38.33	74.00	30.98	H
12205.000	46.01	-29.39	38.79	36.60	74.00	28.00	H

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2484.591	61.66	4.65	27.80	29.21	74.00	12.34	V
2484.638	61.46	4.65	27.80	29.01	74.00	12.54	H
4960.500	40.97	-34.41	33.80	41.59	74.00	33.03	V
7442.000	41.34	-32.80	35.42	38.72	74.00	32.66	V
9918.500	43.67	-32.04	36.84	38.88	74.00	30.33	H
12398.000	46.74	-29.43	38.60	37.56	74.00	27.27	H

©Copyright. All rights reserved by CTTL.

π/4 DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2376.448	60.85	4.58	27.45	28.82	74.00	13.15	V
2387.656	60.94	4.61	27.48	28.86	74.00	13.06	V
4804.500	40.97	-35.05	33.97	42.05	74.00	33.03	H
7206.000	42.08	-33.04	35.52	39.59	74.00	31.92	V
9608.500	44.22	-32.21	36.32	40.11	74.00	29.78	H
12008.500	45.99	-30.20	38.80	37.38	74.00	28.01	H

π/4 DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2347.800	44.35	-35.97	31.21	49.11	74.00	29.65	H
2508.600	46.56	-35.71	32.43	49.84	74.00	27.44	H
4882.500	40.94	-34.37	33.83	41.47	74.00	33.06	V
7323.500	41.99	-33.02	35.40	39.61	74.00	32.01	H
9764.500	43.90	-31.88	36.57	39.20	74.00	30.10	V
12206.000	45.89	-29.39	38.79	36.49	74.00	28.11	H

π/4 DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2484.147	61.58	4.65	27.80	29.13	74.00	12.42	V
2485.319	61.45	4.65	27.80	29.00	74.00	12.55	V
4959.500	40.97	-34.43	33.80	41.60	74.00	33.03	V
7441.000	42.26	-32.80	35.42	39.64	74.00	31.74	H
9920.000	44.89	-32.04	36.84	40.09	74.00	29.11	V
12400.000	45.84	-29.42	38.60	36.66	74.00	28.16	H

©Copyright. All rights reserved by CTTL.

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2387.560	60.96	4.61	27.48	28.88	74.00	13.04	H
2388.129	60.93	4.61	27.48	28.85	74.00	13.07	V
4806.000	40.36	-35.05	33.96	41.44	74.00	33.64	H
7205.500	42.12	-33.04	35.52	39.64	74.00	31.88	V
9608.000	43.69	-32.21	36.32	39.58	74.00	30.31	H
12009.500	45.66	-30.19	38.80	37.05	74.00	28.35	H

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2355.400	44.69	-35.87	31.27	49.29	74.00	29.31	V
2516.200	45.93	-36.06	32.47	49.53	74.00	28.07	V
4881.500	41.06	-34.38	33.83	41.61	74.00	32.94	H
7323.500	42.42	-33.02	35.40	40.05	74.00	31.58	H
9764.000	43.58	-31.87	36.57	38.88	74.00	30.43	H
12206.000	46.60	-29.39	38.79	37.20	74.00	27.40	H

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2484.809	61.73	4.65	27.80	29.28	74.00	12.27	H
2486.794	62.07	4.64	27.80	29.62	74.00	11.93	V
4959.500	40.76	-34.43	33.80	41.40	74.00	33.24	H
7440.500	42.81	-32.79	35.42	40.18	74.00	31.19	H
9920.500	43.50	-32.04	36.84	38.70	74.00	30.50	H
12400.500	46.08	-29.42	38.60	36.89	74.00	27.92	H

©Copyright. All rights reserved by CTTL.

Average Measurement results

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2388.975	46.27	4.61	27.48	14.18	54.00	7.73	V
2389.650	46.31	4.61	27.48	14.21	54.00	7.70	V
4804.000	27.82	-35.05	33.98	28.89	54.00	26.18	H
7206.000	29.85	-33.04	35.52	27.37	54.00	24.15	V
9608.000	30.88	-32.21	36.32	26.78	54.00	23.12	V
12010.000	33.34	-30.19	38.80	24.73	54.00	20.66	H

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2382.450	46.19	4.60	27.47	14.13	54.00	7.81	V
2493.075	47.00	4.63	27.80	14.57	54.00	7.00	V
4882.000	28.38	-34.37	33.83	28.93	54.00	25.62	V
7323.000	29.80	-33.03	35.40	27.42	54.00	24.20	V
9764.000	31.19	-31.87	36.57	26.50	54.00	22.81	H
12205.000	33.96	-29.39	38.79	24.55	54.00	20.04	H

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2483.738	47.29	4.65	27.80	14.83	54.00	6.72	V
2484.150	47.31	4.65	27.80	14.86	54.00	6.69	V
4960.000	27.88	-34.42	33.80	28.51	54.00	26.12	V
7440.000	29.29	-32.79	35.42	26.66	54.00	24.71	V
9920.000	31.05	-32.04	36.84	26.24	54.00	22.96	V
12400.000	33.67	-29.42	38.60	24.49	54.00	20.33	H

©Copyright. All rights reserved by CTTL.

π/4 DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2386.594	46.16	4.61	27.47	14.08	54.00	7.84	V
2389.013	46.23	4.61	27.48	14.14	54.00	7.77	V
4804.000	28.19	-35.05	33.98	29.26	54.00	25.82	V
7206.000	30.24	-33.04	35.52	27.76	54.00	23.76	V
9608.000	31.29	-32.21	36.32	27.18	54.00	22.71	V
12010.000	33.81	-30.19	38.80	25.19	54.00	20.20	H

π/4 DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2387.850	46.19	4.61	27.48	14.11	54.00	7.81	V
2490.488	47.07	4.63	27.80	14.64	54.00	6.93	V
4882.000	28.57	-34.37	33.83	29.11	54.00	25.43	V
7323.000	29.88	-33.03	35.40	27.51	54.00	24.12	V
9764.000	31.18	-31.87	36.57	26.48	54.00	22.82	H
12205.000	34.10	-29.39	38.79	24.69	54.00	19.91	H

π/4 DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2483.606	47.03	4.65	27.80	14.58	54.00	6.97	V
2483.925	47.03	4.65	27.80	14.57	54.00	6.97	V
4960.000	28.22	-34.42	33.80	28.84	54.00	25.78	H
7440.000	29.44	-32.79	35.42	26.82	54.00	24.56	V
9920.000	31.26	-32.04	36.84	26.46	54.00	22.74	V
12400.000	33.88	-29.42	38.60	24.70	54.00	20.12	H

©Copyright. All rights reserved by CTTL.

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2385.675	46.08	4.60	27.47	14.01	54.00	7.92	V
2388.319	46.13	4.61	27.48	14.04	54.00	7.88	V
4804.000	23.35	-35.05	33.98	24.42	54.00	30.65	V
7206.000	30.43	-33.04	35.52	27.94	54.00	23.57	H
9608.000	31.53	-32.21	36.32	27.42	54.00	22.47	H
12010.000	33.99	-30.19	38.80	25.38	54.00	20.01	H

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2385.863	46.15	4.60	27.47	14.08	54.00	7.85	V
2487.206	47.20	4.64	27.80	14.75	54.00	6.80	V
4882.000	28.84	-34.37	33.83	29.38	54.00	25.16	V
7323.000	30.18	-33.03	35.40	27.80	54.00	23.83	V
9764.000	31.65	-31.87	36.57	26.95	54.00	22.35	V
12205.000	34.56	-29.39	38.79	25.15	54.00	19.44	V

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
2483.606	47.18	4.65	27.80	14.73	54.00	6.82	V
2484.263	47.10	4.65	27.80	14.65	54.00	6.90	V
4960.000	28.22	-34.42	33.80	28.84	54.00	25.78	V
7440.000	29.42	-32.79	35.42	26.79	54.00	24.58	H
9920.000	31.11	-32.04	36.84	26.30	54.00	22.89	V
12400.000	33.90	-29.42	38.60	24.72	54.00	20.10	V

Conclusion: Pass

Note: the spurious emission above 18G is noise only and did not show on the report.

©Copyright. All rights reserved by CTTL.

Band edge compliance

Mode	Channel	Frequency Range	Test Results	Conclusion
GFSK	0	2.31GHz ~2.43GHz	Fig.58	P
	78	2.45GHz ~2.5GHz	Fig.59	P

Mode	Channel	Frequency Range	Test Results	Conclusion
π/4 DQPSK	0	2.31GHz ~2.43GHz	Fig.60	P
	78	2.45GHz ~2.5GHz	Fig.61	P

Mode	Channel	Frequency Range	Test Results	Conclusion
8DPSK	0	2.31GHz ~2.43GHz	Fig.62	P
	78	2.45GHz ~2.5GHz	Fig.63	P

Conclusion: PASS

Test graphs as below



Fig.58. Frequency Band Edges: GFSK, Channel 0, Hopping Off, 2.31 GHz – 2.45GHz

©Copyright. All rights reserved by CTTL.



Fig.59. Frequency Band Edges: GFSK, Channel 78, Hopping Off, ch11, 2.45 GHz - 2.50GHz



Fig.60. Frequency Band Edges: π/4 DQPSK, Channel 0, Hopping Off, 2.31 GHz - 2.45GHz

©Copyright. All rights reserved by CTTL.



Fig.61. Frequency Band Edges: π/4 DQPSK, Channel 78, Hopping Off, 2.45 GHz - 2.50GHz



Fig.62. Frequency Band Edges: 8DPSK, Channel 0, 2.31 GHz - 2.45GHz

©Copyright. All rights reserved by CTTL.



Fig.63. Frequency Band Edges: 8DPSK, Channel 78, 2.45 GHz - 2.50GHz

©Copyright. All rights reserved by CTTL.

B.6. Time of Occupancy (Dwell Time)

Method of Measurement: See ANSI C63.10-clause 7.8.4

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = zero span, centered on a hopping channel
- RBW = 1 MHz
- VBW ≥ RBW
- Sweep = as necessary to capture the entire dwell time per hopping channel
- Detector function = peak
- Trace = max hold

Measure a pulse time in time domain at middle frequency and then count the hopping number in 31.6s(which equals with 0.4 multiply 79) of middle frequency ,then multiply the pulse time and hopping number and record them.

Measurement Limit:

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a) (1)(iii)	< 400

Measurement Result:

For GFSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	DH1	Fig.64	0.38	Fig.65	318	120.84	P
	DH3	Fig.66	1.64	Fig.67	116	190.24	P
	DH5	Fig.68	2.88	Fig.69	58	167.04	P

For π/4 DQPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	2DH1	Fig.70	0.39	Fig.71	321	125.19	P
	2DH3	Fig.72	1.64	Fig.73	93	152.52	P
	2DH5	Fig.74	2.89	Fig.75	60	173.4	P

©Copyright. All rights reserved by CTTL.

For 8DPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	3DH1	Fig.76	0.39	Fig.77	320	124.8	P
	3DH3	Fig.78	1.64	Fig.79	94	154.16	P
	3DH5	Fig.80	2.89	Fig.81	71	205.19	P

Conclusion: PASS

Test graphs as below:



Fig.64. Time of occupancy (Dwell Time): Channel 39, Packet DH1

©Copyright. All rights reserved by CTTL.



Fig.65. Number of Transmissions Measurement: Channel 39,Packet DH1



Fig.66. Time of occupancy (Dwell Time): Channel 39, Packet DH3

©Copyright. All rights reserved by CTTL.



Fig.67. Number of Transmissions Measurement: Channel 39,Packet DH3



Fig.68. Time of occupancy (Dwell Time): Channel 39, Packet DH5

©Copyright. All rights reserved by CTTL.



Fig.69. Number of Transmissions Measurement: Channel 39,Packet DH5



Fig.70. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1

©Copyright. All rights reserved by CTTL.



Fig.71. Number of Transmissions Measurement: Channel 39,Packet 2-DH1



Fig.72. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3

©Copyright. All rights reserved by CTTL.



Fig.73. Number of Transmissions Measurement: Channel 39,Packet 2-DH3



Fig.74. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5

©Copyright. All rights reserved by CTTL.



Fig.75. Number of Transmissions Measurement: Channel 39,Packet 2-DH5



Fig.76. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1

©Copyright. All rights reserved by CTTL.



Fig.77. Number of Transmissions Measurement: Channel 39,Packet 3-DH1



Fig.78. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3

©Copyright. All rights reserved by CTTL.



Fig.79. Number of Transmissions Measurement: Channel 39,Packet 3-DH3



Fig.80. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5

©Copyright. All rights reserved by CTTL.



Fig.81. Number of Transmissions Measurement: Channel 39,Packet 3-DH5

©Copyright. All rights reserved by CTTL.

B.7. 20dB Bandwidth

Method of Measurement: See ANSI C63.10-clause 6.9.2

Measurement Procedure - Unwanted Emissions

1. Set RBW = 30kHz.

2. Set VBW = 100 kHz.

3. Set span to 3MHz

4. Detector = peak.

5. Trace Mode = max hold.

6. Sweep = auto couple.

7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(1)	NA *

Use NdB Down function of the SA to measure the 20dB Bandwidth

* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for “carrier frequency separation” test case, in Annex A.8.

Measurement Results:

For GFSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.82	880.50	NA
39	Fig.83	889.50	NA
78	Fig.84	879.75	NA

For π/4 DQPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.85	1286.25	NA
39	Fig.86	1317.00	NA
78	Fig.87	1284.75	NA

For 8DPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.88	1299.75	NA
39	Fig.89	1298.25	NA
78	Fig.90	1281.75	NA

Conclusion: NA

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.82. 20dB Bandwidth: GFSK, Channel 0



Fig.83. 20dB Bandwidth: GFSK, Channel 39

©Copyright. All rights reserved by CTTL.



Fig.84. 20dB Bandwidth: GFSK, Channel 78



Fig.85. 20dB Bandwidth: π/4 DQPSK, Channel 0

©Copyright. All rights reserved by CTTL.



Fig.86. 20dB Bandwidth: π/4 DQPSK, Channel 39



Fig.87. 20dB Bandwidth: π/4 DQPSK, Channel 78

©Copyright. All rights reserved by CTTL.



Fig.88. 20dB Bandwidth: 8DPSK, Channel 0



Fig.89. 20dB Bandwidth: 8DPSK, Channel 39

©Copyright. All rights reserved by CTTL.



Fig.90. 20dB Bandwidth: 8DPSK, Channel 78

©Copyright. All rights reserved by CTTL.

B.8. Carrier Frequency Separation

Method of Measurement: See ANSI C63.10-clause 7.8.2

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = 3MHz
- RBW=300kHz
- VBW=300kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

Search the peak marks of the middle frequency and adjacent channel, then record the separation between them.

* Comment: This limit should be over 25 kHz or (2/3) * 20dB bandwidth, whichever is greater.

Measurement Limit:

Standard	Limit(kHz)
FCC 47 CFR Part 15.247(a)(1)	over 25 kHz or (2/3) * 20dB bandwidth

Measurement Result:

For GFSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.91	1012.50	P

For π/4 DQPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.92	1165.50	P

For 8DPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.93	1002.00	P

Conclusion: PASS

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.91. Carrier frequency separation measurement: GFSK, Channel 39



Fig.92. Carrier frequency separation measurement: π/4 DQPSK, Channel 39

©Copyright. All rights reserved by CTTL.



Fig.93. Carrier frequency separation measurement: 8DPSK, Channel 39

©Copyright. All rights reserved by CTTL.

B.9. Number of Hopping Channels

Method of Measurement: See ANSI C63.10-clause 7.8.3

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = the frequency band of operation
- RBW = 500kHz
- VBW = 500kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a) (1)(iii)	At least 15 non-overlapping channels

Measurement Result:

For GFSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.94	79	P
40~78	Fig.95		

Forπ/4 DQPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.96	79	P
40~78	Fig.97		

For 8DPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.98	79	P
40~78	Fig.99		

Conclusion: PASS

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.94. Number of hopping frequencies: GFSK, Channel 0 - 39



Fig.95. Number of hopping frequencies: GFSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL.



Fig.96. Number of hopping frequencies: π/4 DQPSK, Channel 0 - 39



Fig.97. Number of hopping frequencies: π/4 DQPSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL.



Fig.98. Number of hopping frequencies: 8DPSK, Channel 0 - 39



Fig.99. Number of hopping frequencies: 8DPSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL.

B.10. AC Powerline Conducted Emission

Summary

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section

Method of Measurement:

See Clause 6.2 of ANSI C63.10 specifically.

See Clause 4 and Clause 5 of ANSI C63.10 generally.

The conducted emissions from the AC port of the EUT are measured in a shielding room. The EUT is connected to a Line Impedance Stabilization Network (LISN). An overview sweep with peak detection was performed. The measurements were performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver: Quasi-Peak / Average Detector.

The measurement bandwidth is:

Frequency of Emission (MHz)	RBW/IF bandwidth
0.15-30	9kHz

Test Condition:

Voltage（V）	Frequency（Hz）
120	60

Test setup



©Copyright. All rights reserved by CTTL.

Measurement Result and limit:

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	66 to 56	Fig.B.10.1	Fig. B.10.2	**P**
0.5 to 5	56			
5 to 30	60			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

Bluetooth (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	56 to 46	Fig.B.10.1	Fig. B.10.2	**P**
0.5 to 5	46			
5 to 30	50			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

Conclusion: Pass

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.B.10.1 AC Powerline Conducted Emission- bluetooth

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	53.9	2000.0	9.000	Off	L1	19.7	12.1	66.0
0.195000	53.7	2000.0	9.000	Off	L1	19.7	10.1	63.8
0.213000	41.5	2000.0	9.000	Off	N	19.7	21.6	63.1
0.240000	37.6	2000.0	9.000	Off	N	19.6	24.5	62.1
0.249000	47.1	2000.0	9.000	Off	L1	19.7	14.7	61.8
0.289500	43.1	2000.0	9.000	Off	L1	19.7	17.5	60.5

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.154500	43.0	2000.0	9.000	Off	N	19.7	12.7	55.8
0.163500	36.7	2000.0	9.000	Off	N	19.7	18.6	55.3
0.199500	31.2	2000.0	9.000	Off	L1	19.7	22.4	53.6
0.240000	31.1	2000.0	9.000	Off	N	19.6	21.0	52.1
0.249000	35.0	2000.0	9.000	Off	L1	19.7	16.8	51.8
0.294000	31.9	2000.0	9.000	Off	L1	19.6	18.5	50.4

©Copyright. All rights reserved by CTTL.



Fig.B.10.2 AC Powerline Conducted Emission-Idle

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.154500	43.4	2000.0	9.000	Off	L1	19.7	22.4	65.8
0.163500	47.6	2000.0	9.000	Off	L1	19.7	17.6	65.3
0.172500	47.4	2000.0	9.000	Off	L1	19.7	17.5	64.8
0.181500	48.0	2000.0	9.000	Off	L1	19.7	16.4	64.4
0.190500	48.7	2000.0	9.000	Off	L1	19.7	15.3	64.0
0.244500	37.2	2000.0	9.000	Off	L1	19.7	24.7	61.9

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.154500	35.1	2000.0	9.000	Off	N	19.7	20.6	55.8
0.163500	28.0	2000.0	9.000	Off	L1	19.7	27.2	55.3
0.190500	33.3	2000.0	9.000	Off	N	19.7	20.7	54.0
0.285000	20.5	2000.0	9.000	Off	N	19.6	30.1	50.7
0.294000	32.0	2000.0	9.000	Off	N	19.6	18.4	50.4
3.871500	25.1	2000.0	9.000	Off	L1	19.7	20.9	46.0

©Copyright. All rights reserved by CTTL.

B.11. Antenna Requirement

The antenna of the device is permanently attached. There are no provisions for connection to an external antenna.
The unit complies with the requirement of FCC Part 15.203.

©Copyright. All rights reserved by CTTL.

ANNEX C: Accreditation Certificate

Accredited Laboratory

A2LA has accredited

TELECOMMUNICATION TECHNOLOGY LABS, CAICT

Beijing, People's Republic of China

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (*refer to joint ISO-ILAC-IAF Communiqué dated April 2017*).

Presented this 26th day of June 2023.

Mr. Trace McInturff, Vice President, Accreditation Services
For the Accreditation Council
Certificate Number 7049.01
Valid to July 31, 2024

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

*****END OF REPORT*****

©Copyright. All rights reserved by CTTL.