FCC PART 15C
TEST REPORT

No. I23Z70158-IOT05

for

Samsung Electronics Co., Ltd.

Multi-band GSM/WCDMA/LTE/5GNR Tablet with Bluetooth, WLAN

Model Name: SM-X216B

FCC ID: ZCASMX216B

with

Hardware Version: REV1.0

Software Version: X216B.001

Issued Date: 2023-9-8

Note:

The test results in this test report relate only to the devices specified in this report.This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504

Email:cttl_terminals@caict.ac.cn, website: www.chinattl.com

©Copyright. All rights reserved by CTTL.

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I23Z70158-IOT05	Rev.0	1st edition	2023-8-22
I23Z70158-IOT05	Rev.1	Add test plot for duty cycle in B.12 and power measurement in B.2.	2023-9-8

Note: the latest revision of the test report supersedes all previous version.

©Copyright. All rights reserved by CTTL.

CONTENTS

1. TEST LABORATORY 5

1.1. INTRODUCTION &ACCREDITATION 5
1.2. TESTING LOCATION 5
1.3. TESTING ENVIRONMENT 6
1.4. PROJECT DATA 6
1.5. SIGNATURE 6

2. CLIENT INFORMATION 7

2.1. APPLICANT INFORMATION 7
2.2. MANUFACTURER INFORMATION 7

3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) 8

3.1. ABOUT EUT 8
3.2. INTERNAL IDENTIFICATION OF EUT 8
3.3. INTERNAL IDENTIFICATION OF AE 8
3.4. NORMAL ACCESSORY SETTING 8
3.5. GENERAL DESCRIPTION 8

4. REFERENCE DOCUMENTS 9

4.1. DOCUMENTS SUPPLIED BY APPLICANT 9
4.2. REFERENCE DOCUMENTS FOR TESTING 9

5. TEST RESULTS 10

5.1. SUMMARY OF TEST RESULTS 10
5.2. STATEMENTS 10

6. TEST FACILITIES UTILIZED 11

7. MEASUREMENT UNCERTAINTY 12

7.1. PEAK OUTPUT POWER - CONDUCTED 12
7.2. FREQUENCY BAND EDGES - CONDUCTED 12
7.3. FREQUENCY BAND EDGES - RADIATED 12
7.4. TRANSMITTER SPURIOUS EMISSION - CONDUCTED 12
7.5. TRANSMITTER SPURIOUS EMISSION - RADIATED 12
7.6. TIME OF OCCUPANCY (DWELL TIME) 12
7.7. 20DB BANDWIDTH 13
7.8. CARRIER FREQUENCY SEPARATION 13
7.9. AC POWERLINE CONDUCTED EMISSION 13

ANNEX A: EUT PARAMETERS 14

ANNEX B: DETAILED TEST RESULTS 15

B.1. MEASUREMENT METHOD 15
B.2. PEAK OUTPUT POWER 16

©Copyright. All rights reserved by CTTL.

B.3. FREQUENCY BAND EDGES – CONDUCTED 22
B.4. FREQUENCY BAND EDGES –RADIATED 29
B.5. TRANSMITTER SPURIOUS EMISSION - CONDUCTED 33
B.6. TRANSMITTER SPURIOUS EMISSION - RADIATED 58
B.7. TIME OF OCCUPANCY (DWELL TIME) 65
B.8. 20DB BANDWIDTH 76
B.9. CARRIER FREQUENCY SEPARATION 82
B.10. NUMBER OF HOPPING CHANNELS 85
B.11. AC POWERLINE CONDUCTED EMISSION 89
B.12. DUTY CYCLE 93
B.13. ANTENNA REQUIREMENT 95

ANNEX C: ACCREDITATION CERTIFICATE 96

©Copyright. All rights reserved by CTTL.

1. Test Laboratory

1.1. Introduction &Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under American Association for Laboratory Accreditation (A2LA) with lab code 7049.01, and is also an FCC accredited test laboratory (CN1349), and ISED accredited test laboratory
(CAB identifier:CN0066). The detail accreditation scope can be found on A2LA website.

1.2. Testing Location

Conducted testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China100191

Radiated testing Location:

CTTL(BDA)

Address: No. 18A, Kangding Street, Beijing Economic-Technology Development Area, Beijing, 100176, P.R. China

CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China100191

©Copyright. All rights reserved by CTTL.

1.3. Testing Environment

Normal Temperature: 20-27℃

Relative Humidity: 20-50%

1.4. Project data

Testing Start Date: 2023-6-12

Testing End Date: 2023-9-7

1.5. Signature



Wu Le

(Prepared this test report)

Sun Zhenyu

(Reviewed this test report)

Hu Xiaoyu

(Approved this test report)

©Copyright. All rights reserved by CTTL.

2. Client Information

2.1. Applicant Information

Company Name:	Samsung Electronics Co., Ltd.
Address /Post:	19 Chapin Rd.,Building D Pine Brook, NJ 07058
Contact Person:	Jenni Chun
Contact Email:	j1.chun@samsung.com
Telephone:	+1-201-937-4203

2.2. Manufacturer Information

Company Name:	Samsung Electronics Co., Ltd.
Address /Post:	Samsung R5, Maetan dong 129, Samsung ro Youngtong gu, Suwon city 443 742, Korea
Contact Person:	조성훈 (Sunghoon Cho)
Contact Email:	ggobi.cho@samsung.com
Telephone:	+82-10-2722-4159
Fax:	/

©Copyright. All rights reserved by CTTL.

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Multi-band GSM/WCDMA/LTE/5GNR Tablet with Bluetooth, WLAN
Model Name	SM-X216B
FCC ID	ZCASMX216B
Frequency Band	ISM 2400MHz~2483.5MHz
Type of Modulation	GFSK/π/4 DQPSK/8DPSK
Number of Channels	79
Power Supply	3.85V DC by Battery
Antenna gain	-1.36dBi

3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
UT25a	I23Z70158UT25a	REV1.0	X216B.001	2023-7-14
UT15a	I23Z70158UT15a	REV1.0	X216B.001	2023-6-12

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

AE ID*	Name	Model	Manufacturer
AE1	Battery	WT-S-W11	SCUD (Fujian) Electronics Co., Ltd.
AE2	Adapter	EP-T1510	DONGGUAN DONGWON ELECTRONICS CO.,LTD.
AE3-1	Date Cable1 C-C	EP-DN980BWE	Guangxi Broad Telecommunication Co.,Ltd.
AE3-2	Date Cable2 C-C	EP-DN980BWE	RFTECH Co., Ltd.
AE3-3	Date Cable3 C-C	EP-DN980BWE	CRESYN HANOI Co., Ltd
AE5	Headset	ESH61ASFWE	/

*AE ID: is used to identify the test sample in the lab internally.
*AE2 and A5 are not the AE for EUT, provided by the client for relevant tests.

3.4. Normal Accessory setting

Fully charged battery should be used during the test.

3.5. General Description

The Equipment Under Test (EUT) is a model of Multi-band GSM/WCDMA/LTE/5GNR Tablet with Bluetooth, WLAN with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfill the test. Samples undergoing test were selected by the Client.

©Copyright. All rights reserved by CTTL.

4. Reference Documents

4.1. Documents supplied by applicant

EUT parameters, referring to Annex A for detailed information, is supplied by the client or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz.	2021
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	June,2013

©Copyright. All rights reserved by CTTL.

5. Test Results

5.1. Summary of Test Results

Abbreviations used in this clause:

P Pass, The EUT complies with the essential requirements in the standard.

F Fail, The EUT does not comply with the essential requirements in the standard

NA Not Applicable, The test was not applicable

NP Not Performed, The test was not performed by CTTL

SUMMARY OF MEASUREMENT RESULTS	Sub-clause	Verdict
Peak Output Power	15.247 (b)(1)	**P**
Frequency Band Edges- Conducted	15.247 (d)	**P**
Frequency Band Edges- Radiated	15.247, 15.205, 15.209	**P**
Transmitter Spurious Emission - Conducted	15.247 (d)	**P**
Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	**P**
Time of Occupancy (Dwell Time)	15.247 (a) (1)(iii)	**P**
20dB Bandwidth	15.247 (a)(1)	**NA**
Carrier Frequency Separation	15.247 (a)(1)	**P**
Number of hopping channels	15.247 (a)(iii)	**P**
AC Powerline Conducted Emission	15.107, 15.207	**P**
Duty cycle	/	**NA**
Antenna Requirement	15.203	**P**

Please refer to **ANNEX A** for detail.

The measurement is made according to ANSI C63.10.

5.2. Statements

CTTL has evaluated the test cases requested by the applicant /manufacturer as listed in section 5.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.2

©Copyright. All rights reserved by CTTL.

6. Test Facilities Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ26	100024	R&S	1 year	2024-03-09
2	Bluetooth Tester	CBT	100315	R&S	1 year	2024-03-08
6	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100376	R&S	1 year	2023-09-22
2	Test Receiver	FSV40	101047	R&S	1 year	2024-06-25
3	Test Receiver	ESW44	103144	R&S	1 year	2023-10-25
4	Loop Antenna	HFH2-Z2	829324/007	R&S	1 year	2023-12-22
5	EMI Antenna	VULB9163	01177	Schwarzbeck	1 year	2023-09-03
6	EMI Antenna	3117	00119021	ETS-Lindgren	1 year	2024-06-24
7	EMI Antenna	LB-180400-25-C-KF	2110084000006	A-INFO	1 year	2024-03-02
8	Universal Radio Communication Tester	CMW500	159408	R&S	1 year	2024-03-26

Note:

The EMI Antenna which series number is 01177 was before the CAL. DUE DATE when used.

AC Power Line Conducted Emission

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	LISN	ENV216	101459	R&S	1 year	2024-02-29
2	Test Receiver	ESCI	100766	R&S	1 year	2024-03-30
3	Universal Radio Communication Tester	CMW500	159408	R&S	1 year	2024-03-26

©Copyright. All rights reserved by CTTL.

7. Measurement Uncertainty

7.1. Peak Output Power - Conducted

Measurement Uncertainty:

Measurement Uncertainty (k=2)	0.66dB

7.2. Frequency Band Edges - Conducted

Measurement Uncertainty:

Measurement Uncertainty (k=2)	0.66dB

7.3. Frequency Band Edges - Radiated

Measurement Uncertainty:

Measurement Uncertainty (k=2)	/

7.4. Transmitter Spurious Emission - Conducted

Measurement Uncertainty:

Frequency Range	Uncertainty (k=2)
30 MHz ~ 8 GHz	1.22dB
8 GHz ~ 12.75 GHz	1.51dB
12.7GHz ~ 26 GHz	1.51dB

7.5. Transmitter Spurious Emission - Radiated

Measurement Uncertainty:

Frequency Range	Uncertainty(dBm) (k=2)
9kHz-30MHz	4.92
30MHz ≤ f ≤ 1GHz	5.73
1GHz ≤ f ≤18GHz	5.58
18GHz ≤ f ≤40GHz	3.37

7.6. Time of Occupancy (Dwell Time)

Measurement Uncertainty:

Measurement Uncertainty (k=2)	0.88ms

©Copyright. All rights reserved by CTTL.

7.7. 20dB Bandwidth

Measurement Uncertainty:

Measurement Uncertainty (k=2)	61.936Hz

7.8. Carrier Frequency Separation

Measurement Uncertainty:

Measurement Uncertainty (k=2)	61.936Hz

7.9. AC Powerline Conducted Emission

Measurement Uncertainty:

Measurement Uncertainty (k=2)	3.10dB

©Copyright. All rights reserved by CTTL.

ANNEX A: EUT parameters

Disclaimer: The antenna gain provided by the client may affect the validity of the measurement results in this report, and the client shall bear the impact and consequences arising therefrom.

©Copyright. All rights reserved by CTTL.

ANNEX B: Detailed Test Results

B.1. Measurement Method

B.1.1. Conducted Measurements

The measurement is made according to ANSI C63.10.

1). Connect the EUT to the test system correctly.

2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).

3). Set the EUT to the required channel.

4). Set the EUT hopping mode (hopping or hopping off).

5). Set the spectrum analyzer to start measurement.

6). Record the values. Vector Signal Analyzer



B.1.2. Radiated Emission Measurements

The measurement is made according to ANSI C63.10

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 3MHz;



©Copyright. All rights reserved by CTTL.

B.2. Peak Output Power

B.2.1. Peak Output Power – Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.5

a) Use the following spectrum analyzer settings:

- Span: 6MHz
- RBW: 3MHz
- VBW: 3MHz
- Sweep time: 2.5ms
- Detector function: peak
- Trace: max hold

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power.

Measurement Limit:

Standard	Limits	
FCC Part 15.247 (b)(1)	Bandwidth≤1MHz	30dBm (1W)
	Bandwidth＞1MHz	21dBm (125mW)

Measurement Results:

For GFSK

Channel	Ch 0 2402 MHz		Ch 39 2441 MHz		Ch 78 2480 MHz		Conclusion
Peak Output Power -Conducted (dBm)	Fig.1	9.94	Fig.2	10.44	Fig.3	10.28	P

For π/4 DQPSK

Channel	Ch 0 2402 MHz		Ch 39 2441 MHz		Ch 78 2480 MHz		Conclusion
Peak Output Power -Conducted (dBm)	Fig.4	9.73	Fig.5	10.29	Fig.6	10.06	P

For 8DPSK

Channel	Ch 0 2402 MHz		Ch 39 2441 MHz		Ch 78 2480 MHz		Conclusion
Peak Output Power -Conducted (dBm)	Fig.7	10.03	Fig.8	10.57	Fig.9	10.30	P

Conclusion: PASS

©Copyright. All rights reserved by CTTL.

B.2.2. E.I.R.P.

The radiated E.I.R.P. is listed below:

Antenna gain = -1.36dBi

For GFSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
E.I.R.P (dBm)	8.58	9.08	8.92	P

Forπ/4 DQPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
E.I.R.P (dBm)	8.37	8.93	8.70	P

For 8DPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
E.I.R.P (dBm)	8.67	9.21	8.94	P

Note: E.I.R.P. are calculated with the antenna gain.

Conclusion: PASS

Test graphs as below



Fig.1. Peak Output Power -Conducted: GFSK, Channel 0,

©Copyright. All rights reserved by CTTL.



Fig.2. Peak Output Power -Conducted: GFSK, Channel 39,



Fig.3. Peak Output Power -Conducted: GFSK, Channel 78,

©Copyright. All rights reserved by CTTL.



Fig.4. Peak Output Power -Conducted: π/4 DQPSK, Channel 0,



Fig.5. Peak Output Power -Conducted: π/4 DQPSK, Channel 39,

©Copyright. All rights reserved by CTTL.



Fig.6. Peak Output Power -Conducted: π/4 DQPSK, Channel 78,



Fig.7. Peak Output Power -Conducted: 8DPSK, Channel 0,

©Copyright. All rights reserved by CTTL.



Fig.8. Peak Output Power -Conducted: 8DPSK, Channel 39,



Fig.9. Peak Output Power -Conducted: 8DPSK, Channel 78,

©Copyright. All rights reserved by CTTL.

B.3. Frequency Band Edges – Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.6

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below (be sure to enter all losses between the unlicensed wireless device output and the spectrum analyzer).

– Span: 10 MHz
– Resolution Bandwidth: 100 kHz
– Video Bandwidth: 300 kHz
– Sweep Time:Auto
– Detector: Peak
– Trace: max hold

Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel.

Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not an absolute field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	< -20

Measurement Result:

For GFSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.10	-65.22	P
	Hopping ON	Fig.11	-65.91	P
78	Hopping OFF	Fig.12	-66.39	P
	Hopping ON	Fig.13	-66.79	P

For π/4 DQPSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.14	-58.56	P
	Hopping ON	Fig.15	-63.76	P
78	Hopping OFF	Fig.16	-64.35	P
	Hopping ON	Fig.17	-64.23	P

For 8DPSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.18	-57.84	P
	Hopping ON	Fig.19	-61.22	P

©Copyright. All rights reserved by CTTL.

78	Hopping OFF	Fig.20	-63.99	P
	Hopping ON	Fig.21	-65.61	P

Conclusion: PASS

Test graphs as below



Fig.10. Frequency Band Edges: GFSK, Channel 0, Hopping Off



Fig.11. Frequency Band Edges: GFSK, Channel 0, Hopping On

©Copyright. All rights reserved by CTTL.



Fig.12. Frequency Band Edges: GFSK, Channel 78, Hopping Off



Fig.13. Frequency Band Edges: GFSK, Channel 78, Hopping On

©Copyright. All rights reserved by CTTL.



Fig.14. Frequency Band Edges: π/4 DQPSK, Channel 0, Hopping Off



Fig.15. Frequency Band Edges: π/4 DQPSK, Channel 0, Hopping On

©Copyright. All rights reserved by CTTL.



Fig.16. Frequency Band Edges: π/4 DQPSK, Channel 78, Hopping Off



Fig.17. Frequency Band Edges: π/4 DQPSK, Channel 78, Hopping On

©Copyright. All rights reserved by CTTL.



Fig.18. Frequency Band Edges: 8DPSK, Channel 0, Hopping Off



Fig.19. Frequency Band Edges: 8DPSK, Channel 0, Hopping On

©Copyright. All rights reserved by CTTL.



Fig.20. Frequency Band Edges: 8DPSK, Channel 78, Hopping Off



Fig.21. Frequency Band Edges: 8DPSK, Channel 78, Hopping On

©Copyright. All rights reserved by CTTL.

B.4. Frequency Band Edges –Radiated

Method of Measurement: See ANSI C63.10-clause 6.4 &6.5 & 6.6

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength (uV/m)	Field strength (dBuV/m)	Measurement distance (m)
Above 960	500	54	3

Set up:

Tabletop devices shall be placed on a nonconducting platform with nominal top surface dimensions 1 m by 1.5 m and the table height shall be 1.5 m.

The EUT and transmitting antenna shall be centered on the turntable.

Measurement Results:

EUT ID: UT25a

Mode	Channel	Frequency Range	Test Results	Conclusion
GFSK	0	2.31GHz ~2.45GHz	Fig.22	P
	78	2.45GHz ~2.5GHz	Fig.23	P

Mode	Channel	Frequency Range	Test Results	Conclusion
π/4 DQPSK	0	2.31GHz ~2.43GHz	Fig.24	P
	78	2.45GHz ~2.5GHz	Fig.25	P

Mode	Channel	Frequency Range	Test Results	Conclusion
8DPSK	0	2.31GHz ~2.45GHz	Fig.26	P
	78	2.45GHz ~2.5GHz	Fig.27	P

Conclusion: PASS

©Copyright. All rights reserved by CTTL.

Test graphs as below



Fig.22. Frequency Band Edges: GFSK, Channel 0, 2.31 GHz – 2.45GHz



Fig.23. Frequency Band Edges: GFSK, Channel 78, 2.45 GHz - 2.50GHz

©Copyright. All rights reserved by CTTL.



Fig.24. Frequency Band Edges: π/4 DQPSK, Channel 0, 2.31 GHz - 2.45GHz



Fig.25. Frequency Band Edges: π/4 DQPSK, Channel 78, 2.45 GHz - 2.50GHz

©Copyright. All rights reserved by CTTL.



Fig.26. Frequency Band Edges: 8DPSK, Channel 0, 2.38 GHz - 2.45GHz



Fig.27. Frequency Band Edges: 8DPSK, Channel 78, 2.45 GHz - 2.50GHz

©Copyright. All rights reserved by CTTL.

B.5. Transmitter Spurious Emission - Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.8

Measurement Procedure – Reference Level

1. Set the RBW = 100 kHz.

2. Set the VBW = 300 kHz.

3. Set the span to 5-30 % greater than the EBW.

4. Detector = peak.

5. Sweep time = auto couple.

6. Trace mode = max hold.

7. Allow trace to fully stabilize.

8. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW. Next, determine the power in 100 kHz band segments outside of the authorized frequency band using the following measurement:

Measurement Procedure - Unwanted Emissions

1. Set RBW = 100 kHz.

2. Set VBW = 300 kHz.

3. Set span to encompass the spectrum to be examined.

4. Detector = peak.

5. Trace Mode = max hold.

6. Sweep = auto couple.

7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified above.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

Measurement Results:

For GFSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0	Center Frequency	Fig.28	P

©Copyright. All rights reserved by CTTL.

2402 MHz	30 MHz ~ 1 GHz	Fig.29	P
	1 GHz ~ 3 GHz	Fig.30	P
	3 GHz ~ 10 GHz	Fig.31	P
	10 GHz ~ 26 GHz	Fig.32	P
Ch 39 2441 MHz	Center Frequency	Fig.33	P
	30 MHz ~ 1 GHz	Fig.34	P
	1 GHz ~ 3 GHz	Fig.35	P
	3 GHz ~ 10 GHz	Fig.36	P
	10 GHz ~ 26 GHz	Fig.37	P
Ch 78 2480 MHz	Center Frequency	Fig.38	P
	30 MHz ~ 1 GHz	Fig.39	P
	1 GHz ~ 3 GHz	Fig.40	P
	3 GHz ~ 10 GHz	Fig.41	P
	10 GHz ~ 26 GHz	Fig.42	P

For π/4 DQPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	Center Frequency	Fig.43	P
	30 MHz ~ 1 GHz	Fig.44	P
	1 GHz ~ 3 GHz	Fig.45	P
	3 GHz ~ 10 GHz	Fig.46	P
	10 GHz ~ 26 GHz	Fig.47	P
Ch 39 2441 MHz	Center Frequency	Fig.48	P
	30 MHz ~ 1 GHz	Fig.49	P
	1 GHz ~ 3 GHz	Fig.50	P
	3 GHz ~ 10 GHz	Fig.51	P
	10 GHz ~ 26 GHz	Fig.52	P
Ch 78 2480 MHz	Center Frequency	Fig.53	P
	30 MHz ~ 1 GHz	Fig.54	P
	1 GHz ~ 3 GHz	Fig.55	P
	3 GHz ~ 10 GHz	Fig.56	P
	10 GHz ~ 26 GHz	Fig.57	P

For 8DPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	Center Frequency	Fig.58	P
	30 MHz ~ 1 GHz	Fig.59	P
	1 GHz ~ 3 GHz	Fig.60	P
	3 GHz ~ 10 GHz	Fig.61	P
	10 GHz ~ 26 GHz	Fig.62	P

©Copyright. All rights reserved by CTTL.

Ch 39 2441 MHz	Center Frequency	Fig.63	P
	30 MHz ~ 1 GHz	Fig.64	P
	1 GHz ~ 3 GHz	Fig.65	P
	3 GHz ~ 10 GHz	Fig.66	P
	10 GHz ~ 26 GHz	Fig.67	P
Ch 78 2480 MHz	Center Frequency	Fig.68	P
	30 MHz ~ 1 GHz	Fig.69	P
	1 GHz ~ 3 GHz	Fig.70	P
	3 GHz ~ 10 GHz	Fig.71	P
	10 GHz ~ 26 GHz	Fig.72	P

Conclusion: PASS

Test graphs as below



Fig.28. Conducted spurious emission: GFSK, Channel 0,2402MHz

©Copyright. All rights reserved by CTTL.



Fig.29. Conducted spurious emission: GFSK, Channel 0, 30MHz - 1GHz



Fig.30. Conducted spurious emission: GFSK, Channel 0, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL.



Fig.31. Conducted spurious emission: GFSK, Channel 0, 3GHz - 10GHz



Fig.32. Conducted spurious emission: GFSK, Channel 0,10GHz - 26GHz

©Copyright. All rights reserved by CTTL.



Fig.33. Conducted spurious emission: GFSK, Channel 39, 2441MHz



Fig.34. Conducted spurious emission: GFSK, Channel 39, 30MHz - 1GHz

©Copyright. All rights reserved by CTTL.



Fig.35. Conducted spurious emission: GFSK, Channel 39, 1GHz – 3GHz



Fig.36. Conducted spurious emission: GFSK, Channel 39, 3GHz – 10GHz

©Copyright. All rights reserved by CTTL.



Fig.37. Conducted spurious emission: GFSK, Channel 39, 10GHz – 26GHz



Fig.38. Conducted spurious emission: GFSK, Channel 78, 2480MHz

©Copyright. All rights reserved by CTTL.



Fig.39. Conducted spurious emission: GFSK, Channel 78, 30MHz - 1GHz



Fig.40. Conducted spurious emission: GFSK, Channel 78, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL.



Fig.41. Conducted spurious emission: GFSK, Channel 78, 3GHz - 10GHz



Fig.42. Conducted spurious emission: GFSK, Channel 78, 10GHz - 26GHz

©Copyright. All rights reserved by CTTL.



Fig.43. Conducted spurious emission: π/4 DQPSK, Channel 0,2402MHz



Fig.44. Conducted spurious emission: π/4 DQPSK, Channel 0, 30MHz - 1GHz

©Copyright. All rights reserved by CTTL.



Fig.45. Conducted spurious emission: π/4 DQPSK, Channel 0, 1GHz - 3GHz



Fig.46. Conducted spurious emission: π/4 DQPSK, Channel 0, 3GHz - 10GHz

©Copyright. All rights reserved by CTTL.



Fig.47. Conducted spurious emission: π/4 DQPSK, Channel 0,10GHz - 26GHz



Fig.48. Conducted spurious emission: π/4 DQPSK, Channel 39, 2441MHz

©Copyright. All rights reserved by CTTL.



Fig.49. Conducted spurious emission: π/4 DQPSK, Channel 39, 30MHz - 1GHz



Fig.50. Conducted spurious emission: π/4 DQPSK, Channel 39, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL.



Fig.51. Conducted spurious emission: π/4 DQPSK, Channel 39, 3GHz - 10GHz



Fig.52. Conducted spurious emission: π/4 DQPSK, Channel 39, 10GHz – 26GHz

©Copyright. All rights reserved by CTTL.



Fig.53. Conducted spurious emission: π/4 DQPSK, Channel 78, 2480MHz



Fig.54. Conducted spurious emission: π/4 DQPSK, Channel 78, 30MHz - 1GHz

©Copyright. All rights reserved by CTTL.



Fig.55. Conducted spurious emission: π/4 DQPSK, Channel 78, 1GHz - 3GHz



Fig.56. Conducted spurious emission: π/4 DQPSK, Channel 78, 3GHz - 10GHz

©Copyright. All rights reserved by CTTL.



Fig.57. Conducted spurious emission: π/4 DQPSK, Channel 78, 10GHz - 26GHz



Fig.58. Conducted spurious emission: 8DPSK, Channel 0,2402MHz

©Copyright. All rights reserved by CTTL.