



FCC PART 15.247 TEST REPORT

For

Feitian Technologies Co., Ltd.

Floor 17th, Tower B, Huizhi Mansion, No.9 Xueqing Road, Haidian District, Beijing, China

FCC ID: ZD3FTF360

Report Type: Original Report	Product Name: Android POS Terminal
Report Number:	RKSA240319001-00C
Report Date:	2024-11-11
Reviewed By:	Bard Liu 
Approved By:	Kyle Xu 
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu Province, China Tel: +86-512-86175000 Fax: +86-512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.

TABLE OF CONTENTS

REPORT REVISION HISTORY.....	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY.....	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
SPECIAL ACCESSORIES.....	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	8
TEST EQUIPMENT LIST	11
SUMMARY OF TEST RESULTS	12
FCC §1.1307(b) & §2.1093– RF EXPOSURE	13
APPLICABLE STANDARD	13
FCC §15.203 – ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
TEST SYSTEM SETUP.....	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	16
TEST RESULTS SUMMARY	16
TEST DATA: SEE APPENDIX	16
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	17
APPLICABLE STANDARD	17
TEST SYSTEM SETUP.....	17
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE	18
TEST RESULTS SUMMARY	19
TEST DATA: SEE APPENDIX	19
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	20
APPLICABLE STANDARD	20
TEST PROCEDURE	20
TEST DATD: SEE APPENDIX	20
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST DATD: SEE APPENDIX	21
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	22

APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST DATD: SEE APPENDIX	22
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST DATD: SEE APPENDIX	23
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST DATD: SEE APPENDIX	24
FCC §15.247(d) - BAND EDGES TESTING	25
APPLICABLE STANDARD	25
TEST PROCEDURE	25
TEST DATD: SEE APPENDIX	25
EUT PHOTOGRAPHS	26
TEST SETUP PHOTOGRAPHS	27
APPENDIX - TEST DATA.....	28
ENVIRONMENTAL CONDITIONS & TEST INFORMATION.....	28
AC LINE CONDUCTED EMISSIONS	29
RADIATED EMISSIONS & RESTRICTED BANDS EMISSIONS	31
CHANNEL SEPARATION TEST	51
20 dB BANDWIDTH TEST	52
QUANTITY OF HOPPING CHANNEL TEST	57
PEAK OUTPUT POWER MEASUREMENT.....	65
BAND EDGES.....	71

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	RKSA240319001-00C	R1V1	2024-11-11	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Feitian Technologies Co., Ltd.
Product Name:	Android POS Terminal
Tested Model	F360
Power Supply:	DC 3.7V from battery or DC 5V charging by adapter
Maximum peak Output Power:	GFSK: -2.91 dBm $\pi/4$ -DQPSK: -0.96 dBm 8DPSK: -0.71 dBm
RF Function:	Classic BT
Operating Band/Frequency:	2402-2480 MHz
Channel Number:	79
Channel Separation:	1 MHz
Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Type:	FPC Antenna
★Maximum Antenna Gain:	-1.12 dBi

Adapter Information:

Model: TEKA-UCA20US

Input: 100-240V, 50/60Hz, 0.35A Max

Output: 5.0V, 2.0A

Note: The maximum antenna gain was declared by the manufacturer.

All measurement and test data in this report was gathered from production sample serial number: RKSA240319001-1 (Assigned by the BACL (Kunshan). The EUT supplied by the applicant was received on 2024-03-19.)

Objective

This test report is prepared for *Feitian Technologies Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and 558074 D01 15.247 Meas Guidance v05r02.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	9 kHz~150 kHz	3.8dB
	150 kHz~30 MHz	3.4dB
	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu Province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) is accredited in accordance with ISO/IEC 17025:2017 by NVLAP (Lab code: 600338-0), and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No. : CN5055.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	...	...
...	...	...	...
...	...	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

RF Test Tool: QRCT 4

★Power level: Default

Note: The power level was declared by the applicant.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To
Power Cable	1.0	AC Source/LISN	Adapter
USB Cable	1.5	Adapter	EUT

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1 GHz):



TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber #1)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2024-04-23	2025-04-22
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2023-11-11	2024-11-10
Narda	6dB Attenuator	773-6	10690812-2-1	2023-11-11	2024-11-10
ETS-LINDGREN	Loop Antenna	6512	108100	2024-11-03	2025-11-02
Sonoma Instrument	Pre-amplifier	310N	171205	2024-04-23	2025-04-22
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2024-04-25	2025-04-24
MICRO-COAX	Coaxial Cable	Cable-9	009	2024-04-23	2025-04-22
Radiated Emission Test (Chamber #2)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207/040	2024-04-25	2025-04-24
ETS-LINDGREN	Horn Antenna	3115	9311-4159	2023-12-02	2024-12-01
ETS-LINDGREN	Horn Antenna	3116	2516	2024-01-06	2025-01-05
A.H.Systems, inc	Amplifier	PAM-0118P	512	2024-04-25	2025-04-24
SELECTOR	Amplifier	EM18G40G	060726	2024-04-25	2025-04-24
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2023-08-05	2024-08-04
Narda	Attenuator	10dB	010	2024-04-23	2025-04-22
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2024-04-25	2025-04-24
MICRO-COAX	Coaxial Cable	Cable-11	011	2024-04-25	2025-04-24
MICRO-COAX	Coaxial Cable	Cable-12	012	2024-04-25	2025-04-24
MICRO-COAX	Coaxial Cable	Cable-13	013	2024-04-25	2025-04-24
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2024-04-24	2025-04-23
Rohde & Schwarz	Spectrum Analyzer	FSIQ26	100048	2024-04-24	2025-04-23
Narda	Attenuator	10dB	010	2023-08-15	2024-08-14
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	101746	2024-04-23	2025-04-22
Rohde & Schwarz	LISN	ENV216	101115	2024-04-23	2025-04-22
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse Limiter	ESH3-Z2	0357.8810.54	2024-04-24	2025-04-23
MICRO-COAX	Coaxial Cable	Cable-15	015	2024-04-23	2025-04-22

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307(b)(1)& §2.1093	RF EXPOSURE	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

FCC §1.1307(b) & §2.1093– RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Result

Mode	Frequency Range (MHz)	Max Tune-up Conducted Power		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
		(dBm)	(mW)				
BT	2402-2480	-0.5	0.89	5.0	0.28	3.0	Yes

Result: So the standalone SAR evaluation is not necessary.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has a FPC Antenna for Bluetooth, and the antenna gain is -1.12 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

Test System Setup



The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	VBW
150 kHz - 30 MHz	9 kHz	30 kHz

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the EUT or adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

If the maximum peak value of the emissions is below the average limit, the QP value and average value measurement will not need to be performed and only record the maximum peak measured value to meet the requirements.

Level & Over Limit Calculation

The Level is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

Level (dBμV) = Read level (dBμV) + Factor (dB)

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

Over Limit (dB) = Level (dBμV) - Limit (dBμV)



Test Results Summary


According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data: See Appendix

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

Test System Setup**9kHz - 30MHz:****30 MHz - 1 GHz:**

Above 1GHz:

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	VBW	IF B/W	Measurement
9 kHz - 150 kHz	200 Hz	1 kHz	200 Hz	QP/Average
150 kHz - 30 MHz	9 kHz	30 kHz	9 kHz	QP/ Average
30 MHz - 1000 MHz	100 kHz	300 kHz	/	Peak
	/	/	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	Peak
	1MHz	3 MHz	/	Average

For 9 kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

If the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is at least 6 dB below the QP emission limit, there's no need to record the measured QP level of the emissions in the report.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dBμV/m) = Meter Reading (dBμV) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Note: The QuasiPeak (dBμV/m), MaxPeak (dBμV/m), Average (dBμV/m) which shown in the data table are all Corrected Amplitude.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data: See Appendix

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: Wide enough to capture the peaks of two adjacent channels.
- b. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c. Video (or average) bandwidth (VBW) $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.



Test Datd: See Appendix


FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Datd: See Appendix

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard


Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c. VBW $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.



Test Datd: See Appendix


FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a Span: Zero span, centered on a hopping channel.
- b RBW shall be $\leq$ channel spacing and where possible RBW should be set $\geq 1 / T$, where T is the expected dwell time per channel.
- c Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d Detector function: Peak.
- e Trace: Max hold.



Test Datd: See Appendix


FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

- a. Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW $\geq$ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b. Allow trace to stabilize.
- c. Use the marker-to-peak function to set the marker to the peak of the emission.
- d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e. A plot of the test results and setup description shall be included in the test report.



Test Datd: See Appendix


FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Datd: See Appendix

EUT PHOTOGRAPHS

Please refer to the attachment EXHIBIT A - EUT EXTERNAL PHOTOGRAPHS and EXHIBIT B - EUT INTERNAL PHOTOGRAPHS.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment EXHIBIT C - TEST SETUP PHOTOGRAPHS.


APPENDIX - TEST DATA

Environmental Conditions & Test Information

Test Item:	AC LINE CONDUCTED EMISSIONS	RADIATED EMISSIONS		
		9 kHz – 30 MHz	30 MHz - 1 GHz	1 GHz - 18 GHz
Test Date:	2024-05-24	2024-11-09	2024-05-16	2024-04-26 to 2024-04-27
Temperature:	24.4 °C	22.4 °C	21.3 °C	16.7-20.3 °C
Relative Humidity:	57 %	47 %	48 %	47-51 %
ATM Pressure:	101.2 kPa	102.3 kPa	101.9 kPa	100.7-100.2 kPa
Test Result:	Pass	Pass	Pass	Pass
Test Engineer:	Frank Liu	Jerry Yan	Leah Li	Peter Wang

Test Item:	18 GHz - 25 GHz	CHANNEL SEPARATION TEST	20 DB BANDWIDTH TEST
Test Date:	2024-06-03	2024-06-20	2024-05-17
Temperature:	23.2 °C	23.1°C	21.3 °C
Relative Humidity:	43 %	46%	41 %
ATM Pressure:	100.9 kPa	100.1 kPa	101.0 kPa
Test Result:	Pass	Pass	Pass
Test Engineer:	Hugh Wu	Jason Lu	Loki Shi


Test Item:	QUANTITY OF HOPPING CHANNEL TEST	TIME OF OCCUPANCY (DWELL TIME)	TRANSMITTER OUTPUT POWER MEASUREMENT	OUT OF BAND EMISSIONS
Test Date:	2024-05-18	2024-06-24	2024-05-29	2024-05-17
Temperature:	22.3 °C	21.5 °C	22.5 °C	21.3 °C
Relative Humidity:	48 %	51 %	47 %	41 %
ATM Pressure:	101.9 kPa	101.3 kPa	101.0 kPa	101.0 kPa
Test Result:	Pass	Pass	Pass	Pass
Test Engineer:	Loki Shi	Jay Liu	Jay Liu	Loki Shi

AC LINE CONDUCTED EMISSIONS*EUT operation mode: Transmitting in 8DPSK Mode middle channel (maximum output power mode)***AC 120V/60 Hz, Line**

Site : CE
Condition : FCC Part 15.207
: DET:Peak
Project No. : RKSA240319001
Model : F360
Phase : L
Voltage : 120V/60Hz
Mode : Transmitting in BT-3DH5 mode middle channel
Test Equipment : ENV216,ESR
Temperature : 24.4℃
Humidity : 57%
Atmospheric pressure: 101.2kPa
Test Engineer : Frank Liu



	Freq MHz	Read		Level dBuV	Limit	Over	Remark
		Level dBuV	Factor dB		Line dBuV	Limit dB	
1	0.183	23.16	20.12	43.28	64.34	-21.06	Peak
2	0.243	17.78	20.13	37.91	61.98	-24.07	Peak
3	0.364	15.29	20.20	35.49	58.63	-23.14	Peak
4	0.640	21.00	20.09	41.09	56.00	-14.91	Peak
5	0.739	18.49	20.02	38.51	56.00	-17.49	Peak
6	1.378	16.03	19.93	35.96	56.00	-20.04	Peak

AC 120V/60 Hz, Neutral



Site : CE
Condition : FCC Part 15.207
: DET:Peak
Project No. : RKSA240319001
Model : F360
Phase : N
Voltage : 120V/60Hz
Mode : Transmitting in BT-3DHS mode middle channel
Test Equipment : ENV216,ESR
Temperature : 24.4℃
Humidity : 57%
Atmospheric pressure: 101.2kPa
Test Engineer : Frank Liu

		Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.172	25.98	20.11	46.09	64.88	-18.79	Peak
2	0.231	21.37	20.12	41.49	62.40	-20.91	Peak
3	0.287	17.87	20.16	38.03	60.62	-22.59	Peak
4	0.562	16.60	20.11	36.71	56.00	-19.29	Peak
5	0.646	20.06	20.08	40.14	56.00	-15.86	Peak
6	0.743	18.10	20.01	38.11	56.00	-17.89	Peak

RADIATED EMISSIONS & RESTRICTED BANDS EMISSIONS*EUT operation mode: Transmitting**After pre-scan in the X, Y and Z axes of orientation, the worst case is below:***9 kHz-30 MHz:** (Transmitting maximum output power mode and channel)**9 kHz-30 MHz: Transmitting in 8DPSK Mode middle channel (maximum output power mode)
Parallel(worst case)****9K-150K****150K-30M**Project No.RKSA240319001
Date: 9.NOV.2024 13:38:57

Tester:Jerry Yan

Project No.RKSA240319001
Date: 9.NOV.2024 15:21:02

Tester:Jerry Yan

9kHz-150kHz


Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.015486	75.05	PK	52.87	123.81	48.76
0.02028	71.29	PK	49.92	121.46	50.17
0.023664	69.71	PK	48.97	120.12	50.41
0.03438	70.86	PK	46.06	116.88	46.02

150kHz-30MHz

Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.15000	55.07	PK	50.90	104.08	49.01
0.62760	44.37	PK	21.51	71.65	27.28
2.23950	34.08	PK	13.39	69.54	35.46
3.61260	30.09	PK	15.59	69.54	39.45

30 MHz - 1 GHz (Transmitting in maximum output power 8DPSK mode):**Low Channel: 2402 MHz****Common Information**


Project No:	RKSA240319001
EUT Model:	F360
Test Mode:	Transmitting in BT-3DH5 mode low channel
Standard:	FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment:	ESCI, JB3, 310N
Temperature:	21.3°C
Humidity:	48%
Barometric Pressure:	101.9kPa
Test Engineer:	Leah Li
Test Date:	2024/5/16

**Critical Freqs**

Frequency (MHz)	Corrected Amplitude QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
30.606250	28.13	40.00	11.87	H	-4.9
63.707500	23.95	40.00	16.05	V	-17.2
80.318750	24.47	40.00	15.53	V	-17.6
129.788750	24.05	43.50	19.45	V	-11.4
545.797500	29.06	46.00	16.94	V	-5.3
936.101250	35.35	46.00	10.65	H	1.4

Middle Channel: 2441 MHz**Common Information**

Project No: RKSA240319001
EUT Model: F360
Test Mode: Transmitting in BT-3DH5 mode middle channel
Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment: ESCI, JB3, 310N
Temperature: 21.3°C
Humidity: 48%
Barometric Pressure: 101.9kPa
Test Engineer: Leah Li
Test Date: 2024/5/16

**Critical Freqs**

Frequency (MHz)	Corrected Amplitude QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Pol	Corr. (dB/m)
30.000000	28.93	40.00	11.07	H	-4.4
64.071250	24.16	40.00	15.84	V	-17.2
79.106250	23.28	40.00	16.72	V	-17.5
131.728750	24.11	43.50	19.39	V	-11.4
553.193750	28.56	46.00	17.44	V	-5.3
896.816250	35.66	46.00	10.34	V	1.2

High Channel:2480 MHz

Common Information

Project No:

EUT Model:

Test Mode:

Standard:

Test Equipment:

Temperature:

Humidity:

Barometric Pressure:

Test Engineer:

Test Date:

RKSA240319001

F360

Transmitting in BT-3DH5 mode high channel

FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209

ESCI, JB3, 310N


21.3℃

48%

101.9kPa

Leah Li

2024/5/16




Critical Freqs

Frequency (MHz)	Corrected Amplitude QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
31.818750	28.81	40.00	11.19	H	-5.7
63.222500	24.40	40.00	15.60	V	-17.3
80.076250	23.16	40.00	16.84	V	-17.6
124.575000	24.17	43.50	19.33	V	-11.3
542.523750	28.34	46.00	17.66	H	-5.4
953.076250	36.00	46.00	10.00	V	1.5

1 GHz - 18 GHz:**GFSK:****Low Channel: 2402 MHz****Common Information**

Project No.:
Test Mode:
Standard:
Test Engineer:


RKSA240319001
Transmitting in BT-DH5 mode low channel
FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Peter Wang

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1197.200000	---	22.57	54.00	31.43	H	-14.9
1197.200000	33.16	---	74.00	40.84	H	-14.9
2601.400000	---	28.73	54.00	25.27	V	-9.4
2601.400000	35.36	---	74.00	38.64	V	-9.4
4605.700000	---	35.60	54.00	18.40	V	-3.3
4605.700000	40.19	---	74.00	33.81	V	-3.3
8043.100000	---	38.31	54.00	15.69	H	3.8
8043.100000	46.75	---	74.00	27.25	H	3.8
12084.000000	---	42.70	54.00	11.30	H	7.1
12084.000000	47.88	---	74.00	26.12	H	7.1
17260.500000	---	43.60	54.00	10.40	V	13.0
17260.500000	53.92	---	74.00	20.08	V	13.0

Middle Channel: 2441 MHz**Common Information**


Project No.: RKSA240319001
 Test Mode: Transmitting in BT-DH5 mode middle channel
 Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
 Test Engineer: Peter Wang

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1324.700000	---	23.27	54.00	30.73	V	-14.5
1324.700000	29.71	---	74.00	44.29	V	-14.5
2688.100000	---	28.65	54.00	25.35	V	-9.1
2688.100000	36.89	---	74.00	37.11	V	-9.1
5253.400000	---	38.04	54.00	15.96	H	-0.2
5253.400000	44.23	---	74.00	29.77	H	-0.2
8000.600000	---	38.84	54.00	15.16	H	3.8
8000.600000	47.82	---	74.00	26.18	H	3.8
12055.100000	---	42.55	54.00	11.45	H	7.0
12055.100000	48.82	---	74.00	25.18	H	7.0
17255.400000	---	43.26	54.00	10.74	V	13.0
17255.400000	53.04	---	74.00	20.96	V	13.0

High Channel: 2480 MHz**Common Information**


Project No.: RKSA240319001
 Test Mode: Transmitting in BT-DH5 mode high channel
 Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
 Test Engineer: Peter Wang

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB)
1289.000000	---	23.69	54.00	30.31	V	-14.6
1289.000000	30.31	---	74.00	43.69	V	-14.6
2303.900000	---	26.66	54.00	27.34	V	-10.1
2303.900000	36.53	---	74.00	37.47	V	-10.1
4478.200000	---	32.79	54.00	21.21	H	-3.9
4478.200000	40.94	---	74.00	33.06	H	-3.9
9316.400000	---	38.66	54.00	15.34	V	5.3
9316.400000	48.25	---	74.00	25.75	V	5.3
12682.400000	---	41.55	54.00	12.45	H	8.7
12682.400000	49.46	---	74.00	24.54	H	8.7
17561.400000	---	45.18	54.00	8.82	V	13.4
17561.400000	53.95	---	74.00	20.05	V	13.4

Band Edge:**Left Side****Common Information**

Project No.:	RKSA240319001
Test Mode:	Transmitting in BT-DH5 mode low channel
Standard:	FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Engineer:	Peter Wang

Full Spectrum**Critical Freqs**


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2345.630000	---	38.88	54.00	15.12	V	0.0
2345.630000	48.63	---	74.00	25.37	V	0.0
2379.706000	---	41.02	54.00	12.98	V	0.0
2379.706000	44.15	---	74.00	29.85	V	0.0

Right Side

Common Information

Project No.: RKSA240319001
Test Mode: Transmitting in BT-DH5 mode high channel
Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Engineer: Peter Wang

Full Spectrum



Critical_Freqs


Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.740000	---	38.65	54.00	15.35	H	0.2
2483.740000	49.57	---	74.00	24.43	H	0.2
2484.430000	---	41.74	54.00	12.26	H	0.2
2484.430000	47.84	---	74.00	26.16	H	0.2

$\pi/4$ -DQPSK:

Low Channel: 2402 MHz

Common Information


Project No.: RKSA240319001
 Test Mode: Transmitting in BT-2DH5 mode low channel
 Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
 Test Engineer: Peter Wang

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1198.900000	32.19	---	74.00	41.81	H	-14.9
1198.900000	---	24.05	54.00	29.95	H	-14.9
2671.100000	---	28.88	54.00	25.12	H	-9.2
2671.100000	36.18	---	74.00	37.82	H	-9.2
5250.000000	---	37.59	54.00	16.41	H	-0.2
5250.000000	44.62	---	74.00	29.38	H	-0.2
8432.400000	---	38.11	54.00	15.89	H	3.9
8432.400000	47.39	---	74.00	26.61	H	3.9
12123.100000	---	41.77	54.00	12.23	H	7.2
12123.100000	49.16	---	74.00	24.84	H	7.2
17600.500000	---	46.46	54.00	7.54	V	13.2
17600.500000	52.32	---	74.00	21.68	V	13.2

Middle Channel: 2441 MHz**Common Information**


Project No.: RKSA240319001
 Test Mode: Transmitting in BT-2DH5 mode middle channel
 Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
 Test Engineer: Peter Wang

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1209.100000	---	23.68	54.00	30.32	H	-14.9
1209.100000	32.43	---	74.00	41.57	H	-14.9
2234.200000	---	27.73	54.00	26.27	H	-10.2
2234.200000	34.87	---	74.00	39.13	H	-10.2
4469.700000	---	33.46	54.00	20.54	V	-3.9
4469.700000	40.12	---	74.00	33.88	V	-3.9
7681.000000	---	39.76	54.00	14.24	V	4.1
7681.000000	46.80	---	74.00	27.20	V	4.1
12067.000000	---	41.57	54.00	12.43	V	7.0
12067.000000	49.11	---	74.00	24.89	V	7.0
17569.900000	---	45.75	54.00	8.25	H	13.3
17569.900000	51.80	---	74.00	22.20	H	13.3

High Channel: 2480 MHz**Common Information**


Project No.: RKSA240319001
 Test Mode: Transmitting in BT-2DH5 mode high channel
 Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
 Test Engineer: Peter Wang

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1232.900000	---	24.36	54.00	29.64	V	-14.8
1232.900000	32.16	---	74.00	41.84	V	-14.8
2749.300000	---	28.47	54.00	25.53	V	-8.9
2749.300000	34.89	---	74.00	39.11	V	-8.9
4643.100000	---	35.34	54.00	18.66	V	-3.1
4643.100000	40.96	---	74.00	33.04	V	-3.1
7602.800000	47.96	---	74.00	26.04	H	4.1
7602.800000	---	38.65	54.00	15.35	H	4.1
10912.700000	---	41.14	54.00	12.86	V	6.5
10912.700000	47.49	---	74.00	26.51	V	6.5
15178.000000	---	45.52	54.00	8.48	H	10.7
15178.000000	52.89	---	74.00	21.11	H	10.7

Band Edge:**Left Side****Common Information**

Project No.: RKSA240319001
Test Mode: Transmitting in BT-2DH5 mode low channel
Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Engineer: Peter Wang

Full Spectrum**Critical Freqs**


Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2359.434000	---	39.46	54.00	14.54	V	0.0
2359.434000	48.30	---	74.00	25.70	V	0.0
2368.716000	---	40.42	54.00	13.58	V	0.0
2368.716000	46.21	---	74.00	27.79	V	0.0

Right Side

Common Information

Project No.: RKSA240319001
Test Mode: Transmitting in BT-2DH5 mode high channel
Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Engineer: Peter Wang

Full Spectrum




Critical_Freqs

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.662000	51.19	---	74.00	22.81	H	0.2
2483.662000	---	40.32	54.00	13.68	H	0.2
2491.462000	47.14	---	74.00	26.86	H	0.2
2491.462000	---	41.51	54.00	12.49	H	0.2

8DPSK:**Low Channel: 2402 MHz****Common Information**


Project No.: RKSA240319001
 Test Mode: Transmitting in BT-3DH5 mode low channel
 Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
 Test Engineer: Peter Wang

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1253.300000	---	23.87	54.00	30.13	V	-14.7
1253.300000	31.72	---	74.00	42.28	V	-14.7
2796.900000	---	28.26	54.00	25.74	H	-8.7
2796.900000	35.42	---	74.00	38.58	H	-8.7
5006.900000	---	36.45	54.00	17.55	V	-1.2
5006.900000	42.28	---	74.00	31.72	V	-1.2
9304.500000	---	38.35	54.00	15.65	H	5.2
9304.500000	48.29	---	74.00	25.71	H	5.2
12774.200000	---	40.80	54.00	13.20	V	8.8
12774.200000	48.77	---	74.00	25.23	V	8.8
17138.100000	---	45.38	54.00	8.62	H	12.7
17138.100000	52.54	---	74.00	21.46	H	12.7

Middle Channel: 2441 MHz**Common Information**

Project No.: RKSA240319001
Test Mode: Transmitting in BT-3DH5 mode middle channel
Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Engineer: Peter Wang

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1348.500000	---	22.51	54.00	31.49	V	-14.4
1348.500000	31.34	---	74.00	42.66	V	-14.4
2091.400000	---	27.37	54.00	26.63	V	-10.4
2091.400000	33.98	---	74.00	40.02	H	-10.4
3840.700000	---	31.56	54.00	22.44	H	-5.4
3840.700000	40.13	---	74.00	33.87	H	-5.4
7079.200000	---	39.00	54.00	15.00	V	3.9
7079.200000	47.04	---	74.00	26.96	V	3.9
9931.800000	---	41.80	54.00	12.20	H	7.6
9931.800000	48.21	---	74.00	25.79	H	7.6
17544.400000	---	44.78	54.00	9.22	H	13.4
17544.400000	52.38	---	74.00	21.62	H	13.4

High Channel: 2480 MHz**Common Information**

Project No.:

RKSA240319001

Test Mode:

Transmitting in BT-3DH5 mode high channel

Standard:


FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209

Test Engineer:

Peter Wang

Fundamental Test
with notch filter


Full Spectrum

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1107.100000	---	21.44	54.00	32.56	H	-15.2
1107.100000	30.58	---	74.00	43.42	H	-15.2
2795.200000	---	27.85	54.00	26.15	V	-8.7
2795.200000	35.38	---	74.00	38.62	V	-8.7
5052.800000	---	36.46	54.00	17.54	H	-1.0
5052.800000	44.23	---	74.00	29.77	H	-1.0
8633.000000	---	37.86	54.00	16.14	H	3.8
8633.000000	47.14	---	74.00	26.86	H	3.8
13682.000000	---	45.29	54.00	8.71	V	10.8
13682.000000	52.90	---	74.00	21.10	V	10.8
17607.300000	---	46.59	54.00	7.41	V	13.2
17607.300000	56.19	---	74.00	17.81	V	13.2

Band Edge:**Left Side****Common Information**


Project No.: RKSA240319001
Test Mode: Transmitting in BT-3DH5 mode low channel
Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Engineer: Peter Wang

Full Spectrum**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2347.324000	---	38.59	54.00	15.41	H	0.0
2347.324000	49.09	---	74.00	24.91	H	0.0
2380.154000	---	40.35	54.00	13.65	H	0.0
2380.154000	46.53	---	74.00	27.47	H	0.0

Right Side**Common Information**


Project No.: RKSA240319001
Test Mode: Transmitting in BT-3DH5 mode high channel
Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Engineer: Peter Wang

Full Spectrum**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2484.394000	47.71	---	74.00	26.29	H	0.2
2484.394000	---	42.23	54.00	11.77	H	0.2

18 GHz - 25 GHz (8DPSK Mode low channel):


Horizontal



Project No : RKSA240319001
Date: 3.JUN.2024 18:01:12

Tester: Hugh Wu

Vertical



Project No : RKSA240319001
Date: 3.JUN.2024 17:02:12


Tester: Hugh Wu

Note: The test distance is 3m. The limit is 74dBμV/m(Peak) and 54dBμV/m(Average).

CHANNEL SEPARATION TEST*EUT operation mode: Transmitting*

Test Mode	Channel	Result (MHz)	Limit (MHz)	Verdict
GFSK	Hop	0.996	0.847	PASS

Note: only GFSK mode result is report since EDR ($\pi/4$ -DQPSK, 8DPSK) has the exact same channel plan and the Limit is maximum 20 dB bandwidth*2/3 Limit = 20 dB bandwidth*2/3

BDR (GFSK): Middle Channel

ProjectNo.: RKSA240319001 Tester: Jason Lu


Date: 20 JUN. 2024 11:00:27

20 dB BANDWIDTH TEST

EUT operation mode: Transmitting


Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.905
	Middle	2441	0.902
	High	2480	0.908
EDR ($\pi/4$ -DQPSK)	Low	2402	1.271
	Middle	2441	1.271
	High	2480	1.271
EDR (8DPSK)	Low	2402	1.262
	Middle	2441	1.265
	High	2480	1.265

BDR (GFSK): Low Channel




ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 17.MAY.2024 17:19:41

BDR (GFSK): Middle Channel




ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 17.MAY.2024 17:26:55

BDR (GFSK): High Channel




ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 17.MAY.2024 17:29:11

EDR ($\pi/4$ -DQPSK): Low Channel




ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 17.MAY.2024 17:45:15

EDR($\pi/4$ -DQPSK): Middle Channel




ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 17.MAY.2024 17:50:32

EDR ($\pi/4$ -DQPSK): High Channel




ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 17.MAY.2024 17:53:38

EDR (8DPSK): Low Channel




ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 17.MAY.2024 18:50:29

EDR (8DPSK): Middle Channel



ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 17.MAY.2024 18:55:32

EDR (8DPSK): High Channel




ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 17.MAY.2024 18:57:38

QUANTITY OF HOPPING CHANNEL TEST

EUT operation mode: Hopping


Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15

BDR (GFSK): Number of Hopping Channels




ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 18.MAY.2024 11:19:23

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



ProjectNo.:RKSA240319001 Tester:Loki Shi
 Date: 18.MAY.2024 11:16:58

EDR (8DPSK): Number of Hopping Channels




ProjectNo.:RKSA240319001 Tester:Loki Shi
 Date: 18.MAY.2024 11:23:41

TIME OF OCCUPANCY (DWELL TIME)

EUT operation mode: Hopping


Mode		Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
BDR (GFSK)	DH1	Middle	0.407	0.130	0.4	Pass
		Note: DH1: Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH3	Middle	1.672	0.268	0.4	Pass
		Note: DH3: Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH5	Middle	2.942	0.314	0.4	Pass
		Note: DH5: Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ($\pi/4$ -DQPSK)	2DH1	Middle	0.413	0.132	0.4	Pass
		Note: 2DH1: Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH3	Middle	1.669	0.267	0.4	Pass
		Note: 2DH3: Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH5	Middle	2.942	0.314	0.4	Pass
		Note: 2DH5: Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH1	Middle	0.414	0.132	0.4	Pass
		Note: 3 DH1: Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH3	Middle	1.669	0.267	0.4	Pass
		Note: 3DH3: Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH5	Middle	2.947	0.314	0.4	Pass
		Note: 3DH5: Dwell time = Pulse time*(1600/6/79)*31.6S				

BDR (GFSK): Pulse time, Middle Channel, DH1




ProjectNo.:RKSA240319001 Tester:Jay Liu
Date: 24.JUN.2024 14:18:47

BDR (GFSK): Pulse time, Middle Channel, DH3




ProjectNo.:RKSA240319001 Tester:Jay Liu
Date: 24.JUN.2024 14:19:38

BDR (GFSK): Pulse time, Middle Channel, DH5




ProjectNo.:RKSA240319001 Tester:Jay Liu
Date: 24.JUN.2024 14:20:25

EDR ($\pi/4$ -DQPSK): Pulse time, Middle Channel, 2DH1




ProjectNo.:RKSA240319001 Tester:Jay Liu
 Date: 24.JUN.2024 14:21:24

EDR ($\pi/4$ -DQPSK): Pulse time, Middle Channel, 2DH3




ProjectNo.:RKSA240319001 Tester:Jay Liu
 Date: 24.JUN.2024 14:30:40

EDR ($\pi/4$ -DQPSK): Pulse time, Middle Channel, 2DH5




ProjectNo.:RKSA240319001 Tester:Jay Liu
 Date: 24.JUN.2024 14:23:15

EDR (8DPSK): Pulse time, Middle Channel, 3DH1




ProjectNo.:RKSA240319001 Tester:Jay Liu
 Date: 24.JUN.2024 14:24:05

EDR (8DPSK): Pulse time, Middle Channel, 3DH3



ProjectNo.:RKSA240319001 Tester:Jay Liu
 Date: 24.JUN.2024 14:32:17

EDR (8DPSK): Pulse time, Middle Channel, 3DH5




ProjectNo.:RKSA240319001 Tester:Jay Liu
 Date: 24.JUN.2024 14:33:02

PEAK OUTPUT POWER MEASUREMENT*EUT operation mode: Transmitting*


Mode	Channel	Frequency (MHz)	Result (dBm)	Limit (dBm)
GFSK	Low	2402	-3.34	21
	Middle	2441	-2.91	
	High	2480	-3.76	
$\pi/4$ DQPSK	Low	2402	-1.41	
	Middle	2441	-0.96	
	High	2480	-1.80	
8DPSK	Low	2402	-1.00	
	Middle	2441	-0.71	
	High	2480	-1.40	

BDR (GFSK): 2402MHz



ProjectNo.:RKSA240319001 Tester:Jay Liu
Date: 29.MAY.2024 15:16:36

BDR (GFSK): 2441MHz



ProjectNo.:RKSA240319001 Tester:Jay Liu
Date: 29.MAY.2024 15:17:36

Ref 20 dBm *Att 20 dB SWT 2.5 ms 2.480048077 GHz

20 Offset 20.5 dB

10

0

-10

-20

-30

-40

-50

-60

-70

-80

Center 2.48 GHz 1 MHz/ Span 10 MHz

*RBW 3 MHz

*VBW 10 MHz

Marker 1 [T1] -3.76 dBm


1 PR

30000

3dB


LVL

EDR($\pi/4$ -DQPSK): 2402MHz




Page 67 of 78

EDR($\pi/4$ -DQPSK): 2441MHz




ProjectNo.:RKSA240319001 Tester:Jay Liu
Date: 29.MAY.2024 15:20:58

EDR($\pi/4$ -DQPSK): 2480MHz




ProjectNo.:RKSA240319001 Tester:Jay Liu
Date: 29.MAY.2024 15:19:51

EDR(8DPSK): 2402MHz




ProjectNo.:RKSA240319001 Tester:Jay Liu
Date: 29.MAY.2024 15:24:33

EDR(8DPSK): 2441MHz



ProjectNo.:RKSA240319001 Tester:Jay Liu
Date: 29.MAY.2024 15:25:22

EDR(8DPSK): 2480MHz




ProjectNo.:RKSA240319001 Tester:Jay Liu
Date: 29.MAY.2024 15:26:14

BAND EDGES*EUT operation mode: Transmitting & Hopping**Test Result: Compliant.*

Mode	Channel	Frequency (MHz)	Result (dBc)	Limit (dBc)
GFSK	Low	2402	38.24	20
	High	2480	38.63	
$\pi/4$ DQPSK	Low	2402	38.72	
	High	2480	39.14	
8DPSK	Low	2402	38.20	
	High	2480	39.08	
GFSK (Hopping)	Low	2402	38.96	
	High	2480	38.58	
$\pi/4$ DQPSK (Hopping)	Low	2402	38.78	
	High	2480	39.47	
8DPSK (Hopping)	Low	2402	39.40	
	High	2480	38.87	


Band Edge

BDR (GFSK): Left Side - Transmitting




ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 17.MAY.2024 17:22:30

BDR (GFSK): Right Side - Transmitting




ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 17.MAY.2024 17:33:18

EDR ($\pi/4$ -DQPSK): Left Side - Transmitting



ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 17.MAY.2024 17:48:07

EDR ($\pi/4$ -DQPSK): Right Side - Transmitting



ProjectNo.:RKSA240319001 Tester:Loki Shi
Date: 17.MAY.2024 17:57:46