

FCC Part 15C Measurement and Test Report

For

ShenZhen Foscam Intelligent Technology Co., Limited

**Room A, 9/F, Block F5, TCL International E City, No. 1001 Zhongshanyuan
Road, Xili, Shenzhen, China**

FCC ID: ZDEG2

FCC Rule(s):	<u>FCC Part 15C</u>
Product Description:	<u>Outdoor HD IP Camera</u>
Tested Model:	<u>G2</u>
Report No.:	<u>STRD1805169I</u>
Sample Receipt Date:	<u>2018-06-13</u>
Tested Date:	<u>2018-06-14 to 2018-06-27</u>
Issued Date:	<u>2018-06-28</u>
Tested By:	<u>Mike Shi / Engineer</u>
Reviewed By:	<u>Silin Chen / EMC Manager</u>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u>
Prepared By:	

Mike Shi

Silin Chen

Jandy So

Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,

Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND TEST MODE.....	6
1.6 MEASUREMENT UNCERTAINTY.....	6
1.7 TEST EQUIPMENT LIST AND DETAILS.....	7
2. SUMMARY OF TEST RESULTS.....	8
3. RF EXPOSURE.....	9
3.1 STANDARD APPLICABLE.....	9
3.2 TEST RESULT.....	9
4. ANTENNA REQUIREMENT.....	10
4.1 STANDARD APPLICABLE.....	10
4.2 EVALUATION INFORMATION.....	10
5. POWER SPECTRAL DENSITY.....	11
5.1 STANDARD APPLICABLE.....	11
5.2 TEST PROCEDURE.....	11
5.3 ENVIRONMENTAL CONDITIONS.....	11
5.4 SUMMARY OF TEST RESULTS/PLOTS.....	12
6. 6DB BANDWIDTH.....	19
6.1 STANDARD APPLICABLE.....	19
6.2 TEST PROCEDURE.....	19
6.3 ENVIRONMENTAL CONDITIONS.....	19
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	19
7. RF OUTPUT POWER.....	26
7.1 STANDARD APPLICABLE.....	26
7.2 TEST PROCEDURE.....	26
7.3 ENVIRONMENTAL CONDITIONS.....	26
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	27
8. FIELD STRENGTH OF SPURIOUS EMISSIONS.....	34
8.1 STANDARD APPLICABLE.....	34
8.2 TEST PROCEDURE.....	34
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	35
8.4 ENVIRONMENTAL CONDITIONS.....	35
8.5 SUMMARY OF TEST RESULTS/PLOTS.....	36
9. OUT OF BAND EMISSIONS.....	43
9.1 STANDARD APPLICABLE.....	43
9.2 TEST PROCEDURE.....	43
9.3 ENVIRONMENTAL CONDITIONS.....	44
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	44
10. CONDUCTED EMISSIONS.....	64
10.1 TEST PROCEDURE.....	64
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....	64
10.3 ENVIRONMENTAL CONDITIONS.....	64
10.4 TEST RECEIVER SETUP.....	65
10.5 SUMMARY OF TEST RESULTS/PLOTS.....	65
10.6 CONDUCTED EMISSIONS TEST DATA.....	65

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: ShenZhen Foscam Intelligent Technology Co., Limited
Address of applicant: Room A, 9/F, Block F5, TCL International E City, No.
1001 Zhongshanyuan Road, Xili, Shenzhen, China

Manufacturer: ShenZhen Foscam Intelligent Technology Co., Limited
Address of manufacturer: Room A, 9/F, Block F5, TCL International E City, No.
1001 Zhongshanyuan Road, Xili, Shenzhen, China

General Description of EUT	
Product Name:	Outdoor HD IP Camera
Trade Name:	FOSCAM
Model No.:	G2
Adding Model(s):	G2VX、G2C VX、G2E VX、G2 Plus VX、G2 Lite VX、G4 VX、G4C VX、G4E VX、G4 Plus VX、G4 Lite VX、FI9900P VX、FI9900EP VX、FI9901P VX、FI9901EP VX、FI9902P VX、FC5415P VX、FC5618P VX、FC5618EP VX、FC5718EP VX (which “X” can be from 0 to 9,the default state is null while it is V0)
Rated Voltage:	Power Port:DC12V
Battery:	/
Power Adapter Model:	Model:SAW12F-120-1000U Input:100~240V 50/60Hz 0.5A Output:DC12V,1000mA
<i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model G2, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
RF Output Power:	9.66dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation:	5MHz
Type of Antenna:	External Antenna
Antenna Gain:	2.0dBi
Lowest Internal Frequency:	24MHz

1.2 Test Standards

The following report is prepared on behalf of the ShenZhen Foscam Intelligent Technology Co., Limited in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 v04 for digital transmission systems shall be performed also.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	2412MHz, 2437MHz, 2462MHz
TM2	802.11g	2412MHz, 2437MHz, 2462MHz
TM3	802.11n-HT20	2412MHz, 2437MHz, 2462MHz
TM4	802.11n-HT40	2422MHz, 2437MHz, 2452MHz
Note: All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.		

Accessories Equipment List and Details			
Description	Manufacturer	Model No.	Serial Number
Notebook	Lenovo	ThinkPad Edge E445	/
Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
Network cable1	5	Shielded	Without Core
Network cable2	1.5	Unshielded	Without Core
Network cable3	1.5	Shielded	Without Core
EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
DC Cable	1.5	Unshielded	Without Core

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2018-05-22	2019-05-21
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2018-05-22	2019-05-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2018-05-22	2019-05-21
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2018-05-22	2019-05-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2018-05-22	2019-05-21
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2020-06-07
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2018-05-22	2019-05-21
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2018-05-22	2019-05-21
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2018-05-22	2019-05-21
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2018-05-22	2019-05-21
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2018-05-22	2019-05-21
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2018-05-22	2019-05-21
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2018-03-19	2021-03-18
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2018-05-22	2019-05-21
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2018-05-22	2019-05-21
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2018-05-22	2019-05-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2018-03-19	2019-03-18
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2018-03-19	2019-03-18
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2018-03-19	2019-03-18
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2018-03-19	2019-03-18
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	6 dB Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has a detachable special antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure

According to the KDB 558074 D01 v04, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

5.3 Environmental Conditions


Temperature:	24° C
Relative Humidity:	56%
ATM Pressure:	1011 mbar

5.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b	2412	-22.91	8
	2437	-22.84	8
	2462	-21.19	8
802.11g	2412	-28.43	8
	2437	-28.09	8
	2462	-27.83	8
802.11n HT20	2412	-26.20	8
	2437	-25.62	8
	2462	-24.47	8
802.11n HT40	2422	-28.91	8
	2437	-28.82	8
	2452	-28.30	8

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



6. 6dB Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 Environmental Conditions


Temperature:	24° C
Relative Humidity:	56%
ATM Pressure:	1018 mbar

6.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	6 dB Bandwidth MHz	99% Bandwidth MHz	Limit kHz
802.11b	2412	10.093	12.1931	≥ 500
	2437	10.086	12.1818	≥ 500
	2462	10.084	12.1789	≥ 500
802.11g	2412	16.580	16.4885	≥ 500
	2437	16.564	16.4710	≥ 500
	2462	16.617	16.5320	≥ 500
802.11n-HT20	2412	17.732	17.5695	≥ 500
	2437	17.636	17.5674	≥ 500
	2462	17.636	17.5715	≥ 500
802.11n-HT40	2422	36.468	36.1072	≥ 500
	2437	36.530	36.1608	≥ 500
	2452	36.511	36.1596	≥ 500

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel





802.11n-HT20-High Channel



802.11n-HT40-Low Channel





7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure

According to the KDB-558074 D01 v04, 9.2.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This gives bin-to-bin spacing $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

7.3 Environmental Conditions


Temperature:	24° C
Relative Humidity:	56%
ATM Pressure:	1011 mbar

7.4 Summary of Test Results/Plots


Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b _ 11Mbps	2412	9.48	8.87	1000
	2437	9.66	9.25	1000
	2462	9.37	8.65	1000
802.11g_54Mbps	2412	8.98	7.91	1000
	2437	9.01	7.96	1000
	2462	8.88	7.73	1000
802.11n HT20_MCS7	2412	8.53	7.13	1000
	2437	8.38	6.89	1000
	2462	8.30	6.76	1000
802.11n HT40_MCS7	2422	7.95	6.24	1000
	2437	7.27	5.33	1000
	2452	7.97	6.27	1000

Please refer to the following test plots:


802.11b-11Mbps-Low Channel




802.11b -11Mbps-Middle Channel




802.11b -11Mbps-High Channel




802.11g-54Mbps-Low Channel




802.11g-54Mbps-Middle Channel




802.11g-54Mbps-High Channel




802.11n-HT20-MCS7-Low Channel




802.11n-HT20-MCS7-Middle Channel




802.11n-HT20-MCS7-High Channel




802.11n-HT40-MCS7-Low Channel



802.11n-HT40-MCS7-Middle Channel



802.11n-HT40-MCS7-High Channel



8. Field Strength of Spurious Emissions

8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=360KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56%
ATM Pressure:	1012 mbar

8.5 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: Outdoor HD IP Camera

Tested Model: G2

Operating Condition: 802.11b Transmitting Low Channel-2412MHz(worst case)


Comment: AC120V 60Hz

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	45.8553	35.64	-18.57	17.07	40.00	-22.93	249	100	peak
2	109.7960	36.61	-17.98	18.63	43.50	-24.87	93	100	peak
3	218.3085	34.51	-14.11	20.40	46.00	-25.60	252	100	peak
4	324.4561	32.15	-8.09	24.06	46.00	-21.94	94	100	peak
5	597.2234	27.98	-3.06	24.92	46.00	-21.08	216	100	peak
6	744.8661	29.47	-2.59	26.88	46.00	-19.12	208	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	53.1313	45.14	-18.48	26.66	40.00	-13.34	360	100	peak
2	111.7380	50.75	-17.97	32.78	43.50	-10.72	95	100	peak
3	239.9874	41.44	-11.91	29.53	46.00	-16.47	201	100	peak
4	432.5457	38.01	-8.27	29.74	46.00	-16.26	119	100	peak
5	541.3725	34.09	-7.36	26.73	46.00	-19.27	150	100	peak

Operating Condition: 802.11b Transmitting Middle Channel-2437MHz(worst case)


Comment: AC120V 60Hz

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	54.2610	35.01	-18.44	16.57	40.00	-23.43	335	100	peak
2	110.5687	36.94	-17.98	18.96	43.50	-24.54	162	100	peak
3	218.3085	34.91	-14.11	20.80	46.00	-25.20	91	100	peak
4	324.4561	32.47	-8.09	24.38	46.00	-21.62	93	100	peak
5	601.4265	27.46	-2.66	24.80	46.00	-21.20	320	100	peak
6	938.8326	30.72	-4.23	26.49	46.00	-19.51	115	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	58.8185	45.04	-18.25	26.79	40.00	-13.21	337	100	peak
2	111.7380	50.75	-17.97	32.78	43.50	-10.72	125	100	peak
3	167.8243	47.13	-19.69	27.44	43.50	-16.06	74	100	peak
4	236.6447	40.22	-12.21	28.01	46.00	-17.99	114	100	peak
5	432.5457	38.11	-8.27	29.84	46.00	-16.16	219	100	peak
6	938.8326	31.46	-4.23	27.23	46.00	-18.77	231	100	peak

Operating Condition: 802.11b Transmitting High Channel-2462MHz(worst case)


Comment: AC120V 60Hz

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	52.0251	35.15	-18.52	16.63	40.00	-23.37	86	100	peak
2	110.9571	36.64	-17.97	18.67	43.50	-24.83	135	100	peak
3	245.9509	31.63	-11.54	20.09	46.00	-25.91	95	100	peak
4	379.9141	32.22	-8.47	23.75	46.00	-22.25	144	100	peak
5	747.4826	29.50	-2.71	26.79	46.00	-19.21	143	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	44.4308	41.23	-18.55	22.68	40.00	-17.32	256	100	peak
2	58.8185	45.99	-18.25	27.74	40.00	-12.26	309	100	peak
3	111.3468	50.45	-17.96	32.49	43.50	-11.01	67	100	peak
4	237.4760	41.21	-12.14	29.07	46.00	-16.93	293	100	peak
5	377.2591	37.32	-8.43	28.89	46.00	-17.11	123	100	peak
6	541.3725	34.32	-7.36	26.96	46.00	-19.04	285	100	peak

Spurious Emissions Above 1GHz

Test Mode: 802.11b (worst case)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	56.12	-3.87	52.25	74	-21.75	H	PK
4824.000	40.74	-3.87	36.87	54	-17.13	H	AV
7236.000	59.34	1.14	60.48	74	-13.52	H	PK
7236.000	40.48	1.19	41.67	54	-12.33	H	AV
4824.000	60.88	-3.86	57.02	74	-16.98	V	PK
4824.000	49.01	-3.86	45.15	54	-8.85	V	AV
7236.000	59.40	1.10	60.50	74	-13.50	V	PK
7236.000	45.56	1.10	46.66	54	-7.34	V	AV
Middle Channel-2437MHz							
4874.000	60.06	-3.74	56.32	74	-17.68	H	PK
4874.000	43.51	-3.74	39.77	54	-14.23	H	AV
7311.000	58.03	1.47	59.50	74	-14.50	H	PK
7311.000	41.55	1.47	43.02	54	-10.98	H	AV
4874.000	62.60	-3.74	58.86	74	-15.14	V	PK
4874.000	50.42	-3.74	46.68	54	-7.32	V	AV
7311.000	63.23	1.47	64.70	74	-9.30	V	PK
7311.000	41.55	1.47	43.02	54	-10.98	V	AV
High Channel-2462MHz							
4924.000	53.82	-3.59	50.23	74	-23.77	H	PK
4924.000	39.54	-3.59	35.95	54	-18.05	H	AV
7386.000	56.56	1.79	58.35	74	-15.65	H	PK
7386.000	40.75	1.79	42.54	54	-11.46	H	AV
4924.000	64.64	-3.59	61.05	74	-12.95	V	PK
4924.000	47.80	-3.59	44.21	54	-9.79	V	AV
7386.000	64.33	1.79	66.12	74	-7.88	V	PK
7386.000	43.27	1.79	45.06	54	-8.94	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074D01 v04, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 v04, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW $\geq$ 300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.


9.3 Environmental Conditions

Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

802.11b-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	39.13	-5.28	33.85	54.00	-20.15	Average Detector
	2310.000	52.19	-5.28	46.91	74.00	-27.09	Peak Detector
2	2390.000	38.16	-6.12	32.04	54.00	-21.96	Average Detector
	2390.000	55.91	-6.12	49.79	74.00	-24.21	Peak Detector
3	2414.625	97.97	-6.25	91.72	/	/	Average Detector
	2410.500	108.84	-6.25	102.59	/	/	Peak Detector

802.11b-Highest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2464.550	105.29	-6.13	99.16	/	/	Average Detector
	2463.250	110.15	-6.13	104.02	/	/	Peak Detector
2	2483.500	45.94	-6.08	39.86	54.00	-14.14	Average Detector
	2483.500	56.53	-6.08	50.45	74.00	-23.55	Peak Detector
3	2500.000	38.23	-6.04	32.19	54.00	-21.81	Average Detector
	2500.000	50.63	-6.04	44.59	74.00	-29.41	Peak Detector

802.11g-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	38.55	-5.28	33.27	54.00	-20.73	Average Detector
	2310.000	52.25	-5.28	46.97	74.00	-27.03	Peak Detector
2	2390.000	51.88	-6.12	45.76	54.00	-8.24	Average Detector
	2390.000	72.05	-6.12	65.93	74.00	-8.07	Peak Detector
3	2419.000	97.43	-6.23	91.20	/	/	Average Detector
	2418.250	107.78	-6.23	101.55	/	/	Peak Detector

802.11g-Highest Bandedge


Vertical (Worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2468.650	109.41	-6.11	103.30	/	/	Average Detector
	2469.000	99.44	-6.11	93.33	/	/	Peak Detector
2	2483.500	74.64	-6.08	68.56	74.00	-5.44	Average Detector
	2483.500	55.65	-6.08	49.57	54.00	-4.43	Peak Detector
3	2500.000	55.60	-6.04	49.56	74.00	-24.44	Average Detector
	2500.000	40.49	-6.04	34.45	54.00	-19.55	Peak Detector

802.11n-HT20-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	38.57	-5.28	33.29	54.00	-20.71	Average Detector
	2310.000	50.45	-5.28	45.17	74.00	-28.83	Peak Detector
2	2390.000	54.38	-6.12	48.26	54.00	-5.74	Average Detector
	2390.000	78.29	-6.12	72.17	74.00	-1.83	Peak Detector
3	2418.875	97.18	-6.23	90.95	/	/	Average Detector
	2419.250	107.81	-6.23	101.58	/	/	Peak Detector

802.11n-HT20-Highest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2468.850	97.10	-6.11	90.99	/	/	Average Detector
	2469.100	107.79	-6.11	101.68	/	/	Peak Detector
2	2483.500	55.26	-6.08	49.18	54.00	-4.82	Average Detector
	2483.500	76.31	-6.08	70.23	74.00	-3.77	Peak Detector
3	2500.000	38.92	-6.04	32.88	54.00	-21.12	Average Detector
	2500.000	51.10	-6.04	45.06	74.00	-28.94	Peak Detector

802.11n-HT40-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	41.60	-5.28	36.32	54.00	-17.68	Average Detector
	2310.000	51.65	-5.28	46.37	74.00	-27.63	Peak Detector
2	2390.000	58.36	-6.12	52.24	54.00	-1.76	Average Detector
	2390.000	76.78	-6.12	70.66	74.00	-3.34	Peak Detector
3	2420.160	93.50	-6.23	87.27	/	/	Average Detector
	2419.620	105.81	-6.23	99.58	/	/	Peak Detector

802.11n-HT40-Highest Bandedge

Vertical (Worst case)





No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2436.020	94.09	-6.19	87.90	/	/	Average Detector
	2436.230	104.75	-6.19	98.56	/	/	Peak Detector
2	2483.500	57.28	-6.08	51.20	54.00	-2.80	Average Detector
	2483.500	72.09	-6.08	66.01	74.00	-7.99	Peak Detector
3	2500.000	47.17	-6.04	41.13	54.00	-12.87	Average Detector
	2500.000	65.95	-6.04	59.91	74.00	-14.09	Peak Detector



Spurious (Conducted)

802.11b-Lowest



Lowest



Middle





Highest





Spurious (Conducted)

802.11g-Lowest



Lowest





Middle





Highest





Spurious (Conducted)
802.11n-HT20-Lowest
Lowest





Middle





Highest





Spurious (Conducted)
802.11n-HT40-Lowest
Lowest



Middle



Highest




10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram



10.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

10.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150 kHz
Stop Frequency	30 MHz
Sweep Speed	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal

10.5 Summary of Test Results/Plots

According to the data in section 10.6, the EUT complied with the FCC Part 15.207 Conducted margin for this device, with the *worst* margin reading of:


2.96 dB at 0.1740 MHz in the Neutral mode, QP detector, 0.15-30MHz

10.6 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: Outdoor HD IP Camera
 Tested Model: G2
 Operating Condition: Transmitting(Wi-Fi)
 Comment: AC 120V/60Hz;

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1580	20.90	10.10	31.00	55.57	-24.57	AVG
2*	0.1740	51.70	10.11	61.81	64.77	-2.96	QP
3	0.3860	36.95	10.24	47.19	58.15	-10.96	QP
4	0.4300	24.98	10.26	35.24	47.25	-12.01	AVG
5	15.9060	32.84	11.05	43.89	60.00	-16.11	QP
6	15.9060	20.91	11.05	31.96	50.00	-18.04	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1740	51.21	10.11	61.32	64.77	-3.45	QP
2	0.1820	19.58	10.11	29.69	54.39	-24.70	AVG
3	0.4220	36.18	10.26	46.44	57.41	-10.97	QP
4	0.4260	22.62	10.26	32.88	47.33	-14.45	AVG
5	15.8980	31.13	11.05	42.18	60.00	-17.82	QP
6	15.8980	22.20	11.05	33.25	50.00	-16.75	AVG

***** END OF REPORT *****