



Radio Test Report

Report No.: STS2509162W07

Issued for

Buddi Limited

Talbot House, 17 Church Street, Rickmansworth, WD3 1DE,
Hertfordshire, UK

Product Name: Alco Tag

Brand Name: Buddi Limited

Model Name: A2-BUD-A-TENX-B-TEEU-BS

Series Model(s): 4000003

FCC ID: ZDLST8

Test Standards: FCC Part 15.249

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT**

Applicant's Name : Buddi Limited
Address : Talbot House, 17 Church Street, Rickmansworth, WD3 1DE,
Hertfordshire, UK
Manufacturer's Name : Buddi Limited
Address : Talbot House, 17 Church Street, Rickmansworth, WD3 1DE,
Hertfordshire, UK

Product Description

Product Name : Smart Beacon V2.2
Brand Name : Buddi Limited
Model Name : A2-BUD-A-TENX-B-TEEU-BS
Series Model(s) : 4000003
Test Standards : FCC Part15.249
Test Procedure : ANSI C63.10-2020

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test :
Date of receipt of test item : 24 Sept. 2025
Date of performance of tests . : 24 Sept. 2025 ~ 30 Sept. 2025
Date of Issue : 30 Sept. 2025
Test Result : **Pass**

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Skylar Li

(Skylar Li)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





Table of Contents

Page

1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACTORY	6
1.2 MEASUREMENT UNCERTAINTY	6
2. GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF THE EUT	7
2.2 DESCRIPTION OF THE TEST MODES	9
2.3 TEST SOFTWARE AND POWER LEVEL	9
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	10
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3. EMC EMISSION TEST	12
3.1 CONDUCTED EMISSION MEASUREMENT	12
3.2 RADIATED EMISSION MEASUREMENT	14
4. ANTENNA REQUIREMENT	38
4.1 STANDARD REQUIREMENT	38
4.2 EUT ANTENNA	38
APPENDIX- PHOTOS OF TEST SETUP	39

**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	07 Sept. 2023	STS2308302W03	ALL	Initial Issue
00	30 Sept. 2025	STS2509162W07	ALL	Update the model, product name, appearance and radiated emission



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part 15.249 , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	
15.203	Antenna Requirement	PASS	
15.249	Radiated Spurious Emission	PASS	
15.249	Radiated Band Edge Emission	PASS	
15.249	Field Strength of fundamental	PASS	
15.215°C	20dB Bandwidth	N/A	

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2020.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	Unwanted Emissions, conducted	$\pm 2.874\text{dB}$
2	All emissions, radiated 9K-30MHz	$\pm 3.80\text{dB}$
3	All emissions, radiated 30M-1GHz	$\pm 4.18\text{dB}$
4	All emissions, radiated 1G-6GHz	$\pm 4.90\text{dB}$
5	All emissions, radiated >6G	$\pm 5.24\text{dB}$
6	Conducted Emission (9KHz-150KHz)	$\pm 2.19\text{dB}$
7	Conducted Emission (150KHz-30MHz)	$\pm 2.53\text{dB}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Alco Tag	
Brand Name	Buddi Limited	
Model Name	A2-BUD-A-TENX-B-TEEU-BS	
Series Model(s)	4000003	
Model Difference	The difference only in the model name.	
Product Description	The EUT is a Alco Tag.	
	Operation Frequency:	914.5-921MHz
	Modulation Type:	ASK
	Antenna Designation:	Internal
	Antenna Gain(Peak):	0
	Based on the application, features, or specification exhibited in User Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User Manual.	
Adapter	OBC Dock: Input: 100-240V~47-63Hz 0.4A Output: DC 5.99V 2A max OBC charger: Input: DC 5.99V 2A Output: DC 5V, 800mA	
Battery	Main device battery: Rated Voltage: 3.7V Charge Limit Voltage: 4.2V Capacity: 1200mAh Charger OBC battery: Rated Voltage: 3.7V Charge Limit Voltage: 4.2V Capacity: 2300mAh	
Rating	Input: DC 5V, 800mA	
Connecting I/O Port(s)	Please refer to the Note 1.	
Hardware version number	V1.1	
Software version number	1.40.20	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
- 2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	914.50	2	917.50	3	921.00



3.

Test channel List		
Test Channel	EUT Channel	Test Frequency (MHz)
lowest	CH01	914.50
middle	CH02	917.50
highest	CH03	921.00

Note: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.

2.2 DESCRIPTION OF THE TEST MODES

For conducted test items and radiated spurious emissions
Each of these EUT operation mode(s) or test configuration mode(s) mentioned below was evaluated respectively.

Pretest Mode	Description	Data/Modulation
Mode 1	TX/CH01	ASK
Mode 2	TX/CH02	ASK
Mode 3	TX/CH03	ASK

Note:

(1) All above mode have been measurement, only worst data was reported.

2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
Other SRD	917.50 MHz	ASK	0	Default	The EUT has signal transmission when it is powered on

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters.

Radiated Spurious Emission Test





2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
N/A	N/A	N/A	N/A	N/A	N/A

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
N/A	N/A	N/A	N/A	N/A	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

RF Radiation Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Pre-Amplifier(0.1M-3GHz)	EM	EM330	060665	2025.02.22	2026.02.21
Pre-Amplifier(1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2025.09.25	2026.09.24
Pre-Amplifier(18G-40GHz)	SKET	LNPA_1840-50	SK2018101801	2025.02.22	2026.02.21
Active loop Antenna	ZHINAN	ZN30900C	16035	2025.02.25	2027.02.24
Bilog Antenna	TESEQ	CBL6111D	34678	2025.09.27	2027.09.26
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	2025.09.27	2027.09.26
Horn Antenna	A-INFOMW	LB-180400-KF	J211020657	2025.09.27	2027.09.26
Positioning Controller	MF	MF-7802	MF-780208587	N/A	N/A
Signal Analyzer	R&S	FSV 40-N	101823	2025.09.26	2026.09.25
Switch Control Box	N/A	N/A	N/A	N/A	N/A
Filter Box	BALUN Technology	SU319E	BL-SZ1530051	N/A	N/A
Antenna Mast	MF	MFA-440H	N/A	N/A	N/A
Turn Table	MF	SC100_1	60531	N/A	N/A
AC Power Source	APC	KDF-11010G	F214050035	N/A	N/A
DC power supply	HONGSHENG FENG	DPS-305AF	17064939	2025.09.22	2026.09.21
Test SW	EZ-EMC	Ver.STSLAB-03A1 RE			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “*” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support.

3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.5 TEST RESULT

Temperature:	--℃	Relative Humidity:	--%
Test Voltage:	N/A	Phase:	L/N
Test Mode:	N/A		

Note: Battery powered, not applicable.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part 15.249 and the Part 15.209(a) limit in the table below has to be followed.

Standard FCC 15.209

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3
Above 1000	Other:74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	3

Standard FCC 15.249

Frequency of Emission (MHz)	Field Strength of fundamental (millivolts /meter)	Field Strength of Harmonics (microvolts/meter)
900~928	50	500
2400~2483.5	50	500
5725~5875	50	500
24000~242500	250	2500

Notes:

- (1) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7



6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

Spectrum Parameter	Setting
Detector	Peak/AV
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB (emission in restricted band)	>20BW
VB (emission in restricted band)	=3xRB

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
	90kHz~110kHz / RB 200Hz for QP
	110kHz~490kHz / RB 200Hz for PK & AV
	490kHz~30MHz / RB 9kHz for QP
	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE


- a. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation (Below 1GHz)
- b. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation (Above 1GHz)
- c. The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- d. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform (Below 1GHz)
- f. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak & AVG limits and then only Peak mode was measured, but AVG mode didn't perform. (Above 1GHz)
- g. For the actual test configuration, please refer to the related Item –EUT Test Photos.
Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz





3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

Margin=PL-PK L or AL- AV L; Margin only shown the worst case.

Where

PR = Peak Reading

AR = Average Reading

PL = Peak Level

AL = Average Level

AF = Antenna Factor

PK L = Peak Limit

AV L = AV Limit

For example

Frequency	PR	AR	AF	PL	AL	PK L	AV L	Margin
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV/m)	(dBμV/m)	(dBμV/m)	(dB)
2178	40.23	30.31	9.83	50.06	40.14	74.00	54.00	-13.86



3.2.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

Below 30 MHz

Temperature:	23.1℃	Relative Humidity:	60%
Test Voltage:	DC 3.7V	Polarization:	---
Test Mode:	TX Mode		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})(\text{dB})$;

Limit line = specific limits(dBuv) + distance extrapolation factor.




Between 30MHz – 1000 MHz Radiation Spurious

Temperature:	23.1℃	Relative Humidity:	60%
Test Voltage:	DC 3.7V	Phase:	Horizontal
Test Mode:	Mode 1		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.9100	32.22	-14.33	17.89	40.00	-22.11	peak
2	109.5400	33.74	-19.11	14.63	43.50	-28.87	peak
3	418.0000	29.66	-10.18	19.48	46.00	-26.52	peak
4	618.7900	28.99	-5.49	23.50	46.00	-22.50	peak
5	755.5600	29.78	-2.17	27.61	46.00	-18.39	peak
6	976.7200	27.53	2.45	29.98	54.00	-24.02	peak

Remark:

1. Margin = Result (Result = Reading + Factor) – Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) – Amplifier gain






Temperature:	23.1℃	Relative Humidity:	60%
Test Voltage:	DC 3.7V	Phase:	Vertical
Test Mode:	Mode 1		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	34.8500	32.76	-15.34	17.42	40.00	-22.58	peak
2	125.4457	32.94	-18.22	14.72	43.50	-28.78	peak
3	401.5100	30.08	-11.06	19.02	46.00	-26.98	peak
4	614.9100	29.23	-5.49	23.74	46.00	-22.26	peak
5	826.3700	29.22	-1.19	28.03	46.00	-17.97	peak
6	992.2400	29.26	2.05	31.31	54.00	-22.69	peak

Remark:

1. $\text{Margin} = \text{Result} (\text{Result} = \text{Reading} + \text{Factor}) - \text{Limit}$
2. $\text{Factor} = \text{Antenna factor} + \text{Cable attenuation factor} (\text{cable loss}) - \text{Amplifier gain}$





Temperature:	23.1℃	Relative Humidity:	60%
Test Voltage:	DC 3.7V	Phase:	Horizontal
Test Mode:	Mode 2		


No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	33.5623	32.84	-14.64	18.20	40.00	-21.80	peak
2	101.2883	33.64	-20.00	13.64	43.50	-29.86	peak
3	413.1500	29.78	-10.42	19.36	46.00	-26.64	peak
4	599.3900	29.03	-5.84	23.19	46.00	-22.81	peak
5	733.2500	30.10	-2.35	27.75	46.00	-18.25	peak
6	951.5000	29.96	1.62	31.58	46.00	-14.42	peak

Remark:

3. Margin = Result (Result = Reading + Factor) - Limit

4. Factor = Antenna factor + Cable attenuation factor (cable loss) - Amplifier gain

100.0 dBuV/m





Temperature:	23.1℃	Relative Humidity:	60%
Test Voltage:	DC 3.7V	Phase:	Vertical
Test Mode:	Mode 2		


No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.7486	32.76	-14.25	18.51	40.00	-21.49	peak
2	120.2766	33.55	-18.35	15.20	43.50	-28.30	peak
3	403.4500	29.48	-10.95	18.53	46.00	-27.47	peak
4	486.8700	29.57	-8.36	21.21	46.00	-24.79	peak
5	733.2500	28.52	-2.35	26.17	46.00	-19.83	peak
6	977.6900	27.80	2.52	30.32	54.00	-23.68	peak

Remark:

3. Margin = Result (Result =Reading + Factor)-Limit

4. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain

100.0 dBuV/m






Temperature:	23.1℃	Relative Humidity:	60%
Test Voltage:	DC 3.7V	Phase:	Horizontal
Test Mode:	Mode 3		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.2924	32.93	-14.03	18.90	40.00	-21.10	peak
2	335.5500	29.62	-13.54	16.08	46.00	-29.92	peak
3	453.8900	30.76	-9.59	21.17	46.00	-24.83	peak
4	558.6500	28.39	-5.52	22.87	46.00	-23.13	peak
5	733.2500	30.17	-2.35	27.82	46.00	-18.18	peak
6	985.4500	28.51	2.33	30.84	54.00	-23.16	peak

Remark:

5. Margin = Result (Result =Reading + Factor)-Limit

6. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain





Temperature:	23.1℃	Relative Humidity:	60%
Test Voltage:	DC 3.7V	Phase:	Vertical
Test Mode:	Mode 3		


No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	35.1278	34.01	-15.50	18.51	40.00	-21.49	peak
2	120.2100	33.28	-18.35	14.93	43.50	-28.57	peak
3	482.0200	29.27	-8.57	20.70	46.00	-25.30	peak
4	616.8500	29.38	-5.49	23.89	46.00	-22.11	peak
5	744.8900	28.78	-2.13	26.65	46.00	-19.35	peak
6	921.4300	30.54	0.06	30.60	46.00	-15.40	peak

Remark:

5. Margin = Result (Result =Reading + Factor)-Limit

6. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain

100.0 dBuV/m






Above 1G Radiation Spurious

Temperature:	23.4°C	Relative Humidity:	60%
Test Mode:	Mode 1	Phase:	Horizontal
Describe:	Low		

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1200.000	40.17	28.60	-1.21	74.0	54.0	-25.40	95.10	100	Horizontal	Pass
2948.000	47.25	36.57	5.88	74.0	54.0	-17.43	327.50	100	Horizontal	Pass
4826.000	45.69	40.34	-6.83	74.0	54.0	-13.66	258.00	100	Horizontal	Pass
6962.000	50.69	39.64	0.50	74.0	54.0	-14.36	182.00	100	Horizontal	Pass
10121.250	60.34	49.63	7.17	74.0	54.0	-4.37	3.80	100	Horizontal	Pass
16627.750	62.47	50.95	10.05	74.0	54.0	-3.05	1.10	100	Horizontal	Pass



Temperature:	23.4°C	Relative Humidity:	60%
Test Mode:	Mode 1	Phase:	Vertical
Describe:	Low		

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1379.000	40.91	29.64	-0.72	74.0	54.0	-24.36	273.50	100	Vertical	Pass
2977.500	47.62	36.68	6.01	74.0	54.0	-17.32	24.60	100	Vertical	Pass
4826.000	52.10	49.27	-6.83	74.0	54.0	-4.73	0.30	100	Vertical	Pass
8724.250	57.87	47.38	5.08	74.0	54.0	-6.62	165.70	100	Vertical	Pass
10932.500	62.01	50.54	9.70	74.0	54.0	-3.46	206.10	100	Vertical	Pass
14405.750	62.15	51.89	11.36	74.0	54.0	-2.11	110.40	100	Vertical	Pass



Temperature:	23.4°C	Relative Humidity:	60%
Test Mode:	Mode 2	Phase:	Horizontal
Describe:	Middle		

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1304.500	40.42	29.32	-0.92	74.0	54.0	-24.68	23.30	100	Horizontal	Pass
2826.500	47.33	35.72	5.45	74.0	54.0	-18.28	357.10	100	Horizontal	Pass
4041.000	41.84	30.62	-10.06	74.0	54.0	-23.38	209.70	100	Horizontal	Pass
4876.000	46.35	41.54	-6.53	74.0	54.0	-12.46	149.90	100	Horizontal	Pass
7313.500	56.79	49.75	3.35	74.0	54.0	-4.25	65.90	100	Horizontal	Pass
14243.500	62.11	51.73	11.26	74.0	54.0	-2.27	278.00	100	Horizontal	Pass



Temperature:	23.4°C	Relative Humidity:	60%
Test Mode:	Mode 2	Phase:	Vertical
Describe:	Middle		

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1206.500	40.79	28.70	-1.17	74.0	54.0	-25.30	28.40	100	Vertical	Pass
1878.500	45.43	39.10	0.81	74.0	54.0	-14.90	193.20	100	Vertical	Pass
2986.500	47.74	36.97	6.05	74.0	54.0	-17.03	139.10	100	Vertical	Pass
4876.000	52.10	49.40	-6.53	74.0	54.0	-4.60	343.20	100	Vertical	Pass
11023.250	61.88	51.34	10.09	74.0	54.0	-2.66	108.10	100	Vertical	Pass
17098.000	62.75	51.72	10.47	74.0	54.0	-2.28	311.80	100	Vertical	Pass



Temperature:	23.4°C	Relative Humidity:	60%
Test Mode:	Mode 3	Phase:	Horizontal
Describe:	High		

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1251.500	40.29	29.15	-0.91	74.0	54.0	-24.85	228.50	100	Horizontal	Pass
2974.000	47.24	36.60	6.00	74.0	54.0	-17.40	157.80	100	Horizontal	Pass
3425.000	49.67	42.43	-11.63	74.0	54.0	-11.57	248.70	100	Horizontal	Pass
4929.000	50.48	47.46	-6.39	74.0	54.0	-6.54	29.20	100	Horizontal	Pass
7393.250	57.64	50.36	3.00	74.0	54.0	-3.64	62.90	100	Horizontal	Pass
17098.000	62.10	51.59	10.47	74.0	54.0	-2.41	41.30	100	Horizontal	Pass



Temperature:	23.4°C	Relative Humidity:	60%
Test Mode:	Mode 3	Phase:	Vertical
Describe:	High		

RE_FCC Test Case_FCC 15C 1GHz-18GHz




Frequency (MHz)	Peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Table (o)	Height (cm)	ANT	Verdict
1336.500	40.84	29.28	-0.83	74.0	54.0	-24.72	286.40	100	Vertical	Pass
1970.500	46.92	42.39	1.22	74.0	54.0	-11.61	61.80	100	Vertical	Pass
2894.000	47.36	36.56	5.61	74.0	54.0	-17.44	105.90	100	Vertical	Pass
4929.000	51.27	47.92	-6.39	74.0	54.0	-6.08	36.60	100	Vertical	Pass
10990.250	61.65	51.37	10.14	74.0	54.0	-2.63	191.40	100	Vertical	Pass
15338.000	63.01	51.61	10.35	74.0	54.0	-2.39	40.20	100	Vertical	Pass



(Radiation Band edge)

914.5MHz

Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	897.9220	31.07	-0.50	30.57	46.00	-15.43	peak
2	902.0000	29.04	-0.40	28.64	46.00	-17.36	peak

Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
3	914.5000	83.82	-0.11	-	83.71	94	-10.29	QP



Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	895.9840	30.55	-0.55	30.00	46.00	-16.00	peak
2	902.0000	28.91	-0.40	28.51	46.00	-17.49	peak

Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
3	914.5000	91.08	-0.11	-	90.97	94	-3.03	QP



917.5MHz
Horizontal




Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	917.5000	80.49	-0.06	-	80.43	94	-13.57	QP



Vertical




Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	917.5000	90.13	-0.06	-	90.07	94	-3.97	QP



921.00MHz
Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2	928.0000	27.70	0.43	28.13	46.00	-17.87	peak
3	931.6750	30.41	0.69	31.10	46.00	-14.90	peak

Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	921.0000	79.98	0.04	-	80.02	94	-13.98	QP



Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2	928.0000	28.57	0.43	29.00	46.00	-17.00	peak
3	930.0750	30.32	0.56	30.88	46.00	-15.12	peak

Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	921.0000	91.05	0.04	-	91.09	94	-2.91	QP



4. ANTENNA REQUIREMENT

4.1 STANDARD REQUIREMENT

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

4.2 EUT ANTENNA

The EUT antenna is Internal Antenna. It conforms to the standard requirements.



APPENDIX- PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

*****END OF THE REPORT*****