TEST REPORT

FCC ID: ZJPSR210

Product: BLUETOOTH SOUNDBAR

Model No.: SR210-15

Additional Model No.: Akixno 210-15,SR210-5,SR210-10,SR210

Trade Mark: Akixno

Report No.: FCC17121025A

Issued Date: February 26, 2018

Issued for:

Shenzhen SKY DRAGON Audio-videoTechnology Co.,LTD

B16,Laneway3,Liuxian 2RD,District 71,Baoan,Shenzhen

Issued By:

World Standardization Certification & Testing Group Co.,Ltd.

Building A-B, Baoshi Science & Technology Park, Baoshi Road,

Bao'an District, Shenzhen, Guangdong, China

TEL: +86-18126238805

FAX: +86-755-26992653

Note: *The results contained in this report pertain only to the tested sample. This report shall not be reproduced, except in full, without written approval of World Standardization Certification & Testing Group Co .,Ltd. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.*

Table of Contents

1. GENERAL INFORMATION 4
1. 2.GENERAL DESCRIPTION OF EUT 5
1.3. FACILITIES AND ACCREDITATIONS 6
1.3.1. ACCREDITATIONS 6
1.3.2. TEST DESCRIPTION 6
1.3.3.1MEASUREMENT UNCERTAINTY 6
1.4 DESCRIPTION OF TEST MODES 7
1.5 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING 8
1.5.1CONFIGURATION OF SYSTEM UNDER TEST 8
1.6 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 9
2. SUMMARY OF TEST RESULTS 10
3. MEASUREMENT INSTRUMENTS 11
4. EMC EMISSION TEST 12
4.1 CONDUCTED EMISSION MEASUREMENT 12
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS 12
4.1.2 TEST PROCEDURE 13
5.1.3 DEVIATION FROM TEST STANDARD 13
4.1.4 TEST SETUP 13
4.1.5EUT OPERATING CONDITIONS 13
4.1.6TEST RESULTS 14
4.2 RADIATED EMISSION MEASUREMENT 16
4.2.1RADIATED EMISSION LIMITS 16
4.2.2 TEST PROCEDURE 17
4.2.3 DEVIATION FROM TEST STANDARD 17
4.2.4 TEST SETUP 18
4.2.5EUT OPERATING CONDITIONS 19
4.2.5.1 RESULTS (BELOW 30 MHZ) 20
4.2.5.2 TEST RESULTS (BETWEEN 30M – 1000 MHZ) 21
4.2.5.3 TEST RESULTS(1GHZ TO 25GHZ) 23
4.3 TEST PROCEDURE 33
4.4 DEVIATION FROM STANDARD 33
4.5 TEST SETUP 33
4.6 EUT OPERATION CONDITIONS 33
4.7 TEST RESULTS 34
5. AVERAGE TIME OF OCCUPANCY 35
5.1 APPLIED PROCEDURES / LIMIT 35
5.2 TEST PROCEDURE 35
5.3 DEVIATION FROM STANDARD 35
5.4 TEST SETUP 36
5.5 EUT OPERATION CONDITIONS 36
5.6TEST RESULTS 37

Table of Contents

6. HOPPING CHANNEL SEPARATION MEASUREMENT 43
6.1 APPLIED PROCEDURES / LIMIT 43
6.2 TEST PROCEDURE 43
6.3 DEVIATION FROM STANDARD 43
6.4 TEST SETUP 43
6.5 EUT OPERATION CONDITIONS 44
6.6TEST RESULTS 44
7. BANDWIDTH TEST 53
7.1 APPLIED PROCEDURES / LIMIT 53
7.2 TEST PROCEDURE 53
7.3 DEVIATION FROM STANDARD 53
7.4 TEST SETUP 53
7.5 EUT OPERATION CONDITIONS 53
7.6TEST RESULTS 54
8. PEAK OUTPUT POWER TEST 63
8.1 APPLIED PROCEDURES / LIMIT 63
8.2 TEST PROCEDURE 63
8.3 DEVIATION FROM STANDARD 63
8.4 TEST SETUP 63
8.5 EUT OPERATION CONDITIONS 63
8.6TEST RESULTS 64
9. 100KHZ BAND EDGES MEASUREMENT 69
9.1 APPLIED PROCEDURES / LIMIT 69
10. ANTENNA APPLICATION 80
11. EUT TEST PHOTO 81
12.PHOTOGRAPHS OF EUT 83

1. GENERAL INFORMATION

Product:	BLUETOOTH SOUNDBAR
Model No.:	SR210-15
Additional Model:	Akixno 210-15,SR210-5,SR210-10,SR210
Applicant:	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Address:	B16,Laneway3,Liuxian 2RD,District 71,Baoan,Shenzhen
Manufacturer:	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Address:	B16,Laneway3,Liuxian 2RD,District 71,Baoan,Shenzhen
Data of receipt:	January 25, 2018
Date of Test:	February 09, 2018 to February 25, 2018
Applicable Standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247

The above equipment has been tested by World Standardization Certification & Testing Group Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: Pu Shi Xi **Date:** 2018.02.26
(Pu Shixi)

Check By: Qin Shuiquan **Date:** 2018.02.26
(Qin Shuiquan)

Approved By: Wang Fengbing **Date:** 2018.02.26
(Wang Fengbing)

1. 2.GENERAL DESCRIPTION OF EUT

Equipment Type	BLUETOOTH SOUNDBAR
Test Model	SR210-15
Additional Model	Akixno 210-15,SR210-5,SR210-10,SR210
Applicant	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Address	B16,Laneway3,Liuxian 2RD,District 71,Baoan,Shenzhen
Manufacturer	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Address	B16,Laneway3,Liuxian 2RD,District 71,Baoan,Shenzhen
Brand Name	**Akixno**
Hardware version:	N/A
Software version:	N/A
Extreme Temp. Tolerance	-10℃ to +65℃
Adapter Information:	MODEL:JDA0301200250WUS INPUT:100-240V~50/60Hz 0.8A OUTPUT:12.0V⎓2.50A
Battery information:	N/A
Operating Frequency	2402-2480MHz
Channels	79
Channel Spacing	1MHz
Modulation Type	GFSK, π /4-DQPSK, 8-DPSK
Version	3.0
Antenna Type:	PCB Antenna
Antenna gain:	-0.68dBi

Model deference：

Model	Differences
Akixno 210-15	only the model name and Screen Printing not same. The PCB and shell material are the same.
SR210-15	
SR210-5	
SR210-10	
SR210	

1.3. FACILITIES AND ACCREDITATIONS

All measurement facilities used to collect the measurement data are located at **Building A-B, Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China of the World Standardization Certification & Testing Group CO., LTD, 518108**
FCC Registration Number: 366353
The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C 63.10:2013. The sample tested as described in this report is in compliance with the FCC Rules Part15 Subpart C.
ALL the testing were referenced KDB NO.453039
The test results of this report relate only to the tested sample identified in this report.

1.3.1. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	**NVLAP (The certificate registration number is NVLAP LAB CODE:600142-0)**
Japan	**VCCI (The certificate registration number is C-4790, R-3684, G-837)**
Canada	**INDUSTRY CANADA (The certificated registration number is 7700A-1)**
China	**CNAS (The certificated registration number is L3732)**

Copies of granted accreditation certificates are available for downloading from our web site, **http://www.wsct-cert.com**

1.3.2. TEST DESCRIPTION

1.3.3.1MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y ±U** , where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2** , providing a level of confidence of approximately **95** %。

No.	Item	Uncertainty
1	Conducted Emission Test	±3.2dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.7dB
5	All emissions,radiated(>1G)	±4.7dB
6	Temperature	±0.5°C
7	Humidity	±2%

1.4 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Modulation type	Mode
1Mbps	Mode 1、Mode 2、Mode 3、Mode 4
2Mbps	
3Mbps	

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	Normal Hopping

For Conducted Emission	
Final Test Mode	Description
Mode 4	Normal Hopping

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	Normal Hopping

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2)The data rate was set in 1Mbps,2 Mbps,3 Mbps for radiated emission due to the highest RF output power.

(3) Record the worst case of each test item in this report.

1.5 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	N/A		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1Mbps)	DEF	DEF	DEF
Parameters(2Mbps)	DEF	DEF	DEF
Parameters(3Mbps)	DEF	DEF	DEF

1.5.1CONFIGURATION OF SYSTEM UNDER TEST

(EUT: BLUETOOTH SOUNDBAR)

1.6 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Adapter	/	JDA0301200250WUS	/	/

Note:

(1) The support equipment was authorized by Declaration of Confirmation.

(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

(3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.247(d)	100kHz Band Edges	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this test report.

3. MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Calibration Date	Calibration Due.
EMI Test Receiver	R&S	ESCI	100005	08/19/2017	08/18/2018
LISN	AFJ	LS16	16010222119	08/19/2017	08/18/2018
LISN(EUT)	Mestec	AN3016	04/10040	08/19/2017	08/18/2018
Universal Radio Communication Tester	R&S	CMU 200	1100.0008.02	08/19/2017	08/18/2018
Coaxial cable	Megalon	LMR400	N/A	08/12/2017	08/11/2018
GPIB cable	Megalon	GPIB	N/A	08/12/2017	08/11/2018
Spectrum Analyzer	R&S	FSU	100114	08/19/2017	08/18/2018
Pre Amplifier	H.P.	HP8447E	2945A02715	10/13/2017	10/12/2018
Pre-Amplifier	CDSI	PAP-1G18-38	--	10/13/2017	10/12/2018
Bi-log Antenna	SUNOL Sciences	JB3	A021907	09/13/2017	09/12/2018
9*6*6 Anechoic	--	--	--	08/21/2017	08/20/2018
Horn Antenna	COMPLIANCE ENGINEERING	CE18000	--	09/13/2017	09/12/2018
Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-631	08/23/2017	08/22/2018
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	04/25/2017	04/24/2018
System-Controller	CCS	N/A	N/A	N.C.R	N.C.R
Turn Table	CCS	N/A	N/A	N.C.R	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R	N.C.R
RF cable	Murata	MXHQ87WA3000	-	08/21/2017	08/20/2018
Loop Antenna	EMCO	6502	00042960	08/22/2017	08/21/2018
Horn Antenna	SCHWARZBECK	BBHA 9170	1123	08/19/2017	08/18/2018
Power meter	Anritsu	ML2487A	6K00003613	08/23/2017	08/22/2018
Power sensor	Anritsu	MX248XD	--	08/19/2017	08/18/2018

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Conducted limit (dBμV)		Conducted limit (dBμV)
	Quasi-peak	Quasi-peak	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

5.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6TEST RESULTS

Model Name	SR210-15	Voltage	120V/60Hz
Temperature	26 ℃	Relative Humidity	54%
Pressure	1010hPa	Phase	L
Test Mode	Mode 4		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1740	44.24	10.44	54.68	64.76	-10.08	QP
2		0.1780	19.32	10.44	29.76	54.57	-24.81	AVG
3		0.2180	41.96	10.43	52.39	62.89	-10.50	QP
4		0.2220	18.46	10.43	28.89	52.74	-23.85	AVG
5		0.3100	37.64	10.42	48.06	59.97	-11.91	QP
6		0.3100	16.67	10.42	27.09	49.97	-22.88	AVG
7		0.3660	35.10	10.42	45.52	58.59	-13.07	QP
8		0.3820	20.38	10.41	30.79	48.23	-17.44	AVG
9		0.4340	33.94	10.41	44.35	57.18	-12.83	QP
10		0.4863	11.44	10.40	21.84	46.23	-24.39	AVG
11		0.4980	31.39	10.40	41.79	56.03	-14.24	QP
12		1.4860	9.93	10.32	20.25	46.00	-25.75	AVG

Remark: All the modes have been investigated, and only worst mode is presented in this report.

Model Name	SR210-15	Voltage	120V/60Hz
Temperature	26 ℃	Relative Humidity	54%
Pressure	1010hPa	Phase	N
Test Mode	Mode 4		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1580	18.82	10.44	29.26	55.56	-26.30	AVG
2		0.1660	43.95	10.44	54.39	65.15	-10.76	QP
3		0.1660	18.48	10.44	28.92	55.15	-26.23	AVG
4		0.1780	43.77	10.44	54.21	64.57	-10.36	QP
5		0.1860	43.44	10.44	53.88	64.21	-10.33	QP
6		0.1900	16.64	10.44	27.08	54.03	-26.95	AVG
7		0.2380	40.53	10.43	50.96	62.16	-11.20	QP
8		0.2380	14.47	10.43	24.90	52.16	-27.26	AVG
9	*	0.2500	48.31	10.43	58.74	61.75	-3.01	peak
10		0.3940	17.80	10.41	28.21	47.98	-19.77	AVG
11		0.4300	33.32	10.41	43.73	57.25	-13.52	QP
12		0.5340	9.81	10.40	20.21	46.00	-25.79	AVG

Remark: All the modes have been investigated, and only worst mode is presented in this report.

4.2 RADIATED EMISSION MEASUREMENT

4.2.1RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2.2 TEST PROCEDURE

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



4.2.5EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.5.1 RESULTS (BELOW 30 MHZ)

Model Name	SR210-15	Polarization	Horizontal / Vertical
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 1/ Mode 2/ Mode 3

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

NOTE:

No result in this part for margin above 20dB.

Distance extrapolation factor =40 log (specific distance/test distance)(dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

4.2.5.2 TEST RESULTS (BETWEEN 30M – 1000 MHZ)

Model Name	SR210-15	Test Mode	Mode 1 with GFSK modulation
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization :	Horizontal

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		32.0667	26.63	4.00	30.63	40.00	-9.37	QP
2		55.2207	32.25	-5.64	26.61	40.00	-13.39	QP
3		110.5687	27.39	-1.92	25.47	43.50	-18.03	QP
4		167.8243	33.20	-6.32	26.88	43.50	-16.62	QP
5	*	260.1444	45.27	-4.21	41.06	46.00	-4.94	QP
6	!	321.0608	42.56	-2.10	40.46	46.00	-5.54	QP

Remark: All the modes have been investigated, and only worst mode is presented in this report.

Model Name	SR210-15	Test Mode	Mode 1 with GFSK modulation
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization :	Vertical

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	!	30.0054	31.71	4.79	36.50	40.00	-3.50	QP
2	*	34.5173	33.65	3.06	36.71	40.00	-3.29	QP
3	!	37.8121	35.24	1.21	36.45	40.00	-3.55	QP
4	!	43.3198	36.28	-1.38	34.90	40.00	-5.10	QP
5		100.9339	34.04	-3.63	30.41	43.50	-13.09	QP
6		276.1235	32.64	-3.39	29.25	46.00	-16.75	QP

Remark: All the modes have been investigated, and only worst mode is presented in this report.

4.2.5.3 TEST RESULTS(1GHZ TO 25GHZ)

Model Name	SR210-15	Test Mode	Mode 1 TX(1Mbps)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa		

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
4804	V	59.82	39.39	74	54	-14.18	-14.61
7206	V	58.67	39.46	74	54	-15.33	-14.54
4804	H	58.05	40.50	74	54	-15.95	-13.50
7206	H	59.81	40.81	74	54	-14.19	-13.19

Remark:
All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Model Name	SR210-15	Test Mode	Mode 2 TX(2Mbps)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa		

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
4882	V	58.12	41.41	74	54	-15.88	-12.59
7323	V	59.31	40.51	74	54	-14.69	-13.49
4882	H	59.51	40.00	74	54	-14.49	-14.00
7323	H	58.29	39.29	74	54	-15.71	-14.71

Remark:
All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Model Name	SR210-15	Test Mode	Mode 3 TX(3Mbps)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa		

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
4960	V	58.99	41.73	74	54	-15.01	-12.27
7440	V	58.51	39.01	74	54	-15.49	-14.99
4960	H	59.21	40.42	74	54	-14.79	-13.58
7440	H	59.00	40.00	74	54	-15.00	-14.00

Remark:
All emissions not reported were more than 20dB below the specified limit or in the noise floor.

4.2.5.4 TEST RESULTS (Restricted Bands Requirements)

Test result for 1Mbps Mode:

Model Name	SR210-15	Test Mode	TX /Mode1-1Mbps(CH0)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2387	63.01	-8.76	54.25	74	19.75	peak
2387	56.20	-8.76	47.44	54	6.56	AVG
2390	59.91	-8.73	51.18	74	22.82	peak
2390	55.37	-8.73	46.64	54	7.36	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Model Name	SR210-15	Test Mode	TX /Mode1-1Mbps(CH0)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2384	60.29	-8.76	51.53	74	22.47	peak
2384	53.16	-8.76	44.40	54	9.60	AVG
2390	62.17	-8.73	53.44	74	20.56	peak
2390	55.02	-8.73	46.29	54	7.71	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Model Name	SR210-15	Test Mode	TX /Mode 3-1Mbps(CH78)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	61.00	-8.17	52.83	74	21.17	peak
2483.5	54.27	-8.17	46.10	54	7.90	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Model Name	SR210-15	Test Mode	TX /Mode 3-1Mbps(CH78)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	60.10	-8.17	51.93	74	22.07	peak
2483.5	54.98	-8.17	46.81	54	7.19	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Test result for 2Mbps Mode:

Model Name	SR210-15	Test Mode	TX /Mode1-2Mbps(CH0)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2387	63.75	-8.76	54.99	74	19.01	peak
2387	55.70	-8.76	46.94	54	7.06	AVG
2390	62.12	-8.73	53.39	74	20.61	peak
2390	55.50	-8.73	46.77	54	7.23	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Model Name	SR210-15	Test Mode	TX /Mode1-2Mbps(CH0)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2384	62.71	-8.76	53.95	74	20.05	peak
2384	53.80	-8.76	45.04	54	8.96	AVG
2390	59.33	-8.73	50.60	74	23.40	peak
2390	57.84	-8.73	49.11	54	4.89	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Model Name	SR210-15	Test Mode	TX /Mode3-2Mbps(CH78)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	62.48	-8.17	54.31	74	19.69	peak
2483.5	53.64	-8.17	45.47	54	8.53	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Model Name	SR210-15	Test Mode	TX /Mode3-2Mbps(CH78)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.5	64.33	-8.17	56.16	74	17.84	peak
2483.5	54.87	-8.17	46.70	54	7.30	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Test result for 3Mbps Mode:

Model Name	SR210-15	Test Mode	TX /Model 1-3Mbps(CH0)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2387	62.22	-8.76	53.46	74	20.54	peak
2387	55.56	-8.76	46.80	54	7.20	AVG
2390	63.42	-8.73	54.69	74	19.31	peak
2390	55.08	-8.73	46.35	54	7.65	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Model Name	SR210-15	Test Mode	TX /Mode 1-3Mbps(CH0)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2384	60.43	-8.76	51.67	74	22.33	peak
2384	53.27	-8.76	44.51	54	9.49	AVG
2390	61.08	-8.73	52.35	74	21.65	peak
2390	56.45	-8.73	47.72	54	6.28	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Model Name	SR210-15	Test Mode	TX /Model 3-3Mbps(CH78)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.5	63.03	-8.17	54.86	74	19.14	peak
2483.5	54.30	-8.17	46.13	54	7.87	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Model Name	SR210-15	Test Mode	TX /Model 3-3Mbps(CH78)
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.5	64.70	-8.17	56.53	74	17.47	peak
2483.5	53.37	-8.17	45.20	54	8.80	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Test result for hopping mode:

Model Name	SR210-15	Test Mode	hopping mode-1Mbps
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2387	60.52	-8.76	51.76	74	22.24	peak
2387	56.48	-8.76	47.72	54	6.28	AVG
2390	63.83	-8.73	55.10	74	18.90	peak
2390	56.36	-8.73	47.63	54	6.37	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Model Name	SR210-15	Test Mode	Hopping mode-1Mbps
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2387	60.16	-8.76	51.40	74	22.60	peak
2387	56.85	-8.76	48.09	54	5.91	AVG
2390	59.48	-8.73	50.75	74	23.25	peak
2390	55.94	-8.73	47.21	54	6.79	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Model Name	SR210-15	Test Mode	Hopping mode-1Mbps
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.5	60.63	-8.76	51.87	74	22.13	peak
2483.5	53.91	-8.76	45.15	54	8.85	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Model Name	SR210-15	Test Mode	Hopping mode-1Mbps
Temperature	20 ℃	Relative Humidity	48%
Pressure	1010 hPa	Polarization	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.5	63.53	-8.17	55.36	74	18.64	peak
2483.5	53.40	-8.17	45.23	54	8.77	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

5. NUMBER OF HOPPING CHANNEL6.1 Applied procedures / limit

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.3 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
b. Spectrum Setting: RBW= 1MHz, VBW=3MHz, Sweep time = Auto.

4.4 DEVIATION FROM STANDARD

No deviation.

4.5 TEST SETUP

4.6 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.7 TEST RESULTS

Model Name	SR210-15	Test Mode	Hopping Mode
Temperature	25℃	Relative Humidity	60%
Pressure	1015 hPa	Number of Hopping Channel	79

2400MHz-2483.5MHz



5. AVERAGE TIME OF OCCUPANCY

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

5.2 TEST PROCEDURE

a. The EUT test port was connected to the spectrum analyzer with RF cable and antenna connector.
b. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz.
c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
d. Sweep Time is more than once pulse time.
e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
f. Measure the maximum time duration of one single pulse.
g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
h. Measure the maximum time duration of one single pulse.
i. DH1 Dwell time = Pulse time*(1600/2/79)*31.6S
DH3 Dwell time = Pulse time*(1600/4/79)*31.6S
DH5 Dwell time = Pulse time*(1600/6/79)*31.6S

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6TEST RESULTS

Note: ***the worst case is 1Mbps as result in this part.***

Model Name	SR210-15	Test Mode	DH1-1Mbps
Temperature	25℃	Relative Humidity	60%
Pressure	1012 hPa		

Data Packet	Frequency	Pulse time(ms)	Dwell Time(S)	Limits（S）
DH1	2402MHz	0.556	0.178	0.4
DH1	2441MHz	0.556	0.178	0.4
DH1	2480MHz	0.556	0.178	0.4

CH00-DH1



CH39-DH1



CH78-DH1



Model Name	SR210-15	Test Mode	DH3-1Mbps
Temperature	25℃	Relative Humidity	60%
Pressure	1012 hPa		

Data Packet	Frequency	Pulse time(ms)	Dwell Time(S)	Limits（S）
DH3	2402MHz	1.764	0.282	0.4
DH3	2441MHz	1.764	0.282	0.4
DH3	2480MHz	1.764	0.282	0.4

CH00-DH3



CH39-DH3



CH78-DH3



Model Name	SR210-15	Test Mode	DH5-1Mbps
Temperature	25℃	Relative Humidity	60%
Pressure	1012 hPa		

Data Packet	Frequency	Pulse time(ms)	Dwell Time(S)	Limits（S）
DH5	2402MHz	2.876	0.307	0.4
DH5	2441MHz	2.876	0.307	0.4
DH5	2480MHz	2.876	0.307	0.4

CH00-DH5



CH39-DH5



CH78-DH5



6. HOPPING CHANNEL SEPARATION MEASUREMENT

6.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span
VB	Video (or Average) Bandwidth (VBW) ≥ RBW
Detector	Peak
Trace	Max hold
Sweep Time	Auto

6.2 TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels: Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span; Video (or Average) Bandwidth (VBW) ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold
3. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
4. Repeat above procedures until all frequencies measured were complete.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.6TEST RESULTS

Model Name	SR210-15	Test Mode	CH00 / CH39 /CH78 (1Mbps Mode)
Temperature	25℃	Relative Humidity	60%
Pressure	1012 hPa	Test Result	Pass

Channel number	Channel frequency （MHz）	Separation Read value (KHz)	Separation limit (KHz)
00	2402	1003	20dB BW
39	2441	1000	20dB BW
78	2480	1003	20dB BW

Note: 20db bandwidth refer to section9.6

CH00 -1Mbps



CH39 -1Mbps


RBW 30 kHz
VBW 100 kHz
SWT 10 ms
Delta 1 [T1]
-0.60 dB
1.000000000 MHz
Ref 30 dBm
Att 30 dB
Marker 1 [T1]
5.12 dBm
2.440839744 GHz
1 PK
VIEW
A
TDF
3DB
30
20
10
0
-10
-20
-30
-40
-50
-60
-70
Center 2.4415 GHz
200 kHz/
Span 2 MHz

CH78 -1Mbps


RBW 30 kHz
VBW 100 kHz
SWT 10 ms
Delta 1 [T1]
0.03 dB
1.003205128 MHz
Ref 30 dBm
Att 30 dB
Marker 1 [T1]
2.31 dBm
2.478836538 GHz
1 PK
VIEW
TDF
3DB
Center 2.4795 GHz
200 kHz/
Span 2 MHz

Model Name	SR210-15	Test Mode	CH00 / CH39 /CH78 (2Mbps Mode)
Temperature	25℃	Relative Humidity	60%
Pressure	1012 hPa	Test Result	Pass

Channel number	Channel frequency （MHz）	Separation Read value (KHz)	Separation limit (KHz)
00	2402	1000	2/3 *20dB BW
39	2441	1003	2/3 *20dB BW
78	2480	1000	2/3 *20dB BW

Note: 20db bandwidth refer to section 9.6

CH00 -2Mbps



CH39 -2Mbps


RBW 30 kHz
VBW 100 kHz
SWT 10 ms
Delta 1 [T1]
0.03 dB
1.003205128 MHz
Ref 30 dBm
Att 30 dB
Marker 1 [T1]
1.73 dBm
2.441121795 GHz
1 PK
VIEW
A
TDF
3DB
Center 2.4415 GHz
200 kHz/
Span 2 MHz

CH78 -2Mbps


RBW 30 kHz
VBW 100 kHz
Ref 30 dBm
Att 30 dB
SWT 10 ms
Delta 1 [T1]
-0.07 dB
1.000000000 MHz
Marker 1 [T1]
-0.18 dBm
2.479125000 GHz
1 PK VIEW
TDF
3DB
Center 2.4795 GHz
200 kHz/
Span 2 MHz

Model Name	SR210-15	Test Mode	CH00 / CH39 /CH78 (3Mbps Mode)
Temperature	25℃	Relative Humidity	60%
Pressure	1012 hPa	Test Result	Pass

Channel number	Channel frequency （MHz）	Separation Read value (KHz)	Separation limit (KHz)
00	2402	1003	2/3 *20dB BW
39	2441	1003	2/3 *20dB BW
78	2480	1003	2/3 *20dB BW

Note: 20db bandwidth refer to section 9.6

CH00 -3Mbps



CH39 -3Mbps

RBW 30 kHz
VBW 100 kHz
SWT 10 ms
Delta 1 [T1]
0.04 dB
1.003205128 MHz
Ref 30 dBm
Att 30 dB
Marker 1 [T1]
1.63 dBm
2.440996795 GHz
1 PK
VIEW
A
TDF
3DB
30
20
10
0
-10
-20
-30
-40
-50
-60
-70
Center 2.4415 GHz
200 kHz/
Span 2 MHz

CH78 -3Mbps


RBW 30 kHz
VBW 100 kHz
SWT 10 ms
Delta 1 [T1]
-0.07 dB
1.003205128 MHz
Ref 30 dBm
Att 30 dB
Marker 1 [T1]
-0.27 dBm
2.478996795 GHz
1 PK
VIEW
A
TDF
3DB
Center 2.4795 GHz
200 kHz/
Span 2 MHz

7. BANDWIDTH TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30kHz
VB	100 kHz
Detector	Peak
Trace	Max hold
Sweep Time	Auto

7.2 TEST PROCEDURE

1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
2. Set the spectrum analyzer as follows: VBW =30kHz, RBW=100kHz, Sweep = auto Detector function = peak ,Trace = max hold
3. Measure the highest amplitude appearing on spectral display and record the level to calculate results.
4. Repeat above procedures until all frequencies measured were complete.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6TEST RESULTS

Note: ***the worst case is DH5 as result in this part.***

Model Name	SR210-15	Test Mode	CH00/CH39/C78(1Mbps)
Temperature	25℃	Relative Humidity	60%
Pressure	1012 hPa		

Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	837	PASS
2441 MHz	822	PASS
2480 MHz	832	PASS

CH00 -1Mbps



CH39 -1Mbps


RBW 30 kHz
VBW 100 kHz
SWT 15 ms
Marker 1 [T1]
-15.52 dBm
2.440567308 GHz
Marker 2 [T1]
4.37 dBm
2.440841346 GHz
Delta 1 [T1]
-0.11 dB
822.115384613 kHz
Ref 30 dBm
Att 30 dB
1 PK
VIEW
TDF
3DB
D1 -15.63 dBm
Center 2.441 GHz
300 kHz/
Span 3 MHz

CH78 -1Mbps



世标检测认证股份
World Standardization Certification & Testing Group Co.,Ltd.
ADD:Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL:86-755-26996143/26996144/26996145/26996192 FAX:86-755-86376605 E-mail:Fengbing.Wang@wsct-cert.com Http:www.wsct-cert.com
Member of the WSCT INC.

Note: ***the worst case is DH5as result in this part.***

Model Name	SR210-15	Test Mode	CH00/CH39/C78(2Mbps)
Temperature	25℃	Relative Humidity	60%
Pressure	1012 hPa		

Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	1135	PASS
2441 MHz	1168	PASS
2480 MHz	1135	PASS

CH00 -2Mbps



CH39 -2Mbps


RBW 30 kHz
VBW 100 kHz
SWT 15 ms
Delta 1 [T1]
-0.26 dB
1.168269231 MHz
Ref 30 dBm
Att 30 dB
Marker 1 [T1]
-19.86 dBm
2.440418269 GHz
Marker 2 [T1]
1.15 dBm
2.441125000 GHz
1 PK VIEW
TDF
3DB
D1 -19.85 dBm
Center 2.441 GHz
300 kHz/
Span 3 MHz

CH78 -2Mbps


RBW 30 kHz
VBW 100 kHz
SWT 15 ms
Marker 1 [T1]
-20.82 dBm
2.479423077 GHz
Ref 30 dBm
Att 30 dB
Marker 2 [T1]
-0.81 dBm
2.480125000 GHz
Delta 1 [T1]
0.18 dB
1.134615385 MHz
1 PK
VIEW
TDF
3DB
D1 -20.81 dBm
Center 2.48 GHz
300 kHz/
Span 3 MHz

Note: ***the worst case is DH5as result in this part.***

Model Name	SR210-15	Test Mode	CH00/CH39/C78(3Mbps)
Temperature	25℃	Relative Humidity	60%
Pressure	1012 hPa		

Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	1144	PASS
2441 MHz	1144	PASS
2480 MHz	1149	PASS

CH00 -3Mbps



CH39 -3Mbps


RBW 30 kHz
VBW 100 kHz
SWT 15 ms
Marker 1 [T1]
-18.57 dBm
2.440432692 GHz
Marker 2 [T1]
1.15 dBm
2.441000000 GHz
Delta 1 [T1]
-0.49 dB
1.144230769 MHz
Ref 30 dBm
Att 30 dB
1 PK
VIEW
D1 -18.85 dBm
TDF
3DB
Center 2.441 GHz
300 kHz/
Span 3 MHz

CH78 -3Mbps


RBW 30 kHz
VBW 100 kHz
Ref 30 dBm
Att 30 dB
SWT 15 ms
Marker 1 [T1]
-20.65 dBm
2.479432692 GHz
Marker 2 [T1]
-0.78 dBm
2.480000000 GHz
Delta 1 [T1]
-0.36 dB
1.14903846 MHz
1 PK
VIEW
TDF
3DB
Center 2.48 GHz
300 kHz/
Span 3 MHz

8. PEAK OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(i)	Peak Output Power	1W for 1Mbps 0.125Wfor2/3Mbps	2400-2483.5	PASS

8.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzerand antenna output port as show in the block diagram below,

b. Setting : RBW ≥ the 20 dB bandwidth of the emission being measured

Span ≥ approximately 3 times the 20 dB bandwidth, centered on a hopping channel

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP

8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6TEST RESULTS

Model Name	SR210-15	Test Mode	CH00/ CH39 /CH78 (1M/2M/3Mbps Mode)
Temperature	25℃	Relative Humidity	60%
Pressure	1012 hPa		

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT(dBm)	Result
1Mbps				
CH00	2402	**0.00**	30	Pass
CH39	2441	4.22	30	Pass
CH78	2480	2.06	30	Pass
2Mbps				
CH00	2402	-1.18	20.97	Pass
CH39	2441	2.86	20.97	Pass
CH78	2480	0.83	20.97	Pass
3Mbps				
CH00	2402	-1.17	20.97	Pass
CH39	2441	2.86	20.97	Pass
CH78	2480	0.86	20.97	Pass

1Mbps

Channel: Low



Channel: Middle



Channel: High



2Mbps

Channel: Low



Channel: Middle



Channel: High



3Mbps

Channel: Low



Channel: Middle



Channel: High



9. 100KHZ BAND EDGES MEASUREMENT
9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(d)	Band Edges Measurement	(20dB bandwidth)	2400-2483.5	PASS

1Mbps
Channel: Low





Date: 11.JAN.2018 16:08:40

Channel: High





2Mbps
Channel: Low





Channel: High





3Mbps
Channel: Low





Channel: High





1Mbps

Channel: Low



Channel: Middle



Channel: High



2Mbps

Channel: Low



Channel: Middle



Channel: High



3Mbps

Channel: Low



Channel: Middle



Channel: High



10. ANTENNA APPLICATION

10.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247

FCC part 15C section 15.247 requirements: Systems operating in the 2402-2480MHz band that are used exclusively for fixed.

10.2 Result

The EUT's antenna integrated on PCB, The antenna's gain is -0.68dBi and meets the requirement.



11. EUT TEST PHOTO

CONDUCTED EMISSION TEST

RADIATED EMISSION TEST
(Frequency from 30MHz to 1GHz)



RADIATED EMISSION TEST
(Frequency above 1GHz)



12.PHOTOGRAPHS OF EUT

Appearance photograph of EUT



Appearance photograph of EUT

Appearance photograph of EUT

Appearance photograph of EUT

Internal photograph of EUT

Internal photograph of EUT



Internal photograph of EUT



Internal photograph of EUT



Internal photograph of EUT



Internal photograph of EUT



Internal photograph of EUT



Internal photograph of EUT



Internal photograph of EUT



Internal photograph of EUT



---END OF REPORT---