# FCC TEST REPORT

For

Shenzhen Geniatech Inc., Ltd.

Edge Computer Box

Test Model: APC3576V2

| | | |
|---|---|---|
| Prepared for | : | Shenzhen Geniatech Inc., Ltd. |
| Address | : | Room 02-04, 10 / F, Block A, Building 8, Shenzhen International Innovation Valley, Dashi Road, Nanshan District, Shenzhen, Guangdong, China. |
| Prepared by | : | Shenzhen LCS Compliance Testing Laboratory Ltd. |
| Address | : | 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China |
| Tel | : | (+86)755-82591330 |
| Fax | : | (+86)755-82591332 |
| Web | : | www.LCS-cert.com |
| Mail | : | webmaster@LCS-cert.com |
| Date of receipt of test sample | : | July 01, 2026 |
| Number of tested samples | : | 2 |
| Sample number | : | A260626065-1, A260626065-2 |
| Serial number | : | Prototype |
| Date of Test | : | July 01, 2026 ~ July 27, 2026 |
| Date of Report | : | July 28, 2026 |



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

# FCC TEST REPORT
## FCC CFR 47 PART 15 C(15.247)

| | | |
|---|---|---|
| **Report Reference No. .....** | : | **LCSA06296129EC** |
| Date of Issue ..... | : | July 28, 2026 |
| **Testing Laboratory Name.....** | : | **Shenzhen LCS Compliance Testing Laboratory Ltd.** |
| Address ..... | : | 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China |
| Testing Location/ Procedure ..... | : | Full application of Harmonised standards ■<br>Partial application of Harmonised standards □<br>Other standard testing method □ |
| **Applicant's Name .....** | : | **Shenzhen Geniatech Inc., Ltd.** |
| Address ..... | : | Room 02-04, 10 / F, Block A, Building 8, Shenzhen International Innovation Valley, Dashi Road, Nanshan District, Shenzhen, Guangdong, China. |
| **Test Specification** | | |
| Standard..... | : | FCC CFR 47 PART 15 C(15.247) |
| TRF Originator..... | : | Shenzhen LCS Compliance Testing Laboratory Ltd. |
| Master TRF ..... | : | Dated 2011-03 |

**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

| | | |
|---|---|---|
| **EUT Description. .....** | : | **Edge Computer Box** |
| Trade Mark ..... | : | N/A |
| Test Model..... | : | APC3576V2 |
| Ratings ..... | : | Please Refer to Page 6 |
| **Result .....** | : | **PASS** |

| **Compiled by:** | **Supervised by:** | **Approved by:** |
|---|---|---|
| Vera Deng | Kevin Huang | Gavin Liang |
| Vera Deng/ Administrator | Kevin Huang/ RF Manager | Gavin Liang/ Manager |



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

# FCC -- TEST REPORT

| | |
|---|---|
| **Test Report No. :** **LCSA06296129EC** | July 28, 2026<br>Date of issue |

| | |
|---|---|
| Test Model..... | : APC3576V2 |
| EUT..... | : Edge Computer Box |
| **Applicant.....** | **: Shenzhen Geniatech Inc., Ltd.** |
| Address..... | : Room 02-04, 10 / F, Block A, Building 8, Shenzhen International Innovation Valley, Dashi Road, Nanshan District, Shenzhen, Guangdong, China. |
| Telephone..... | : / |
| Fax..... | : / |
| **Manufacturer.....** | **: Shenzhen Geniatech Inc., Ltd.** |
| Address..... | : Room 02-04, 10 / F, Block A, Building 8, Shenzhen International Innovation Valley, Dashi Road, Nanshan District, Shenzhen, Guangdong, China. |
| Telephone..... | : / |
| Fax..... | : / |
| **Factory.....** | **: Shenzhen Geniatech Inc., Ltd.** |
| Address..... | : 2F~3F, Block A, Yinghaosheng Industrial Park, Fu'an Road, Dayang Development Zone, Funyong Town, Bao'an District, Shenzhen, China. |
| Telephone..... | : / |
| Fax..... | : / |

| **Test Result** | **PASS** |
|---|---|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

## Revision History

| Report Version | Issue Date | Revision Content | Revised By |
|---|---|---|---|
| 000 | July 28, 2026 | Initial Issue | --- |
| | | | |
| | | | |



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

# TABLE OF CONTENTS

**1. GENERAL INFORMATION ..... 6**
1.1. DESCRIPTION OF DEVICE (EUT) ..... 6
1.2. SUPPORT EQUIPMENT LIST ..... 9
1.3 EXTERNAL I/O CABLE ..... 9
1.4. DESCRIPTION OF TEST FACILITY ..... 9
1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY ..... 9
1.6. MEASUREMENT UNCERTAINTY ..... 10
1.7. DESCRIPTION OF TEST MODES ..... 10
**2. TEST METHODOLOGY ..... 12**
2.1. EUT CONFIGURATION ..... 12
2.2. EUT EXERCISE ..... 12
2.3. GENERAL TEST PROCEDURES ..... 12
2.4. TEST SAMPLE ..... 12
**3. SYSTEM TEST CONFIGURATION ..... 13**
3.1. JUSTIFICATION ..... 13
3.2. EUT EXERCISE SOFTWARE ..... 13
3.3. SPECIAL ACCESSORIES ..... 13
3.4. BLOCK DIAGRAM/SCHEMATICS ..... 13
3.5. EQUIPMENT MODIFICATIONS ..... 13
3.6. TEST SETUP ..... 13
**4. SUMMARY OF TEST RESULTS ..... 14**
**5. TEST RESULT ..... 15**
5.1. 6 DB SPECTRUM BANDWIDTH MEASUREMENT ..... 15
5.2. RADIATED EMISSIONS MEASUREMENT ..... 16
5.3. MAXIMUM AVERAGE CONDUCTED OUTPUT POWER MEASUREMENT ..... 32
5.4. POWER SPECTRAL DENSITY MEASUREMENT ..... 34
5.5. BAND EDGE MEASUREMENTS AND CONDUCTED SPURIOUS EMISSIONS TEST ..... 36
5.6. ON TIME AND DUTY CYCLE ..... 37
5.7. EMISSIONS IN RESTRICTED BANDS ..... 38
5.8. AC POWER LINE CONDUCTED EMISSIONS ..... 40
5.9. ANTENNA REQUIREMENTS ..... 45
**6. LIST OF MEASURING EQUIPMENTS ..... 46**
**7. TEST SETUP PHOTOGRAPHS OF EUT ..... 47**
**8. EXTERIOR PHOTOGRAPHS OF THE EUT ..... 47**
**9. INTERIOR PHOTOGRAPHS OF THE EUT ..... 47**



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

# 1. GENERAL INFORMATION

## 1.1. Description of Device (EUT)

| | | |
|---|---|---|
| EUT | : | Edge Computer Box |
| Test Model | : | APC3576V2 |
| Ratings | : | Input: 12.0V⎓2.0A<br>For Adapter Input: 100-240V~, 50/60Hz, 0.6A Max<br>Output: 12.0V⎓2.0A, 24.0W |
| Hardware Version | : | RKU241216（RK3576/RK3576J) |
| Software Version | : | Android |
| Bluetooth | : | |
| Frequency Range | : | 2402MHz~2480MHz |
| Channel Number | : | 79 channels for Bluetooth V5.0 (DSS)<br>40 channels for Bluetooth V5.0 (DTS) |
| Channel Spacing | : | 1MHz for Bluetooth V5.0 (DSS)<br>2MHz for Bluetooth V5.0 (DTS) |
| Modulation Type | : | GFSK, π/4-DQPSK, 8-DPSK for Bluetooth V5.0 (DSS)<br>GFSK for Bluetooth V5.0 (DTS) |
| Bluetooth Version | : | V5.0 |
| Antenna Description | : | External Antenna1: BGS-001F(RA), 2.87dBi(max.)<br>Dipole Antenna1: E199TN00024R, 1.5dBi(max.) |
| WIFI(2.4G Band) | : | |
| Frequency Range | : | 2412MHz~2462MHz |
| Channel Spacing | : | 5MHz |
| Channel Number | : | 11 channels for 20MHz bandwidth (2412~2462MHz)<br>7 channels for 40MHz bandwidth (2422~2452MHz) |
| Modulation Type | : | IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK)<br>IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK) |
| Antenna Description | : | External Antenna: BGS-001F(RA)<br>Antenna1: 2.87dBi(Max.)<br>Antenna2: 2.87dBi(Max.)<br>Dipole Antenna: E199TN00024R<br>Antenna1: 1.5dBi(Max.)<br>Antenna2: 1.5dBi(Max.) |
| WIFI(5.2G Band) | : | |
| Frequency Range | : | 5180MHz~5240MHz |
| Channel Number | : | 4 channels for 20MHz bandwidth(5180MHz~5240MHz)<br>2 channels for 40MHz bandwidth(5190MHz~5230MHz)<br>1 channels for 80MHz bandwidth(5210MHz) |
| Modulation Type | : | IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) |



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

| | | |
|---|---|---|
| | | IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK) |
| Antenna Description | : | External Antenna: BGS-001F(RA)<br>Antenna1: 4.24dBi(Max.)<br>Antenna2: 4.24dBi(Max.)<br>Dipole Antenna: E199TN00024R<br>Antenna1: 3.0dBi(Max.)<br>Antenna2: 3.0dBi(Max.) |
| WIFI(5.3G Band) | | |
| Frequency Range | : | 5260MHz~5320MHz |
| Channel Number | : | 4 channels for 20MHz bandwidth(5260MHz~5320MHz)<br>2 channels for 40MHz bandwidth(5270MHz~5310MHz)<br>1 channels for 80MHz bandwidth(5290MHz) |
| Modulation Type | : | IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK) |
| Antenna Description | : | External Antenna: BGS-001F(RA)<br>Antenna1: 4.24dBi(Max.)<br>Antenna2: 4.24dBi(Max.)<br>Dipole Antenna: E199TN00024R<br>Antenna1: 3.0dBi(Max.)<br>Antenna2: 3.0dBi(Max.) |
| WIFI(5.5G Band) | : | |
| Frequency Range | : | 5500MHz~5700MHz |
| Channel Number | : | 11 channels for 20MHz bandwidth(5500MHz~5700MHz)<br>5 channels for 40MHz bandwidth(5510MHz~5670MHz)<br>2 channels for 80MHz bandwidth(5530MHz, 5610MHz) |
| Modulation Type | : | IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK) |
| Antenna Description | : | External Antenna: BGS-001F(RA)<br>Antenna1: 4.24dBi(Max.)<br>Antenna2: 4.24dBi(Max.)<br>Dipole Antenna: E199TN00024R<br>Antenna1: 3.0dBi(Max.)<br>Antenna2: 3.0dBi(Max.) |
| WIFI(5.8G Band) | : | |


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

| | | |
|---|---|---|
| Frequency Range | : | 5745MHz~5825MHz |
| Channel Number | : | 5 channels for 20MHz bandwidth(5745MHz~5825MHz)<br>2 channels for 40MHz bandwidth(5755MHz~5795MHz)<br>1 channels for 80MHz bandwidth(5775MHz) |
| Modulation Type | : | IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK) |
| Antenna Description | : | External Antenna: BGS-001F(RA)<br>Antenna1: 4.24dBi(Max.)<br>Antenna2: 4.24dBi(Max.)<br>Dipole Antenna: E199TN00024R<br>Antenna1: 3.0dBi(Max.)<br>Antenna2: 3.0dBi(Max.) |

Note: There are External Antenna and Dipole Antenna for choice. For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

## 1.2. Support equipment List

| Manufacturer | Description | Model | Serial Number | Certificate |
|---|---|---|---|---|
| SHENZHEN FUJIA APPLIANCE CO., LTD | SWITCHING ADAPTOR | FJ-SW1202000 N | --- | FCC |

## 1.3 External I/O Cable

| I/O Port Description | Quantity | Cable |
|---|---|---|
| DC IN Port | 1 | N/A |
| Type-C Port | 1 | N/A |
| HDMI Port | 1 | N/A |
| USB Port | 2 | N/A |
| S/PDIF Port | 1 | N/A |
| phone-jack | 1 | N/A |
| RJ45 Port | 2 | N/A |
| ANT Port | 2 | N/A |

## 1.4. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63 10-2020 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

## 1.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

## 1.6. Measurement Uncertainty

| Test Item | | Frequency Range | Uncertainty | Note |
|---|---|---|---|---|
| Radiation Uncertainty | : | 9KHz~30MHz | ±3.10dB | (1) |
| | | 30MHz~200MHz | ±2.96dB | (1) |
| | | 200MHz~1000MHz | ±3.10dB | (1) |
| | | 1GHz~26.5GHz | ±3.80dB | (1) |
| | | 26.5GHz~40GHz | ±3.90dB | (1) |
| Conduction Uncertainty | : | 150kHz~30MHz | ±1.63dB | (1) |
| Power disturbance | : | 30MHz~300MHz | ±1.60dB | (1) |
| Output power | : | 1GHz-40GHz | ±0.57dB | (1) |
| Power Spectral Density | : | 1GHz-40GHz | ±1.2dB | (1) |
| Occupied Channel Bandwidth | : | 1GHz-40GHz | ±5% | (1) |
| Conducted RF Spurious Emission | : | 9kHz-40GHz | ±1.80dB | (1) |
| Emissions in Restricted Bands | : | 1GHz-40GHz | ±2.47dB | (1) |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 1.7. Description of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in Y position.

AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/50Hz modes, recorded worst case at AC 120V/60Hz.

AC conducted emission pre-test at both at power adapter modes, recorded worst case.

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was determined to be IEEE 802.11n HT20 MIMO mode (Low Channel).

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was determined to be IEEE 802.11n HT20 MIMO mode (Low Channel).

Worst-Case data rates were utilized from preliminary testing of the Chipset, worst-case data rates used during the testing are as follows:

IEEE 802.11b Mode: 1 Mbps, DSSS.
IEEE 802.11g Mode: 6 Mbps, OFDM.
IEEE 802.11n Mode HT20: MCS0, OFDM.
IEEE 802.11n Mode HT40: MCS0, OFDM.
IEEE 802.11ax Mode HE20: HE1MCS0, RU242, OFDM, OFDMA.
IEEE 802.11ax Mode HE40: HE1MCS11, RU484, OFDM, OFDMA.
Note: for 802.11ax mode, all RU are tested, and only the worst RU(full RU)are recorded in the report.

Antenna & Bandwidth

| Antenna | Chain 1 (Ant1) | | Chain 2 (Ant2) | | Simultaneously |
|---|---|---|---|---|---|
| Bandwidth Mode | 20MHz | 40MHz | 20MHz | 40MHz | / |
| IEEE 802.11b | ☑ | ☐ | ☑ | ☐ | ☐ |
| IEEE 802.11g | ☑ | ☐ | ☑ | ☐ | ☐ |
| IEEE 802.11n | ☑ | ☑ | ☑ | ☑ | ☑ |
| IEEE 802.11ax | ☑ | ☑ | ☑ | ☑ | ☑ |



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

Channel List & Frequency

IEEE 802.11b/g/n/ax HE20

| Frequency Band | Channel No. | Frequency(MHz) | Channel No. | Frequency(MHz) |
|---|---|---|---|---|
| 2412~2462MHz | 1 | 2412 | 7 | 2442 |
| | 2 | 2417 | 8 | 2447 |
| | 3 | 2422 | 9 | 2452 |
| | 4 | 2427 | 10 | 2457 |
| | 5 | 2432 | 11 | 2462 |
| | 6 | 2437 | --- | --- |

IEEE 802.11n/ax HE40

| Frequency Band | Channel No. | Frequency(MHz) | Channel No. | Frequency(MHz) |
|---|---|---|---|---|
| 2422~2452MHz | --- | --- | 7 | 2442 |
| | --- | --- | 8 | 2447 |
| | 3 | 2422 | 9 | 2452 |
| | 4 | 2427 | --- | --- |
| | 5 | 2432 | --- | --- |
| | 6 | 2437 | --- | --- |



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

# 2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

## 2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

## 2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure KDB558074 D01 15.247 Meas Guidance v05r02 and KDB 662911 D01 Multiple Transmitter Output v02r01 are required to be used for this kind of FCC 15.247 digital modulation device.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

## 2.3. General Test Procedures

### 2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2020 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

### 2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz and 1.5 m above ground plane above 1GHz. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2020.

## 2.4. Test Sample

The application provides 2 samples to meet requirement;

| Sample Number | Description |
|---|---|
| Sample 1(A260626065-1) | Engineer sample – continuous transmit |
| Sample 2(A260626065-2) | Normal sample – Intermittent transmit |



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

# 3. SYSTEM TEST CONFIGURATION

## 3.1. Justification

The system was configured for testing in a continuous transmits condition.

## 3.2. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software provided by application.

## 3.3. Special Accessories

N/A.

## 3.4. Block Diagram/Schematics

Please refer to the related document

## 3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

## 3.6. Test Setup

Please refer to the test setup photo.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

# 4. SUMMARY OF TEST RESULTS

| Applied Standard: FCC Part 15 Subpart C | | | | |
|---|---|---|---|---|
| FCC Rules | Description of Test | Test Sample | Result | Remark |
| §15.247(a)(2) | 6dB Bandwidth | Sample 1 | Compliant | Appendix C.1 |
| §15.209(a) | Radiated Spurious Emissions | Sample 1<br>Sample 2 | Compliant | Note 1 |
| §15.247(b) | Maximum Average Conducted Output Power | Sample 1 | Compliant | Appendix C.2 |
| §15.247(e) | Power Spectral Density | Sample 1 | Compliant | Appendix C.3 |
| §15.247(d) | Band Edge Measurements and Conducted Spurious Emissions | Sample 1 | Compliant | Appendix C.4<br>Appendix C.5 |
| / | On Time and Duty Cycle | Sample 1 | / | Only reported;<br>Appendix C.6 |
| §15.205 | Emissions at Restricted Band | Sample 1 | Compliant | Appendix C.7 |
| §15.207(a) | Conducted Emissions | Sample 2 | Compliant | Note 1 |
| §15.203 | Antenna Requirements | Sample 1 | Compliant | Note 1 |
| §15.247(i)§1.1310<br>§15.247(i)§2.1091 | RF Exposure | N/A | Compliant | Note 2 |

*Remark:*
*1. Note 1 – Test results inside test report;*
*2. Note 2 – Test results in other test report (RF Exposure Evaluation);*


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

# 5. TEST RESULT

## 5.1. 6 dB Spectrum Bandwidth Measurement

### 5.1.1. Standard Applicable

According to §15.247(a) (2): For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

### 5.1.2. Measuring Instruments and Setting

Please refer to equipment's list in this report. The following table is the setting of the Spectrum Analyzer.

| Spectrum Parameter | Setting |
|---|---|
| Attenuation | Auto |
| Span Frequency | > RBW |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | No faster than coupled (auto) time. |

### 5.1.3. Test Procedures

5.1.3.1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
5.1.3.2. Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
Set the VBW ≥ [3 × RBW].
5.1.3.3. Measured the 6dB bandwidth and 99% occupied bandwidth by related function of the spectrum analyzer.

### 5.1.4. Test Setup Layout




### 5.1.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

### 5.1.6. Test Result of 6dB Spectrum Bandwidth

*PASS*

***Please refer to Appendix C.1***
*Remark:*
*1). Measured 6dB bandwidth at difference data rate for each mode and recorded worst case for each mode.*
*2). Test results including cable loss;*
*3). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40; 6.5Mbps at IEEE 802.11ax HE20; 13.5Mbps at IEEE 802.11ax HE40;*


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

## 5.2. Radiated Emissions Measurement

### 5.2.1. Standard Applicable

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|---|---|---|---|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| \1\ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293. | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (\2\) |
| 13.36-13.41 | | | |

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|---|---|---|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

5.2.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter | Setting |
|---|---|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10th carrier harmonic |
| RB / VB (Emission in restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |
| RB / VB (Emission in non-restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |

| Receiver Parameter | Setting |
|---|---|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG |
| Start ~ Stop Frequency | 150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB/VB 120kHz/1MHz for QP |

5.2.3. Test Procedures

**1) Sequence of testing 9 kHz to 30 MHz**

**Setup:**

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions.

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

**Premeasurement:**

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna height is 1.0 meter.

--- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

**Final measurement:**

--- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

**2) Sequence of testing 30 MHz to 1 GHz**

**Setup:**

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

**Premeasurement:**

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

**Final measurement:**

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter.

--- The final measurement will be done with QP detector with an EMI receiver.

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

**3) Sequence of testing 1 GHz to 18 GHz**

**Setup:**

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

**Premeasurement:**

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height scan range is 1 meter to 2.5 meter.

--- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

**Final measurement:**

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.

--- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

**4) Sequence of testing above 18 GHz**

**Setup:**

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 1 meter.

--- The EUT was set into operation.

**Premeasurement:**

--- The antenna is moved spherical over the EUT in different polarizations of the antenna.

**Final measurement:**

--- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.

--- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

5.2.4. Test Setup Layout




Below 30MHz




Below 1GHz




Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade form 3m to 1m.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

5.2.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.2.6. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

**FS (dBuV/m) = RA (dBuV) + AF (dB/m) + CL (dB) – AG (dB)**

| | |
|---|---|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude | AG = Amplifier Gain |
| AF = Antenna Factor | |

5.2.7. Results of Radiated Emissions (9 KHz~30MHz)

| | | | |
|---|---|---|---|
| Temperature | 23.8℃ | Humidity | 52.1% |
| Test Engineer | Jerry Chu | Configurations | IEEE 802.11b/g/n/ax |

| Freq. (MHz) | Level (dBuV) | Over Limit (dB) | Over Limit (dB) | Remark |
|---|---|---|---|---|
| - | - | - | - | See Note |

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
Limit line = specific limits (dBuV) + distance extrapolation factor.

5.2.8. Results of Radiated Emissions (30MHz~1GHz)

| | | | |
|---|---|---|---|
| Temperature | 23.8℃ | Humidity | 52.1% |
| Test Engineer | Jerry Chu | Configurations | IEEE 802.11b/g/n/ax |

**PASS.**

The test data please refer to following page.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

*External Antenna:*
*Horizontal*




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Margin | | |
|---|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector | Comment |
| 1 | | 44.2751 | 27.19 | -17.83 | 9.36 | 40.00 | -30.64 | QP | |
| 2 | | 72.5915 | 30.44 | -20.66 | 9.78 | 40.00 | -30.22 | QP | |
| 3 | | 96.7750 | 30.39 | -19.48 | 10.91 | 43.50 | -32.59 | QP | |
| 4 | | 273.2340 | 31.31 | -17.19 | 14.12 | 46.00 | -31.88 | QP | |
| 5 | * | 501.1790 | 37.77 | -12.22 | 25.55 | 46.00 | -20.45 | QP | |
| 6 | | 750.1082 | 33.57 | -8.13 | 25.44 | 46.00 | -20.56 | QP | |


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

*Vertical*




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Margin | | |
|---|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector | Comment |
| 1 | | 36.6374 | 38.00 | -18.91 | 19.09 | 40.00 | -20.91 | QP | |
| 2 | | 47.3255 | 37.60 | -18.16 | 19.44 | 40.00 | -20.56 | QP | |
| 3 | | 71.0803 | 38.60 | -20.85 | 17.75 | 40.00 | -22.25 | QP | |
| 4 | | 98.1418 | 37.99 | -19.62 | 18.37 | 43.50 | -25.13 | QP | |
| 5 | | 313.2760 | 29.28 | -15.47 | 13.81 | 46.00 | -32.19 | QP | |
| 6 | * | 625.0780 | 40.94 | -10.23 | 30.71 | 46.00 | -15.29 | QP | |

*Note:*

*Pre-scan all modes and recorded the worst case results in this report IEEE 802.11n HT20 MIMO mode (Low Channel).*

*Emission level (dBuV/m) = 20 log Emission level (uV/m).*

*Level = Reading + Factor, Margin = Level – Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor*



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

*Dipole Antenna:*
*Horizontal*




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Margin | | |
|---|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector | Comment |
| 1 | | 36.1269 | 30.09 | -18.78 | 11.31 | 40.00 | -28.69 | QP | |
| 2 | | 94.7600 | 34.40 | -19.91 | 14.49 | 43.50 | -29.01 | QP | |
| 3 | | 273.2340 | 34.31 | -17.19 | 17.12 | 46.00 | -28.88 | QP | |
| 4 | | 501.1790 | 41.77 | -12.22 | 29.55 | 46.00 | -16.45 | QP | |
| 5 | * | 625.0780 | 40.33 | -9.53 | 30.80 | 46.00 | -15.20 | QP | |
| 6 | | 750.1082 | 37.07 | -8.13 | 28.94 | 46.00 | -17.06 | QP | |


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

*Vertical*




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Margin | | |
|---|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector | Comment |
| 1 | | 43.8120 | 42.30 | -18.25 | 24.05 | 40.00 | -15.95 | QP | |
| 2 | | 68.6310 | 42.33 | -20.71 | 21.62 | 40.00 | -18.38 | QP | |
| 3 | | 98.1418 | 41.49 | -19.62 | 21.87 | 43.50 | -21.63 | QP | |
| 4 | * | 501.1790 | 46.05 | -12.54 | 33.51 | 46.00 | -12.49 | QP | |
| 5 | | 625.0780 | 42.94 | -10.23 | 32.71 | 46.00 | -13.29 | QP | |
| 6 | | 750.1082 | 39.58 | -9.03 | 30.55 | 46.00 | -15.45 | QP | |

*Note:*

*Pre-scan all modes and recorded the worst case results in this report IEEE 802.11n HT20 MIMO mode (Low Channel).*

*Emission level (dBuV/m) = 20 log Emission level (uV/m).*

*Level = Reading + Factor, Margin = Level – Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor*



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

5.2.9. Results for Radiated Emissions (1 GHz~26.5 GHz)

*Note: All the modes have been tested and recorded worst mode in the report.*
*IEEE 802.11b-(Ant1-the worst)*

*Channel 1 / 2412 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4824.00 | 54.02 | 33.06 | 35.04 | 3.94 | 55.98 | 74.00 | -18.02 | Peak | Horizontal |
| 4824.00 | 41.32 | 33.06 | 35.04 | 3.94 | 43.28 | 54.00 | -10.72 | Average | Horizontal |
| 4824.00 | 55.45 | 33.06 | 35.04 | 3.94 | 57.41 | 74.00 | -16.59 | Peak | Vertical |
| 4824.00 | 44.38 | 33.06 | 35.04 | 3.94 | 46.34 | 54.00 | -7.66 | Average | Vertical |

*Channel 6 / 2437 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4874.00 | 60.12 | 33.16 | 35.15 | 3.96 | 62.09 | 74.00 | -11.91 | Peak | Horizontal |
| 4874.00 | 41.12 | 33.16 | 35.15 | 3.96 | 43.09 | 54.00 | -10.91 | Average | Horizontal |
| 4874.00 | 57.12 | 33.16 | 35.15 | 3.96 | 59.09 | 74.00 | -14.91 | Peak | Vertical |
| 4874.00 | 40.96 | 33.16 | 35.15 | 3.96 | 42.93 | 54.00 | -11.07 | Average | Vertical |

*Channel 11 / 2462 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4924.00 | 60.52 | 33.26 | 35.14 | 3.98 | 62.62 | 74.00 | -11.38 | Peak | Horizontal |
| 4924.00 | 40.02 | 33.26 | 35.14 | 3.98 | 42.12 | 54.00 | -11.88 | Average | Horizontal |
| 4924.00 | 60.00 | 33.26 | 35.14 | 3.98 | 62.10 | 74.00 | -11.90 | Peak | Vertical |
| 4924.00 | 43.04 | 33.26 | 35.14 | 3.98 | 45.14 | 54.00 | -8.86 | Average | Vertical |

*IEEE 802.11g*-(Ant1-the worst)

*Channel 1 / 2412 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4824.00 | 58.03 | 33.06 | 35.04 | 3.94 | 59.99 | 74.00 | -14.01 | Peak | Horizontal |
| 4824.00 | 43.55 | 33.06 | 35.04 | 3.94 | 45.51 | 54.00 | -8.49 | Average | Horizontal |
| 4824.00 | 53.67 | 33.06 | 35.04 | 3.94 | 55.63 | 74.00 | -18.37 | Peak | Vertical |
| 4824.00 | 45.37 | 33.06 | 35.04 | 3.94 | 47.33 | 54.00 | -6.67 | Average | Vertical |


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

*Channel 6 / 2437 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4874.00 | 55.77 | 33.16 | 35.15 | 3.96 | 57.74 | 74.00 | -16.26 | Peak | Horizontal |
| 4874.00 | 41.41 | 33.16 | 35.15 | 3.96 | 43.38 | 54.00 | -10.62 | Average | Horizontal |
| 4874.00 | 55.58 | 33.16 | 35.15 | 3.96 | 57.55 | 74.00 | -16.45 | Peak | Vertical |
| 4874.00 | 45.39 | 33.16 | 35.15 | 3.96 | 47.36 | 54.00 | -6.64 | Average | Vertical |

*Channel 11 / 2462 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4924.00 | 59.42 | 33.26 | 35.14 | 3.98 | 61.52 | 74.00 | -12.48 | Peak | Horizontal |
| 4924.00 | 44.11 | 33.26 | 35.14 | 3.98 | 46.21 | 54.00 | -7.79 | Average | Horizontal |
| 4924.00 | 56.99 | 33.26 | 35.14 | 3.98 | 59.09 | 74.00 | -14.91 | Peak | Vertical |
| 4924.00 | 45.23 | 33.26 | 35.14 | 3.98 | 47.33 | 54.00 | -6.67 | Average | Vertical |

*IEEE 802.11n HT20 MIMO*

*Channel 1 / 2412 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4824.00 | 54.72 | 33.06 | 35.04 | 3.94 | 56.68 | 74.00 | -17.32 | Peak | Horizontal |
| 4824.00 | 43.25 | 33.06 | 35.04 | 3.94 | 45.21 | 54.00 | -8.79 | Average | Horizontal |
| 4824.00 | 54.84 | 33.06 | 35.04 | 3.94 | 56.80 | 74.00 | -17.20 | Peak | Vertical |
| 4824.00 | 45.41 | 33.06 | 35.04 | 3.94 | 47.37 | 54.00 | -6.63 | Average | Vertical |

*Channel 6 / 2437 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4874.00 | 57.69 | 33.16 | 35.15 | 3.96 | 59.66 | 74.00 | -14.34 | Peak | Horizontal |
| 4874.00 | 45.71 | 33.16 | 35.15 | 3.96 | 47.68 | 54.00 | -6.32 | Average | Horizontal |
| 4874.00 | 58.67 | 33.16 | 35.15 | 3.96 | 60.64 | 74.00 | -13.36 | Peak | Vertical |
| 4874.00 | 44.32 | 33.16 | 35.15 | 3.96 | 46.29 | 54.00 | -7.71 | Average | Vertical |

*Channel 11 / 2462 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4924.00 | 56.86 | 33.26 | 35.14 | 3.98 | 58.96 | 74.00 | -15.04 | Peak | Horizontal |
| 4924.00 | 42.06 | 33.26 | 35.14 | 3.98 | 44.16 | 54.00 | -9.84 | Average | Horizontal |
| 4924.00 | 57.16 | 33.26 | 35.14 | 3.98 | 59.26 | 74.00 | -14.74 | Peak | Vertical |
| 4924.00 | 41.53 | 33.26 | 35.14 | 3.98 | 43.63 | 54.00 | -10.37 | Average | Vertical |


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

*IEEE 802.11n HT40 MIMO*
*Channel 3 / 2422 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4844.00 | 56.75 | 33.06 | 35.04 | 3.94 | 58.71 | 74.00 | -15.29 | Peak | Horizontal |
| 4844.00 | 42.85 | 33.06 | 35.04 | 3.94 | 44.81 | 54.00 | -9.19 | Average | Horizontal |
| 4844.00 | 57.82 | 33.06 | 35.04 | 3.94 | 59.78 | 74.00 | -14.22 | Peak | Vertical |
| 4844.00 | 44.86 | 33.06 | 35.04 | 3.94 | 46.82 | 54.00 | -7.18 | Average | Vertical |

*Channel 6 / 2437 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4874.00 | 55.05 | 33.16 | 35.15 | 3.96 | 57.02 | 74.00 | -16.98 | Peak | Horizontal |
| 4874.00 | 42.18 | 33.16 | 35.15 | 3.96 | 44.15 | 54.00 | -9.85 | Average | Horizontal |
| 4874.00 | 54.36 | 33.16 | 35.15 | 3.96 | 56.33 | 74.00 | -17.67 | Peak | Vertical |
| 4874.00 | 45.90 | 33.16 | 35.15 | 3.96 | 47.87 | 54.00 | -6.13 | Average | Vertical |

*Channel 9 / 2452 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4904.00 | 53.77 | 33.26 | 35.14 | 3.98 | 55.87 | 74.00 | -18.13 | Peak | Horizontal |
| 4904.00 | 41.12 | 33.26 | 35.14 | 3.98 | 43.22 | 54.00 | -10.78 | Average | Horizontal |
| 4904.00 | 56.84 | 33.26 | 35.14 | 3.98 | 58.94 | 74.00 | -15.06 | Peak | Vertical |
| 4904.00 | 44.29 | 33.26 | 35.14 | 3.98 | 46.39 | 54.00 | -7.61 | Average | Vertical |

*IEEE 802.11ax HE20 MIMO*

*Channel 1 / 2412 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4824.00 | 58.82 | 33.06 | 35.04 | 3.94 | 60.78 | 74.00 | -13.22 | Peak | Horizontal |
| 4824.00 | 40.06 | 33.06 | 35.04 | 3.94 | 42.02 | 54.00 | -11.98 | Average | Horizontal |
| 4824.00 | 60.44 | 33.06 | 35.04 | 3.94 | 62.40 | 74.00 | -11.60 | Peak | Vertical |
| 4824.00 | 43.64 | 33.06 | 35.04 | 3.94 | 45.60 | 54.00 | -8.40 | Average | Vertical |

*Channel 6 / 2437 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4874.00 | 54.64 | 33.16 | 35.15 | 3.96 | 56.61 | 74.00 | -17.39 | Peak | Horizontal |
| 4874.00 | 44.35 | 33.16 | 35.15 | 3.96 | 46.32 | 54.00 | -7.68 | Average | Horizontal |
| 4874.00 | 58.71 | 33.16 | 35.15 | 3.96 | 60.68 | 74.00 | -13.32 | Peak | Vertical |


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 4874.00 | 43.24 | 33.16 | 35.15 | 3.96 | 45.21 | 54.00 | -8.79 | Average | Vertical |

*Channel 11 / 2462 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4924.00 | 55.49 | 33.26 | 35.14 | 3.98 | 57.59 | 74.00 | -16.41 | Peak | Horizontal |
| 4924.00 | 40.29 | 33.26 | 35.14 | 3.98 | 42.39 | 54.00 | -11.61 | Average | Horizontal |
| 4924.00 | 60.53 | 33.26 | 35.14 | 3.98 | 62.63 | 74.00 | -11.37 | Peak | Vertical |
| 4924.00 | 40.11 | 33.26 | 35.14 | 3.98 | 42.21 | 54.00 | -11.79 | Average | Vertical |

*IEEE 802.11ax HE40 MIMO*

*Channel 3 / 2422 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4844.00 | 55.76 | 33.06 | 35.04 | 3.94 | 57.72 | 74.00 | -16.28 | Peak | Horizontal |
| 4844.00 | 43.07 | 33.06 | 35.04 | 3.94 | 45.03 | 54.00 | -8.97 | Average | Horizontal |
| 4844.00 | 55.54 | 33.06 | 35.04 | 3.94 | 57.50 | 74.00 | -16.50 | Peak | Vertical |
| 4844.00 | 41.33 | 33.06 | 35.04 | 3.94 | 43.29 | 54.00 | -10.71 | Average | Vertical |

*Channel 6 / 2437 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4874.00 | 54.68 | 33.16 | 35.15 | 3.96 | 56.65 | 74.00 | -17.35 | Peak | Horizontal |
| 4874.00 | 45.50 | 33.16 | 35.15 | 3.96 | 47.47 | 54.00 | -6.53 | Average | Horizontal |
| 4874.00 | 55.30 | 33.16 | 35.15 | 3.96 | 57.27 | 74.00 | -16.73 | Peak | Vertical |
| 4874.00 | 42.09 | 33.16 | 35.15 | 3.96 | 44.06 | 54.00 | -9.94 | Average | Vertical |

*Channel 9 / 2452 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|---|---|---|---|---|---|---|---|---|---|
| 4904.00 | 54.66 | 33.26 | 35.14 | 3.98 | 56.76 | 74.00 | -17.24 | Peak | Horizontal |
| 4904.00 | 44.32 | 33.26 | 35.14 | 3.98 | 46.42 | 54.00 | -7.58 | Average | Horizontal |
| 4904.00 | 59.90 | 33.26 | 35.14 | 3.98 | 62.00 | 74.00 | -12.00 | Peak | Vertical |
| 4904.00 | 43.72 | 33.26 | 35.14 | 3.98 | 45.82 | 54.00 | -8.18 | Average | Vertical |

Notes*:*

1). Measuring frequencies from 9 KHz - 10th harmonic or 26.5GHz (which is less), at least have 20dB margin between lowest internal used/generated frequency to 30MHz.

2). Radiated emissions measured in frequency range from 9 KHz~10th harmonic or 26.5GHz (which is less) were made with an instrument using Peak detector mode.

3). Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

measured.

4). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20 - MIMO; 13.5Mbps at IEEE 802.11n HT40 - MIMO; 6.5Mbps at IEEE 802.11ax HE20 - MIMO; 13.5Mbps at IEEE 802.11ax HE40 - MIMO.

5).Measured Level = Reading Level + Factor, Margin = Measured Level–Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

## 5.3. Maximum Average Conducted Output Power Measurement

### 5.3.1. Standard Applicable

According to §15.247(b): For systems using digital modulation in the 2400-2483.5 MHz and 5725-5850 MHz band, the limit for maximum peak conducted output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter peak output power.

### 5.3.2. Measuring Instruments and Setting

Please refer to equipment's list in this report. The following table is the setting of the power meter.

### 5.3.3. Test Procedures

According to ANSI C63.10-2020 clause 11.9.2.3 RF average power meter method.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

Gate triggering can be implemented in such a way that the sweep of the instrument is only active during the burst period of the device. Any Gate triggering shall be performed on the full power portion of the pulses and care must be taken to ensure that static portions of the pulse are not included in the measurement (ensuring that the trace is averaged over the entire symbol range). All Gate triggered measurements shall be accompanied by a Gate setup plot in the test report.

### 5.3.4. Test Setup Layout




### 5.3.5. EUT Operation during Test

1) The EUT is configured to transmit continuously.
2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

### 5.3.6. Test Result of Maximum Average Conducted Output Power

Limits

| Mode | Antenna 1 Gain (dBi) | Antenna 2 Gain (dBi) | Directional Gain (dBi) | FCC Power Limit (dBm) |
|---|---|---|---|---|
| IEEE 802.11b | 2.87 | 2.87 | -/- | 30 |
| IEEE 802.11g | 2.87 | 2.87 | -/- | 30 |
| IEEE 802.11n HT20 | 2.87 | 2.87 | 2.87 | 30 |
| IEEE 802.11n HT40 | 2.87 | 2.87 | 2.87 | 30 |
| IEEE 802.11ax HE20 | 2.87 | 2.87 | 2.87 | 30 |
| IEEE 802.11ax HE40 | 2.87 | 2.87 | 2.87 | 30 |


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

*PASS*

***Please refer to Appendix C.2***

Remark:
1). Measured output power at difference data rate for each mode and recorded worst case for each mode.
2). Test results including cable loss;
3). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40; 6.5Mbps at IEEE 802.11ax HE20; 13.5Mbps at IEEE 802.11ax HE40; ;
4). For power measurements on IEEE 802.11 devices;
Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4;
Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any NANT;
Array Gain = 5 log (NANT/NSS) dB or 3 dB, whichever is less, for 20-MHz channel widths with NANT ≥ 5.


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

## 5.4. Power Spectral Density Measurement

### 5.4.1. Standard Applicable

According to §15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.4.2. Measuring Instruments and Setting

Please refer to equipment's list in this report. The following table is the setting of Spectrum Analyzer.

### 5.4.3. Test Procedures

a) Measure the duty cycle (D) of the transmitter output signal as described in 11.6.
b) Set instrument center frequency to DTS channel center frequency.
c) Set span to > 1.5 times the OBW.
d) Set RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
e) Set VBW ≥ [3 × RBW].
f) Detector = power averaging (rms) or sample detector (when rms not available).
g) Ensure that the number of measurement points in the sweep ≥ [2 × span / RBW].
h) Sweep time = auto couple.
i) Do not use sweep triggering; allow sweep to "free run."
j) Employ trace averaging (rms) mode over a minimum of 100 traces.
k) Use the peak marker function to determine the maximum amplitude level.
l) Add [10 log (1 / D)], where D is the duty cycle measured in step a), to the measured PSD to compute the average PSD during the actual transmission time.
m) If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this might require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

### 5.4.4. Test Setup Layout




### 5.4.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

5.4.6. Test Result of Power Spectral Density

Limits

| Mode | Antenna 1 Gain (dBi) | Antenna 2 Gain (dBi) | Directional Gain (dBi) | FCC PSD Limit (dBm/3KHz) |
|---|---|---|---|---|
| IEEE 802.11b | 2.87 | 2.87 | -/- | 8 |
| IEEE 802.11g | 2.87 | 2.87 | -/- | 8 |
| IEEE 802.11n HT20 | 2.87 | 2.87 | 5.88 | 8 |
| IEEE 802.11n HT40 | 2.87 | 2.87 | 5.88 | 8 |
| IEEE 802.11ax HE20 | 2.87 | 2.87 | 5.88 | 8 |
| IEEE 802.11ax HE40 | 2.87 | 2.87 | 5.88 | 8 |

Note:Directional Gain=Antenna 1(max)+3.01

*PASS*

***Please refer to Appendix C.3***

*Remark:*

1). Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode;

2). Test results including cable loss;

3). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40; 6.5Mbps at IEEE 802.11ax HE20; 13.5Mbps at IEEE 802.11ax HE40; ;

4) The PSD limits of IEEE 802.11n HT20 and IEEE 802.11 n HT40 for MIMO with CDD technology should be according to KDB662911 D01 Multiple Transmitter Output v02r01;

5). For MIMO with CCD technology device, The Directional Gain= Gain of individual transmit antennas (dBi) + Array gain;

ANTANT/NSS) dB, where ANT/NSS) dB, where NANT is the number of transmit antennas and NSS is 1.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

## 5.5. Band Edge Measurements and Conducted Spurious Emissions Test

### 5.5.1. Standard Applicable

According to §15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 5.5.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of the spectrum analyzer.

| Spectrum Parameter | Setting |
|---|---|
| Detector | Peak |
| Attenuation | Auto |
| RB / VB (Emission in restricted band) | 100KHz/300KHz |
| RB / VB (Emission in non-restricted band) | 100KHz/300KHz |

### 5.5.3. Test Procedures

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 300 KHz

The spectrum from 30 MHz to 26.5 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

### 5.5.4. Test Setup Layout

This test setup layout is the same as that shown in section 5.4.4.

### 5.5.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

### 5.5.6. Test Results of Conducted Spurious Emissions

*PASS*

***Please refer to Appendix C.4 for Band Edge Measurements;***

***Please refer to Appendix C.5 for Conducted Spurious Emissions.***

*Remark:*
*1). Measured RF conducted spurious emission at difference data rate for each mode and recorded worst case for each mode.*
*2). Test results including cable loss;*
*3). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40; 6.5Mbps at IEEE 802.11ax HE20; 13.5Mbps at IEEE 802.11ax HE40; ;*
*4). "---"means that the fundamental frequency not for 15.209 limits requirement.*
*5). Not recorded emission from 9 KHz to 30 MHz as emission level at least 20dBc lower than emission limit.*


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

## 5.6. On Time and Duty Cycle

### 5.6.1. Standard Applicable

None: for reporting purpose only.

### 5.6.2. Measuring Instruments and Setting

Please refer to equipment's list in this report. The following table is the setting of the spectrum analyzer.

### 5.6.3. Test Procedures

1. Set the centre frequency of the spectrum analyzer to the transmitting frequency;
2. Set the span=0MHz, RBW=8.0MHz, VBW=8.0MHz, Sweep time=auto;
3. Detector = peak;
4. Trace mode = Single hold.

### 5.6.4. Test Setup Layout




### 5.6.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

### 5.6.6. Test result

*For reporting purpose only.*

***Please refer to Appendix C.6***



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

## 5.7. Emissions in Restricted Bands

### 5.7.1 Standard Applicable

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 5.7.2. Test Setup Layout




### 5.7.3. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

### 5.7.4. Test Procedures

According to KDB558074 D01 15.247 Meas Guidance v05r02 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.
1). Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2). Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to an EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3). Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=1/T for AV detector.
4). Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5). Repeat above procedures until all measured frequencies were complete.
6). Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 12.2.2, 12.2.3, and 12.2.4 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
7). Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
8). Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
9). For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10). Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

E = EIRP – 20log D + 104.8=EIRP+95.26


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

Where:
E = electric field strength in dBμV/m,
EIRP = equivalent isotropic radiated power in dBm
D = specified measurement distance in meters.
11). Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
12). Compare the resultant electric field strength level to the applicable regulatory limit.
13). Perform radiated spurious emission test duress until all measured frequencies were complete.

5.7.5 Test Results

*PASS*

***Please refer to Appendix C.7***

*Remark:*

*1). Measured Band edge measurement for radiated emission at difference data rate for each mode and recorded worst case for each mode.*

*2). Test results including cable loss;*

*3). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40; 6.5Mbps at IEEE 802.11ax HE20; 13.5Mbps at IEEE 802.11ax HE40; ;*

*4). "---"means that the fundamental frequency not for 15.209 limits requirement.*


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

## 5.8. AC Power line conducted emissions

### 5.8.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range (MHz) | Limits (dBμV) | |
|---|---|---|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

* Decreasing linearly with the logarithm of the frequency

### 5.8.2 Block Diagram of Test Setup




### 5.8.3 Disturbance Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

**CD (dBuV) = RA (dBuV) + PL (dB) + CL (dB)**

| | |
|---|---|
| Where CD = Conducted Disturbance | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude | PL = 10 dB Pulse Limiter Factor |

### 5.8.4 Test Results

| | | | |
|---|---|---|---|
| Temperature | 22.5℃ | Humidity | 53.7% |
| Test Engineer | Jerry Chu | Configurations | IEEE 802.11b/g/n |

PASS.

The test data please refer to following page.


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

*External Antenna:*
*Line*




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Margin | | |
|---|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB | dBuV | dBuV | dB | Detector | Comment |
| 1 | | 0.433 | 22.22 | 20.38 | 42.60 | 57.19 | -14.59 | QP | |
| 2 | | 0.433 | 10.58 | 20.38 | 30.96 | 47.19 | -16.23 | AVG | |
| 3 | | 0.546 | 29.08 | 20.21 | 49.29 | 56.00 | -6.71 | QP | |
| 4 | | 0.546 | 4.18 | 20.21 | 24.39 | 46.00 | -21.61 | AVG | |
| 5 | | 1.050 | 29.15 | 19.61 | 48.76 | 56.00 | -7.24 | QP | |
| 6 | | 1.050 | 13.51 | 19.61 | 33.12 | 46.00 | -12.88 | AVG | |
| 7 | * | 2.940 | 29.62 | 19.73 | 49.35 | 56.00 | -6.65 | QP | |
| 8 | | 2.940 | 15.45 | 19.73 | 35.18 | 46.00 | -10.82 | AVG | |
| 9 | | 10.306 | 20.04 | 20.08 | 40.12 | 60.00 | -19.88 | QP | |
| 10 | | 10.306 | 9.09 | 20.08 | 29.17 | 50.00 | -20.83 | AVG | |
| 11 | | 17.209 | 10.71 | 19.95 | 30.66 | 60.00 | -29.34 | QP | |
| 12 | | 17.209 | 2.51 | 19.95 | 22.46 | 50.00 | -27.54 | AVG | |


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

*Neutral*




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Margin | | |
|---|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB | dBuV | dBuV | dB | Detector | Comment |
| 1 | | 0.424 | 22.52 | 20.36 | 42.88 | 57.37 | -14.49 | QP | |
| 2 | | 0.424 | 14.78 | 20.36 | 35.14 | 47.37 | -12.23 | AVG | |
| 3 | * | 0.550 | 30.60 | 20.18 | 50.78 | 56.00 | -5.22 | QP | |
| 4 | | 0.550 | 16.97 | 20.18 | 37.15 | 46.00 | -8.85 | AVG | |
| 5 | | 1.091 | 28.47 | 19.63 | 48.10 | 56.00 | -7.90 | QP | |
| 6 | | 1.091 | 12.29 | 19.63 | 31.92 | 46.00 | -14.08 | AVG | |
| 7 | | 2.450 | 29.97 | 19.76 | 49.73 | 56.00 | -6.27 | QP | |
| 8 | | 2.450 | 15.60 | 19.76 | 35.36 | 46.00 | -10.64 | AVG | |
| 9 | | 9.897 | 20.01 | 20.14 | 40.15 | 60.00 | -19.85 | QP | |
| 10 | | 9.897 | 8.80 | 20.14 | 28.94 | 50.00 | -21.06 | AVG | |
| 11 | | 17.421 | 11.56 | 19.89 | 31.45 | 60.00 | -28.55 | QP | |
| 12 | | 17.421 | 2.37 | 19.89 | 22.26 | 50.00 | -27.74 | AVG | |

****Note: 1). Pre-scan all modes and recorded the worst case results in this report IEEE 802.11n HT20 MIMO mode (Low Channel).*
*2). Measurement = Reading + Correct Factor, Margin = Measurement – Limit,*
*Correct Factor=Lisn Factor+Cable Factor+Insertion loss of Pulse Limiter.*


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

*Dipole Antenna:*
*Line*




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Margin | | |
|---|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB | dBuV | dBuV | dB | Detector | Comment |
| 1 | | 0.344 | 22.61 | 20.36 | 42.97 | 59.11 | -16.14 | QP | |
| 2 | | 0.344 | 11.25 | 20.36 | 31.61 | 49.11 | -17.50 | AVG | |
| 3 | | 0.546 | 26.45 | 20.21 | 46.66 | 56.00 | -9.34 | QP | |
| 4 | | 0.546 | 12.44 | 20.21 | 32.65 | 46.00 | -13.35 | AVG | |
| 5 | * | 1.081 | 27.26 | 19.62 | 46.88 | 56.00 | -9.12 | QP | |
| 6 | | 1.081 | 14.55 | 19.62 | 34.17 | 46.00 | -11.83 | AVG | |
| 7 | | 1.644 | 17.47 | 19.66 | 37.13 | 56.00 | -18.87 | QP | |
| 8 | | 1.644 | 5.32 | 19.66 | 24.98 | 46.00 | -21.02 | AVG | |
| 9 | | 2.409 | 13.51 | 19.71 | 33.22 | 56.00 | -22.78 | QP | |
| 10 | | 2.409 | 1.98 | 19.71 | 21.69 | 46.00 | -24.31 | AVG | |
| 11 | | 12.755 | 8.06 | 20.19 | 28.25 | 60.00 | -31.75 | QP | |
| 12 | | 12.755 | -1.03 | 20.19 | 19.16 | 50.00 | -30.84 | AVG | |


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

*Neutral*




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Margin | | |
|---|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB | dBuV | dBuV | dB | Detector | Comment |
| 1 | | 0.263 | 20.67 | 20.30 | 40.97 | 61.34 | -20.37 | QP | |
| 2 | | 0.263 | 7.97 | 20.30 | 28.27 | 51.34 | -23.07 | AVG | |
| 3 | * | 0.550 | 28.73 | 20.18 | 48.91 | 56.00 | -7.09 | QP | |
| 4 | | 0.550 | 18.42 | 20.18 | 38.60 | 46.00 | -7.40 | AVG | |
| 5 | | 1.077 | 26.64 | 19.63 | 46.27 | 56.00 | -9.73 | QP | |
| 6 | | 1.077 | 12.96 | 19.63 | 32.59 | 46.00 | -13.41 | AVG | |
| 7 | | 2.477 | 15.60 | 19.76 | 35.36 | 56.00 | -20.64 | QP | |
| 8 | | 2.477 | 5.71 | 19.76 | 25.47 | 46.00 | -20.53 | AVG | |
| 9 | | 8.304 | 11.02 | 20.39 | 31.41 | 60.00 | -28.59 | QP | |
| 10 | | 8.304 | -2.21 | 20.39 | 18.18 | 50.00 | -31.82 | AVG | |
| 11 | | 13.371 | 9.06 | 20.24 | 29.30 | 60.00 | -30.70 | QP | |
| 12 | | 13.371 | -1.56 | 20.24 | 18.68 | 50.00 | -31.32 | AVG | |

****Note: 1). Pre-scan all modes and recorded the worst case results in this report IEEE 802.11n HT20 MIMO mode (Low Channel).*
*2). Measurement = Reading + Correct Factor, Margin = Measurement – Limit,*
*Correct Factor=Lisn Factor+Cable Factor+Insertion loss of Pulse Limiter.*


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

## 5.9. Antenna Requirements

### 5.9.1 Standard Applicable

According to antenna requirement of §15.203.

According to antenna requirement of §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

### 5.9.2 Antenna Connected Construction

#### 5.9.2.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 5.9.2.2. Antenna Connector Construction

The directional gains of antenna used for transmitting is 2.87dBi(Max.) for Antenna 1 and 2.87dBi(Max.) for Antenna 2, 1.5dBi(Max.) for Antenna 3 and 1.5dBi(Max.) for Antenna 4,The antennas are external and dipole antennas, and their replacement is not considered. Please refer to the EUT photos for details.

#### 5.9.2.3. Results: Compliance.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

# 6. LIST OF MEASURING EQUIPMENTS

| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|---|---|---|---|---|---|---|
| 1 | Power Meter | R&S | NRVS | 100444 | 2026-05-21 | 2027-05-20 |
| 2 | Power Sensor | R&S | NRP-Z81 | 100458 | 2026-05-21 | 2027-05-20 |
| 3 | Power Sensor | R&S | U2021 | 10057 | 2026-05-21 | 2027-05-20 |
| 4 | Test Software | MWRFtest | MTS 8310 | / | N/A | N/A |
| 5 | RF Control Unit | MWRFtest | MW100-RFCB | / | 2025-11-07 | 2026-11-06 |
| 6 | MXA Signal Analyzer | Agilent | N9020A | MY53300304 | 2026-04-21 | 2027-04-20 |
| 7 | DC Power Supply | Agilent | E3642A | N/A | 2025-09-27 | 2026-09-26 |
| 8 | EMI Test Software | Farad | EZ-EMC | Ver. EMC-CON 3A1.1+ | N/A | N/A |
| 9 | 3m Semi Anechoic Chamber | Maorui | 966 | / | 2023-10-12 | 2026-10-11 |
| 10 | Positioning Controller | Max-Full | MF7802BS | MF780208586 | N/A | N/A |
| 11 | Active Loop Antenna | SCHWARZBECK | FMZB 1519B | 00005 | 2024-07-13 | 2027-07-12 |
| 12 | By-log Antenna | SCHWARZBECK | VULB9163 | 9163-470 | 2024-08-03 | 2027-08-02 |
| 13 | Horn Antenna | SCHWARZBECK | BBHA 9120D | 9120D-1925 | 2024-07-13 | 2027-07-12 |
| 14 | Broadband Horn Antenna | SCHWARZBECK | BBHA 9170 | 791 | 2024-07-13 | 2027-07-12 |
| 15 | Broadband Preamplifier | SCHWARZBECK | BBV9719 | 9719-025 | 2024-07-30 | 2027-07-29 |
| 16 | EMI Test Receiver | R&S | ESR3 | 101181 | 2026-05-06 | 2027-05-05 |
| 17 | RS SPECTRUM ANALYZER | R&S | FSP40 | 100503 | 2026-04-21 | 2027-04-20 |
| 18 | Low-frequency amplifier | SchwarzZBECK | BBV9745 | 00253 | 2025-09-27 | 2026-09-26 |
| 19 | High-frequency amplifier | JS Denki Pte | PA0118-43 | JSPA21009 | 2025-09-27 | 2026-09-26 |
| 20 | 6dB Attenuator | / | 100W/6dB | 1172040 | 2026-04-21 | 2027-04-20 |
| 21 | 3dB Attenuator | / | 2N-3dB | / | 2025-09-28 | 2026-09-27 |
| 22 | EMI Test Receiver | R&S | ESPI | 101940 | 2026-04-21 | 2027-04-20 |
| 23 | Artificial Mains | R&S | ENV216 | 101479 | 2026-04-21 | 2027-04-20 |
| 24 | Pulse Limiter | R&S | ESH3-Z2 | 102750-NB | 2026-05-06 | 2027-05-05 |
| 25 | EMI Test Software | Farad | EZ-EMC | Ver. EMC-CON 3A1.1+ | N/A | N/A |
| 26 | Antenna Mast | Max-Full | MFA-515BSN | 1308572 | N/A | N/A |


Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity

# 7. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

# 8. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

# 9. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

----------THE END OF REPORT----------



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity