



CTK Co., Ltd.
The First Leader of Global Regulatory Compliance

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

RF EXPOSURE EVALUATION

Applicant : Haier US Appliance Solutions, Inc.

Applicant Address : Appliance Park AP5-2N-65, Louisville, Kentucky, KY
40225, United States

Kind of Product : Wi-Fi/Bluetooth Combo ACM(Appliance Connect Module)

**Equipment
model name** : WCATC002

FCC ID : ZKJ-WCATC002

**Certification
Number IC** : 10229A-WCATC002

Standard Requirement

The following RF exposure procedures are applicable :

- FCC Rules

Part 1.1310 Radiofrequency radiation exposure limits

Table 1 below sets forth limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

Table 1—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

- ISED Rules

RSS-102 Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

Table 7 : RF field strength and power density limits for devices used by the general public (uncontrolled environment)

Frequency Range (MHz)	Electric Field (V _{RMS} /m)	Magnetic Field (A _{RMS} /m)	Power Density (W/m ²)	Reference Period (minutes)
10-20	27.46	0.0728	2	6
20-48	58.07/ $f^{0.25}$	0.1540/ $f^{0.25}$	8.944/ $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 × 10 ⁻⁴ $f^{0.5}$	6.67 × 10 ⁻⁵ f	616000/ $f^{1.2}$
Note: <i>f</i> is frequency in MHz.				

MPE Calculations

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user. The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

EIRP = P + G	Where, P = Power input to the antenna (mW) G = Power gain of the antenna (dBi)
--------------	--

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

$$G = \text{Log}^{-1} (\text{dB antenna gain} / 10)$$

Power density at the specific separation:

$S = PG / (4R^2\pi)$	Where, S = Maximum power density (mW/cm ²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)
----------------------	---

Estimated safe separation:

$R = \sqrt{(PG / 4\pi)}$	Where, P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)
--------------------------	--



CTK Co., Ltd.
The First Leader of Global Regulatory Compliance

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

RF Exposure Results

Mode	P (dBm)	G (dBi)	EIRP (dBm)	P (mW)	Power Density		Limit		R (cm)
					FCC (mW/cm ²)	ISED (W/m ²)	FCC (mW/cm ²)	ISED (W/m ²)	
BLE	3.27	2.60	5.87	2.12	0.0008	0.008	1.000	5.351	20
WLAN 2.4 GHz	16.37	2.60	18.97	43.35	0.0157	0.157	1.000	5.366	