REPORT No.: SZ25010160W01

TEST REPORT

APPLICANT	:	Power Idea Technology (Shenzhen) Co., Ltd.
PRODUCT NAME	:	BT Radio Speaker Mic
MODEL NAME	:	H3-BD
BRAND NAME	:	RugGear
FCC ID	:	ZLE-H3-BD
STANDARD(S)	:	47 CFR Part 15 Subpart C
RECEIPT DATE	:	2025-02-12
TEST DATE	:	2025-02-21 to 2025-03-25
ISSUE DATE	:	2025-05-19

Edited by: Su Xiaoxian

Su Xiaoxian (Rapporteur)

Approved by: Shen Junsheng

Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525
Http://www.morlab.cn E-mail: service@morlab.cn

DIRECTORY

1. Summary of Test Result ····· 4
1.1. Testing Applied Standards ····· 5
1.2. Test Equipment List ····· 6
1.3. Measurement Uncertainty ····· 8
1.4. Testing Laboratory ····· 8
2. General Description ····· 9
2.1. Information of Applicant and Manufacturer ····· 9
2.2. Information of EUT ····· 9
2.3. Channel List of EUT ····· 10
2.4. Test Configuration of EUT ····· 11
2.5. Test Conditions ····· 11
2.6. Test Setup Layout Diagram ····· 11
3. Test Results ····· 14
3.1. Antenna Requirement ····· 14
3.2. Hopping Mechanism ····· 15
3.3. Number of Hopping Frequency ····· 16
3.4. Duty Cycle of Test Signal ····· 17
3.5. Maximum Peak Conducted Output Power ····· 18
3.6. Maximum Average Conducted Output Power ····· 19
3.7. 20 dB Bandwidth ····· 20
3.8. Carried Frequency Separation ····· 21
3.9. Time of Occupancy (Dwell time) ····· 22
3.10. Conducted Spurious Emissions and Band Edge ····· 23
3.11. Conducted Emission ····· 24
3.12. Restricted Frequency Bands ····· 25
3.13. Radiated Emission ····· 26

Annex A Test Data and Result ····· 28

Change History		
Version	**Date**	**Reason for change**
1.0	2025-05-19	First edition

1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	15.247(a) 15.247(h)	Hopping Mechanism	N/A	N/A	PASS	No deviation
3	15.247(a)	Number of Hopping Frequency	Feb. 25, 2025	Li Xinpeng	PASS	No deviation
4	ANSI C63.10	Duty Cycle	Feb. 25, 2025	Li Xinpeng	PASS	No deviation
5	15.247(b)	Maximum Peak Conducted Output Power	Feb. 25, 2025	Li Xinpeng	PASS	No deviation
6	15.247(b)	Maximum Average Conducted Output Power	Feb. 25, 2025	Li Xinpeng	PASS	No deviation
7	15.247(a)	20dB Bandwidth	Feb. 25, 2025	Li Xinpeng	PASS	No deviation
8	15.247(a)	Carrier Frequency Separation	Feb. 25, 2025	Li Xinpeng	PASS	No deviation
9	15.247(a)	Time of Occupancy (Dwell time)	Feb. 25, 2025	Li Xinpeng	PASS	No deviation
10	15.247(d)	Conducted Spurious Emission and Band Edge	Feb. 25, 2025	Li Xinpeng	PASS	No deviation
11	15.207	Conducted Emission	Feb. 21, 2025	Fan Shengquan	PASS	No deviation
12	15.247(d)	Restricted Frequency Bands	Mar. 24, 2025	Gao Jianrou	PASS	No deviation

13	15.209, 15.247(d)	Radiated Emission	Mar. 24, 2025	Gao Jianrou	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013, KDB 558074 D01 v05r02 and DA 00-075.

Note 2: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 3: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

• 47 CFR Part 15 Subpart C Radio Frequency Devices

1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analzyer	MY53470836	N9010A	Agilent	2025.01.15	2026.01.14
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2025.01.06	2026.01.05
LISN	8127449	NSLK 8127	Schwarzbeck	2025.01.09	2026.01.08
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2024.05.30	2025.05.29
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	2024.07.02	2025.07.01

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

1.2.4 Radiated Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2024.05.30	2025.05.29
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2024.06.03	2025.06.02
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2024.06.22	2025.06.21
Preamplifier (10MHz-6GHz)	46732	S10M100L3802	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (2GHz-18GHz)	61171/61172	S020180L3203	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	N/A	N/A
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	N/A	N/A
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	N/A	N/A
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09

1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Number of Hopping Frequency	±5%	Confidence levels of 95%
Peak Output Power	±2.22dB	Confidence levels of 95%
Bandwidth	±5%	Confidence levels of 95%
Carrier Frequency Separation	±5%	Confidence levels of 95%
Time of Occupancy (Dwell time)	±5%	Confidence levels of 95%
Conducted Spurious Emission	±2.77dB	Confidence levels of 95%
Restricted Frequency Bands	±5%	Confidence levels of 95%
Radiated Emission	±2.95dB	Confidence levels of 95%
Conducted Emission	±2.44dB	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174

2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	Power Idea Technology (Shenzhen) Co., Ltd.
Applicant Address:	4th Floor, A Section, Languang Science&technology, Xinxi RD, Hi-Tech Industrial Park North, Nanshan, ShenZhen, China
Manufacturer:	Power Idea Technology (Shenzhen) Co., Ltd.
Manufacturer Address:	4th Floor, A Section, Languang Science&technology, Xinxi RD, Hi-Tech Industrial Park North, Nanshan, ShenZhen, China

2.2. Information of EUT

Product Name:	BT Radio Speaker Mic	
Sample No.:	1#, 6#	
Hardware Version:	V1.0	
Software Version:	V1.0	
Equipment Type:	Bluetooth classic	
Bluetooth Version:	3.0	
Modulation Type:	FHSS (GFSK(1Mbps), π/4-DQPSK(EDR 2Mbps), 8-DPSK(EDR 3Mbps))	
Operating Frequency Range:	2402MHz-2480MHz	
Antenna Type:	PCB Antenna	
Antenna Gain:	2.54dBi	
Accessory Information:	Battery	
	Brand Name:	N/A
	Model No.:	784050
	Serial No.:	N/A
	Capacity:	1600mAh
	Rated Voltage:	3.7V
	Charge Limit:	4.2V
	Manufacturer:	Dongguan SYO Electronic Technology Co.,LTD

Note 1: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.3. Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	**2402**	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	**78**	**2480**
19	2421	**39**	**2441**	59	2461		

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT

Test mode is used to control the EUT under the maximum power level during test.

2.5. Test Conditions

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.6. Test Setup Layout Diagram

2.6.1.Conducted Measurement



2.6.2.Conducted Emission Measurement



2.6.3.Radiation Measurement

1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to1GHz



3) For radiated emissions above 1GHz



3. Test Results

3.1. Antenna Requirement

3.1.1.Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2.Test Result

Antenna location	Antenna Type	Coupling Method
☒Internal ☐External	☐FPC Antenna ☐Spring Antenna ☐Ceramic Antenna ☐Integrated Antenna ☐Dipole Antenna ☒PCB Antenna ☐PIFA Antenna ☐On-board Antenna	☐I-PEX Connector ☐SMA Connector ☐RP-SMA Connector ☐Metal Shrapnel ☒Layout

3.2. Hopping Mechanism

3.2.1.Requirement

According to FCC section 15.247(a)(1), a frequency hopping spread spectrum system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

According to FCC section 15.247(h), the incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

3.2.2.Test Result

The hopping mechanism of the EUT is in compliance with the document "***Bluetooth core specification v5.1***".

3.3. Number of Hopping Frequency

3.3.1.Requirement

According to FCC section 15.247(a)(1)(iii), frequency hopping systems operating in the 2400MHz to 2483.5MHz bands shall use at least 15 hopping frequencies.

3.3.2.Test Procedures

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = the frequency band of operation
RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold
Allow the trace to stabilize

3.3.3.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4.Test Result

Refer to Annex A.1 in this report.

3.4. Duty Cycle of Test Signal

3.4.1.Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%).When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration(T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e.,no transmitter OFF-time is to be considered).
When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than ±2%; otherwise, the duty cycle is considered to be non constant.

3.4.2.Test Result

Refer to Annex A.2 in this report.

3.5. Maximum Peak Conducted Output Power

3.5.1. Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

3.5.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

3.5.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.4. Test Result

Refer to Annex A.3 in this report.

3.6. Maximum Average Conducted Output Power

3.6.1.Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

3.6.2.Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

3.6.3.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4.Test Result

Refer to Annex A.4 in this report.

3.7. 20 dB Bandwidth

3.7.1.Requirement

According to FCC section 15.247(a)(1), the 20 dB bandwidth is known as the 99% emission bandwidth, or 20 dB bandwidth (10*log1% = 20 dB) taking the total RF output power.

3.7.1.Test Procedures

Use the following spectrum analyzer settings:
Span = between 2 to 5 times the OBW, centered on the test channel
RBW= 1% to 5% of the OBW
VBW ≥ 3 x RBW
Sweep = auto
Detector function = peak
Trace = max hold

3.7.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.7.3.Test Result

Refer to Annex A.5 in this report.

3.8. Carried Frequency Separation

3.8.1.Requirement

According to FCC section 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

3.8.2.Test Procedures

The EUT must have its hopping function enabled. According to DA 00-705, use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels
Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span
Video (or Average) Bandwidth (VBW) ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold
Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

3.8.3.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.8.4.Test Result

Refer to Annex A.6 in this report.

3.9. Time of Occupancy (Dwell time)

3.9.1.Requirement

According to FCC section 15.247(a) (1) (iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

3.9.2.Test Procedures

Normal Mode:
DH1: Dwell time equal to Pulse time (ms) *(1600 / 2 /79)*31.6 Millisecond DH3: Dwell time equal to Pulse time (ms) * (1600 /4 /79) *31.6 Millisecond DH5: Dwell time equal to Pulse Time (ms)* (1600 / 6 /79) *31.6 Millisecond
AFH Mode:
DH1: Dwell time equal to Pulse time (ms) *(800 / 2 /20)*(0.4*20) Millisecond DH3: Dwell time equal to Pulse time (ms) * (800 / 4 /20)*(0.4*20) Millisecond DH5: Dwell time equal to Pulse Time (ms)* (800 / 6 /20)*(0.4*20) Millisecond.

3.9.3.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.9.4.Test Result

Refer to Annex A.7 in this report.

3.10. Conducted Spurious Emissions and Band Edge

3.10.1.Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.10.2.Test Procedures

Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold
Allow the trace to stabilize.

3.10.3.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.10.4.Test Result

Refer to Annex A.8 and A.9 in this report.

3.11. Conducted Emission

3.11.1.Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

(a) The lower limit shall apply at the band edges.

(b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.11.2.Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

3.11.3.Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.11.4.Test Result

Refer to Annex A.10 in this report.

3.12. Restricted Frequency Bands

3.12.1.Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.12.2.Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.
For the Test Antenna:
Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1GHz, 100 kHz for f < 1GHz
VBW = 3 MHz
Sweep = auto
Detector function = peak/average
Trace = max hold
Allow the trace to stabilize

3.12.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.12.4.Test Result

Refer to Annex A.11 in this report.

3.13. Radiated Emission

3.13.1.Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).

3.13.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz.The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.13.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.13.4.Test Result

Refer to Annex A.12 in this report.

Annex A Test Data and Result

A.1. Number of Hopping Frequency

Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH5	Ant1	79	15	Pass
NVNT	2-DH5	Ant1	79	15	Pass
NVNT	3-DH5	Ant1	79	15	Pass

Test Graphs

Hopping No. NVNT 1-DH5 2441MHz Ant1



Hopping No. NVNT 2-DH5 2441MHz Ant1



Hopping No. NVNT 3-DH5 2441MHz Ant1



A.2. Duty Cycle of Test Signal

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	1-DH5	2402	Ant1	77.84	1.09	0.34
NVNT	1-DH5	2441	Ant1	77.87	1.09	0.34
NVNT	1-DH5	2480	Ant1	77.87	1.09	0.34
NVNT	2-DH5	2402	Ant1	78.08	1.07	0.34
NVNT	2-DH5	2441	Ant1	78.08	1.07	0.34
NVNT	2-DH5	2480	Ant1	78.11	1.07	0.34
NVNT	3-DH5	2402	Ant1	78.11	1.07	0.34
NVNT	3-DH5	2441	Ant1	78.13	1.07	0.34
NVNT	3-DH5	2480	Ant1	78.11	1.07	0.34

Test Graphs

Duty Cycle NVNT 1-DH5 2402MHz Ant1



Duty Cycle NVNT 1-DH5 2441MHz Ant1



Duty Cycle NVNT 1-DH5 2480MHz Ant1



Duty Cycle NVNT 2-DH5 2402MHz Ant1



Duty Cycle NVNT 2-DH5 2441MHz Ant1



Duty Cycle NVNT 2-DH5 2480MHz Ant1



Duty Cycle NVNT 3-DH5 2402MHz Ant1



Duty Cycle NVNT 3-DH5 2441MHz Ant1



Duty Cycle NVNT 3-DH5 2480MHz Ant1



A.3. Maximum Peak Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	5.01	0	5.01	0.00317	30	Pass
NVNT	1-DH5	2441	Ant1	5.28	0	5.28	0.00337	30	Pass
NVNT	1-DH5	2480	Ant1	5.69	0	5.69	0.00371	30	Pass
NVNT	2-DH5	2402	Ant1	4.27	0	4.27	0.00267	30	Pass
NVNT	2-DH5	2441	Ant1	4.61	0	4.61	0.00289	30	Pass
NVNT	2-DH5	2480	Ant1	4.78	0	4.78	0.00301	30	Pass
NVNT	3-DH5	2402	Ant1	4.59	0	4.59	0.00288	30	Pass
NVNT	3-DH5	2441	Ant1	4.81	0	4.81	0.00303	30	Pass
NVNT	3-DH5	2480	Ant1	4.98	0	4.98	0.00315	30	Pass

Test Graphs

Peak Power NVNT 1-DH5 2402MHz Ant1



Peak Power NVNT 1-DH5 2441MHz Ant1

Peak Power NVNT 1-DH5 2480MHz Ant1



Peak Power NVNT 2-DH5 2402MHz Ant1



Peak Power NVNT 2-DH5 2441MHz Ant1



Peak Power NVNT 2-DH5 2480MHz Ant1

Peak Power NVNT 3-DH5 2402MHz Ant1



Peak Power NVNT 3-DH5 2441MHz Ant1



Peak Power NVNT 3-DH5 2480MHz Ant1



A.4. Maximum Average Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	3.69	1.09	4.78	0.00301	30	Pass
NVNT	1-DH5	2441	Ant1	4.09	1.09	5.18	0.0033	30	Pass
NVNT	1-DH5	2480	Ant1	4.41	1.09	5.5	0.00355	30	Pass
NVNT	2-DH5	2402	Ant1	1.3	1.07	2.37	0.00173	30	Pass
NVNT	2-DH5	2441	Ant1	1.93	1.07	3	0.002	30	Pass
NVNT	2-DH5	2480	Ant1	1.76	1.07	2.83	0.00192	30	Pass
NVNT	3-DH5	2402	Ant1	1.58	1.07	2.65	0.00184	30	Pass
NVNT	3-DH5	2441	Ant1	1.73	1.07	2.8	0.00191	30	Pass
NVNT	3-DH5	2480	Ant1	1.78	1.07	2.85	0.00193	30	Pass

Test Graphs

Average Power NVNT 1-DH5 2402MHz Ant1

Average Power NVNT 1-DH5 2441MHz Ant1



Average Power NVNT 1-DH5 2480MHz Ant1



Average Power NVNT 2-DH5 2402MHz Ant1



Average Power NVNT 2-DH5 2441MHz Ant1



Average Power NVNT 2-DH5 2480MHz Ant1



Average Power NVNT 3-DH5 2402MHz Ant1



Average Power NVNT 3-DH5 2441MHz Ant1



Average Power NVNT 3-DH5 2480MHz Ant1



A.5. 20 dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)
NVNT	1-DH5	2402	Ant1	0.9257
NVNT	1-DH5	2441	Ant1	0.92
NVNT	1-DH5	2480	Ant1	0.9307
NVNT	2-DH5	2402	Ant1	1.333
NVNT	2-DH5	2441	Ant1	1.259
NVNT	2-DH5	2480	Ant1	1.228
NVNT	3-DH5	2402	Ant1	1.3
NVNT	3-DH5	2441	Ant1	1.298
NVNT	3-DH5	2480	Ant1	1.298

Test Graphs

-20dB Bandwidth NVNT 1-DH5 2402MHz Ant1

-20dB Bandwidth NVNT 1-DH5 2441MHz Ant1

-20dB Bandwidth NVNT 1-DH5 2480MHz Ant1

-20dB Bandwidth NVNT 2-DH5 2402MHz Ant1

-20dB Bandwidth NVNT 2-DH5 2441MHz Ant1

-20dB Bandwidth NVNT 2-DH5 2480MHz Ant1

-20dB Bandwidth NVNT 3-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2441MHz Ant1

-20dB Bandwidth NVNT 3-DH5 2480MHz Ant1

A.6. Carried Frequency Separation

Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH5	Ant1	2401.94	2402.97	1.03	0.617	Pass
NVNT	1-DH5	Ant1	2440.976	2441.994	1.018	0.613	Pass
NVNT	1-DH5	Ant1	2478.994	2480.008	1.014	0.62	Pass
NVNT	2-DH5	Ant1	2402.014	2402.994	0.98	0.889	Pass
NVNT	2-DH5	Ant1	2440.998	2442.022	1.024	0.839	Pass
NVNT	2-DH5	Ant1	2478.986	2480.156	1.17	0.819	Pass
NVNT	3-DH5	Ant1	2402.004	2402.992	0.988	0.867	Pass
NVNT	3-DH5	Ant1	2441	2442	1	0.865	Pass
NVNT	3-DH5	Ant1	2479.008	2479.986	0.978	0.865	Pass

Test Graphs

CFS NVNT 1-DH5 2402MHz Ant1



CFS NVNT 1-DH5 2441MHz Ant1

CFS NVNT 1-DH5 2480MHz Ant1

CFS NVNT 2-DH5 2402MHz Ant1



CFS NVNT 2-DH5 2441MHz Ant1



CFS NVNT 2-DH5 2480MHz Ant1



CFS NVNT 3-DH5 2402MHz Ant1



CFS NVNT 3-DH5 2441MHz Ant1



CFS NVNT 3-DH5 2480MHz Ant1



A.7. Time of Occupancy (Dwell time)

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH5	2402	Ant1	2.902	310.514	107	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.902	310.514	107	31600	400	Pass
NVNT	1-DH5	2480	Ant1	2.903	310.621	107	31600	400	Pass
NVNT	2-DH5	2402	Ant1	2.911	311.477	107	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.17	232.19	107	31600	400	Pass
NVNT	2-DH5	2480	Ant1	2.17	232.19	107	31600	400	Pass
NVNT	3-DH5	2402	Ant1	2.912	311.584	107	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.259	241.713	107	31600	400	Pass
NVNT	3-DH5	2480	Ant1	2.913	311.691	107	31600	400	Pass

Test Graphs

Dwell NVNT 1-DH5 2402MHz Ant1 One Burst



Dwell NVNT 1-DH5 2402MHz Ant1 Accumulated



Dwell NVNT 1-DH5 2441MHz Ant1 One Burst



Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated



Dwell NVNT 1-DH5 2480MHz Ant1 One Burst



Dwell NVNT 1-DH5 2480MHz Ant1 Accumulated



Dwell NVNT 2-DH5 2402MHz Ant1 One Burst



Dwell NVNT 2-DH5 2402MHz Ant1 Accumulated



Dwell NVNT 2-DH5 2441MHz Ant1 One Burst



Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated



Dwell NVNT 2-DH5 2480MHz Ant1 One Burst



Dwell NVNT 2-DH5 2480MHz Ant1 Accumulated



Dwell NVNT 3-DH5 2402MHz Ant1 One Burst



Dwell NVNT 3-DH5 2402MHz Ant1 Accumulated



Dwell NVNT 3-DH5 2441MHz Ant1 One Burst



Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated



Dwell NVNT 3-DH5 2480MHz Ant1 One Burst



Dwell NVNT 3-DH5 2480MHz Ant1 Accumulated



A.8. Conducted Spurious Emissions

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	-43.89	-20	Pass
NVNT	1-DH5	2441	Ant1	-48.74	-20	Pass
NVNT	1-DH5	2480	Ant1	-52.76	-20	Pass
NVNT	2-DH5	2402	Ant1	-50.71	-20	Pass
NVNT	2-DH5	2441	Ant1	-50.42	-20	Pass
NVNT	2-DH5	2480	Ant1	-52.02	-20	Pass
NVNT	3-DH5	2402	Ant1	-50.99	-20	Pass
NVNT	3-DH5	2441	Ant1	-53.05	-20	Pass
NVNT	3-DH5	2480	Ant1	-52.21	-20	Pass

Test Graphs
Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Ref

Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Emission



Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Ref

Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Emission



Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Ref

Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Emission



Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Ref

Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Emission



Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Ref

Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Emission



Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Ref

Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Ref

Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Ref

Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Ref

Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Emission



A.9. Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	No-Hopping	-42.11	-20	Pass
NVNT	1-DH5	2480	Ant1	No-Hopping	-51.6	-20	Pass
NVNT	2-DH5	2402	Ant1	No-Hopping	-44.69	-20	Pass
NVNT	2-DH5	2480	Ant1	No-Hopping	-43.47	-20	Pass
NVNT	3-DH5	2402	Ant1	No-Hopping	-45.73	-20	Pass
NVNT	3-DH5	2480	Ant1	No-Hopping	-45.56	-20	Pass
NVNT	1-DH5	2402	Ant1	Hopping	-53.66	-20	Pass
NVNT	1-DH5	2480	Ant1	Hopping	-51.81	-20	Pass
NVNT	2-DH5	2402	Ant1	Hopping	-54.5	-20	Pass
NVNT	2-DH5	2480	Ant1	Hopping	-44.71	-20	Pass
NVNT	3-DH5	2402	Ant1	Hopping	-52.67	-20	Pass
NVNT	3-DH5	2480	Ant1	Hopping	-45.15	-20	Pass

Test Graphs

Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Ref

Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Ref

Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Ref

Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Ref

Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Ref

Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Emission



Test Graphs

Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Emission



A.10. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+PC+PC adapter+Data cable+Earphone+BT TX

Test voltage: AC 120V/60Hz

The measurement results are obtained as below:

E [dBμV] $=U_R + L_{Cable\ loss}$ [dB] + A_{Factor}

U_R: Receiver Reading

A_{Factor}: Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1590	49.47	32.47	65.52	55.52	Line	PASS
2	0.2085	42.73	28.33	63.26	53.26		PASS
3	2.9582	33.52	24.13	56.00	46.00		PASS
4	8.7985	23.40	16.51	60.00	50.00		PASS
5	17.8765	43.23	35.14	60.00	50.00		PASS
6	21.2958	41.80	34.01	60.00	50.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1905	46.22	32.38	64.02	54.02	Neutral	PASS
2	0.3030	35.48	25.74	60.16	50.16		PASS
3	0.4875	32.99	24.68	56.21	46.21		PASS
4	2.5979	30.54	22.50	56.00	46.00		PASS
5	4.8388	33.03	26.82	56.00	46.00		PASS
6	19.1456	39.46	28.40	60.00	50.00		PASS

A.11. Restricted Frequency Bands

Note 1: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (Horizontal) was recorded in this test report.

Note 2: All test modes were considered and evaluated respectively by performing full test, only the worst data were recorded.

GFSK Mode

Plot for Channel 0



Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2350.44	2.3	39.71	37.460	54.00	14.29	150	203	AV	PASS
2350.56	15.2	52.69	37.460	74.00	21.31	150	37	PK	PASS
2372.66	2.1	39.58	37.480	54.00	14.42	150	136	AV	PASS
2373.88	14.9	52.38	37.480	74.00	21.62	150	78	PK	PASS
2385.97	15.8	53.25	37.490	74.00	20.75	150	100	PK	PASS
2385.97	5.1	42.59	37.490	54.00	11.41	150	230	AV	PASS

Plot for Channel 78



Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2483.52	19.1	57.40	38.280	74.00	16.60	150	135	PK	PASS
2483.52	8.5	46.76	38.280	54.00	7.24	150	216	AV	PASS
2483.66	18.4	56.72	38.280	74.00	17.28	150	89	PK	PASS
2483.76	8.2	46.44	38.270	54.00	7.56	150	216	AV	PASS
2484.24	7.1	45.32	38.270	54.00	8.68	150	216	AV	PASS
2485.25	17.8	56.09	38.270	74.00	17.91	150	334	PK	PASS

8-DPSK Mode

Plot for Channel 0



Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2377.43	17.6	55.10	37.480	74.00	18.90	150	145	PK	PASS
2378.77	4.7	42.21	37.480	54.00	11.79	150	56	AV	PASS
2386.10	5.5	42.97	37.490	54.00	11.03	150	98	AV	PASS
2388.29	17.3	54.80	37.490	74.00	19.20	150	306	PK	PASS
2389.64	4.9	42.37	37.490	54.00	11.63	150	230	AV	PASS
2389.64	17.4	54.89	37.490	74.00	19.11	150	322	PK	PASS

Plot for Channel 78



Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2483.52	20.0	58.28	38.280	74.00	15.72	150	94	PK	PASS
2483.57	6.7	45.02	38.280	54.00	8.98	150	56	AV	PASS
2483.76	6.5	44.80	38.270	54.00	9.20	150	216	AV	PASS
2483.81	18.4	56.64	38.270	74.00	17.36	150	56	PK	PASS
2483.95	6.3	44.59	38.270	54.00	9.41	150	86	AV	PASS
2484.05	17.9	56.20	38.270	74.00	17.80	150	52	PK	PASS

A.12. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

E [dBμV/m] $=U_R + A_T + A_{Factor}$ [dB]; $A_T = L_{Cable\ loss}$ [dB]$-G_{preamp}$ [dB]

A_T: Total correction Factor except Antenna

U_R: Receiver Reading

G_{preamp}: Preamplifier Gain

A_{Factor}: Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note 4: All test modes were considered and evaluated respectively by performing full test, only the worst data were recorded.

Field strength of fundamental:

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Detector	Antenna Polarity
2401.85	40.8	78.30	37.530	PK	Horizontal

The field strength (the lowest) of fundamenta is more than 20dB higher than the unwanted emissions, in accordance with FCC part 15.215(b).

GFSK Mode

Plot for Channel 0



(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
59.59	64.4	35.77	-28.580	40.00	4.23	150	200	PK	PASS
72.00	66.3	34.95	-31.380	40.00	5.05	150	130	PK	PASS
86.94	64.1	31.88	-32.200	40.00	8.12	150	55	PK	PASS
250.40	59.8	32.34	-27.460	46.00	13.66	150	19	PK	PASS
332.12	53.6	29.14	-24.410	46.00	16.86	150	220	PK	PASS
899.70	42.1	30.50	-11.630	46.00	15.50	150	29	PK	PASS



(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1601.91	47.1	46.71	-0.380	74.00	27.29	150	155	PK	PASS
1601.91	45.1	44.69	-0.380	54.00	9.31	150	155	AV	PASS
2659.04	26.8	33.07	6.260	54.00	20.93	150	70	AV	PASS
2695.49	40.5	46.63	6.110	74.00	27.37	150	169	PK	PASS
4803.56	54.0	48.88	-5.150	74.00	25.12	150	198	PK	PASS
4803.56	52.0	46.84	-5.150	54.00	7.16	150	198	AV	PASS
5219.07	50.2	46.84	-3.340	74.00	27.16	150	263	PK	PASS
5225.07	42.5	39.20	-3.250	54.00	14.80	150	102	AV	PASS
11076.27	29.2	42.93	13.770	54.00	11.07	150	0	AV	PASS
11111.27	37.9	51.90	14.010	74.00	22.10	150	351	PK	PASS
14552.89	34.4	54.43	20.080	74.00	19.57	150	315	PK	PASS
14687.39	25.2	45.72	20.570	54.00	8.28	150	306	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
36.64	62.7	33.35	-29.390	40.00	6.65	150	59	PK	PASS
61.19	63.6	34.81	-28.770	40.00	5.19	150	100	PK	PASS
104.40	58.0	28.53	-29.470	43.50	14.97	150	310	PK	PASS
273.82	59.9	33.63	-26.290	46.00	12.37	150	250	PK	PASS
332.95	57.1	32.59	-24.490	46.00	13.41	150	220	PK	PASS
913.08	45.6	33.46	-12.100	46.00	12.54	150	315	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1601.91	41.7	41.27	-0.380	54.00	12.73	150	38	AV	PASS
1601.91	44.2	43.86	-0.380	74.00	30.14	150	38	PK	PASS
2660.37	47.2	53.40	6.250	74.00	20.60	150	109	PK	PASS
2661.70	31.3	37.57	6.240	54.00	16.43	150	109	AV	PASS
4803.56	53.4	48.21	-5.150	54.00	5.79	150	351	AV	PASS
4803.56	56.2	51.09	-5.150	74.00	22.91	150	351	PK	PASS
6000.10	37.4	37.22	-0.160	54.00	16.78	150	132	AV	PASS
6108.60	42.7	43.59	0.900	74.00	30.41	150	219	PK	PASS
9634.22	31.7	40.88	9.200	54.00	13.12	150	351	AV	PASS
11258.78	39.5	52.66	13.190	74.00	21.34	150	262	PK	PASS
14536.38	25.7	45.70	20.000	54.00	8.30	150	190	AV	PASS
14617.39	34.5	54.86	20.390	74.00	19.14	150	14	PK	PASS

Plot for Channel 39



(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
60.41	64.6	35.90	-28.650	40.00	4.10	150	200	PK	PASS
72.10	66.7	35.19	-31.460	40.00	4.81	150	123	PK	PASS
87.33	64.3	32.18	-32.110	40.00	7.82	150	18	PK	PASS
185.11	60.9	30.58	-30.280	43.50	12.92	150	13	PK	PASS
266.01	58.9	31.59	-27.350	46.00	14.41	150	23	PK	PASS
468.03	49.7	28.16	-21.540	46.00	17.84	150	49	PK	PASS



(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1627.70	48.1	47.85	-0.210	74.00	26.15	150	153	PK	PASS
1627.70	45.3	45.07	-0.210	54.00	8.93	150	153	AV	PASS
2475.44	39.1	45.02	5.910	74.00	28.98	150	204	PK	PASS
3256.01	44.1	32.75	-11.30	54.00	21.25	150	119	AV	PASS
4881.56	48.6	43.61	-5.010	54.00	10.39	150	191	AV	PASS
4882.06	52.5	47.46	-5.020	74.00	26.54	150	191	PK	PASS
5219.07	42.0	38.61	-3.340	54.00	15.39	150	46	AV	PASS
5219.07	49.0	45.68	-3.340	74.00	28.32	150	38	PK	PASS
7323.14	36.4	40.65	4.300	54.00	13.35	150	83	AV	PASS
11045.77	39.1	52.52	13.380	74.00	21.48	150	191	PK	PASS
14473.88	34.7	54.19	19.510	74.00	19.81	150	220	PK	PASS
14697.39	24.7	45.29	20.600	54.00	8.71	150	351	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
36.21	64.4	34.85	-29.530	40.00	5.15	150	325	PK	PASS
60.31	63.2	34.61	-28.620	40.00	5.39	150	99	PK	PASS
82.43	62.9	31.14	-31.760	40.00	8.86	150	59	PK	PASS
279.25	57.9	31.58	-26.320	46.00	14.42	150	290	PK	PASS
331.93	55.9	31.45	-24.400	46.00	14.55	150	275	PK	PASS
944.61	41.5	30.29	-11.180	46.00	15.71	150	114	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1627.70	45.6	45.39	-0.210	74.00	28.61	150	32	PK	PASS
1627.70	42.2	41.95	-0.210	54.00	12.05	150	32	AV	PASS
3990.03	57.6	49.56	-8.070	74.00	24.44	150	108	PK	PASS
3990.03	42.5	34.39	-8.070	54.00	19.61	150	108	AV	PASS
4881.56	52.1	47.05	-5.010	54.00	6.95	150	12	AV	PASS
4881.56	55.1	50.13	-5.010	74.00	23.87	150	20	PK	PASS
5224.57	43.8	40.51	-3.260	54.00	13.49	150	130	AV	PASS
5225.07	50.6	47.39	-3.250	74.00	26.61	150	130	PK	PASS
11123.77	29.0	42.94	13.940	54.00	11.06	150	5	AV	PASS
11182.77	38.0	51.60	13.590	74.00	22.40	150	57	PK	PASS
14471.38	34.6	54.06	19.490	74.00	19.94	150	286	PK	PASS
14695.39	24.8	45.40	20.590	54.00	8.60	150	190	AV	PASS

Plot for Channel 78



(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
59.63	64.5	35.93	-28.580	40.00	4.07	150	207	PK	PASS
72.05	67.2	35.75	-31.420	40.00	4.25	150	126	PK	PASS
88.20	63.3	31.35	-31.960	43.50	12.15	150	40	PK	PASS
154.02	59.4	27.76	-31.620	43.50	15.74	150	258	PK	PASS
333.24	54.1	29.56	-24.520	46.00	16.44	150	166	PK	PASS
782.95	45.7	30.27	-15.380	46.00	15.73	150	9	PK	PASS



(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1653.92	49.3	49.23	-0.040	74.00	24.77	150	151	PK	PASS
1653.92	47.6	47.59	-0.040	54.00	6.41	150	151	AV	PASS
2659.48	28.1	34.36	6.260	54.00	19.64	150	90	AV	PASS
2660.81	41.7	47.91	6.250	74.00	26.09	150	71	PK	PASS
3307.51	44.6	33.61	-10.98	54.00	20.39	150	242	AV	PASS
3308.01	49.5	38.55	-10.98	74.00	35.45	150	126	PK	PASS
4959.57	45.6	40.93	-4.630	54.00	13.07	150	212	AV	PASS
4959.57	49.2	44.57	-4.630	74.00	29.43	150	205	PK	PASS
5222.57	41.7	38.40	-3.290	54.00	15.60	150	351	AV	PASS
5225.07	49.5	46.27	-3.250	74.00	27.73	150	25	PK	PASS
14612.89	33.9	54.23	20.370	74.00	19.77	150	264	PK	PASS
14688.89	25.0	45.53	20.570	54.00	8.47	150	83	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
31.60	65.9	35.28	-30.570	40.00	4.72	150	129	PK	PASS
60.36	63.6	34.96	-28.640	40.00	5.04	150	84	PK	PASS
72.15	68.3	36.78	-31.500	40.00	3.22	150	99	PK	PASS
276.97	59.7	33.49	-26.180	46.00	12.51	150	281	PK	PASS
332.75	57.7	33.20	-24.480	46.00	12.80	150	241	PK	PASS
917.25	40.4	28.52	-11.840	46.00	17.48	150	0	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1653.92	41.9	41.87	-0.040	54.00	12.13	150	167	AV	PASS
1660.59	46.7	46.66	0.000	74.00	27.34	150	126	PK	PASS
2658.59	28.7	34.92	6.250	54.00	19.08	150	65	AV	PASS
2658.59	43.7	49.94	6.250	74.00	24.06	150	65	PK	PASS
3991.03	55.3	47.18	-8.080	74.00	26.82	150	54	PK	PASS
3991.03	41.3	33.17	-8.080	54.00	20.83	150	54	AV	PASS
4959.57	53.9	49.30	-4.630	74.00	24.70	150	351	PK	PASS
4959.57	50.3	45.68	-4.630	54.00	8.32	150	5	AV	PASS
5219.07	42.8	39.43	-3.340	54.00	14.57	150	11	AV	PASS
5221.07	49.3	46.01	-3.310	74.00	27.99	150	240	PK	PASS
14669.89	34.0	54.52	20.520	74.00	19.48	150	97	PK	PASS
14693.39	25.6	46.17	20.590	54.00	7.83	150	322	AV	PASS

END OF REPORT