Certificate #6613.01

FCC TEST REPORT

(PART 24)

Applicant:	Power Idea Technology (Shenzhen) Co., Ltd.
Address:	4th Floor, A Section, Languang Science&technology Building, No.7 Xinxi RD, Hi-Tech Industrial Park North, Nanshan District, ShenZhen, P.R.C.

Manufacturer or Supplier:	Power Idea Technology (Shenzhen) Co., Ltd.
Address:	4th Floor, A Section, Languang Science&technology Building, No.7 Xinxi RD, Hi-Tech Industrial Park North, Nanshan District, ShenZhen, P.R.C.
Product:	Smart Phone
Brand Name:	RugGear
Model Name:	PSM05G
Marketing name：	RG880i
FCC ID:	ZLE-PSM05G
Date of tests:	Aug. 28, 2024 ~ Sep.27, 2024

The tests have been carried out according to the requirements of the following standard:

☒ **FCC PART 24, Subpart E** ☒ **FCC PART 2**
☒ **ANSI/TIA/EIA-603-D** ☒ **ANSI/TIA/EIA-603-E** ☒ **ANSI C63.26-2015**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
Xu Hanwen	Sun Peibo
Date: Sep.27, 2024	Date: Sep.27, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD 5

1 SUMMARY OF TEST RESULTS 6

1.1 MEASUREMENT UNCERTAINTY 7

1.2 TEST SITE AND INSTRUMENTS 8

2 GENERAL INFORMATION 11

2.1 GENERAL DESCRIPTION OF EUT 11

2.2 CONFIGURATION OF SYSTEM UNDER TEST 14

2.3 DESCRIPTION OF SUPPORT UNITS 15

2.4 TEST ITEM AND TEST CONFIGURATION 15

2.5 EUT OPERATING CONDITIONS 19

2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS 19

3 TEST TYPES AND RESULTS 20

3.1 OUTPUT POWER MEASUREMENT 20
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT 20
3.1.2 TEST PROCEDURES 20
3.1.3 TEST SETUP 21
3.1.4 TEST RESULTS 21

3.2 FREQUENCY STABILITY MEASUREMENT 36
3.2.1 LIMITS OF FREQUENCY STABILIITY MEASUREMENT 36
3.2.2 TEST PROCEDURE 36
3.2.3 TEST SETUP 36
3.2.4 TEST RESULTS 37

3.3 OCCUPIED BANDWIDTH MEASUREMENT 38
3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT 38
3.3.2 TEST SETUP 38
3.3.3 TEST PROCEDURES 38
3.3.4 TEST RESULTS 39

3.4 BAND EDGE MEASUREMENTC 40
3.4.1 LIMITS OF BAND EDGE MEASUREMENT 40
3.4.2 TEST SETUP 40
3.4.3 TEST PROCEDURES 41
3.4.4. TEST RESULTS 42

3.5 CONDUCTED SPURIOUS EMISSIONS 43
3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT 43
3.5.2 TEST PROCEDURE 43
3.5.3 TEST SETUP 43
3.5.4 TEST RESULTS 44

3.6 RADIATED EMISSION MEASUREMENT 45
3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT 45
3.6.2 TEST PROCEDURES 45
3.6.3 DEVIATION FROM TEST STANDARD 45

3.6.4 TEST SETUP 46
3.6.5 TEST RESULTS 48

3.7 PEAK TO AVERAGE RATIO 90
3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT 90
3.7.2 TEST SETUP 90
3.7.3 TEST PROCEDURES 90
3.7.4 TEST RESULTS 91

4 INFORMATION ON THE TESTING LABORATORIES 92

5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 93

6 APPENDIX 94

GSM 1900 94

PEAK-TO-AVERAGE RATIO(CCDF) 94
TEST RESULT 94
TEST GRAPHS 95

26DB BANDWIDTH AND OCCUPIED BANDWIDTH 98
TEST RESULT 98

BAND EDGE 105
TEST RESULT 105
TEST GRAPHS 106

CONDUCTED SPURIOUS EMISSIONTEST RESULT 108
TEST GRAPHS 109

FREQUENCY STABILITY 112
TEST RESULT 112

CDMA2000 BC1 114

PEAK-TO-AVERAGE RATIO(CCDF) 114
TEST RESULT 114
TEST GRAPHS 115

26DB BANDWIDTH AND OCCUPIED BANDWIDTH 116
TEST RESULT 116
TEST GRAPHS 117

BAND EDGE 118
TEST RESULT 118
TEST GRAPHS 119

CONDUCTED SPURIOUS EMISSION 120
TEST RESULT 120
TEST GRAPHS 121

FREQUENCY STABILITY 122
TEST RESULT 122

WCDMA BAND2 124

PEAK-TO-AVERAGE RATIO 124
TEST RESULT 124
TEST GRAPHS 125

26DB BANDWIDTH AND OCCUPIED BANDWIDTH 127
TEST RESULT 127
TEST GRAPHS 128

BAND EDGE 131
TEST RESULT 131
TEST GRAPHS 132

CONDUCTED SPURIOUS EMISSION 133
TEST RESULT 133
TEST GRAPHS 134

FREQUENCY STABILITY 136
TEST RESULT 136

LTE BAND 2 138

PEAK-TO-AVERAGE RATIO(CCDF) 138
TEST RESULT 138
TEST GRAPHS 141

26DB BANDWIDTH AND OCCUPIED BANDWIDTH 155
TEST RESULT 155

BAND EDGE 171
TEST RESULT 171
TEST GRAPHS 173

CONDUCTED SPURIOUS EMISSION 182
TEST RESULT 182
TEST GRAPHS 184

FREQUENCY STABILITY 193
TEST RESULT 193

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-NQN2406210109RF02	Original release	Sep.27, 2024

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 24 & Part 2			
STANDARD SECTION	**TEST TYPE**	**RESULT**	**Test lab***
§2.1046	Coduncted Output Power	Compliance	A
§24.232(c)	Equivalent Isotropic Radiated Power	Compliance	A
§2.1055 §24.235	Frequency Stability	Compliance	A/B
§2.1049 §24.238(b)	Occupied Bandwidth	Compliance	A/B
§24.232(d)	Peak to average ratio*	Compliance	A/B
§2.1051 §24.238(a)(b)	Band Edge Measurements	Compliance	A/B
§2.1051 §24.238(a)(b)	Conducted Spurious Emissions	Compliance	A/B
§2.1053 §24.238(a)(b)	Radiated Spurious Emissions	Compliance	A/B

* Refer to KDB 971168 D01 Power Meas License Digital Systems v03r01.

NOTE: The maximum RF output power level is 1xRTT RC3 SO55 mode for CDMA2000 BC1, so only 1xRTT mode was used for all tests.

***Test Lab Information Reference**

Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.

Lab B:

BV 7Layers Communications Technology (Shenzhen) Co. Ltd

Lab Address:

Room B37, Warehouse A5, No.3 Chiwan 4th Road, Zhaoshang Street, Nanshan District Shenzhen, Guangdong, People's Republic of China

Accredited Test Lab Cert 3939.01

The FCC Site Registration No. is 525120; The Designation No. is CN1171.

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Frequency Stability	±76.97Hz
Radiated emissions (9KHz~30MHz)	±2.68dB
Radiated emissions & Radiated Power (30MHz~1GHz)	±4.98dB
Radiated emissions & Radiated Power (1GHz ~6GHz)	±4.70dB
Radiated emissions (6GHz ~18GHz)	±4.60dB
Radiated emissions (18GHz ~40GHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Band Edge Measurements	±4.70dB
Peak to average ratio	±0.76dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.

1.2 TEST SITE AND INSTRUMENTS

Lab A：

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.30,22	Aug.29,24
Pre-Amplifier	R&S	SCU18F1	100815	Aug.29,24	Aug.28,26
Pre-Amplifier	R&S	SCU08F1	101028	Sep.16,22	Sep.15,24
Pre-Amplifier	R&S	SCU08F1	101028	Sep.15,24	Sep.14,26
Vector Signal Generator	R&S	SMBV100B	102176	Mar.29,24	Mar.28,26
Signal Generator	R&S	SMB100A	182185	Mar.29,24	Mar.28,26
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.25,22	Nov.24,25
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.25,22	Nov.24,25
EMI TEST Receiver	R&S	ESR26	101734	Mar.28,24	Mar.27,26
EMI TEST Receiver	R&S	ESW44	101973	Mar.28,24	Mar.27,26
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Dec.26,23	Dec.25,25
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.21,24	Aug.20,26
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Jul.15,24	Jul.14,26
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.21,24	Aug.20,26
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.22,24	Feb.21,26
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.19,24	Jun.18,26
Test Software	EMC32	EMC32	N/A	N/A	N/A
6DB attenuator	Tonscend Technology Co., Ltd	N/A	23062787	N/A	N/A
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	Oct.01,22	Sep.30,24
DC Source	HYELEC	HY3010B	551016	Aug.31,22	Aug.30,24
DC Source	HYELEC	HY3010B	551016	Aug.30,24	Aug.29,26
Hygrothermograph	DELI	20210528	SZ014	Sep.06,22	Sep.05,24
Hygrothermograph	DELI	20210528	SZ014	Sep.05,24	Sep.04,26
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
CABLE	R&S	W13.02	N/A	Apr.27,24	Apr.26,25
CABLE	R&S	W12.14	N/A	Apr.27,24	Apr.26,25
CABLE	R&S	J12J103539-00-1	SEP-03-20-069	Apr.27,24	Apr.26,25

CABLE	R&S	J12J103539-00-1	SEP-03-20-070	Apr.27,24	Apr.26,25
Temperature Chamber	votsch	VT4002	58566078100050	May.30,24	May.29,26

NOTE: 1. The calibration interval of the above test instruments is 12/ 24 / 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.

3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.

4. The FCC Site Registration No. is 434559; The Designation No. is CN1325.

Lab B：

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 27,24	Mar. 26,25
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	May.09,24	May.08,25
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.02,23	Sep.01,24
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.01,24	Aug.30,25
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Feb. 17,24	Feb. 16,25
Horn Antenna	ETS-LINDGREN	3117	00168692	Feb. 17,24	Feb. 16,25
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Sep.03, 23	Sep.02, 24
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Sep.02, 24	Sep.01, 25
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 13,24	Feb. 12,25
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May. 05,24	May. 04,25
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.09,24	May.08,25
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb.16,24	Feb.15,25
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Nov. 14,23	Nov. 13,26
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	JS1120	3.1.36	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	50HF-010-SMA	May. 05,24	May. 04,26
Power Meter	Anritsu	ML2495A	1506002	Feb. 13,24	Feb. 12,25
Power Sensor	Anritsu	MA2411B	1339352	Feb. 13,24	Feb. 12,25
Temperature Chamber	ESPEC	SH-242	93000855	May. 05,24	May. 04,25
MXG Analog Microvave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 13,24	Feb. 12,25
Base station R&S CMW500	Rohde&Schwarz	CMW500	153085	May.09,24	May.08,25
DC Source	Kikusui/JP	PMX18-5A	N/A	Aug. 11,23	Aug. 10,24
DC Source	Kikusui/JP	PMX18-5A	N/A	Aug. 10,24	Aug. 09,26

NOTE: 1. The calibration interval of the above test instruments is 12/ 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.

3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.

4. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT*	Smart Phone	
BRAND NAME*	RugGear	
MODEL NAME*	PSM05G	
MARKETING NAME*	RG880i	
NOMINAL VOLTAGE*	5.0Vdc/ 9.0Vdc/ 12.0Vdc(Adapter) 3.85Vdc (Battery)	
MODULATION TYPE*	**GSM/GPRS:** GMSK **EDGE:** 8PSK **CDMA2000 BC1:** 1xRTT: BPSK, QPSK **CDMA2000 BC1:** 1xEV-DO: 8PSK **WCDMA:** BPSK, QPSK **LTE Band 2:** QPSK, 16QAM, 64QAM	
FREQUENCY RANGE	**GSM/ EDGE**	1850.2MHz ~ 1909.8MHz
	CDMA 2000 BC1	1851.25MHz ~ 1908.75MHz
	WCDMA	1852.4MHz ~ 1907.6MHz
	LTE Band 2 Channel Bandwidth: 1.4MHz	1850.7MHz ~ 1909.3MHz
	LTE Band 2 Channel Bandwidth: 3MHz	1851.5MHz ~ 1908.5MHz
	LTE Band 2 Channel Bandwidth: 5MHz	1852.5MHz ~ 1907.5MHz
	LTE Band 2 Channel Bandwidth: 10MHz	1855.0MHz ~ 1905.0MHz
	LTE Band 2 Channel Bandwidth: 15MHz	1857.5MHz ~ 1902.5MHz
	LTE Band 2 Channel Bandwidth: 20MHz	1860.0MHz ~ 1900.0MHz
MAX. EIRP POWER	**GSM**	948.42mW
	EDGE	293.09mW
	CDMA2000 BC1 1xRTT	168.66mW
	CDMA2000 BC1 1xEV-DO	166.34mW
	WCDMA	180.72mW

MAX. EIRP POWER	**LTE Band 2 Channel Bandwidth: 1.4MHz**	167.11mW
	LTE Band 2 Channel Bandwidth: 3MHz	161.81mW
	LTE Band 2 Channel Bandwidth: 5MHz	160.69mW
	LTE Band 2 Channel Bandwidth: 10MHz	160.69mW
	LTE Band 2 Channel Bandwidth: 15MHz	162.93mW
	LTE Band 2 Channel Bandwidth: 20MHz	164.44mW
EMISSION DESIGNATOR	**GSM**	246KGXW
	EDGE	246KG7W
	CDMA2000 BC1	1M29F9W
	WCDMA	4M14F9W
	LTE Band 2 Channel Bandwidth: 1.4MHz	QPSK: 1M09G7D
		16QAM: 1M09W7D
		64QAM: 1M09W7D
	LTE Band 2 Channel Bandwidth: 3MHz	QPSK: 2M69G7D
		16QAM: 2M69W7D
		64QAM: 2M69W7D
	LTE Band 2 Channel Bandwidth: 5MHz	QPSK: 4M49G7D
		16QAM: 4M49W7D
		64QAM: 4M48W7D
	LTE Band 2 Channel Bandwidth: 10MHz	QPSK: 8M95G7D
		16QAM: 8M95W7D
		64QAM: 8M94W7D
	LTE Band 2 Channel Bandwidth: 15MHz	QPSK: 13M5G7D
		16QAM: 13M4W7D
		64QAM: 13M5W7D
	LTE Band 2 Channel Bandwidth: 20MHz	QPSK: 17M9G7D
		16QAM: 17M9W7D
		64QAM: 17M9W7D
ANTENNA TYPE*	PIFA Antenna with -0.6dBi gain for GSM1900/ CDMA2000 BC1/WCDMA II/LTE B2	
HW VERSION*	V02	
SW VERSION*	RG880i_EAA_00.00_1	

I/O PORTS*	Refer to user's manual
CABLE SUPPLIED*	USB cable: non-shielded cable, with w/o ferrite core, 1.0 meter
EXTREME TEMPERATURE*	-10℃-55℃
EXTREME VOLTAGE*	3.6V – 4.4V

NOTE:

1. ***Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information , Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.

2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

3. The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and two receivers.

MODULATION MODE	TX FUNCTION
GSM/GPRS/EDGE	1TX
CDMA 2000 BC1	1TX
WCDMA	1TX
LTE	1TX

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

5. **List of Accessory:**

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
CPU	QUALCOMM	N/A	SM6225	N/A
eMMC 1 (=ROM 1)	SAMSUNG	N/A	KM2L9001CM-B518	N/A
eMMC 2 (=ROM 2)	Hynix	N/A	H9QT0GECN6X145R	N/A
RAM 1	N/A	N/A	N/A	N/A
RAM 2	N/A	N/A	N/A	N/A
BT/WLAN Module	N/A	N/A	N/A	N/A
NFC chipset	NXP	N/A	N/A	N/A
Battery	N/A	N/A	BL450AGP	Power Rating: 4.4V 4500mAh
Adapter	N/A	Huizhou Juwei Electronics Co.,Ltd	FG18AQC3.0UU	I/P: 100-240Vac, 50/60Hz, 0.5A, O/P:5.0V 3.0A or 9.0V 2.0A or 12.0V 1.5A
USB Cable	N/A	N/A	N/A	N/A

2.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST





2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	N/A	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	USB Line: Shielded, Detachable 1.0m;

2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports The worst case in EIRP and radiated emission was found when positioned on X-plane for GSM/EDGE/ LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Adapter+ USB Cable with GSM or CDMA2000 or WCDMA or LTE link
B	EUT + Battery / DC Supply with GSM or CDMA2000 or WCDMA or LTE link

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	512 to 810	512, 661, 810	GSM,EDGE
B	FREQUENCY STABILITY	512 to 810	512, 661, 810	GSM,EDGE
A	OCCUPIED BANDWIDTH	512 to 810	512, 661, 810	GSM,EDGE
A	PEAK TO AVERAGE RATIO	512 to 810	512, 661, 810	GSM,EDGE
A	BAND EDGE	512 to 810	512, 810	GSM,EDGE
A	CONDCUDETED EMISSION	512 to 810	512, 661, 810	GSM,EDGE
A	RADIATED EMISSION	512 to 810	512, 661, 810	GSM,EDGE

CDMA2000 BC1

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	ERP	25 to 1175	25, 600, 1175	CDMA
B	FREQUENCY STABILITY	25 to 1175	25, 600, 1175	CDMA
A	OCCUPIED BANDWIDTH	25 to 1175	25, 600, 1175	CDMA
A	BAND EDGE	25 to 1175	25, 1175	CDMA
A	CONDCUDETED EMISSION	25 to 1175	25, 600, 1175	CDMA
A	RADIATED EMISSION	25 to 1175	25, 600, 1175	CDMA
A	PEAK TO AVERAGE RATIO	25 to 1175	25, 600, 1175	CDMA

WCDMA

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
B	FREQUENCY STABILITY	9262 to 9538	9262, 9400, 9538	WCDMA
A	OCCUPIED BANDWIDTH	9262 to 9538	9262, 9400, 9538	WCDMA
A	PEAK TO AVERAGE RATIO	9262 to 9538	9262, 9400, 9538	WCDMA
A	BAND EDGE	9262 to 9538	9262, 9538	WCDMA
A	CONDCUDETED EMISSION	9262 to 9538	9262, 9400, 9538	WCDMA
A	RADIATED EMISSION	9262 to 9538	9262, 9400, 9538	WCDMA

LTE BAND 2 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	EIRP	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM,64QAM	Full RB / 0 RB Offset
A	OCCUPIED BANDWIDTH	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM,64QAM	Full RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM,64QAM	Full RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM,64QAM	Full RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM,64QAM	Full RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM,64QAM	Full RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM,64QAM	Full RB / 0 RB Offset
A	PEAK TO AVERAGE RATIO	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
A	BAND EDGE	18607 to 19193	18607	1.4MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
			19193	1.4MHz	QPSK,16QAM,64QAM	1 RB / 5 RB Offset Full RB / 0 RB Offset
		18615 to 19185	18615	3MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
			19185	3MHz	QPSK,16QAM,64QAM	1 RB / 14 RB Offset Full RB / 0 RB Offset
		18625 to 19175	18625	5MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
			19175	5MHz	QPSK,16QAM,64QAM	1 RB / 24 RB Offset Full RB / 0 RB Offset
		18650 to 19150	18650	10MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
			19150	10MHz	QPSK,16QAM,64QAM	1 RB / 49 RB Offset Full RB / 0 RB Offset
		18675 to 19125	18675	15MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset

			19125	15MHz	QPSK,16QAM,64QAM	1 RB / 74 RB Offset
						Full RB / 0 RB Offset
		18700 to 19100	18700	20MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset
						Full RB / 0 RB Offset
			19100	20MHz	QPSK,16QAM,64QAM	1 RB / 99 RB Offset
						Full RB / 0 RB Offset
A	CONDCUDETED EMISSION	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM,64QAM	1 RB / 0 RB Offset
A	RADIATED EMISSION	18607 to 19193	18900	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18900	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18900	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18900	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18900	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK	1 RB / 0 RB Offset

Note: 1.This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP	23deg. C, 70%RH	DC 5.0V/ 9.0V/ 12.0V By Adapter	Hanwen Xu
FREQUENCY STABILITY	23deg. C, 70%RH	DC 3.6V/ 3.85V/ 4.4V By Battery	Hanwen Xu/ Jace Hu
OCCUPIED BANDWIDTH	23deg. C, 70%RH	DC 5.0V/ 9.0V/ 12.0V By Adapter	Hanwen Xu/ Jace Hu
BAND EDGE	23deg. C, 70%RH	DC 5.0V/ 9.0V/ 12.0V By Adapter	Hanwen Xu/ Jace Hu
CONDCUDETED EMISSION	23deg. C, 70%RH	DC 5.0V/ 9.0V/ 12.0V By Adapter	Hanwen Xu/ Jace Hu
RADIATED EMISSION	23deg. C, 70%RH	DC 5.0V/ 9.0V/ 12.0V By Adapter	Hanwen Xu/ Jace Hu
PEAK TO AVERAGE RATIO	23deg. C, 70%RH	DC 5.0V/ 9.0V/ 12.0V By Adapter	Hanwen Xu/ Jace Hu

2.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.

2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile and portable stations are limited to 2 watts EIRP.

3.1.2 TEST PROCEDURES

EIRP MEASUREMENT:

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determing the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

ERP or EIRP = $P_{Meas} + G_T - L_C$

Where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas}, typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_T = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

3.1.3 TEST SETUP

EIRP / ERP Measurement:

CONDUCTED POWER MEASUREMENT:



3.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm) :

Band	GSM1900		
Channel	512	661	810
Frequency(MHz)	1850.2	1880	1909.8
GSM	**30.37**	30.35	30.20
GPRS 1Tx Slot	30.35	30.33	30.17
GPRS 2Tx Slot	28.21	28.08	28.09
GPRS 3Tx Slot	26.28	26.18	26.20
GPRS 4Tx Slot	25.31	25.11	25.14
EDGE 1Tx Slot	25.27	25.23	25.12
EDGE 2Tx Slot	24.32	24.29	24.25
EDGE 3Tx Slot	23.35	23.23	23.36
EDGE 4Tx Slot	22.80	22.76	22.76

Band	CDMA2000 BC1		
Channel	25	600	1175
Frequency(MHz)	1851.25	1880	1908.75
RC1 SO55	**22.87**	22.65	22.68
RC3 SO55	22.85	22.64	22.67
RC3 SO32 (F+SCH)	22.84	22.62	22.66
RC3 SO32 (+SCH)	22.82	22.61	22.66
RTAP 153.6Kbps	22.81	22.60	22.65
RETAP 4096Bits	22.80	22.58	22.63

Band	WCDMA II		
TX Channel	9262	9400	9538
Rx Channel	9662	9800	9938
Frequency(MHz)	1852.4	1880	1907.6
RMC 12.2K	23.13	23.05	**23.17**
HSDPA Subtest-1	22.55	22.47	22.59
HSDPA Subtest-2	22.54	22.46	22.58
HSDPA Subtest-3	22.03	21.95	22.07
HSDPA Subtest-4	22.02	21.94	22.06
DC-HSDPA Subtest-1	22.47	22.41	22.51
DC-HSDPA Subtest-2	22.46	22.40	22.50
DC-HSDPA Subtest-3	22.04	21.89	22.01
DC-HSDPA Subtest-4	22.03	21.88	22.00
HSUPA Subtest-1	22.51	22.43	22.55
HSUPA Subtest-2	21.50	21.42	21.54
HSUPA Subtest-3	21.98	21.91	22.03
HSUPA Subtest-4	21.47	21.40	21.52
HSUPA Subtest-5	22.46	22.39	22.51
HSPA+ Subtest-1	22.02	21.96	22.08

LTE BAND 2

Band/BW	Modulation	RB Size	RB Offset	Low CH 18607	Mid CH 18900	High CH 19193
				Frequency 1850.7 MHz	Frequency 1880 MHz	Frequency 1909.3 MHz
2/ 1.4	QPSK	1	0	22.41	22.39	22.43
		1	2	22.56	22.71	22.66
		1	5	22.15	22.27	22.23
		3	0	22.58	22.64	22.61
		3	1	22.75	22.83	22.75
		3	3	22.40	22.55	22.47
		6	0	21.47	21.62	21.55
	16QAM	1	0	21.66	21.85	21.77
		1	2	21.94	22.05	21.86
		1	5	21.35	21.62	21.61
		3	0	21.53	21.62	21.67
		3	1	21.67	21.79	21.85
		3	3	21.37	21.60	21.54
		6	0	20.43	20.56	20.58
	64QAM	1	0	20.61	20.72	20.63
		1	2	20.85	20.88	20.79
		1	5	20.34	20.29	20.32
		3	0	20.54	20.63	20.69
		3	1	20.56	20.72	20.76
		3	3	20.35	20.56	20.48
		6	0	19.46	19.48	19.67

Band/BW	Modulation	RB Size	RB Offset	Low CH 18615	Mid CH 18900	High CH 19185
				Frequency 1851.5 MHz	Frequency 1880 MHz	Frequency 1908.5 MHz
2/ 3	QPSK	1	0	22.52	22.42	22.41
		1	7	22.52	22.69	22.63
		1	14	22.18	22.15	22.18
		8	0	21.55	21.74	21.70
		8	3	21.67	21.81	21.75
		8	7	21.48	21.65	21.58
		15	0	21.45	21.59	21.65
	16QAM	1	0	21.77	21.73	21.74
		1	7	22.00	22.13	21.95
		1	14	21.33	21.55	21.49
		8	0	20.60	20.63	20.58
		8	3	20.66	20.79	20.85
		8	7	20.38	20.49	20.47
		15	0	20.42	20.65	20.65
	64QAM	1	0	20.49	20.68	20.73
		1	7	20.84	20.77	20.70
		1	14	20.26	20.42	20.33
		8	0	19.47	19.60	19.67
		8	3	19.61	19.64	19.67
		8	7	19.30	19.58	19.44
		15	0	19.53	19.50	19.66

Band/BW	Modulation	RB Size	RB Offset	Low CH 18625	Mid CH 18900	High CH 19175
				Frequency 1852.5 MHz	Frequency 1880 MHz	Frequency 1907.5 MHz
2/ 5	QPSK	1	0	22.43	22.40	22.46
		1	12	22.46	22.66	22.64
		1	24	22.18	22.23	22.23
		12	0	21.50	21.61	21.71
		12	6	21.71	21.72	21.78
		12	13	21.40	21.61	21.58
		25	0	21.51	21.66	21.65
	16QAM	1	0	21.72	21.72	21.70
		1	12	21.92	22.07	21.89
		1	24	21.34	21.57	21.60
		12	0	20.62	20.63	20.58
		12	6	20.64	20.73	20.79
		12	13	20.41	20.50	20.46
		25	0	20.45	20.68	20.65
	64QAM	1	0	20.61	20.65	20.68
		1	12	20.79	20.79	20.70
		1	24	20.26	20.35	20.43
		12	0	19.57	19.73	19.61
		12	6	19.62	19.66	19.66
		12	13	19.35	19.51	19.56
		25	0	19.55	19.49	19.60

Band/BW	Modulation	RB Size	RB Offset	Low CH 18650	Mid CH 18900	High CH 19150
				Frequency 1855 MHz	Frequency 1880 MHz	Frequency 1905 MHz
2/ 10	QPSK	1	0	22.40	22.43	22.50
		1	24	22.50	22.64	22.66
		1	49	22.18	22.18	22.24
		25	0	21.55	21.68	21.69
		25	12	21.73	21.78	21.69
		25	25	21.47	21.64	21.53
		50	0	21.59	21.63	21.55
	16QAM	1	0	21.69	21.72	21.73
		1	24	21.95	22.12	21.95
		1	49	21.38	21.60	21.55
		25	0	20.59	20.63	20.66
		25	12	20.61	20.86	20.78
		25	25	20.34	20.55	20.48
		50	0	20.53	20.55	20.59
	64QAM	1	0	20.58	20.66	20.73
		1	24	20.79	20.75	20.77
		1	49	20.29	20.38	20.45
		25	0	19.51	19.60	19.58
		25	12	19.57	19.68	19.70
		25	25	19.37	19.53	19.54
		50	0	19.49	19.56	19.65

Band/BW	Modulation	RB Size	RB Offset	Low CH 18675	Mid CH 18900	High CH 19125
				Frequency 1857.5 MHz	Frequency 1880 MHz	Frequency 1902.5 MHz
2/ 15	QPSK	1	0	22.50	22.39	22.46
		1	37	22.51	22.66	22.72
		1	74	22.19	22.23	22.18
		36	0	21.64	21.62	21.68
		36	19	21.67	21.82	21.79
		36	39	21.45	21.66	21.44
		75	0	21.53	21.63	21.63
	16QAM	1	0	21.74	21.76	21.80
		1	37	21.94	22.06	21.84
		1	74	21.34	21.64	21.62
		36	0	20.51	20.68	20.63
		36	19	20.68	20.77	20.79
		36	39	20.28	20.48	20.57
		75	0	20.52	20.64	20.65
	64QAM	1	0	20.52	20.76	20.64
		1	37	20.74	20.88	20.80
		1	74	20.32	20.30	20.42
		36	0	19.53	19.69	19.59
		36	19	19.63	19.70	19.74
		36	39	19.37	19.57	19.56
		75	0	19.49	19.58	19.62

Band/BW	Modulation	RB Size	RB Offset	Low CH 18700	Mid CH 18900	High CH 19100
				Frequency 1860 MHz	Frequency 1880 MHz	Frequency 1900 MHz
2/ 20	QPSK	1	0	22.55	22.49	22.54
		1	50	22.60	**22.76**	22.73
		1	99	22.25	22.30	22.33
		50	0	21.65	21.75	21.74
		50	25	21.78	21.86	21.82
		50	50	21.49	21.70	21.59
		100	0	21.60	21.69	21.67
	16QAM	1	0	21.81	21.86	21.82
		1	50	22.06	22.19	21.99
		1	99	21.43	21.67	21.64
		50	0	20.64	20.72	20.68
		50	25	20.75	20.88	20.86
		50	50	20.42	20.61	20.59
		100	0	20.57	20.70	20.68
	64QAM	1	0	20.62	20.78	20.75
		1	50	20.86	20.89	20.85
		1	99	20.35	20.43	20.46
		50	0	19.61	19.74	19.70
		50	25	19.70	19.79	19.80
		50	50	19.41	19.64	19.59
		100	0	19.57	19.61	19.71

EIRP POWER (dBm)

GSM 1900

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
512	1850.2	30.37	-0.6	29.77	948.42	2
661	1880	30.35	-0.6	29.75	944.06	2
810	1909.8	30.2	-0.6	29.6	912.01	2

EDGE 1900

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
512	1850.2	25.27	-0.6	24.67	293.09	2
661	1880	25.23	-0.6	24.63	290.4	2
810	1909.8	25.12	-0.6	24.52	283.14	2

CDMA2000 BC1 1xRTT

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
25	1851.25	22.87	-0.6	22.27	168.66	2
600	1880	22.65	-0.6	22.05	160.32	2
1175	1908.75	22.68	-0.6	22.08	161.44	2

CDMA2000 BC1 1xEV-DO

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
25	1851.25	22.81	-0.6	22.21	166.34	2
600	1880	22.6	-0.6	22	158.49	2
1175	1908.75	22.65	-0.6	22.05	160.32	2

WCDMA II

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
9262	1852.4	23.13	-0.6	22.53	179.06	2
9400	1880	23.05	-0.6	22.45	175.79	2
9538	1907.6	23.17	-0.6	22.57	180.72	2

LTE BAND 2

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	22.75	-0.6	22.15	164.06	2
18900	1880.0	22.83	-0.6	22.23	167.11	2
19193	1909.3	22.75	-0.6	22.15	164.06	2

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	21.94	-0.6	21.34	136.14	2
18900	1880.0	22.05	-0.6	21.45	139.64	2
19193	1909.3	21.86	-0.6	21.26	133.66	2

CHANNEL BANDWIDTH: 1.4MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	20.85	-0.6	20.25	105.93	2
18900	1880	20.88	-0.6	20.28	106.66	2
19193	1909.3	20.79	-0.6	20.19	104.47	2

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	22.52	-0.6	21.92	155.6	2
18900	1880	22.69	-0.6	22.09	161.81	2
19185	1908.5	22.63	-0.6	22.03	159.59	2

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	22	-0.6	21.4	138.04	2
18900	1880	22.13	-0.6	21.53	142.23	2
19185	1908.5	21.95	-0.6	21.35	136.46	2

CHANNEL BANDWIDTH: 3MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	20.84	-0.6	20.24	105.68	2
18900	1880	20.77	-0.6	20.17	103.99	2
19185	1908.5	20.73	-0.6	20.13	103.04	2

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	22.46	-0.6	21.86	153.46	2
18900	1880	22.66	-0.6	22.06	160.69	2
19175	1907.5	22.64	-0.6	22.04	159.96	2

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	21.92	-0.6	21.32	135.52	2
18900	1880	22.07	-0.6	21.47	140.28	2
19175	1907.5	21.89	-0.6	21.29	134.59	2

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	20.79	-0.6	20.19	104.47	2
18900	1880	20.79	-0.6	20.19	104.47	2
19175	1907.5	20.7	-0.6	20.1	102.33	2

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855	22.5	-0.6	21.9	154.88	2
18900	1880	22.64	-0.6	22.04	159.96	2
19150	1905	22.66	-0.6	22.06	160.69	2

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855	21.95	-0.6	21.35	136.46	2
18900	1880	22.12	-0.6	21.52	141.91	2
19150	1905	21.95	-0.6	21.35	136.46	2

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855	20.79	-0.6	20.19	104.47	2
18900	1880	20.75	-0.6	20.15	103.51	2
19150	1905	20.77	-0.6	20.17	103.99	2

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	22.51	-0.6	21.91	155.24	2
18900	1880	22.66	-0.6	22.06	160.69	2
19125	1902.5	22.72	-0.6	22.12	162.93	2

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	21.94	-0.6	21.34	136.14	2
18900	1880	22.06	-0.6	21.46	139.96	2
19125	1902.5	21.84	-0.6	21.24	133.05	2

CHANNEL BANDWIDTH: 15MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	20.74	-0.6	20.14	103.28	2
18900	1880	20.88	-0.6	20.28	106.66	2
19125	1902.5	20.8	-0.6	20.2	104.71	2

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	22.6	-0.6	22	158.49	2
18900	1880	22.76	-0.6	22.16	164.44	2
19100	1900	22.73	-0.6	22.13	163.31	2

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	22.06	-0.6	21.46	139.96	2
18900	1880	22.19	-0.6	21.59	144.21	2
19100	1900	21.99	-0.6	21.39	137.72	2

CHANNEL BANDWIDTH: 20MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G_T-L_C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	20.86	-0.6	20.26	106.17	2
18900	1880	20.89	-0.6	20.29	106.91	2
19100	1900	20.85	-0.6	20.25	105.93	2

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).

3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILIITY MEASUREMENT

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.2.2 TEST PROCEDURE

a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.

b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.

c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ±0.5℃ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP



3.2.4 TEST RESULTS

Please Refer to Appendix Of this test report.

Note: VL = Low voltage(3.6V); VN/NV = Normal voltage(3.85V); VH = High voltage(4.4V);
NT = Normal temperature (25℃)

3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage
0.5 %of the total mean power of a given emission.

3.3.2 TEST SETUP



3.3.3 TEST PROCEDURES

a. The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
b. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

3.3.4 TEST RESULTS

Please Refer to Appendix Of this test report.

3.4 BAND EDGE MEASUREMENTC

3.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.4.2 TEST SETUP



3.4.3 TEST PROCEDURES

a) All measurements were done at low and high operational frequency range

b) Connect the transmitter to the spectrum analyzer via coaxial cable while ensuring proper impedance matching.

c) Tune the analyzer to the nominal center frequency of the emission bandwidth (EBW)

d) .Set the resolution bandwidth (RBW) ≧ 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.

e) Beyond the 1MHz band from the band edge, RBW=1MHz was used.

f) Set the video bandwidth (VBW) to ≧3 x RBW.

g) Select the average power (RMS) display detector.

h) Set the number of measurement points to ≧ 1001.

i) Use auto-coupled sweep time.

j) Perform the measurement over an interval of time when the transmission is continuous and at its maximum power level.

k) The RF fundamental frequency should be excluded against the limit line in the operating frequency band and use RBW is 10KHz or 100KHz.

l) Record the max trace plot into the test report.

3.4.4. TEST RESULTS

Please Refer to Appendix Of this test report.

3.5 CONDUCTED SPURIOUS EMISSIONS

3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The emission limit equal to –13dBm.

3.5.2 TEST PROCEDURE

a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.

b. Measuring frequency range is from 30MHz up to a frequency including its 10th harmonic. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

3.5.3 TEST SETUP



3.5.4 TEST RESULTS

NOTE ：The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

Please Refer to Appendix Of this test report.

3.6 RADIATED EMISSION MEASUREMENT

3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The emission limit equal to –13dBm.

3.6.2 TEST PROCEDURES

a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.

b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G

c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

3.6.3 DEVIATION FROM TEST STANDARD

No deviation

3.6.4 TEST SETUP

< Frequency Range below 30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.6.5 TEST RESULTS

NOTE ：The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA

30 MHz – 1GHz data:

EDGE 1900：

CHANNEL BANDWIDTH: 512~810

MODE	TX channel 661	**FREQUENCY RANGE**	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	36.305	-46.88	-13.0	33.88	4.55	H	191.8	1.0
1	60.07	-54.22	-13.0	41.22	0.48	H	289.8	1.0
1	92.08	-58.51	-13.0	45.51	-5.51	H	267.5	2.0
1	184.23	-45.51	-13.0	32.51	-1.08	H	191.8	1.0
1	379.685	-57.04	-13.0	44.04	6.29	H	93.7	1.0
1	648.86	-57.55	-13.0	44.55	7.6	H	359.0	2.0



MODE	TX channel 661	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	32.91	-47.95	-13.0	34.95	-1.18	V	359.1	1.0
1	58.615	-51.66	-13.0	38.66	1.98	V	359.1	1.0
1	99.84	-38.23	-13.0	25.23	10.3	V	269.4	1.0
1	214.3	-59.9	-13.0	46.9	-1.77	V	75.1	2.0
1	338.945	-57.42	-13.0	44.42	5.84	V	75.1	2.0
1	585.81	-58.61	-13.0	45.61	6.75	V	75.1	2.0



ABOVE 1GHz DATA

Note: For higher frequency, the emission is too low to be detected.

WORST-CASE DATA

PCS 1900:

CH 512

MODE	TX channel 512	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,700.000	-50.75	-13.0	37.75	20.98	H	359	1.0
4	5,550.000	-50.52	-13.0	37.52	23.76	H	359	2.0



MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,700.000	-50.2	-13.0	37.2	21.57	V	359.1	1.0
4	5,550.000	-49.35	-13.0	36.35	24.45	V	124.1	2.0



CH 661

MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,760.000	-47.08	-13.0	34.08	21.19	H	0.9	2.0
4	5,640.000	-49.94	-13.0	36.94	24.12	H	359.1	1.0



MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,760.000	-49.68	-13.0	36.68	21.68	V	359.1	1.0
4	5,640.000	-48.88	-13.0	35.88	24.46	V	1.0	1.0



CH 810

MODE	TX channel 810	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,819.600	-48.76	-13.0	35.76	21.85	H	359.1	1.0
4	5,729.400	-49.78	-13.0	36.78	24.45	H	234.6	1.0



MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,819.600	-46.66	-13.0	33.66	22.2	V	125.3	2.0
4	5,729.400	-49.09	-13.0	36.09	24.92	V	359.1	1.0



EDGE 1900:

CH 512

MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,700.000	-52.16	-13.0	39.16	20.98	H	359.0	1.0
4	5,550.000	-49.7	-13.0	36.7	23.76	H	235.8	1.0



MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,700.000	-51.52	-13.0	38.52	21.57	V	359.0	2.0
4	5,550.000	-49.23	-13.0	36.23	24.45	V	0.9	2.0



CH 661

MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,760.000	-46.31	-13.0	33.31	21.19	H	235.9	1.0
4	5,640.000	-49.62	-13.0	36.62	24.12	H	125.3	2.0



MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,760.000	-45.56	-13.0	32.56	21.68	V	124.1	2.0
4	5,640.000	-49.41	-13.0	36.41	24.46	V	0.9	2.0



CH 810

MODE	TX channel 810	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,819.600	-49.25	-13.0	36.25	21.85	H	0.9	2.0
4	5,729.400	-49.91	-13.0	36.91	24.45	H	0.9	2.0



MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,819.600	-48.8	-13.0	35.8	22.2	V	1.0	1.0
4	5,729.400	-49.77	-13.0	36.77	24.92	V	235.9	1.0



CDMA2000 BC1:

CH 25

MODE	TX channel 25	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3701.000	-51.73	-60.13	-13.00	-38.73	8.40	Peak	Horizontal
2 PP	5553.000	-50.48	-62.28	-13.00	-37.48	11.80	Peak	Horizontal



MODE	TX channel 25	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3702.000	-50.08	-58.71	-13.00	-37.08	8.63	Peak	Vertical
2	PP	5551.000	-49.68	-62.01	-13.00	-36.68	12.33	Peak	Vertical



CH 600

MODE	TX channel 600	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3756.500	-52.25	-60.60	-13.00	-39.25	8.35	Peak	Horizontal
2 PP	5640.000	-49.80	-61.61	-13.00	-36.80	11.81	Peak	Horizontal



MODE	TX channel 600	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3756.500	-51.38	-60.01	-13.00	-38.38	8.63	Peak	Vertical
2 PP	5640.000	-50.06	-62.38	-13.00	-37.06	12.32	Peak	Vertical



CH 1175

MODE	TX channel 1175	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3817.500	-51.94	-60.25	-13.00	-38.94	8.31	Peak	Horizontal
2 PP	5717.500	-51.10	-62.92	-13.00	-38.10	11.82	Peak	Horizontal



MODE	TX channel 1175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3812.000	-50.32	-58.95	-13.00	-37.32	8.63	Peak	Vertical
2	PP	5725.250	-50.12	-62.43	-13.00	-37.12	12.31	Peak	Vertical



WCDMA Band II

CH 9262

MODE	TX channel 9262	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,704.800	-51.1	-13.0	38.1	20.95	H	97.6	1.0
4	5,557.200	-49.36	-13.0	36.36	23.75	H	0.9	2.0



MODE	TX channel 9262	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,704.800	-50.22	-13.0	37.22	21.55	V	96.8	2.0
4	5,557.200	-50.17	-13.0	37.17	24.45	V	1.0	1.0



CH 9400

MODE	TX channel 9400	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,760.000	-51.82	-13.0	38.82	21.19	H	0.9	2.0
4	5,640.000	-49.53	-13.0	36.53	24.12	H	0.9	2.0



MODE	TX channel 9400	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,760.000	-50.74	-13.0	37.74	21.68	V	137.2	2.0
4	5,640.000	-49.07	-13.0	36.07	24.46	V	1.0	2.0



CH 9538

MODE	TX channel 9538	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,815.200	-50.27	-13.0	37.27	21.82	H	265.9	2.0
4	5,722.800	-48.63	-13.0	35.63	24.42	H	359.0	1.0



MODE	TX channel 9538	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,815.200	-49.85	-13.0	36.85	22.15	V	359.0	2.0
4	5,722.800	-50.43	-13.0	37.43	24.88	V	160.5	2.0



LTE Band 2

CHANNEL BANDWIDTH: 1.4MHz / QPSK

MODE	TX channel 18900	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Hanwen Xu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,758.740	-52.06	-13.0	39.06	21.17	H	299.2	1.0
4	5,638.110	-48.49	-13.0	35.49	24.11	H	120.9	2.0



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,758.740	-50.68	-13.0	37.68	21.68	V	185.3	1.0
4	5,638.110	-50.36	-13.0	37.36	24.45	V	0.9	2.0



CHANNEL BANDWIDTH: 3MHz / QPSK

MODE	TX channel 18900	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,758.740	-50.71	-13.0	37.71	21.17	H	297.8	1.0
4	5,638.110	-49.78	-13.0	36.78	24.11	H	359.0	2.0



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,758.740	-51.7	-13.0	38.7	21.68	V	176.8	2.0
4	5,638.110	-48.82	-13.0	35.82	24.45	V	0.9	2.0



CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 18900	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,755.500	-49.92	-13.0	36.92	21.11	H	16.9	2.0
4	5,633.250	-50.0	-13.0	37.0	24.1	H	119.5	2.0



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,755.500	-48.3	-13.0	35.3	21.66	V	125.1	2.0
4	5,633.250	-49.61	-13.0	36.61	24.43	V	20.3	2.0



CHANNEL BANDWIDTH: 10MHz / QPSK

MODE	TX channel 18900	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,751.000	-47.55	-13.0	34.55	21.04	H	24.6	2.0
4	5,626.500	-50.5	-13.0	37.5	24.07	H	99.7	1.0



MODE	TX channel 18900	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,751.000	-50.45	-13.0	37.45	21.64	V	1	1.0
4	5,626.500	-48.89	-13.0	35.89	24.43	V	359	2.0



CHANNEL BANDWIDTH: 15MHz / QPSK

MODE	TX channel 18900	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,746.500	-49.61	-13.0	36.61	20.97	H	164.0	2.0
4	5,619.750	-51.34	-13.0	38.34	24.03	H	265.3	2.0



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,746.500	-48.9	-13.0	35.9	21.62	V	262.4	2.0
4	5,619.750	-47.33	-13.0	34.33	24.43	V	1.0	1.0



CHANNEL BANDWIDTH: 20MHz / QPSK

CH18700

MODE	TX channel 18700	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,702.000	-48.24	-13.0	35.24	20.97	H	173.3	2.0
4	5,553.000	-51.04	-13.0	38.04	23.75	H	242.6	1.0



MODE	TX channel 18700	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,702.500	-46.74	-13.0	33.74	21.56	V	0.9	2.0
4	5,553.000	-48.27	-13.0	35.27	24.45	V	359.0	1.0



CH18900

MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,742.000	-46.45	-13.0	33.45	20.95	H	154.9	2.0
4	5,613.000	-50.44	-13.0	37.44	23.99	H	0.9	2.0



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,742.000	-48.71	-13.0	35.71	21.6	V	184.6	1.0
4	5,613.000	-50.54	-13.0	37.54	24.43	V	359.1	1.0



CH19100

MODE	TX channel 19100	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,782.000	-50.57	-13.0	37.57	21.58	H	251.0	1.0
4	5,673.000	-50.79	-13.0	37.79	24.2	H	154.2	1.0



MODE	TX channel 19100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,782.000	-50.25	-13.0	37.25	21.78	V	101.8	1.0
4	5,673.000	-47.7	-13.0	34.7	24.6	V	1.0	1.0



3.7 PEAK TO AVERAGE RATIO

3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

3.7.2 TEST SETUP



3.7.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

3.7.4 TEST RESULTS

Please Refer to Appendix Of this test report.

4 INFORMATION ON THE TESTING LABORATORIES

We, Huarui 7layers High Technology (Suzhou) Co., Ltd. ,were founded in 2020 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Huarui 7Layers High Technology (Suzhou) Co., Ltd.
Lab Address:
Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province
Accredited Test Lab Cert 6613.01

If you have any comments, please feel free to contact us at the following:

Suzhou EMC/RF Lab:
Tel: +86 (0557) 368 1008

5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

6 Appendix

GSM 1900

PEAK-TO-AVERAGE RATIO(CCDF)

Test Result

Band	Channel	Result(dB)	Limit(dB)	Verdict
GSM1900	512	0.96	13	PASS
GSM1900	661	0.96	13	PASS
GSM1900	810	1.04	13	PASS
EGPRS1900	512	1.84	13	PASS
EGPRS1900	661	2.36	13	PASS
EGPRS1900	810	2.36	13	PASS

Test Graphs

GSM1900-512



GSM1900-661



GSM1900-810



EGPRS1900-512



EGPRS1900-661



EGPRS1900-810



26DB BANDWIDTH AND OCCUPIED BANDWIDTH

Test Result

Band	Channel	Occupied Bandwidth (kHz)	26dB Bandwidth (kHz)	Verdict
GSM1900	512	245.780	319.18	PASS
GSM1900	661	245.218	318.68	PASS
GSM1900	810	244.991	315.18	PASS
EGPRS1900	512	245.117	306.69	PASS
EGPRS1900	661	241.630	312.69	PASS
EGPRS1900	810	245.815	312.19	PASS

Test Graphs

Occupied Bandwidth

GSM1900-512



GSM1900-661



GSM1900-810