

# TEST REPORT

**Reference No.**..... : WTS19S09066153W001 V1  
**FCC ID** ..... : ZLZ-WMTSAP70  
**Applicant**..... : Shenzhen Mindray BIO-Medical electronics Co.,LTD.  
**Address**..... : Mindray Building, Keji 12th Road South, Hi-tech Ind, Shenzhen, China  
**Manufacturer** ..... : The same as above  
**Address**..... : The same as above  
**Product**..... : WMTS Access Point  
**Model(s)** ..... : AP70  
**Brand Name**..... : Mindray  
**Standards**..... : FCC CFR47 Part 95 Subpart H  
**Date of Receipt sample** .... : 2019-09-23  
**Date of Test** ..... : 2019-09-24 to 2019-11-25  
**Date of Issue**..... : 2020-03-17  
**Test Result**..... : **Pass**

**Remarks:**

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

**Prepared By:**

**Waltek Services (Shenzhen) Co., Ltd.**

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

*Ford Wang*

Ford Wang / Project Engineer

Approved by:



*Philip Zhong*

Philip Zhong / Manager

## 2 Contents

|                                                     | <b>Page</b> |
|-----------------------------------------------------|-------------|
| <b>1 COVER PAGE.....</b>                            | <b>1</b>    |
| <b>2 CONTENTS .....</b>                             | <b>2</b>    |
| <b>3 REVISION HISTORY .....</b>                     | <b>3</b>    |
| <b>4 GENERAL INFORMATION.....</b>                   | <b>4</b>    |
| 4.1 GENERAL DESCRIPTION OF E.U.T. ....              | 4           |
| 4.2 DETAILS OF E.U.T. ....                          | 4           |
| 4.3 TEST MODE .....                                 | 5           |
| <b>5 TEST SUMMARY .....</b>                         | <b>6</b>    |
| <b>6 TEST FACILITY .....</b>                        | <b>7</b>    |
| <b>7 EQUIPMENT USED DURING TEST .....</b>           | <b>8</b>    |
| 7.1 EQUIPMENTS LIST .....                           | 8           |
| 7.2 MEASUREMENT UNCERTAINTY .....                   | 8           |
| 7.3 TEST EQUIPMENT CALIBRATION .....                | 9           |
| <b>8 FIELD STRENGTH OF FUNDAMENTAL.....</b>         | <b>10</b>   |
| 8.1 EUT OPERATION.....                              | 10          |
| 8.2 TEST PROCEDURE .....                            | 10          |
| 8.3 TEST LIMITS .....                               | 10          |
| 8.4 TEST RESULT .....                               | 11          |
| <b>9 FIELD STRENGTH OF SPURIOUS EMISSIONS .....</b> | <b>12</b>   |
| 9.1 EUT OPERATION.....                              | 12          |
| 9.2 TEST SETUP .....                                | 12          |
| 9.3 SPECTRUM ANALYZER SETUP .....                   | 14          |
| 9.4 TEST PROCEDURE .....                            | 15          |
| 9.5 SUMMARY OF TEST RESULTS .....                   | 16          |
| <b>10 OCCUPIED BANDWIDTH.....</b>                   | <b>18</b>   |
| 10.1 EUT OPERATION.....                             | 18          |
| 10.2 TEST PROCEDURE.....                            | 18          |
| 10.3 TEST RESULT .....                              | 19          |
| <b>11 FREQUENCY STABILITY.....</b>                  | <b>29</b>   |
| 11.1 EUT OPERATION.....                             | 29          |
| 11.2 TEST PROCEDURE.....                            | 29          |
| 11.3 TEST RESULT .....                              | 30          |
| <b>12 RF EXPOSURE.....</b>                          | <b>40</b>   |
| <b>13 PHOTOGRAPHS OF TEST SETUP AND EUT.....</b>    | <b>41</b>   |

### 3 Revision History

| Test report No.           | Date of Receipt sample | Date of Test | Date of Issue | Purpose   | Comment | Approved |
|---------------------------|------------------------|--------------|---------------|-----------|---------|----------|
| WTS19S09066<br>153W001    | 2019-09-23             | 2019-09-24   | 2019-11-25    | original  | -       | Replaced |
| WTS19S09066<br>153W001 V1 | 2019-09-23             | 2019-09-24   | 2020-03-17    | Version 1 | Updated | Valid    |

## 4 General Information

### 4.1 General Description of E.U.T.

|                    |                   |
|--------------------|-------------------|
| Product:           | WMTS Access Point |
| Model(s):          | AP70              |
| Model Description: | N/A               |
| Support:           | WMTS              |
| Hardware Version:  | 1.0               |
| Software Version:  | 1.0               |

### 4.2 Details of E.U.T.

|                       |                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------|
| Operation Frequency:  | 608MHz(608-614MHz)<br>1.4GHz(1395-1400MHz)<br>1.4GHz(1427-1432MHz)                              |
| Max. RF output power: | RF1:608MHz:104.62dBu/m ,1.4GHz: 100.65 dBu/m<br>RF2: 608MHz: 104.13 dBu/m, 1.4GHz: 101.11 dBu/m |
| Type of Modulation:   | GFSK                                                                                            |
| Antenna installation: | WMTS: External antenna                                                                          |
| Ratings:              | POE power:44-57V 0.1A<br>DC 5V 1A From adapter                                                  |

### 4.3 Test Mode

All channels and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

| Support Band                                | Channel Frequency |
|---------------------------------------------|-------------------|
| 608-614MHz                                  | 608.66 MHz        |
|                                             | 611.06 MHz        |
|                                             | 613.46 MHz        |
| 1395-1400MHz and 1427-1432 MHz(wide band)   | 1395.5 MHz        |
|                                             | 1399.5 MHz        |
|                                             | 1431.5 MHz        |
| 1395-1400MHz and 1427-1432 MHz(narrow band) | 1395.4 MHz        |
|                                             | 1399.6 MHz        |
|                                             | 1431.6 MHz        |

## 5 Test Summary

| Test Items                           | Test Requirement | Result |
|--------------------------------------|------------------|--------|
| FIELD STRENGTH OF FUNDAMENTAL        | 95.2369(a)(b)    | PASS   |
| FIELD STRENGTH OF SPURIOUS EMISSIONS | 95.2379(a)(b)    | PASS   |
| OCCUPIED BANDWIDTH                   | 2.1049           | PASS   |
| FREQUENCY STABILITY                  | 95.2365          | PASS   |

## 6 Test Facility

The test facility has a test site registered with the following organizations:

**ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.**

Waltek Services(Shenzhen) Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

**FCC Designation No.: CN1201. Test Firm Registration No.: 523476.**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

## 7 Equipment Used during Test

### 7.1 Equipments List

| 3m Semi-anechoic Chamber for Radiation Emissions Test site 1# |                             |                                  |             |            |                       |                      |
|---------------------------------------------------------------|-----------------------------|----------------------------------|-------------|------------|-----------------------|----------------------|
| Item                                                          | Equipment                   | Manufacturer                     | Model No.   | Serial No. | Last Calibration Date | Calibration Due Date |
| 1                                                             | Spectrum Analyzer           | R&S                              | FSP         | 100091     | 2019-04-19            | 2020-04-18           |
| 2                                                             | LARGE LOOP ANTENNA          | Laplace                          | RF300       | 9057       | 2019-09-17            | 2020-09-16           |
| 3                                                             | Trilog Broadband Antenna    | SCHWARZBECK                      | VULB9163    | 336        | 2019-04-28            | 2020-04-27           |
| 4                                                             | Coaxial Cable (below 1GHz)  | Top                              | TYPE16(13M) | -          | 2019-04-28            | 2020-04-27           |
| 5                                                             | Broad-band Horn Antenna     | SCHWARZBECK                      | BBHA 9120 D | 667        | 2019-04-19            | 2020-04-18           |
| 6                                                             | Broad-band Horn Antenna     | SCHWARZBECK                      | BBHA 9170   | 335        | 2019-04-28            | 2020-04-27           |
| 7                                                             | Broadband Preamplifier      | COMPLIANCE DIRECTION             | PAP-1G18    | 2004       | 2019-04-19            | 2020-04-18           |
| 8                                                             | Coaxial Cable (above 1GHz)  | Top                              | 1GHz-25GHz  | EW02014-7  | 2019-04-19            | 2020-04-18           |
| 10                                                            | Signal Generator            | R&S                              | SMR20       | 100046     | 2019-07-12            | 2020-07-11           |
| 11                                                            | Smart Antenna               | SCHWARZBECK                      | HA08        | -          | 2019-04-09            | 2020-04-08           |
| 3m Semi-anechoic Chamber for Radiation Emissions Test site 2# |                             |                                  |             |            |                       |                      |
| Item                                                          | Equipment                   | Manufacturer                     | Model No.   | Serial No  | Last Calibration Date | Calibration Due Date |
| 1                                                             | Test Receiver               | R&S                              | ESCI        | 101296     | 2019-04-20            | 2020-04-19           |
| 2                                                             | Trilog Broadband Antenna    | SCHWARZBECK                      | VULB9160    | 9160-3325  | 2019-05-24            | 2020-05-23           |
| 3                                                             | Amplifier                   | Compliance pirection systems inc | PAP-0203    | 22024      | 2019-04-19            | 2020-04-18           |
| 4                                                             | Cable                       | HUBER+SUHNER                     | CBL2        | 525178     | 2019-04-20            | 2020-04-19           |
| RF Conducted Testing                                          |                             |                                  |             |            |                       |                      |
| Item                                                          | Equipment                   | Manufacturer                     | Model No.   | Serial No. | Last Calibration Date | Calibration Due Date |
| 2.                                                            | Spectrum Analyzer (9k-6GHz) | R&S                              | FSL6        | 100959     | 2019-09-12            | 2020-09-11           |

### 7.2 Measurement Uncertainty

| Parameter          | Uncertainty                      |
|--------------------|----------------------------------|
| Conducted Emission | ± 3.64 dB(AC mains 150KHz~30MHz) |

|                                                 |                                         |
|-------------------------------------------------|-----------------------------------------|
| Radiated Spurious Emissions                     | ± 5.08 dB (Bilog antenna 30M~1000MHz)   |
|                                                 | ± 5.47 dB (Horn antenna 1000M~25000MHz) |
| Radio Frequency                                 | ± 1 x 10 <sup>-7</sup> Hz               |
| RF Power                                        | ± 0.42 dB                               |
| RF Power Density                                | ± 0.7dB                                 |
| Conducted Spurious Emissions                    | ± 2.76 dB (9kHz~26500MHz)               |
| Confidence interval: 95%. Confidence factor:k=2 |                                         |

### 7.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

## 8 FIELD STRENGTH OF FUNDAMENTAL

|                   |                     |
|-------------------|---------------------|
| Test Requirement: | 95.2369(a)(b)       |
| Test Method:      | ANSI/TIA-603-E-2016 |
| Test Mode:        | TX transmitting     |

### 8.1 EUT Operation

Operating Environment :

|                       |           |
|-----------------------|-----------|
| Temperature:          | 22.5 °C   |
| Humidity:             | 52.1 % RH |
| Atmospheric Pressure: | 101.2kPa  |

### 8.2 Test Procedure

Radiated method:

1. The setup of EUT is according with per TIA/EIA/EIA Standard 603-C.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

### 8.3 Test limits

(a) For WMTS transmitter types operating in the 608-614 MHz band, the field strength of the transmitted signal must not exceed 200 mV/m, measured at a distance of 3 meters, using instrumentation with a CISPR quasi-peak detector.

(b) For WMTS transmitter types operating in the 1395-1400 MHz and 1427-1432 MHz bands, the field strength of the transmitted signal must not exceed 740 mV/m, measured at 3 meters, using instrumentation with an averaging detector and a 1MHz reference bandwidth.

## 8.4 Test Result

### FIELD STRENGTH OF FUNDAMENTAL

RF1:

| Test channels(MHz) | Field Strength(dBuv/m) | limits(dBuv/m) | Result |
|--------------------|------------------------|----------------|--------|
| 608.66 MHz         | 104.62                 | 106            | PASS   |
| 611.06 MHz         | 104.10                 | 106            | PASS   |
| 613.46 MHz         | 103.20                 | 106            | PASS   |
| 1395.5 MHz(WB)     | 99.98                  | 117.4          | PASS   |
| 1399.5 MHz(WB)     | 100.65                 | 117.4          | PASS   |
| 1431.5 MHz(WB)     | 98.89                  | 117.4          | PASS   |
| 1395.4 MHz(NB)     | 99.48                  | 117.4          | PASS   |
| 1399.6 MHz(NB)     | 99.48                  | 117.4          | PASS   |
| 1431.6 MHz(NB)     | 98.89                  | 117.4          | PASS   |

RF2:

| Test channels(MHz) | Field Strength(dBuv/m) | limits(dBuv/m) | Result |
|--------------------|------------------------|----------------|--------|
| 608.66 MHz         | 103.80                 | 106            | PASS   |
| 611.06 MHz         | 104.13                 | 106            | PASS   |
| 613.46 MHz         | 103.52                 | 106            | PASS   |
| 1395.5 MHz(WB)     | 101.11                 | 117.4          | PASS   |
| 1399.5 MHz(WB)     | 100.71                 | 117.4          | PASS   |
| 1431.5 MHz(WB)     | 99.42                  | 117.4          | PASS   |
| 1395.4 MHz(NB)     | 100.38                 | 117.4          | PASS   |
| 1399.6 MHz(NB)     | 100.02                 | 117.4          | PASS   |
| 1431.6 MHz(NB)     | 98.77                  | 117.4          | PASS   |

## 9 FIELD STRENGTH OF SPURIOUS EMISSIONS

Test Requirement: 95.2379(a)(b)  
Test Method: ANSI/TIA-603-E-2016  
Test Mode: TX transmitting


### 9.1 EUT Operation

Operating Environment :


Temperature: 23.5 °C  
Humidity: 52.1 % RH  
Atmospheric Pressure: 101.2kPa

### 9.2 Test Setup


The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site.  
The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



### 9.3 Spectrum Analyzer Setup

30MHz ~ 1GHz

Sweep Speed ..... Auto  
Detector ..... PK  
Resolution Bandwidth.....100kHz  
Video Bandwidth.....300kHz  
Detector ..... QP.  
Resolution Bandwidth.....100kHz  
Video Bandwidth.....300kHz

Above 1GHz

Sweep Speed ..... Auto  
Detector ..... PK  
Resolution Bandwidth.....1MHz  
Video Bandwidth.....3MHz  
Detector ..... Ave.  
Resolution Bandwidth.....1MHz  
Video Bandwidth.....3MHz

## 9.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m for below 1GHz and 1.5m for above 1GHz above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from 30MHz up to the tenth harmonic of the highest fundamental frequency.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the Z position. So the data shown was the Z position only.
7. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.  
  
Spurious emissions in dB =  $10 \lg (\text{TXpwr in Watts}/0.001)$  – the absolute level  
Spurious attenuation limit in dB =  $43 + 10 \lg (\text{power out in Watts})$
8. Repeat above procedures until the measurements for all frequencies are completed.

## 9.5 Summary of Test Results

For 26MHz~30MHz,

The measurements were more than 20 dB below the limit and not reported.

Remark: Test performed from 30MHz to 10<sup>th</sup> harmonics with low/middle/high channels at RF1 and RF2 ANT, only the worst data were recorded.

**RF1 Low channel(1395.5MHz WB)**

| Freq (MHz) | Reading (dBuv/m) | Factor (dB) | Polar (V/H) | Result (dBuv/m) | Limit (dBuv/m) | Margin (dB) | Detector |
|------------|------------------|-------------|-------------|-----------------|----------------|-------------|----------|
| 252.0627   | 42.55            | -16.12      | V           | 26.43           | 46.00          | -19.57      | QP       |
| 417.6411   | 45.56            | -11.81      | V           | 33.75           | 46.00          | -12.25      | QP       |
| 492.4685   | 40.93            | -10.19      | H           | 30.74           | 46.00          | -15.26      | QP       |
| 492.4685   | 40.93            | -3.31       | H           | 29.74           | 46.00          | -16.26      | QP       |
| 2791.000   | 37.09            | -10.93      | V           | 26.16           | 54.00          | -27.84      | AV       |
| 4186.500   | 37.60            | -4.70       | V           | 32.90           | 54.00          | -21.10      | AV       |
| 2791.000   | 33.17            | -7.21       | H           | 25.96           | 54.00          | -28.04      | AV       |
| 4186.500   | 37.34            | -4.62       | H           | 32.72           | 54.00          | -21.28      | AV       |

**RF1 Low channel(1395.5MHz NB)**

| Freq (MHz) | Reading (dBuv/m) | Factor (dB) | Polar (V/H) | Result (dBuv/m) | Limit (dBuv/m) | Margin (dB) | Detector |
|------------|------------------|-------------|-------------|-----------------|----------------|-------------|----------|
| 492.4685   | 40.93            | -10.19      | V           | 30.74           | 46.00          | -15.26      | QP       |
| 887.6099   | 33.05            | -3.31       | V           | 29.74           | 46.00          | -16.26      | QP       |
| 501.1790   | 40.50            | -10.06      | H           | 30.44           | 46.00          | -15.56      | QP       |
| 801.7863   | 33.39            | -4.42       | H           | 28.97           | 46.00          | -17.03      | QP       |
| 2730.800   | 36.60            | -11.10      | V           | 25.50           | 54.00          | -28.50      | AV       |
| 4186.200   | 37.35            | -4.70       | V           | 32.65           | 54.00          | -21.35      | AV       |
| 2730.800   | 32.40            | -7.27       | H           | 25.13           | 54.00          | -28.87      | AV       |
| 4186.200   | 37.10            | -4.62       | H           | 32.48           | 54.00          | -21.52      | AV       |

**RF1 Low channel(608.66MHz)**

| Freq<br>(MHz) | Reading<br>(dBuv/m) | Factor<br>(dB) | Polar<br>(V/H) | Result<br>(dBuv/m) | Limit<br>(dBuv/m) | Margin<br>(dB) | Detector |
|---------------|---------------------|----------------|----------------|--------------------|-------------------|----------------|----------|
| 250.3012      | 42.18               | -16.16         | V              | 26.02              | 46.00             | -19.98         | QP       |
| 382.5879      | 41.60               | -12.76         | V              | 28.84              | 46.00             | -17.16         | QP       |
| 237.4760      | 45.76               | -16.63         | H              | 29.13              | 46.00             | -16.87         | QP       |
| 420.5803      | 40.78               | -11.71         | H              | 29.07              | 46.00             | -16.93         | QP       |
| 1217.320      | 40.37               | -14.91         | V              | 25.46              | 54.00             | -28.54         | AV       |
| 1825.980      | 36.47               | -11.65         | V              | 24.82              | 54.00             | -29.18         | AV       |
| 1198.000      | 46.74               | -12.80         | H              | 33.94              | 54.00             | -20.06         | AV       |
| 1217.320      | 36.45               | -12.70         | H              | 23.75              | 54.00             | -30.25         | AV       |

Note: Margin = Limit-Result

## 10 OCCUPIED BANDWIDTH

|                   |                     |
|-------------------|---------------------|
| Test Requirement: | 2.1049              |
| Test Method:      | ANSI/TIA-603-E-2016 |
| Test Mode:        | TX transmitting     |

### 10.1 EUT Operation

|                         |           |
|-------------------------|-----------|
| Operating Environment : |           |
| Temperature:            | 23.5 °C   |
| Humidity:               | 52.3 % RH |
| Atmospheric Pressure:   | 101.3kPa  |

### 10.2 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 10kHz, VBW = 30kHz

### 10.3 Test Result

RF1:


| Test Channel   | Bandwidth(KHz) |
|----------------|----------------|
| 608.66 MHz     | 449.10         |
| 611.06 MHz     | 449.10         |
| 613.46 MHz     | 447.10         |
| 1395.5 MHz(WB) | 878.20         |
| 1399.5 MHz(WB) | 878.20         |
| 1431.5 MHz(WB) | 878.20         |
| 1395.4 MHz(NB) | 441.10         |
| 1399.6 MHz(NB) | 441.10         |
| 1431.6 MHz(NB) | 441.10         |

RF2


| Test Channel   | Bandwidth(KHz) |
|----------------|----------------|
| 608.66 MHz     | 451.10         |
| 611.06 MHz     | 451.10         |
| 613.46 MHz     | 451.10         |
| 1395.5 MHz(WB) | 878.20         |
| 1399.5 MHz(WB) | 878.20         |
| 1431.5 MHz(WB) | 878.20         |
| 1395.4 MHz(NB) | 439.70         |
| 1399.6 MHz(NB) | 441.10         |
| 1431.6 MHz(NB) | 441.10         |



RF1:Test plots



608.66 MHz






611.06MHz


















RF2



RF1:Test plots











## 11 FREQUENCY STABILITY

|                   |                                         |
|-------------------|-----------------------------------------|
| Test Requirement: | FCC Part 2.1055                         |
| Test Method:      | ANSI/TIA-603-E-2016<br>ANSI C63.26:2015 |
| Test Mode:        | TX transmitting                         |
| Note:             | N/A                                     |

### 11.1 EUT Operation

Operating Environment :


|                       |           |
|-----------------------|-----------|
| Temperature:          | 22.9 °C   |
| Humidity:             | 52.0 % RH |
| Atmospheric Pressure: | 101.3kPa  |

### 11.2 Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



### 11.3 Test Result

RF1 ANT

| Test Frequency:1395.5MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 17                   | 0.0122                | 100         |
| 40                       |                    | 1                    | 0.0007                | 100         |
| 30                       |                    | 11                   | 0.0079                | 100         |
| 20                       |                    | 9                    | 0.0064                | 100         |
| 10                       |                    | 12                   | 0.0086                | 100         |
| 0                        |                    | 14                   | 0.0100                | 100         |
| -10                      |                    | 12                   | 0.0086                | 100         |
| -20                      |                    | 14                   | 0.0100                | 100         |
| -30                      |                    | 11                   | 0.0079                | 100         |
| 20                       | 4.50               | 13                   | 0.0093                | 100         |
| 20                       | 5.75               | 14                   | 0.0100                | 100         |

| Test Frequency:1399.5MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 8                    | 0.0057                | 100         |
| 40                       |                    | 17                   | 0.0121                | 100         |
| 30                       |                    | 5                    | 0.0036                | 100         |
| 20                       |                    | 9                    | 0.0064                | 100         |
| 10                       |                    | 15                   | 0.0107                | 100         |
| 0                        |                    | 5                    | 0.0036                | 100         |
| -10                      |                    | 9                    | 0.0064                | 100         |
| -20                      |                    | 11                   | 0.0079                | 100         |
| -30                      |                    | 1                    | 0.0007                | 100         |
| 20                       | 4.50               | 11                   | 0.0079                | 100         |
| 20                       | 5.75               | 12                   | 0.0086                | 100         |

| Test Frequency:1431.5MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 12                   | 0.0084                | 100         |
| 40                       |                    | 12                   | 0.0084                | 100         |
| 30                       |                    | 5                    | 0.0035                | 100         |
| 20                       |                    | 9                    | 0.0063                | 100         |
| 10                       |                    | 14                   | 0.0098                | 100         |
| 0                        |                    | 4                    | 0.0028                | 100         |
| -10                      |                    | 17                   | 0.0119                | 100         |
| -20                      |                    | 7                    | 0.0049                | 100         |
| -30                      |                    | 0                    | 0.0000                | 100         |
| 20                       | 4.50               | 4                    | 0.0028                | 100         |
| 20                       | 5.75               | 8                    | 0.0056                | 100         |

| Test Frequency:1395.4MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 15                   | 0.0107                | 100         |
| 40                       |                    | 17                   | 0.0122                | 100         |
| 30                       |                    | 1                    | 0.0007                | 100         |
| 20                       |                    | 9                    | 0.0064                | 100         |
| 10                       |                    | 17                   | 0.0122                | 100         |
| 0                        |                    | 11                   | 0.0079                | 100         |
| -10                      |                    | 16                   | 0.0115                | 100         |
| -20                      |                    | 17                   | 0.0122                | 100         |
| -30                      |                    | 2                    | 0.0014                | 100         |
| 20                       | 4.50               | 9                    | 0.0064                | 100         |
| 20                       | 5.75               | 2                    | 0.0014                | 100         |

| Test Frequency:1399.6MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 12                   | 0.0086                | 100         |
| 40                       |                    | 16                   | 0.0114                | 100         |
| 30                       |                    | 10                   | 0.0071                | 100         |
| 20                       |                    | 9                    | 0.0064                | 100         |
| 10                       |                    | 4                    | 0.0029                | 100         |
| 0                        |                    | 16                   | 0.0114                | 100         |
| -10                      |                    | 11                   | 0.0079                | 100         |
| -20                      |                    | 10                   | 0.0071                | 100         |
| -30                      |                    | 11                   | 0.0079                | 100         |
| 20                       | 4.50               | 6                    | 0.0043                | 100         |
| 20                       | 5.75               | 14                   | 0.0100                | 100         |

| Test Frequency:1431.6MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 14                   | 0.0098                | 100         |
| 40                       |                    | 1                    | 0.0007                | 100         |
| 30                       |                    | 2                    | 0.0014                | 100         |
| 20                       |                    | 9                    | 0.0063                | 100         |
| 10                       |                    | 2                    | 0.0014                | 100         |
| 0                        |                    | 6                    | 0.0042                | 100         |
| -10                      |                    | 11                   | 0.0077                | 100         |
| -20                      |                    | 1                    | 0.0007                | 100         |
| -30                      |                    | 3                    | 0.0021                | 100         |
| 20                       | 4.50               | 13                   | 0.0091                | 100         |
| 20                       | 5.75               | 12                   | 0.0084                | 100         |

| Test Frequency:608.66MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 2                    | 0.0033                | 100         |
| 40                       |                    | 11                   | 0.0181                | 100         |
| 30                       |                    | 9                    | 0.0148                | 100         |
| 20                       |                    | 9                    | 0.0148                | 100         |
| 10                       |                    | 9                    | 0.0148                | 100         |
| 0                        |                    | 5                    | 0.0082                | 100         |
| -10                      |                    | 2                    | 0.0033                | 100         |
| -20                      |                    | 9                    | 0.0148                | 100         |
| -30                      |                    | 3                    | 0.0049                | 100         |
| 20                       | 4.50               | 3                    | 0.0049                | 100         |
| 20                       | 5.75               | 17                   | 0.0279                | 100         |

| Test Frequency:611.06MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 3                    | 0.0049                | 100         |
| 40                       |                    | 13                   | 0.0213                | 100         |
| 30                       |                    | 8                    | 0.0131                | 100         |
| 20                       |                    | 9                    | 0.0147                | 100         |
| 10                       |                    | 9                    | 0.0147                | 100         |
| 0                        |                    | 5                    | 0.0082                | 100         |
| -10                      |                    | 11                   | 0.0180                | 100         |
| -20                      |                    | 17                   | 0.0278                | 100         |
| -30                      |                    | 12                   | 0.0196                | 100         |
| 20                       | 4.50               | 15                   | 0.0245                | 100         |
| 20                       | 5.75               | 8                    | 0.0131                | 100         |

| Test Frequency:613.46MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 17                   | 0.0277                | 100         |
| 40                       |                    | 15                   | 0.0245                | 100         |
| 30                       |                    | 15                   | 0.0245                | 100         |
| 20                       |                    | 9                    | 0.0147                | 100         |
| 10                       |                    | 11                   | 0.0179                | 100         |
| 0                        |                    | 4                    | 0.0065                | 100         |
| -10                      |                    | 4                    | 0.0065                | 100         |
| -20                      |                    | 3                    | 0.0049                | 100         |
| -30                      |                    | 15                   | 0.0245                | 100         |
| 20                       | 4.50               | 18                   | 0.0293                | 100         |
| 20                       | 5.75               | 5                    | 0.0082                | 100         |

## RF2 ANT

| Test Frequency:1395.5MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 11                   | 0.0059                | 100         |
| 40                       |                    | 12                   | 0.0064                | 100         |
| 30                       |                    | -3                   | -0.0016               | 100         |
| 20                       |                    | 6                    | 0.0032                | 100         |
| 10                       |                    | -1                   | -0.0005               | 100         |
| 0                        |                    | 13                   | 0.0069                | 100         |
| -10                      |                    | 4                    | 0.0021                | 100         |
| -20                      |                    | 13                   | 0.0069                | 100         |
| -30                      |                    | 0                    | 0.0000                | 100         |
| 20                       | 4.50               | 1                    | 0.0005                | 100         |
| 20                       | 5.75               | -2                   | -0.0011               | 100         |

| Test Frequency:1399.5MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 2                    | 0.0024                | 100         |
| 40                       |                    | -2                   | -0.0024               | 100         |
| 30                       |                    | 0                    | 0.0000                | 100         |
| 20                       |                    | 5                    | 0.0060                | 100         |
| 10                       |                    | 1                    | 0.0012                | 100         |
| 0                        |                    | 11                   | 0.0131                | 100         |
| -10                      |                    | -2                   | -0.0024               | 100         |
| -20                      |                    | 8                    | 0.0096                | 100         |
| -30                      |                    | -1                   | -0.0012               | 100         |
| 20                       | 4.50               | 5                    | 0.0060                | 100         |
| 20                       | 5.75               | -4                   | -0.0048               | 100         |

| Test Frequency:1431.5MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 7                    | 0.0084                | 100         |
| 40                       |                    | 17                   | 0.0203                | 100         |
| 30                       |                    | 9                    | 0.0108                | 100         |
| 20                       |                    | 8                    | 0.0096                | 100         |
| 10                       |                    | 1                    | 0.0012                | 100         |
| 0                        |                    | 7                    | 0.0084                | 100         |
| -10                      |                    | 0                    | 0.0000                | 100         |
| -20                      |                    | 2                    | 0.0024                | 100         |
| -30                      |                    | 16                   | 0.0191                | 100         |
| 20                       | 4.50               | 15                   | 0.0179                | 100         |
| 20                       | 5.75               | 0                    | 0.0000                | 100         |

| Test Frequency:1395.4MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 6                    | 0.0072                | 100         |
| 40                       |                    | 2                    | 0.0024                | 100         |
| 30                       |                    | 10                   | 0.0120                | 100         |
| 20                       |                    | 6                    | 0.0072                | 100         |
| 10                       |                    | 10                   | 0.0120                | 100         |
| 0                        |                    | 11                   | 0.0131                | 100         |
| -10                      |                    | 14                   | 0.0167                | 100         |
| -20                      |                    | 14                   | 0.0167                | 100         |
| -30                      |                    | -1                   | -0.0012               | 100         |
| 20                       | 4.50               | 6                    | 0.0072                | 100         |
| 20                       | 5.75               | 12                   | 0.0143                | 100         |

| Test Frequency:1399.6MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 12                   | 0.0086                | 100         |
| 40                       |                    | 16                   | 0.0114                | 100         |
| 30                       |                    | 10                   | 0.0071                | 100         |
| 20                       |                    | 9                    | 0.0064                | 100         |
| 10                       |                    | 4                    | 0.0029                | 100         |
| 0                        |                    | 16                   | 0.0114                | 100         |
| -10                      |                    | 11                   | 0.0079                | 100         |
| -20                      |                    | 10                   | 0.0071                | 100         |
| -30                      |                    | 11                   | 0.0079                | 100         |
| 20                       | 4.50               | 6                    | 0.0043                | 100         |
| 20                       | 5.75               | 14                   | 0.0100                | 100         |

| Test Frequency:1431.6MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 10                   | 0.0053                | 100         |
| 40                       |                    | 10                   | 0.0053                | 100         |
| 30                       |                    | -1                   | -0.0005               | 100         |
| 20                       |                    | 7                    | 0.0037                | 100         |
| 10                       |                    | 15                   | 0.0080                | 100         |
| 0                        |                    | 8                    | 0.0043                | 100         |
| -10                      |                    | 11                   | 0.0059                | 100         |
| -20                      |                    | 2                    | 0.0011                | 100         |
| -30                      |                    | 2                    | 0.0011                | 100         |
| 20                       | 4.50               | -2                   | -0.0011               | 100         |
| 20                       | 5.75               | 12                   | 0.0064                | 100         |

| Test Frequency:608.66MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 7                    | 0.0037                | 100         |
| 40                       |                    | -2                   | -0.0011               | 100         |
| 30                       |                    | 2                    | 0.0011                | 100         |
| 20                       |                    | 3                    | 0.0016                | 100         |
| 10                       |                    | 2                    | 0.0011                | 100         |
| 0                        |                    | 0                    | 0.0000                | 100         |
| -10                      |                    | 9                    | 0.0048                | 100         |
| -20                      |                    | -4                   | -0.0021               | 100         |
| -30                      |                    | -1                   | -0.0005               | 100         |
| 20                       | 4.50               | 10                   | 0.0053                | 100         |
| 20                       | 5.75               | 4                    | 0.0021                | 100         |

| Test Frequency:611.06MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 1                    | 0.0005                | 100         |
| 40                       |                    | 11                   | 0.0059                | 100         |
| 30                       |                    | -3                   | -0.0016               | 100         |
| 20                       |                    | 5                    | 0.0027                | 100         |
| 10                       |                    | 10                   | 0.0053                | 100         |
| 0                        |                    | -1                   | -0.0005               | 100         |
| -10                      |                    | -1                   | -0.0005               | 100         |
| -20                      |                    | 12                   | 0.0064                | 100         |
| -30                      |                    | 6                    | 0.0032                | 100         |
| 20                       | 4.50               | 8                    | 0.0043                | 100         |
| 20                       | 5.75               | 6                    | 0.0032                | 100         |

| Test Frequency:613.46MHz |                    |                      |                       |             |
|--------------------------|--------------------|----------------------|-----------------------|-------------|
| Temperature (°C)         | Power Supply (VDC) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 50                       | 5                  | 2                    | 0.0024                | 100         |
| 40                       |                    | -5                   | -0.0060               | 100         |
| 30                       |                    | 0                    | 0.0000                | 100         |
| 20                       |                    | 1                    | 0.0012                | 100         |
| 10                       |                    | -7                   | -0.0084               | 100         |
| 0                        |                    | -4                   | -0.0048               | 100         |
| -10                      |                    | -2                   | -0.0024               | 100         |
| -20                      |                    | -6                   | -0.0072               | 100         |
| -30                      |                    | 6                    | 0.0072                | 100         |
| 20                       | 4.50               | 8                    | 0.0096                | 100         |
| 20                       | 5.75               | 9                    | 0.0108                | 100         |

## **12 RF Exposure**

Remark: refer to MPE test report: WTS19S09066153W002

### **13 Photographs of test setup and EUT.**

Note: Please refer to appendix AP70 -Photo.

===== End of Report =====