

FCC ID: ZMABC6-Y

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

EDR:

Model1:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	1.286	1.34	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.441	2.079	1.61	2±1	3.00	2.00	<5	0.62347	3.00	YES
	2.480	1.622	1.45	1±1	2.00	1.58	<5	0.49918	3.00	YES
π /4DQPSK	2.402	1.811	1.52	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.441	2.419	1.75	2±1	3.00	2.00	<5	0.62347	3.00	YES
	2.480	2.116	1.63	2±1	3.00	2.00	<5	0.62843	3.00	YES
8DQPSK	2.402	2.037	1.60	2±1	3.00	2.00	<5	0.61847	3.00	YES
	2.441	2.751	1.88	2±1	3.00	2.00	<5	0.62347	3.00	YES
	2.480	2.447	1.76	2±1	3.00	2.00	<5	0.62843	3.00	YES

Model2:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	1.743	1.49	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.441	1.798	1.51	1±1	2.00	1.58	<5	0.49524	3.00	YES
	2.480	1.428	1.39	1±1	2.00	1.58	<5	0.49918	3.00	YES
π /4DQPSK	2.402	2.481	1.77	2±1	3.00	2.00	<5	0.61847	3.00	YES
	2.441	2.457	1.76	2±1	3.00	2.00	<5	0.62347	3.00	YES
	2.480	2.087	1.62	2±1	3.00	2.00	<5	0.62843	3.00	YES
8DQPSK	2.402	2.759	1.89	2±1	3.00	2.00	<5	0.61847	3.00	YES
	2.441	2.769	1.89	2±1	3.00	2.00	<5	0.62347	3.00	YES
	2.480	2.379	1.73	2±1	3.00	2.00	<5	0.62843	3.00	YES

Conclusion:

For the max result : $0.62843 \leq \text{FCC Limit } 3.0$ for 1g SAR.

Note: BT does not support simultaneous launch