



REPORT No.: SZ25050056W01

TEST REPORT

APPLICANT : Fibocom Wireless Inc.

PRODUCT NAME : Algorithm Board

MODEL NAME : APM215-GL

BRAND NAME : Fibocom

FCC ID : ZMOAPM215GL

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2025-05-21

TEST DATE : 2025-06-10 to 2025-08-26

ISSUE DATE : 2025-11-19



Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	4
1.2. Test Equipment List	5
1.3. Measurement Uncertainty	7
1.4. Testing Laboratory	7
2. General Description	8
2.1. Information of Applicant and Manufacturer	8
2.2. Information of EUT	8
2.3. Channel List of EUT	9
2.4. Test Configuration of EUT	10
2.5. Test Conditions	10
2.6. Test Setup Layout Diagram	10
3. Test Results	13
3.1. Antenna Requirement	13
3.2. Duty Cycle of Test Signal	14
3.3. Maximum Peak Conducted Output Power	15
3.4. Maximum Average Conducted Output Power	16
3.5. 6 dB Bandwidth	17
3.6. Conducted Spurious Emissions and Band Edge	18
3.7. Power Spectral Density	19
3.8. Conducted Emission	20
3.9. Restricted Frequency Bands	21
3.10. Radiated Emission	22
Annex A Test Data and Result	24



REPORT No.: SZ25050056W01

Change History		
Version	Date	Reason for change
1.0	2025-11-19	First edition



1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	/
2	N/A	Duty Cycle of Test Signal	Jul. 30, 2025	Zhu Peihong	PASS	/
3	15.247(b)	Maximum Peak Conducted Output Power	Jul. 30, 2025	Zhu Peihong	PASS	/
4	15.247(b)	Maximum Average Conducted Output Power	Jul. 30, 2025	Zhu Peihong	PASS	/
5	15.247(a)	Bandwidth	Jul. 30, 2025	Zhu Peihong	PASS	/
6	15.247(d)	Conducted Spurious Emission and Band Edge	Jul. 30, 2025	Zhu Peihong	PASS	/
7	15.247(e)	Power Spectral Density	Jul. 30, 2025	Zhu Peihong	PASS	/
8	15.207	Conducted Emission	Jun. 19, 2025	Wang Yapeng	PASS	/
9	15.247(d)	Restricted Frequency Bands	Aug. 14, 2025	Gao Jianrou	PASS	/
10	15.209, 15.247(d)	Radiated Emission	Jul. 17, 2025 Aug. 14, 2025	Gao Jianrou	PASS	/

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2020 and KDB 558074 D01 v05r02.

Note 2: Any additions, deviation, or exclusions from the method shall be noted in the “Remark”.

1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2025.01.15	2026.01.14
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	101052	ESPI	R&S	2025.05.15	2026.05.14
LISN	103131	ENV 216	R&S	2025.03.20	2026.03.19
RF Coaxial Cable (DC-100MHz)	EMC-CE-00514	N/A	N/A	2025.05.06	2026.05.05

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2025.05.13	2026.05.12
Test Antenna - Bi-Log	9163-274	VULB 9163	Schwarzbeck	2024.06.22	2025.06.21
				2025.06.28	2026.06.27
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2025.05.16	2026.05.15
Test Antenna – Horn	9120D-963	BBHA 9120D	Schwarzbeck	2025.05.16	2026.05.15
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2024.06.22	2025.06.21
				2025.06.20	2026.06.19
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	N/A	N/A
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	N/A	N/A
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	N/A	N/A
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.11.30	2025.11.29



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	Fibocom Wireless Inc.
Applicant Address:	1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen, China
Manufacturer:	Fibocom Wireless Inc.
Manufacturer Address:	1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen, China

2.2. Information of EUT

Product Name:	Algorithm Board
Sample No.:	1#, 5#
Hardware Version:	V1.2
Software Version:	16121.0001.01.01.21_1012.01
Equipment Type:	Bluetooth LE
Bluetooth Version:	5.4
Modulation Type:	GFSK
Data Rate:	1Mbps, 2Mbps
Operating Frequency Range:	2402MHz-2480MHz
Antenna Type:	FPC Antenna
Antenna Gain:	2.98dBi

Note 1: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



2.3.Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT


The EUT is controlled by dedicated software to transmit at the default maximum power level.

2.5. Test Conditions


Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement




2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☒ Internal ☐ External	☒ FPC Antenna ☐ Spring Antenna ☐ Ceramic Antenna ☐ Integrated Antenna ☐ Dipole Antenna ☐ PCB Antenna ☐ PIFA Antenna ☐ Inverted F Antenna	☒ I-PEX Connector ☐ SMA Connector ☐ RP-SMA Connector ☐ Metal Shrapnel ☐ Layout

3.2. Duty Cycle of Test Signal

3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration(T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e.,no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.2.2. Test Result

Refer to Annex A.1 in this report.



3.3. Maximum Peak Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

3.3.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 in this report.



3.4. Maximum Average Conducted Output Power

3.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

3.4.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

3.4.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.4. Test Result

Refer to Annex A.3 in this report.



3.5.6 dB Bandwidth

3.5.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.5.1.Test Procedures

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., $RBW = 100\text{ kHz}$, $VBW \geq 3 \times RBW$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq 6\text{ dB}$.

3.5.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.3.Test Result

Refer to Annex A.4 in this report.



3.6. Conducted Spurious Emissions and Band Edge

3.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.6.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.5 and A.6 in this report.



3.7. Power Spectral Density

3.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.7.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW

3.7.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.7.4. Test Result

Refer to Annex A.7 in this report.

3.8. Conducted Emission

3.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.8.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10.

3.8.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.8.4. Test Result

Refer to Annex A.8 in this report.



3.9. Restricted Frequency Bands

3.9.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.9.2. Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.9.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4. Test Result

Refer to Annex A.9 in this report.

3.10. Radiated Emission

3.10.1.Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2:For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.10.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.10.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.10.4.Test Result

Refer to Annex A.10 in this report.




Annex A Test Data and Result

A.1. Duty Cycle of Test Signal


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant1	84.94	0.71	0.47
NVNT	BLE 1M	2440	Ant1	84.95	0.71	0
NVNT	BLE 1M	2480	Ant1	84.95	0.71	0
NVNT	BLE 2M	2402	Ant1	56.84	2.45	0.94
NVNT	BLE 2M	2440	Ant1	56.85	2.45	0.94
NVNT	BLE 2M	2480	Ant1	56.85	2.45	0.94

Test Graphs


Duty Cycle NVNT BLE 1M 2402MHz Ant1




Duty Cycle NVNT BLE 1M 2440MHz Ant1




Duty Cycle NVNT BLE 1M 2480MHz Ant1



Duty Cycle NVNT BLE 2M 2402MHz Ant1



Duty Cycle NVNT BLE 2M 2440MHz Ant1



Duty Cycle NVNT BLE 2M 2480MHz Ant1



**A.2. Maximum Peak Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	8.2	0	8.2	0.00661	30	Pass
NVNT	BLE 1M	2440	Ant1	6.23	0	6.23	0.0042	30	Pass
NVNT	BLE 1M	2480	Ant1	3.56	0	3.56	0.00227	30	Pass
NVNT	BLE 2M	2402	Ant1	8.46	0	8.46	0.00701	30	Pass
NVNT	BLE 2M	2440	Ant1	6.27	0	6.27	0.00424	30	Pass
NVNT	BLE 2M	2480	Ant1	3.8	0	3.8	0.0024	30	Pass

Test Graphs


Peak Power NVNT BLE 1M 2402MHz Ant1



Peak Power NVNT BLE 1M 2440MHz Ant1




Peak Power NVNT BLE 1M 2480MHz Ant1



Peak Power NVNT BLE 2M 2402MHz Ant1



Peak Power NVNT BLE 2M 2440MHz Ant1



Peak Power NVNT BLE 2M 2480MHz Ant1




**A.3. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	7.18	0.71	7.89	0.00615	30	Pass
NVNT	BLE 1M	2440	Ant1	5.22	0.71	5.93	0.00392	30	Pass
NVNT	BLE 1M	2480	Ant1	2.64	0.71	3.35	0.00216	30	Pass
NVNT	BLE 2M	2402	Ant1	5.78	2.45	8.23	0.00665	30	Pass
NVNT	BLE 2M	2440	Ant1	3.59	2.45	6.04	0.00402	30	Pass
NVNT	BLE 2M	2480	Ant1	1.05	2.45	3.5	0.00224	30	Pass



Test Graphs

Average Power NVNT BLE 1M 2402MHz Ant1




Average Power NVNT BLE 1M 2440MHz Ant1





Average Power NVNT BLE 1M 2480MHz Ant1




Average Power NVNT BLE 2M 2402MHz Ant1





Average Power NVNT BLE 2M 2440MHz Ant1



Average Power NVNT BLE 2M 2480MHz Ant1



**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.6939	0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.6501	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.6672	0.5	Pass
NVNT	BLE 2M	2402	Ant1	1.209	0.5	Pass
NVNT	BLE 2M	2440	Ant1	1.267	0.5	Pass
NVNT	BLE 2M	2480	Ant1	1.239	0.5	Pass



Test Graphs

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1




-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2440MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2480MHz Ant1



**A.5. Conducted Spurious Emissions**


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-46.94	-20	Pass
NVNT	BLE 1M	2440	Ant1	-44.58	-20	Pass
NVNT	BLE 1M	2480	Ant1	-42.25	-20	Pass
NVNT	BLE 2M	2402	Ant1	-45.99	-20	Pass
NVNT	BLE 2M	2440	Ant1	-43.31	-20	Pass
NVNT	BLE 2M	2480	Ant1	-41.37	-20	Pass

Test Graphs

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Emission





REPORT No.: SZ25050056W01

A.6. Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-49.16	-20	Pass
NVNT	BLE 1M	2480	Ant1	-58.93	-20	Pass
NVNT	BLE 2M	2402	Ant1	-29.47	-20	Pass
NVNT	BLE 2M	2480	Ant1	-55.53	-20	Pass

Test Graphs

Band Edge NVNT BLE 1M 2402MHz Ant1 Ref




Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref




Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



Band Edge NVNT BLE 2M 2402MHz Ant1 Ref




Band Edge NVNT BLE 2M 2402MHz Ant1 Emission



Band Edge NVNT BLE 2M 2480MHz Ant1 Ref



Band Edge NVNT BLE 2M 2480MHz Ant1 Emission



**A.7. Power Spectral Density**

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant1	-8.08	0	-8.08	8	Pass
NVNT	BLE 1M	2440	Ant1	-10.03	0	-10.03	8	Pass
NVNT	BLE 1M	2480	Ant1	-12.67	0	-12.67	8	Pass
NVNT	BLE 2M	2402	Ant1	-11.22	0	-11.22	8	Pass
NVNT	BLE 2M	2440	Ant1	-13.47	0	-13.47	8	Pass
NVNT	BLE 2M	2480	Ant1	-15.97	0	-15.97	8	Pass

Test Graphs

PSD NVNT BLE 1M 2402MHz Ant1



PSD NVNT BLE 1M 2440MHz Ant1





PSD NVNT BLE 1M 2480MHz Ant1



PSD NVNT BLE 2M 2402MHz Ant1



PSD NVNT BLE 2M 2440MHz Ant1



PSD NVNT BLE 2M 2480MHz Ant1





A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+PC+PC adapter+DC source+Antenna+BLE TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1860	46.89	37.59	64.21	54.21	Line	PASS
2	0.4290	41.30	34.06	57.27	47.27		PASS
3	2.8815	35.81	28.04	56.00	46.00		PASS
4	4.9473	41.88	36.06	56.00	46.00		PASS
5	7.0795	42.22	36.64	60.00	50.00		PASS
6	22.0616	39.70	31.81	60.00	50.00		PASS



(N Phase)


No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1905	46.41	36.31	64.02	54.02	Neutral	PASS
2	2.3998	32.55	26.17	56.00	46.00		PASS
3	2.9083	36.24	28.94	56.00	46.00		PASS
4	4.9196	41.34	35.56	56.00	46.00		PASS
5	7.4538	41.11	34.16	60.00	50.00		PASS
6	22.1113	39.20	31.13	60.00	50.00		PASS

A.9. Restricted Frequency Bands

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition was recorded in this test report.

1Mbps


Plot for Channel 0



Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
2356.27	8.6	46.02	37.460	54.00	7.98	128	AV	Horizontal	PASS
2356.33	21.5	59.00	37.460	74.00	15.00	246	PK	Horizontal	PASS
2379.64	21.0	58.47	37.480	74.00	15.53	1	PK	Horizontal	PASS
2380.32	8.6	46.03	37.480	54.00	7.97	109	AV	Horizontal	PASS
2389.29	8.4	45.93	37.490	54.00	8.07	217	AV	Horizontal	PASS
2389.53	21.6	59.12	37.490	74.00	14.88	114	PK	Horizontal	PASS



Plot for Channel 39




Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
2485.26	8.3	46.52	38.270	54.00	7.48	116	AV	Horizontal	PASS
2485.47	20.6	58.88	38.270	74.00	15.12	73	PK	Horizontal	PASS
2488.31	8.2	46.48	38.270	54.00	7.52	35	AV	Horizontal	PASS
2488.67	20.3	58.61	38.270	74.00	15.39	164	PK	Horizontal	PASS
2491.07	8.3	46.58	38.270	54.00	7.42	193	AV	Horizontal	PASS
2491.57	20.6	58.90	38.260	74.00	15.10	126	PK	Horizontal	PASS



2Mbps


Plot for Channel 0



Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
2357.49	21.4	58.84	37.460	74.00	15.16	112	PK	Horizontal	PASS
2357.98	8.5	46.00	37.460	54.00	8.00	219	AV	Horizontal	PASS
2375.19	20.8	58.28	37.480	74.00	15.72	112	PK	Horizontal	PASS
2376.41	8.6	46.09	37.480	54.00	7.91	261	AV	Horizontal	PASS
2385.69	21.5	59.01	37.490	74.00	14.99	229	PK	Horizontal	PASS
2386.05	8.5	46.01	37.490	54.00	7.99	121	AV	Horizontal	PASS



Plot for Channel 39



Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
2484.42	8.3	46.52	38.270	54.00	7.48	19	AV	Horizontal	PASS
2484.66	20.6	58.90	38.270	74.00	15.10	84	PK	Horizontal	PASS
2486.79	8.2	46.44	38.270	54.00	7.56	196	AV	Horizontal	PASS
2486.99	20.6	58.88	38.270	74.00	15.12	121	PK	Horizontal	PASS
2489.84	8.3	46.56	38.260	54.00	7.44	159	AV	Horizontal	PASS
2490.20	20.6	58.84	38.270	74.00	15.16	215	PK	Horizontal	PASS



A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note 4: All test modes were considered and evaluated respectively by performing full test, only the worst data were recorded.


1Mbps

Plot for Channel 0




(Antenna Horizontal, 30MHz to 1GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
31.31	63.3	32.66	-30.640	40.00	7.34	173	PK	Horizontal	PASS
62.06	60.0	31.40	-28.560	40.00	8.60	2	PK	Horizontal	PASS
109.06	63.8	35.12	-28.660	43.50	8.38	51	PK	Horizontal	PASS
201.17	59.7	30.77	-28.920	43.50	12.73	147	PK	Horizontal	PASS
316.21	53.7	28.16	-25.510	46.00	17.84	0	PK	Horizontal	PASS
668.15	43.2	26.93	-16.250	46.00	19.07	18	PK	Horizontal	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
1595.32	32.3	31.90	-0.430	54.00	22.10	351	AV	Horizontal	PASS
1595.72	45.6	45.20	-0.420	74.00	28.80	323	PK	Horizontal	PASS
2468.69	39.6	45.56	5.930	74.00	28.44	351	PK	Horizontal	PASS
4803.91	48.0	42.87	-5.150	74.00	31.13	106	PK	Horizontal	PASS
4804.34	41.6	36.49	-5.140	54.00	17.51	106	AV	Horizontal	PASS
7205.69	40.9	45.97	5.030	54.00	8.03	106	AV	Horizontal	PASS
7206.98	46.7	51.67	5.020	74.00	22.33	90	PK	Horizontal	PASS
11105.37	30.6	44.67	14.040	54.00	9.33	131	AV	Horizontal	PASS
11110.52	39.7	53.71	14.020	74.00	20.29	309	PK	Horizontal	PASS
14685.33	35.9	56.45	20.570	74.00	17.55	146	PK	Horizontal	PASS
14705.91	27.3	47.80	20.550	54.00	6.20	240	AV	Horizontal	PASS



(Antenna Vertical, 30MHz to 1GHz)


Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
30.44	62.7	31.95	-30.780	40.00	8.05	242	PK	Vertical	PASS
65.84	62.2	31.92	-30.310	40.00	8.08	269	PK	Vertical	PASS
116.63	66.5	36.22	-30.270	43.50	7.28	91	PK	Vertical	PASS
149.27	63.0	31.33	-31.690	43.50	12.17	145	PK	Vertical	PASS
242.49	54.4	26.72	-27.650	46.00	19.28	229	PK	Vertical	PASS
672.08	53.8	37.63	-16.200	46.00	8.37	63	PK	Vertical	PASS



(Antenna Vertical, 1GHz to 18GHz)


Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
1597.32	50.3	49.90	-0.410	74.00	24.10	169	PK	Vertical	PASS
1597.72	35.3	34.94	-0.400	54.00	19.06	169	AV	Vertical	PASS
2472.69	28.3	34.24	5.910	54.00	19.76	186	AV	Vertical	PASS
2474.29	40.6	46.46	5.900	74.00	27.54	351	PK	Vertical	PASS
4791.91	50.5	45.25	-5.250	74.00	28.75	348	PK	Vertical	PASS
4804.77	40.7	35.55	-5.140	54.00	18.45	320	AV	Vertical	PASS
5999.66	48.6	48.41	-0.160	74.00	25.59	358	PK	Vertical	PASS
6000.09	44.3	44.09	-0.160	54.00	9.91	358	AV	Vertical	PASS
7205.26	48.4	53.40	5.040	74.00	20.60	118	PK	Vertical	PASS
7206.98	43.3	48.29	5.020	54.00	5.71	64	AV	Vertical	PASS
14762.05	27.4	47.47	20.060	54.00	6.53	158	AV	Vertical	PASS
14837.48	37.5	56.84	19.350	74.00	17.16	308	PK	Vertical	PASS

Plot for Channel 19




(Antenna Horizontal, 30MHz to 1GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
30.78	62.6	31.84	-30.730	40.00	8.16	168	PK	Horizontal	PASS
62.59	61.4	32.55	-28.820	40.00	7.45	5	PK	Horizontal	PASS
133.07	68.2	36.30	-31.850	43.50	7.20	65	PK	Horizontal	PASS
200.78	57.3	28.43	-28.870	43.50	15.07	202	PK	Horizontal	PASS
308.69	53.0	27.64	-25.350	46.00	18.36	127	PK	Horizontal	PASS
648.02	49.8	33.01	-16.810	46.00	12.99	120	PK	Horizontal	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
1596.12	47.1	46.64	-0.420	74.00	27.36	351	PK	Horizontal	PASS
1597.32	34.1	33.64	-0.410	54.00	20.36	351	AV	Horizontal	PASS
2439.89	41.7	47.55	5.820	-	-	120	PK	Horizontal	NA
2440.29	38.7	44.56	5.820	-	-	114	AV	Horizontal	NA
4879.77	49.2	44.16	-5.000	74.00	29.84	118	PK	Horizontal	PASS
4880.20	44.5	39.49	-5.000	54.00	14.51	104	AV	Horizontal	PASS
7319.69	41.8	46.10	4.270	54.00	7.90	90	AV	Horizontal	PASS
7320.12	46.0	50.24	4.270	74.00	23.76	90	PK	Horizontal	PASS
11125.95	40.2	54.07	13.920	74.00	19.93	265	PK	Horizontal	PASS
11144.80	30.5	44.32	13.820	54.00	9.68	198	AV	Horizontal	PASS
14686.19	26.7	47.26	20.560	54.00	6.74	225	AV	Horizontal	PASS
14690.05	35.9	56.43	20.570	74.00	17.57	250	PK	Horizontal	PASS



(Antenna Vertical, 30MHz to 1GHz)


Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
30.87	60.9	30.19	-30.720	40.00	9.81	140	PK	Vertical	PASS
65.94	61.2	30.77	-30.430	40.00	9.23	338	PK	Vertical	PASS
117.69	67.4	36.81	-30.620	43.50	6.69	338	PK	Vertical	PASS
238.90	53.0	25.12	-27.880	46.00	20.88	318	PK	Vertical	PASS
421.22	48.5	26.09	-22.420	46.00	19.91	120	PK	Vertical	PASS
664.22	53.7	37.52	-16.150	46.00	8.48	112	PK	Vertical	PASS



(Antenna Vertical, 1GHz to 18GHz)


Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
1597.72	48.1	47.65	-0.400	74.00	26.35	58	PK	Vertical	PASS
1598.12	34.5	34.07	-0.400	54.00	19.93	58	AV	Vertical	PASS
2440.29	30.3	36.10	5.820	-	-	26	AV	Vertical	NA
2462.29	40.1	46.05	5.940	74.00	27.95	307	PK	Vertical	PASS
5999.66	47.9	47.70	-0.160	74.00	26.30	350	PK	Vertical	PASS
6000.51	44.5	44.33	-0.150	54.00	9.67	64	AV	Vertical	PASS
7319.69	42.3	46.56	4.270	54.00	7.44	104	AV	Vertical	PASS
7319.69	47.6	51.83	4.270	74.00	22.17	117	PK	Vertical	PASS
10555.50	41.4	53.41	12.060	74.00	20.59	267	PK	Vertical	PASS
10627.50	31.5	43.65	12.190	54.00	10.35	104	AV	Vertical	PASS
14321.04	37.3	56.76	19.430	74.00	17.24	117	PK	Vertical	PASS
14685.76	26.9	47.49	20.560	54.00	6.51	157	AV	Vertical	PASS

Plot for Channel 39




(Antenna Horizontal, 30MHz to 1GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
30.34	64.2	33.44	-30.790	40.00	6.56	104	PK	Horizontal	PASS
62.06	60.6	31.99	-28.560	40.00	8.01	0	PK	Horizontal	PASS
113.67	64.9	35.45	-29.460	43.50	8.05	193	PK	Horizontal	PASS
200.39	59.8	30.97	-28.830	43.50	12.53	1	PK	Horizontal	PASS
305.01	52.9	27.83	-25.090	46.00	18.17	118	PK	Horizontal	PASS
664.22	46.3	30.13	-16.150	46.00	15.87	36	PK	Horizontal	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
1593.72	46.3	45.82	-0.440	74.00	28.18	136	PK	Horizontal	PASS
1594.52	30.2	29.72	-0.440	54.00	24.28	351	AV	Horizontal	PASS
2471.49	28.6	34.47	5.910	54.00	19.53	98	AV	Horizontal	PASS
2473.89	39.5	45.43	5.900	74.00	28.57	279	PK	Horizontal	PASS
4960.34	40.2	35.63	-4.610	54.00	18.37	88	AV	Horizontal	PASS
4960.34	46.9	42.27	-4.610	74.00	31.73	104	PK	Horizontal	PASS
7439.27	46.8	51.42	4.630	74.00	22.58	117	PK	Horizontal	PASS
7439.70	39.3	43.97	4.630	54.00	10.03	117	AV	Horizontal	PASS
10104.63	31.9	42.57	10.720	54.00	11.43	211	AV	Horizontal	PASS
10193.78	41.6	52.56	10.950	74.00	21.44	76	PK	Horizontal	PASS
14687.05	27.4	47.99	20.570	54.00	6.01	211	AV	Horizontal	PASS
14689.62	35.9	56.43	20.570	74.00	17.57	211	PK	Horizontal	PASS



(Antenna Vertical, 30MHz to 1GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
56.43	59.3	31.27	-28.010	40.00	8.73	90	PK	Vertical	PASS
61.82	61.7	33.08	-28.580	40.00	6.92	347	PK	Vertical	PASS
114.93	63.9	33.74	-30.170	43.50	9.76	124	PK	Vertical	PASS
201.17	54.7	25.76	-28.920	43.50	17.74	84	PK	Vertical	PASS
300.35	55.5	30.02	-25.430	46.00	15.98	253	PK	Vertical	PASS
670.14	55.0	38.71	-16.310	46.00	7.29	84	PK	Vertical	PASS



(Antenna Vertical, 1GHz to 18GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
1595.72	48.7	48.25	-0.420	74.00	25.75	351	PK	Vertical	PASS
1599.32	33.6	33.24	-0.390	54.00	20.76	54	AV	Vertical	PASS
3198.86	52.9	42.01	-10.840	74.00	31.99	64	PK	Vertical	PASS
3200.58	45.2	34.30	-10.860	54.00	19.70	50	AV	Vertical	PASS
4779.91	38.7	33.37	-5.340	54.00	20.63	158	AV	Vertical	PASS
4793.19	49.2	43.93	-5.230	74.00	30.07	37	PK	Vertical	PASS
5999.66	49.0	48.85	-0.160	74.00	25.15	356	PK	Vertical	PASS
6000.09	45.3	45.12	-0.160	54.00	8.88	344	AV	Vertical	PASS
7439.70	42.6	47.20	4.630	54.00	6.80	117	AV	Vertical	PASS
7440.13	47.6	52.24	4.630	74.00	21.76	210	PK	Vertical	PASS
14681.91	26.9	47.42	20.550	54.00	6.58	238	AV	Vertical	PASS
14687.91	36.8	57.38	20.570	74.00	16.62	290	PK	Vertical	PASS

————— END OF REPORT —————