



**BUREAU  
VERITAS**

Test Report No.: RF190813W001



# FCC TEST REPORT

## (Part 15, Subpart C)

|            |                                                                           |
|------------|---------------------------------------------------------------------------|
| Applicant: | Fibocom Wireless Inc.                                                     |
| Address:   | 5/F, Tower A, Technology Building II, 1057 Nanhai Avenue, Shenzhen, China |

|                           |                                                                           |
|---------------------------|---------------------------------------------------------------------------|
| Manufacturer or Supplier: | Fibocom Wireless Inc.                                                     |
| Address:                  | 5/F, Tower A, Technology Building II, 1057 Nanhai Avenue, Shenzhen, China |
| Product:                  | BT Module                                                                 |
| Brand Name:               | Fibocom                                                                   |
| Model Name:               | B830-GL                                                                   |
| FCC ID:                   | ZMOB830GL                                                                 |
| Date of tests:            | Aug 14, 2019 ~ Sep 03, 2019                                               |

The tests have been carried out according to the requirements of the following standard:

- ☒ **FCC Part 15, Subpart C, Section 15.247**
- ☒ **ANSI C63.10-2013**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

|                                                                                                             |                                                                                                              |
|-------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Prepared by Alex Chen<br>Engineer / Mobile Department                                                       | Approved by Luke Lu<br>Manager / Mobile Department                                                           |
| <br>Date: Sept. 04, 2019 | <br>Date: Sept. 04, 2019 |

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



## TABLE OF CONTENTS

|                                                              |           |
|--------------------------------------------------------------|-----------|
| <b>RELEASE CONTROL RECORD .....</b>                          | <b>4</b>  |
| <b>1 SUMMARY OF TEST RESULTS.....</b>                        | <b>5</b>  |
| 1.1 MEASUREMENT UNCERTAINTY .....                            | 5         |
| <b>2 GENERAL INFORMATION .....</b>                           | <b>6</b>  |
| 2.1 GENERAL DESCRIPTION OF EUT .....                         | 6         |
| 2.2 DESCRIPTION OF TEST MODES .....                          | 7         |
| 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST .....               | 8         |
| 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... | 8         |
| 2.3 DUTY CYCLE OF TEST SIGNAL .....                          | 11        |
| 2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS .....           | 12        |
| 2.5 DESCRIPTION OF SUPPORT UNITS .....                       | 12        |
| 2.6 ANTENNA REQUIREMENT .....                                | 13        |
| CONCLUSION:.....                                             | 13        |
| <b>3 TEST TYPES AND RESULTS.....</b>                         | <b>14</b> |
| 3.1 RADIATED EMISSION MEASUREMENT .....                      | 14        |
| 3.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....          | 14        |
| 3.1.2 TEST INSTRUMENTS.....                                  | 15        |
| 3.1.3 TEST PROCEDURES .....                                  | 16        |
| 3.1.4 DEVIATION FROM TEST STANDARD .....                     | 16        |
| 3.1.5 TEST SETUP .....                                       | 17        |
| 3.1.6 EUT OPERATING CONDITIONS .....                         | 18        |
| 3.1.7 TEST RESULTS .....                                     | 19        |
| 3.2 6 DB BANDWIDTH MEASUREMENT .....                         | 33        |
| 3.2.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT .....              | 33        |
| 3.2.2 TEST INSTRUMENTS.....                                  | 33        |
| 3.2.3 TEST PROCEDURE.....                                    | 33        |
| 3.2.4 DEVIATION FROM TEST STANDARD .....                     | 33        |
| 3.2.5 TEST SETUP .....                                       | 34        |
| 3.2.6 EUT OPERATING CONDITIONS .....                         | 34        |
| 3.2.7 TEST RESULTS .....                                     | 35        |
| 3.3 CONDUCTED OUTPUT POWER.....                              | 39        |
| 3.3.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT .....     | 39        |
| 3.3.2 TEST SETUP .....                                       | 39        |
| 3.3.3 TEST INSTRUMENTS.....                                  | 39        |



**BUREAU  
VERITAS**

**Test Report No.: RF190813W001**

|         |                                                                                             |    |
|---------|---------------------------------------------------------------------------------------------|----|
| 3.3.4   | TEST PROCEDURES .....                                                                       | 39 |
| 3.3.5   | DEVIATION FROM TEST STANDARD .....                                                          | 39 |
| 3.3.6   | EUT OPERATING CONDITIONS .....                                                              | 39 |
| 3.3.7   | TEST RESULTS .....                                                                          | 40 |
| 3.3.7.1 | MAXIMUM PEAK OUTPUT POWER .....                                                             | 40 |
| 3.4     | POWER SPECTRAL DENSITY MEASUREMENT .....                                                    | 41 |
| 3.4.1   | LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....                                          | 41 |
| 3.4.2   | TEST SETUP .....                                                                            | 41 |
| 3.4.3   | TEST INSTRUMENTS .....                                                                      | 41 |
| 3.4.4   | TEST PROCEDURE .....                                                                        | 41 |
| 3.4.5   | DEVIATION FROM TEST STANDARD .....                                                          | 41 |
| 3.4.6   | EUT OPERATING CONDITION .....                                                               | 41 |
| 3.4.7   | TEST RESULTS .....                                                                          | 42 |
| 3.5     | OUT OF BAND EMISSION MEASUREMENT .....                                                      | 46 |
| 3.5.1   | LIMITS OF OUT OF BAND EMISSION MEASUREMENT .....                                            | 46 |
| 3.5.2   | TEST SETUP .....                                                                            | 46 |
| 3.5.3   | TEST INSTRUMENTS .....                                                                      | 46 |
| 3.5.4   | TEST PROCEDURE .....                                                                        | 46 |
| 3.5.5   | DEVIATION FROM TEST STANDARD .....                                                          | 47 |
| 3.5.6   | EUT OPERATING CONDITION .....                                                               | 47 |
| 3.5.7   | TEST RESULTS .....                                                                          | 47 |
| 4       | PHOTOGRAPHS OF THE TEST CONFIGURATION .....                                                 | 56 |
| 5       | APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT<br>BY THE LAB ..... | 57 |



Test Report No.: RF190813W001

## RELEASE CONTROL RECORD

| ISSUE NO.    | REASON FOR CHANGE | DATE ISSUED    |
|--------------|-------------------|----------------|
| RF190813W001 | Original release  | Sept. 04, 2019 |



## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247) |                                  |            |
|-----------------------------------------------------------|----------------------------------|------------|
| STANDARD SECTION                                          | TEST TYPE AND LIMIT              | RESULT     |
| 15.205<br>15.209                                          | Radiated Emissions               | Compliance |
| 15.247(d)                                                 | Out of band Emission Measurement | Compliance |
| 15.247(a)(2)                                              | 6dB bandwidth                    | Compliance |
| 15.247(b)                                                 | Conducted Output power           | Compliance |
| 15.247(e)                                                 | Power Spectral Density           | Compliance |
| 15.203                                                    | Antenna Requirement              | Compliance |

### 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| MEASUREMENT                         | UNCERTAINTY |
|-------------------------------------|-------------|
| Radiated emissions (30MHz~1GMHz)    | ±4.98dB     |
| Radiated emissions (1GMHz ~6GMHz)   | ±4.70dB     |
| Radiated emissions (6GMHz ~18GMHz)  | ±4.60dB     |
| Radiated emissions (18GMHz ~40GMHz) | ±4.12dB     |
| Conducted emissions                 | ±4.01dB     |
| Occupied Channel Bandwidth          | ±43.58KHz   |
| Conducted Output power              | ±2.06dB     |
| Power Spectral Density              | ±0.85 dB    |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .



## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                            |                                              |
|----------------------------|----------------------------------------------|
| <b>PRODUCT</b>             | BT Module                                    |
| <b>BRAND NAME</b>          | Fibocom                                      |
| <b>MODEL NAME</b>          | B830-GL                                      |
| <b>NOMINAL VOLTAGE</b>     | DC 3.3V                                      |
| <b>MODULATION</b>          | GFSK                                         |
| <b>TRANSMISSION RATE</b>   | BT_LE 5.0: 1 Mbps/2 Mbps/0.125 Mbps/0.5 Mbps |
| <b>OPERATING FREQUENCY</b> | 2402-2480MHz for BT-LE                       |
| <b>MAX. OUTPUT POWER</b>   | BT-LE : 6.546mW (Maximum)                    |
| <b>ANTENNA TYPE</b>        | BT-LE : External Antenna with -2dBi gain     |
| <b>HW VERSION</b>          | V1.0.3                                       |
| <b>SW VERSION</b>          | B830-GL-02-TA-V1.0.0                         |
| <b>I/O PORTS</b>           | Refer to user's manual                       |

**NOTE:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

| <b>MODULATION MODE</b>  | <b>TX/RX FUNCTION</b> |
|-------------------------|-----------------------|
| <b>BT-LE CODED(S=2)</b> | 1TX /1RX              |
| <b>BT-LE CODED(S=8)</b> | 1TX /1RX              |
| <b>BT-LE(1M)</b>        | 1TX /1RX              |
| <b>BT-LE(2M)</b>        | 1TX /1RX              |

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



## 2.2 DESCRIPTION OF TEST MODES

40 channels are provided for BT-LE (GFSK):

| CHANNEL | FREQ.<br>(MHZ) | CHANNEL | FREQ.<br>(MHZ) | CHANNEL | FREQ.<br>(MHZ) | CHANNEL | FREQ.<br>(MHZ) |
|---------|----------------|---------|----------------|---------|----------------|---------|----------------|
| 0       | 2402           | 10      | 2422           | 20      | 2442           | 30      | 2462           |
| 1       | 2404           | 11      | 2424           | 21      | 2444           | 31      | 2464           |
| 2       | 2406           | 12      | 2426           | 22      | 2446           | 32      | 2466           |
| 3       | 2408           | 13      | 2428           | 23      | 2448           | 33      | 2468           |
| 4       | 2410           | 14      | 2430           | 24      | 2450           | 34      | 2470           |
| 5       | 2412           | 15      | 2432           | 25      | 2452           | 35      | 2472           |
| 6       | 2414           | 16      | 2434           | 26      | 2454           | 36      | 2474           |
| 7       | 2416           | 17      | 2436           | 27      | 2456           | 37      | 2476           |
| 8       | 2418           | 18      | 2438           | 28      | 2458           | 38      | 2478           |
| 9       | 2420           | 19      | 2440           | 29      | 2460           | 39      | 2480           |



## 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

## 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

| EUT<br>CONFIGURE<br>MODE | APPLICABLE TO |       |     |      | MODE |
|--------------------------|---------------|-------|-----|------|------|
|                          | RE<1G         | RE≥1G | PLC | APCM |      |
| -                        | √             | √     | -   | √    | -    |

Where **RE<1G**: Radiated Emission below 1GHz

**RE≥1G**: Radiated Emission above 1GHz

**PLC**: Power Line Conducted Emission

**APCM**: Antenna Port Conducted Measurement

**NOTE**: No need to concern of Conducted Emission due to the EUT is powered by battery.

## RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE      | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION | DATA<br>RATE<br>(Mbps) |
|-----------|----------------------|-------------------|------------|------------------------|
| BT-LE(2M) | 0 to 39              | 39                | GFSK       | 2                      |

**RADIATED EMISSION TEST (ABOVE 1GHz):**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE             | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION | DATA RATE (Mbps) |
|------------------|-------------------|----------------|------------|------------------|
| BT-LE CODED(S=2) | 0 to 39           | 0,19, 39       | GFSK       | 0.125            |
| BT-LE CODED(S=8) | 0 to 39           | 0,19, 39       | GFSK       | 0.5              |
| BT-LE(1M)        | 0 to 39           | 0,19, 39       | GFSK       | 1                |
| BT-LE(2M)        | 0 to 39           | 0,19, 39       | GFSK       | 2                |

**BANDEDGE MEASUREMENT:**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE             | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION | DATA RATE (Mbps) |
|------------------|-------------------|----------------|------------|------------------|
| BT-LE CODED(S=2) | 0 to 39           | 0,19, 39       | GFSK       | 0.125            |
| BT-LE CODED(S=8) | 0 to 39           | 0,19, 39       | GFSK       | 0.5              |
| BT-LE(1M)        | 0 to 39           | 0,19, 39       | GFSK       | 1                |
| BT-LE(2M)        | 0 to 39           | 0,19, 39       | GFSK       | 2                |

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE             | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION | DATA RATE (Mbps) |
|------------------|-------------------|----------------|------------|------------------|
| BT-LE CODED(S=2) | 0 to 39           | 0,19, 39       | GFSK       | 0.125            |
| BT-LE CODED(S=8) | 0 to 39           | 0,19, 39       | GFSK       | 0.5              |
| BT-LE(1M)        | 0 to 39           | 0,19, 39       | GFSK       | 1                |
| BT-LE(2M)        | 0 to 39           | 0,19, 39       | GFSK       | 2                |

**TEST CONDITION:**

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | TEST VOLTAGE         | TESTED BY |
|---------------|--------------------------|----------------------|-----------|
| RE<1G         | 23deg. C, 70%RH          | DC 3.3V from battery | Tony      |
| RE≥1G         | 23deg. C, 70%RH          | DC 3.3V from battery | Tony      |
| APCM          | 25deg. C, 60%RH          | DC 3.3V from battery | Big Wang  |



BUREAU  
VERITAS

Test Report No.: RF190813W001


## 2.3 Duty Cycle of Test Signal

**BT-LE CODED(S=2):** Duty cycle =  $1.072/1.876 = 0.571 < 98\%$ , Duty factor =  $10 * \log(1/0.571) = 2.430$

**BT-LE CODED(S=8):** Duty cycle =  $3.096/3.759 = 0.824 < 98\%$ , Duty factor =  $10 * \log(1/0.824) = 0.843$

**BT-LE (1M):** Duty cycle =  $385/627 = 0.614 < 98\%$ , Duty factor =  $10 * \log(1/0.614) = 2.118$

**BT-LE (2M):** Duty cycle =  $201/637 = 0.316 < 98\%$ , Duty factor =  $10 * \log(1/0.316) = 5.009$





## 2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C, Section 15.247**

**558074 D01 15.247 Meas Guidance v05r02**

**ANSI C63.10-2013**

Note:

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (sDOC). The test report has been issued separately.

## 2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT   | BRAND    | MODEL NO. | SERIAL NO. | FCC ID |
|-----|-----------|----------|-----------|------------|--------|
| 1   | DC source | LONG WEI | PS-6403D  | 010934269  | N/A    |
| 2   | PC        | HP       | A6608CN   | 3CR83825X3 | N/A    |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|-----------------------------------------------------|
| 1   | DC Line: Unshielded, Detachable 1.0m                |
| 2   | AC Line: Unshielded, Detachable 1.5m                |



## 2.6 ANTENNA REQUIREMENT

Per FCC Part 15.203. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### Conclusion:

The EUT use one External antenna that was permanently attached and the detail information list as below:

| ANT Gain | Type             | TX/RX   | Frequency range |
|----------|------------------|---------|-----------------|
| -2       | External Antenna | TX & RX | 2400~2483.5GHz  |



### 3 TEST TYPES AND RESULTS

#### 3.1 RADIATED EMISSION MEASUREMENT

##### 3.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

| FREQUENCIES<br>(MHz) | FIELD STRENGTH<br>(microvolts/meter) | MEASUREMENT DISTANCE<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009 ~ 0.490        | 2400/F(kHz)                          | 300                              |
| 0.490 ~ 1.705        | 24000/F(kHz)                         | 30                               |
| 1.705 ~ 30.0         | 30                                   | 30                               |
| 30 ~ 88              | 100                                  | 3                                |
| 88 ~ 216             | 150                                  | 3                                |
| 216 ~ 960            | 200                                  | 3                                |
| Above 960            | 500                                  | 3                                |

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



### 3.1.2 TEST INSTRUMENTS

| Equipment                  | Manufacturer | Model No.                   | Serial No.                  | Last Cal.   | Next Cal.   |
|----------------------------|--------------|-----------------------------|-----------------------------|-------------|-------------|
| 3m Semi-anechoic Chamber   | ETS-LINDGREN | 9m*6m*6m                    | Euroshieldpn-CT0001143-1216 | Feb. 26,19  | Feb. 25,20  |
| Bilog Antenna              | ETS-LINDGREN | 3143B                       | 00161965                    | Feb. 26,19  | Feb. 25,20  |
| Horn Antenna               | ETS-LINDGREN | 3117                        | 00168728                    | Feb. 26,19  | Feb. 25,20  |
| Horn Antenna (18GHz-40GHz) | N/A          | QWH-SL-18-40-K-SG/QMS-00361 | 15433                       | Nov. 21, 18 | Nov. 20, 19 |
| Test Software              | E3           | V 9.160323                  | N/A                         | N/A         | N/A         |
| Test Software              | ADT          | ADT_Radiated_V7.6.15.9.2    | N/A                         | N/A         | N/A         |
| 10dB Attenuator            | JFW/USA      | 50HF-010-SMA                | 1505                        | Jun. 24,19  | Jun. 23,20  |
| MXE EMI Receiver           | KEYSIGHT     | N9038A-544                  | MY54450026                  | Feb. 26,19  | Feb. 25,20  |
| Signal Pre-Amplifier       | EMSI         | EMC 9135                    | 980249                      | Jun. 24,19  | Jun. 23,20  |
| Signal Pre-Amplifier       | EMSI         | EMC 012645B                 | 980257                      | Jun. 24,19  | Jun. 23,20  |
| Signal Pre-Amplifier       | EMSI         | EMC 184045B                 | 980259                      | Jun. 24,19  | Jun. 23,20  |

**NOTE:** 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in 3m Chamber.

3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



### 3.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

**Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.


### 3.1.4 DEVIATION FROM TEST STANDARD

No deviation




### 3.1.5 TEST SETUP

#### < Frequency Range 30MHz~1GHz >



#### <Frequency Range above 1GHz>



**Note:** Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).



**Test Report No.: RF190813W001**

### 3.1.6 EUT OPERATING CONDITIONS

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.



### 3.1.7 TEST RESULTS

#### BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:


BT LE (2M)

|                 |               |                   |                 |
|-----------------|---------------|-------------------|-----------------|
| CHANNEL         | TX Channel 39 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz  |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |               |                        |                 |                    |                     |                      |             |
|-----------------------------------------------------|-------------------------|-------------------|----------------|---------------|------------------------|-----------------|--------------------|---------------------|----------------------|-------------|
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB)   | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK      |
| 62.98                                               | 27.05                   | 56.23             | 40             | -12.95        | 7.04                   | 1.11            | 37.33              | 200                 | 360                  | Peak        |
| <b>75.59</b>                                        | <b>27.55</b>            | <b>55.7</b>       | <b>40</b>      | <b>-12.45</b> | <b>7.99</b>            | <b>1.2</b>      | <b>37.34</b>       | <b>200</b>          | <b>360</b>           | <b>Peak</b> |
| 88.2                                                | 27.8                    | 55.25             | 43.5           | -15.7         | 8.55                   | 1.27            | 37.27              | 200                 | 360                  | Peak        |
| 113.42                                              | 24.24                   | 50.89             | 43.5           | -19.26        | 9.06                   | 1.4             | 37.11              | 200                 | 360                  | Peak        |
| 189.08                                              | 25.4                    | 49.68             | 43.5           | -18.1         | 10.58                  | 1.74            | 36.6               | 200                 | 360                  | Peak        |
| 226.91                                              | 24.78                   | 47.37             | 46             | -21.22        | 12.09                  | 1.92            | 36.6               | 200                 | 360                  | Peak        |

#### REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.





**BUREAU  
VERITAS**


Test Report No.: RF190813W001

|                 |               |                   |                 |
|-----------------|---------------|-------------------|-----------------|
| CHANNEL         | TX Channel 39 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz  |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |        |
|---------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|--------|
| FREQ.<br>(MHz)                                    | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK |
| 113.42                                            | 26.62                         | 53.44                   | 43.5              | -16.88         | 8.89                         | 1.4                   | 37.11                    | 100                       | 360                        | Peak   |
| 226.91                                            | 30.69                         | 53.39                   | 46                | -15.31         | 11.98                        | 1.92                  | 36.6                     | 100                       | 360                        | Peak   |
| 301.6                                             | 30.93                         | 51.31                   | 46                | -15.07         | 14.15                        | 2.22                  | 36.75                    | 100                       | 360                        | Peak   |
| 450.98                                            | 29.76                         | 46.01                   | 46                | -16.24         | 17.86                        | 2.81                  | 36.92                    | 100                       | 360                        | Peak   |
| 515.97                                            | 28.01                         | 43.29                   | 46                | -17.99         | 18.76                        | 3.02                  | 37.06                    | 100                       | 360                        | Peak   |
| 728.4                                             | 30.59                         | 41.43                   | 46                | -15.41         | 23.11                        | 3.63                  | 37.58                    | 100                       | 360                        | Peak   |

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.





**BUREAU  
VERITAS**

**Test Report No.: RF190813W001**

# **ABOVE 1GHz WORST-CASE DATA:**

**Note:** For higher frequency, the emission is too low to be detected.

## **BT\_LE CODED S2**

|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 0 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 59.8                          | 63.26                   | 74                | -14.2          | 33.1                         | 4.88                  | 41.44                    | 186                       | 66                         | Peak    |
| 2390                                                | 45.48                         | 48.94                   | 54                | -8.52          | 33.1                         | 4.88                  | 41.44                    | 186                       | 66                         | Average |
| 2402                                                | 107.07                        | 110.5                   |                   |                | 33.12                        | 4.89                  | 41.44                    | 186                       | 66                         | Peak    |
| 2402                                                | 101.77                        | 105.2                   |                   |                | 33.12                        | 4.89                  | 41.44                    | 186                       | 66                         | Average |
| 2483.5                                              | 57.23                         | 60.44                   | 74                | -16.77         | 33.27                        | 4.98                  | 41.46                    | 186                       | 66                         | Peak    |
| 2483.5                                              | 44.68                         | 47.89                   | 54                | -9.32          | 33.27                        | 4.98                  | 41.46                    | 186                       | 66                         | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 62.26                         | 66.61                   | 74                | -11.74         | 32.21                        | 4.88                  | 41.44                    | 155                       | 110                        | Peak    |
| 2390                                                | 44.31                         | 48.66                   | 54                | -9.69          | 32.21                        | 4.88                  | 41.44                    | 155                       | 110                        | Average |
| 2402                                                | 111.64                        | 115.94                  |                   |                | 32.25                        | 4.89                  | 41.44                    | 155                       | 110                        | Peak    |
| 2402                                                | 101.1                         | 105.4                   |                   |                | 32.25                        | 4.89                  | 41.44                    | 155                       | 110                        | Average |
| 2483.5                                              | 57.38                         | 61.4                    | 74                | -16.62         | 32.46                        | 4.98                  | 41.46                    | 155                       | 110                        | Peak    |
| 2483.5                                              | 43.69                         | 47.71                   | 74                | -30.31         | 32.46                        | 4.98                  | 41.46                    | 155                       | 110                        | Peak    |

## **REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF190813W001

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 19 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 63.11                         | 66.57                   | 74                | -10.89         | 33.1                         | 4.88                  | 41.44                    | 160                       | 200                        | Peak    |
| 2390                                                | 45.69                         | 49.15                   | 54                | -8.31          | 33.1                         | 4.88                  | 41.44                    | 160                       | 200                        | Average |
| 2440                                                | 106.4                         | 109.72                  |                   |                | 33.19                        | 4.94                  | 41.45                    | 160                       | 200                        | Peak    |
| 2440                                                | 100.88                        | 104.2                   |                   |                | 33.19                        | 4.94                  | 41.45                    | 160                       | 200                        | Average |
| 2483.5                                              | 57.42                         | 60.63                   | 74                | -16.58         | 33.27                        | 4.98                  | 41.46                    | 160                       | 200                        | Peak    |
| 2483.5                                              | 44.74                         | 47.95                   | 54                | -9.26          | 33.27                        | 4.98                  | 41.46                    | 160                       | 200                        | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 56.72                         | 61.07                   | 74                | -17.28         | 32.21                        | 4.88                  | 41.44                    | 150                       | 105                        | Peak    |
| 2390                                                | 43.24                         | 47.59                   | 54                | -10.76         | 32.21                        | 4.88                  | 41.44                    | 150                       | 105                        | Average |
| 2440                                                | 109.09                        | 113.26                  |                   |                | 32.34                        | 4.94                  | 41.45                    | 150                       | 105                        | Peak    |
| 2440                                                | 100.33                        | 104.5                   |                   |                | 32.34                        | 4.94                  | 41.45                    | 150                       | 105                        | Average |
| 2483.5                                              | 57.25                         | 61.27                   | 74                | -16.75         | 32.46                        | 4.98                  | 41.46                    | 150                       | 105                        | Peak    |
| 2483.5                                              | 43.75                         | 47.77                   | 54                | -10.25         | 32.46                        | 4.98                  | 41.46                    | 150                       | 105                        | Average |

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF190813W001

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 39 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 57.74                         | 61.2                    | 74                | -16.26         | 33.1                         | 4.88                  | 41.44                    | 120                       | 220                        | Peak    |
| 2390                                                | 44.73                         | 48.19                   | 54                | -9.27          | 33.1                         | 4.88                  | 41.44                    | 120                       | 220                        | Average |
| 2480                                                | 106.22                        | 109.44                  |                   |                | 33.26                        | 4.98                  | 41.46                    | 120                       | 220                        | Peak    |
| 2480                                                | 100.29                        | 103.51                  |                   |                | 33.26                        | 4.98                  | 41.46                    | 120                       | 220                        | Average |
| 2483.5                                              | 60.96                         | 64.17                   | 74                | -13.04         | 33.27                        | 4.98                  | 41.46                    | 120                       | 220                        | Peak    |
| 2483.5                                              | 45.69                         | 48.9                    | 54                | -8.31          | 33.27                        | 4.98                  | 41.46                    | 120                       | 220                        | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 56.97                         | 61.32                   | 74                | -17.03         | 32.21                        | 4.88                  | 41.44                    | 100                       | 0                          | Peak    |
| 2390                                                | 43.81                         | 48.16                   | 54                | -10.19         | 32.21                        | 4.88                  | 41.44                    | 100                       | 0                          | Average |
| 2480                                                | 109.79                        | 113.82                  |                   |                | 32.45                        | 4.98                  | 41.46                    | 100                       | 0                          | Peak    |
| 2480                                                | 101.37                        | 105.4                   |                   |                | 32.45                        | 4.98                  | 41.46                    | 100                       | 0                          | Average |
| 2483.5                                              | 63.59                         | 67.61                   | 74                | -10.41         | 32.46                        | 4.98                  | 41.46                    | 100                       | 0                          | Peak    |
| 2483.5                                              | 46.07                         | 50.09                   | 54                | -7.93          | 32.46                        | 4.98                  | 41.46                    | 100                       | 0                          | Average |

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF190813W001

# BT\_LE CODED S8

|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 0 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 59.12                         | 62.58                   | 74                | -14.88         | 33.1                         | 4.88                  | 41.44                    | 145                       | 75                         | Peak    |
| 2390                                                | 44.63                         | 48.09                   | 54                | -9.37          | 33.1                         | 4.88                  | 41.44                    | 145                       | 75                         | Average |
| 2402                                                | 107.33                        | 110.76                  |                   |                | 33.12                        | 4.89                  | 41.44                    | 145                       | 75                         | Peak    |
| 2402                                                | 98.77                         | 102.2                   |                   |                | 33.12                        | 4.89                  | 41.44                    | 145                       | 75                         | Average |
| 2483.5                                              | 57.9                          | 61.11                   | 74                | -16.1          | 33.27                        | 4.98                  | 41.46                    | 145                       | 75                         | Peak    |
| 2483.5                                              | 45.04                         | 48.25                   | 54                | -8.96          | 33.27                        | 4.98                  | 41.46                    | 145                       | 75                         | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 56.71                         | 61.06                   | 74                | -17.29         | 32.21                        | 4.88                  | 41.44                    | 100                       | 100                        | Peak    |
| 2390                                                | 44.04                         | 48.39                   | 54                | -9.96          | 32.21                        | 4.88                  | 41.44                    | 100                       | 100                        | Average |
| 2402                                                | 109.25                        | 113.55                  |                   |                | 32.25                        | 4.89                  | 41.44                    | 100                       | 100                        | Peak    |
| 2402                                                | 98.4                          | 102.7                   |                   |                | 32.25                        | 4.89                  | 41.44                    | 100                       | 100                        | Average |
| 2483.5                                              | 56.46                         | 60.48                   | 74                | -17.54         | 32.46                        | 4.98                  | 41.46                    | 100                       | 100                        | Peak    |
| 2483.5                                              | 44.13                         | 48.15                   | 74                | -29.87         | 32.46                        | 4.98                  | 41.46                    | 100                       | 100                        | Peak    |

## REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF190813W001

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 19 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 57.3                          | 60.76                   | 74                | -16.7          | 33.1                         | 4.88                  | 41.44                    | 162                       | 70                         | Peak    |
| 2390                                                | 44.38                         | 47.84                   | 54                | -9.62          | 33.1                         | 4.88                  | 41.44                    | 162                       | 70                         | Average |
| 2440                                                | 103.25                        | 106.57                  |                   |                | 33.19                        | 4.94                  | 41.45                    | 162                       | 70                         | Peak    |
| 2440                                                | 95.52                         | 98.84                   |                   |                | 33.19                        | 4.94                  | 41.45                    | 162                       | 70                         | Average |
| 2483.5                                              | 57.47                         | 60.68                   | 74                | -16.53         | 33.27                        | 4.98                  | 41.46                    | 162                       | 70                         | Peak    |
| 2483.5                                              | 44.76                         | 47.97                   | 54                | -9.24          | 33.27                        | 4.98                  | 41.46                    | 162                       | 70                         | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 58.13                         | 62.48                   | 74                | -15.87         | 32.21                        | 4.88                  | 41.44                    | 150                       | 100                        | Peak    |
| 2390                                                | 44.23                         | 48.58                   | 54                | -9.77          | 32.21                        | 4.88                  | 41.44                    | 150                       | 100                        | Average |
| 2440                                                | 108.98                        | 113.15                  |                   |                | 32.34                        | 4.94                  | 41.45                    | 150                       | 100                        | Peak    |
| 2440                                                | 98.43                         | 102.6                   |                   |                | 32.34                        | 4.94                  | 41.45                    | 150                       | 100                        | Average |
| 2483.5                                              | 56.86                         | 60.88                   | 74                | -17.14         | 32.46                        | 4.98                  | 41.46                    | 150                       | 100                        | Peak    |
| 2483.5                                              | 43.92                         | 47.94                   | 54                | -10.08         | 32.46                        | 4.98                  | 41.46                    | 150                       | 100                        | Average |

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU  
VERITAS**

**Test Report No.: RF190813W001**

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 39 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 58.61                         | 62.07                   | 74                | -15.39         | 33.1                         | 4.88                  | 41.44                    | 160                       | 220                        | Peak    |
| 2390                                                | 44.77                         | 48.23                   | 54                | -9.23          | 33.1                         | 4.88                  | 41.44                    | 160                       | 220                        | Average |
| 2480                                                | 106.01                        | 109.23                  |                   |                | 33.26                        | 4.98                  | 41.46                    | 160                       | 220                        | Peak    |
| 2480                                                | 96.59                         | 99.81                   |                   |                | 33.26                        | 4.98                  | 41.46                    | 160                       | 220                        | Average |
| 2483.5                                              | 63.1                          | 66.31                   | 74                | -10.9          | 33.27                        | 4.98                  | 41.46                    | 160                       | 220                        | Peak    |
| 2483.5                                              | 45.61                         | 48.82                   | 54                | -8.39          | 33.27                        | 4.98                  | 41.46                    | 160                       | 220                        | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 57.84                         | 62.19                   | 74                | -16.16         | 32.21                        | 4.88                  | 41.44                    | 100                       | 360                        | Peak    |
| 2390                                                | 43.65                         | 48                      | 54                | -10.35         | 32.21                        | 4.88                  | 41.44                    | 100                       | 360                        | Average |
| 2480                                                | 109.6                         | 113.63                  |                   |                | 32.45                        | 4.98                  | 41.46                    | 100                       | 360                        | Peak    |
| 2480                                                | 98.27                         | 102.3                   |                   |                | 32.45                        | 4.98                  | 41.46                    | 100                       | 360                        | Average |
| 2483.5                                              | 63.32                         | 67.34                   | 74                | -10.68         | 32.46                        | 4.98                  | 41.46                    | 100                       | 360                        | Peak    |
| 2483.5                                              | 45.35                         | 49.37                   | 54                | -8.65          | 32.46                        | 4.98                  | 41.46                    | 100                       | 360                        | Average |

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF190813W001

# BT\_LE (1M)

|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 0 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 67.98                         | 71.44                   | 74                | -6.02          | 33.1                         | 4.88                  | 41.44                    | 160                       | 71                         | Peak    |
| 2390                                                | 43.95                         | 47.41                   | 54                | -10.05         | 33.1                         | 4.88                  | 41.44                    | 160                       | 71                         | Average |
| 2402                                                | 104.97                        | 108.4                   |                   |                | 33.12                        | 4.89                  | 41.44                    | 160                       | 71                         | Peak    |
| 2402                                                | 98.27                         | 101.7                   |                   |                | 33.12                        | 4.89                  | 41.44                    | 160                       | 71                         | Average |
| 2483.5                                              | 57.72                         | 60.93                   | 74                | -16.28         | 33.27                        | 4.98                  | 41.46                    | 160                       | 71                         | Peak    |
| 2483.5                                              | 44.23                         | 47.44                   | 54                | -9.77          | 33.27                        | 4.98                  | 41.46                    | 160                       | 71                         | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 59.12                         | 63.47                   | 74                | -14.88         | 32.21                        | 4.88                  | 41.44                    | 100                       | 126                        | Peak    |
| 2390                                                | 43.75                         | 48.1                    | 54                | -10.25         | 32.21                        | 4.88                  | 41.44                    | 100                       | 126                        | Average |
| 2402                                                | 109.39                        | 113.69                  |                   |                | 32.25                        | 4.89                  | 41.44                    | 100                       | 126                        | Peak    |
| 2402                                                | 99.4                          | 103.7                   |                   |                | 32.25                        | 4.89                  | 41.44                    | 100                       | 126                        | Average |
| 2483.5                                              | 56.41                         | 60.43                   | 74                | -17.59         | 32.46                        | 4.98                  | 41.46                    | 100                       | 126                        | Peak    |
| 2483.5                                              | 43.84                         | 47.86                   | 54                | -10.16         | 32.46                        | 4.98                  | 41.46                    | 100                       | 126                        | Average |

## REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF190813W001

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 19 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 59.88                         | 63.34                   | 74                | -14.12         | 33.1                         | 4.88                  | 41.44                    | 106                       | 46                         | Peak    |
| 2390                                                | 44.96                         | 48.42                   | 54                | -9.04          | 33.1                         | 4.88                  | 41.44                    | 106                       | 46                         | Average |
| 2440                                                | 107.67                        | 110.99                  |                   |                | 33.19                        | 4.94                  | 41.45                    | 106                       | 46                         | Peak    |
| 2440                                                | 100.48                        | 103.8                   |                   |                | 33.19                        | 4.94                  | 41.45                    | 106                       | 46                         | Average |
| 2483.5                                              | 58.04                         | 61.25                   | 74                | -15.96         | 33.27                        | 4.98                  | 41.46                    | 106                       | 46                         | Peak    |
| 2483.5                                              | 44.9                          | 48.11                   | 54                | -9.1           | 33.27                        | 4.98                  | 41.46                    | 106                       | 46                         | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 56.63                         | 60.98                   | 74                | -17.37         | 32.21                        | 4.88                  | 41.44                    | 100                       | 120                        | Peak    |
| 2390                                                | 43.09                         | 47.44                   | 54                | -10.91         | 32.21                        | 4.88                  | 41.44                    | 100                       | 120                        | Average |
| 2440                                                | 109.52                        | 113.69                  |                   |                | 32.34                        | 4.94                  | 41.45                    | 100                       | 120                        | Peak    |
| 2440                                                | 99.13                         | 103.3                   |                   |                | 32.34                        | 4.94                  | 41.45                    | 100                       | 120                        | Average |
| 2483.5                                              | 56.43                         | 60.45                   | 74                | -17.57         | 32.46                        | 4.98                  | 41.46                    | 100                       | 120                        | Peak    |
| 2483.5                                              | 43.62                         | 47.64                   | 54                | -10.38         | 32.46                        | 4.98                  | 41.46                    | 100                       | 120                        | Average |

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU  
VERITAS**

**Test Report No.: RF190813W001**

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 39 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 56.8                          | 60.26                   | 74                | -17.2          | 33.1                         | 4.88                  | 41.44                    | 158                       | 45                         | Peak    |
| 2390                                                | 44.09                         | 47.55                   | 54                | -9.91          | 33.1                         | 4.88                  | 41.44                    | 158                       | 45                         | Average |
| 2480                                                | 104.91                        | 108.13                  |                   |                | 33.26                        | 4.98                  | 41.46                    | 158                       | 45                         | Peak    |
| 2480                                                | 97.19                         | 100.41                  |                   |                | 33.26                        | 4.98                  | 41.46                    | 158                       | 45                         | Average |
| 2483.5                                              | 61.02                         | 64.23                   | 74                | -12.98         | 33.27                        | 4.98                  | 41.46                    | 158                       | 45                         | Peak    |
| 2483.5                                              | 44.91                         | 48.12                   | 54                | -9.09          | 33.27                        | 4.98                  | 41.46                    | 158                       | 45                         | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 56.95                         | 61.3                    | 74                | -17.05         | 32.21                        | 4.88                  | 41.44                    | 150                       | 110                        | Peak    |
| 2390                                                | 43.87                         | 48.22                   | 54                | -10.13         | 32.21                        | 4.88                  | 41.44                    | 150                       | 110                        | Average |
| 2480                                                | 112.14                        | 116.17                  |                   |                | 32.45                        | 4.98                  | 41.46                    | 150                       | 110                        | Peak    |
| 2480                                                | 98.57                         | 102.6                   |                   |                | 32.45                        | 4.98                  | 41.46                    | 150                       | 110                        | Average |
| 2483.5                                              | 67.1                          | 71.12                   | 74                | -6.9           | 32.46                        | 4.98                  | 41.46                    | 150                       | 110                        | Peak    |
| 2483.5                                              | 48.68                         | 52.7                    | 54                | -5.32          | 32.46                        | 4.98                  | 41.46                    | 150                       | 110                        | Average |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2462MHz: Fundamental frequency.



**BUREAU VERITAS** Test Report No.: RF190813W001

BT\_LE (2M)

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| CHANNEL         | TX Channel 0 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                        |                 |                    |                     |                      |         |
|-----------------------------------------------------|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390                                                | 57.44                   | 60.9              | 74             | -16.56      | 33.1                   | 4.88            | 41.44              | 121                 | 70                   | Peak    |
| 2390                                                | 44.78                   | 48.24             | 54             | -9.22       | 33.1                   | 4.88            | 41.44              | 121                 | 70                   | Average |
| 2402                                                | 107.64                  | 111.07            |                |             | 33.12                  | 4.89            | 41.44              | 121                 | 70                   | Peak    |
| 2402                                                | 89.82                   | 93.25             |                |             | 33.12                  | 4.89            | 41.44              | 121                 | 70                   | Average |
| 2483.5                                              | 59.3                    | 62.51             | 74             | -14.7       | 33.27                  | 4.98            | 41.46              | 121                 | 70                   | Peak    |
| 2483.5                                              | 45.19                   | 48.4              | 54             | -8.81       | 33.27                  | 4.98            | 41.46              | 121                 | 70                   | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                         |                   |                |             |                        |                 |                    |                     |                      |         |
| FREQ. (MHz)                                         | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390                                                | 57.01                   | 61.36             | 74             | -16.99      | 32.21                  | 4.88            | 41.44              | 100                 | 120                  | Peak    |
| 2390                                                | 44.17                   | 48.52             | 54             | -9.83       | 32.21                  | 4.88            | 41.44              | 100                 | 120                  | Average |
| 2402                                                | 109.28                  | 113.58            |                |             | 32.25                  | 4.89            | 41.44              | 100                 | 120                  | Peak    |
| 2402                                                | 90.1                    | 94.4              |                |             | 32.25                  | 4.89            | 41.44              | 100                 | 120                  | Average |
| 2483.5                                              | 57.47                   | 61.49             | 74             | -16.53      | 32.46                  | 4.98            | 41.46              | 100                 | 120                  | Peak    |
| 2483.5                                              | 44.56                   | 48.58             | 54             | -9.44       | 32.46                  | 4.98            | 41.46              | 100                 | 120                  | Average |

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2422MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF190813W001

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 19 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 59.27                         | 62.73                   | 74                | -14.73         | 33.1                         | 4.88                  | 41.44                    | 140                       | 70                         | Peak    |
| 2390                                                | 45                            | 48.46                   | 54                | -9             | 33.1                         | 4.88                  | 41.44                    | 140                       | 70                         | Average |
| 2440                                                | 108.29                        | 111.61                  |                   |                | 33.19                        | 4.94                  | 41.45                    | 140                       | 70                         | Peak    |
| 2440                                                | 91.46                         | 94.78                   |                   |                | 33.19                        | 4.94                  | 41.45                    | 140                       | 70                         | Average |
| 2483.5                                              | 57.74                         | 60.95                   | 74                | -16.26         | 33.27                        | 4.98                  | 41.46                    | 140                       | 70                         | Peak    |
| 2483.5                                              | 45.02                         | 48.23                   | 74                | -28.98         | 33.27                        | 4.98                  | 41.46                    | 140                       | 70                         | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 57.38                         | 61.73                   | 74                | -16.62         | 32.21                        | 4.88                  | 41.44                    | 100                       | 112                        | Peak    |
| 2390                                                | 44.32                         | 48.67                   | 54                | -9.68          | 32.21                        | 4.88                  | 41.44                    | 100                       | 112                        | Average |
| 2440                                                | 111.68                        | 115.85                  |                   |                | 32.34                        | 4.94                  | 41.45                    | 100                       | 112                        | Peak    |
| 2440                                                | 89.58                         | 93.75                   |                   |                | 32.34                        | 4.94                  | 41.45                    | 100                       | 112                        | Average |
| 2483.5                                              | 57.62                         | 61.64                   | 74                | -16.38         | 32.46                        | 4.98                  | 41.46                    | 100                       | 112                        | Peak    |
| 2483.5                                              | 44.42                         | 48.44                   | 54                | -9.58          | 32.46                        | 4.98                  | 41.46                    | 100                       | 112                        | Average |

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: RF190813W001

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 39 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 57.22                         | 60.68                   | 74                | -16.78         | 33.1                         | 4.88                  | 41.44                    | 100                       | 45                         | Peak    |
| 2390                                                | 44.68                         | 48.14                   | 54                | -9.32          | 33.1                         | 4.88                  | 41.44                    | 100                       | 45                         | Average |
| 2480                                                | 105.25                        | 108.47                  |                   |                | 33.26                        | 4.98                  | 41.46                    | 100                       | 45                         | Peak    |
| 2480                                                | 87.96                         | 91.18                   |                   |                | 33.26                        | 4.98                  | 41.46                    | 100                       | 45                         | Average |
| 2483.5                                              | 62.39                         | 65.6                    | 74                | -11.61         | 33.27                        | 4.98                  | 41.46                    | 100                       | 45                         | Peak    |
| 2483.5                                              | 46.04                         | 49.25                   | 54                | -7.96          | 33.27                        | 4.98                  | 41.46                    | 100                       | 45                         | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 59.59                         | 63.94                   | 74                | -14.41         | 32.21                        | 4.88                  | 41.44                    | 130                       | 110                        | Peak    |
| 2390                                                | 43.86                         | 48.21                   | 54                | -10.14         | 32.21                        | 4.88                  | 41.44                    | 130                       | 110                        | Average |
| 2480                                                | 111.57                        | 115.6                   |                   |                | 32.45                        | 4.98                  | 41.46                    | 130                       | 110                        | Peak    |
| 2480                                                | 90.3                          | 94.33                   |                   |                | 32.45                        | 4.98                  | 41.46                    | 130                       | 110                        | Average |
| 2483.5                                              | 67.53                         | 71.55                   | 74                | -6.47          | 32.46                        | 4.98                  | 41.46                    | 130                       | 110                        | Peak    |
| 2483.5                                              | 49.44                         | 53.46                   | 54                | -4.56          | 32.46                        | 4.98                  | 41.46                    | 130                       | 110                        | Average |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2452MHz: Fundamental frequency.



### 3.2 6 dB BANDWIDTH MEASUREMENT

#### 3.2.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 3.2.2 TEST INSTRUMENTS

| Equipment           | Manufacturer | Model No.  | Serial No. | Last Cal.  | Next Cal.  |
|---------------------|--------------|------------|------------|------------|------------|
| Power Meter         | ANRITSU      | ML2495A    | 1506002    | Feb. 26,19 | Feb. 25,20 |
| EXA Signal Analyzer | KEYSIGHT     | N9010A-526 | MY54510322 | Feb. 26,19 | Feb. 25,20 |
| EXA Signal Analyzer | KEYSIGHT     | N9010A-544 | MY54510355 | Feb. 26,19 | Feb. 25,20 |
| Power Sensor        | ANRITSU      | MA2411B    | 1339352    | Feb. 26,19 | Feb. 25,20 |

**NOTE:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

#### 3.2.3 TEST PROCEDURE


1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 3.2.4 DEVIATION FROM TEST STANDARD

No deviation.



### 3.2.5 TEST SETUP



### 3.2.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




BUREAU  
VERITAS

Test Report No.: RF190813W001

### 3.2.7 TEST RESULTS

#### BT\_LE CODED S2

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | 6dB<br>BANDWIDTH<br>(MHz) | MINIMUM LIMIT<br>(MHz) | PASS / FAIL |
|---------|-------------------------------|---------------------------|------------------------|-------------|
| 0       | 2402                          | 0.64                      | 0.5                    | PASS        |
| 19      | 2440                          | 0.65                      | 0.5                    | PASS        |
| 39      | 2480                          | 0.65                      | 0.5                    | PASS        |






BUREAU  
VERITAS

Test Report No.: RF190813W001

#### BT\_LE CODED S8

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | 6dB<br>BANDWIDTH<br>(MHz) | MINIMUM LIMIT<br>(MHz) | PASS / FAIL |
|---------|-------------------------------|---------------------------|------------------------|-------------|
| 0       | 2402                          | 0.62                      | 0.5                    | PASS        |
| 19      | 2440                          | 0.62                      | 0.5                    | PASS        |
| 39      | 2480                          | 0.62                      | 0.5                    | PASS        |






BUREAU  
VERITAS

Test Report No.: RF190813W001

#### BT\_LE (1M)

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | 6dB<br>BANDWIDTH<br>(MHz) | MINIMUM LIMIT<br>(MHz) | PASS / FAIL |
|---------|-------------------------------|---------------------------|------------------------|-------------|
| 0       | 2402                          | 0.69                      | 0.5                    | PASS        |
| 19      | 2440                          | 0.70                      | 0.5                    | PASS        |
| 39      | 2480                          | 0.71                      | 0.5                    | PASS        |






BUREAU  
VERITAS

Test Report No.: RF190813W001

BT\_LE (2M)

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | 6dB<br>BANDWIDTH<br>(MHz) | MINIMUM LIMIT<br>(MHz) | PASS / FAIL |
|---------|-------------------------------|---------------------------|------------------------|-------------|
| 0       | 2402                          | 0.79                      | 0.5                    | PASS        |
| 19      | 2440                          | 0.79                      | 0.5                    | PASS        |
| 39      | 2480                          | 0.79                      | 0.5                    | PASS        |






### 3.3 CONDUCTED OUTPUT POWER

#### 3.3.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

#### 3.3.2 TEST SETUP



#### 3.3.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

#### 3.3.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

#### 3.3.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 3.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

**3.3.7 TEST RESULTS****3.3.7.1 MAXIMUM PEAK OUTPUT POWER****BT\_LE CODED S2**

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | PEAK<br>POWER<br>(dBm) | PEAK<br>POWER<br>(mW) | PEAK<br>POWER LIMIT(W) | PASS/FAIL |
|---------|-------------------------------|------------------------|-----------------------|------------------------|-----------|
| 0       | 2402                          | 8.05                   | 6.383                 | 1                      | PASS      |
| 19      | 2440                          | 8.12                   | 6.486                 | 1                      | PASS      |
| 39      | 2480                          | 8.16                   | <b>6.546</b>          | 1                      | PASS      |

**BT\_LE CODED S8**

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | PEAK<br>POWER<br>(dBm) | PEAK<br>POWER<br>(mW) | PEAK<br>POWER LIMIT(W) | PASS/FAIL |
|---------|-------------------------------|------------------------|-----------------------|------------------------|-----------|
| 0       | 2402                          | 8.04                   | 6.368                 | 1                      | PASS      |
| 19      | 2440                          | 8.12                   | 6.486                 | 1                      | PASS      |
| 39      | 2480                          | 8.16                   | 6.546                 | 1                      | PASS      |

**BT\_LE (1M)**

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | PEAK<br>POWER<br>(dBm) | PEAK<br>POWER<br>(mW) | PEAK<br>POWER LIMIT(W) | PASS/FAIL |
|---------|-------------------------------|------------------------|-----------------------|------------------------|-----------|
| 0       | 2402                          | 7.73                   | 5.929                 | 1                      | PASS      |
| 19      | 2440                          | 7.89                   | 6.152                 | 1                      | PASS      |
| 39      | 2480                          | 8.11                   | 6.471                 | 1                      | PASS      |

**BT\_LE (2M)**

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | PEAK<br>POWER<br>(dBm) | PEAK<br>POWER<br>(mW) | PEAK<br>POWER LIMIT(W) | PASS/FAIL |
|---------|-------------------------------|------------------------|-----------------------|------------------------|-----------|
| 0       | 2402                          | 7.81                   | 6.039                 | 1                      | PASS      |
| 19      | 2440                          | 7.98                   | 6.281                 | 1                      | PASS      |
| 39      | 2480                          | 8.15                   | 6.531                 | 1                      | PASS      |




### 3.4 POWER SPECTRAL DENSITY MEASUREMENT

#### 3.4.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

#### 3.4.2 TEST SETUP



#### 3.4.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

#### 3.4.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 3 kHz, VBW  $\geq 3 \times$  RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

#### 3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 3.4.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




BUREAU  
VERITAS

Test Report No.: RF190813W001

### 3.4.7 TEST RESULTS

#### BT\_LE CODED S2

| Channel | FREQ.<br>(MHz) | PSD<br>(dBm/3kHz) | Limit<br>(dBm/3kHz) | PASS<br>/FAIL |
|---------|----------------|-------------------|---------------------|---------------|
| 0       | 2402           | 2.29              | 8                   | PASS          |
| 19      | 2440           | 2.39              | 8                   | PASS          |
| 39      | 2480           | 2.61              | 8                   | PASS          |






BUREAU  
VERITAS

Test Report No.: RF190813W001

#### BT\_LE CODED S8

| Channel | FREQ.<br>(MHz) | PSD<br>(dBm/3kHz) | Limit<br>(dBm/3kHz) | PASS<br>/FAIL |
|---------|----------------|-------------------|---------------------|---------------|
| 0       | 2402           | 2.15              | 8                   | PASS          |
| 19      | 2440           | 2.28              | 8                   | PASS          |
| 39      | 2480           | 2.47              | 8                   | PASS          |






BUREAU  
VERITAS

Test Report No.: RF190813W001

### BT\_LE (1M)

| Channel | FREQ.<br>(MHz) | PSD<br>(dBm/3kHz) | Limit<br>(dBm/3kHz) | PASS<br>/FAIL |
|---------|----------------|-------------------|---------------------|---------------|
| 0       | 2402           | -6.55             | 8                   | PASS          |
| 19      | 2440           | -6.47             | 8                   | PASS          |
| 39      | 2480           | -6.34             | 8                   | PASS          |






BUREAU  
VERITAS

Test Report No.: RF190813W001

### BT\_LE (2M)

| Channel | FREQ.<br>(MHz) | PSD<br>(dBm/3kHz) | Limit<br>(dBm/3kHz) | PASS<br>/FAIL |
|---------|----------------|-------------------|---------------------|---------------|
| 0       | 2402           | -7.42             | 8                   | PASS          |
| 19      | 2440           | -7.27             | 8                   | PASS          |
| 39      | 2480           | -7.10             | 8                   | PASS          |






### 3.5 OUT OF BAND EMISSION MEASUREMENT

#### 3.5.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

#### 3.5.2 TEST SETUP



#### 3.5.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

#### 3.5.4 TEST PROCEDURE

##### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



## MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

### 3.5.5 DEVIATION FROM TEST STANDARD

No deviation.

### 3.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

### 3.5.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.





BUREAU  
VERITAS



Test Report No.: RF190813W001

## BT\_LE CODED S2



### CH 0



### CH 19



### CH 39







BUREAU  
VERITAS

Test Report No.: RF190813W001

### CH 0 Band Edge



### CH 39 Band Edge






BUREAU  
VERITAS


Test Report No.: RF190813W001

## BT\_LE CODED S8


### CH 0



### CH 19



### CH 39







BUREAU  
VERITAS

Test Report No.: RF190813W001

### CH 0 Band Edge



### CH 39 Band Edge






BUREAU  
VERITAS


Test Report No.: RF190813W001

## BT\_LE LE (1M)


### CH 0



### CH 19



### CH 39







BUREAU  
VERITAS

Test Report No.: RF190813W001

### CH 0 Band Edge



### CH 39 Band Edge







**BUREAU VERITAS** Test Report No.: RF190813W001

**BT\_LE (2M)**


### CH 0



### CH 19




### CH 39





BUREAU  
VERITAS

Test Report No.: RF190813W001





Test Report No.: RF190813W001

## 4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF190813W001

## 5 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---