FCC RF Test Report

APPLICANT	:	Fibocom Wireless Inc.
EQUIPMENT	:	5G Module
BRAND NAME	:	Fibocom
MODEL NAME	:	FG190W-NA, FG190-NA
FCC ID	:	ZMOFG190WNA
STANDARD	:	47 CFR Part 27
CLASSIFICATION	:	PCS Licensed Transmitter (PCB)
TEST DATE(S)	:	Aug. 14, 2024 ~ Aug. 21, 2024

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED
Cert #5145.01

Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 5
1.5 Modification of EUT 6
1.6 Maximum Conducted Power and Emission Designator 6
1.7 Testing Site 6
1.8 Test Software 7
1.9 Applied Standards 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**
2.1 Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Support Unit used in test configuration and system 9
2.4 Measurement Results Explanation Example 9
2.5 Frequency List of Low/Middle/High Channels 10
3 CONDUCTED TEST ITEMS **11**
3.1 Measuring Instruments 11
3.2 Test Setup 11
3.3 Test Result of Conducted Test 11
3.4 Conducted Output Power Measurement 12
3.5 Peak-to-Average Ratio 13
3.6 EIRP 14
3.7 Occupied Bandwidth 15
3.8 Conducted Band Edge Measurement 16
3.9 Conducted Spurious Emission Measurement 17
3.10 Frequency Stability Measurement 18
4 RADIATED TEST ITEMS **19**
4.1 Measuring Instruments 19
4.2 Test Setup 19
4.3 Test Result of Radiated Test 20
4.4 Radiated Spurious Emission Measurement 21
5 LIST OF MEASURING EQUIPMENT **22**
6 MEASUREMENT UNCERTAINTY **23**
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG472418F	Rev. 01	Initial issue of report	Sep. 04, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	—	Report Only	-
3.5	-	Peak-to-Average Ratio	—	Report Only	
3.6	§27.50 (a)(3)	EIRP	EIRP < 250mW/5MHz	PASS	-
3.7	§2.1049	Occupied Bandwidth	—	Report Only	-
3.8	§2.1051 §27.53 (a)(4)	Conducted Band Edge Measurement	Refer standard	PASS	-
3.9	§2.1051 §27.53 (a)(4)	Conducted Spurious Emission	< $70+10\log_{10}$(P[Watts])	PASS	-
3.10	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within the band	PASS	-
4.4	§2.1053 §27.53 (a)(4)	Radiated Spurious Emission	< $70+10\log_{10}$(P[Watts])	PASS	Under limit 14.29 dB at 9222.00 MHz

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Fibocom Wireless Inc.
1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen, China

1.2 Manufacturer

Fibocom Wireless Inc.
1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	5G Module
Brand Name	Fibocom
Model Name	FG190W-NA, FG190-NA
FCC ID	ZMOFG190WNA
IMEI Code	Conducted: 864410070003781 Radiation: 864410070004029
HW Version	V1.3
SW Version	99101.1000.00.01.06.23
EUT Stage	Production Unit

Remark: There are two types of EUT: Sample1(FG190W-NA) and Sample2(FG190-NA) . The difference between them is that Sample1 with RF interface while Sample2 without, all the others are the same. According to the difference, we only evaluated sample 1 to perform full test.

1.4 Product Specification of Equipment Under Test

Product Feature	
Tx Frequency	LTE Band 30 : 2305 MHz ~ 2315 MHz
Rx Frequency	LTE Band 30 : 2350 MHz ~ 2360 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	<Ant 1> : LTE Band 30 : 22.16 dBm
Antenna Gain	<Ant 1> : LTE Band 30 : 0.22 dBi
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Conducted Power and Emission Designator

LTE Band 30		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum Conducted power (W)	Emission Designator (99%OBW)	Maximum Conducted power (W)	Emission Designator (99%OBW)
5	2307.5 ~ 2312.5	0.1618	4M48G7D	0.1374	4M50W7D
10	2310.0	0.1644	9M01G7D	0.1365	9M09W7D

1.7 Testing Site

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	TH01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH03-SZ	CN1256	421272

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH03-SZ	AUDIX	E3	6.2009-8-24

1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 27(D)
- ANSI C63.26-2015
- FCC KDB 971168 Power Meas License Digital Systems D01 v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01
-

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission. (X Plane)

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16 QAM	64 QAM	256 QAM	1	Half	Full	L	M	H
Max. Output Power	30	-	-	V		-	-	V	V	V	V	V			V	V	V
		-	-		V	-	-	V	V	V	V	V	V	V		V	
Peak-to-Average Ratio	30	-	-		V	-	-	V	V	V				V		V	
E.I.R.P	30	-	-	V		-	-	V	V			V			V	V	V
		-	-		V	-	-	V	V	V	V	V	V	V		V	
26dB and 99% Bandwidth	30	-	-	V	V	-	-	V	V					V		V	
Conducted Band Edge	30	-	-	V	V	-	-	V	V	V		V		V	V		V
Conducted Spurious Emission	30	-	-	V		-	-	V				V			V	V	V
		-	-		V	-	-	V				V				V	
Frequency Stability	30	-	-		V	-	-	V						V		V	
Radiated Spurious Emission	30	-	-		V	-	-	V				V				V	
Note	1. The mark “v “ means that this configuration is chosen for testing 2. The mark “-“ means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.																

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Adapter	N/A	N/A	N/A	N/A	N/A
4.	Test Jig	N/A	N/A	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 5.0 + 10 = 15.0 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 30 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
10	Channel	-	27710	-
	Frequency	-	2310	-
5	Channel	27685	27710	27735
	Frequency	2307.5	2310	2312.5

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied / 26dB Bandwidth ,Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power Measurement

3.4.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 EIRP

3.6.1 Description of EIRP

For mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth. Power averaging shall not include intervals in which the transmitter is off.

3.6.2 Test Procedures

1. According to KDB 412172 D01 Power Approach,
2. EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

   P_T = transmitter output power in dBm

   G_T = gain of the transmitting antenna in dBi

   L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.7 Occupied Bandwidth

3.7.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.8 Conducted Band Edge Measurement

3.8.1 Description of Conducted Band Edge Measurement

27.53 (a)(4)

For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands:

(i) By a factor of not less than: 43 + 10 log (P) dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than 55 + 10 log (P) dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than 67 + 10 log (P) dB on all frequencies between 2328 and 2337 MHz;

(ii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2296 and 2300 MHz, 61 + 10 log (P) dB on all frequencies between 2292 and 2296 MHz, 67 + 10 log (P) dB on all frequencies between 2288 and 2292 MHz, and 70 + 10 log (P) dB below 2288 MHz;

(iii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2360 and 2365 MHz, and not less than 70 + 10 log (P) dB above 2365 MHz.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW >= 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

3.9 Conducted Spurious Emission Measurement

3.9.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 70 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 9 kHz up to a frequency including its 10th harmonic.

3.9.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from 70 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [70 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [70 + 10log(P)] (dB)
    = -40dBm

3.10 Frequency Stability Measurement

3.10.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.10.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.10.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 70 + 10 log (P) dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
   EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
   ERP (dBm) = EIRP - 2.15
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
    The limit line is derived from 70 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [70 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [70 + 10log(P)] (dB)
    = -40dBm.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 09, 2024	Aug. 19, 2024~ Aug. 21, 2024	Apr. 08, 2025	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V，3A	Oct. 16, 2023	Aug. 19, 2024~ Aug. 21, 2024	Oct. 15, 2024	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GHz	Dec. 25, 2023	Aug. 19, 2024~ Aug. 21, 2024	Dec. 24, 2024	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 03, 2024	Aug. 19, 2024~ Aug. 21, 2024	Jul. 02, 2025	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 09, 2024	Aug. 14, 2024	Apr. 08, 2025	Radiation (03CH03-SZ)
EXA Spectrum Anaiyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 09, 2024	Aug. 14, 2024	Apr. 08, 2025	Radiation (03CH03-SZ
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 29, 2023	Aug. 14, 2024	Dec. 28, 2024	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz-2GHz	Aug. 20, 2023	Aug. 14, 2024	Aug. 19, 2025	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Apr. 09, 2024	Aug. 14, 2024	Apr. 08, 2025	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 09, 2024	Aug. 14, 2024	Apr. 08, 2025	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHz	Oct. 18, 2023	Aug. 14, 2024	Oct. 17, 2024	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 03, 2024	Aug. 14, 2024	Jul.02, 2025	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Dec. 27, 2023	Aug. 14, 2024	Dec. 26, 2024	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010002729	N/A	Oct. 18, 2023	Aug. 14, 2024	Oct. 17, 2024	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Aug. 14, 2024	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Aug. 14, 2024	NCR	Radiation (03CH03-SZ)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Peak to Average Ratio	±1.34 dB
Frequency Stability	±1.3 Hz

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.00 dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.60 dB

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.80 dB

---------- THE END ----------

Appendix A. Test Results of Conducted Test

Test Engineer :	Fly	Temperature :	24~26℃
		Relative Humidity :	50~53%

Conducted Output Power(Average power) and EIRP

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel					27710				
Frequency (MHz)					2310			M	
10	QPSK	1	0		22.16			0.1730	
10	QPSK	1	25		22.14			0.1722	
10	QPSK	1	49		22.02			0.1675	
10	QPSK	25	0		21.13			0.1365	
10	QPSK	25	12		21.21			0.1390	
10	QPSK	25	25		21.11			0.1358	
10	QPSK	50	0		21.16			0.1374	
10	16QAM	1	0		21.35			0.1435	
10	64QAM	1	0		20.36			0.1143	
10	256QAM	1	0		17.00			0.0527	
Channel				27685	27710	27735	EIRP(W)		
Frequency (MHz)				2307.5	2310	2312.5	L	M	H
5	QPSK	1	0	22.09	22.09	22.05	0.1702	0.1702	0.1687
5	16QAM	1	0	21.38	21.30	21.30	0.1445	0.1419	0.1419

Peak-to-Average Ratio

Mode	LTE Band 30 / 10MHz			
Mod.	QPSK	16QAM	64QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Result
Middle CH	3.77	4.99	5.71	PASS

LTE Band 30 / 10MHz / QPSK	LTE Band 30 / 10MHz / 16QAM
Middle Channel / Full RB	Middle Channel / Full RB
	
LTE Band 30 / 10MHz / 64QAM	
Middle Channel / Full RB	
	NA

26dB Bandwidth

Mode	LTE Band 30 : 26dB BW(MHz)			
BW	5MHz		10MHz	
Mod.	QPSK	16QAM	QPSK	16QAM
Middle CH	5.17	5.11	9.75	9.85

LTE Band 30

Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Occupied Bandwidth

Mode	LTE Band 30 : 99%OBW(MHz)			
BW	5MHz		10MHz	
Mod.	QPSK	16QAM	QPSK	16QAM
Middle CH	4.48	4.50	9.01	9.09

LTE Band 30

Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Conducted Band Edge

LTE Band 30 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Highest Band Edge / 1 RB



Lowest Band Edge / 1 RB / Power Integrated



Highest Band Edge / 1 RB / Power Integrated



LTE Band 30 / 5MHz / QPSK

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29596 GHz	-47.61 dBm	-16.61 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29997 GHz	-31.58 dBm	-6.58 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30399 GHz	-21.29 dBm	-8.29 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30499 GHz*	9.53 dBm*	22.53 dB*
2.305 GHz	2.310 GHz	100.000 kHz	2.30839 GHz	7.27 dBm	-22.73 dB
2.310 GHz	2.311 GHz	1.000 MHz	2.31003 GHz*	9.82 dBm*	22.82 dB*
2.311 GHz	2.320 GHz	1.000 MHz	2.31107 GHz	-21.03 dBm	-8.03 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32134 GHz	-47.05 dBm	-22.05 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32451 GHz	-50.01 dBm	-19.01 dB

Date: 20.AUG.2024 08:55:09

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29556 GHz	-50.01 dBm	-19.01 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29919 GHz	-47.26 dBm	-22.26 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30893 GHz	-21.91 dBm	-8.91 dB
2.309 GHz	2.310 GHz	1.000 MHz	2.31000 GHz*	9.88 dBm*	22.88 dB*
2.310 GHz	2.315 GHz	100.000 kHz	2.31366 GHz	7.20 dBm	-22.80 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31501 GHz*	10.12 dBm*	23.12 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31601 GHz	-21.27 dBm	-8.27 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32003 GHz	-30.66 dBm	-5.66 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32406 GHz	-46.68 dBm	-15.68 dB

Date: 20.AUG.2024 08:58:56

Lowest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 08:56:49

Highest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 09:00:11

Lowest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 08:57:21

Highest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 09:00:46

LTE Band 30 / 5MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29543 GHz	-52.71 dBm	-21.71 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29940 GHz	-38.79 dBm	-13.79 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30384 GHz	-31.22 dBm	-18.22 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30495 GHz*	23.32 dBm*	36.32 dB*
2.305 GHz	2.310 GHz	100.000 kHz	2.30533 GHz	20.47 dBm	-9.53 dB
2.310 GHz	2.311 GHz	1.000 MHz	2.31006 GHz	-38.13 dBm	-25.13 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31145 GHz	-44.50 dBm	-31.50 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32226 GHz	-53.08 dBm	-28.08 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32639 GHz	-53.58 dBm	-22.58 dB

Date: 19.AUG.2024 23:24:51

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29476 GHz	-53.14 dBm	-22.14 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29968 GHz	-53.28 dBm	-28.28 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30864 GHz	-38.06 dBm	-25.06 dB
2.309 GHz	2.310 GHz	1.000 MHz	2.30931 GHz	-37.35 dBm	-24.35 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31468 GHz	19.30 dBm	-10.70 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31503 GHz*	22.24 dBm*	35.24 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31602 GHz	-33.71 dBm	-20.71 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32019 GHz	-42.39 dBm	-17.39 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32422 GHz	-52.87 dBm	-21.87 dB

Date: 19.AUG.2024 23:33:51

Lowest Band Edge / 1 RB / Power Integrated



Date: 19.AUG.2024 23:59:31

Highest Band Edge / 1 RB / Power Integrated



Date: 20.AUG.2024 00:10:36

LTE Band 30 / 5MHz / 16QAM

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29573 GHz	-45.40 dBm	-14.40 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29999 GHz	-29.30 dBm	-4.30 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30398 GHz	-18.18 dBm	-5.18 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30499 GHz*	8.70 dBm*	21.70 dB*
2.305 GHz	2.310 GHz	100.000 kHz	2.30825 GHz	6.33 dBm	-23.67 dB
2.310 GHz	2.311 GHz	1.000 MHz	2.31001 GHz*	9.40 dBm*	22.40 dB*
2.311 GHz	2.320 GHz	1.000 MHz	2.31101 GHz	-17.66 dBm	-4.66 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32007 GHz	-45.74 dBm	-20.74 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32407 GHz	-51.00 dBm	-20.00 dB

Date: 19.AUG.2024 23:27:33

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29598 GHz	-50.81 dBm	-19.81 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29973 GHz	-46.70 dBm	-21.70 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30898 GHz	-17.93 dBm	-4.93 dB
2.309 GHz	2.310 GHz	1.000 MHz	2.30998 GHz*	9.22 dBm*	22.22 dB*
2.310 GHz	2.315 GHz	100.000 kHz	2.31049 GHz	6.05 dBm	-23.95 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31501 GHz*	8.92 dBm*	21.92 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31604 GHz	-18.13 dBm	-5.13 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32006 GHz	-30.13 dBm	-5.13 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32406 GHz	-46.30 dBm	-15.30 dB

Date: 19.AUG.2024 23:36:34

Lowest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 00:02:16

Highest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 00:13:39

Lowest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 00:08:28

Highest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 00:13:55

LTE Band 30 / 5MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29496 GHz	-52.54 dBm	-21.54 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29915 GHz	-36.90 dBm	-11.90 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30397 GHz	-33.92 dBm	-20.92 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30494 GHz*	22.41 dBm*	35.41 dB*
2.305 GHz	2.310 GHz	100.000 kHz	2.30535 GHz	19.72 dBm	-10.28 dB
2.310 GHz	2.311 GHz	1.000 MHz	2.31007 GHz	-37.05 dBm	-24.05 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31128 GHz	-49.94 dBm	-36.94 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32018 GHz	-53.21 dBm	-28.21 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32440 GHz	-53.21 dBm	-22.21 dB

Date: 19.AUG.2024 23:25:45

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29505 GHz	-53.25 dBm	-22.25 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29843 GHz	-53.32 dBm	-28.32 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30813 GHz	-50.33 dBm	-37.33 dB
2.309 GHz	2.310 GHz	1.000 MHz	2.30949 GHz	-42.26 dBm	-29.26 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31468 GHz	18.63 dBm	-11.37 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31506 GHz*	21.28 dBm*	34.28 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31600 GHz	-34.97 dBm	-21.97 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32031 GHz	-50.60 dBm	-25.60 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32409 GHz	-53.11 dBm	-22.11 dB

Date: 19.AUG.2024 23:34:45

Lowest Band Edge / 1 RB / Power Integrated



Date: 20.AUG.2024 00:00:01

Highest Band Edge / 1 RB / Power Integrated



Date: 20.AUG.2024 00:10:46

LTE Band 30 / 5MHz / 64QAM

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29599 GHz	-46.58 dBm	-15.58 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29994 GHz	-31.47 dBm	-6.47 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30389 GHz	-22.04 dBm	-9.04 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	7.64 dBm*	20.64 dB*
2.305 GHz	2.310 GHz	100.000 kHz	2.30828 GHz	5.56 dBm	-24.44 dB
2.310 GHz	2.311 GHz	1.000 MHz	2.31002 GHz*	8.43 dBm*	21.43 dB*
2.311 GHz	2.320 GHz	1.000 MHz	2.31120 GHz	-21.47 dBm	-8.47 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32006 GHz	-47.08 dBm	-22.08 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32400 GHz	-51.20 dBm	-20.20 dB

Date: 19.AUG.2024 23:28:27

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29573 GHz	-51.27 dBm	-20.27 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29997 GHz	-47.51 dBm	-22.51 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30877 GHz	-21.81 dBm	-8.81 dB
2.309 GHz	2.310 GHz	1.000 MHz	2.30998 GHz*	7.82 dBm*	20.82 dB*
2.310 GHz	2.315 GHz	100.000 kHz	2.31040 GHz	5.11 dBm	-24.89 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31502 GHz*	8.17 dBm*	21.17 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31625 GHz	-21.83 dBm	-8.83 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32007 GHz	-30.99 dBm	-5.99 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32407 GHz	-47.22 dBm	-16.22 dB

Date: 19.AUG.2024 23:37:28

Lowest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 00:01:42

Highest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 00:13:15

Lowest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 00:08:16

Highest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 00:14:06

LTE Band 30 / 10MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29593 GHz	-52.53 dBm	-21.53 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29996 GHz	-48.28 dBm	-23.28 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30399 GHz	-34.88 dBm	-21.88 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	11.28 dBm*	24.28 dB*
2.305 GHz	2.315 GHz	100.000 kHz	2.30561 GHz	20.77 dBm	-9.23 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31507 GHz	-51.76 dBm	-38.76 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31619 GHz	-52.17 dBm	-39.17 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32055 GHz	-52.88 dBm	-27.88 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32432 GHz	-53.40 dBm	-22.40 dB

Date: 20.AUG.2024 00:25:13

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29310 GHz	-53.35 dBm	-22.35 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29949 GHz	-52.88 dBm	-27.88 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30182 GHz	-52.59 dBm	-39.59 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30496 GHz	-51.96 dBm	-38.96 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31443 GHz	20.30 dBm	-9.70 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31500 GHz*	11.38 dBm*	24.38 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31605 GHz	-33.93 dBm	-20.93 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32011 GHz	-48.18 dBm	-23.18 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32438 GHz	-52.41 dBm	-21.41 dB

Date: 20.AUG.2024 00:19:51

Lowest Band Edge / 1 RB / Power Integrated



Date: 20.AUG.2024 00:31:54

Highest Band Edge / 1 RB / Power Integrated



Date: 20.AUG.2024 00:34:27

LTE Band 30 / 10MHz / QPSK

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29590 GHz	-36.98 dBm	-5.98 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29890 GHz	-31.59 dBm	-6.59 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30397 GHz	-25.90 dBm	-12.90 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	-7.92 dBm*	5.08 dB*
2.305 GHz	2.315 GHz	100.000 kHz	2.31170 GHz	3.01 dBm	-26.99 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31500 GHz*	-7.07 dBm*	5.93 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31614 GHz	-25.66 dBm	-12.66 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32290 GHz	-30.76 dBm	-5.76 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32405 GHz	-36.62 dBm	-5.62 dB

Date: 20.AUG.2024 09:26:36

Lowest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 09:27:48

Lowest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 09:28:03

LTE Band 30 / 10MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29565 GHz	-43.83 dBm	-12.83 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29874 GHz	-39.55 dBm	-14.55 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30358 GHz	-31.91 dBm	-18.91 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	10.99 dBm*	23.99 dB*
2.305 GHz	2.315 GHz	100.000 kHz	2.30560 GHz	20.43 dBm	-9.57 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31501 GHz	-40.27 dBm	-27.27 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31836 GHz	-40.68 dBm	-27.68 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32013 GHz	-52.83 dBm	-27.83 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32443 GHz	-53.38 dBm	-22.38 dB

Date: 20.AUG.2024 00:26:06

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29229 GHz	-53.36 dBm	-22.36 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29934 GHz	-52.47 dBm	-27.47 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30161 GHz	-41.19 dBm	-28.19 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30443 GHz	-42.06 dBm	-29.06 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31442 GHz	19.87 dBm	-10.13 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31500 GHz*	10.94 dBm*	23.94 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31729 GHz	-33.28 dBm	-20.28 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32250 GHz	-40.15 dBm	-15.15 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32434 GHz	-41.78 dBm	-10.78 dB

Date: 20.AUG.2024 00:20:45

Lowest Band Edge / 1 RB / Power Integrated



Date: 20.AUG.2024 00:32:06

Highest Band Edge / 1 RB / Power Integrated



Date: 20.AUG.2024 00:34:15

LTE Band 30 / 10MHz / 16QAM

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29599 GHz	-34.68 dBm	-3.68 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29972 GHz	-28.84 dBm	-3.84 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30395 GHz	-23.92 dBm	-10.92 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	-6.69 dBm*	6.31 dB*
2.305 GHz	2.315 GHz	100.000 kHz	2.31033 GHz	3.11 dBm	-26.89 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31500 GHz*	-5.61 dBm*	7.39 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31604 GHz	-23.74 dBm	-10.74 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32004 GHz	-28.65 dBm	-3.65 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32407 GHz	-34.22 dBm	-3.22 dB

Date: 20.AUG.2024 09:07:16

Lowest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 09:09:58

Lowest Band Edge / Full RB / Power Integrated



Date: 20.AUG.2024 09:10:27

LTE Band 30 / 10MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29553 GHz	-46.17 dBm	-15.17 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29979 GHz	-49.83 dBm	-24.83 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30394 GHz	-36.37 dBm	-23.37 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	10.36 dBm*	23.36 dB*
2.305 GHz	2.315 GHz	100.000 kHz	2.30558 GHz	19.42 dBm	-10.58 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31501 GHz	-50.00 dBm	-37.00 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31864 GHz	-52.57 dBm	-39.57 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32023 GHz	-52.95 dBm	-27.95 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32502 GHz	-53.40 dBm	-22.40 dB

Date: 20.AUG.2024 00:27:00

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29231 GHz	-53.26 dBm	-22.26 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29899 GHz	-53.17 dBm	-28.17 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30186 GHz	-46.81 dBm	-33.81 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30409 GHz	-52.15 dBm	-39.15 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31443 GHz	19.24 dBm	-10.76 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31500 GHz*	9.73 dBm*	22.73 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31603 GHz	-37.75 dBm	-24.75 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32053 GHz	-49.06 dBm	-24.06 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32540 GHz	-44.79 dBm	-13.79 dB

Date: 20.AUG.2024 00:21:38

Lowest Band Edge / 1 RB / Power Integrated



Date: 20.AUG.2024 00:32:18

Highest Band Edge / 1 RB / Power Integrated



Date: 20.AUG.2024 00:34:03

LTE Band 30 / 10MHz / 64QAM

Lowest Band Edge / Full RB



Lowest Band Edge / Full RB / Power Integrated



Lowest Band Edge / Full RB / Power Integrated



Conducted Spurious Emission

LTE Band 30 / 5MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	988.12344 MHz	-57.39 dBm	-17.39 dB
1.000 GHz	2.288 GHz	1.000 MHz	2.15602 GHz	-58.05 dBm	-18.05 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.99106 GHz	-57.12 dBm	-17.12 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.88821 GHz	-51.75 dBm	-11.75 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.36836 GHz	-59.01 dBm	-19.01 dB
10.000 GHz	14.000 GHz	1.000 MHz	12.75291 GHz	-57.99 dBm	-17.99 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.85102 GHz	-55.40 dBm	-15.40 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.52162 GHz	-53.46 dBm	-13.46 dB

Date: 19.AUG.2024 23:56:11

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	962.91604 MHz	-57.22 dBm	-17.22 dB
1.000 GHz	2.288 GHz	1.000 MHz	2.10495 GHz	-57.83 dBm	-17.83 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.97696 GHz	-57.25 dBm	-17.25 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.94461 GHz	-51.89 dBm	-11.89 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.35636 GHz	-58.86 dBm	-18.86 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.99575 GHz	-57.86 dBm	-17.86 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.84352 GHz	-55.38 dBm	-15.38 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.50262 GHz	-53.72 dBm	-13.72 dB

Date: 19.AUG.2024 23:55:00

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	890.20240 MHz	-57.34 dBm	-17.34 dB
1.000 GHz	2.288 GHz	1.000 MHz	2.15259 GHz	-57.89 dBm	-17.89 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.98502 GHz	-56.91 dBm	-16.91 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.93141 GHz	-51.66 dBm	-11.66 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.37385 GHz	-59.14 dBm	-19.14 dB
10.000 GHz	14.000 GHz	1.000 MHz	12.73141 GHz	-57.85 dBm	-17.85 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.83652 GHz	-55.47 dBm	-15.47 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.52012 GHz	-53.58 dBm	-13.58 dB

Date: 19.AUG.2024 23:53:45

LTE Band 30 / 10MHz

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	961.94653 MHz	-57.16 dBm	-17.16 dB
1.000 GHz	2.288 GHz	1.000 MHz	2.13070 GHz	-58.02 dBm	-18.02 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.98542 GHz	-57.17 dBm	-17.17 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.81142 GHz	-51.95 dBm	-11.95 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.34536 GHz	-59.16 dBm	-19.16 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.99725 GHz	-58.00 dBm	-18.00 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.85552 GHz	-55.49 dBm	-15.49 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.50662 GHz	-53.09 dBm	-13.09 dB

Date: 20.AUG.2024 00:30:59

Frequency Stability

Test Conditions		LTE Band 30 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0008	PASS
40	Normal Voltage	0.0005	
30	Normal Voltage	0.0010	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0004	
0	Normal Voltage	0.0012	
-10	Normal Voltage	0.0014	
-20	Normal Voltage	0.0003	
-30	Normal Voltage	0.0005	
20	Maximum Voltage	0.0003	
20	Normal Voltage	0.0000	
20	Minimum Voltage	0.0005	

Note:

1. Normal Voltage = 3.8 V. ; Minimum Voltage = 3.3 V. ; Maximum Voltage = 4.4 V.
2. The frequency fundamental emissions stay within the authorized frequency block.

Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

Test Engineer :	Shunping You	Temperature :	22~25℃
		Relative Humidity :	48~52%

LTE Band 30 / 10MHz / QPSK/ Ant.1									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	4611.50	-63.00	-40	-23.00	-47.98	-69.25	6.45	12.70	H
	6916.50	-61.72	-40	-21.72	-50.96	-65.12	8.40	11.80	H
	9222.00	-54.29	-40	-14.29	-50.59	-56.64	9.65	12.00	H
	4611.50	-61.22	-40	-21.22	-46.05	-67.47	6.45	12.70	V
	6916.50	-61.67	-40	-21.67	-50.87	-65.07	8.40	11.80	V
	9222.00	-53.37	-40	-13.37	-49.25	-55.72	9.65	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.