

#01_FR1 n48_40M_BPSK_1_53_Bottom of Laptop_0mm_Ch645332

Communication System: 5G NR; Frequency: 3679.98 MHz; Duty Cycle: 1:1
Medium: HSL_3700_231204 Medium parameters used: $f = 3679.98$ MHz; $\sigma = 3.14$ S/m; $\epsilon_r = 38.2$
Ambient Temperature: 23.4°C; Liquid Temperature: 22.4°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7793; ConvF(6.15, 5.95, 6.26); Calibrated: 2023-03-08
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn376; Calibrated: 2023-09-14
- Phantom: ELI V8.0-I; Serial: 2196-0mm; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: 5G NR FR1 TDD, 10903-AAD

Area Scan (60.0 mm x 120.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.871 W/kg; SAR (10g) = 0.381 W/kg;

Zoom Scan (28.0 mm x 28.0 mm x 28.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.4 mm
Power Drift = -0.01 dB
SAR (1g) = 0.941 W/kg; SAR (8g) = 0.427 W/kg; SAR (10g) = 0.384 W/kg

