



FCC RF Test Report

APPLICANT : FIBOCOM WIRELESS INC.
EQUIPMENT : LTE Module
BRAND NAME : Fibocom
MODEL NAME : L830-EA
FCC ID : ZMOL830
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Aug. 25, 2015 and testing was completed on Oct. 12, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Prepared by: Andy Yeh / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

**1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	7
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.7 Testing Location	8
1.8 Applicable Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	10
2.3 Support Unit used in test configuration	10
2.4 Measurement Results Explanation Example	11
3 CONDUCTED TEST RESULT	12
3.1 Measuring Instruments.....	12
3.2 Test Setup	12
3.3 Test Result of Conducted Test.....	12
3.4 Conducted Output Power and ERP/EIRP	13
3.5 Peak-to-Average Ratio	14
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	15
3.7 Conducted Band Edge	16
3.8 Conducted Spurious Emission	17
3.9 Frequency Stability	18
4 RADIATED TEST ITEMS	19
4.1 Measuring Instruments.....	19
4.2 Test Setup	19
4.3 Test Result of Radiated Test.....	19
4.4 Field Strength of Spurious Radiation Measurement	20
5 LIST OF MEASURING EQUIPMENT	21
6 UNCERTAINTY OF EVALUATION	22
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG582503A	Rev. 01	Initial issue of report	Jan. 27, 2016

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.4	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b) §27.53(g)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 34.09 dB at 7520.000 MHz



1 General Description

1.1 Applicant

FIBOCOM WIRELESS INC.

5/F, Tower A, Technology Building II, 1057# Nanhai Blvd, Shenzhen, P.R.China

1.2 Manufacturer

FIBOCOM WIRELESS INC.

5/F, Tower A, Technology Building II, 1057# Nanhai Blvd, Shenzhen, P.R.China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	LTE Module
Brand Name	Fibocom
Model Name	L830-EA
FCC ID	ZMOL830
EUT supports Radios application	GPRS/EGPRS/WCDMA/HSPA/ HSPA+(16QAM uplink is not supported)/DC-HSDPA/LTE
IMEI Code	Conducted: 867603020008770 Radiation: 867603020009190
HW Version	V1.0.2
SW Version	L830_V3E.1C.01.00
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM/GPRS/EDGE: 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz WCDMA: Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz Band IV: 1712.4 MHz ~ 1752.6 MHz
Rx Frequency	GSM/GPRS/EDGE: 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz WCDMA: Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz Band IV: 2112.4 MHz ~ 2152.6 MHz
Maximum Output Power to Antenna	GSM/GPRS/EDGE: 850: 32.54 dBm 1900: 29.76 dBm WCDMA: Band V: 22.98 dBm Band II: 22.95 dBm Band IV: 23.01 dBm
Antenna Type	Fixed External Antenna
Type of Modulation	GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : QPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM (16QAM uplink is not supported) DC-HSDPA : 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Conducted Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum Conducted Power (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GPRS class 10	GMSK	1.7947	0.0203 ppm	248KGXW
Part 22	GSM850 EDGE class 10	8PSK	0.5117	0.0108 ppm	256KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.1986	0.0478 ppm	4M08F9W
Part 24	GSM1900 GPRS class 8	GMSK	0.9462	0.0115 ppm	246KGXW
Part 24	GSM1900 EDGE class 10	8PSK	0.4305	0.0125 ppm	254KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.1972	0.0186 ppm	4M09F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK	0.2000	0.0242 ppm	4M08F9W

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.
Test Site Location	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595
Test Site No.	Sporton Site No. TH01-SZ

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398
Test Site No.	Sporton Site No. 03CH01-SZ
	FCC Registration No. 831040

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI / TIA / EIA-603-D-2010
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS class 10 Link ■ EDGE class 10 Link	■ GPRS class 10 Link ■ EDGE class 10 Link
GSM 1900	■ GPRS class 8 Link ■ EDGE class 10 Link	■ GPRS class 8 Link ■ EDGE class 10 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Notebook	Lenovo	G480	N/A	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m
3.	USB Cable	N/A	N/A	N/A	Unshielded, 1.5m	N/A
4.	WWAN Antenna	N/A	N/A	N/A	N/A	N/A
5.	WWAN Diversity & GPS & Glonass Antenna	N/A	N/A	N/A	N/A	N/A



2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.5 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.5 + 10 = 14.5 \text{ (dB)}\end{aligned}$$


3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for WCDMA Band II.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for WCDMA.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
Record the maximum PAPR level associated with a probability of 0.1%.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Jan. 28, 2015	Oct. 09, 2015~ Oct. 10, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Aug. 07, 2015	Oct. 09, 2015~ Oct. 10, 2015	Aug. 06, 2016	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	May 26, 2015	Oct. 12, 2015	May 25, 2016	Radiation (03CH01-SZ)
Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz;Max 30dBm	Jun. 07, 2015	Oct. 12, 2015	Jun. 06, 2016	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz~2GHz	Nov. 07, 2014	Oct. 12, 2015	Nov. 06, 2015	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1285	1GHz~18GHz	Jan. 20, 2015	Oct. 12, 2015	Jan. 19, 2016	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Aug.19, 2015	Oct. 12, 2015	Aug. 18, 2016	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz ~3000MHz / 30 dB	Jan. 28, 2015	Oct. 12, 2015	Jan. 27, 2016	Radiation (03CH01-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 28, 2015	Oct. 12, 2015	Jan. 27, 2016	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	May 05, 2015	Oct. 12, 2015	May 04, 2016	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Oct. 12, 2015	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Oct. 12, 2015	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Oct. 12, 2015	NCR	Radiation (03CH01-SZ)



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8 dB
---	---------------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS class 8	32.52	32.53	32.51	29.63	29.76	29.67
GPRS class 10	32.51	32.54	32.46	29.65	29.75	29.66
GPRS class 11	31.72	31.75	31.70	28.84	28.92	28.85
GPRS class 12	29.70	29.71	29.69	27.71	27.77	27.65
EGPRS class 8	27.01	26.82	26.70	25.80	26.02	26.30
EGPRS class 10	27.09	26.97	26.78	25.86	26.05	26.34
EGPRS class 11	26.28	26.15	26.03	25.07	25.23	25.53
EGPRS class 12	25.15	25.01	24.83	23.86	24.06	24.31

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
RMC 12.2K	22.95	22.98	22.94	22.95	22.94	22.83	22.83	23.01	22.81
HSDPA Subtest-1	22.69	22.73	22.77	22.63	22.62	22.32	22.53	22.85	22.57
HSDPA Subtest-2	22.73	22.73	22.74	22.62	22.60	22.31	22.56	22.87	22.58
HSDPA Subtest-3	22.48	22.49	22.50	22.23	22.17	21.81	22.56	22.87	22.60
HSDPA Subtest-4	22.24	22.23	22.26	21.81	21.83	21.62	22.31	22.66	22.36
DC-HSDPA Subtest-1	20.60	20.56	20.58	20.51	20.50	20.46	20.33	20.42	20.40
DC-HSDPA Subtest-2	20.63	20.56	20.58	20.40	20.39	20.36	20.35	20.41	20.38
DC-HSDPA Subtest-3	20.65	20.61	20.57	20.37	20.37	20.35	20.33	20.41	20.38
DC-HSDPA Subtest-4	20.62	20.61	20.57	20.38	20.30	20.28	20.39	20.42	20.38
HSUPA Subtest-1	21.30	21.33	21.37	22.24	22.25	21.94	21.10	21.42	21.09
HSUPA Subtest-2	20.65	20.76	20.79	20.48	20.54	20.17	20.87	21.19	20.86
HSUPA Subtest-3	21.53	21.61	21.61	21.50	21.41	21.21	21.15	21.88	21.59
HSUPA Subtest-4	20.96	20.97	21.04	20.80	20.81	20.54	21.01	21.36	21.03
HSUPA Subtest-5	22.70	22.80	22.80	22.50	22.60	22.30	22.60	22.90	22.50



Cellular Band (GT - LC =5 dB)									
Modes	GSM850 (GPRS 10)			GSM850 (EDGE 10)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128	189	251	128	189	251	4132	4182	4233
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
(MHz)									
Conducted Power (dBm)	32.51	32.54	32.46	27.09	26.97	26.78	22.95	22.98	22.94
Conducted Power (Watts)	1.7824	1.7947	1.7620	0.5117	0.4977	0.4764	0.1972	0.1986	0.1968
ERP(dBm)	35.36	35.39	35.31	29.94	29.82	29.63	25.80	25.83	25.79
ERP(Watts)	3.4356	3.4594	3.3963	0.9863	0.9594	0.9183	0.3802	0.3828	0.3793

PCS Band (GT - LC =3dB)									
Modes	GSM1900 (GPRS 8)			GSM1900 (EDGE 10)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512	661	810	512	661	810	9262	9400	9538
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
(MHz)									
Conducted Power (dBm)	29.63	29.76	29.67	25.86	26.05	26.34	22.95	22.94	22.83
Conducted Power (Watts)	0.9183	0.9462	0.9268	0.3855	0.4027	0.4305	0.1972	0.1968	0.1919
EIRP(dBm)	32.63	32.76	32.67	28.86	29.05	29.34	25.95	25.94	25.83
EIRP(Watts)	1.8323	1.8880	1.8493	0.7691	0.8035	0.8590	0.3936	0.3926	0.3828



AWS Band (GT - LC $\approx$ 3dB)			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312 (Low)	1413 (Mid)	1513 (High)
Frequency	1712.4	1732.6	1752.6
(MHz)			
Conducted Power (dBm)	22.83	23.01	22.81
Conducted Power (Watts)	0.1919	0.2000	0.1910
EIRP(dBm)	25.83	26.01	25.81
EIRP(Watts)	0.3828	0.3990	0.3811















A1. GSM

Peak-to-Average Ratio

Mode	GSM850		Limit: 13dB
Mod.	GPRS class 10	EDGE class 10	Result
Lowest CH	0.20	2.60	PASS
Middle CH	0.24	2.76	
Highest CH	0.16	2.64	

Mode	GSM1900		Limit: 13Db
Mod.	GPRS class 8	EDGE class 10	Result
Lowest CH	0.20	2.60	PASS
Middle CH	0.20	2.48	
Highest CH	0.20	2.48	


GSM850 (GPRS class 10)	GSM850 (EDGE class 10)
Lowest Channel	Lowest Channel
 Center 824.2 MHz 2 dB Mean Pwr = 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 31.75 dBm Peak 31.93 dBm Crest 0.19 dB 10 % 0.16 dB 1 % 0.20 dB .1 % 0.20 dB .01 % 0.20 dB	 Center 824.2 MHz 2 dB Mean Pwr = 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 26.36 dBm Peak 29.04 dBm Crest 2.68 dB 10 % 2.20 dB 1 % 2.52 dB .1 % 2.60 dB .01 % 2.64 dB
Middle Channel	Middle Channel
 Center 836.4 MHz 2 dB Mean Pwr = 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 31.72 dBm Peak 31.93 dBm Crest 0.21 dB 10 % 0.16 dB 1 % 0.20 dB .1 % 0.24 dB .01 % 0.24 dB	 Center 836.4 MHz 2 dB Mean Pwr = 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 25.99 dBm Peak 28.83 dBm Crest 2.84 dB 10 % 2.24 dB 1 % 2.68 dB .1 % 2.76 dB .01 % 2.80 dB
Highest Channel	Highest Channel
 Center 848.8 MHz 2 dB Mean Pwr = 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 31.78 dBm Peak 31.93 dBm Crest 0.15 dB 10 % 0.16 dB 1 % 0.16 dB .1 % 0.16 dB .01 % 0.16 dB	 Center 848.8 MHz 2 dB Mean Pwr = 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 25.97 dBm Peak 28.69 dBm Crest 2.71 dB 10 % 2.16 dB 1 % 2.56 dB .1 % 2.64 dB .01 % 2.72 dB


GSM1900 (GPRS class 8)	GSM1900 (EDGE class 10)
Lowest Channel	Lowest Channel
 Center 1.8502 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 29.23 dBm Peak 29.47 dBm Crest 0.24 dB 10 % 0.16 dB 1 % 0.20 dB .1 % 0.20 dB .01 % 0.24 dB	 Center 1.8502 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 25.24 dBm Peak 27.92 dBm Crest 2.68 dB 10 % 2.16 dB 1 % 2.52 dB .1 % 2.60 dB .01 % 2.64 dB
Middle Channel	Middle Channel
 Center 1.88 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 29.09 dBm Peak 29.33 dBm Crest 0.24 dB 10 % 0.16 dB 1 % 0.20 dB .1 % 0.20 dB .01 % 0.24 dB	 Center 1.88 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 25.31 dBm Peak 27.85 dBm Crest 2.53 dB 10 % 2.08 dB 1 % 2.40 dB .1 % 2.48 dB .01 % 2.52 dB
Highest Channel	Highest Channel
 Center 1.9098 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 28.95 dBm Peak 29.19 dBm Crest 0.24 dB 10 % 0.16 dB 1 % 0.20 dB .1 % 0.20 dB .01 % 0.24 dB	 Center 1.9098 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 25.46 dBm Peak 27.99 dBm Crest 2.52 dB 10 % 2.08 dB 1 % 2.40 dB .1 % 2.48 dB .01 % 2.52 dB

**26dB Bandwidth**

Mode	GSM850	
Mod.	GPRS class 10	EDGE class 10
Lowest CH	0.303	0.285
Middle CH	0.317	0.314
Highest CH	0.310	0.305

Mode	GSM1900	
Mod.	GPRS class 8	EDGE class 10
Lowest CH	0.310	0.313
Middle CH	0.313	0.312
Highest CH	0.314	0.319





**Occupied Bandwidth**


Mode	GSM850	
Mod.	GPRS class 10	EDGE class 10
Lowest CH	0.248	0.244
Middle CH	0.246	0.256
Highest CH	0.241	0.244

Mode	GSM1900	
Mod.	GPRS class 8	EDGE class 10
Lowest CH	0.245	0.253
Middle CH	0.244	0.254
Highest CH	0.246	0.251




GSM850 (GPRS class 10)

Lowest Channel




GSM850 (EDGE class 10)


Lowest Channel




Middle Channel




Middle Channel




Highest Channel



Highest Channel








Conducted Band Edge




GSM850 (GPRS class 10)

Lowest Band Edge



Date: 9.OCT.2015 11:13:50


Highest Band Edge



Date: 9.OCT.2015 11:15:18


GSM850 (EDGE class 10)

Lowest Band Edge



Date: 9.OCT.2015 11:43:35

Highest Band Edge




Date: 9.OCT.2015 11:45:02




GSM1900 (GPRS class 8)

Lowest Band Edge



Date: 9.OCT.2015 17:29:41


Highest Band Edge



Date: 9.OCT.2015 17:31:07


GSM1900 (EDGE class 10)

Lowest Band Edge



Date: 9.OCT.2015 17:38:44


Highest Band Edge




Date: 9.OCT.2015 17:40:11



Conducted Spurious Emission





**Frequency Stability**

Test Conditions	Middle Channel	GSM850 (GPRS class 10)	GSM850 (EDGE class 10)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0094	0.0045	PASS
40	Normal Voltage	0.0029	0.0066	
30	Normal Voltage	0.0019	0.0085	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0117	0.0006	
0	Normal Voltage	0.0136	0.0044	
-10	Normal Voltage	0.0145	0.0067	
-20	Normal Voltage	0.0134	0.0093	
-30	Normal Voltage	0.0190	0.0062	
20	Maximum Voltage	0.0203	0.0024	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0120	0.0108	

Test Conditions	Middle Channel	GSM1900 (GPRS class 8)	GSM1900 (EDGE class 10)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0115	0.0125	PASS
40	Normal Voltage	0.0076	0.0108	
30	Normal Voltage	0.0059	0.0112	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0004	0.0002	
0	Normal Voltage	0.0002	0.0003	
-10	Normal Voltage	0.0048	0.0046	
-20	Normal Voltage	0.0037	0.0054	
-30	Normal Voltage	0.0096	0.0107	
20	Maximum Voltage	0.0028	0.0118	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0058	0.0068	

Note:

1. Normal Voltage = 3.3V ; Battery End Point (BEP) = 3.135V ; Maximum Voltage = 4.4 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.








A2. WCDMA



Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.92	2.96	3.20	PASS
Middle CH	2.88	3.24	3.04	
Highest CH	2.88	3.16	3.16	




WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	Lowest Channel
 Center 828.4 MHz Trace 1 Mean 21.87 dBm Peak 25.10 dBm Crest 3.24 dB 10 % 1.72 dB 1 % 2.52 dB .1 % 2.92 dB .01 % 3.12 dB	 Center 1.8524 GHz Trace 1 Mean 21.90 dBm Peak 25.25 dBm Crest 3.35 dB 10 % 1.72 dB 1 % 2.56 dB .1 % 2.96 dB .01 % 3.16 dB
Middle Channel	Middle Channel
 Center 836.4 MHz Trace 1 Mean 21.79 dBm Peak 24.96 dBm Crest 3.18 dB 10 % 1.72 dB 1 % 2.44 dB .1 % 2.88 dB .01 % 3.04 dB	 Center 1.85 GHz Trace 1 Mean 21.62 dBm Peak 25.18 dBm Crest 3.55 dB 10 % 1.76 dB 1 % 2.72 dB .1 % 3.24 dB .01 % 3.44 dB
Highest Channel	Highest Channel
 Center 846.6 MHz Trace 1 Mean 21.84 dBm Peak 24.96 dBm Crest 3.12 dB 10 % 1.72 dB 1 % 2.52 dB .1 % 2.88 dB .01 % 3.04 dB	 Center 1.9076 GHz Trace 1 Mean 21.37 dBm Peak 24.89 dBm Crest 3.52 dB 10 % 1.72 dB 1 % 2.64 dB .1 % 3.16 dB .01 % 3.36 dB



WCDMA Band IV (RMC 12.2Kbps)	
Lowest Channel	
 Center 1.7124 GHz 2 dB/ Mean Per + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 22.12 dBm Peak 25.67 dBm Crest 3.55 dB 10 % 1.80 dB 1 % 2.72 dB .1 % 3.20 dB .01 % 3.40 dB	
Middle Channel	
 Center 1.7326 GHz 2 dB/ Mean Per + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 22.25 dBm Peak 25.60 dBm Crest 3.35 dB 10 % 1.76 dB 1 % 2.60 dB .1 % 3.04 dB .01 % 3.24 dB	
Highest Channel	
 Center 1.7526 GHz 2 dB/ Mean Per + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 22.04 dBm Peak 25.60 dBm Crest 3.56 dB 10 % 1.80 dB 1 % 2.72 dB .1 % 3.16 dB .01 % 3.36 dB	

**26dB Bandwidth**


Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.65	4.64	4.63
Middle CH	4.62	4.64	4.64
Highest CH	4.63	4.62	4.62






WCDMA Band IV (RMC 12.2Kbps)


Lowest Channel



Middle Channel




Highest Channel



**Occupied Bandwidth**


Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.08	4.09	4.07
Middle CH	4.08	4.09	4.08
Highest CH	4.05	4.07	4.07






WCDMA Band IV (RMC 12.2Kbps)


Lowest Channel



Middle Channel



Highest Channel






Conducted Band Edge




WCDMA Band V (RMC 12.2Kbps)

Lowest Band Edge



Date: 9.OCT.2015 12:42:26

Highest Band Edge




Date: 9.OCT.2015 12:45:08




WCDMA Band II (RMC 12.2Kbps)

Lowest Band Edge



Date: 9.OCT.2015 16:29:08

Highest Band Edge




Date: 9.OCT.2015 16:31:49




WCDMA Band IV (RMC 12.2Kbps)

Lowest Band Edge



Date: 9.OCT.2015 16:54:56


Highest Band Edge



Date: 9.OCT.2015 16:57:37




Conducted Spurious Emission






WCDMA Band IV (RMC 12.2Kbps)


Lowest Channel



Middle Channel



Highest Channel



**Frequency Stability**

Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2KbpsRMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0418	PASS
40	Normal Voltage	0.0263	
30	Normal Voltage	0.0084	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0048	
0	Normal Voltage	0.0084	
-10	Normal Voltage	0.0227	
-20	Normal Voltage	0.0371	
-30	Normal Voltage	0.0478	
20	Maximum Voltage	0.0287	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0084	

Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0186	PASS
40	Normal Voltage	0.0138	
30	Normal Voltage	0.0059	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0011	
0	Normal Voltage	0.0027	
-10	Normal Voltage	0.0059	
-20	Normal Voltage	0.0112	
-30	Normal Voltage	0.0149	
20	Maximum Voltage	0.0117	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0043	

Note:

1. Normal Voltage = 3.3V ; Battery End Point (BEP) = 3.135V ; Maximum Voltage =4.4 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Test Conditions	Middle Channel	WCDMA Band IV (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0242	PASS
40	Normal Voltage	0.0167	
30	Normal Voltage	0.0087	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0012	
0	Normal Voltage	0.0017	
-10	Normal Voltage	0.0017	
-20	Normal Voltage	0.0058	
-30	Normal Voltage	0.0110	
20	Maximum Voltage	0.0087	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0035	

Note:

1. Normal Voltage = 3.3V ; Battery End Point (BEP) = 3.135V ; Maximum Voltage = 4.4 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

GSM850 (GPRS class 10)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-49.17	-13	-36.17	-52.80	-52.99	0.53	6.50	H
	2510	-52.84	-13	-39.84	-58.26	-55.71	0.68	5.70	H
	3346	-56.17	-13	-43.17	-66.19	-61.21	0.81	8.00	H
	1672	-50.37	-13	-37.37	-54.62	-54.19	0.53	6.50	V
	2510	-56.65	-13	-43.65	-60.97	-59.52	0.68	5.70	V
	3346	-56.75	-13	-43.75	-65.76	-61.79	0.81	8.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM850 (EDGE class 10)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-60.83	-13	-47.83	-63.38	-64.65	0.53	6.50	H
	2510	-57.67	-13	-44.67	-63.09	-60.54	0.68	5.70	H
	3346	-56.00	-13	-43.00	-66.02	-61.04	0.81	8.00	H
	1672	-60.33	-13	-47.33	-63.24	-64.15	0.53	6.50	V
	2510	-57.11	-13	-44.11	-61.43	-59.98	0.68	5.70	V
	3346	-57.39	-13	-44.39	-66.40	-62.43	0.81	8.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (GPRS class 8)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-50.67	-13	-37.67	-63.44	-57.86	0.81	8.00	H
	5640	-48.51	-13	-35.51	-67.26	-58.50	1.01	11.00	H
	7520	-47.38	-13	-34.38	-69.55	-59.62	1.46	13.70	H
	3760	-51.34	-13	-38.34	-64.41	-58.53	0.81	8	V
	5640	-48.72	-13	-35.72	-67.78	-58.71	1.01	11	V
	7520	-47.09	-13	-34.09	-69.58	-59.33	1.46	13.7	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (EDGE class 10)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-53.51	-13	-40.51	-66.28	-60.70	0.81	8.00	H
	5640	-49.68	-13	-36.68	-68.43	-59.67	1.01	11.00	H
	7520	-48.14	-13	-35.14	-70.31	-60.38	1.46	13.70	H
	3760	-53.46	-13	-40.46	-66.53	-60.65	0.81	8	V
	5640	-49.37	-13	-36.37	-68.43	-59.36	1.01	11	V
	7520	-47.51	-13	-34.51	-70	-59.75	1.46	13.7	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band V(RMC 12.2Kbps)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-61.15	-13	-48.15	-63.70	-64.97	0.53	6.50	H
	2510	-57.52	-13	-44.52	-62.94	-60.39	0.68	5.70	H
	3346	-56.90	-13	-43.90	-66.92	-61.94	0.81	8.00	H
	1672	-61.08	-13	-48.08	-63.99	-64.90	0.53	6.50	V
	2510	-56.60	-13	-43.60	-60.92	-59.47	0.68	5.70	V
	3346	-57.01	-13	-44.01	-66.02	-62.05	0.81	8.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band II(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-50.06	-13	-37.06	-62.83	-57.25	0.81	8.00	H
	5640	-49.44	-13	-36.44	-68.19	-59.43	1.01	11.00	H
	7520	-48.15	-13	-35.15	-70.32	-60.39	1.46	13.70	H
	3760	-51.44	-13	-38.44	-64.51	-58.63	0.81	8	V
	5640	-49.53	-13	-36.53	-68.59	-59.52	1.01	11	V
	7520	-47.38	-13	-34.38	-69.87	-59.62	1.46	13.7	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band IV(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Highest	3465	-53.03	-13	-40.03	-65.86	-60.22	0.81	8.00	H
	5197.5	-49.57	-13	-36.57	-68.10	-58.62	0.95	10.00	H
	6930	-47.76	-13	-34.76	-69.10	-60.03	1.13	13.40	H
	3465	-51.70	-13	-38.70	-65.04	-63.49	0.81	12.6	V
	5197.5	-50.01	-13	-37.01	-68.64	-61.76	0.95	12.7	V
	6930	-47.94	-13	-34.94	-68.93	-58.51	1.13	11.7	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.